



Common Data Model for in situ observations

C3S311a Lot 2: Global Land and Marine Observations Database

Issued by: NUIM / Peter Thorne

Date: 21/08/2017

Ref: C3S_D311a_Lot2.2.1.1_201708_Initial_specification_for_CDM_v1

Official reference number service contract: 2017/C3S_311a_Lot2_NUIM/SC1



This document has been produced in the context of the Copernicus Climate Change Service (C3S). The activities leading to these results have been contracted by the European Centre for Medium-Range Weather Forecasts, operator of C3S on behalf of the European Union (Delegation Agreement signed on 11/11/2014). All information in this document is provided "as is" and no guarantee or warranty is given that the information is fit for any particular purpose. The user thereof uses the information at its sole risk and liability. For the avoidance of all doubts, the European Commission and the European Centre for Medium-Range Weather Forecasts has no liability in respect of this document, which is merely representing the authors view.



Contributors

NATIONAL OCEANOGRAPHY CENTRE (NOC), NATURAL ENVIRONMENT RESEARCH COUNCIL (NERC)

1. David I. Berry (Lot 2)
2. Elizabeth C. Kent (Lot 2)

ISTITUTO DI METODOLOGIE PER L'ANALISI AMBIENTALE (IMAA), CONSIGLIO NAZIONALE DELLE RICERCHE (CNR)

1. Fabio Madonna (Lot 3)
2. Emanuele Tramutola (Lot 3)

INSTITUTO DOM LUIZ, UNIVERSIDADE DE LISBOA

1. Maria Antónia Valente (Lot 1)

UNIVERSITAT ROVIRA I VIRGILI

1. Alba Gilabert Gallart (Lot 1)
2. Manola Brunet (Lot 1)

MET OFFICE

1. Robert Dunn (Lot 2)
2. Philip Brohan (Lot 1)
3. Rob Allan (Lot 1)

NATIONAL UNIVERSITY OF IRELAND MAYNOOTH (NUIM)

1. Peter Thorne (Lots 2 and 3)
2. Simon Noone (Lot 2)

SCIENCE TECHNOLOGY FACILITIES COUNCIL (STFC)

1. Ag Stephens (Lot 2)

KONINKLIJK NEDERLANDS METEOROLOGISCH INSTITUUT (KNMI)

1. Else van den Besselaar (Lot 4)



Executive Summary

This document defines the initial version of the Common Data Model (CDM) developed within the Copernicus Climate Change Service (C3S) Access to Global Land and Marine Observations Database (C3S 311a Lot 2) service. This has been developed in consultation across the four C3S 311a (Collection and Processing of In Situ Observations) Lots and ECMWF.

Tab separated versions of the code tables defining the data model can be found at:

https://github.com/ glamod/common_data_model/tree/master/tables/

Version	Release date	Release notes
1	31/08/2017	Initial version of the common data model



Contents

1	Introduction	10
1.1	Purpose of this document	10
1.2	Scope	10
1.3	Structure of this document	11
2	Background and existing standards	11
2.1	Observational sources and requirements of the data model	11
2.2	ECMWF Observations DataBase (ODB)	12
2.3	BUFR and WIGOS Metadata Standard	13
3	Governance of the Common Data Model	14
4	Common Data Model	14
4.1	Header table	17
4.2	Observations table	19
4.3	Station configuration	22
4.4	Profile configuration	24
4.5	Source configuration	25
4.6	Sensor configuration	27
4.7	Quality control flags	28
4.8	Uncertainty budget	29
4.9	Homogenisation data	29
5	References	30
6	Appendix	31
6.1	Table definitions	31
6.1.1	Data tables	31
6.1.2	Code tables	45
6.2	Code tables	62



List of Tables

1	Simplified example of records in ODB type data model, with observations from reports 1 and 2 spanning multiple records. For simplicity, the z coordinate has been omitted but profile data would be represented with each layer / height as a separate record . .	13
2	header_table definition	17
3	observations_table definition	19
4	station_configuration definition	22
5	station_configuration_optional definition	24
6	profile_configuration definition	25
7	profile_configuration_optional definition	25
8	source_configuration definition	25
9	source_configuration_optional definition	27
10	sensor_configuration definition	27
11	sensor_configuration_optional definition	28
12	qc_table definition	28
13	uncertainty_table definition	29
14	homogenisation_table definition	29
15	adjustment definition	31
16	contact definition	31
17	header_table definition	31
18	homogenisation_table definition	34
19	observations_table definition	34
20	organisation definition	38
21	profile_configuration definition	38
22	profile_configuration_optional definition	39
23	qc_table definition	39
24	sensor_configuration definition	39
25	sensor_configuration_optional definition	40
26	source_configuration definition	40
27	source_configuration_optional definition	41
28	station_configuration definition	42
29	station_configuration_optional definition	44
30	uncertainty_table definition	44
31	application_area definition (WIGOS 2-01)	45
32	automation_status definition	45
33	calibration_status definition (WIGOS 5-08)	45
34	communication_method definition (Various sources (WMO47, WIGOS, BUFR))	45
35	conversion_flag definition	46
36	conversion_method definition	46
37	crs definition (BUFR 0 01 150)	46
38	data_policy_licence definition (WIGOS 9-02)	46
39	data_present definition	47
40	duplicate_status definition (Simplified version of duplicate status flags from IMMA (ICOADS))	47



41	events_at_station definition (WIGOS 4-04)	47
42	homogenisation_method definition	47
43	homogenisation_operator definition	47
44	id_scheme definition	48
45	instrument_exposure_quality definition (WIGOS 5-15)	48
46	kind definition	48
47	location_method definition (based on WIGOS 11-01 and BUFR 0 02 148)	48
48	location_quality definition	49
49	meaning_of_time_stamp definition (Based on simplified version of WIGOS 11-03)	49
50	method_of_estimating_uncertainty definition	49
51	observation_code_table definition	50
52	observation_value_significance definition (based on BUFR 0 08 023)	50
53	observed_variable definition	50
54	observing_frequency definition (WMO47 - 0602)	51
55	observing_method definition	51
56	observing_programme definition (WIGOS 2-02)	51
57	platform_sub_type definition (based on WMO47, ICOADS, BUFR 0 02 149)	52
58	platform_type definition (IMMA (ICOADS) and BUFR 0 03 001 (0 - 31))	52
59	processing_code definition	52
60	processing_level definition (WIGOS 7-06)	52
61	product_level definition	53
62	product_status definition	53
63	profile_configuration_codes definition	53
64	profile_configuration_fields definition	53
65	profile_type definition	54
66	qc_method definition	54
67	quality_flag definition (BUFR 0 33 020)	54
68	region definition (WIGOS 3-01)	54
69	report_processing_codes definition	55
70	report_processing_level definition	55
71	report_type definition	55
72	role definition (ISOTC211/19115 CIRoleCode)	55
73	sampling_strategy definition (WIGOS 6-03)	56
74	sea_level_datum definition (BUFR 0 01 151)	56
75	secondary_variable definition	56
76	sensor_configuration_codes definition	56
77	sensor_configuration_fields definition	57
78	source_configuration_codes definition	57
79	source_configuration_fields definition	58
80	source_format definition	58
81	spatial_representativeness definition (WIGOS 1-05)	58
82	standard_time definition	58
83	station_configuration_codes definition	59
84	station_configuration_fields definition	59



85	station_type definition (WIGOS 3-04)	59
86	sub_region definition	59
87	time_quality definition	60
88	time_reference definition (WIGOS: 7-10)	60
89	traceability definition (WIGOS 8-05)	60
90	uncertainty_method definition	60
91	units definition	61
92	update_frequency definition	61
93	z_coordinate_method definition	61
94	z_coordinate_type definition	61
95	application_area codes	62
96	automation_status codes	62
97	calibration_status codes	63
98	communication_method codes	63
99	conversion_flag codes	65
100	conversion_method codes	65
101	crs codes	65
102	data_policy_licence codes	66
103	data_present codes	67
104	duplicate_status codes	67
105	events_at_station codes	67
106	homogenisation_method codes	68
107	homogenisation_operator codes	68
108	id_scheme codes	68
109	instrument_exposure_quality codes	69
110	kind codes	69
111	location_method codes	69
112	location_quality codes	70
113	meaning_of_time_stamp codes	70
114	method_of_estimating_uncertainty codes	71
115	observation_code_table codes	72
116	observation_value_significance codes	73
117	observed_variable codes	74
118	observing_frequency codes	87
119	observing_method codes	87
120	observing_programme codes	87
121	platform_sub_type codes	91
122	platform_type codes	95
123	processing_code codes	96
124	processing_level codes	96
125	product_level codes	97
126	product_status codes	98
127	profile_configuration_codes codes	99
128	profile_configuration_fields codes	102



129	profile_type codes	103
130	qc_method codes	103
131	quality_flag codes	103
132	region codes	104
133	report_processing_codes codes	104
134	report_processing_level codes	104
135	report_type codes	104
136	role codes	105
137	sampling_strategy codes	105
138	sea_level_datum codes	105
139	secondary_variable codes	106
140	sensor_configuration_codes codes	110
141	sensor_configuration_fields codes	117
142	source_configuration_codes codes	121
143	source_configuration_fields codes	124
144	source_format codes	124
145	spatial_representativeness codes	124
146	standard_time codes	125
147	station_configuration_codes codes	126
148	station_configuration_fields codes	129
149	station_type codes	130
150	sub_region codes	130
151	time_quality codes	137
152	time_reference codes	137
153	traceability codes	137
154	uncertainty_method codes	137
155	units codes	138
156	update_frequency codes	138
157	z_coordinate_method codes	138
158	z_coordinate_type codes	138



1 Introduction

1.1 Purpose of this document

This document defines the initial version of the Common Data Model (CDM)¹ developed within the Copernicus Climate Change Service (C3S) Access to Global Land and Marine Observations Database (C3S 311a Lot 2) service. This has been developed in consultation across the four C3S 311a (Collection and Processing of In Situ Observations) Lots and with ECMWF.

1.2 Scope

The defined common data model is intended for use with in situ land and marine observations. Instantaneous (or point) observations and temporal statistics (e.g. daily and monthly min / max temperatures, accumulation of precipitation etc.) are supported through the use of a significance qualifier. Similarly, column average data are supported through the reporting of the observed variable alongside its value. Profile data is supported through reporting the z-coordinate for each observed value.

Whilst initially intended for use with observations of Essential Climate Variables (ECVs; e.g. GCOS, 2016) the data model is not restricted to the ECVs. As noted above, and following the ECMWF Observations DataBase (ODB) type data model, the observed variable is reported alongside the observed value.

Comprehensive metadata is supported through the use of configuration tables, recording information on:

- Source level metadata: e.g. original source of data, source data centre, citation information etc.
- Station level metadata: e.g. location, operating institute, parameters reported etc.
- Profile level metadata: Additional information for profile data, e.g. unwinder type, type of balloon or expendable bathythermograph (XBT) etc.
- Sensor level metadata: e.g. calibration history and status, sensor type / serial number etc.

Comprehensive quality control and uncertainty information can be recorded using linked Entity-Attribute-Value (EAV) tables.

¹As noted in the ITT: A common data model is different from a file format, which defines how information is encoded in a file. The purpose of a data model is to provide a well-defined data structure that can be used to represent data records from a variety of sources, in such a way that the information contained in those records can be unambiguously accessed using a common set of tools. Development of a common data model for observations involves specification of data attributes and their symbolic names, including, for example, identifiers for different instruments, observed parameters, geolocation and timing, etc. A governance structure is required to manage such specifications, ensure consistency with standards where they exist, and to ensure a controlled evolution of the data model.



1.3 Structure of this document

Section 2 of this document provides background information on the data model and existing relevant data models and standards. Section 3 proposes a governance mechanism for the CDM in recognition that the data model will change and evolve as the requirements of the users and the C3S Climate Data Store develop. Section 4 describes the core components and tables of the data model. The appendix includes the individual table definitions and preliminary versions of the code tables. The code tables listed are provisional and will be expanded as the service develops.

2 Background and existing standards

2.1 Observational sources and requirements of the data model

Across the C3S 311a service (Collection and Processing of In Situ Observations) access will be provided to observations from surface terrestrial and marine environments and upper air data in a common data model. The observations included range from point observations made from moving platforms to daily and monthly statistics at fixed locations. The parameters reported include, inter alia: air temperature; humidity; wind speed; pressure; cloud cover information; present weather. The statistics include, inter alia: daily min, max and mean air temperature; accumulated precipitation over 3 or 24 hours; mean wind speed over the preceding 10 minutes. The full range of parameters and statistics to be reported will evolve as the service is developed. As new parameters are recovered from newly digitised sources and the reprocessed climate archives the list of parameters will need to expand.

Both surface level (terrestrial and marine) and upper air data will be initially included in the service. The surface level data include observations made at standard and non-standard heights. The upper air data will include multiple observations, starting at the surface and at increasing heights through the atmosphere, often as a function of pressure or geopotential height. Columnar averages will be included. As a result the data model needs to include the flexibility to record the height and the units used for reporting the height of measurement with every observation. Similarly, some reporting stations, and hence observations, will move in the horizontal plane, and the horizontal coordinates need to be reported with each observation. To avoid ambiguity, the coordinate reference system (CRS) should be provided with each location reported.

The period covered by Lot 2 of the service ranges from ~1850 to present. Over this period there have been many changes to the instruments and practices used to record the various parameters. The choice of instruments and practices will influence the quality of the observations and a change in instrumentation, or location, may introduce inhomogeneities into the record. To mitigate this risk comprehensive observational metadata are required. Similarly, information on adjustments and conversions applied to the data need to be recorded. The full range of observational practices and instruments used is not currently known and developed data model will need to be extendable to accommodate new metadata as required.

The observations to be included will be sourced from a variety of existing datasets, such as the International Comprehensive Ocean and Atmosphere Data Set (ICOADS; e.g. Freeman et al., 2017), and newly



digitised sources. In defining the data model the provenance and lineage of the data sources need to be preserved. Similarly, usage rights and citation information need to be preserved and provided to users alongside the observational data. This is a common requirement across all Lots within the service.

In order to meet the above requirements a data model based on the ECMWF Observations DataBase (ODB) model has been developed, with the use of linked tables providing information on the observational and provenance metadata. The ODB type model allows for extension to new parameters through the use of a parameterized observation list (see next section). The linked tables will define a core set of parameters under 4 different categories (station, source, profile and sensor), flexibility will be provided through the specification of optional elements and associated decode tables.

2.2 ECMWF Observations DataBase (ODB)

The data model developed and used in the ECMWF Observations DataBase (ODB) software allows the representation of environmental data from many sources, including in situ observations and weather reports, satellite data and model output. As noted in Hersbach et al. (2015), in the ODB implementation a distinction is made between weather reports and observations and this same distinction is made within the CDM and this document. A weather report, such as a ship weather report or a radiosonde ascent, may contain multiple observations of one or more parameters. In the case of a ship weather report observations of the air temperature and humidity, sea level pressure, sea surface temperature, wind speed and direction are typically made and recorded in a single report. In the case of a radiosonde report observations of the temperature will be made at a range of levels from the surface to the burst point of the balloon. To enable flexibility and scalability with the ODB data model the different elements making up a weather report are split into header elements, recording information common across a weather report, and observational (or body) elements specific to a single observation.

In the original version of ODB, e.g. Saarinen (2004), these elements were split between a header table, containing the header elements, and a linked body table containing the observations or body elements. Within the body table the name of the parameter being observed, or its numerical code, is recorded in one column and the observed value within a second column. Other columns, recording information such as QC results, are permissible. This data model allows the efficient expansion of the data model to new variables, without the need to change the underlying structure, by the addition of the new variable to the enumerated list defining the reportable variables. Within the latest version of ODB (ODB-2; e.g. Hersbach et al., 2015) the header and body tables have been combined into a single flat table, with the header rows repeated, to enable efficient archival within the ECMWF MARS system. A simplified schematic of the ODB-2 structure is shown in Table 1.

Within the CDM defined in this document we have opted for the original ODB type data model, with the reports split into header and observational records stored within separate tables. These are described fully within Section 3 of this document. When these tables are stored in a relational database, or similar structure, performing a join on the tables should result in ODB-2 compatible records.



Table 1: Simplified example of records in ODB type data model, with observations from reports 1 and 2 spanning multiple records. For simplicity, the z coordinate has been omitted but profile data would be represented with each layer / height as a separate record

header information					observation information		
record id	re-port id	obs id	date	location	parameter	value	units
1	1	1	2012-01-01 12:00+0.0	POINT(-40 40)	air temperature	300.0	K
2	1	2	2012-01-01 12:00+0.0	POINT(-40 40)	sea level pressure	1013.0	hPa
3	2	3	2012-01-01 18:00+0.0	POINT(-40.1 40.2)	air temperature	300.3	K
4	2	4	2012-01-01 18:00+0.0	POINT(-40.1 40.2)	sea level pressure	1013.2	hPa
End of table							

2.3 BUFR and WIGOS Metadata Standard

There has been a large body of work and significant effort invested in defining data models and parameterising the data and metadata for encoding the data into those data models. Within the scope of the CDM and the C3S 311a service, the WMO Binary Universal Form for the Representation of meteorological data (BUFR) (WMO, 2015a) and the WMO Integrated Observing System Metadata Standard (WMDS) (WMO, 2015b) are key background material.

The BUFR format (WMO 2015a) is a flexible and efficient table driven format for reporting weather observations on the WMO Global Telecommunications System (GTS) in binary. The tables defined as part of the BUFR format include many of the parameters that will be included in the CDM. For example, Common code table C6 (WMO 2015a) includes all the measurement units reportable in BUFR (and other WMO codes). Similarly, code tables are defined for reporting instrument types and methods, station types etc. Where possible, these code tables have been referenced and used in preference to defining new code tables. BUFR tables from Version 27 of Master Table 0 have been used in this version of this document.

In recognition of the increasing importance of observational metadata the WMDS is currently under development and phased implementation (WMO, 2015b). The WMDS extends the ISO19115 metadata standard, with additional mandatory elements describing both the station level and discovery metadata as well as specific information on the instrumentation used and processing steps. As part of the process simplified versions of BUFR and other tables have been included in the standard. As with BUFR these tables have been referenced, where appropriate, in preference to defining new code tables.



3 Governance of the Common Data Model

A working group will be set up to manage the governance of the common data model. This group will operate remotely via email and regular teleconferences. Proposals to add new entries to the code tables or make changes to the structure of the common data model shall be made via email to email address:

`c3s_311a_CDM_governance@surfacetemperatures.org`.

Emails to this address will be distributed to all members of the working group.

During the initial development stage of the service proposals sent to the above email address will be assessed monthly, with discussion via email and teleconference as required. Accepted changes will be implemented at the beginning of the following month or with at least 2 weeks notice. These changes will be published both via the service website and via a subscription email list:

`c3s_311a_CDM_notifications@surfacetemperatures.org`.

The working group will be self nominating and initially contain at least one member from each Lot to act as a primary point of contact for that Lot and to represent their requirements on the working group. The working group will also contain a representative from ECMWF, or a nominated representative from another organisation, to represent the needs of the wider C3S community. Additional members from the different Lots will be welcomed. In the case of disagreement over proposed changes each Lot will have one vote irrespective of the number of members in the working group. In the case of a hung vote ECMWF, or their representative, will have the deciding vote.

4 Common Data Model

As noted above, the CDM is based on the original ODB data model, with meteorological reports split into header and observational records stored in separate tables, `header_table` and `observations_table` respectively. In support of these two primary tables, four auxiliary tables have been defined to enable the comprehensive reporting of metadata at different levels:

- Source level metadata (*source_configuration* table). This level contains detailed information on the source dataset, including: information on the product; whether any processing has been applied; the original data centre the data were sourced from; citation information; the data licence for the product; how to cite the data source etc.
- Station level metadata (*station_configuration* table). This level contains detailed information on the station reporting the data including: station operator; the type of station; station / AWS model type; location; operating territory; reporting frequency etc.



- Profile level metadata (*profile_configuration* table). This level contains detailed metadata for atmospheric and oceanic profiles, including: profile type; type of launcher; direction of profile; balloon / XBT type etc.
- Instrument (or sensor) level metadata (*sensor_configuration* table). This level contains detailed information on the sensor used to make a particular observation, including: calibration status; sampling strategy; observing method; sensor housing and ventilation; instrument model and serial number etc.

These tables are defined in the following section and contain elements that are mandatory across all report types. Additional optional elements are provided through Entity-Attribute-Value based tables linked to the configuration tables. Two additional tables have been defined to include the reporting of comprehensive uncertainty estimates and quality control flags. A simplified schematic of the 12 tables forming the core of the CDM is shown in Figure 1 - a more complete schematic can be found at https://github.com/glamod/common_data_model/blob/master/cdm_full.pdf.

Within the tables in the following sections the following syntax has been used:

- numeric Any numeric value (integer or floating point).
- int An integer value.
- varchar A variable length character string.
- timestamp A timestamp with time zone, e.g. "2017-07-01 00:00:0.0+00".
- [] An array of the indicated type.
- * An optional element.
- (pk) The indicated elements marked as (pk) within a table form the unique ID for the record.

Unless indicated otherwise all elements listed are mandatory but may be encoded as missing (e.g NA, NULL or format specific equivalent) if not available. Optional elements are indicated by *. Whilst arrays have been indicated for the elements containing multiple values this does not preclude other implementations. Within the table definitions references to external tables are indicated in the *external_table* column. These references are composed of two parts separated by a colon (:). The first part indicates the table, the second the element within the table. For example, *station_configuration:primary_id* indicates a reference to the *primary_id* element in the *station_configuration* table.




Figure 1: Simplified schematic showing overview of common data model



4.1 Header table

Table 2: header_table definition

element_name	kind	external_table	description
report_id	varchar (pk)		Unique ID for report (unique ID given by combination of report_id and observation_id)
region	int	region:region	Region (WMO region / Ocean basin)
sub_region	int	sub_region:sub_region	Country / regional sea
application_area	int[]	application_area:application_area	WMO application area(s)
observing_programme	int[]	observing_programme:observing_programme	Observing programme, e.g. VOS
report_type	int	report_type:type	e.g. SYNOP, TEMP, CLIMAT, etc
station_name	varchar		e.g. GRUAN station name, ship name, site name etc
station_type	int	station_type:type	Type of station, e.g. land station, sea station etc
platform_type	int	platform_type:type	Structure upon which sensor is mounted, e.g. ship, drifting buoy, tower etc
platform_sub_type	int	platform_sub_type:sub_type	Sub-type for platform, e.g. 3m discuss buoy
primary_station_id	varchar	station_configuration:primary_id	Primary station identifier, e.g. WIGOS ID
station_record_number	int	station_configuration:record_number	Together with primary_station_id this forms a link to the station configuration table.
primary_station_id_scheme	int	id_scheme:scheme	Scheme used for station ID
longitude	numeric		Longitude of station, -180.0 to 180.0 (or other as defined by station_crs)
latitude	numeric		Latitude of station, -90 to 90 (or other as defined by station_crs)
location_accuracy	numeric		Accuracy to which station location recorded (radius in km)
location_method	int	location_method:method	Method by which location determined

Continued on next page



Table 2 header_table (cont.)

element_name	kind	external_table	description
location_quality	int	location_quality:quality	Quality flag for station location
crs	int	crs:crs	Coordinate reference scheme for station location
station_speed	numeric		Station speed over ground if mobile (m/s)
station_course	numeric		Station course over ground if mobile (degree true)
station_heading	numeric		Station heading if mobile
height_of_station_above_local_ground	numeric		Height of station above local ground (m)
height_of_station_above_sea_level	numeric		Height of station above mean sea level (m), negative values for below sea level.
height_of_station_above_sea_level_accuracy	numeric		Accuracy to which height of station known (m)
sea_level_datum	int	sea_level_datum:datum	Datum used for sea level
report_meaning_of_time_stamp	int	meaning_of_time_stamp:meaning	Report time - beginning, middle or end of reporting period
report_timestamp	timestamp with time-zone		e.g. 1991-01-01 12:00:0.0+0
report_duration	int		Report duration (s), e.g. 86400 = daily obs, 3600 hourly etc
report_time_accuracy	numeric		Precision to which time was recorded (s)
report_time_quality	int	time_quality:quality	Quality flag for report_timestamp
report_time_reference	int	time_reference:reference	Reference Time (e.g. referenced to time server, atomic clock, radio clock etc)
profile_id	varchar	profile_configuration:profile_id	Information on profile (atmospheric / oceanographic) configuration. Set to Record ID for profile data or missing (NULL) otherwise.
events_at_station	int[]*	events_at_station:event	e.g. ship hove to, crop burning etc.
report_quality	int	quality_flag:flag	Overall quality of report

Continued on next page



Table 2 header_table (cont.)

element_name	kind	external_table	description
duplicate_status	int	duplicate_status:status	E.g. no duplicates, best duplicate, duplicate, not checked.
duplicates	varchar[]*	header_table:report_id	Array of report_id's for duplicates
record_timestamp	timestamp with time-zone		Timestamp of revision for this record
history	varchar		Sequence of processing steps. Free text with timestamp 1 : history 1; timestamp 2 : history 2 etc.
processing_level	int	report_processing_level:level	Level of processing applied to this report
processing_codes	int[]*	report_processing_codes:code	Processing applied to this report
source_id	varchar	source_configuration:source_id	Original source of data, link to external table
source_record_id	varchar		Record ID in source data, e.g. ID of event from GRUAN meta database

End of table

4.2 Observations table

Table 3: observations_table definition

element_name	kind	external_table	description
observation_id	varchar (pk)		unique ID for observation
report_id	varchar	header_table:report_id	Link to header information
data_policy_licence	int	data_policy_licence:policy	WMOessential, WMOadditional, WMOother
date_time	timestamp with time-zone		timestamp for observation
date_time_meaning	int	meaning_of_timestamp:meaning	beginning, middle, end
observation_duration	int		Duration/period over which observation was made (s)

Continued on next page



Table 3 observations_table (cont.)

element_name	kind	external_table	description
longitude	numeric		Longitude of the observed value, -180 to 180 (or other as defined by CRS). This may or may not be the same as the report location.
latitude	numeric		Latitude of the observed value, -90 to 90 (or other as defined by CRS)
crs	int	crs:crs	Coordinate reference scheme use to encode location
z_coordinate	numeric		z coordinate of observation
z_coordinate_type	int	z_coordinate_type:type	Type of z coordinate
observation_height_above_station_surface	numeric		Height of sensor above local ground or sea surface. Positive values for above surface (e.g. sondes), negative for below (e.g. xbt). For visual observations, height of the visual observing platform.
observed_variable	int	observed_variable:variable	The variable being observed / measured
secondary_variable	int	secondary_variable:variable	Secondary variable required to understand observation, e.g. chemical constituent. Set to NA / missing if not applicable.
observation_value	numeric		The observed value
value_significance	int	observation_value_significance:significance	e.g. min, max, mean, sum
secondary_value	int	secondary_variable:value	value for the secondary variable. Set to NA or missing if not applicable.
units	int	units:units	Units for the observed variable
code_table	int	observation_code_table:code_table	Encode / decode table for variable (if encoded)
conversion_flag	int	conversion_flag:flag	Flag indicating whether original, converted or both values are available.

Continued on next page



Table 3 observations_table (cont.)

element_name	kind	external_table	description
location_method	int	location_method:method	Method of determining location,
location_precision	numeric		Precision to which location is reported (radius km)
z_coordinate_method	int	z_coordinate_method:method	Method of determining z coordinate
bbox_min_longitude	numeric		Bounding box for observation, valid range given by CRS
bbox_max_longitude	numeric		Bounding box for observation, valid range given by CRS
bbox_min_latitude	numeric		Bounding box for observation, valid range given by CRS
bbox_max_latitude	numeric		Bounding box for observation, valid range given by CRS
spatial_representativeness	int	spatial_representativeness:representativeness	Spatial representativeness of observation
quality_flag	int	quality_flag:flag	Quality flag for observation
qc_passed	int		Number of quality control checks passed (see qc_table for more information)
qc_failed	int		Number of quality control checks failed (see qc_table for more information)
numerical_precision	int		Reporting precision of observation in units given by 'units' variable. Equivalent to BUFR scale factor
standard_uncertainty	numeric		Standard uncertainty in reported value
method_of_estimating_standard_uncertainty	int	method_of_estimating_standard_uncertainty:method	Method of estimating the standard uncertainty
sensor_id	varchar	sensor_configuration:sensor_id	Link to sensor_configuration table.
sensor_automation_status	int	automation_status:automation	Automated, manual, mixed or visual observation
exposure_of_sensor	int	instrument_exposure_quality:exposure	Whether the exposure of the instrument will impact on the quality of the measurement
original_precision	int		Original reporting precision in units given by 'original_units'

Continued on next page



Table 3 observations_table (cont.)

element_name	kind	external_table	description
original_units	int	units:units	Original units
original_value	numeric		Original value as reported or recorded in log book.
conversion_method	int	conversion_method:method	Link to table describing conversion process
processing_code	int[]*	processing_code:code	e.g. TRC (temperature radiation corrections) etc. Encoded in table.
processing_level	int	processing_level:level	Level of processing applied to observation.
adjustment_id	int	adjustment:adjustment_id	Total adjustment applied to observation reported in observation value (observation_value = original + adjustment)
traceability	int	traceability:traceability	Whether observation can be traced to international standards.
advanced_qc	int	data_present:flag	Flag indicating whether advanced qc data are available
advanced_uncertainty	int	data_present:flag	Flag indicating whether advanced uncertainty estimates are available
advanced_homo genisation	int	data_present:flag	Flag indicating whether advanced homogenisation information is available

End of table

4.3 Station configuration

Table 4: station_configuration definition

element_name	type	external_table	description
primary_id	varchar (pk)		Primary (e.g. WMO) ID for station
primary_id_scheme	int	id_scheme:scheme	Scheme used for primary ID
record_number	int (pk)		Record number for this station entry
secondary_id	varchar[]*		Secondary (e.g. local) ID for station

Continued on next page



Table 4 station_configuration (cont.)

element_name	type	external_table	description
secondary_id_scheme	int[]*	id_scheme:scheme	Scheme used for secondary ID
station_name	varchar		Name of station (e.g. Tateno)
station_abbreviation	varchar		Abbreviation of station name (e.g. TAT)
alternative_name	varchar[]*		Alternative name for station
station_crs	int	crs:crs	coordinate reference system used to report stations location
longitude	numeric		Report position for station if stationary or NULL if mobile. If more than one estimate record best here and additional values using optional fields.
latitude	numeric		Report position for station if stationary or NULL if mobile
local_gravity	numeric		Local gravity at station location (units ms-2)
start_date	timestamp		Date that the station first started reporting in this configuration
end_date	timestamp		Last data the station reported in this configuration
station_type	int	station_type:type	Type of reporting station
platform_type	int	platform_type:type	Generic type of observing platform
platform_sub_type	int	platform_sub_type:sub_type	Specific type of observing platform
operating_institute	int	organisation:organisation_id	Institute operating the station (e.g. National Oceanography Centre)
operating_territory	int	sub_region:sub_region	Sub-region where station is located or country of registry for mobile station
city	varchar		Nearest city / town to station location
contact	varchar[]	contact:contact_id	Contact for station
role	int[]	role:role	Role of contact

Continued on next page



Table 4 station_configuration (cont.)

element_name	type	external_table	description
observing_frequency	int	observing_frequency:frequency	Typical frequency of observations for this station (reports per day). If irregular use reporting_time.
reporting_time	int[]		Reporting hour(s) if non-standard / irregular hours used
telecommunication_method	int[]	communication_method:method	Method used to report observations
station_automation	int	automation_status:automation	Whether station is automated, manual or mixed
measuring_system_model	varchar[]		Station / AWS model type
measuring_system_id	varchar[]		ID or serial number of measuring system
observed_variables	int[]	observed_variable:variable	array indicating which variables are observed by this station
comment	varchar		Any other comments / footnotes
optional_data	int	data_present:flag	Flag indicating availability of additional data

End of table

Table 5: station_configuration_optional definition

element_name	kind	external_table	description
station_primary_id	varchar	station_configuration:primary_id	Link to station for which this entry corresponds
record_number	int	station_configuration:record_number	Link to station for which this entry corresponds
kind	int	kind:kind	Enumerated data type (numeric, int, etc)
field	varchar	station_configuration_fields:field_id	Field that this entry corresponds to
value			Kind inherited from field
comments	varchar		Any additional comments.

End of table

4.4 Profile configuration



Table 6: profile_configuration definition

element_name	kind	external_table	description
profile_id	varchar (pk)		Unique ID for this profile entry
profile_type	int	profile_type:type	Type of profile (e.g. atmospheric or oceanic)
standard_time	int	standard_time:time	e.g. Standard / scheduled time for launch or report, e.g. 00, 06, 12, 18 UTC
actual_time	timestamp		Actual report / launch time
profile_number	numeric		e.g. Balloon Number
comments	varchar		Any additional comments / footnotes
optional_data	int	data_present:flag	Flag indicating whether there is additional meta-data available

End of table

Table 7: profile_configuration_optional definition

element_name	kind	external_table	description
profile_id	varchar	profile_configuration:profile_id	Link to profile for which this entry corresponds
kind	int	kind:kind	Enumerated data type (numeric, int, etc)
field	varchar	profile_configuration_fields:field_id	Field that this entry corresponds to
value			Kind inherited from field
comments	varchar		Any additional comments.

End of table

4.5 Source configuration

Table 8: source_configuration definition

element_name	type	external_table	description
source_id	varchar (pk)		Unique record ID for dataset
product_id	varchar		ID for product

Continued on next page



Table 8 source_configuration (cont.)

element_name	type	external_table	description
product_name	varchar		Name of source, e.g. International Comprehensive Ocean Atmosphere Data Set, RS92 GRUAN Data Product
product_code	varchar		Abbreviations / product code, e.g. ICOADS, RS92-GDP
product_version	varchar		Version number for dataset, e.g. Release 3.0.0
product_level	int	product_level:level	Level of product
product_uri	varchar		URI for product, either to original source or to CDS
description	varchar		Description of dataset / comments
product_references	varchar[]		References describing the dataset
product_citation	varchar[]		Citation to use when using this product
product_status	int	product_status:status	Status of product, draft, pre-release, release
source_format	int	source_format:format	Original format for data
source_format_version	varchar		Version of original data format
source_file	varchar		Filename for data from source
source_file_checksum	varchar		Checksum of source datafile
data_centre	int	organisation:organisation_id	Data centre from which data sourced
data_centre_url	varchar		URL for data centre
data_policy_licence	int	data_policy_licence:policy	Data policy / licence
contact	varchar[]	contact:contact_id	contact for data source with role specified by role element
contact_role	int[]	role:role	role of contact
history	varchar		History of source
comments	varchar		Additional comments / footnotes
timestamp	timestamp with time-zone		Date record created / created

Continued on next page



Table 8 source_configuration (cont.)

element_name	type	external_table	description
maintenance_and_update_frequency	int	update_frequency:frequency	Frequency with which modifications and deletions are made to the data after it is first produced
optional_data	int	data_present:flag	Flag indicating availability of additional data

End of table

Table 9: source_configuration_optional definition

element_name	kind	external_table	description
source_id	varchar (fk)	source_configuration:source_id	Link to source for which this entry corresponds
kind	int	kind:kind	Enumerated data type (numeric, int, etc)
field	varchar	source_configuration_fields:field_id	Field that this entry corresponds to
value			Kind inherited from field
comments	varchar		Any additional comments.

End of table

4.6 Sensor configuration

Table 10: sensor_configuration definition

element_name	type	external_table	description
sensor_id	varchar (pk)		Unique ID for this instrument
observing_method	int	observing_method:method	Method (instrumental, estimated / visual, computed) by which observation made
sampling_strategy	int	sampling_strategy:strategy	Sampling strategy used by instrument
calibration_status	int	calibration_status:status	Whether the sensor is in / out of calibration
calibration_date	timestamp		Date of last calibration
comments	varchar		additional comments for sensor not reportable elsewhere
date_start	timestamp		start date for period of validity associated with this entry

Continued on next page



Table 10 sensor_configuration (cont.)

element_name	type	external_table	description
date_end	timestamp		end date for period of validity associated with this entry
optional_data	int	data_present:flag	Flag indicating if additional data available

End of table

Table 11: sensor_configuration_optional definition

element_name	kind	external_table	description
sensor_id	varchar (fk)	sensor_configuration:sensor_id	Link to sensor for which this entry corresponds
kind	int	kind:kind	Enumerated data type (numeric, int, etc)
field	varchar	sensor_configuration_fields:field_id	Field that this entry corresponds to
value			Kind inherited from field
comments	varchar		Any additional comments.

End of table

4.7 Quality control flags

A single QC flag is provided in the observations table for the observed value. Additional flags can be provided using the qc_table and by setting the advanced_qc flag to true in the observations_table.

Table 12: qc_table definition

element_name	kind	external_table	description
report_id	varchar	header_table:report_id	Link to report this entry is for
observation_id	varchar	observations_table:observation_id	Link to observation this entry is for. Set to NULL / NA if entry for report level QC
qc_method	int	qc_method:method	Link to table describing QC method used to set this flag
qc_flag	int	quality_flag:flag	E.g. 0 = good, 1 = inconsistent etc

End of table



4.8 Uncertainty budget

A single standard uncertainty value is provided for each observed value in the observations table. Additional values can be provided using the uncertainty_table and by setting the advanced_uncertainty to true in the observations_table.

Table 13: uncertainty_table definition

element_name	kind	external_table	description
observation_id	varchar	observations_table:observation_id	Link to observation this entry is for
uncertainty_type	varchar		Text description of the type of uncertainty described by this entry
uncertainty_method	int	uncertainty_method:method	Method used to estimate this uncertainty
uncertainty_value	numeric		Expected error standard deviation due to specified uncertainty source
uncertainty_units	int	units:units	The units used to report the uncertainty. This may be different to the reporting units (e.g. %)

End of table

4.9 Homogenisation data

Table 14: homogenisation_table definition

element_name	kind	external_table	description
observation_id	varchar	observations_table:observation_id	Link to observation this entry is for
homogenisation_method	int	homogenisation_method:method	Method used to homogenise data
homogenisation_adjustment	numeric		Value applied to homogenise data (homogenised_value = original (+/-/*) homogenisation_adjustment)
homogenisation_operator	int	homogenisation_operator:operator	Operator (+/-/*) used to apply adjustment

Continued on next page



Table 14 homogenisation_table (cont.)

element_name	kind	external_table	description
homogenisation_order	int		Order in which the adjustments are applied. Set to NA or missing if not applicable

End of table

5 References

- Freeman E., S. D. Woodruff, S. J. Worley, S. J. Lubker, E. C. Kent, W. E. Angel, D. I. Berry , P. Brohan, R. Eastman, L. Gates, W. Gloeden, Z. Ji, J. Lawrimore, N. A. Rayner, G. Rosenhagen, S. R. Smith, 2017: ICOADS Release 3.0: A Major Update to the Historical Marine Climate Record, International Journal of Climatology, 37, 2211 - 2232. doi:10.1002/joc.4775
- GCOS, 2016: The Global Observing System for Climate: Implementation Needs. GCOS-200 / GOOS-214, WMO, Geneva, 342pp.
- Hersbach, H., P. Poli and D. Dee, 2015: The observation feedback archive for ICOADS and ISPD datasets. ERA Report Series No. 18, ECMWF, Reading, UK, 31pp.
- Saarinen, S., 2004: ODB User guide (draft 1st edition), ECMWF, Reading, UK, 289pp.
- WMO, 2015a: Manual On Codes (WMO-No 306), Volume I.2, Part B - Binary Codes, WMO, Geneva.
- WMO, 2015b: Manual on the WMO Integrated Global Observing System: Annex VIII to the Technical Regulations (WMO-No 1160), WMO, Geneva.



6 Appendix

6.1 Table definitions

6.1.1 Data tables

Table 15: adjustment definition

element_name	kind	external_table	description
adjustment_id	varchar (pk)		unique ID for adjustment record
observation_id	varchar	observations_table:observation_id	link to observation that this entry is for
value	numeric		adjustment value
reference	varchar		reference describing adjustment

End of table

Table 16: contact definition

element_name	kind	external_table	description
contact_id	varchar (pk)		primary key
title	varchar		Title of contact (e.g. Mr, Mrs, Dr. etc)
name	varchar		Name of contact
organisation	varchar	organisation:organisation_id	Link to organisation that contact is associated with
telephone	varchar		telephone number for contact
email	varchar		email address for contact
url	varchar		website for contact

End of table

Table 17: header_table definition

element_name	kind	external_table	description
report_id	varchar (pk)		Unique ID for report (unique ID given by combination of report_id and observation_id)
region	int	region:region	Region (WMO region / Ocean basin)
sub_region	int	sub_region:sub_region	Country / regional sea

Continued on next page



Table 17 header_table (cont.)

element_name	kind	external_table	description
application_area	int[]	application_area:application_area	WMO application area(s)
observing_programme	int[]	observing_programme:observing_programme	Observing programme, e.g. VOS
report_type	int	report_type:type	e.g. SYNOP, TEMP, CLIMAT, etc
station_name	varchar		e.g. GRUAN station name, ship name, site name etc
station_type	int	station_type:type	Type of station, e.g. land station, sea station etc
platform_type	int	platform_type:type	Structure upon which sensor is mounted, e.g. ship, drifting buoy, tower etc
platform_sub_type	int	platform_sub_type:sub_type	Sub-type for platform, e.g. 3m discuss buoy
primary_station_id	varchar	station_configuration:primary_id	Primary station identifier, e.g. WIGOS ID
station_record_number	int	station_configuration:record_number	Together with primary_station_id this forms a link to the station configuration table.
primary_station_id_scheme	int	id_scheme:scheme	Scheme used for station ID
longitude	numeric		Longitude of station, -180.0 to 180.0 (or other as defined by station_crs)
latitude	numeric		Latitude of station, -90 to 90 (or other as defined by station_crs)
location_accuracy	numeric		Accuracy to which station location recorded (radius in km)
location_method	int	location_method:method	Method by which location determined
location_quality	int	location_quality:quality	Quality flag for station location
crs	int	crs:crs	Coordinate reference scheme for station location
station_speed	numeric		Station speed over ground if mobile (m/s)
station_course	numeric		Station course over ground if mobile (degree true)
station_heading	numeric		Station heading if mobile

Continued on next page



Table 17 header_table (cont.)

element_name	kind	external_table	description
height_of_station_above_local_ground	numeric		Height of station above local ground (m)
height_of_station_above_sea_level	numeric		Height of station above mean sea level (m), negative values for below sea level.
height_of_station_above_sea_level_accuracy	numeric		Accuracy to which height of station known (m)
sea_level_datum	int	sea_level_datum:datum	Datum used for sea level
report_meaning_of_time_stamp	int	meaning_of_time_stamp:meaning	Report time - beginning, middle or end of reporting period
report_timestamp	timestamp with time-zone		e.g. 1991-01-01 12:00:0.0+0
report_duration	int		Report duration (s), e.g. 86400 = daily obs, 3600 hourly etc
report_time_accuracy	numeric		Precision to which time was recorded (s)
report_time_quality	int	time_quality:quality	Quality flag for report_timestamp
report_time_reference	int	time_reference:reference	Reference Time (e.g. referenced to time server, atomic clock, radio clock etc)
profile_id	varchar	profile_configuration:profile_id	Information on profile (atmospheric / oceanographic) configuration. Set to Record ID for profile data or missing (NULL) otherwise.
events_at_station	int[]*	events_at_station:event	e.g. ship hove to, crop burning etc.
report_quality	int	quality_flag:flag	Overall quality of report
duplicate_status	int	duplicate_status:status	E.g. no duplicates, best duplicate, duplicate, not checked.
duplicates	varchar[]*	header_table:report_id	Array of report_id's for duplicates
record_timestamp	timestamp with time-zone		Timestamp of revision for this record

Continued on next page



Table 17 header_table (cont.)

element_name	kind	external_table	description
history	varchar		Sequence of processing steps. Free text with timestamp 1 : history 1; timestamp 2 : history 2 etc.
processing_level	int	report_processing_level:level	Level of processing applied to this report
processing_codes	int[]*	report_processing_codes:code	Processing applied to this report
source_id	varchar	source_configuration:source_id	Original source of data, link to external table
source_record_id	varchar		Record ID in source data, e.g. ID of event from GRUAN meta database

End of table

Table 18: homogenisation_table definition

element_name	kind	external_table	description
observation_id	varchar	observations_table:observation_id	Link to observation this entry is for
homogenisation_method	int	homogenisation_method:method	Method used to homogenise data
homogenisation_adjustment	numeric		Value applied to homogenise data (homogenised_value = original (+/-/*) homogenisation_adjustment)
homogenisation_operator	int	homogenisation_operator:operator	Operator (+/-/*) used to apply adjustment
homogenisation_order	int		Order in which the adjustments are applied. Set to NA or missing if not applicable

End of table

Table 19: observations_table definition

element_name	kind	external_table	description
observation_id	varchar (pk)		unique ID for observation
report_id	varchar	header_table:report_id	Link to header information

Continued on next page



Table 19 observations_table (cont.)

element_name	kind	external_table	description
data_policy_licence	int	data_policy_licence:policy	WMOessential, WMOadditional, WMOother
date_time	timestamp with time-zone		timestamp for observation
date_time_meaning	int	meaning_of_time_stamp:meaning	beginning, middle, end
observation_duration	int		Duration/period over which observation was made (s)
longitude	numeric		Longitude of the observed value, -180 to 180 (or other as defined by CRS). This may or may not be the same as the report location.
latitude	numeric		Latitude of the observed value, -90 to 90 (or other as defined by CRS)
crs	int	crs:crs	Coordinate reference scheme use to encode location
z_coordinate	numeric		z coordinate of observation
z_coordinate_type	int	z_coordinate_type:type	Type of z coordinate
observation_height_above_station_surface	numeric		Height of sensor above local ground or sea surface. Positive values for above surface (e.g. sondes), negative for below (e.g. xbt). For visual observations, height of the visual observing platform.
observed_variable	int	observed_variable:variable	The variable being observed / measured
secondary_variable	int	secondary_variable:variable	Secondary variable required to understand observation, e.g. chemical constituent. Set to NA / missing if not applicable.
observation_value	numeric		The observed value
value_significance	int	observation_value_significance:significance	e.g. min, max, mean, sum

Continued on next page



Table 19 observations_table (cont.)

element_name	kind	external_table	description
secondary_value	int	secondary_variable:value	value for the secondary variable. Set to NA or missing if not applicable.
units	int	units:units	Units for the observed variable
code_table	int	observation_code_table:code_table	Encode / decode table for variable (if encoded)
conversion_flag	int	conversion_flag:flag	Flag indicating whether original, converted or both values are available.
location_method	int	location_method:method	Method of determining location,
location_precision	numeric		Precision to which location is reported (radius km)
z_coordinate_method	int	z_coordinate_method:method	Method of determining z coordinate
bbox_min_longitude	numeric		Bounding box for observation, valid range given by CRS
bbox_max_longitude	numeric		Bounding box for observation, valid range given by CRS
bbox_min_latitude	numeric		Bounding box for observation, valid range given by CRS
bbox_max_latitude	numeric		Bounding box for observation, valid range given by CRS
spatial_representativeness	int	spatial_representativeness:representativeness	Spatial representativeness of observation
quality_flag	int	quality_flag:flag	Quality flag for observation
qc_passed	int		Number of quality control checks passed (see qc_table for more information)
qc_failed	int		Number of quality control checks failed (see qc_table for more information)
numerical_precision	int		Reporting precision of observation in units given by 'units' variable. Equivalent to BUFR scale factor
standard_uncertainty	numeric		Standard uncertainty in reported value

Continued on next page



Table 19 observations_table (cont.)

element_name	kind	external_table	description
method_of_estimating_standard_uncertainty	int	method_of_estimating_uncertainty:method	Method of estimating the standard uncertainty
sensor_id	varchar	sensor_configuration:sensor_id	Link to sensor_configuration table.
sensor_automation_status	int	automation_status:automation	Automated, manual, mixed or visual observation
exposure_of_sensor	int	instrument_exposure_quality:exposure	Whether the exposure of the instrument will impact on the quality of the measurement
original_precision	int		Original reporting precision in units given by 'original_units'
original_units	int	units:units	Original units
original_value	numeric		Original value as reported or recorded in log book.
conversion_method	int	conversion_method:method	Link to table describing conversion process
processing_code	int[]*	processing_code:code	e.g. TRC (temperature radiation corrections) etc. Encoded in table.
processing_level	int	processing_level:level	Level of processing applied to observation.
adjustment_id	int	adjustment:adjustment_id	Total adjustment applied to observation reported in observation value (observation_value = original + adjustment)
traceability	int	traceability:traceability	Whether observation can be traced to international standards.
advanced_qc	int	data_present:flag	Flag indicating whether advanced qc data are available
advanced_uncertainty	int	data_present:flag	Flag indicating whether advanced uncertainty estimates are available
advanced_homogenisation	int	data_present:flag	Flag indicating whether advanced homogenisation information is available

End of table



Table 20: organisation definition

element_name	kind	external_table	description
organisation_id	varchar (pk)		unique ID for organisation
parent_organisation	varchar	organisation:organisation_id	Link to parent organisation (or NA/NULL or none)
name	varchar		Name of organisation
abbreviation	varchar		Abbreviated name (or NA/NULL)
address	varchar		Road / building name
city	varchar		City
admin_area	varchar		County or admin region
region	int	region:region	WMO Region
country	int	sub_region:sub_region	Country
postal_code	varchar		Postal / zip code
telephone	varchar		Primary telephone number of organisation
url	varchar		Link to organisation website
email	varchar		Primary email contact for website

End of table

Table 21: profile_configuration definition

element_name	kind	external_table	description
profile_id	varchar (pk)		Unique ID for this profile entry
profile_type	int	profile_type:type	Type of profile (e.g. atmospheric or oceanic)
standard_time	int	standard_time:time	e.g. Standard / scheduled time for launch or report, e.g. 00, 06, 12, 18 UTC
actual_time	timestamp		Actual report / launch time
profile_number	numeric		e.g. Balloon Number
comments	varchar		Any additional comments / footnotes
optional_data	int	data_present:flag	Flag indicating whether there is additional meta-data available

End of table



Table 22: profile_configuration_optional definition

element_name	kind	external_table	description
profile_id	varchar	profile_configuration:profile_id	Link to profile for which this entry corresponds
kind	int	kind:kind	Enumerated data type (numeric, int, etc)
field	varchar	profile_configuration_fields:field_id	Field that this entry corresponds to
value			Kind inherited from field
comments	varchar		Any additional comments.

End of table

Table 23: qc_table definition

element_name	kind	external_table	description
report_id	varchar	header_table:report_id	Link to report this entry is for
observation_id	varchar	observations_table:observation_id	Link to observation this entry is for. Set to NULL / NA if entry for report level QC
qc_method	int	qc_method:method	Link to table describing QC method used to set this flag
qc_flag	int	quality_flag:flag	E.g. 0 = good, 1 = inconsistent etc

End of table

Table 24: sensor_configuration definition

element_name	type	external_table	description
sensor_id	varchar (pk)		Unique ID for this instrument
observing_method	int	observing_method:method	Method (instrumental, estimated / visual, computed) by which observation made
sampling_strategy	int	sampling_strategy:strategy	Sampling strategy used by instrument
calibration_status	int	calibration_status:status	Whether the sensor is in / out of calibration
calibration_date	timestamp		Date of last calibration
comments	varchar		additional comments for sensor not reportable elsewhere

Continued on next page



Table 24 sensor_configuration (cont.)

element_name	type	external_table	description
date_start	timestamp		start date for period of validity associated with this entry
date_end	timestamp		end date for period of validity associated with this entry
optional_data	int	data_present:flag	Flag indicating if additional data available

End of table

Table 25: sensor_configuration_optional definition

element_name	kind	external_table	description
sensor_id	varchar (fk)	sensor_configuration:sensor_id	Link to sensor for which this entry corresponds
kind	int	kind:kind	Enumerated data type (numeric, int, etc)
field	varchar	sensor_configuration_fields:field_id	Field that this entry corresponds to
value			Kind inherited from field
comments	varchar		Any additional comments.

End of table

Table 26: source_configuration definition

element_name	type	external_table	description
source_id	varchar (pk)		Unique record ID for dataset
product_id	varchar		ID for product
product_name	varchar		Name of source, e.g. International Comprehensive Ocean Atmosphere Data Set, RS92 GRUAN Data Product
product_code	varchar		Abbreviations / product code, e.g. ICOADS, RS92-GDP
product_version	varchar		Version number for dataset, e.g. Release 3.0.0
product_level	int	product_level:level	Level of product
product_uri	varchar		URI for product, either to original source or to CDS
description	varchar		Description of dataset / comments

Continued on next page



Table 26 source_configuration (cont.)

element_name	type	external_table	description
product_references	varchar[]		References describing the dataset
product_citation	varchar[]		Citation to use when using this product
product_status	int	product_status:status	Status of product, draft, pre-release, release
source_format	int	source_format:format	Original format for data
source_format_version	varchar		Version of original data format
source_file	varchar		Filename for data from source
source_file_checksum	varchar		Checksum of source datafile
data_centre	int	organisation:organisation_id	Data centre from which data sourced
data_centre_url	varchar		URL for data centre
data_policy_licence	int	data_policy_licence:policy	Data policy / licence
contact	varchar[]	contact:contact_id	contact for data source with role specified by role element
contact_role	int[]	role:role	role of contact
history	varchar		History of source
comments	varchar		Additional comments / footnotes
timestamp	timestamp with time-zone		Date record created / created
maintenance_and_update_frequency	int	update_frequency:frequency	Frequency with which modifications and deletions are made to the data after it is first produced
optional_data	int	data_present:flag	Flag indicating availability of additional data

End of table

Table 27: source_configuration_optional definition

element_name	kind	external_table	description
source_id	varchar (fk)	source_configuration:source_id	Link to source for which this entry corresponds
kind	int	kind:kind	Enumerated data type (numeric, int, etc)

Continued on next page



Table 27 source_configuration_optional (cont.)

element_name	kind	external_table	description
field	varchar	source_configuration_fields:field_id	Field that this entry corresponds to
value			Kind inherited from field
comments	varchar		Any additional comments.

End of table

Table 28: station_configuration definition

element_name	type	external_table	description
primary_id	varchar (pk)		Primary (e.g. WMO) ID for station
primary_id_scheme	int	id_scheme:scheme	Scheme used for primary ID
record_number	int (pk)		Record number for this station entry
secondary_id	varchar[]*		Secondary (e.g. local) ID for station
secondary_id_scheme	int[]*	id_scheme:scheme	Scheme used for secondary ID
station_name	varchar		Name of station (e.g. Tateno)
station_abbreviation	varchar		Abbreviation of station name (e.g. TAT)
alternative_name	varchar[]*		Alternative name for station
station_crs	int	crs:crs	coordinate reference system used to report stations location
longitude	numeric		Report position for station if stationary or NULL if mobile. If more than one estimate record best here and additional values using optional fields.
latitude	numeric		Report position for station if stationary or NULL if mobile
local_gravity	numeric		Local gravity at station location (units ms-2)
start_date	timestamp		Date that the station first started reporting in this configuration
end_date	timestamp		Last data the station reported in this configuration
station_type	int	station_type:type	Type of reporting station

Continued on next page



Table 28 station_configuration (cont.)

element_name	type	external_table	description
platform_type	int	platform_type:type	Generic type of observing platform
platform_sub_type	int	platform_sub_type:sub_type	Specific type of observing platform
operating_institute	int	organisation:organisation_id	Institute operating the station (e.g. National Oceanography Centre)
operating_territory	int	sub_region:sub_region	Sub-region where station is located or country of registry for mobile station
city	varchar		Nearest city / town to station location
contact	varchar[]	contact:contact_id	Contact for station
role	int[]	role:role	Role of contact
observing_frequency	int	observing_frequency:frequency	Typical frequency of observations for this station (reports per day). If irregular use reporting_time.
reporting_time	int[]		Reporting hour(s) if non-standard / irregular hours used
telecommunication_method	int[]	communication_method:method	Method used to report observations
station_automation	int	automation_status:automation	Whether station is automated, manual or mixed
measuring_system_model	varchar[]		Station / AWS model type
measuring_system_id	varchar[]		ID or serial number of measuring system
observed_variables	int[]	observed_variable:variable	array indicating which variables are observed by this station
comment	varchar		Any other comments / footnotes
optional_data	int	data_present:flag	Flag indicating availability of additional data

End of table



Table 29: station_configuration_optional definition

element_name	kind	external_table	description
station_primary_id	varchar	station_configuration:primary_id	Link to station for which this entry corresponds
record_number	int	station_configuration:record_number	Link to station for which this entry corresponds
kind	int	kind:kind	Enumerated data type (numeric, int, etc)
field	varchar	station_configuration_fields:field_id	Field that this entry corresponds to
value			Kind inherited from field
comments	varchar		Any additional comments.
End of table			

Table 30: uncertainty_table definition

element_name	kind	external_table	description
observation_id	varchar	observations_table:observation_id	Link to observation this entry is for
uncertainty_type	varchar		Text description of the type of uncertainty described by this entry
uncertainty_method	int	uncertainty_method:method	Method used to estimate this uncertainty
uncertainty_value	numeric		Expected error standard deviation due to specified uncertainty source
uncertainty_units	int	units:units	The units used to report the uncertainty. This may be different to the reporting units (e.g. %)
End of table			



6.1.2 Code tables

Table 31: application_area definition (WIGOS 2-01)

element_name	kind	external_table	description
application_area	int(pk)		Unique ID for code entry
description	varchar		Description of application area
End of table			

Table 32: automation_status definition

element_name	kind	external_table	description
automation	int(pk)		Unique ID for entry
description	varchar		description of automation status (e.g. automatic observations, manual observation etc)
End of table			

Table 33: calibration_status definition (WIGOS 5-08)

element_name	kind	external_table	description
status	int(pk)		unique ID for entry
description	varchar		Description of calibration status (e.g. No changes - in calibration etc)
End of table			

Table 34: communication_method definition (Various sources (WMO47, WIGOS, BUFR))

elemet_name	kind	external_table	description
method	int(pk)		Primary key / unique ID for entry
description	varchar		Decoded value / text description of communication method
End of table			



Table 35: conversion_flag definition

element_name	kind	external_table	description
flag	int(pk)		primary key
description	varchar		Description of whether the original value has been converted or decoded and is stored in the observed variable element

End of table

Table 36: conversion_method definition

element_name	kind	external_table	description
method	int(pk)		unique ID for entry
description	varchar		text description of conversion method
implementation	varchar		details of implementation
reference	varchar		reference / doi of document giving more details on conversion method

End of table

Table 37: crs definition (BUFR 0 01 150)

element_name	kind	external_table	description
crs	int(pk)		primary key
description	varchar		Decoded value / description of coordinate reference system

End of table

Table 38: data_policy_licence definition (WIGOS 9-02)

element_name	kind	external_table	description
policy	int (pk)		Primary key for table
name	varchar		short name of data policy
description	varchar		Description of data licence, usage rights and restrictions

End of table



Table 39: data_present definition

element_name	kind	external_table	description
flag	int(pk)		Primary key for table
description	varchar		Decoded value indicating presence of additional data

End of table

Table 40: duplicate_status definition (Simplified version of duplicate status flags from IMMA (ICOADS))

element_name	kind	external_table	description
status	int(pk)		Primary key for table
description	varchar		Decoded value / description of duplicate status (e.g. unique, best duplicate etc)

End of table

Table 41: events_at_station definition (WIGOS 4-04)

element_name	kind	external_table	description
event	int(pk)		primary key for table
description	varchar		Decoded value / description of events at the time of report / observation

End of table

Table 42: homogenisation_method definition

element_name	kind	external_table	description
method	int (pk)		Primary key for table
description	varchar		Description of method
reference	varchar		DOI or reference for method

End of table

Table 43: homogenisation_operator definition

element_name	kind	external_table	description
operator	int (pk)		Primary key for table

Continued on next page



Table 43 homogenisation_operator (cont.)

element_name	kind	external_table	description
symbol	varchar		symbol representation of operator, e.g. +
description	varchar		text representation of operator, e.g. add

End of table

Table 44: id_scheme definition

element_name	kind	external_table	description
scheme	int(pk)		Primary key for table
description	varchar		Decoded value / description of ID scheme used to report the station ID

End of table

Table 45: instrument_exposure_quality definition (WIGOS 5-15)

element_name	kind	external_table	description
exposure	int(pk)		primary key for table
description	varchar		decoded value / description of instrument exposure quality

End of table

Table 46: kind definition

element_name	kind	external_table	description
kind	int(pk)		primary key
description	varchar		kind of data (int, numeric etc)

End of table

Table 47: location_method definition (based on WIGOS 11-01 and BUFR 0 02 148)

element_name	kind	external_table	description
method	int(pk)		primary key for table

Continued on next page



Table 47 location_method (cont.)

element_name	kind	external_table	description
description	varchar		decoded value / description of method by which the station location has been determined

End of table

Table 48: location_quality definition

element_name	kind	external_table	description
quality	int (pk)		primary key for table
description	varchar		decoded value / description of the quality of the location this indicator is for

End of table

Table 49: meaning_of_time_stamp definition (Based on simplified version of WIGOS 11-03)

element_name	kind	external_table	description
meaning	int(pk)		primary key
name	varchar		abbreviation / simple name for meaning of time stamp
description	varchar		definition of meaning of time stamp

End of table

Table 50: method_of_estimating_uncertainty definition

element_name	kind	external_table	description
method	int(pk)		primary key for table
description	varchar		decoded value / description of how the uncertainty has been determined
reference	varchar		Reference or DOI describing method

End of table



Table 51: observation_code_table definition

element_name	kind	external_table	description
code_table	int (pk)		Primary key for table
code_table_scheme	varchar		External scheme used for code table (e.g. BUFR)
code_table_id	varchar		ID used to identify table within scheme (e.g. F XX YYY for BUFR tables)
code_table_name	varchar		Name of code table
value	int		coded value
description	varchar		decoded value / meaning of decoded value
End of table			

Table 52: observation_value_significance definition (based on BUFR 0 08 023)

element_name	kind	external_table	description
significance	int (pk)		Primary key for table
description	varchar		decoded value / description of indicated significance (e.g. min over specified period)
End of table			

Table 53: observed_variable definition

element_name	kind	external_table	description
variable	int(pk)		primary key for table
parameter_group	varchar		parameter group (e.g. temperature, pressure) that this variable belongs to
domain	varchar		Observation domain (atmospheric, oceanic etc) that this variable is typically reported for
sub_domain	varchar		Sub-domain (e.g. upper air, surface etc)
name	varchar		common name for variable
units	varchar		ASCII abbreviation of units
Continued on next page			



Table 53 observed_variable (cont.)

element_name	kind	external_table	description
description	varchar		Description / definition of variable

End of table

Table 54: observing_frequency definition (WMO47 - 0602)

element_name	kind	external_table	description
frequency	int(pk)		primary key for table
description	varchar		decoded value / description of reporting frequency (e.g. once per day)

End of table

Table 55: observing_method definition

element_name	kind	external_table	description
method	int (pk)		primary key for table
description	varchar		decoded value indicating method of observing (e.g. measured, estimating or computed)

End of table

Table 56: observing_programme definition (WIGOS 2-02)

element_name	kind	external_table	description
observing_programme	int(pk)		primary key for table
abbreviation	varchar		Commonly used abbreviation for observing programme (e.g. VOS)
description	varchar		Description or name of observing programme (e.g. Voluntary Observing Ships)
sponsor	varchar		primary sponsor of observing programme (e.g. JCOMM)

End of table



Table 57: platform_sub_type definition (based on WMO47, ICOADS, BUFR 0 02 149)

element_name	kind	external_table	description
sub_type	int (pk)		primary key for table
platform_type	int	platform_type:type	platform type to which this sub-type belongs
abbreviation	varchar		abbreviation used to indicate this platform sub-type
description	varchar		description of observing platform sub-type (e.g. Container ship)

End of table

Table 58: platform_type definition (IMMA (ICOADS) and BUFR 0 03 001 (0 - 31))

element_name	kind	external_table	description
type	int (pk)		primary key for table
description	varchar		Description of class of observing platform

End of table

Table 59: processing_code definition

element_name	kind	external_table	description
code	int (pk)		primary key for table
abbreviation	varchar		abbreviation for processing code
description	varchar		description / meaning of processing code

End of table

Table 60: processing_level definition (WIGOS 7-06)

element_name	kind	external_table	description
level	int (pk)		primary key for table
name	varchar		Name commonly used to indicate level of processing
description	varchar		Description of processing level

End of table



Table 61: product_level definition

element_name	kind	external_table	description
level	int (pk)		primary key for table
description	varchar		Meaning of product level
End of table			

Table 62: product_status definition

element_name	kind	external_table	description
status	int(pk)		primary key for table
abbreviation	varchar		abbreviation used to indicate product status
description	varchar		Meaning of product status
End of table			

Table 63: profile_configuration_codes definition

element_name	kind	external_table	description
field_id	varchar (pk)	profile_configuration_fields:field_id	Link to field code is for
field_name	varchar		Name of field
code_value	int (pk)		Coded value. Together with field_id forms primary key
abbreviation	varchar		Abbreviation used for coded value
description	varchar		Decoded value / meaning of code
start_date	timestamp		Start of validity period for indicated code
end_date	timestamp		End of validity period for indicated code
End of table			

Table 64: profile_configuration_fields definition

element_name	kind	external_table	description
field_id	varchar (pk)		primary key
field_name	varchar		Name of field described by this entry
Continued on next page			



Table 64 profile_configuration_fields (cont.)

element_name	kind	external_table	description
type	int	kind:kind	The variable type used to store information on the indicated field
description	varchar		Description of the indicated field

End of table

Table 65: profile_type definition

element_name	kind	external_table	description
type	int (pk)		primary key for table
description	varchar		type of profile measurements (atmospheric, oceanographic etc)

End of table

Table 66: qc_method definition

element_name	kind	external_table	description
method	int (pk)		Primary key for table
description	varchar		Description of method
reference	varchar		DOI or reference for method

End of table

Table 67: quality_flag definition (BUFR 0 33 020)

element_name	kind	external_table	description
flag	int (pk)		primary key for table
description	varchar		meaning of quality flag

End of table

Table 68: region definition (WIGOS 3-01)

element_name	kind	external_table	description
region	int(pk)		primary key for table
WMO_region	int		WMO region that this corresponds to
desription	varchar		Definition of region

Continued on next page



Table 68 region (cont.)

element_name	kind	external_table	description
End of table			

Table 69: report_processing_codes definition

element_name	kind	external_table	description
code	int (pk)		primary key for table
abbreviation	varchar		abbreviation used to indicate processing code
description	varchar		definition of processing code
End of table			

Table 70: report_processing_level definition

element_name	kind	external_table	description
level	int(pk)		primary key for table
abbreviation	varchar		abbreviation used to indicate processing level
description	varchar		definition of processing level
End of table			

Table 71: report_type definition

element_name	kind	external_table	description
type	int(pk)		primary key for table
abbreviation	varchar		abbreviation used to indicate report type (e.g. SHIP)
description	varchar		description of report type, e.g. routine weather report made by ship
End of table			

Table 72: role definition (ISOTC211/19115 CIRoleCode)

element_name	kind	external_table	description
role	int(pk)		primary key for table
description	varchar		definition of role
End of table			



Table 73: sampling_strategy definition (WIGOS 6-03)

element_name	kind	external_table	description
strategy	int (pk)		primary key for table
name	varchar		name or abbreviation used to indicate sampling strategy
description	varchar		definition of sampling strategy
End of table			

Table 74: sea_level_datum definition (BUFR 0 01 151)

element_name	kind	external_table	description
datum	int(pk)		primary key for table
description	varchar		Long name of sea level datum
End of table			

Table 75: secondary_variable definition

element_name	kind	external_table	description
variable	int(pk)		part of primary key - indicator for secondary variable name
variable_name	varchar		name / description of secondary variable
value	int(pk)		coded value for secondary variable
symbol	varchar		abbreviation or symbol used to represent decoded value, e.g. chemical symbol for atmospheric constituent
description	varchar		Name or description of decoded value
End of table			

Table 76: sensor_configuration_codes definition

element_name	kind	external_table	description
field_id	varchar (pk)	sensor_configuration_fields:field_id	Link to field code is for
field_name	varchar		Name of field

Continued on next page



Table 76 sensor_configuration_codes (cont.)

element_name	kind	external_table	description
parameter	varchar		Which parameter this entry is valid for
code_value	int (pk)		Coded value. Together with field_id forms primary key
abbreviation	varchar		Abbreviation used for coded value
description	varchar		Decoded value / meaning of code

End of table

Table 77: sensor_configuration_fields definition

element_name	kind	external_table	description
field_id	varchar (pk)		primary key
field_name	varchar		Name of field described by this entry
parameter	varchar		Which parameter this entry is relevant for
type	int	kind:kind	The variable type used to store information on the indicated field
description	varchar		Description of the indicated field

End of table

Table 78: source_configuration_codes definition

element_name	kind	external_table	description
field_id	varchar (pk)	source_configuration_fields:field_id	Link to field code is for
field_name	varchar		Name of field
code_value	int (pk)		Coded value. Together with field_id forms primary key
abbreviation	varchar		Abbreviation used for coded value
description	varchar		Decoded value / meaning of code

End of table



Table 79: source_configuration_fields definition

element_name	kind	external_table	description
field_id	varchar (pk)		primary key
field_name	varchar		Name of field described by this entry
type	int	kind:kind	The variable type used to store information on the indicated field
description	varchar		Description of the indicated field

End of table

Table 80: source_format definition

element_name	kind	external_table	description
format	int(pk)		primary key for table
description	varchar		description of data format, e.g. NetCDF

End of table

Table 81: spatial_representativeness definition (WIGOS 1-05)

element_name	kind	external_table	description
representativeness	int (pk)		primary key for table. coded value
description	varchar		meaning / definition of decoded value

End of table

Table 82: standard_time definition

element_name	kind	external_table	description
time	int(pk)		primary key for table, encoded value
description	varchar		decoded observing time, e.g. 12 UTC

End of table



Table 83: station_configuration_codes definition

element_name	kind	external_table	description
field_id	varchar (pk)	station_configuration_fields:field_id	Link to field code is for
field_name	varchar		Name of field
code_value	int (pk)		Coded value. Together with field_id forms primary key
abbreviation	varchar		Abbreviation used for coded value
description	varchar		Decoded value / meaning of code

End of table

Table 84: station_configuration_fields definition

element_name	kind	external_table	description
field_id	varchar (pk)		primary key
field_name	varchar		Name of field described by this entry
type	int	kind:kind	The variable type used to store information on the indicated field
description	varchar		Description of the indicated field

End of table

Table 85: station_type definition (WIGOS 3-04)

element_name	kind	external_table	description
type	int (pk)		primary key for table, coded value
description	varchar		decoded station type

End of table

Table 86: sub_region definition

element_name	kind	external_table	description
sub_region	int(pk)		primary key
type	varchar		type of sub region, e.g. country, regional sea etc

Continued on next page



Table 86 sub_region (cont.)

element_name	kind	external_table	description
code	varchar		abbreviation or character code
name	varchar		decoded value

End of table

Table 87: time_quality definition

element_name	kind	external_table	description
quality	int(pk)		primary key, coded value
description	varchar		decoded value expressing quality of time / date information

End of table

Table 88: time_reference definition (WIGOS: 7-10)

element_name	kind	external_table	description
reference	int(pk)		primary key, coded value
description	varchar		decoded base time to which times referenced

End of table

Table 89: traceability definition (WIGOS 8-05)

element_name	kind	external_table	description
traceability	int(pk)		primary key, coded value
description	varchar		definition of traceability of measurement

End of table

Table 90: uncertainty_method definition

element_name	kind	external_table	description
method	int (pk)		Primary key for table
description	varchar		Description of method
reference	varchar		DOI or reference for method

End of table



Table 91: units definition

element_name	kind	external_table	description
units	int(pk)		primary key
name	varchar		name of units
abbreviation	varchar		conventional abbreviation in ASCII
base_units	varchar		definition in base units

End of table

Table 92: update_frequency definition

element_name	kind	external_table	description
frequency	int (pk)		primary key
description	varchar		Description of update frequency

End of table

Table 93: z_coordinate_method definition

element_name	kind	external_table	description
method	int (pk)		primary key, coded value
description	varchar		description of method used to determine z location

End of table

Table 94: z_coordinate_type definition

element_name	kind	external_table	description
type	int(pk)		primary key, coded value
description	varchar		description of units / type of z coordinate

End of table



6.2 Code tables

Table 95: application_area codes

application_area	description
1	Global numerical weather prediction (GNWP)
2	High-resolution numerical weather prediction (HRNWP)
3	Nowcasting and very short range forecasting (NVSFR)
4	Seasonal and inter-annual forecasting (SIAF)
5	General weather forecasting
6	Aeronautical meteorology
7	Ocean applications
8	Agricultural meteorology
9	Hydrology
10	Climate monitoring (as undertaken through the Global Climate Observing System, GCOS)
11	Climate applications
12	Space weather
13	Cryosphere applications
14	Energy sector
15	Transportation sector
16	Health sector
17	Terrestrial ecology
18	Operational air quality forecasting
19	Atmospheric composition forecasting
20	Atmospheric composition monitoring and analysis
21	Large urban complexes

End of table

Table 96: automation_status codes

automation	description
0	Automatic observation.
1	Automatic, always supplemented by manual input.
2	Automatic, occasionally supplemented by manual input.

Continued on next page



Table 96 automation_status (cont.)

automation	description
3	Automatic, supplemented by manual observations.
4	Manual observation.
5	Unknown.
6	Visual observation.

End of table

Table 97: calibration_status codes

status	description
0	No changes - in calibration.
1	No changes - out of calibration.
2	No changes - calibration unknown.
3	Recalibrated - in calibration.

End of table

Table 98: communication_method codes

method	description
0	Cellular (unspecified)
1	Meteosat DCP
2	Iridium (unspecified)
3	GOES DCP
4	VSAT (unspecified)
5	Landline telephone
6	Radio modem
7	E-mail (unspecified)
8	Voice (ship). The observation is sent to a NMS through the telephone network. The communication may use Inmarsat, Iridium, Vsat, VHF
9	Email (ship). The observation is sent to a NMS through an email. The WMO message is attached to this email. The satellite communication provider may be Inmarsat, Iridium, Vsat

Continued on next page



Table 98 communication_method (cont.)

method	description
10	Web (ship). The observation is sent through the Web (example: TurboWeb). The satellite communication provider may be Inmarsat, Iridium, Vsat
11	Inmarsat-C (FM13, SAC41). Standard procedure used to report observations (FM13 messages) from conventional VOS for many years. Collect call system: the NMS which receives the observations pays the communication costs
12	Inmarsat-C (FM13, other SAC). FM13 messages are sent to a dedicated SAC (other than SAC41) established at one, or more LES. In general, communications are paid by the country who recruited the ship
13	Inmarsat-C (EUHC). Text messages containing compressed data (E-SURFMAR format) are sent ashore through Inmarsat-C to a dedicated SAC and LES. Communications are paid by the country who recruited the ship
14	Inmarsat-C (SEAS). SEAS binary messages sent through Inmarsat-C Data Mode to a dedicated SAC and LES. Communications are paid by NOAA/NWS
15	Automated Identification System (direct or through satellite)
16	Argos system
17	Cellular (Dial-up). Dial-up communication using terrestrial wireless networks (GSM, GPRS)
18	Cellular (SMS). SMS sent through terrestrial wireless networks (GSM, GPRS)
19	Globalstar communication system
20	GMS (DCP). Data Collecting Platform of Geostationary Meteorological Satellites
21	Iridium (SBD). Short Burst Data service of Iridium communication system
22	Iridium (Email). Email sent through Iridium (e.g. Easymail)
23	Iridium (Dial-up). Dial-up communication using Iridium

Continued on next page



Table 98 communication_method (cont.)

method	description
24	Inmarsat-C (Data Mode). Data Mode service of Inmarsat-C used by S-AWS. See above for SEAS which also uses this service for conventional VOS
25	Inmarsat-C (Email). Email sent through Inmarsat-C
26	Orbcomm communication system
27	Vsat (Email). Email sent through Vsat
28	Vsat (Dial-up). Dial-up communication using Vsat
29	Delayed Mode only
30	Other (specify in footnote).

End of table

Table 99: conversion_flag codes

flag	description
0	Both original (non SI) and converted (SI) values available, see conversion_method for details.
1	Only original value in non-SI units available, no conversion has been performed. See original_value field.
2	Original value in SI units available, no conversion required.
3	Value coded - see code_table for details.

End of table

Table 100: conversion_method codes

method	description	implementation	reference
TBD	TBD	TBD	TBD

End of table

Table 101: crs codes

crs	description
0	WGS84

Continued on next page



Table 101 crs (cont.)

crs	description
1	ETRS89
2	NAD83
3	DHDN
4	Ellipsoidal datum using International Reference Meridian maintained by the International Earth Rotation and Reference System Services (IERS)

End of table

Table 102: data_policy_licence codes

policy	name	description
0	Open	Data in public domain and freely available (no cost and unrestricted).
1	WMO essential	WMO Essential Data: free and unrestricted international exchange of basic data and products.
2	WMO additional	WMO Additional Data: free and unrestricted access to data and products exchanged under the auspices of WMO to the research and education communities for non-commercial activities. A more precise definition of the data policy may be additionally supplied within the metadata. In all cases it shall be the responsibility of the data consumer to ensure that they understand the data policy specified by the data provider – which may necessitate dialogue with the data publisher for confirmation of terms and conditions.

Continued on next page



Table 102 data_policy_licence (cont.)

policy	name	description
3	WMO other	Data identified for global distribution via WMO infrastructure (GTS / WIS) that is not covered by WMO Resolution 25 neither WMO Resolution 40 e.g. aviation OPMET data. Data marked with “WMOOther” data policy shall be treated like “WMOAdditional” where a more precise definition of the data policy may be additionally supplied within the metadata. In all cases it shall be the responsibility of the data consumer to ensure that they understand the data policy specified by the data provider – which may necessitate dialogue with the data publisher for confirmation of terms and conditions.

End of table

Table 103: data_present codes

flag	description
0	Indicated data is not available
1	Indicated data available

End of table

Table 104: duplicate_status codes

status	description
0	Unique observation, no known duplicates
1	Best duplicate
2	Duplicate
3	Worst duplicate
4	Unchecked

End of table

Table 105: events_at_station codes

event	description
1	Grass-cutting
2	Snow clearing

Continued on next page



Table 105 events_at_station (cont.)

event	description
3	Tree removal
4	Construction activity
5	Road work
6	Biomass burning
7	Dust storm
8	Storm damage
9	Wind storm
10	Flood
11	Fire
12	Earthquake
13	Land slide
14	Storm surge or tsunami
15	Lightning
16	Vandalism

End of table

Table 106: homogenisation_method codes

method	description	reference
TBD	TBD	TBD

End of table

Table 107: homogenisation_operator codes

operator	symbol	description
TBD	TBD	TBD

End of table

Table 108: id_scheme codes

scheme	description
0	WIGOS ID
1	GRUAN ID
2	IMO Number
3	National ID
4	WMO buoy / station number
5	Ship / platform callsign
6	Generic ID (e.g. SHIP, PLAT etc)

Continued on next page



Table 108 id_scheme (cont.)

scheme	description
7	Station name
8	ICOADS other
9	ICOADS unknown
10	ICOADS composite
11	Oceangraphic platform / cruise number
12	Other buoy number (e.g. Argo)

End of table

Table 109: instrument_exposure_quality codes

exposure	description
1	Class 1 - Exposure of instrument allows reference level measurements
2	Class 2 - Exposure of instrument has small or infrequent influence on measurement
3	Class 3 - Exposure of instrument leads to increased uncertainty or occasional invalid measurements
4	Class 4 - Exposure of instrument leads to high uncertainty or regular invalid measurements
5	Class 5 - Exposure of instrument leads to invalid measurements

End of table

Table 110: kind codes

kind	description
0	int
1	numeric
2	varchar
3	timestamp with timezone

End of table

Table 111: location_method codes

method	description
0	Argos
1	ARGOS DOPPLER

Continued on next page



Table 111 location_method (cont.)

method	description
2	ARGOS Kalman
3	Argos-3
4	Argos-4
5	From map
6	GALILEO
7	GOES DCP
8	GPS
9	INMARSAT
10	Iridium
11	Iridium and GPS
12	IRIDIUM DOPPLER
13	LORAN
14	Meteosat DCP
15	Orbcomm
16	Surveyed

End of table

Table 112: location_quality codes

quality	description
0	Good - location consistent with other reports from this station
1	Doubtful
2	Bad - Track check failed
3	Unchecked

End of table

Table 113: meaning_of_time_stamp codes

meaning	name	description
1	beginning	Date / time specified indicates the start of the period over which the observation was made.
2	end	Date / time specified indicates the end of the period over which the observation was made.
3	middle	Date / time specified indicates the middle of the period over which the observation was made.

End of table



Table 114: method_of_estimating_uncertainty codes

method	description	reference
TBD	TBD	TBD

End of table



Table 115: observation_code_table codes

code_table	code_table_ scheme	code_table_id	code_table _name	value	description
0	BUFR	0 20 003	Present weather	NA	See BUFR 0 20 003
1	BUFR	0 20 004	Past weather	NA	See BUFR 0 20 004
2	BUFR	0 10 063	Characteristics of pressure tendency	NA	See BUFR 0 10 063
					End of table



Table 116: observation_value_significance codes

significance	description
0	Maximum value over indicated period
1	Minimum value over indicated period
2	Mean value over indicated period
3	Median value over indicated period
4	Modal value over indicated period
5	Mean absolute error over indicated period
6	Best estimate of standard deviation (N-1) of observed parameter over indicated period
7	Standard deviation (N) of observed parameter over indicated period
8	Harmonic mean of observed parameter over indicated period
9	Root mean square vector error of observed parameter over indicated period
10	root mean square of observed parameter over indicated period
11	Vector mean of observed parameter over indicated period
12	Instantaneous value of observed parameter
13	Accumulation over specified period
14	Not applicable

End of table



Table 117: observed_variable codes

variable	parameter_group	domain	sub_domain	name	units	description
0	aerosols			aerosol absorption optical depth	Dimensionless	Vertical column integral of spectral aerosol absorption coefficient: $AAOD = \exp(-K \cdot Dz)$ where K is the absorption coefficient [km^{-1}] and Dz the vertical path [km]
1	aerosols			aerosol column burden	g m^{-2}	2D field of the column burden of condensed particles in the atmosphere
2	aerosols			aerosol dust concentration	g kg^{-1}	3-D field of concentration of dust or sand in the atmosphere
3	aerosols			aerosol effective radius	micro m	3D field of mean aerosol particle size, defined as the ratio of the third and second moments of the number size distribution of aerosol particles. Requested in the troposphere (assumed height: 12 km) and as columnar average.
4	aerosols			aerosol extinction coefficient	m^{-1}	3D field of spectral volumetric extinction cross-section of aerosol particles.
5	aerosols			aerosol mass mixing ratio	g kg^{-1}	3D field of the mass mixing ratio of condensed particles in the atmosphere
6	aerosols			aerosol optical depth	Dimensionless	The AOD is the effective depth of the aerosol column from the viewpoint of radiation propagation: Vertical column integral of spectral aerosol extinction coefficient $AOD = \exp(-K \cdot Dz)$ where K is the extinction coefficient [km^{-1}] and Dz the vertical path [km]

Continued on next page



Table 117 observed_variable (cont.)

variable	paramete r_group	domain	sub_domain	name	units	description
7	aerosols			aerosol species mole fraction	moles per mole of dry air	3D field of the mole fraction of condensed- phase chemical species (e.g., sulfate, nitrate, ammonium, elemental carbon, organic carbon), in the atmosphere
8	aerosols			aerosol species to- tal column burden	moles m-2	2D field of the total column burden concentration of condensed-phase chemical species (e.g., sulfate, nitrate, ammonium, elemental carbon, organic carbon), in the atmosphere
9	aerosols			aerosol type	coded	Selection, out of a pre-defined set of aerosol classes, that best fits an input data set (observed or modeled). The pre-defined set of aerosol classes includes specification of the particle composition, mixing state, complex refractive index, and shape as a function of particle size. The definition of aerosol type includes specification of all the classes as well as the algorithm used to choose the best fit to the input data.
10	aerosols			aerosol vol- canic ash	g kg-1	3D field of mass mixing ratio of volcanic ash
11	aerosols			total column aerosol vol- canic ash	g m-2	Field of total column mass of volcanic ash
12	aerosols			air conduc- tivity	km	TBD
13	albedo			blue ice and snow albedo	percent	TBD

Continued on next page



Table 117 observed_variable (cont.)

variable	parameter_group	domain	sub_domain	name	units	description
14	albedo			blue ice bidirectional reflectance	sr-1	TBD
15	albedo			clean glacier ice albedo	percent	TBD
16	albedo			dirty glacier ice albedo	percent	TBD
17	albedo			earth surface albedo	percent	Hemispherically integrated reflectance of the Earth surface in the range 0.4 - 0.7 micro-m
18	albedo			snow bidirectional reflectance	sr-1	TBD
19	cloud	atmospheric	upper-air	cloud base height	m	cloud base height (hb)
20	cloud	atmospheric	upper-air	cloud base lowest height	coded	Height above surface of the base of the lowest cloud seen (coded 0-9)
21	cloud	atmospheric	upper-air	cloud cover	Okta or percent	3D field of fraction of sky filled by clouds.
22	cloud	atmospheric	upper-air	cloud genus	Coded	Genus of cloud (0 - Cirrus to 9 - Cumulo-Nimbus)
23	cloud	atmospheric	upper-air	cloud genus base height	Coded or m	Height of base of cloud whose genus is c
24	cloud	atmospheric	upper-air	high cloud type	coded	type of high clouds (ch)
25	cloud	atmospheric	upper-air	low cloud type	coded	type of low clouds (cl)
26	cloud	atmospheric	upper-air	lowest cloud amount	Okta	low or (if low clouds don't exist) middle cloud amount

Continued on next page



Table 117 observed_variable (cont.)

variable	paramete r_group	domain	sub_domain	name	units	description
27	cloud	atmospheric	upper-air	middle cloud type	coded	type of middle clouds (cm)
28	cloud	atmospheric	upper-air	total cloud amount	Okta	total amount of clouds
29	evaporation	atmospheric		evaporation	mm	TBD
30	evaporation	atmospheric		evaporation	kg m-2 s-1	TBD
31	evaporation	atmospheric		potential evapotran- spiration	mm day-1	Quantity of water evaporated from the soil and plants when the ground is at its natural moisture content.
32	evaporation	atmospheric		real evapo- transpiration	mm day-1	TBD
33	humidity	atmospheric		absolute hu- midity	g m-3	TBD
34	humidity	atmospheric	surface; upper-air	dew point depression	K	Dew point depression is also called dew point deficit. It is the amount by which the air temperature exceeds its dew point temperature. Dew point temperature is the temperature at which a parcel of air reaches saturation upon being cooled at constant pressure and specific humidity.
36	humidity	atmospheric	surface; upper-air	dew point temperature	K	Dew point temperature is the temper- ature at which a parcel of air reaches saturation upon being cooled at constant pressure and specific humidity.
37	humidity	atmospheric	surface; upper-air	ice bulb tem- perature	K	TBD
38	humidity	atmospheric	surface; upper-air	relative hu- midity	percent	TBD

Continued on next page



Table 117 observed_variable (cont.)

variable	parameter_group	domain	sub_domain	name	units	description
39	humidity	atmospheric	surface; upper-air	specific humidity	g kg ⁻¹	specific means per unit mass. Specific humidity is the mass fraction of water vapor in (moist) air.
40	humidity	atmospheric		water vapour pressure	hPa	TBD
41	humidity	atmospheric	surface; upper-air	wet bulb temperature	K	TBD
43	ice			ice thickness	m	Thickness of the ice sheet. It is related to sea-ice elevation and ice density
44	precipitation	atmospheric		accumulated precipitation	mm	accumulated precipitation over specified period
45	precipitation	atmospheric		fresh snow	mm	TBD
46	precipitation	atmospheric		hydrometeor type	Code table	3D field of the predominant form of condensed water in a volume of free atmosphere, including liquid cloud, rain, ice crystals, snow, graupel and hail. (This variable replaces "precipitation type").
47	precipitation	atmospheric		precipitation	g m ⁻² s ⁻¹	Precipitation (liquid or solid)
48	precipitation	atmospheric		precipitation intensity	mm h ⁻¹	Precipitation intensity at surface (liquid or solid)
49	precipitation	atmospheric		precipitation intensity	mm h ⁻¹	Precipitation intensity at surface (solid)
50	precipitation	atmospheric		precipitation type	coded	Liquid, snow, hail, fog
51	precipitation	atmospheric		rainy days	Days	TBD
52	precipitation	atmospheric		snow cover	percent	Fraction of a given area which is covered by snow

Continued on next page



Table 117 observed_variable (cont.)

variable	paramete r_group	domain	sub_domain	name	units	description
53	precipitation	atmospheric		snow depth	cm	Vertical distance from the snow surface to the underlying surface (ground, glacier ice or sea ice).
54	precipitation	atmospheric		snow status	coded	Wet or dry
55	precipitation	atmospheric		snow water equivalent	mm	Surface snow amount
56	pressure	atmospheric	surface	adjunct temperature barometer	K	temperature of the adjunct thermometer to the barometer to reduce pressure to 0 degC
57	pressure	atmospheric	surface	air pressure	Pa	pressure of air column at specified height
58	pressure	atmospheric	surface	air pressure at sea level	Pa	sea level means mean sea level, which is close to the geoid in sea areas. Air pressure at sea level is the quantity often abbreviated as MSLP or PMSL.
59	pressure	atmospheric	surface	pressure tendency	Pa	pressure tendency
60	pressure	atmospheric	surface	pressure tendency characteristics	coded	characteristic of pressure tendency (used in synoptic maps)
61	radiation	atmospheric		diffuse radiation	W m-2	TBD
62	radiation	atmospheric		downward longwave irradiance at earth surface	W m-2	Flux density of radiation emitted by the gases, aerosols and clouds of the atmosphere to the Earth's surface
63	radiation	atmospheric		downward shortwave irradiance at earth surface	W m-2	Flux density of the solar radiation at the Earth surface

Continued on next page



Table 117 observed_variable (cont.)

variable	paramete r_group	domain	sub_domain	name	units	description
64	radiation	atmospheric		downward shortwave irradiance at toa	W m-2	Flux density of the solar radiation at the top of the atmosphere
65	radiation	atmospheric		earth surface shortwave bidirectional reflectance	percent	Reflectance of the Earth surface as a function of the viewing angle and the illumination angle in the range 0.4-0.7 micro m . The distribution of this variable is represented by the Bidirectional Reflectance Distribution Function (BRDF)
66	radiation	atmospheric		fraction of absorbed par	percent	Fraction of PAR absorbed by vegetation (land or marine) for photosynthesis processes (generally around the 'red')
67	radiation	atmospheric		global ra- diation	W m-2	TBD
68	radiation	atmospheric		longwave earth surface emissivity	percent	TBD
69	radiation	atmospheric		longwave radiation	W m-2	TBD
70	radiation	atmospheric		meteo- logical opti- cal range	m	Meteorological optical range at surface
71	radiation	atmospheric		photosyn- thetically ac- tive radiation	W m-2	Flux of downwelling photons of wavelength 0.4-0.7 micro m
72	radiation	atmospheric		shortwave cloud re- flectance	percent	Reflectance of the solar radiation from clouds

Continued on next page



Table 117 observed_variable (cont.)

variable	parameter_group	domain	sub_domain	name	units	description
73	radiation	atmospheric		shortwave radiation	W m-2	TBD
74	radiation	atmospheric		solar gamma ray flux	W m-2	Radiative flux integrated over the gamma-ray domain.
75	radiation	atmospheric		solar UV flux	W m-2	Integrated UV flux over the solar disk.
76	radiation	atmospheric		solar VIS flux	W m-2	Integrated VIS flux over the solar disk
77	radiation	atmospheric		solar X ray flux	W m-2	Integrated X-ray flux over the solar disk
78	radiation	atmospheric		sunshine duration	h	TBD
79	radiation	atmospheric		upward long-wave irradiance at Earth surface	W m-2	Flux density of terrestrial radiation emitted by the Earth surface
80	radiation	atmospheric		upward long-wave irradiance at TOA	W m-2	Flux density of terrestrial radiation emitted by the Earth surface and the gases, aerosols and clouds of the atmosphere at the top of the atmosphere
81	radiation	atmospheric		upward shortwave irradiance at TOA	W m-2	Flux density of solar radiation, reflected by the Earth surface and atmosphere, emitted to space at the top of the atmosphere
82	radiation	atmospheric		upward spectral radiance at TOA	W m-2 nm-1 sr-1	Upward radiant power measured at the top of the atmosphere per area unit, per solid angle, and per wavelength interval. Spectral range 0.2-200 micro m.
83	salinity	oceanic	surface; subsurface	salinity	psu	ocean salinity (PSU)

Continued on next page



Table 117 observed_variable (cont.)

variable	parameter_group	domain	sub_domain	name	units	description
85	temperature	atmospheric	surface; upper-air	air temperature	K	Air temperature is the bulk temperature of the air, not the surface (skin) temperature.
86	temperature	atmospheric		daily maximum air temperature	K	TBD
87	temperature	atmospheric		daily maximum air temperature with direct sun exposure	K	TBD
88	temperature	atmospheric		daily maximum grass temperature	K	Grass maximum thermometer is 5 cm above ground
89	temperature	atmospheric		daily minimum air temperature	K	TBD
90	temperature	atmospheric		daily minimum air temperature with direct sun exposure	K	TBD
91	temperature	atmospheric		daily minimum grass temperature	K	Grass minimum thermometer is 5 cm above ground
92	temperature	atmospheric		days with ground frost	Days	TBD
93	temperature	atmospheric		snow temperature	K	TBD

Continued on next page



Table 117 observed_variable (cont.)

variable	parameter_group	domain	sub_domain	name	units	description
94	temperature	atmospheric		soil temperature	K	Lot 1 is using Ts - WMO abbrev.
95	temperature	oceanic	surface; sub-surface	water temperature	K	Water (sea, river, lake) temperature at depth indicated
96	visibility	atmospheric	surface	horizontal visibility in air	m	The visibility is the distance at which something can be seen.
97	weather			lightning detection	deg (lat, lon) and UTC	Detection of the time and location (latitude, longitude) of lightning events. Accuracy expressed in terms of Hit Rate and False Alarm Rate, which requires predetermination of a specific distance and time tolerance.
98	weather			lightning duration	s	TBD
99	weather			lightning horizontal distance	Km	TBD
100	weather	atmospheric	surface	past weather 1	coded	past weather 1 - most extreme phenomenon (w)
101	weather	atmospheric	surface	past weather 2	coded	past weather 2 - most frequent phenomenon (used in synoptic maps)
102	weather	atmospheric	surface	present weather	coded	present weather (ww)
103	weather			Total lightning density	Dimensionless	Total number of detected flashes in the corresponding time interval and the space unit. The space unit (grid box) should be equal to the horizontal resolution and the accumulation time to the observing cycle

Continued on next page



Table 117 observed_variable (cont.)

variable	paramete r_group	domain	sub_domain	name	units	description
104	wind	atmospheric	surface; upper-air	eastward wind speed	m s-1	Eastward indicates a vector component which is positive when directed eastward (negative westward). Wind is defined as a two-dimensional (horizontal) air velocity vector, with no vertical component. (Vertical motion in the atmosphere has the standard name upward air velocity.)
105	wind	atmospheric	surface; upper-air	northward wind speed	m s-1	Northward indicates a vector component which is positive when directed northward (negative southward). Wind is defined as a two-dimensional (horizontal) air velocity vector, with no vertical component. (Vertical motion in the atmosphere has the standard name upward air velocity.)
106	wind	atmospheric	surface; upper-air	wind from direction	degree	direction from which the wind is blowing Lot 1 uses dd - WMO abbrev.
107	wind	atmospheric	surface; upper-air	wind speed	m s-1	Speed is the magnitude of velocity. Wind is defined as a two-dimensional (horizontal) air velocity vector, with no vertical component. (Vertical motion in the atmosphere has the standard name upward air velocity.) The wind speed is the magnitude of the wind velocity. Lot 1 uses ff - WMO abbrev.

Continued on next page



Table 117 observed_variable (cont.)

variable	paramete r_group	domain	sub_domain	name	units	description
108	wind	atmospheric	surface	wind speed of gust	m s-1	Speed is the magnitude of velocity. Wind is defined as a two-dimensional (horizontal) air velocity vector, with no vertical component. (Vertical motion in the atmosphere has the standard name upward air velocity.) The wind speed is the magnitude of the wind velocity. A gust is a sudden brief period of high wind speed. In an observed timeseries of wind speed, the gust wind speed can be indicated by a cell methods of maximum for the time-interval. In an atmospheric model which has a parametrised calculation of gustiness, the gust wind speed may be separately diagnosed from the wind speed. Lot 1 uses fx - WMO abbrev.
109	wind	atmospheric		wind speed max	m s-1	Maximum observed wind speed over specified period Lot 1 uses fm - WMO abbrev.
110				turbulence	J m-3	TBD
110				turbulence	J m-3	TBD
111				precipitable water col- umn	kg m-2	TBD
112				tropopause height	m	TBD
113				tropopause temperature	K	TBD
114				tropopause pressure	Pa	TBD

Continued on next page



Table 117 observed_variable (cont.)

variable	paramete r_group	domain	sub_domain	name	units	description
115				tropopause potential temperature	K	TBD
116				frost point temperature	K	TBD
End of table						



Table 118: observing_frequency codes

frequency	description
0	One observation per day (24 hour intervals).
1	Two observations per day (12 hour intervals).
2	Four observations per day (6 hour intervals).
3	Eight observations per day (3 hour intervals).
4	Hourly observations.
5	Irregular observations.

End of table

Table 119: observing_method codes

method	description
0	Measured
1	Estimated
2	Computed

End of table

Table 120: observing_programme codes

observing_programme	abbreviation	description	sponsor
1	AMDAR	Global Aircraft Meteorological Data Relay	WMO/GOS
2	EPA	Environmental Protection Agency	NA
3	EUMETNET	Grouping of European National Meteorological Services	WMO/GOS
4	WMO/GAW	World Meteorological Organization/Global Atmospheric Watch	NA
5	GCOS	Global Climate Observing System	NA
6	GCW	Global Cryosphere Watch	NA

Continued on next page



Table 120 observing_programme (cont.)

observing_programme	abbreviation	description	sponsor
7	GOOS	Global Ocean Observing System	NA
8	IPA	International Permafrost Association	NA
9	JCOMM	Joint Technical Commission for Oceanography and Marine Meteorology	WMO/GOS
10	WMO/GOS	World Meteorological Organization/Global Observing System	NA
11	GTOS	Global Terrestrial Observing System	NA
12	IAGOS	In-service Aircraft for a Global Observing System	NA
13	WHYCOS	World Hydrological Cycle Observing System	NA
14	WMO/CLW	World Meteorological Office/Climate and Water Department	NA
15	ADNET	Asian dust and aerosol lidar observation network	GALION ; WMO/GAW
16	Aeronet	AEROSOL ROBOTIC NETWORK	NASA?
17	ANTON	Antarctic Observing Network	WMO/GOS
18	ASAP	Automated Ship-board Aerological Program	WMO/GOS
19	BSRN	Baseline Surface Radiation Network	WMO/GAW & GCOS

Continued on next page



Table 120 observing_programme (cont.)

observing_programme	abbreviation	description	sponsor
20	CASTNET	Clean Air Status and Trends Network	(National - USA)
21	CIS-LiNet	Lidar network for monitoring atmosphere over CIS regions	GALION ; WMO/GAW
22	CLN	CREST Lidar Network	GALION ; WMO/GAW
23	DART	Deep-ocean Assessment and Reporting of Tsunamis	NOAA Centre for Tsunamis Research
24	E-AMДАР	European - Aircraft Meteorological Data Relay	EUMETNET ; WMO/GOS
25	E-ASAP	European - Automated Ship-board Aerological Program	EUMETNET ; WMO/GOS
26	E-GVAP	European - GNSS water vapour programme	EUMETNET ; WMO/GOS
27	E-PROFILE	European - wind profiles from radar	EUMETNET ; WMO/GOS
28	E-SURFMAR	European - Surface Marine Operational Service	EUMETNET ; WMO/GOS
29	EARLINET	European Aerosol Research Lidar Network	GALION ; WMO/GAW
30	GALION	GAW Aerosol Lidar Observation Network	WMO/GAW
31	GAW-PFR	GAW-Precision Filter Radiometers	WMO/GAW
32	German AOD Network	German Aerosol Optical Depth Network	WMO/GAW

Continued on next page



Table 120 observing_programme (cont.)

observing_programme	abbreviation	description	sponsor
33	GLOSS	Global Sea Level Observing System	JCOMM ; WMO/GOS
34	GRUAN	GCOS Reference Upper Air Network	GCOS
35	GSN	GCOS Surface Network	GCOS
36	GTN-G	Global Terrestrial Network - Glaciers	GCOS
37	GTN-H	Global Terrestrial Network - Hydrology	WMO/CLW ; GCOS ; GTOS
38	GTN-P	Global Terrestrial Network - Permafrost	IPA ; GCOS ; GTOS
39	GUAN	GCOS Upper Air Network	GCOS
40	IAGOS-MOZAIC	Measurement of Ozone and Water Vapour on Airbus in-service Aircraft	IAGOS
41	LALINET	Latin America Lidar Network	GALION; WMO/GAW
42	MPLNET	Micro Pulse Lidar Network	GALION; WMO/GAW
43	NDACC	Network for the Detection of Atmospheric Composition Change	GALION; WMO/GAW
44	OPERA	European Weather Radar Project	EUMETNET; (WMO/GOS)
45	PIRATA	Prediction and Research Moored Array in the Atlantic	GOOS; WMO/GOS
46	PolarAOD	Polar Aerosol Optical Depth Measurement Network Project	WMO/GAW

Continued on next page



Table 120 observing_programme (cont.)

observing_programme	abbreviation	description	sponsor
47	RAMA	Research Moored Array for African-Asian-Australian Monsoon Analysis and Prediction	NOAA
48	RBCN	Regional Basic Climatological Network	WMO/GOS
49	RBON	Regional Basic Observing Network	WMO/GOS
50	RBSN	Regional Basic Synoptic Network	WMO/GOS
51	TAO	Tropical Atmosphere and Ocean Array	NOAA; GCOS
52	SKYNET	Aerosol -cloud-radiation interaction in the atmosphere project	WMO/GAW
53	SibRad	NA	WMO/GAW
54	SOOP	Ship of Opportunity	JCOMM ; WMO/GOS
55	U.S. IOOS	United States Integrated Ocean Observing System	(National - USA)
56	VOS	Voluntary Observing Fleet	JCOMM ; WMO/GOS
57	VOSCLIM	Voluntary Observing Fleet (VOS) Climate Project	JCOMM ; WMO/GOS
58	WRAP	Worldwide Recurring ASAP Project	JCOMM ; WMO/GOS

End of table

Table 121: platform_sub_type codes

sub_type	platform_type	abbreviation	description
0	2	BA	Barge
1	2	BC	Bulk Carrier

Continued on next page



Table 121 platform_sub_type (cont.)

sub_type	platform_type	abbreviation	description
2	2	CA	Cable ship
3	2	CG	Coast Guard Ship
4	2	CS	Container Ship
5	2	DR	Dredger
6	2	FE	Passenger ferries
7	2	FP	Floating production and storage units
8	2	FV	Other Fishing Vessel
9	2	GC	General Cargo
10	2	GT	Gas Tanker
11	2	IC	Icebreaking vessel
12	2	IF	Inshore Fishing Vessel
13	2	LC	Livestock carrier
14	2	LT	Liquid Tanker
15	2	LV	Light Vessel
16	2	MI	Mobile installation including mobile offshore drill ships, jack-up rigs and semi-submersibles
17	2	MS	Military Ship
18	2	OT	Other
19	2	MW	Ocean Weather Ship
20	2	PI	Pipe layer
21	2	PS	Passenger ships and cruise liners
22	2	RF	Ro/Ro Ferry
23	2	RR	Ro/Ro Cargo
24	2	RS	Refrigerated cargo ships including banana ships
25	2	RV	Research Vessel
26	2	SA	Large sailing vessels
27	2	SV	Support Vessel
28	2	TR	Trawler
29	2	TU	Tug
30	2	VC	Vehicle carriers
31	2	YA	Yacht / Pleasure Craft
32	2	BA	Barges, including crane barges and tank barges.
33	2	BC	Bulk Carriers, including Ore/Bulk/Oil (OBO) carriers and Ore/Oil carriers.
34	2	CA	Cable ships.
35	2	CG	Coastguard cutters, patrol ships and launches.

Continued on next page



Table 121 platform_sub_type (cont.)

sub_type	platform_type	abbreviation	description
36	2	CS	Container ships, including open and closed container ships and refrigerated container ships.
37	2	DR	Dredgers including bucket, hopper, grab and suction dredgers.
38	2	FE	Passenger ferries (carrying passengers only).
39	2	FP	Floating Production and Storage Units.
40	2	FV	Fishing Vessels including purse seiners, long liners etc., but excluding trawlers.
41	2	GC	General Cargo ships with one or more holds.
42	2	GT	Liquefied gas carriers/tankers including LNG and LPG carriers.
43	2	IC	Icebreaking vessels (dedicated vessel). If the vessel fits in another category and is ice strengthened
44	2	LC	Livestock Carrier (dedicated ship for the carriage of livestock).
45	2	LT	Liquid tankers including oil product tankers, chemical tankers and crude oil tankers (including VLCC's and ULCC's).
46	2	LV	Light vessels.
47	2	MI	Mobile installations, including mobile offshore drill ships, jack-up rigs, semi-submersibles.
48	2	MS	Military ships.
49	2	OW	Ocean Weather Ships (dedicated weather ship).
50	2	PI	Pipe Layers.
51	2	PS	Passenger ships and Cruise liners.
52	2	RF	Ro Ro ferries (carrying passengers and laden vehicles).
53	2	RR	Ro Ro cargo ships for carriage of road and/or rail vehicles and cargo, including containerised cargo.
54	2	RS	Refrigerated cargo ships including banana ships.
55	2	RV	Research Vessels, including oceanographic, meteorological and hydrographic research ships and seismographic research ships.

Continued on next page



Table 121 platform_sub_type (cont.)

sub_type	platform_type	abbreviation	description
56	2	SA	Large sailing vessels, including sail training vessels.
57	2	SV	Support vessels including offshore support vessels, offshore supply vessels, stand-by vessels, pipe carriers, anchor handling vessels, buoy tenders (including coastguard vessels engaged solely on buoy tending duties), diving support vessels, etc.
58	2	TR	Trawler fishing vessels.
59	2	TU	Tugs, including fire-fighting tugs, salvage tugs, pusher tugs, pilot vessels, tenders etc.
60	2	VC	Vehicle Carriers: dedicated multi deck ships for the carriage of new unladen road vehicles.
61	2	YA	Yachts and pleasure craft.
62	2	OT	Other (specify in footnote).
63	0		Synoptic network
64	7		Local Network
65	2		Ocean Weather Ship (on station)
66	2		Ocean Weather Ship (off station)
67	43		Other
68	43		Coastal-Marine Automated Network (C-MAN) (NDBC operated)
69	5		Unspecified drifting buoy
70	5		Standard Lagrangian drifter (Global Drifter Programme)
71	5		Standard FGGE type drifting buoy (non-Lagrangian meteorological drifting buoy)
72	5		Wind measuring FGGE type drifting buoy (non-Lagrangian meteorological drifting buoy)
73	6		Ice drifter
74	5		SVPG Standard Lagrangian drifter with GPS
75	5		SVP-HR drifter with high-resolution temperature or thermistor string
76	37		Unspecified subsurface float
77	36		SOFAR
78	36		ALACE
79	36		MARVOR
80	36		RAFOS
81	36		PROVOR

Continued on next page



Table 121 platform_sub_type (cont.)

sub_type	platform_type	abbreviation	description
82	36		SOLO
83	36		APEX
84	4		Unspecified moored buoy
85	4		Nomad
86	4		3-metre discus
87	4		10-12-metre discus
88	4		ODAS 30 series
89	4		ATLAS (e.g. TAO area)
90	4		TRITON buoy
91	4		FLEX mooring (e.g. TIP area)
92	4		Omnidirectional waverider
93	4		Directional waverider
94	36		Subsurface ARGO float
95	36		PALACE
96	36		NEMO
97	36		NINJA
98	6		Ice buoy/float (POPS or ITP)
99	4		Mooring oceanographic
100	4		Mooring meteorological
101	4		Mooring multidisciplinary (OceanSITES)
102	4		Mooring tide gauge or tsunami buoy
103	6		Ice beacon
104	6		Ice mass balance buoy

End of table

Table 122: platform_type codes

type	description
0	Land station (synoptic network)
1	Shallow water station (fixed to sea / lake floor)
2	Ship
3	Rig / platform
4	Moored buoy
5	Drifting buoy (of drifter)
6	Ice buoy
7	Land station (local network)
8	Land vehicle
9	Autonomous marine vehicle
32	Ice station

Continued on next page



Table 122 platform_type (cont.)

type	description
33	Lightship
34	Mechanical / digital / micro bathythermograph (MBT)
35	Oceanographic station data (bottle and low resolution CTD / XCTD data)
36	Profiling float
37	Subsurface float (moving)
38	Tide gauge
39	Underwater platform
40	Undulating oceanographic recorder
41	Aircraft
42	Autonomous pinneped bathythermograph
43	Coastal / Island
44	Expendable bathythermograph (XBT)
45	Glider
46	High-resolution Conductivity-Temperature-Depth (CTD) / Expendable CTD(XCTD)

End of table

Table 123: processing_code codes

index	processing_code	abbreviation	description
TBD	TBD	TBD	TBD

End of table

Table 124: processing_level codes

level	name	description
0	Unknown	NA
1	Raw	NA
2	Level 0	Analogue/digital electric signals

Continued on next page



Table 124 processing_level (cont.)

level	name	description
3	Level I	Level I data (Primary Data): in general, are instrument readings expressed in appropriate physical units, and referred to Earth geographical coordinates. They require conversion to the normal meteorological variables (identified in Part I, Chapter 1). Level I data themselves are in many cases obtained from the processing of electrical signals such as voltages, referred to as raw data. Examples of these data are satellite radiances and water-vapour pressure, positions of constant-level balloons, etc. but not raw telemetry signals. Level I data still require conversion to the meteorological parameters specified in the data requirements.
4	Level II	Level II Data (Meteorological parameters). They may be obtained directly from many kinds of simple instruments, or derived from Level I data. For example, a sensor cannot measure visibility, which is a Level II quantity; instead, sensors measure the extinction coefficient, which is a Level I quantity.
5	Level III	Level III (Initial state parameters) are internally consistent data sets, generally in gridpoint form obtained from level II data by applying established initialization procedures. NOTE: Data exchanged internationally are level II or level III data.
6	Level IV	NA

End of table

Table 125: product_level codes

level	description
TBD	TBD

End of table



Table 126: product_status codes

status	description	extended_description
TBD	TBD	TBD

End of table



Table 127: profile_configuration_codes codes

field_id	field_name	code_value	abbreviation	description	start_date	end_date
0	include descent	0	NA	Descent excluded	NA	NA
0	include descent	1	NA	Descent included	NA	NA
1	processing code	0	cc	Calibration correction (of humidity sensors)	NA	NA
1	processing code	1	HRC	Humidity radiation correction	NA	NA
1	processing code	2	or	Outlier removal (remove temperature spikes)	NA	NA
1	processing code	3	pGPS	Combination of pressure and GPS	NA	NA
1	processing code	4	TL	Time-lag correction	NA	NA
1	processing code	5	TRC	Temperature radiation correction	NA	NA
B002003	type of measuring equipment used	0 - 15	NA	See BUFR table 0 02 003	NA	NA

Continued on next page



Table 127 profile_configuration_codes (cont.)

field_id	field_name	code_value	abbreviation	description	start_date	end_date
B002011	radiosonde sounding system	0 - 255	NA	See BUFR table 0 02 011	NA	NA
B002013	solar and infrared radiation correction	0 - 15	NA	See BUFR table 0 02 013	NA	NA
B002014	tracking technique	0 - 127	NA	See BUFR table 0 02 014	NA	NA
B002015	radiosonde completeness	0 - 15	NA	See BUFR table 0 02 015	NA	NA
B002017	humidity correction algorithm	0 - 31	NA	See BUFR table 0 02 017	NA	NA
B002066	radiosonde ground receiving system	0 - 63	NA	See BUFR table 0 02 066	NA	NA
B002080	balloon manufacturer	0 - 63	NA	See BUFR table 0 02 080	NA	NA
B002081	balloon type	0 - 31	NA	See BUFR table 0 02 081	NA	NA
B002083	type of balloon shelter	NA	NA	See BUFR table 0 02 083	NA	NA
B002084	type of gas used in balloon	NA	NA	See BUFR table 0 02 084	NA	NA
B002095	type of pressure sensor	0 - 31	NA	See BUFR table 0 02 095	NA	NA

Continued on next page



Table 127 profile_configuration_codes (cont.)

field_id	field_name	code_value	abbreviation	description	start_date	end_date
B002191	geopotential height calculation	0 - 15	NA	See BUFR table 0 02 191	NA	NA
B003011	method of depth calculation	0 - 3	NA	See BUFR table 0 03 011	NA	NA
B022056	profile direction	0 - 3	NA	See BUFR table 0 22 056	NA	NA
B022067	instrument type for water temperature salinity profile	0 - 1023	NA	See BUFR table 0 22 067	NA	NA
B022068	water temperature recorder type	0 - 127	NA	See BUFR table 0 22 068	NA	NA
B022178	XBT launcher type	0 - 255	NA	See BUFR table 0 22 178	NA	NA
B035035	reason for termination	0 - 31	NA	See BUFR table 0 35 035	NA	NA
End of table						



Table 128: profile_configuration_fields codes

field_id	field_name	type	description
0	include descent	int (fk)	See profile_configuration_codes
1	processing code	int (fk)	See profile_configuration_codes
2	unwinder type	varchar	NA
3	burstpoint altitude	numeric	NA
4	burstpoint pressure	numeric	NA
5	filling weight	numeric	NA
6	gross weight	numeric	NA
7	payload	numeric	NA
8	unwinder length	numeric	NA
9	ascent rate	numeric	Rate of ascent / descent for profile (+ve values indicate ascent, -ve descent)(m/s)
B002016	radiosonde configuration	int (fk)	See profile_configuration_codes
B002003	type of measuring equipment used	int (fk)	See profile_configuration_codes
B002011	radiosonde sounding system	int (fk)	See profile_configuration_codes
B002011	radiosonde type	int (fk)	See profile_configuration_codes
B002013	solar and infrared radiation correction	int (fk)	See profile_configuration_codes
B002014	tracking technique	int (fk)	See profile_configuration_codes
B002015	radiosonde completeness	int (fk)	See profile_configuration_codes
B002017	humidity correction algorithm	int (fk)	See profile_configuration_codes
B002066	radiosonde ground receiving system	int (fk)	See profile_configuration_codes
B002080	balloon manufacturer	int (fk)	See profile_configuration_codes
B002081	balloon type	int (fk)	See profile_configuration_codes
B002083	type of balloon shelter	int (fk)	See profile_configuration_codes
B002084	type of gas used in balloon	int (fk)	See profile_configuration_codes
B002095	type of pressure sensor	int (fk)	See profile_configuration_codes

Continued on next page



Table 128 profile_configuration_fields (cont.)

field_id	field_name	type	description
B002191	geopotential height calculation	int (fk)	See profile_configuration_codes
B003011	method of depth calculation	int (fk)	See profile_configuration_codes
B022056	profile direction	int (fk)	See profile_configuration_codes
B022067	instrument type for water temperature salinity profile	int (fk)	See profile_configuration_codes
B022068	water temperature profile recorder type	int (fk)	See profile_configuration_codes
B022178	XBT launcher type	int (fk)	See profile_configuration_codes
B035035	reason for termination	int (fk)	See profile_configuration_codes

End of table

Table 129: profile_type codes

type	description
0	Atmospheric
1	Oceanographic
2	Soil
3	Snow

End of table

Table 130: qc_method codes

method	description	reference
TBD	TBD	TBD

End of table

Table 131: quality_flag codes

flag	description
0	Good
1	Inconsistent
2	Doubtful
3	Wrong

Continued on next page



Table 131 quality_flag (cont.)

flag	description
4	Not checked
5	Has been changed
6	Estimated
7	Missing value

End of table

Table 132: region codes

region	WMO_region	description
0	NA	Reserved
1	1	Africa
2	2	Asia
3	3	South America
4	4	North America, Central America, Caribbean
5	5	South-West Pacific
6	6	Europe
7	7	Antarctica

End of table

Table 133: report_processing_codes codes

code	abbreviation	description
TBD	TBD	TBD

End of table

Table 134: report_processing_level codes

level	abbreviation	description
TBD	TBD	TBD

End of table

Table 135: report_type codes

type	abbreviation	description
TBD	TBD	TBD

End of table



Table 136: role codes

role	description
TBD	TBD

End of table

Table 137: sampling_strategy codes

strategy	name	description
1	Continuous	Sampling is done continuously, but not necessarily at regular time intervals. Sampling is integrating, i.e., none of the medium escapes observations.
2	Discrete	Sampling is done at regular time intervals for certain sampling periods that are smaller than the time interval. Sampling is not integrating, i.e., parts of the medium escape observation.
3	Event	Sampling is done at irregular time intervals.

End of table

Table 138: sea_level_datum codes

datum	description
0	Earth Gravitational Model 1996
1	Baltic height system 1977

End of table



Table 139: secondary_variable codes

variable	variable_name	value	symbol	description
0	atmospheric con-stituent	0	BrO	Bromine monoxide
0	atmospheric con-stituent	1	C10H16	3-Carene
0	atmospheric con-stituent	2	C10H16	Alpha pinene
0	atmospheric con-stituent	3	C10H16	Beta pinene
0	atmospheric con-stituent	4	C10H16	Limonene
0	atmospheric con-stituent	5	C2H2	Ethyne (Acetylene)
0	atmospheric con-stituent	6	C2H5OH	Ethanol
0	atmospheric con-stituent	7	C2H6	Propene
0	atmospheric con-stituent	8	C2H6S	Ethanethiol
0	atmospheric con-stituent	9	C3H6O	Acetone
0	atmospheric con-stituent	10	C4H10	Methylpropane
0	atmospheric con-stituent	11	C4H10	n-butane
0	atmospheric con-stituent	12	C5H12	2-Methylbutane
0	atmospheric con-stituent	13	C5H12	n-Pentane

Continued on next page



Table 139 secondary_variable (cont.)

variable	variable_name	value	symbol	description
0	atmospheric con-stituent	14	C5H8	Isoprene
0	atmospheric con-stituent	15	C6H6	Benzene
0	atmospheric con-stituent	16	C7H8	Toluene
0	atmospheric con-stituent	17	CFC-11	CFC-11
0	atmospheric con-stituent	18	CFC-12	CFC-12
0	atmospheric con-stituent	19	CH3CN	Acetonitrile
0	atmospheric con-stituent	20	CH3OH	Methanol
0	atmospheric con-stituent	21	CH4	Methane
0	atmospheric con-stituent	22	ClO	Chlorine monoxide
0	atmospheric con-stituent	23	ClONO2	Chlorine nitrate
0	atmospheric con-stituent	24	CO	Carbon monoxide
0	atmospheric con-stituent	25	CO2	Carbon dioxide
0	atmospheric con-stituent	26	COS	Carbonyl sulfide
0	atmospheric con-stituent	27	H2O	Water vapour
0	atmospheric con-stituent	28	HCHO	Formaldehyde

Continued on next page

Table 139 secondary_variable (cont.)

variable	variable_name	value	symbol	description
0	atmospheric con-stituent	29	HCHO	Formaldehyde (Total Column)
0	atmospheric con-stituent	30	HCl	Hydrogen chloride
0	atmospheric con-stituent	31	HDO	???
0	atmospheric con-stituent	32	HNO3	Nitric acid
0	atmospheric con-stituent	33	N2O	Nitrous oxide
0	atmospheric con-stituent	34	N2O5	Dinitrogen pentoxide
0	atmospheric con-stituent	35	NO	Nitrogen monoxide
0	atmospheric con-stituent	36	NO2	Nitrogen dioxide
0	atmospheric con-stituent	37	NO2	Nitrogen dioxide (Total column)
0	atmospheric con-stituent	38	O3	Ozone
0	atmospheric con-stituent	39	O3	Ozone (Total column)
0	atmospheric con-stituent	40	OH	???
0	atmospheric con-stituent	41	PAN	???
0	atmospheric con-stituent	42	PSC occurrence	???
0	atmospheric con-stituent	43	SF6	Sulphur hexafluoride

Continued on next page



Table 139 secondary_variable (cont.)

variable	variable_name	value	symbol	description
0	atmospheric con-stituent	44	SO2	Sulphur dioxide
0	atmospheric con-stituent	45	SO2	Sulphur dioxide (Total column)
End of table				



Table 140: sensor_configuration_codes codes

field_id	field_name	parameter	code_value	abbreviation	description
B002033	sensor type - salinity	salinity	0 - 7		See BUFR table 0 02 033
B002038	sensor type - water tem- perature	water tem- perature	0 - 15		See BUFR table 0 02 038
B002038	sensor type - water tem- perature	water tem- perature	16		Bait tanks thermometer.
B002038	sensor type - water tem- perature	water tem- perature	17		electronic sensor
B002038	sensor type - water tem- perature	water tem- perature	18		implied bucket [note: applicable to early ICOADS data]
B002038	sensor type - water tem- perature	water tem- perature	19		Radiation thermometer.
B002038	sensor type - water tem- perature	water tem- perature	20		Through Hull sensor.
B002038	sensor type - water tem- perature	water tem- perature	21		Trailing thermistor
B002038	sensor type - water tem- perature	water tem- perature	22		unknown or non-bucket
B002051	sensor type - extremes	air temperature	0 - 15		See BUFR table 0 02 051

Continued on next page



Table 140 sensor_configuration_codes (cont.)

field_id	field_name	parameter	code_value	abbreviation	description
B002096	sensor type - air temperature	air temperature	0		See BUFR table 0 02 096
B002097	sensor type - humidity	humidity	0 - 31		See BUFR table 0 02 097
B002169	sensor type - wind speed	wind speed	0 - 15		See BUFR table 0 02 169
B002169	sensor type - wind speed	wind speed	16		Anemograph.
B002169	sensor type - wind speed	wind speed	17		Anemometer - type unspecified
B002169	sensor type - wind speed	wind speed	18		Beaufort force
B002169	sensor type - wind speed	wind speed	19		Cup anemometer and wind vane (combined unit).
B002169	sensor type - wind speed	wind speed	20		Cup anemometer and wind vane (separate instruments).
B002169	sensor type - wind speed	wind speed	21		Handheld anemometer.
B002169	sensor type - wind speed	wind speed	22		Other (specify in footnote).
B002169	sensor type - wind speed	wind speed	23		Propeller vane.
B002185	sensor type - evaporation	evaporation	0 - 15		See BUFR table 0 02 185
B003003	sensor housing - type	all	0 - 15		See BUFR table 0 03 003
B003004	sensor housing - radiation shielding	all	0 - 15		See BUFR table 0 03 004

Continued on next page



Table 140 sensor_configuration_codes (cont.)

field_id	field_name	parameter	code_value	abbreviation	description
B003008	sensor housing - ventilation	all	0 - 7		See BUFR table 0 03 008
B003020	sensor housing - material	all	0 - 7		See BUFR table 0 03 020
B003021	sensor housing - heating	all	0 - 4		See BUFR table 0 03 021
B003022	sensor owner	all	0 - 7		See BUFR table 0 03 022
B003023	sensor housing - configuration	all	0 - 7		See BUFR table 0 03 023
BARG	sensor type - barograph	pressure trend	0		Open Scale barograph with 1 day clock.
BARG	sensor type - barograph	pressure trend	1		Open Scale barograph with 2 day clock.
BARG	sensor type - barograph	pressure trend	2		Open Scale barograph with 3 day clock.
BARG	sensor type - barograph	pressure trend	3		Open Scale barograph with 4 day clock.
BARG	sensor type - barograph	pressure trend	4		Open Scale barograph with 5 day clock.
BARG	sensor type - barograph	pressure trend	5		Open Scale barograph with 6 day clock.
BARG	sensor type - barograph	pressure trend	6		Open Scale barograph with 7 day clock.
BARG	sensor type - barograph	pressure trend	7		Open Scale barograph with 8 day clock.
BARG	sensor type - barograph	pressure trend	8		Open Scale barograph with 9 day clock.
BARG	sensor type - barograph	pressure trend	9		Open Scale barograph.

Continued on next page



Table 140 sensor_configuration_codes (cont.)

field_id	field_name	parameter	code_value	abbreviation	description
BARG	sensor type - barograph	pressure trend	10		Other (specify in footnote).
BARG	sensor type - barograph	pressure trend	11		Small Scale barograph.
BARG	sensor type - barograph	pressure trend	12		Tendency obtained from an electronic digital barometer.
BARM	sensor type - barometer	pressure	0		Aneroid barometer (issued by the PMO or a NMS).
BARM	sensor type - barometer	pressure	1		Digital aneroid barometer (aka Precision Aneroid Barometer).
BARM	sensor type - barometer	pressure	2		Electronic digital barometer (consisting of one or more pressure transducers).
BARM	sensor type - barometer	pressure	3		Mercury barometer.
BARM	sensor type - barometer	pressure	4		Other
BARM	sensor type - barometer	pressure	5		Ship's aneroid barometer.
IBS	ice bulb status	humidity	0		Ice bulb
IBS	ice bulb status	humidity	1		Wet bulb
MANU	manufacturer	all	0		Vaisala
SLOC	sensor location - ship	all	0		Aft mast.
SLOC	sensor location - ship	all	1		Bridge wing
SLOC	sensor location - ship	all	2		Foremast yardarm
SLOC	sensor location - ship	all	3		Foremast.

Continued on next page



Table 140 sensor_configuration_codes (cont.)

field_id	field_name	parameter	code_value	abbreviation	description
SLOC	sensor location - ship	all	4		Handheld.
SLOC	sensor location - ship	all	5		Main deck
SLOC	sensor location - ship	all	6		Mainmast yardarm
SLOC	sensor location - ship	all	7		Mainmast.
SLOC	sensor location - ship	all	8		Mast on wheelhouse top yardarm
SLOC	sensor location - ship	all	9		Mast on wheelhouse top.
SLOC	sensor location - ship	all	10		Meteorological mast.
SLOC	sensor location - ship	all	11		Not fitted.
SLOC	sensor location - ship	all	12		Other
SLOC	sensor location - ship	all	13		Pressurised wheelhouse (closed and not vented to the outside).
SLOC	sensor location - ship	all	14		Wheelhouse
SLOC	sensor location - ship	all	15		Wheelhouse, not pressurised (vented to the outside).
SRR	sensor type - precipitation	precipitation	NA		Place holder
SSIDE	sensor side - ship	all	0		Center
SSIDE	sensor side - ship	all	1		Port

Continued on next page



Table 140 sensor_configuration_codes (cont.)

field_id	field_name	parameter	code_value	abbreviation	description
SSIDE	sensor side - ship	all	2		Starboard
SSIDE	sensor side - ship	all	3		Windward side
SWV	sensor type - waves	waves	0		buoy
SWV	sensor type - waves	waves	1		other
SWV	sensor type - waves	waves	2		shipborne wave recorder
SWW	sensor type - present weather	present weather	0		Automatic, included (using WMO Codes 4677 and 4561)
SWW	sensor type - present weather	present weather	1		Automatic, included (using WMO codes 4680 and 4531)
SWW	sensor type - present weather	present weather	2		Automatic, omitted (no observa- tion, data not available)
SWW	sensor type - present weather	present weather	3		Automatic, omitted (no significant phenomenon to report)
SWW	sensor type - present weather	present weather	4		Manned, included
SWW	sensor type - present weather	present weather	5		Manned, omitted (no observa- tion, data not available)

Continued on next page



Table 140 sensor_configuration_codes (cont.)

field_id	field_name	parameter	code_value	abbreviation	description
SWW	sensor type - present weather	present weather	6		Manned, omitted (no significant phenomenon to report)
TSONDE	telem- try_sonde	sonde	TBD		TBD
STREAT	sample treat- ment	all	TBD		TBD
SPROC	sample pro- cedure	all	TBD		TBD
QCPROC	quality control procedure	all	TBD		TBD
CALMETH	Calibration method	all	TBD		TBD
End of table					



Table 141: sensor_configuration_fields codes

field_id	field_name	parameter	type	description
SACC	sensor accuracy	all	numeric	Reported accuracy (trueness) of sensor in units of measurement.
SPRE	sensor precision	all	numeric	Reported precision (repeatability) of sensor in units of measurement
B002033	sensor type - salinity	salinity	int (fk)	NA
B002038	sensor type - water temperature	water temperature	int (fk)	NA
B002051	sensor type - air temperature extremes	air temperature	int (fk)	NA
B002096	sensor type - air temperature	air temperature	int (fk)	NA
B002097	sensor type - humidity	humidity	int (fk)	NA
B002169	sensor type - wind speed	wind speed	int (fk)	NA
B002185	sensor type - evaporation	evaporation	int (fk)	NA
B003003	sensor housing - type	all	int (fk)	NA
B003004	sensor housing - radiation shielding	all	int (fk)	NA
B003008	sensor housing - ventilation	all	int (fk)	NA
B003020	sensor housing - material	all	int (fk)	NA
B003021	sensor housing - heating	all	int (fk)	NA
B003022	sensor owner	all	int (fk)	NA

Continued on next page



Table 141 sensor_configuration_fields (cont.)

field_id	field_name	parameter	type	description
B003023	sensor housing - configuration	all	int (fk)	NA
BARG	sensor type - barograph	pressure trend	int (fk)	NA
BARM	sensor type - barometer	pressure	int (fk)	NA
CALINT	calibration interval	all	numeric	Maximum number of months recommended between calibrations.
CALMETH	calibration method	all	int (fk)	Method used to calibrate instrument
CALREF	calibration reference	all	varchar	Reference instrument (make, model and serial number) used to perform calibration
CALDEV	calibration chamber	all	varchar	Calibration chamber (or device) used to perform the calibration
CALPRTY	calibration party	all	varchar	Who performed the calibration
CALRES	calibration result	all	varchar	Result of the calibration
CALCERT	calibration certificate	all	varchar	Certificate number of calibration certificate
FREQ	sampling frequency	all	numeric	time period (s) between successive measurements from sensor
IBS	ice bulb status	humidity	int (fk)	NA
LDCL	sensor location - distance from center line	wind speed	numeric	NA
LDFB	sensor location - distance from bow	wind speed	numeric	NA
LHAD	sensor location - height above deck	wind speed	numeric	NA
MANU	manufacturer	all	int (fk)	NA
QCPROC	quality control procedure	all	int (fk)	Procedure used to quality control the observation and set quality flag

Continued on next page



Table 141 sensor_configuration_fields (cont.)

field_id	field_name	parameter	type	description
SERIAL	serial number	all	varchar	NA
SHVR	sensor housing - ventilation rate	all	numeric	NA
SLOC	sensor location - ship	all	int (fk)	NA
SMAX	sensor range - max	all	numeric	Maximum observable value with sensor in reported units of measurement
SMIN	sensor range - min	all	numeric	Minimum observable value with sensor in reported units of measurement
SMOD	sensor model	all	varchar	NA
SOFT	software_version	all	varchar	NA
SPROC	sampling procedure	all	int (fk)	how the sample was obtained
SRES	sensor resolution	all	numeric	NA
SRESP	sensor response time	all	numeric	Time (s) for sensor to change from previous state to current state
SRR	sensor type - precipitation	precipitation	int (fk)	NA
SSIDE	sensor side - ship	all	int (fk)	NA
STAB	sensor stability	all	numeric	Reported stability of sensor in reported units of measurement per year.
SWV	sensor type - waves	waves	int (fk)	NA
SWW	sensor type - present weather	present weather	int (fk)	NA
STREAT	sample treatment	all	int (fk)	treatment of the sample prior to analysis
TSONDE	telemetry_sonde	sonde	int (fk)	NA
WGHT	weight	sonde	numeric	NA
STIME	sample times	all	timestamp	time of the samples used to calculate statistics
INSTDATE	installation date	all	timestamp	Date when sensor was installed

Continued on next page



Table 141 sensor_configuration_fields (cont.)

field_id	field_name	parameter	type	description
MNTDATE	maintenance date	all	timestamp	Date when maintenance performed (use MTNCE to summarise activities undertaken)
MNTMETH	maintenance	all	varchar	Summary of maintenance performed
MNTPRTY	maintenance party	all	varchar	Who performed the maintenance
MNTINT	maintenance interval	all	numeric	Maximum number of months recommended between maintenance activities
End of table				



Table 142: source_configuration_codes codes

field_id	field_name	code_value	abbreviation	description
0	delayed mode format	0	IMMT version just prior to version number being included	NA
0	delayed mode format	1	IMMT-1 (in effect from 2 Nov. 1994)	NA
0	delayed mode format	2	IMMT-2 (in effect from Jan. 2003)	NA
0	delayed mode format	3	IMMT-3 (in effect from Jan. 2007)	NA
0	delayed mode format	4	IMMT-4 (in effect from Jan. 2011)	NA
0	delayed mode format	5	IMMT-5 (in effect from June 2012)	NA
1	metadata source	0	COAPS	NA
1	metadata source	1	WMO Publication 47	NA
2	metadata source format	1	Output from digitisation project, semi-colon delimited format (1955)	NA
2	metadata source format	2	Output from digitisation project, semi-colon delimited format (1956)	NA
2	metadata source format	3	Output from digitisation project, semi-colon delimited format (1957 - 1967)	NA

Continued on next page



Table 142 source_configuration_codes (cont.)

field_id	field_name	code_value	abbreviation	description
2	metadata source format	4	Output from digitisation project, semi-colon delimited format (1968 - 1969)	NA
2	metadata source format	5	Fixed format (1970 - 1004)	NA
2	metadata source format	6	Semi-colon delimited format (1995 - 2001)	NA
2	metadata source format	7	Semi-colon delimited format (2002 - 2007 q1)	NA
2	metadata source format	8	Semi-colon delimited format (2007 - 2008)	NA
2	metadata source format	9	Semi-colon delimited format (2009 - 2014)	NA
3	observation source type	0	unknown	NA
3	observation source type	1	delayed mode - logbook (paper)	NA
3	observation source type	2	real time - national telecommunication channels	NA
3	observation source type	3	delayed mode - national publications	NA
3	observation source type	4	delayed mode - logbook (electronic)	NA

Continued on next page



Table 142 source_configuration_codes (cont.)

field_id	field_name	code_value	abbreviation	description
3	observation source type	5	real time - global telecommunication system (GTS)	NA
3	observation source type	6	delayed mode - International publications	NA
4	real time format	0	previous to FM24-V	NA
4	real time format	1	FM 24-V	NA
4	real time format	2	FM 24-VI Ext.	NA
4	real time format	3	FM 13-VII	NA
4	real time format	4	FM 13-VIII	NA
4	real time format	5	FM 13-VIII Ext.	NA
4	real time format	6	FM 12-IX	NA
4	real time format	7	FM 13-IX Ext.	NA
4	real time format	8	FM 13-X	NA
4	real time format	9	FM 13-XI	NA
4	real time format	10	FM 13-XII Ext.	NA
4	real time format	11	FM 13-XIII	NA
4	real time format	12	FM 13-XIV Ext.	NA
5	source format	0	IMMA - Version 0	NA
5	source format	1	IMMA - Version 1	NA
6	icoads source deck	NA	See ICOADS Source Deck	NA
7	icoads source id	NA	See ICOADS Source ID	NA
8	product level	2	Data read from original data file	NA
9	product status	1	Data approved	Data exist, read from chache, PTU + altitude columns available, all GC25 tests ok, all uncertainties as expected

End of table



Table 143: source_configuration_fields codes

field_id	field_name	kind	description
0	delayed mode format	int (fk)	NA
1	metadata source	int (fk)	NA
2	metadata source format	int (fk)	NA
3	observation source type	int (fk)	NA
4	real time format	int (fk)	NA
5	source format	int (fk)	NA
6	source deck	int (fk)	NA
7	source id	int (fk)	NA
10	product original time resolution	numeric	NA

End of table

Table 144: source_format codes

format	description
0	ASCII (comma seperated values)

End of table

Table 145: spatial_representativeness codes

representativeness	description
0	Nil reason - None of the codes in the table is applicable in the context of the observed quantity or unknown, or not available information.
1	Microscale - An area or volume less than 100 m horizontal extent (for example, evaporation)
2	Toposcale, local scale - An area or volume of 100 m to 3 km horizontal extent (for example, air pollution, tornadoes)
3	Mesoscale - An area or volume of 3 km to 100 km horizontal extent (for example, thunderstorms, sea and mountain breezes)

Continued on next page



Table 145 spatial_representativeness (cont.)

representativeness	description
4	Large scale- An area or volume of 100 km to 3000 km horizontal extent (for example, fronts, various cyclones, cloud clusters)
5	Planetary scale - An area or volume of more than 3000 km horizontal extent (for example, long upper tropospheric waves)
6	Drainage area - An area (also known as 'catchment') having a common outlet for its surface runoff, in km ²

End of table

Table 146: standard_time codes

time	description
0	00 UTC
1	06 UTC
2	12 UTC
3	18 UTC

End of table



Table 147: station_configuration_codes codes

field_id	field_name	code_value	abbreviation	description
0	AWS Entry and Display Software			TBD
1	AWS Entry and Display Software Version			TBD
2	AWS Model			TBD
3	AWS Model Version			TBD
4	AWS Software			TBD
5	AWS Software version			TBD
9	Drogue type	NA		See BUFR code table 0 02 034
11	Lagrangian drifter drogue status	NA		See BUFR code table 0 22 060
11	LogBook software and version			TBD
16	Other instruments	0	BAT	Baththermometer.
16	Other instruments	1	BT	Baththermograph (towed).
16	Other instruments	2	FLM	Fluorometer.
16	Other instruments	3	LWR	Long wave radiation.
16	Other instruments	4	MAX	Maximum thermometer.
16	Other instruments	5	MIN	Minimum thermometer.
16	Other instruments	6	NTE	Nitrate sensor.
16	Other instruments	7	NTT	Nutrient sensor.
16	Other instruments	8	P	Pilot balloon equipment.
16	Other instruments	9	CO2	pCO2 system.
16	Other instruments	10	PLK	Plankton recorder.
16	Other instruments	11	PRS	Photosynthetic radiation sensor.
16	Other instruments	12	PYG	Pyrogeometer.
16	Other instruments	13	R	Radiosonde equipment.

Continued on next page



Table 147 station_configuration_codes (cont.)

field_id	field_name	code_value	abbreviation	description
16	Other instruments	14	RG	Rain gauge.
16	Other instruments	15	RSD	Radar storm and meteorological phenomena detection.
16	Other instruments	16	RT	Reversing thermometer.
16	Other instruments	17	SKY	Sky camera.
16	Other instruments	18	SLM	Solarimeter.
16	Other instruments	19	ST	Sea thermograph.
16	Other instruments	20	SWR	Short wave radiation.
16	Other instruments	21	TSD	Temperature/salinity/depth probe.
16	Other instruments	22	TUR	Turbidity sensor.
16	Other instruments	23	W	Radiowind or radarwind equipment.
16	Other instruments	24	WR	Wave Recorder
16	Other instruments	25	XBT	Expendable bathythermograph.
16	Other instruments	26	OT	Other (specify in footnote).
17	Station status	1		Planned
17	Station status	2		Pre-operational
17	Station status	3		Operational / Reporting
17	Station status	4		Partly reporting
17	Station status	5		Temporarily suspended
17	Station status	6		Closed
18	Type of meteorological reporting ship	0	70	Auxiliary ship
18	Type of meteorological reporting ship	1	75	Auxiliary ship (AWS)
18	Type of meteorological reporting ship	2	10	Selected
18	Type of meteorological reporting ship	3	15	Selected (AWS)
18	Type of meteorological reporting ship	4	40	Supplementary

Continued on next page



Table 147 station_configuration_codes (cont.)

field_id	field_name	code_value	abbreviation	description
18	Type of meteorological reporting ship	5	45	Supplementary (AWS)
18	Type of meteorological reporting ship	6	80	Third party
18	Type of meteorological reporting ship	7	85	Third party (AWS)
18	Type of meteorological reporting ship	8	99	Unknown
18	Type of meteorological reporting ship	9	30	VOSClim - VOS Climate
18	Type of meteorological reporting ship	10	35	VOSClim (AWS) - VOS Climate (AWS)
End of table				



Table 148: station_configuration_fields codes

field_id	field_name	kind	description
0	AWS Entry and Display Software	int (fk)	See station_configuration_codes
1	AWS Entry and Display Software Version	int (fk)	See station_configuration_codes
2	AWS Model	int (fk)	See station_configuration_codes
3	AWS Model Version	int (fk)	See station_configuration_codes
4	AWS Software	int (fk)	See station_configuration_codes
5	AWS Software version	int (fk)	See station_configuration_codes
6	Cargo height	numeric	Height of cargo above deck (m)
7	Distance of bridge from bow	numeric	(m)
8	Draught	numeric	(m)
9	Drogue type	int (fk)	See station_configuration_codes
10	Freeboard	numeric	NA
11	Lagrangian drifter drogue status	int (fk)	See station_configuration_codes
12	Length overall of the ship, ignoring bulbous bow	numeric	NA
13	LogBook software and version	int (fk)	See station_configuration_codes
14	Maximum operating speed on normal service	numeric	NA
15	Moulded breadth	numeric	NA
16	Other instruments	int (fk)	See station_configuration_codes
17	Station status	int (fk)	See station_configuration_codes
18	Type of meteorological reporting ship	int (fk)	See station_configuration_codes
19	Surface cover	int (fk)	See station_configuration_codes
20	Surface cover scheme	int (fk)	See station_configuration_codes
21	Topography	int (fk)	See station_configuration_codes
22	Topography scheme	int (fk)	See station_configuration_codes

Continued on next page



Table 148 station_configuration_fields (cont.)

field_id	field_name	kind	description
23	Soil type	int (fk)	See station_configuration_codes
24	Land use	int (fk)	See station_configuration_codes
25	Alternate lon- gitude	numeric	NA
26	Alternate latitude	numeric	NA
27	Distance from road	numeric	Distance from nearest road (in km)
28	Distance from water body	numeric	Distance from nearest water body (in km)

End of table

Table 149: station_type codes

type	description
1	Land station
2	Sea station
3	Aircraft
4	Satellite
5	Underwater platform

End of table

Table 150: sub_region codes

sub_region	type	code	name
0	country	AD	ANDORRA
1	country	AE	UNITED ARAB EMIRATES
2	country	AF	AFGHANISTAN
3	country	AG	ANTIGUA AND BARBUDA
4	country	AI	ANGUILLA
5	country	AL	ALBANIA
6	country	AM	ARMENIA
7	country	AN	NETHERLANDS ANTILLES
8	country	AO	ANGOLA
9	country	AQ	ANTARCTICA
10	country	AR	ARGENTINA
11	country	AS	AMERICAN SAMOA
12	country	AT	AUSTRIA
13	country	AU	AUSTRALIA
14	country	AW	ARUBA
15	country	AX	ALAND ISLANDS

Continued on next page



Table 150 sub_region (cont.)

sub_region	type	code	name
16	country	AZ	AZERBAIJAN
17	country	BA	BOSNIA AND HERZEGOVINA
18	country	BB	BARBADOS
19	country	BD	BANGLADESH
20	country	BE	BELGIUM
21	country	BF	BURKINA FASO
22	country	BG	BULGARIA
23	country	BH	BAHRAIN
24	country	BI	BURUNDI
25	country	BJ	BENIN
26	country	BL	SAINT BARTHAÉILEMY
27	country	BM	BERMUDA
28	country	BN	BRUNEI DARUSSALAM
29	country	BO	BOLIVIA
30	country	BR	BRAZIL
31	country	BS	BAHAMAS
32	country	BT	BHUTAN
33	country	BV	BOUVET ISLAND
34	country	BW	BOTSWANA
35	country	BY	BELARUS
36	country	BZ	BELIZE
37	country	CA	CANADA
38	country	CC	COCOS (KEELING) ISLANDS
39	country	CD	CONGO, THE DEMOCRATIC REPUBLIC OF THE
40	country	CF	CENTRAL AFRICAN REPUBLIC
41	country	CG	CONGO
42	country	CH	SWITZERLAND
43	country	CI	COTE D'IVOIRE
44	country	CK	COOK ISLANDS
45	country	CL	CHILE
46	country	CM	CAMEROON
47	country	CN	CHINA
48	country	CO	COLOMBIA
49	country	CR	COSTA RICA
50	country	CU	CUBA
51	country	CV	CAPE VERDE
52	country	CX	CHRISTMAS ISLAND
53	country	CY	CYPRUS
54	country	CZ	CZECH REPUBLIC
55	country	DD	GERMAN DEMOCRATIC REPUBLIC

Continued on next page



Table 150 sub_region (cont.)

sub_region	type	code	name
56	country	DE	GERMANY
57	country	DJ	DJIBOUTI
58	country	DK	DENMARK
59	country	DM	DOMINICA
60	country	DO	DOMINICAN REPUBLIC
61	country	DZ	ALGERIA
62	country	EC	ECUADOR
63	country	EE	ESTONIA
64	country	EG	EGYPT
65	country	EH	WESTERN SAHARA
66	country	ER	ERITREA
67	country	ES	SPAIN
68	country	ET	ETHIOPIA
69	country	FI	FINLAND
70	country	FJ	FIJI
71	country	FK	FALKLAND ISLANDS (MALVINAS)
72	country	FM	MICRONESIA, FEDERATED STATES OF
73	country	FO	FAROE ISLANDS
74	country	FR	FRANCE
75	country	GA	GABON
76	country	GB	UNITED KINGDOM
77	country	GD	GRENADA
78	country	GE	GEORGIA
79	country	GF	FRENCH GUIANA
80	country	GG	GUERNSEY
81	country	GH	GHANA
82	country	GI	GIBRALTAR
83	country	GL	GREENLAND
84	country	GM	GAMBIA
85	country	GN	GUINEA
86	country	GP	GUADELOUPE
87	country	GQ	EQUATORIAL GUINEA
88	country	GR	GREECE
89	country	GS	SOUTH GEORGIA AND THE SOUTH SANDWICH ISLANDS
90	country	GT	GUATEMALA
91	country	GU	GUAM
92	country	GW	GUINEA-BISSAU
93	country	GY	GUYANA
94	country	HK	HONG KONG

Continued on next page



Table 150 sub_region (cont.)

sub_region	type	code	name
95	country	HM	HEARD ISLAND AND MCDONALD ISLANDS
96	country	HN	HONDURAS
97	country	HR	CROATIA
98	country	HT	HAITI
99	country	HU	HUNGARY
100	country	ID	INDONESIA
101	country	IE	IRELAND
102	country	IL	ISRAEL
103	country	IM	ISLE OF MAN
104	country	IN	INDIA
105	country	IO	BRITISH INDIAN OCEAN TERRITORY
106	country	IQ	IRAQ
107	country	IR	IRAN, ISLAMIC REPUBLIC OF
108	country	IS	ICELAND
109	country	IT	ITALY
110	country	JE	JERSEY
111	country	JM	JAMAICA
112	country	JO	JORDAN
113	country	JP	JAPAN
114	country	KE	KENYA
115	country	KG	KYRGYZSTAN
116	country	KH	CAMBODIA
117	country	KI	KIRIBATI
118	country	KM	COMOROS
119	country	KN	SAINT KITTS AND NEVIS
120	country	KP	KOREA, DEMOCRATIC PEOPLE'S REPUBLIC OF
121	country	KR	KOREA, REPUBLIC OF
122	country	KW	KUWAIT
123	country	KY	CAYMAN ISLANDS
124	country	KZ	KAZAKHSTAN
125	country	LA	LAO PEOPLE'S DEMOCRATIC REPUBLIC
126	country	LB	LEBANON
127	country	LC	SAINT LUCIA
128	country	LI	LIECHTENSTEIN
129	country	LK	SRI LANKA
130	country	LR	LIBERIA
131	country	LS	LESOTHO
132	country	LT	LITHUANIA
133	country	LU	LUXEMBOURG
134	country	LV	LATVIA

Continued on next page



Table 150 sub_region (cont.)

sub_region	type	code	name
135	country	LY	LIBYAN ARAB JAMAHIRIYA
136	country	MA	MOROCCO
137	country	MC	MONACO
138	country	MD	MOLDOVA, REPUBLIC OF
139	country	ME	MONTENEGRO
140	country	MF	SAINT MARTIN
141	country	MG	MADAGASCAR
142	country	MH	MARSHALL ISLANDS
143	country	MK	MACEDONIA, THE FORMER YU-GOSLAV REPUBLIC OF
144	country	ML	MALI
145	country	MM	MYANMAR
146	country	MN	MONGOLIA
147	country	MO	MACAO
148	country	MP	NORTHERN MARIANA ISLANDS
149	country	MQ	MARTINIQUE
150	country	MR	MAURITANIA
151	country	MS	MONTserrat
152	country	MT	MALTA
153	country	MU	MAURITIUS
154	country	MV	MALDIVES
155	country	MW	MALAWI
156	country	MX	MEXICO
157	country	MY	MALAYSIA
158	country	MZ	MOZAMBIQUE
159	country	NA	NAMIBIA
160	country	NC	NEW CALEDONIA
161	country	NE	NIGER
162	country	NF	NORFOLK ISLAND
163	country	NG	NIGERIA
164	country	NI	NICARAGUA
165	country	NL	NETHERLANDS
166	country	NO	NORWAY
167	country	NP	NEPAL
168	country	NR	NAURU
169	country	NU	NIUE
170	country	NZ	NEW ZEALAND
171	country	OM	OMAN
172	country	PA	PANAMA
173	country	PE	PERU

Continued on next page



Table 150 sub_region (cont.)

sub_region	type	code	name
174	country	PF	FRENCH POLYNESIA
175	country	PG	PAPUA NEW GUINEA
176	country	PH	PHILIPPINES
177	country	PK	PAKISTAN
178	country	PL	POLAND
179	country	PM	SAINT PIERRE AND MIQUELON
180	country	PN	PITCAIRN
181	country	PR	PUERTO RICO
182	country	PS	PALESTINIAN TERRITORY, OCCUPIED
183	country	PT	PORTUGAL
184	country	PW	PALAU
185	country	PY	PARAGUAY
186	country	QA	QATAR
187	country	RE	REUNION
188	country	RO	ROMANIA
189	country	RS	SERBIA
190	country	RU	RUSSIAN FEDERATION
191	country	RW	RWANDA
192	country	SA	SAUDI ARABIA
193	country	SB	SOLOMON ISLANDS
194	country	SC	SEYCHELLES
195	country	SD	SUDAN
196	country	SE	SWEDEN
197	country	SG	SINGAPORE
198	country	SH	SAINT HELENA
199	country	SI	SLOVENIA
200	country	SJ	SVALBARD AND JAN MAYEN
201	country	SK	SLOVAKIA
202	country	SL	SIERRA LEONE
203	country	SM	SAN MARINO
204	country	SN	SENEGAL
205	country	SO	SOMALIA
206	country	SR	SURINAME
207	country	ST	SAO TOME AND PRINCIPE
208	country	SU	USSR
209	country	SV	EL SALVADOR
210	country	SY	SYRIAN ARAB REPUBLIC
211	country	SZ	SWAZILAND
212	country	TC	TURKS AND CAICOS ISLANDS
213	country	TD	CHAD

Continued on next page



Table 150 sub_region (cont.)

sub_region	type	code	name
214	country	TF	FRENCH SOUTHERN TERRITORIES
215	country	TG	TOGO
216	country	TH	THAILAND
217	country	TJ	TAJIKISTAN
218	country	TK	TOKELAU
219	country	TL	TIMOR-LESTE
220	country	TM	TURKMENISTAN
221	country	TN	TUNISIA
222	country	TO	TONGA
223	country	TR	TURKEY
224	country	TT	TRINIDAD AND TOBAGO
225	country	TV	TUVALU
226	country	TW	TAIWAN, PROVINCE OF CHINA
227	country	TZ	TANZANIA, UNITED REPUBLIC OF
228	country	UA	UKRAINE
229	country	UG	UGANDA
230	country	UM	UNITED STATES MINOR OUTLYING ISLANDS
231	country	US	UNITED STATES
232	country	UY	URUGUAY
233	country	UZ	UZBEKISTAN
234	country	VA	HOLY SEE (VATICAN CITY STATE)
235	country	VC	SAINT VINCENT AND THE GRENADINES
236	country	VE	VENEZUELA
237	country	VG	VIRGIN ISLANDS, BRITISH
238	country	VI	VIRGIN ISLANDS, U.S.
239	country	VN	VIET NAM
240	country	VU	VANUATU
241	country	WF	WALLIS AND FUTUNA
242	country	WS	SAMOA
243	country	YE	YEMEN
244	country	YT	MAYOTTE
245	country	YU	YUGOSLAVIA
246	country	ZA	SOUTH AFRICA
247	country	ZM	ZAMBIA
248	country	ZW	ZIMBABWE
249	country	ZZ	THIRD PARTY SUPPORT SHIPS

End of table



Table 151: time_quality codes

quality	description
0	Timestamp valid, time reported to nearest second
1	Timestamp valid, time reported to nearest minute
2	Timestamp valid, time reported to nearest hour
3	Time missing, date valid. Report set to local midday
4	Day missing
5	Invalid date / time

End of table

Table 152: time_reference codes

reference	description
0	Unknown
1	Time server
2	Radio clock
3	Manual comparison

End of table

Table 153: traceability codes

traceability	description
0	Unknown
1	Traceable to international standards
2	Traceable to other standards

End of table

Table 154: uncertainty_method codes

method	description	reference
TBD	TBD	TBD

End of table



Table 155: units codes

units	name	abbreviation	base_units
1 - 1024			See BUFR Common Code Table C-6
End of table			

Table 156: update_frequency codes

frequency	description
0	Irregular
1	Daily
2	Weekly
3	Monthly
4	Annual
End of table	

Table 157: z_coordinate_method codes

method	description
0	Value from chart
End of table	

Table 158: z_coordinate_type codes

type	description
0	height (m) above sea level
End of table	



ECMWF - Shinfield Park, Reading RG2 9AX, UK

Contact: info@copernicus-climate.eu