

2	Mobile Phone Application for Measuring Air Parameters in Getting Discomfort Index and
3	Amount of Air Pollutants with the Use of a Microcontroller-based System
4	
	A TOL
5	A Thesis
6	Presented to the Faculty of the
7	Department of Electronics and Communications Engineering
8	Gokongwei College of Engineering
9	De La Salle University
10	
10	
11	In Partial Fulfillment of the
12	Requirements for the Degree of
13	Bachelor of Science in Computer Engineering
14	
15	by
	- 7
16	CHEONG, Junlae
17	NIHALANI, Rohit P.
18	PAULINO, Noel B.
19	PO, Ryback Tyrone G.
	·
20	August, 2016



ORAL DEFENSE RECOMMENDATION SHEET

21

22

23

24 25

26

27

28

29

30

31

32 33

34

35

36

37

This thesis, entitled Mobile Phone Application for Measuring Air Parameters in Getting Discomfort Index and Amount of Air Pollutants with the Use of a Microcontroller**based System**, prepared and submitted by thesis group, ESG-04, composed of:

> CHEONG, Junlae NIHALANI, Rohit P. PAULINO, Noel B. PO, Ryback Tyrone G.

in partial fulfillment of the requirements for the degree of Bachelor of Science in Computer Engineering (BS-CPE) has been examined and is recommended for acceptance and approval for **ORAL DEFENSE**.

> Engr. Donabel D. Abuan Adviser

August 13, 2016

De La Salle University THESIS APPROVAL SHEET This thesis entitled Mobile Phone Application for Measuring Air Parameters in Get-39 ting Discomfort Index and Amount of Air Pollutants with the Use of a Microcontroller-40 based System, prepared and submitted by: 41 42 CHEONG, Junlae 43 NIHALANI, Rohit P. 44 PAULINO, Noel B. 45 PO, Ryback Tyrone G. 46 with group number ESG-04 in partial fulfillment of the requirements for the degree of 47 Bachelor of Science in Computer Engineering (BS-CPE) has been examined and is 48 recommended for acceptance and approval. 49 50 PANEL OF EXAMINERS 51 52 Engr. Julius P. Bancud 53 Chair Engr. Blanca I. Bucao Dr. Rionel B. Caldo Member Member 56 Engr. Donabel D. Abuan 57 Adviser Date: August 13, 2016 59





ACKNOWLEDGMENT

64

65

Write this prior to hard binding if you have submitted all requirements and are told by your adviser that you have passed.

TANKL!	De	La	Salle	Unive	ersity
MANILA					J

67 ABSTRACT

- Keep your abstract short by giving the gist/nutshell of your thesis.
- 69 *Index Terms*—alloy system, characterization, InP, InGaAs.



TABLE OF CONTENTS

71	Oral Defense Recommendation Sheet	ii
72	Thesis Approval Sheet	iii
73	Acknowledgment	v
74	Abstract	vi
75	Table of Contents	vii
76	List of Figures	xi
77	List of Tables	xii
78	Abbreviations	iii
79	Notation	civ
80	Glossary	XV
81	Listings	vi
82	Chapter 1 INTRODUCTION	1
83	1.1 Background of the Study	2
84	1.2 Prior Studies	3
85	1.3 Problem Statement	4
86	1.4 Objectives	5
87	1.4.1 General Objective(s)	5
88	1.4.2 Specific Objectives	5
89	1.5 Significance of the Study	5
90	1.6 Assumptions, Scope and Delimitations	6
91	1.7 Description and Methodology	7
92		10
93		10
94	Chapter 2 LITERATURE REVIEW	12
95		13



96 97 98 99	2.2 Humidity Monitoring System	14 16 16 17 18
101	Chapter 3 THEORETICAL CONSIDERATIONS	19
102	3.1 Microcontroller based temperature humidity meter using Arduino Platform	20
103	3.2 Discomfort Index	20
104	3.3 Bluetooth Technology	21
105	3.4 Comfortability indicator application at De La Salle university using Android	
106	platform	21
107	Chapter 4 DESIGN CONSIDERATIONS	23
108	4.1 Summary	26
109	Chapter 5 METHODOLOGY	27
110	5.1 Implementation	28
111	5.1.1 Planning	28
112	5.1.2 Initial Prototype	29
113	5.1.3 Second Prototype	29
114	5.1.4 Final Prototype	30
115	5.1.5 Integration of Communication Devices	30
116	5.2 Evaluation	30
117	5.2.1 Quantitative Approach	31
118	5.2.2 Crowdsourcing Approach	31
119	5.3 Summary	32
120	Chapter 6 RESULTS AND DISCUSSION	33
121	6.1 Summary	35
122	Chapter 7 CONCLUSIONS, RECOMMENDATIONS, AND FUTURE DIREC-	
123	TIVES	37
124	7.1 Concluding Remarks	38
125	7.2 Contributions	38
126	7.3 Recommendations	38
127	7.4 Future Prospects	40
128	References	41
129	Appendix A ANSWERS TO QUESTIONS TO THIS THESIS	42



	A 1		40
130	A1	How important is the problem to practice?	43
131	A2	How will you know if the solution/s that you will achieve would be better	
132		than existing ones?	43
133		A2.1 How will you measure the improvement/s?	43
134		A2.1.1 What is/are your basis/bases for the improvement/s?	43
135		A2.1.2 Why did you choose that/those basis/bases?	44
136		A2.1.3 How significant are your measure/s of the improvement/s?	44
137	A3	What is the difference of the solution/s from existing ones?	44
138		A3.1 How is it different from previous and existing ones?	44
139	A4	What are the assumptions made (that are behind for your proposed solution	
140		to work)?	45
141		A4.1 Will your proposed solution/s be sensitive to these assumptions? .	45
142		A4.2 Can your proposed solution/s be applied to more general cases	
143		when some of the assumptions are eliminated? If so, how?	45
144	A5	What is the necessity of your approach / proposed solution/s?	46
145		A5.1 What will be the limits of applicability of your proposed solution/s?	46
146		A5.2 What will be the message of the proposed solution to technical	
147		people? How about to non-technical managers and business men?	46
148	A6	How will you know if your proposed solution/s is/are correct?	47
149		A6.1 Will your results warrant the level of mathematics used (i.e., will	
150		the end justify the means)?	47
151	A7	Is/are there an/_ alternative way/s to get to the same solution/s?	47
152		A7.1 Can you come up with illustrating examples, or even better, counter	
153		examples to your proposed solution/s?	48
154		A7.2 Is there an approximation that can arrive at the essentially the same	
155		proposed solution/s more easily?	48
156	A8	If you were the examiner of your proposal, how would you present the	
157		proposal in another way?	48
158		A8.1 What are the weaknesses of your proposal?	49
159		lix B USAGE EXAMPLES	50
160	B1	Equations	51
161	B2	Notations	53
162	В3	Abbreviation	59
163	B4	Glossary	61
164	B5	Figure	62
165	В6	Table	68
166	В7	Algorithm or Pseudocode Listing	72
167	В8	Program/Code Listing	74

De La Salle University

168	B9 Referencing	76
169	B9.1 A subsection	77
170	B9.1.1 A sub-subsection	78
171	B10 Index	79
172	B11 Adding Relevant PDF Pages (e.g. Standards, Datasheets, Specification	
173	Sheets, Application Notes, etc.)	80
174	Appendix C PUBLICATION LIST AND AWARD	84
175	Appendix D VITA	86
176	Index	88



LIST OF FIGURES

178	5.1	System Prototyping Diagram	28
179 180 181	6.2	Accuracy Testing of Temperature from DHT-11 sensor	35
182 183	l	A quadrilateral image example	62 64
19/		Four figures in each corner See List B 7 for the corresponding IATEX code	66



LIST OF TABLES

186	1.1	Gannt Chart Part 1	8
187	1.2	Gannt Chart Part 2	9
188	1.3	Gannt Chart Legend	9
189	1.4	Estimated Budget	10
190	B.1	Feasible triples for highly variable grid	68
101	B 2	Calculation of $u = r^n$	72



ABBREVIATIONS

193	AC	Alternating Current	59
194	HTML	Hyper-text Markup Language	
195	CSS	Cascading Style Sheet	
196	XML	eXtensible Markun Language	59



NOTATION

198	\mathcal{S}	a collection of distinct objects	61
199	\mathcal{U}	the set containing everything	61
200	Ø	the set with no elements	61
201	$ \mathcal{S} $	the number of elements in the set S	61
202	h(t)	impulse response	51
203	x(t)	input signal represented in the time domain	51
204	y(t)	output signal represented in the time domain	51

Throughout this thesis, mathematical notations conform to ISO 80000-2 standard, e.g. variable names are printed in italics, the only exception being acronyms like e.g. SNR, which are printed in regular font. Constants are also set in regular font like j. Functions are also set in regular font, e.g. in $\sin(\cdot)$. Commonly used notations are t, f, $j = \sqrt{-1}$, n and $\exp(\cdot)$, which refer to the time variable, frequency variable, imaginary unit, nth variable, and exponential function, respectively.

SHEW	_	0 11	T T •	•
De	La	Salle	Unive	rsity

GLOSSARY

212



LISTINGS

B.1	Sample LATEX code for equations and notations usage	52
B.2	Sample LaTeX code for notations usage	56
B.3	Sample LaTeX code for abbreviations usage	60
B.4	Sample LaTeX code for glossary and notations usage	61
B.5	Sample LaTeX code for a single figure	63
B.6	Sample LaTeX code for three figures on top of each other	65
B.7	Sample LaTeX code for the four figures	67
B.8	Sample LaTeX code for making typical table environment	70
B.9	Sample LaTeX code for algorithm or pseudocode listing usage	73
B.10	Computing Fibonacci numbers	74
B.11	Sample LaTeX code for program listing	75
		76
B.13	Sample LaTeX code for referencing subsections	77
B.14	Sample LATEX code for referencing sub-subsections	78
B.15	Sample LATEX code for Index usage	79
		80
	B.2 B.3 B.4 B.5 B.6 B.7 B.8 B.9 B.10 B.11 B.12 B.13 B.14 B.15	B.2 Sample LATEX code for notations usage



Chapter 1

INTRODUCTION

Contents

1.1	Background of the Study	2
1.2	Prior Studies	3
1.3	Problem Statement	4
1.4	Objectives	5
	1.4.1 General Objective(s)	5
	1.4.2 Specific Objectives	5
1.5	Significance of the Study	5
1.6	Assumptions, Scope and Delimitations	6
1.7	Description and Methodology	7
1.8	Estimated Work Schedule and Budget	10
1.9	Overview	10



1.1 Background of the Study

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

There has been many reasons why one tries to avoid any outdoor activity but one of these is how the air feels whether it is too hot or too polluted or even both. One undeniable fact is that heat and humidity all play roles in making the weather hot. Both of these weather parameters are involved in the calculation of the heat index and the discomfort index. Heat index and discomfort index have their similarities because the factors that affect these two are the temperature and the relative humidity. The heat index is the perceived temperature by people when the rising temperature and the relative humidity is combined. The unit used here is a unit of temperature and the mathematical formula for computing the heat index shows a rather direct square proportionality with the temperature and the humidity. But when it comes to a more human readable scale, reaching 34 degrees Celsius is already a discomfort to some. Reaching at least 46 degrees Celsius is already dangerous to all as this can cause heat stroke and even imminent death to some people. The discomfort index is similar to the heat index but instead, its mathematical formula only indicates a direct proportionality with the temperature and the relative humidity. The scaling is rather similar to that in the heat index. When the discomfort index reaches at least 21 degrees Celsius, it is already a discomfort for some people. Reaching 29 degrees Celsius is already dangerous to all that when it even gets higher, a state of emergency can be declared. The human body is capable of regulating body temperature because of its abilities as a warm-blooded organism. When the human body detects extreme temperatures, it drastically adjusts the body just to get the internal temperature back to a normal 37 degrees Celsius. When your body detects a lot of heat, it tries to cool itself down by increasing your heart rate and sweating. However, one can sweat too much, he feels drained by the lack of fluids



in his body causing discomfort, weakness, loss of stamina, and even muscle pains, leading to a heat stroke.

Other than high temperatures and humidity, the pollutants in the air can be harmful to the respiratory system. Dust is a particle suspended in the air and it usually comes from the soil or the pollution. This can cause irritation in the respiratory system because dust entering the lungs can cause serious complications. This is already bad for those with respiratory problems such as asthma or emphysema. Carbon monoxide, however, is a colorless and odorless gas and it usually comes from smoke. When this is inhaled, it can cause serious complications in the body since this inhibits the delivery of oxygen from the blood to the other organs in the body which can cause death. Not only do all of this increase the risk of getting sickness but these also affect the visibility of an area.

This study will focus on a mobile application that enables people to have a foresight on how the outside air feels like. A microcontroller-based system will be used in detecting the parameters stated above while the mobile application will take note of the visibility with the use of the phone's camera.

1.2 Prior Studies

Some of the studies that the group has found are about the temperature and humidity monitoring systems. The temperature system can be constructed by using a simple microcontroller-based system with an important tool, the LM35 where the output voltage is directly proportional to the temperature detected. The same procedure can be done with the humidity sensor but this time, it does not make use of the LM35. Both of these sensors are good for agricultural applications and getting the air quality. Another study involves



the use of PM10 sensors in order to detect particulate matter that is 10 micrometers wide. An algorithm has been made with the use of the atmospheric reflectance for temporal monitoring. Another study introduces another concept of air monitoring by taking note of the pollutants present which are namely carbon monoxide, PM 2.5, and ozone which make use of the MQ-7 4 sensor, MQ-131 sensor, and Sharp dust sensor respectively. Another study made use of getting the discomfort index by using temperature, humidity, atmospheric pressure, and carbon dioxide sensors. Finally, a study states the standards set by different parts of the world when it comes to the air quality. These standards all make use of the amount of pollutants present in the air as basis of air quality.

1.3 Problem Statement

Though there have been mobile applications that display the weather in real time, none have been able to show the discomfort index given the data. Also, there are no applications that tell the amount of dust or carbon monoxide in the air considering that these are some important factors when people choose to commute by an ordinary jeepney or do any outdoor activity in urban areas.

The aim of this study is to develop a new mobile application that is able to report the condition of the air such as weather parameters and the amount of pollutants present. The system will make use of a microcontroller along with different sensors that will measure the said parameters. Also, the mobile application will make use of computer vision to measure the visibility in an area.

Can a mobile application be developed to report real time conditions of the air and the amount of pollutants present with the used of a sensor-based microcontroller system?



1.4 Objectives

313

314

315

316

317

318

319

320

321

322

323

325

326

327

328

329

330

1.4.1 General Objective(s)

To design and develop an indoor/outdoor system for getting the discomfort index of the air...;

1.4.2 Specific Objectives

- 1. To make use of the temperature, humidity, amount of dust, amount of carbon monoxide, and visibility in calculating discomfort index and measuring pollutants
- To utilize different sensors for temperature, humidity, dust, and carbon monoxide measurement
- 3. To gather apparent information on the discomfort regarding heat and air pollution with the use of crowd sourcing
- 4. To make use of computer vision with the use of a cellphone camera to measure visibility
- 5. To achieve a social impact on the conditions and quality of the air for the people in urban areas where smoke is present and abundant

1.5 Significance of the Study

The significance of this topic is to be able to design and produce a device of checking the air quality and discomfort index for the public health awareness. There are millions of



commuters in the Philippines riding jeepneys or light rail transit system. The problem of this way of commuting is the air because there are a lot of old vehicles producing smoke and most people just breathe in either direct or indirect way. It is very important for the people to know the status of the air to secure their respiratory health. Together with this, the group aim to the user friendly device that anyone can easily understand how to use the device through an android application. Since a lot of people uses android mobile phones, making an application for free will be very helpful. The application will display the required data in graphics so that it is easy to understand for the public and to make the aware of the effect of the environment to their health. This study will surely help a lot of people who still dont know about why it is important to know the air we are breathing outside.

1.6 Assumptions, Scope and Delimitations

- 1. The given data will only be determined by the air quality index and the discomfort index.
- 2. The application will be used only for displaying the data gathered in the device.
- 3. People should be able to know the importance of their respiratory system in the body.
- 4. Users must aware the connection between air pollution and lung cancer.
- 5. The device will only deal with the common factors for discomfort such as temperature, humidity, and the amount of dust in the air.



1.7 Description and Methodology

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

A device for checking air quality and discomfort index can be functional through the use of the electronic sensors attached in the circuit and sensors for dust, humidity, and temperature will provide the data for air quality index and discomfort index. The device will be user friendly so that anyone can easily control and use it for the given purpose. The goal for this project is to come up with a device and android application for air quality and discomfort index which will provide data related to the health of the public. Challenges to this project would be the design of the circuit with indicated sensors and the accuracy of the data gathered by the device. The size of the device matters because it has to be user friendly and this will be designed for the typical citizens like commuters. The prototype test would determine if it has accurate data and user friendly in general. Android application will be supporting the device as a method of health awareness, the application will be able to show the data gathered in the device and show the effect of air quality index and discomfort index for respiratory health. The information is also one of the important part because people must know why it is important to know the air quality and their discomfort level. The information from the Arduino will be passed on to the HC-06 Bluetooth module in order to relay the information to an Android phone. With the use of crowd sourcing, any Android phone can update the discomfort index and other information from the sensors that will be stored in a firebase database and another phone can access these data.



TABLE 1.1 GANNT CHART PART 1

W1	W2	W3	W4	W5	W6	W7
Research for a topic All						
Submission of proposed topic	All					
Background of the study	1 111	NP				
Statement of the problem		NP				
Objectives		NP, JC				
Scope and delimitation		JC				
Review of related literature		RN, RP				
Methodology		,	All	All		
Individual Research			All	All	A11	All
Schematic diagram			NP	NP	NP	
Sensor Collection					JC, RN	JC, RN
Sensor Testing						
Arduino programming					NP	NP
Android programming					JC, RN	JC, RN
Android layout					,	,
OpenCV Integration					RP	RP
Board design						
Board layout						
Fabrication						
Mounting						
Proofreading and Revisions						
Final documentation						
Defense						



TABLE 1.2 GANNT CHART PART 2

	W8	W9	W10	W11	W12	W13	W14
Research for a topic							
Submission of proposed topic							
Background of the study							
Statement of the problem							
Objectives							
Scope and delimitation							
Review of related literature							
Methodology							
Individual Research	All	All	All	All	All		
Schematic diagram							
Sensor Collection	JC, RN						
Sensor Testing		All	All	All	All		
Arduino programming	NP	NP	NP	NP	NP		
Android programming	JC, RN						
Android layout			RP, RN	RP, RN	RP, RN		
OpenCV Integration	RP	RP	RP	RP			
Board design							
Board layout							
Fabrication							
Mounting							
Proofreading and Revisions						All	All
Final documentation						All	All
Defense							All

TABLE 1.3 GANNT CHART LEGEND

	LEGEND:
JC	Junlae Cheong
RN	Rohit Nihalani
NP	Noel Paulino
RP	Ryback Po



TABLE 1.4 ESTIMATED BUDGET

Laptop	30000
Android Phone	6000
Arduino Kit	2500
DHT-11	105
PM2.5 Sensor	1600
Carbon Monoxide Sensor	350
TOTAL COST	41055

1.8 Estimated Work Schedule and Budget

1.9 Overview

In the first chapter, it will be helpful for readers to understand what is the purpose of making the device and android application and why it is important for the society. It also shows how the project will be implemented in the real world from the hypothesis. For the second part of the paper, there will be a lot of helpful literature related to the air quality, discomfort index, respiratory health, prevention of lung cancer, effect of dust to the human body, circuit design for humidity, dust, and temperature sensors. These literature will guide the group what is the right way to develop a project and make it functional in order to fulfill the standard of the public. Theoretical considerations will be the key part to determine the data gathered from the device because there are theoretical standards in other research to know what are the air quality and discomfort index. Considering the design, it will be fully electronic design because the implementation in the hardware will be using electronic circuits. methodology will introduce how the data is gathered in the device and represented to the users. result and discussion will be providing the user feedback and the actual data given by the device in real situation. The value of this project will be determined in the

	1. Introduction	
	De La Salle University	
384	conclusion based on all the provided data and actual simulation. It is the most important	
385	part to prove how this project fulfilled its purpose for the public health awareness.	



386	Chapter 2
387	LITERATURE REVIEW

Contents

2.1	Temperature Monitoring System	13
2.2	Humidity Monitoring System	14
2.3	PM ₁₀ Temporal Monitoring	16
2.4	Wireless Air Quality Monitoring System	16
2.5	Discomfort Index Monitoring System	17
2.6	Air Quality Standards	18



There are several existing studies or researches about different kinds of applications of air parameters. Most of the studies found relating to these parameters are temperature, humidity, temporal, wireless air quality and discomfort index monitoring systems and air quality standards.

2.1 Temperature Monitoring System

An important parameter, not only in the air but also in everything, is the temperature. It is very important to monitor temperature of objects because most objects are sensitive to changes in the temperature such as products and some machines. Some existing researches of temperature monitoring system are found in the field of agriculture. Recent studies [Chavan and V.Karande, 2014] shows how important data-acquisition systems in the agriculture through environmental monitoring. Environmental monitoring refers to the gathering of data of some parameters in the environment that may affect the products. Automated measurements are beneficial because gathering of data and measurements are made several times. Chavan and Karande have developed a system for wireless monitoring of soil moisture, temperature and humidity in the field of agriculture. The system uses a temperature sensor, humidity sensor and soil moisture sensor that are connected to an AVR microcontroller. It also uses GSM-Zigbee based remote monitoring and control system. The application of Zigbee to the monitoring system in the agriculture reduces human power and enables to evaluate some accurate changes that will happen.

Aside from the agricultural implementation of temperature monitoring, there are also existing studies that involves its application to automated systems for electronic devices or appliances. [Mohamed Abd El-Latif Mowad, 2014] designed a smart home automated



control system. The system uses a microcontroller for sensors and android application for the transmission of data and the receiving of data. One of the four major fields of the smart home system or SHS is the environmental monitoring, which includes the monitoring of the humidity and the temperature. The main components used in the system are microcontroller, adruino board, android and a bluetooth module. Wireless internet services are also used for several monitoring and controlling processes. The passive infrared sensors are capable off detecing movements of a human being through sensing the changes in the temperature over the scene. The SHS also uses LM35 temperature sensor for the Temperature sensing system for Air Conditioner. The system can transfer data from the sensors to the android phone. On the same way, it can transmit data or commands from the android to the appliances. The wireless monitoring of temperature allows the user to control electronic devices or appliances from anywhere in the world.

2.2 Humidity Monitoring System

Humidity is always associated with temperature. It plays an important role to human due to the skin being sensitive to the changes in humidity. This is also the reason why humans sweat. Not only humans are affected by the changes in the humidity in the air but also applies to the things related to the field of agriculture.

A group of researchers [Aji Hanggoro and Sari, 2013] designed a green house monitoring and controlling system using an android mobile application. The system can control the humidity inside a green house, based on the readings of the humidity sensor through the microcontroller which is connected to the central server and can be accessed through Wi-Fi connection. The system is consists of humidity sensor, Arduino UNO microcontroller,



serial communication, wireless connection and a computer. The data from the sensor will be transmitted to the microcontroller and transferred to the computer through serial communication. The computer will transmit the data to the android phone via wireless connection and the android phone can now control the system depending on the commands that will be selected. The android can receive data from the humidity sensor, send data for water sprayer to turn on, send data for stepper motor to work and other commands that the system is capable of doing. This system ensures the condition of the green house environment to be in good condition.

Other than agricultural applications, studies also shows how air quality such as temperature and humidity affects the health of a human being. Indoor air quality or IAQ is an important factor that may affect the level of comfort and the health of the people. This may increase the discomfort index of a human being which may result to difficulties in concentration or even headaches. [Folea and Mois, 2015] develop a wireless battery-powered system for online ambient monitoring. The system has the ability to monitor temperature, humidity, carbon dioxide level, absolute pressure and intensity of light in the indoor spaces. The data gathered can be sent through a computer for visualization and can send SMS for alarms. The system has sensors such as ambient, temperature, humidity and many more sensors to evaluate the indoor air quality. Wi-Fi connection is used as a data transmission, from the sensors to the computer, due to the fact that Wi-Fi can be found in almost every home. The study of indoor air quality will help prevent or solve issues that may affect the health and the performance of the people.



2.3 PM₁₀ Temporal Monitoring

 PM_{10} or particulate matter that have a diameter of 10 micrometers wide which are classified under fine particles. One study [Wong et al., 2007] used an internet protocol camera to observe real time changes in the amount of particles found in the air. The camera points to a reference location and the still images were divided into the RGB bands.

They developed an algorithm which makes use of the atmospheric reflectance and the concentration of the PM_{10} using regression. The amount of reflectance is measured using a spectroradiometer and the concentration of the particles are determined by the different RGB bands of the camera. The PM_{10} and the atmospheric reflectance are found to be linearly related through using the skylight parameter model, which utilizes the sun's radiation. The results produced were compared to a DustTrak meter and provide a high correlation coefficient of .78.

2.4 Wireless Air Quality Monitoring System

A study [Reilly et al., 2015] monitored the amount of different air pollutants using Arduino. The pollutants that are measured are carbon monoxide, $PM_{2.5}$, and ozone which make use of the MQ-7 sensor, MQ-131 sensor, and Sharp dust sensor respectively. The sensors are mounted onto a redboard as well as GSM shield to send data wirelessly. The sensors are calibrated using a co-located ADEQ (Air Quality Division) sensor and were validated. The device is placed around the metro area and the data collected will be compared to a monitoring station. Data was collected for a period of time and a trend was found in CO and ozone levels. However, the use of the Sharp dust sensor was not very effective but could find slight differences at high pollution times with low pollution times.



Another similar study [Hebbar et al., 2014] of an air monitoring device is implemented using a microcontroller where several sensors are placed and data is sent through GSM wirelessly. The design tests the amount of CO_2 levels indoors. It also measures the temperature and humidity of the atmosphere locally. Calibration of the sensors is done by concentrating known amount of a certain gas into a test chamber and determine its offset from the results obtained. The design was tested in a seminar hall and the results obtained showed that the start and end of each class attributed to the increase in CO_2 emission. The design also shows the data through an online GUI.

One similar design, called HazeWatch, is done using several sensors and cloud computing [Hu et al., 2016]. The design is made compact and portable and can be mounted onto a car or bike. Data is harvested using a mobile phone and records the location in real time. Data is then sent wirelessly to cloud-based servers and is interpolated (Inverse Weighing and Ordinary Kriging interpolation) to generate estimates. The data can then be view visually using contour maps of the pollution or gas concentration levels in the area. The results obtained are compared to similar products (*Node* and *SensorDrone*)

2.5 Discomfort Index Monitoring System

A research was made about the importance of monitoring and controlling of atmospheric conditions to the efficiency of the performance of the human beings [Noh et al., 2013] . They designed a wireless sensor module that uses a Zigbee communication and sensor module, which consists of temperature, humidity, CO_2 and atmospheric pressure sensor, that maintains a comfortable environment for human beings or to prevent discomfort. The sensor module is the transmitter which delivers the sensor data to the receiver and



the receiver will transmit the filtered or recovered sensor data to a microcontroller board in monitoring the room environment. The room monitoring system is able to provide a comfortable environment for human beings through the wireless sensor network or WSN for monitoring the room environment.

2.6 Air Quality Standards

This review shows the different indoor air quality standards set by different countries across the world. The data is collected from documents from different health and environmental organization. This paper can be set as a tool for evaluating acceptable concentrations of different pollutants within an area. The pollutants included in this study are "carbon dioxide (CO_2), carbon monoxide (CO_2), formaldehyde (CO_2), nitrogen dioxide (CO_2), sulfur dioxide (CO_2), total volatile organic compounds (CO_2) and particulate matter (CO_2) and CO_2). The amount allowable depends on how bad the amount of a certain pollutant exists indoors. The paper also explains different harmful health effects each pollutant has on the human body.

	De La Salle University	
Cha	pter 3	
THE	ORETICAL CONSIDERATIONS	
THE Conte		
	ents	2
Conte		2 2 2
Conte	ents Microcontroller based temperature humidity meter using Arduino Platform	
3.1 3.2	Microcontroller based temperature humidity meter using Arduino Platform Discomfort Index	2



3.1 Microcontroller based temperature humidity meter using Arduino Platform

Arduino is one of the many micro-controller based systems that can be utilized to measure temperature and humidity level. It is a combination of hardware and software computer architecture system that has already made into several versions of small size chipsets. Both of these versions can be used along with the humidity and temperature sensors to detect temperature and humidity in the environment. Temperature and humidity level may vary depends on the locations since every different location are affected by various environments. Different time also affects the result due to the weather change and location of the sun in the sky. The Arduino microcontroller system implemented together with the sensor on a device like a portable temperature and humidity meter. The device used and temperature and humidity sensor must have a physical connection and battery for the power supply. The Arduino device will present the data into a LCD display, in order to make it easier for users to read the humidity and temperature levels.

3.2 Discomfort Index

Discomfort index refer to impact of heat and stress on the individual taking account the combined effect of temperature and humidity. This index is used as a standard to inform the user whether their respective places are not comfortable or good enough for an activity. Several temperature and humidity levels will be gathered in order to give a more accurate discomfort index as a result. Proper gathering of temperature and humidity level data is necessary to fulfill the purpose of the discomfort index. It is important for student to know



which location at the campus is uncomfortable because stress caused by the environments affects the welfare of the students at school.

3.3 Bluetooth Technology

Bluetooth is a wireless communication technology. This technology deals with the regulation of the flow of data. Data transmission is done though the wireless communication in this technology there are paired two devices and these devices can communicate to each other through Bluetooth. After the paring of devices, there is a process of data transfer. It is a bidirection technology since it is capable of sending and receiving data. It has a limited transmission distance between the two devices and it cannot transmit data in far distances. The temperature and humidity data from the Arduino device can be transferred into the android application in terms of wireless Bluetooth communication as indicated above information.

3.4 Comfortability indicator application at De La Salle university using Android platform

Android is one of the operating system programs that can be used in various purposes. This operating system already has several versions such as Ginger Bread, Ice Cream Sandwich, Jelly Bean, KitKat and Marshmallow. All these versions are compatible with the android operating system to show the comfortability indicator. Marshmallow is the latest version and it has the more functions than the older versions but most phones do not support this version yet. older version of android will be used since it is the version where a lot of



students are using it right now. The Comfortability Indicator application will based it on the temperature and humidity data gathered in the Arduino device and it will display the heat map to indicate which area is comfortable and which are not. The students will have information about the discomfort index and the effect of heat and stress to their health and welfare.

	De La Salle University	
576	Chapter 4	
577	DESIGN CONSIDERATIONS	
578	Contents	
579 580 581	4.1 Summary	






Figure 4.1. System Model of the Project




Figure 4.2. System Flowchart





Figure 4.3. Circuit Configuration for Testing the DHT-11

```
#include <dht.h>
588
589
       2
590
          dht DHT;
591
       4
          #define DHT11_PIN 7
592
       6
593
594
          void setup(){
595
             Serial.begin(9600);
          }
       9
596
597
       10
598
       11
          void loop()
599
       12
600
       13
             int chk = DHT.read11(DHT11_PIN);
             Serial.print("Temperature = ");
601
       14
             Serial.println(DHT.temperature);
602
       15
             Serial.print("Humidity = ");
603
       16
             Serial.println(DHT.humidity);
604
       17
             delay(1000);
605
       18
       19
```

Figure 4.4. Code for Temperature and Humidity Gathering

$$DI = T - 0.55(1 - 0.01H)(T - 14.5)$$
(4.1)



Figure 4.5. Formula for Discomfort Index

4.1 Summary

According to the system model, the project will make use of an Arduino microcontroller system that will handle tasks of gathering inputs which are the temperature, humidity, amount of dust, and amount of carbon monoxide. These data will be transmitted an Android system. Afterwards, this data can be submitted to the Android cloud in real time. Each individual Android system in the cloud can make use of the camera to capture the image of the surroundings in order to get the visibility with the aid of computer vision. A crowdsourcing element is considered to be added in each system where the user can rank the amount of discomfort he feels in terms of the heat and air pollution. This information will be utilized in the cloud.

The current accomplishments for the group is the successful gathering of the temperature and humidity with the use of the Arduino system and the DHT-11 sensor. These values are rounded to the nearest units value.



Chapter 5

METHODOLOGY

Contents

5.1	.1 Implementation				
	5.1.1	Planning	28		
	5.1.2	Initial Prototype	29		
	5.1.3	Second Prototype	29		
	5.1.4	Final Prototype	30		
	5.1.5	Integration of Communication Devices	30		
5.2	Evalua	ation	30		
	5.2.1	Quantitative Approach	31		
	5.2.2	Crowdsourcing Approach	31		
5.3	Summ	ary	32		



5.1 Implementation

The group has chosen system prototyping as the primary methodology of the study Fig. 5.1. It is effective to use this because Arduino is quick to learn and would be useful in creating prototypes easily. It will also be advantageous to follow this methodology because of the time constraint and weekly updates. This would, however, not be very effective in terms of developing an Android application with a crowdsourcing element and bluetooth communications due to its unfamiliarity to the group.




Fig. 5.1 System Prototyping Diagram

5.1.1 Planning

The planning stage took around four weeks. In the planning stage, several factors of air quality was taken into consideration. Among these factors are temperature, humidity, dust, and amount of Carbon Monoxide. In creating this design, few more considerations must be accounted for. Among these are portability, Android compatibility, and real time. Different



stages must take place in creating the proposed system. These stages will consist of the integration of the different sensors to our design, testing and evaluating these sensors, and integrating them in the Android application.

5.1.2 Initial Prototype

For the initial prototype, the temperature and humidity are first taken into consideration. The design will include the DHT11 humidity sensor and an LED display to provide feedback on the current temperature and humidity as well as the discomfort index of the area. Several sets of data are first taken in order to retrieve the temperature and humidity. This is done in order to a check the consistency and accuracy of the measuring devices used for comparing the data collected from our design. The data is taken from 3 different days with 2 analog and 1 digital sensor. The prototype will make use of the DHT11 sensor and and its accuracy will be tested using the best thermometer and hygrometer.

5.1.3 Second Prototype

More features are added in the initial prototype. These will include bluetooth communications with the Android app as well as integrating crowdsourcing using FireBase. This will also include the SDS011 particulate matter laser sensor which measures the concentration of dust present locally. The use of this sensor will have a relative error of 10%. This error will be tested by comparing the results to a DustTrak or GRIMM dust monitor.



5.1.4 Final Prototype

Using MQ-7 CO sensor, the prototype will be further extended. The range will be from 10 to 500 ppm which is sufficient to determine how harmful the amount is. This too will be compared to an existing CO meter which will be used to measure the reliability of the sensor. The final prototype will also include the integration of visibility detection. The visibility detection will make use of OpenCV by making use of Canny Edge Detection. The prototype will also finalize the Android application's features and design.

5.1.5 Integration of Communication Devices

The data transferred will not only be transferred to the proposed Android application but also to a cloud. This will involve crowdsourcing which would enable several data to be inputted at real time. To transfer the data from the proposed system to the Android application, the SMiRF Bluetooth module or HC-05 Bluetooth module will be used. The data collected will then be transferred to a Firebase database.

5.2 Evaluation

The study is to develop a mobile phone application that utilizes the use of a microcontroller-based system to measure air parameters in getting the discomfort index and amount of air pollutants. The discomfort index is dependent on air parameters measured by the system. In relation to the air parameters, the study uses a quantitative approach of data gathering, through actual measurements of air parameters using analog and digital meters and sensors. A crowdsourcing approach was then applied for better information gathering between the users of the applications across the map.



5.2.1 Quantitative Approach

Data were gathered four nonconsecutive trials on twenty different locations along De La Salle University. The data collected is consists of the measurements of the available meters, one digital and two analog meters, and the measurements of the actual sensors used on the system. The time and date, when the data were taken, were also recorded due to the fact that the parameters greatly varies on the weather and the time it was measured which also leads to inconsistent recorded data.

The gathered data were used to determine the reliability of the measurements from the sensors used in the system, in resemblance to the measurements from the meters. The use of the meters are for establishing the ground truth of the measurements of air parameters. Also, the data were ranked according to their corresponding computed level of discomfort or discomfort index based on the parameters measured using both the meters and the sensors.

5.2.2 Crowdsourcing Approach

Due to the fact that the data can only be collected when the user is at the specified location, the android application used in this study integrates a crowdsourcing approach in gathering of data. In this way, the user can be aware of the conditions of the air parameters around a location on the map based on the data from the other users that are in the location.

The application is capable of sharing or storing information in a cloud for crowdsourcing. The cloud is used to hold the data from all the information stored by each users of the application. The crowdsourcing application is very dependent on the users data and it would be most effective when more people uses the application. This approach allows the user to gather information and at the same time, contributes to the cloud-based system of



the application which also contributes to the data gathering of other users.

5.3 Summary

The proposed design will contain several sensors that will measure temperature, humidity, particulate matter amount, and levels of carbon dioxide. There are different stages in gathering the various data required. The sensors will be calibrated based from its individual datasheets. The data will be taken in a span of two weeks and at different times throughout the day. The data taken from our design will be compared with commercial sensors that are readily available to test the reliability and consistency of the proposed design.

The data collected from DHT11 sensor for detecting temperature and humidity will be measured. The design will also use a SDS011 PM laser sensor to record the amount of dust present within its range. The MQ-7 CO sensor will record the concentrations of Carbon Monoxide in its vicinity. The range will be from 10 to 500 ppm which is sufficient to determine how harmful the amount of Carbon Monoxide is. These will be tested with their corresponding meters and its accuracy will be determined. The data collected will be sent to a database in a cloud and transferred to the Android application. The program within the application will handle the discomfort index calculation and will determine level of discomfort.

	De La Salle University
Cha	pter 6
RES	SULTS AND DISCUSSION
Conte	
6.1	Summary

De La Salle University

The goal of this research is to be able to provide a system that makes use of an Arduinobased measuring device that can pass on data with a Bluetooth module to an Android phone that can be able to relay this data to a firebase database that can be accessed by another Android phone.

In order to be able to verify the temperature-humidity sensor being used, another device will serve as the basis for true data. Measurements coming from the TH-65, a digital temperature and humidity measuring device, will be established as ground truth.

The following graphs show the accuracy testing of the DHT-11 with the TH-65 as the basis for ground truth. The blue data represents the temperature measured by the DHT-11 while the orange represents data coming from the TH-65. Temperature, humidity, and discomfort index are to be considered in this set of data. From the results, it has been shown that in measuring temperature, the DHT-11 sensor shows 98.91% accuracy and in humidity, the sensor is 89.66% accurate in terms of measuring humidity and in discomfort index, the sensor is 97.79% accurate.




Fig. 6.1 Accuracy Testing of Temperature from DHT-11 sensor

De La Salle University




Fig. 6.2 Accuracy Testing of Humidity from DHT-11 sensor




Fig. 6.3 Accuracy Testing of Discomfort Index from DHT-11 sensor

6.1 Summary

	pter 7 NCLUSIONS, RECOMMENDATIONS,
ANE	FUTURE DIRECTIVES
Sant a	anto.
7.1 7.2 7.3 7.4	Concluding Remarks



7.1 Concluding Remarks

In this Thesis, ...

7.2 Contributions

The interrelated contributions and supplements that have been developed in this Thesisare listed as follows.

- the ;
- the ;
- 765 the ;

7.3 Recommendations

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

De La Salle University

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue



a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

7.4 Future Prospects

There are several prospect related in this research that may be extended for further studies. ... So the suggested topics are listed in the following.

- 1. the
- 2. the
- 817 3. the



REFERENCES

818

849

[Aji Hanggoro and Sari, 2013] Aji Hanggoro, Mahesa Adhitya Putra, R. R. and Sari, R. F. (2013). 819 Green house monitoring and controlling using android mobile application. Quality in Research 820 2013. 821 [Chavan and V.Karande, 2014] Chavan, P. C. H. and V.Karande, M. (2014). Wireless monitoring 822 of soil moisture, temperature & humidity using zigbee in agriculture. International Journal of 823 Engineering Trends and Technology (IJETT). 824 [Folea and Mois, 2015] Folea, S. C. and Mois, G. (2015). A low-power wireless sensor for online 825 ambient monitoring. IEEE SENSORS JOURNAL. 826 [Hebbar et al., 2014] Hebbar, S., V, K., K, K. G., Kumar, A., Kumari, A. S. A., Yasasvi, R., Gupta, 827 A. K., Mishra, V., Amrutur, B., and Bhat, N. (2014). System engineering and deployment of en-828 virobat an urban air pollution monitoring device. In Electronics, Computing and Communication 829 Technologies (IEEE CONECCT), 2014 IEEE International Conference on, pages 1-6. 830 [Hu et al., 2016] Hu, K., Sivaraman, V., Luxan, B. G., and Rahman, A. (2016). Design and 831 evaluation of a metropolitan air pollution sensing system. IEEE Sensors Journal, 16(5):1448-832 1459. 833 [ISO, 2009] ISO (2009). 80000-2. Quantities and units-Part 2: Mathematical signs and symbols 834 to be used in the natural sciences and technology. 835 [Mohamed Abd El-Latif Mowad, 2014] Mohamed Abd El-Latif Mowad, Ahmed Fathy, A. H. 836 (2014). Smart home automated control system using android application and microcontroller. 837 International Journal of Scientific & Engineering Research. 838 [Noh et al., 2013] Noh, S.-K., Kim, K.-S., and Ji, Y.-K. (2013). Design of a room monitoring 839 840 system for wireless sensor networks. International Journal of Distributed Sensor Networks. [Oetiker et al., 2014] Oetiker, T., Partl, H., Hyna, I., and Schlegl, E. (2014). The Not So Short 841 Introduction to $\LaTeX 2_{\varepsilon}Or \LaTeX 2_{\varepsilon}in 157$ minutes. n.a. 842 [Reilly et al., 2015] Reilly, K. M., Birner, M. T., and Johnson, N. G. (2015). Measuring air quality 843 using wireless self-powered devices. In Global Humanitarian Technology Conference (GHTC), 844 2015 IEEE, pages 267-272. 845 [Wong et al., 2007] Wong, C. J., MatJafri, M. Z., Abdullah, K., Lim, H. S., and Low, K. L. 846 (2007). Temporal air quality monitoring using surveillance camera. In 2007 IEEE International 847 Geoscience and Remote Sensing Symposium, pages 2864–2868. 848

Produced: August 13, 2016, 14:06



Appendix A ANSWERS TO QUESTIONS TO THIS THESIS

Contents

54			
55	A1	How important is the problem to practice?	43
56	A2	How will you know if the solution/s that you will achieve would be better	
57		than existing ones?	43
i8		A2.1 How will you measure the improvement/s?	43
9		A2.1.1 What is/are your basis/bases for the improvement/s?	43
0		A2.1.2 Why did you choose that/those basis/bases?	44
		A2.1.3 How significant are your measure/s of the improvement/s?	44
	A3	What is the difference of the solution/s from existing ones?	44
		A3.1 How is it different from previous and existing ones?	44
.	A4	What are the assumptions made (that are behind for your proposed solution	
,		to work)?	45
5		A4.1 Will your proposed solution/s be sensitive to these assumptions? .	45
		A4.2 Can your proposed solution/s be applied to more general cases	
		when some of the assumptions are eliminated? If so, how?	45
	A5	What is the necessity of your approach / proposed solution/s?	46
		A5.1 What will be the limits of applicability of your proposed solution/s?	46
		A5.2 What will be the message of the proposed solution to technical	
		people? How about to non-technical managers and business men?	46
	A6	How will you know if your proposed solution/s is/are correct?	47
.		A6.1 Will your results warrant the level of mathematics used (i.e., will	
		the end justify the means)?	47
	A7	Is/are there an/_ alternative way/s to get to the same solution/s?	47
.		A7.1 Can you come up with illustrating examples, or even better, counter	
		examples to your proposed solution/s?	48
,		A7.2 Is there an approximation that can arrive at the essentially the same	
,		proposed solution/s more easily?	48
	A8	If you were the examiner of your proposal, how would you present the	
		proposal in another way?	48
		A8.1 What are the weaknesses of your proposal?	49
4 .			



A1 How important is the problem to practice?

The Philippines is a country that is prone to discomfort due to the inevitable elements of air pollution and rising heat levels. An Android application for awareness can be able to alert the locals about these issues.

A2 How will you know if the solution/s that you will achieve would be better than existing ones?

Currently, there are no Android applications that provide real-time updates on discomfort index and amount of dust and carbon monoxide in a Philippine implementation.

A2.1 How will you measure the improvement/s?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A2.1.1 What is/are your basis/bases for the improvement/s?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.



A2.1.2 Why did you choose that/those basis/bases?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A2.1.3 How significant are your measure/s of the improvement/s?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A3 What is the difference of the solution/s from existing ones?

Weather reports provide temperature and humidity in different parts of the world but our solution combines them both into a discomfort index derived from heat which is an essential factor in the levels of comfort of an individual.

A3.1 How is it different from previous and existing ones?

Weather stations provide measurements pertaining to temperature and humidity but in this solution, the measurements can be accurately measured with an Arduino-based system. The crowd sourcing element in the research enables these data to be updated time and time again, faster than an selecting an interval of a daily update.



A4 What are the assumptions made (that are behind for your proposed solution to work)?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A4.1 Will your proposed solution/s be sensitive to these assumptions?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A4.2 Can your proposed solution/s be applied to more general cases when some of the assumptions are eliminated? If so, how?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris.



Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A5 What is the necessity of your approach / proposed solution/s?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A5.1 What will be the limits of applicability of your proposed solution/s?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A5.2 What will be the message of the proposed solution to technical people? How about to non-technical managers and business men?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla



tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A6 How will you know if your proposed solution/s is/are correct?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A6.1 Will your results warrant the level of mathematics used (i.e., will the end justify the means)?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A7 Is/are there an/_ alternative way/s to get to the same solution/s?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus



placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A7.1 Can you come up with illustrating examples, or even better, counter examples to your proposed solution/s?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A7.2 Is there an approximation that can arrive at the essentially the same proposed solution/s more easily?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A8 If you were the examiner of your proposal, how would you present the proposal in another way?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec



ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

A8.1 What are the weaknesses of your proposal?

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

	De La Salle University	
1087 1088	Appendix B USAGE EXAMPLES	
	49	



1089 1090 1091

The user is expected to have a working knowledge of LATEX. A good introduction is in [Oetiker et al., 2014]. Its latest version can be accessed at http://www.ctan.org/ tex-archive/info/lshort.

1092

B1 Equations

1093 1094 1095

1096 1097 1098

1099 1100

1101

The following examples show how to typeset equations in LaTeX. This section also shows examples of the use of \gls{} commands in conjunction with the items that are in the notation.tex file. Please make sure that the entries in notation.tex are those that are referenced in the LATEX document files used by this Thesis. Please comment out unused notations and be careful with the commas and brackets in notation.tex .

In (B.1), the output signal y(t) is the result of the convolution of the input signal x(t)and the impulse response h(t).

$$y(t) = h(t) * x(t) = \int_{-\infty}^{+\infty} h(t - \tau) x(\tau) d\tau$$
(B.1)

Other example equations are as follows.

$$\begin{bmatrix} V_1 \\ \overline{I_1} \end{bmatrix} = \begin{bmatrix} A & B \\ C & D \end{bmatrix} \begin{bmatrix} V_2 \\ \overline{I_2} \end{bmatrix}$$
 (B.2)

$$\frac{1}{2} < \left\lfloor \operatorname{mod}\left(\left\lfloor \frac{y}{17} \right\rfloor 2^{-17\lfloor x\rfloor - \operatorname{mod}(\lfloor y\rfloor, 17)}, 2\right) \right\rfloor, \tag{B.3}$$

$$|\zeta(x)^3 \zeta(x+iy)^4 \zeta(x+2iy)| = \exp \sum_{n,p} \frac{3+4\cos(ny\log p) + \cos(2ny\log p)}{np^{nx}} \ge 1$$
 (B.4)



The verbatim LATEX code of Sec. B1 is in List. B.1.

Listing B.1: Sample LATEX code for equations and notations usage

```
The following examples show how to typeset equations in \LaTeX.
2
   In~\eqref{eq:conv}, the output signal \gls{not:output_sigt} is the
3
       result of the convolution of the input signal \gls{not:input_sigt}
       and the impulse response \gls{not:ir}.
4
5
    \begin{eqnarray}
         y\left( t \right) = h\left( t \right) * x\left( t \right)=\int_{-\}
6
             infty}^{+\infty}h\left( t-\tau \right)x\left( \tau \right) \
       \label{eq:conv}
8
    \end{eqnarray}
    Other example equations are as follows.
10
11
12
    \begin{eqnarray}
       \left[ \dfrac{ V_{1} }{ I_{1} } \right] =
13
14
       \begin{bmatrix}
15
          A & B \\
16
          C & D
17
       \end{bmatrix}
18
       \label{left} $$ \left[ \dfrac{ V_{2} }{ I_{2} } \right] \right] $$ \left[ \dfrac{ V_{2} }{ I_{2} } \right] $$
19
       \label{eq:ABCD}
20
    \end{eqnarray}
21
22
    \begin{eqnarray}
23
   {1\over 2} < \left( \int_{\infty} \mathbf{y} \right) 
       right\rfloor 2^{-17 \lfloor x \rfloor - \mathrm{mod}(\lfloor y\
       rfloor, 17)},2\right)\right\rfloor,
24
   \end{eqnarray}
25
26
    \begin{eqnarray}
27
    | \text{zeta(x)^3} \text{zeta(x+iy)^4} \text{zeta(x+2iy)} | =
   \ensuremath{\mbox{ \ exp\sum_{n,p}\frac{3+4\cos(ny\log p) +\cos (2ny\log p)}{np^{nx}}\ge 1}
28
   \end{eqnarray}
```



1103 B2 Notations

1104

1105

1106

1107

1108

1109

1111

1112

1113

1114

1115

1116

In order to use the standardized notation, the user is highly suggested to see the ISO 80000-2 standard [ISO, 2009]. The following were taken from <code>isomath-test.tex</code>.

Math alphabets

If there are other symbols in place of Greek letters in a math alphabet, it uses T1 or OT1 font encoding instead of OML.

$$\begin{array}{ll} \text{mathnormal} & A,B,\Gamma,\Delta,\Theta,\Lambda,\Xi,\Pi,\Sigma,\Phi,\Psi,\Omega,\alpha,\beta,\pi,\nu,\omega,v,w,0,1,9\\ \text{mathit} & A,B,\Gamma,\Delta,\Theta,\Lambda,\Xi,\Pi,\Sigma,\Phi,\Psi,\Omega,f\!f,f\!i,\beta,\stackrel{\circ}{,},!,v,w,0,1,9\\ \text{mathrm} & A,B,\Gamma,\Delta,\Theta,\Lambda,\Xi,\Pi,\Sigma,\Phi,\Psi,\Omega,f\!f,f\!i,\beta,\stackrel{\circ}{,},!,v,w,0,1,9\\ \text{mathbf} & \mathbf{A},\mathbf{B},\Gamma,\Delta,\Theta,\Lambda,\Xi,\Pi,\Sigma,\Phi,\Psi,\Omega,f\!f,f\!i,\beta,\stackrel{\circ}{,},!,v,w,0,1,9\\ \text{mathsf} & A,B,\Gamma,\Delta,\Theta,\Lambda,\Xi,\Pi,\Sigma,\Phi,\Psi,\Omega,f\!f,f\!i,\beta,\stackrel{\circ}{,},!,v,w,0,1,9\\ \text{mathtt} & A,B,\Gamma,\Delta,\Theta,\Lambda,\Xi,\Pi,\Sigma,\Phi,\Psi,\Omega,\uparrow,\downarrow,\beta,\stackrel{\circ}{,},!,v,w,0,1,9 \end{array}$$

New alphabets bold-italic, sans-serif-italic, and sans-serif-bold-italic.

mathbfit
$$A, B, \Gamma, \Delta, \Theta, \Lambda, \Xi, \Pi, \Sigma, \Phi, \Psi, \Omega, \alpha, \beta, \pi, \nu, \omega, v, w, o, 1, 9$$
 mathsfit $A, B, \Gamma, \Delta, \Theta, \Lambda, \Xi, \Pi, \Sigma, \Phi, \Psi, \Omega, \alpha, \beta, \pi, \nu, \omega, v, w, o, 1, 9$ mathsfbfit $A, B, \Gamma, \Delta, \Theta, \Lambda, \Xi, \Pi, \Sigma, \Phi, \Psi, \Omega, \alpha, \beta, \pi, \nu, \omega, v, w, o, 1, 9$

Do the math alphabets match?

 $ax lpha \omega ax lpha \omega ax lpha \omega$ $TC \Theta \Gamma TC \Theta \Gamma TC \Theta \Gamma$

Vector symbols

Alphabetic symbols for vectors are boldface italic, $\lambda = e_1 \cdot a$, while numeric ones (e.g. the zero vector) are bold upright, a + 0 = a.

Matrix symbols

Symbols for matrices are boldface italic, too: $\Lambda = E \cdot A$.

¹However, matrix symbols are usually capital letters whereas vectors are small ones. Exceptions are physical quantities like the force vector F or the electrical field E.



1117 **Tensor symbols**

1119

Symbols for tensors are sans-serif bold italic,

$$\boldsymbol{\alpha} = \boldsymbol{e} \cdot \boldsymbol{a} \iff \alpha_{ijl} = e_{ijk} \cdot a_{kl}.$$

The permittivity tensor describes the coupling of electric field and displacement:

$$oldsymbol{D} = \epsilon_0 oldsymbol{\epsilon}_{\mathrm{r}} oldsymbol{E}$$



1120 Bold math version

The "bold" math version is selected with the commands \boldmath or \mathversion{bold}

mathnormal $A,B,\Gamma,\Delta,\Theta,\Lambda,\Xi,\Pi,\Sigma,\Phi,\Psi,\Omega,\alpha,\beta,\pi,\nu,\omega,v,w,0,1,9$

mathrm $A, B, \Gamma, \Delta, \Theta, \Lambda, \Xi, \Pi, \Sigma, \Phi, \Psi, \Omega, ff, fi, \beta, ^{\circ}, !, v, w, 0, 1, 9$

 $\text{mathbf} \qquad A,B,\Gamma,\Delta,\Theta,\Lambda,\Xi,\Pi,\Sigma,\Phi,\Psi,\Omega,\text{ff},\text{fi},\beta,\ {}^{\circ},!,v,w,0,1,9$

mathsf $A, B, \Gamma, \Delta, \Theta, \Lambda, \Xi, \Pi, \Sigma, \Phi, \Psi, \Omega, ff, fi, B, ^{\circ}, !, v, w, 0, 1, 9$

 $mathtt \qquad A,B,\Gamma,\Delta,\Theta,\Lambda,\Xi,\Pi,\Sigma,\Phi,\Psi,\Omega,\uparrow,\downarrow,\beta,\,\,\mathring{},\,\,!\,,\,v,w,0,1,9$

New alphabets bold-italic, sans-serif-italic, and sans-serif-bold-italic.

mathbfit $A, B, \Gamma, \Delta, \Theta, \Lambda, \Xi, \Pi, \Sigma, \Phi, \Psi, \Omega, \alpha, \beta, \pi, \nu, \omega, v, w, o, 1, 9$

mathsfit $A, B, \Gamma, \Delta, \Theta, \Lambda, \Xi, \Pi, \Sigma, \Phi, \Psi, \Omega, \alpha, \beta, \pi, \nu, \omega, \nu, w, 0, 1, 9$

mathsfbfit $A, B, \Gamma, \Delta, \Theta, \Lambda, \Xi, \Pi, \Sigma, \Phi, \Psi, \Omega, \alpha, \beta, \pi, \nu, \omega, \nu, w, 0, 1, 9$

Do the math alphabets match?

αχαωαχαωαχαω ΤΟΘΓΤΟΘΓ

1125 | Vector symbols

Alphabetic symbols for vectors are boldface italic, $\lambda = e_1 \cdot a$, while numeric ones (e.g. the zero vector) are bold upright, a + 0 = a.

Matrix symbols

Symbols for matrices are boldface italic, too: $\Lambda = E \cdot A$.

Tensor symbols

1131 Symbols for tensors are sans-serif bold italic,

$$\alpha = e \cdot a \iff \alpha_{ijl} = e_{ijk} \cdot a_{kl}$$
.

The permittivity tensor describes the coupling of electric field and displacement:

$$D = \epsilon_0 \epsilon_r E$$

1133

1132

1130

1123

1124

²However, matrix symbols are usually capital letters whereas vectors are small ones. Exceptions are physical quantities like the force vector F or the electrical field E.



The verbatim LATEX code of Sec. B2 is in List. B.2.

Listing B.2: Sample LATEX code for notations usage

```
1135
           % A teststring with Latin and Greek letters::
1136
1137
           \newcommand{\teststring}{%
1138
           % capital Latin letters
1139
        4
           % A,B,C,
        5
1140
           А,В,
1141
        6
           % capital Greek letters
1142
           % \Gamma, \Delta, \Theta, \Lambda, \Xi, \Pi, \Sigma, \Upsilon, \Phi, \Psi,
1143
           \Gamma,\Delta,\Theta,\Lambda,\Xi,\Pi,\Sigma,\Phi,\Psi,\Omega,
1144
        9
           % small Greek letters
1145
       10
           \alpha,\beta,\pi,\nu,\omega,
1146
           \% small Latin letters:
       11
1147
       12
           % compare \nu, \nu, \nu, and \nu
1148
       13
1149
       14
           % digits
1150
       15
           0,1,9
1151
       16
1152
       17
1153
       18
1154
       19
           \subsection * { Math alphabets }
1155
       20
1156
       21
           If there are other symbols in place of Greek letters in a math
1157
       22
           alphabet, it uses T1 or OT1 font encoding instead of OML.
1158
       23
1159
       24
           \begin{eqnarray*}
1160
           \mbox{mathnormal} & & \teststring \\
           \mbox{mathit} & & \mathit{\teststring}\\
1161
1162
       27
           \mbox{mathrm} & & \mathrm{\teststring}\\
1163
       28
           \mbox{mathsf} & & \mathsf{\teststring}\\
mbox{mathtt} & & \mathtt{\teststring}
1164
       29
1165
       30
1166
       31
           \end{eqnarray*}
1167
       32
            New alphabets bold-italic, sans-serif-italic, and sans-serif-bold-
1168
                italic.
1169
           \begin{eqnarray*}
1170
       34
           \mbox{mathbfit}
                                 & & \mathbfit{\teststring}\\
       35
1171
           \mbox{mathsfit}
                                 & & \mathsfit{\teststring}\\
1172
       36
           \mbox{mathsfbfit} & & \mathsfbfit{\teststring}
1173
       37
           \end{eqnarray*}
1174
       38
1175
       39
           Do the math alphabets match?
1176
       40
1177
       41
1178
           \mathnormal {a x \alpha \omega}
1179
       43
           \mathbfit
                          {a x \alpha \omega}
1180
       44
           \mathsfbfit{a x \alpha \omega}
1181
       45
           \quad
1182
       46
           \mathsfbfit{T C \Theta \Gamma}
1183
       47
           \mathbfit
                          {T C \Theta \Gamma}
                        {T C \Theta \Gamma}
1184
       48
           \mathnormal
1185
       49
1186
       50
1187
       51
           \subsection *{ Vector symbols}
1188
       52
```

De La Salle University

```
1189
           Alphabetic symbols for vectors are boldface italic,
1190
           1191
       55
           while numeric ones (e.g. the zero vector) are bold upright,
           vec{a} + vec{0} = vec{a}.
1192
       56
1193
       57
1194
           \subsection *{Matrix symbols}
1195
       59
       60
1196
           Symbols for matrices are boldface italic, too: %
1197
       61
           \footnote{However, matrix symbols are usually capital letters whereas
1198
               vectors
1199
           are small ones. Exceptions are physical quantities like the force
1200
       63
           vector $\vec{F}$ or the electrical field $\vec{E}$.%
1201
       64
1202
       65
           $\matrixsym{\Lambda}=\matrixsym{E}\cdot\matrixsym{A}.$
1203
1204
       67
1205
       68
           \subsection*{Tensor symbols}
1206
       69
1207
       70
           Symbols for tensors are sans-serif bold italic,
1208
       71
1209
       72
           \[
1210
               \tensorsym{\alpha} = \tensorsym{e}\cdot\tensorsym{a}
       73
1211
       74
               \quad \Longleftrightarrow \quad
1212
       75
               \alpha_{ijl} = e_{ijk} \cdot a_{kl}.
           \]
1213
       76
1214
       77
1215
       78
1216
       79
           The permittivity tensor describes the coupling of electric field and
1217
       80
           displacement: \[
           \label{lem:constraint} $$\operatorname{D}=\operatorname{O}\times _{0}\times _{0}\times _{0}. $$
1218
       81
1219
       82
1220
       83
1221
       84
1222
       85
           \newpage
1223
       86
           \subsection * { Bold math version }
1224
       87
1225
           The ''bold'' math version is selected with the commands
       88
1226
       89
           \verb+\boldmath+ or \verb+\mathversion{bold}+
1227
       90
1228
       91
           {\boldmath
1229
       92
               \begin{eqnarray*}
1230
       93
               \mbox{mathnormal} & & \teststring \\
               \mbox{mathit} & & \mathit{\teststring}\\
1231
       94
1232
       95
               \mbox{mathrm} & & \mathrm{\teststring}\\
               \mbox{mathbf} & & \mathbf{\teststring}\\
mbox{mathsf} & & \mathsf{\teststring}\\
1233
       96
1234
       97
1235
       98
               \mbox{mathtt} &
                                & \mathtt{\teststring}
1236
       99
               \end{eqnarray*}
1237
      100
                New alphabets bold-italic, sans-serif-italic, and sans-serif-bold-
1238
                    italic.
1239
      101
               \begin{eqnarray*}
                                      & \mathbfit{\teststring}\\
1240
      102
               \mbox{mathbfit}
                                    &
      103
1241
               \mbox{mathsfit}
                                    & & \mathsfit{\teststring}\\
1242
      104
               \mbox{mathsfbfit} & & \mathsfbfit{\teststring}
1243
      105
               \end{eqnarray*}
1244
      106
1245
      107
               Do the math alphabets match?
```

De La Salle University

```
108
1246
1247
      109
1248
              \mathnormal {a x \alpha \omega}
      110
1249
                           {a x \alpha \omega}
      111
              \mathbfit
1250
              \mathsfbfit{a x \alpha \omega}
      112
1251
      113
              \quad
              \mathsfbfit{T C \Theta \Gamma}
1252
      114
1253
                           {T C \Theta \Gamma}
      115
              \mathbfit
1254
      116
              \mathnormal {T C \Theta \Gamma}
1255
      117
1256
      118
1257
      119
              \subsection*{Vector symbols}
1258
      120
1259
      121
              Alphabetic symbols for vectors are boldface italic,
1260
      122
              1261
      123
              while numeric ones (e.g. the zero vector) are bold upright,
1262
      124
              \vec{a} + \vec{0} = \vec{a}.
1263
      125
1264
      126
1265
      127
1266
      128
1267
      129
              \subsection *{Matrix symbols}
1268
      130
1269
      131
              Symbols for matrices are boldface italic, too: %
1270
      132
              \footnote{However, matrix symbols are usually capital letters whereas
1271
1272
      133
              are small ones. Exceptions are physical quantities like the force
1273
      134
              vector $\vec{F}$ or the electrical field $\vec{E}$.%
1274
      135
1275
      136
              $\matrixsym{\Lambda}=\matrixsym{E}\cdot\matrixsym{A}.$
1276
      137
1277
      138
1278
      139
              \subsection *{Tensor symbols}
1279
      140
1280
      141
              Symbols for tensors are sans-serif bold italic,
1281
      142
1282
      143
              1 [
                  \tensorsym{\alpha} = \tensorsym{e}\cdot\tensorsym{a}
1283
      144
1284
      145
                  \quad \Longleftrightarrow \quad
1285
      146
                  \alpha_{ijl} = e_{ijk} \cdot a_{kl}.
1286
      147
1287
      148
1288
      149
              The permittivity tensor describes the coupling of electric field and
      150
1289
              displacement: \[
1290
      151
              \c {D}=\ensuremath{\c D}=\ensuremath{\c C}\
      152
1292
```



B3 Abbreviation

1293

1294

1295

1296

1297

1298

1299

1300

1301

1303

1304

1305

1306

1307

1308

1309

1310

1311

1312

1313

1315

1316

1317

1318

1319

1320

1321

This section shows examples of the use of LATEX commands in conjunction with the items that are in the abbreviation.tex and in the glossary.tex files. Please see List. B.3. To lessen the LATEX compilation time, it is suggested that you use \acr{ } only for the first occurrence of the word to be abbreviated.

Again please see List. B.3. Here is an example of first use: alternating current (ac). Next use: ac. Full: alternating current (ac). Here's an acronym referenced using \acr : hyper-text markup language (html). And here it is again: html. If you are used to the glossaries package, note the difference in using \gls: hyper-text markup language (html). And again (no difference): hyper-text markup language (html). Here are some more entries:

- extensible markup language (xml) and cascading style sheet (css).
- Next use: xml and css.
- Full form: extensible markup language (xml) and cascading style sheet (css).
- Reset again.
- Start with a capital. Hyper-text markup language (html).
- Next: Html. Full: Hyper-text markup language (html).
- Prefer capitals? Extensible markup language (XML). Next: XML. Full: extensible markup language (XML).
- Prefer small-caps? Cascading style sheet (CSS). Next: CSS. Full: cascading style sheet (CSS).
- Resetting all acronyms.
- Here are the acronyms again:
- Hyper-text markup language (HTML), extensible markup language (XML) and cascading style sheet (CSS).
- Next use: HTML, XML and CSS.
- Full form: Hyper-text markup language (HTML), extensible markup language (XML) and cascading style sheet (CSS).



1323

• Provide your own link text: style sheet.

The verbatim LaTeX code of Sec. B3 is in List. B.3.

Listing B.3: Sample LATEX code for abbreviations usage

```
Again please see List.~\ref{lst:abbrv}. Here is an example of first use:
       \acr{ac}. Next use: \acr{ac}. Full: \gls{ac}. Here's an acronym
      referenced using \verb | \acr |: \acr{html}. And here it is again: \
      acr{html}. If you are used to the \texttt{glossaries} package, note
      difference): \gls{html}. Here are some more entries:
   \begin{itemize}
5
      \item \acr{xml} and \acr{css}.
7
      \item Next use: \acr{xml} and \acr{css}.
8
      \forall Full form: \gls{xml} and \gls{css}.
9
10
      \item Reset again. \glsresetall{abbreviation}
11
12
      \item Start with a capital. \Acr{html}.
13
14
15
      \item Next: \Acr{html}. Full: \Gls{html}.
16
      \item Prefer capitals? \renewcommand{\acronymfont}[1]{\
17
         MakeTextUppercase{#1}} \Acr{xml}. Next: \acr{xml}. Full: \gls{xml}
18
      \item Prefer small-caps? \renewcommand {\acronymfont}[1] {\textsc{#1}}
19
         \Acr{css}. Next: \acr{css}. Full: \gls{css}.
20
21
      \item Resetting all acronyms.\glsresetall{abbreviation}
22
23
      \item Here are the acronyms again:
24
25
      \item \Acr{html}, \acr{xml} and \acr{css}.
26
      \item Next use: \Acr{html}, \acr{xml} and \acr{css}.
27
28
      \item Full form: \Gls{html}, \gls{xml} and \gls{css}.
29
      \item Provide your own link text: \glslink{[textbf]css}{style}
31
32
   \end{itemize}
```



B4 Glossary

1324

1325

1327

1328

1329

1330

1331

1332

1333

1334

1335

1336

1337

This section shows examples of the use of \gls{} commands in conjunction with the items that are in the glossary.tex and notation.tex files. Note that entries in notation.tex are prefixed with "not: "label (see List. B.4).

Please make sure that the entries in notation.tex are those that are referenced in the LATEX document files used by this Thesis. Please comment out unused notations and be careful with the commas and brackets in notation.tex .

- Matrices are usually denoted by a bold capital letter, such as A. The matrix's (i, j)th element is usually denoted a_{ij} . Matrix I is the identity matrix.
- A set, denoted as S, is a collection of objects.
- The universal set, denoted as \mathcal{U} , is the set of everything.
- The empty set, denoted as \emptyset , contains no elements.
- The cardinality of a set, denoted as |S|, is the number of elements in the set.

The verbatim LaTeX code for the part of Sec. B4 is in List. B.4.

Listing B.4: Sample LATEX code for glossary and notations usage

```
\begin{itemize}
2
3
       \item \Glspl{matrix} are usually denoted by a bold capital letter,
           such as \mathbf{A}, The \left[ \mathbf{A}\right]. The \left[ \mathbf{A}\right], s \left( \mathbf{A}\right), the element is
           usually denoted a_{ij}. \Gls{matrix} $\mathbf{I}$ is the
           identity \gls{matrix}.
4
5
       \item A set, denoted as \gls{not:set}, is a collection of objects.
6
       \item The universal set, denoted as \gls{not:universalSet}, is the
           set of everything.
8
       \item The empty set, denoted as \gls{not:emptySet}, contains no
9
           elements.
10
       \item The cardinality of a set, denoted as \gls{not:cardinality}, is
11
           the number of elements in the set.
12
   \end{enumerate}
```



1338 B5 Figure

1339

1340

This section shows several ways of placing figures. PDFLATEX compatible files are PDF, PNG, and JPG. Please see the figure subdirectory.



Fig. B.1 A quadrilateral image example.



Fig. B.1 is a gray box enclosed by a dark border. List. B.5 shows the corresponding LATEX code.

Listing B.5: Sample LATEX code for a single figure

```
begin{figure}[!htbp]

centering

includegraphics[width=0.5\textwidth]{example}

caption{A quadrilateral image example.}

label{fig:example}

cend{figure}

cleardoublepage

fig.~\ref{fig:example} is a gray box enclosed by a dark border. List.~\

ref{lst:onefig} shows the corresponding \LaTeX \ code.

lend{figure}
```





(a) A sub-figure in the top row.



(b) A sub-figure in the middle row.





Listing B.6: Sample LATEX code for three figures on top of each other

```
\begin{figure}[!htbp]
   \centering
   \subbottom[A sub-figure in the top row.]{
   \includegraphics[width=0.35\textwidth]{example}
   \label{fig:top}
   \subbottom[A sub-figure in the middle row.]{
   \includegraphics[width=0.35\textwidth]{example}
10
   \label{fig:mid}
11
   \vertvfill
12
   \subbottom[A sub-figure in the bottom row.]{
13
14
   \includegraphics[width=0.35\textwidth]{example}
15
   \label{fig:botm}
16
17
   \caption{Figures on top of each other}
   \label{fig:tmb}
18
   \end{figure}
```





Loreni jasum dolor sit amet, consecteture allipicing elit. Ut parus elit, vestibulium ut, placerat ae, adipicing vitae, felis. Cumbitur dietum gravida mauris.

Nam aret bleva, nomanung even, consectente el, utputate a., naugan. Donce vitae elit. Dietum delit. Dietum elit. Dietu

- (a) A sub-figure in the upper-left corner.
- (b) A sub-figure in the upper-right corner.



Lerem ipsuum dober sit amet, consecteture afipiscing elit. Ut purus elit, vestilonlus ut, placerat ac, adiplecing vitae. Elis. Cumbhur detum garatis marsis.

White and the situation of the vestigation of the vestigation of the situation of th

- (c) A sub-figure in the lower-left corner.
- (d) A sub-figure in the lower-right corner

Fig. B.3 Four figures in each corner. See List. B.7 for the corresponding LATEX code.



Listing B.7: Sample LATEX code for the four figures

```
\begin{figure}[!htbp]
   \centering
   \subbottom[A sub-figure in the upper-left corner.]{
   \includegraphics[width=0.45\textwidth]{example}
   \label{fig:upprleft}
   \subbottom[A sub-figure in the upper-right corner.]{
   \includegraphics[width=0.45\textwidth]{example}
10
   \label{fig:uppright}
11
12
   \vfill
   \subbottom[A sub-figure in the lower-left corner.]{
13
   \includegraphics[width=0.45\textwidth]{example}
   \label{fig:lowerleft}
15
16
17
   \hfill
   \subbottom[A sub-figure in the lower-right corner]{
18
   \includegraphics[width=0.45\textwidth]{example}
19
20
   \label{fig:lowright}
21
   \verb|\caption{Four figures in each corner. See List.~\ref{lst:fourfigs} for
       the corresponding \LaTeX \ code.}
   \label{fig:fourfig}
   \end{figure}
```



1343 B6 Table

1344

This section shows an example of placing a table (a long one). Table B.1 are the triples.

TABLE B.1 FEASIBLE TRIPLES FOR HIGHLY VARIABLE GRID

Time (s)	Triple chosen	Other feasible triples
0	(1, 11, 13725)	(1, 12, 10980), (1, 13, 8235), (2, 2, 0), (3, 1, 0)
2745	(1, 12, 10980)	(1, 13, 8235), (2, 2, 0), (2, 3, 0), (3, 1, 0)
5490	(1, 12, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
8235	(1, 12, 16470)	(1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1, 0)
10980	(1, 12, 16470)	(1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1, 0)
13725	(1, 12, 16470)	(1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1, 0)
16470	(1, 13, 16470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
19215	(1, 12, 16470)	(1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1, 0)
21960	(1, 12, 16470)	(1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1, 0)
24705	(1, 12, 16470)	(1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1, 0)
27450	(1, 12, 16470)	(1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1, 0)
30195	(2, 2, 2745)	(2,3,0),(3,1,0)
32940	(1, 13, 16470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
35685	(1, 13, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
38430	(1, 13, 10980)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
41175	(1, 12, 13725)	(1, 13, 10980), (2, 2, 2745), (2, 3, 0), (3, 1, 0)
43920	(1, 13, 10980)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
46665	(2, 2, 2745)	(2,3,0),(3,1,0)
49410	(2, 2, 2745)	(2,3,0),(3,1,0)
52155	(1, 12, 16470)	(1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1, 0)
54900	(1, 13, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
57645	(1, 13, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
60390	(1, 12, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
63135	(1, 13, 16470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
65880	(1, 13, 16470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
68625	(2, 2, 2745)	(2, 3, 0), (3, 1, 0)
71370	(1, 13, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
74115	(1, 12, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
76860	(1, 13, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
79605	(1, 13, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0) (2, 2, 2745), (2, 3, 0), (3, 1, 0)
82350	(1, 12, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
85095	(1, 12, 13725)	(1, 13, 10980), (2, 2, 2745), (2, 3, 0), (3, 1, 0)
87840	(1, 13, 16470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
90585	(1, 13, 16470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0) (2, 2, 2745), (2, 3, 0), (3, 1, 0)
93330	(1, 13, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0) (2, 2, 2745), (2, 3, 0), (3, 1, 0)
96075	(1, 13, 16470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
98820	(1, 13, 16470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0) (2, 2, 2745), (2, 3, 0), (3, 1, 0)
101565	(1, 13, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0) (2, 2, 2745), (2, 3, 0), (3, 1, 0)
104310	(1, 13, 16470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
107055	(1, 13, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0) (2, 2, 2745), (2, 3, 0), (3, 1, 0)
109800	(1, 13, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0) (2, 2, 2745), (2, 3, 0), (3, 1, 0)
112545	(1, 13, 13723)	(1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1, 0)
115290	(1, 12, 10470)	(1, 13, 13723), (2, 2, 2743), (2, 3, 0), (3, 1, 0) (2, 2, 2745), (2, 3, 0), (3, 1, 0)
118035	(1, 13, 10470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0) (2, 2, 2745), (2, 3, 0), (3, 1, 0)
120780	(1, 13, 16470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
123525	(1, 13, 10470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0) (2, 2, 2745), (2, 3, 0), (3, 1, 0)
	(-, 10, 10, 20)	Continued on next page

Continued on next page



Continued from previous page

Time (s)	Triple chosen	Other feasible triples
126270	(1, 12, 16470)	(1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1, 0)
129015	(2, 2, 2745)	(2,3,0),(3,1,0)
131760	(2, 2, 2745)	(2,3,0),(3,1,0)
134505	(1, 13, 16470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
137250	(1, 13, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
139995	(2, 2, 2745)	(2,3,0),(3,1,0)
142740	(2, 2, 2745)	(2,3,0),(3,1,0)
145485	(1, 12, 16470)	(1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1, 0)
148230	(2, 2, 2745)	(2,3,0),(3,1,0)
150975	(1, 13, 16470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
153720	(1, 12, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
156465	(1, 13, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
159210	(1, 13, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
161955	(1, 13, 16470)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)
164700	(1, 13, 13725)	(2, 2, 2745), (2, 3, 0), (3, 1, 0)

1345



List. B.8 shows the corresponding LATEX code.

Listing B.8: Sample LATEX code for making typical table environment

```
1347
           \begin{center}
1348
        1
1349
        2
           {\scriptsize
1350
           \beta_{0.0} = \frac{1}{2}
1351
           \caption{Feasible triples for highly variable grid} \label{tab:triple_
1352
1353
               grid} \\
1354
           \hline
1355
           \hline
           \textbf{Time (s)} &
1356
        7
        8
           \textbf{Triple chosen} &
1357
1358
        9
           \textbf{Other feasible triples} \\
1359
       10
           \hline
1360
       11
           \endfirsthead
           \multicolumn{3}{c}%
1361
       12
1362
           {\textit{Continued from previous page}} \\
       13
1363
       14
           \hline
1364
       15
           \hline
1365
       16
           \textbf{Time (s)} &
1366
       17
           \textbf{Triple chosen} &
1367
       18
           \textbf{Other feasible triples} \\
1368
       19
           \hline
1369
       20
           \endhead
1370
       21
           \hline
1371
       22
           \multicolumn{3}{r}{\textit{Continued on next page}} \\
1372
       23
           \endfoot
1373
       24
           \hline
1374
       25
           \endlastfoot
1375
       26
           \hline
1376
       27
           0 & (1, 11, 13725) & (1, 12, 10980), (1, 13, 8235), (2, 2, 0), (3, 1, 0)
1377
       28
1378
           2745 & (1, 12, 10980) & (1, 13, 8235), (2, 2, 0), (2, 3, 0), (3, 1, 0)
1379
       29
1380
           5490 & (1, 12, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1381
1382
       31
           8235 & (1, 12, 16470) & (1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1,
1383
           10980 & (1, 12, 16470) & (1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1,
1384
       32
1385
                0) \\
1386
           13725 & (1, 12, 16470) & (1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1, 1)
                0) \\
1387
           16470 & (1, 13, 16470) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1388
       34
           19215 & (1, 12, 16470) & (1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1,
1389
1390
                0) \\
1391
           21960 & (1, 12, 16470) & (1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1,
                0) \\
1392
           24705 & (1, 12, 16470) & (1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1,
1393
       37
                0) \\
1394
           27450 & (1, 12, 16470) & (1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1,
1395
       38
                0) \\
1396
1397
       39
           30195 & (2, 2, 2745) & (2, 3, 0), (3, 1, 0) \\
           32940 \& (1, 13, 16470) \& (2, 2, 2745), (2, 3, 0), (3, 1, 0) \setminus
1398
       40
1399
           35685 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1400
          38430 & (1, 13, 10980) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
```

De La Salle University

```
41175 & (1, 12, 13725) & (1, 13, 10980), (2, 2, 2745), (2, 3, 0), (3, 1,
1401
1402
            43920 & (1, 13, 10980) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1403
            46665 & (2, 2, 2745) & (2, 3, 0), (3, 1, 0) \\
        45
1404
1405
            49410 & (2, 2, 2745) & (2, 3, 0), (3, 1, 0) \\
       46
1406
            52155 & (1, 12, 16470) & (1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3, 1,
1407
                 0) \\
            54900 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1408
       48
1409
        49
            57645 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0)
            60390 & (1, 12, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0)
1410
       50
                                                                                //
            63135 & (1, 13, 16470) & (2, 2, 2745), (2, 3, 0), (3, 1, 0)
1411
1412
        52
            65880 & (1, 13, 16470) & (2, 2, 2745), (2, 3, 0), (3, 1, 0)
           68625 & (2, 2, 2745) & (2, 3, 0), (3, 1, 0) \\
1413
       53
            71370 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1414
1415
           74115 & (1, 12, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1416
           76860 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
            79605 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
       57
1417
           82350 & (1, 12, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
85095 & (1, 12, 13725) & (1, 13, 10980), (2, 2, 2745), (2, 3, 0), (3, 1,
1418
       58
1419
1420
           87840 & (1, 13, 16470) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1421
           90585 & (1, 13, 16470) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1422
       61
1423
           93330 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \
1424
           96075 & (1, 13, 16470) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
           98820 & (1, 13, 16470) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1425
       64
       65
            101565 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1426
1427
       66
            104310 & (1, 13, 16470) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
           107055 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
109800 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1428
       67
1429
       68
            112545 & (1, 12, 16470) & (1, 13, 13725), (2, 2, 2745), (2, 3, 0),
1430
       69
               1, 0) \\
1431
            115290 & (1, 13, 16470) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1432
1433
            118035 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
            120780 & (1, 13, 16470) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \
1434
           123525 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
126270 & (1, 12, 16470) & (1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3,
1435
       73
1436
1437
               1, 0)
                      11
1438
            129015 &
                      (2, 2, 2745) & (2, 3, 0), (3, 1, 0) \\
            131760 & (2, 2, 2745) & (2, 3, 0), (3, 1, 0) \\
1439
1440
            134505 & (1, 13, 16470) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
       77
1441
       78
            137250 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1442
            139995 & (2, 2, 2745) & (2, 3, 0), (3, 1, 0) \\
            142740 & (2, 2, 2745) & (2, 3, 0), (3, 1, 0) \\
       80
1443
1444
       81
            145485 & (1, 12, 16470) & (1, 13, 13725), (2, 2, 2745), (2, 3, 0), (3,
1445
           148230 & (2, 2, 2745) & (2, 3, 0), (3, 1, 0) \\
150975 & (1, 13, 16470) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1446
1447
       83
            153720 & (1, 12, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1448
1449
            156465 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1450
            159210 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1451
            161955 & (1, 13, 16470) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
            164700 & (1, 13, 13725) & (2, 2, 2745), (2, 3, 0), (3, 1, 0) \\
1452
1453
       89
            \end{tabularx}
1454
       90
           \end{center}
1456
```



B7 Algorithm or Pseudocode Listing

1458 1459 1460 Table B.2 shows an example pseudocode. Note that if the pseudocode exceeds one page, it can mean that its implementation is not modular. List. B.9 shows the corresponding LATEX code.

Table B.2 Calculation of $y = x^n$

Input(s):

n : nth power; $n \in \mathbb{Z}^+$ x : base value; $x \in \mathbb{R}^+$

Output(s):

y: result; $y \in \mathbb{R}^+$

Require: $n \ge 0 \lor x \ne 0$

Ensure: $y = x^n$

1: $y \Leftarrow 1$

2: if n < 0 then

 $X \Leftarrow 1/x$

4: $N \Leftarrow -n$

5: else

6: $X \Leftarrow x$

7: $N \Leftarrow n$

8: **end if**

9: while $N \neq 0$ do

10: **if** N is even **then**

11: $X \Leftarrow X \times X$

12: $N \Leftarrow N/2$ 13: **else** { N is odd

13: **else** $\{N \text{ is odd}\}$ 14: $y \Leftarrow y \times X$

15: $N \Leftarrow N - 1$

16: **end if**

17: end while



Listing B.9: Sample LATEX code for algorithm or pseudocode listing usage

```
\begin{table}[!htbp]
  1
  2
                      \caption{Calculation of $y = x^n$}
  3
                      \label{tab:calcxn}
                      {\footnotesize
  4
                      \begin{tabular}{111}
  5
                      \hline
  7
                      \hline
                      {\bfseries Input(s):} & & \\
  8
  9
                      n & : & nth power; n \in \mathbb{Z}^{+}
10
                      x & : & base value; x \in \mathbb{R}^{+} \\
11
12
                      {\bfseries Output(s):} & & \\
                      $y$ & : & result; $y \in \mathbb{R}^{+}$ \\
13
14
                      \hline
15
                      \hline
16
17
                      \end{tabular}
18
19
                      \begin{algorithmic}[1]
20
                      {\normalfont} \{ \normalfont 
                                \REQUIRE $n \geq 0 \vee x \neq 0$
21
                                \ENSURE $y = x^n$
22
                               \STATE $y \Leftarrow 1$
23
                                \IF { n < 0 }
24
25
                                                     \STATE $X \Leftarrow 1 / x$
                                                     \STATE $N \Leftarrow -n$
26
27
                                \ELSE
28
                                                     \STATE $X \Leftarrow x$
29
                                                     \STATE $N \Leftarrow n$
                                \ENDIF
30
                                \WHILE{$N \neq 0$}
31
32
                                                     \IF{$N$ is even}
33
                                                                         \STATE $X \Leftarrow X \times X$
                                                                         \STATE $N \Leftarrow N / 2$
34
35
                                                     \ELSE[$N$ is odd]
36
                                                                         \STATE $y \Leftarrow y \times X$
37
                                                                         \STATE $N \Leftarrow N - 1$
38
                                                    \ENDIF
                                \ENDWHILE
39
40
41
                      \end{algorithmic}
            \end{table}
```



B8 Program/Code Listing

 List. B.10 is a program listing of a C code for computing Fibonacci numbers by calling the actual code. Please see the code subdirectory.

Listing B.10: Computing Fibonacci numbers in C (./code/fibo.c)

```
/* fibo.c -- It prints out the first N Fibonacci
2
                  numbers.
3
   #include <stdio.h>
7
   int main(void) {
8
        int n;
                       /* Number of fibonacci numbers we will print */
9
                       /* Index of fibonacci number to be printed next */
        int i;
        int current; /* Value of the (i)th fibonacci number */
10
11
                      /st Value of the (i+1)th fibonacci number st/
        int next;
12
        int twoaway; /* Value of the (i+2)th fibonacci number */
13
        printf("HowumanyuFibonacciunumbersudouyouuwantutoucompute?u");
14
        scanf("%d", &n);
15
16
        if (n \le 0)
           printf("The\sqcupnumber\sqcupshould\sqcupbe\sqcuppositive.\setminusn");
17
18
        else {
          printf("\n\n\tI_\tuFibonacci(I)\n\t=========\n");
19
20
          next = current = 1;
21
          for (i=1; i<=n; i++) {
22
       printf("\t^d_{\sqcup}\t^d_{\sqcup}d\n", i, current);
       twoaway = current+next;
current = next;
23
24
               = twoaway;
25
       next
27
   }
28
29
30
   /* The output from a run of this program was:
31
32
   How many Fibonacci numbers do you want to compute? 9
33
34
           Fibonacci(I)
35
36
37
       2
             1
38
       3
             2
39
             3
       4
40
       5
             5
41
       6
             8
42
       7
             13
43
       8
            21
44
45
46
```



List. B.11 shows the corresponding LATEX code.

Listing B.11: Sample LaTeX code for program listing

List.~\ref{lst:fib_c} is a program listing of a C code for computing Fibonacci numbers by calling the actual code. Please see the \verb| code | subdirectory.

B9 Referencing

Referencing chapters: This appendix is in Appendix B, which is about examples in using various LaTeX commands.

Referencing sections: This section is Sec. B9, which shows how to refer to the locations of various labels that have been placed in the LaTeX files. List. B.12 shows the corresponding LaTeX code.

Listing B.12: Sample L^AT_EX code for referencing sections

Referencing sections: This section is Sec.~\ref{sec:ref}, which shows how to refer to the locations of various labels that have been placed in the \LaTeX \ files. List.~\ref{lst:refsec} shows the corresponding \LaTeX \ code.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.



B9.1 A subsection

Referencing subsections: This section is Sec. B9.1, which shows how to refer to a subsection. List. B.13 shows the corresponding LaTeX code.

Listing B.13: Sample LATEX code for referencing subsections

Referencing subsections: This section is Sec.~\ref{sec:subsec}, which shows how to refer to a subsection. List.~\ref{lst:refsub} shows the corresponding \LaTeX \ code.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.



B9.1.1 A sub-subsection

Referencing sub-subsections: This section is Sec. B9.1.1, which shows how to refer to a sub-subsection. List. B.14 shows the corresponding LaTeX code.

Listing B.14: Sample LATEX code for referencing sub-subsections

Referencing sub-subsections: This section is Sec. \ref{sec:subsubsec},
 which shows how to refer to a sub-subsection. List. \ref{lst:
 refsubsub} shows the corresponding \LaTeX \ code.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.



1504 B10 Index

1505

1506

1507

1508

1510

1511

1512

For key words or topics that are expected (or the user would like) to appear in the Index, use index{key}, where key is an example keyword to appear in the Index. For example, Fredholm integral and Fourier operator of the following paragraph are in the Index.

If we make a very large matrix with complex exponentials in the rows (i.e., cosine real parts and sine imaginary parts), and increase the resolution without bound, we approach the kernel of the Fredholm integral equation of the 2nd kind, namely the Fourier operator that defines the continuous Fourier transform.

List. B.15 is a program listing of the above-mentioned paragraph.

Listing B.15: Sample LATEX code for Index usage

If we make a very large matrix with complex exponentials in the rows (i. e., cosine real parts and sine imaginary parts), and increase the resolution without bound, we approach the kernel of the \index{Fredholm integral} Fredholm integral equation of the 2nd kind, namely the \index{Fourier} Fourier operator that defines the continuous Fourier transform.



B11 Adding Relevant PDF Pages (e.g. Standards, Datasheets, Specification Sheets, Application Notes, etc.)

1513

1514

1515

1516

1517

Selected PDF pages can be added (see List. B.16), but note that the options must be tweaked. See the manual of pdfpages for other options.

Listing B.16: Sample LATEX code for including PDF pages

```
1 \includepdf[pages={8-10},%
2 offset=3.5mm -10mm,%
3 scale=0.73,%
4 frame]
5 {./reference/Xilinx2015-UltraScaleArchitectureOverview.pdf}
```



EXILINX.

UltraScale Architecture and Product Overview

Virtex UltraScale FPGA Feature Summary

Table 6: Virtex UltraScale FPGA Feature Summary

	VU065	VU080	VU095	VU125	VU160	VU190	VU440
Logic Cells	626,640	780,000	940,800	1,253,280	1,621,200	1,879,920	4,432,680
CLB Flip-Flops	716,160	891,424	1,075,200	1,432,320	1,852,800	2,148,480	5,065,920
CLB LUTs	358,080	445,712	537,600	716,160	926,400	1,074,240	2,532,960
Maximum Distributed RAM (Mb)	4.8	3.9	4.8	9.7	12.7	14.5	28.7
Block RAM/FIFO w/ECC (36Kb each)	1,260	1,421	1,728	2,520	3,276	3,780	2,520
Total Block RAM (Mb)	44.3	50.0	60.8	88.6	115.2	132.9	88.6
CMT (1 MMCM, 2 PLLs)	10	16	16	20	30	30	30
I/O DLLs	40	64	64	80	120	120	120
Fractional PLLs	5	8	8	10	15	15	0
Maximum HP I/Os ⁽¹⁾	468	780	780	780	650	650	1,404
Maximum HR I/Os ⁽²⁾	52	52	52	104	52	52	52
DSP Slices	600	672	768	1,200	1,560	1,800	2,880
System Monitor	1	1	1	2	3	3	3
PCIe Gen3 x8	2	4	4	4	5	6	6
150G Interlaken	3	6	6	6	8	9	0
100G Ethernet	3	4	4	6	9	9	3
GTH 16.3Gb/s Transceivers	20	32	32	40	52	60	48
GTY 30.5Gb/s Transceivers	20	32	32	40	52	60	0

- Notes:
 1. HP = High-performance I/O with support for I/O voltage from 1.0V to 1.8V.
- 2. HR = High-range I/O with support for I/O voltage from 1.2V to 3.3V.

DS890 (v2.1) April 27, 2015 **Preliminary Product Specification** www.xilinx.com



EXILINX.

UltraScale Architecture and Product Overview

Virtex UltraScale Device-Package Combinations and Maximum I/Os

Table 7: Virtex UltraScale Device-Package Combinations and Maximum I/Os

	Package	VU065	VU080	VU095	VU125	VU160	VU190	VU440
Package ⁽¹⁾⁽²⁾⁽³⁾	Dimensions (mm)	HR, HP GTH, GTY						
FFVC1517	40x40	52, 468 20, 20	52, 468 20, 20	52, 468 20, 20				
FFVD1517	40x40		52, 286 32, 32	52, 286 32, 32				
FLVD1517	40x40				52, 286 40, 32			
FFVB1760	42.5x42.5		52, 650 32, 16	52, 650 32, 16				
FLVB1760	42.5x42.5				52, 650 36, 16			
FFVA2104	47.5x47.5		52, 780 28, 24	52, 780 28, 24				
FLVA2104	47.5x47.5				52, 780 28, 24			
FFVB2104	47.5x47.5		52, 650 32, 32	52, 650 32, 32				
FLVB2104	47.5x47.5				52, 650 40, 36			
FLGB2104	47.5x47.5					52, 650 40, 36	52, 650 40, 36	
FFVC2104	47.5x47.5			52, 364 32, 32				
FLVC2104	47.5x47.5				52, 364 40, 40			
FLGC2104	47.5x47.5					52, 364 52, 52	52, 364 52, 52	
FLGB2377	50x50							52, 1248 36, 0
FLGA2577	52.5x52.5						0, 448 60, 60	
FLGA2892	55x55							52, 1404 48, 0

- Go to Ordering Information for package designation details.
 All packages have 1.0mm ball pitch.
 Packages with the same last letter and number sequence, e.g., A2104, are footprint compatible with all other UltraScale architecture-based devices with the same sequence. The footprint compatible devices within this family are outlined. See the UltraScale Architecture Product Selection Guide for details on inter-family migration.

DS890 (v2.1) April 27, 2015 **Preliminary Product Specification** www.xilinx.com



EXILINX.

UltraScale Architecture and Product Overview

Virtex UltraScale+ FPGA Feature Summary

Table 8: Virtex UltraScale+ FPGA Feature Summary

	VU3P	VU5P	VU7P	VU9P	VU11P	VU13P
Logic Cells	689,640	1,051,010	1,379,280	2,068,920	2,147,040	2,862,720
CLB Flip-Flops	788,160	1,201,154	1,576,320	2,364,480	2,453,760	3,271,680
CLB LUTs	394,080	600,577	788,160	1,182,240	1,226,880	1,635,840
Max. Distributed RAM (Mb)	12.0	18.3	24.1	36.1	34.8	46.4
Block RAM/FIFO w/ECC (36Kb each)	720	1,024	1,440	2,160	2,016	2,688
Block RAM (Mb)	25.3	36.0	50.6	75.9	70.9	94.5
UltraRAM Blocks	320	470	640	960	1,152	1,536
UltraRAM (Mb)	90.0	132.2	180.0	270.0	324.0	432.0
CMTs (1 MMCM and 2 PLLs)	10	20	20	30	12	16
Max. HP I/O ⁽¹⁾	520	832	832	832	624	832
DSP Slices	2,280	3,474	4,560	6,840	8,928	11,904
System Monitor	1	2	2	3	3	4
GTY Transceivers 32.75Gb/s	40	80	80	120	96	128
PCIe Gen3 x16 and Gen4 x8	2	4	4	6	3	4
150G Interlaken	3	4	6	9	9	12
100G Ethernet w/RS-FEC	3	4	6	9	6	8

Virtex UltraScale+ Device-Package Combinations and Maximum I/Os

Table 9: Virtex UltraScale+ Device-Package Combinations and Maximum I/Os

Package	Package	VU3P	VU5P	VU7P	VU9P	VU11P	VU13P
(1)(2)(3)	Dimensions (mm)	HP, GTY	HP, GTY	HP, GTY	HP, GTY	HP, GTY	HP, GTY
FFVC1517	40x40	520, 40					
FLVF1924	45x45					624, 64	
FLVA2104	47.5x47.5		832, 52	832, 52	832, 52		
FHVA2104	52.5x52.5 ⁽⁴⁾						832, 52
FLVB2104	47.5x47.5		702, 76	702, 76	702, 76	624, 76	
FHVB2104	52.5x52.5 ⁽⁴⁾						702, 76
FLVC2104	47.5x47.5		416, 80	416, 80	416, 104	416, 96	
FHVC2104	52.5x52.5 ⁽⁴⁾						416, 104
FLVA2577	52.5x52.5				448, 120	448, 96	448, 128

- 1. Go to Ordering Information for package designation details.
- 2. All packages have 1.0mm ball pitch.
- Packages with the same last letter and number sequence, e.g., A2104, are footprint compatible with all other UltraScale devices with the same sequence. The footprint compatible devices within this family are outlined.
 These 52.5x52.5mm overhang packages have the same PCB ball footprint as the corresponding 47.5x47.5mm packages (i.e., the same last letter and number sequence) and are footprint compatible.

DS890 (v2.1) April 27, 2015 **Preliminary Product Specification** www.xilinx.com

10

^{1.} HP = High-performance I/O with support for I/O voltage from 1.0V to 1.8V.

Shape and the state of the stat	r 0 1	1 .	•	•
De l	La Sal	le U	nive	rsity

Appendix C PUBLICATION LIST AND AWARD

Journal

1524 1. ...

1521

1522

1525 2. ...

1526 Conference

1527 1. ...

1528 2. ...



	Oth one
1529	Others

1530 1. ...

1531 2. ...

1532 Award

1533 1. ...

1534 2. ...



Appendix D VITA

 Junlae Cheong is a sixth year student at De La Salle University. He is currently taking up his B.Sc. Computer Engineering studies. His strengths in the field are electronics circuit design and configuration. His fields of interest are electronics hardware and computer microprocessor.

Rohit P. Nihalani is a third year student at De La Salle University. He is currently taking up his B.Sc. Computer Engineering studies. He has designed communication systems which covers basic AM radios. His fields of interest are digital communications and computer networks.

Noel B. Paulino is a third year student at De La Salle University. He is currently taking up his B.Sc. Computer Engineering studies. His strengths in the field are microcontroller program design and advanced electronics.

Ryback Tyrone G. Po is a fourth year student at De La Salle University. He is currently taking up his B.Sc. Computer Engineering studies. He has designed and

De La Salle Univer	csity

INDEX

contributions, 38

Fourier operator, 79 Fredholm integral, 79