



Comment	Description	Designator	Footprint	LibRef	Quantity
100nF	Capacitor SMD 1206	C1, C2	Cap 1206	Cap 1206	2
SS14	Dán	D1, D2, D3, D4	DIODESMA	Diode SS14 (1N5819)	4
EncoderA	Cắm	H1	XH2.54M-4	Header 4P2.54 Duc Thang	1
EncoderB	Cắm	H2	XH2.54M-4	Header 4P 2.54 Duc Thang	1
PWMA	Cắm	H3	XH2.54M-4	Header 4P 2.54 Duc Thang	1
PWMB	Cắm	H4	XH2.54M-4	Header 4P 2.54 Duc Thang	1
UART1	Cắm	H5	XH2.54M-4	Header 4P 2.54 Duc Thang	1
UART2	Cắm	H6	XH2.54M-4	Header 4P 2.54 Duc Thang	1
I2C1	Cắm	H7	XH2.54M-4	Header 4P 2.54 Duc Thang	1
I2C2	Cắm	H8	XH2.54M-4	Header 4P 2.54 Duc Thang	1
ADC1	Cắm	H9	XH2.54M-4	Header 4P 2.54 Duc Thang	1
ADC2	Cắm	H10	XH2.54M-4	Header 4P2.54 Duc Thang	1
24V Vin		H11	barrier_terminal	Barrier Terminal	1
H-Bridge 1		H12	barrier_terminal	Barrier Terminal	1
H-Bridge 2		H13	barrier_terminal	Barrier Terminal	1
		JI	SAMTEC_TSW-101-07- G-T-LL	TSW-101-07-G-T-LL	1
	TERMINAL BLOCK, PCB, 2WAY, 26- 12AWG; Connector Type: PCB Terminal Block; Connector Mounting: PCB; Pitch Spacing: 5.08	æ	MULTICOMP_MC0000 48	MC000048	1
470	Dán	R1, R2	tro smd 1206	Tro 1206 1% 470k	2
STM32F4DISCOVERY	Development kit: ARM ST; pin strips, pin header; No.of	TB1	MODULE_STM32F4DIS COVERY	STM32F4DISCOVERY	1