



Comment	Description	Designator	Footprint	LibRef	Quantity
Male Header 2.54mm 10x2 Pin		CN1, CN3	HDR2X10	HDR-10x2-M	2
Header 20X2	Header, 20- Pin, Dual row	CN2, CN4	HDR2X20	Header 20X2	2
Header 10X1_Female	Header, 10- Pin, Single row,female	CN5	HDR1X10	Header 10X1_Female	1
Header 8X1_Female	Header, 8-Pin, Single row,female	CN6, CN9	HDR1X8	Header 8X1_Female	2
Header 6	Header, 6-Pin	CN7, CN10	HDR1X6	Header 6	2
Header 6X1_Female	Header, 6-Pin, Single row,female	CN8	HDR1X6	Header 6X1_Female	1
Header 8X2	Header, 8-Pin, Dual row	CN13	HDR2X8	Header 8X2	1
Header 4X2	Header, 4-Pin, Dual row	CN14	HDR2X4	Header 4X2	1
Header 10	Header, 10-Pin	CN15, CN16	HDR1X10	Header 10	2
Header 8	Header, 8-Pin	CN17, CN18	HDR1X8	Header 8	2
Header 2	Header, 2-Pin	CN19, J1	HDR1X2	Header 2	2
Header 3	Header, 3-Pin	CN20	HDR1X3	Header 3	1
B6B-ZR(LF)(SN)	ZR Series 1.5 mm Pitch 6 Position Through Hole Top Entry Shrouded Header	JM1, JM2	*JST_B6B- ZR(LF)(SN)	B6B-ZR(LF)(SN)	2
BLM15AX601S N1D	Ferrite Beads 0402 600ohms	L1	0402FB	BLM15AX601S N1D	1
10K	0402 Chip Resistor	R1	0402R	0402-R	1
Close	Circuit Breaker	SB1, SB3	0603SB	Circuit Breaker	2
Open	Circuit Breaker	SB2, SB4	0603SB	Circuit Breaker	2