

JUBAO聚宝
NINGBO JUBAO ELECTRICAL TECHNICAL

📍 No.58, Jing 7th Road, Fuhai Industry Zone, Cixi, Ningbo City, Zhejiang Province, China
📠 +86-0574-58584005 ☎ +86-0574-58584001 🌐 www.jubaoelectrical.com

JUBAO聚宝
NINGBO JUBAO ELECTRICAL TECHNICAL
www.jubaoelectrical.com

WATER DISPENSER, AIR COOLER
ELECTRIC FAN, TOWER FAN, HEATER





► CONTENTS

Water Dispenser

01~06

Air Cooler

07~14

Electric Fan

15~20

Tower Fan

21~24

Heater

25~28

► ABOUT US

NINGBO JUBAO Electrical Technology CO., LTD., was founded in 2007, is a private key factory integrating productation researching, developing, manufacturing, saleing and servicing. At present, the company covers an area of more than 35000 square meters, more than 500 employees, with more than 60 senior technical management personnel of various types, specializing in the production of water dispenser, water purifier, fan, heater, cooling fan and other products.

In recent years, the company has invested more than one hundred million in setting up 20 domestic first-class production line and equipped with perfect testing equipment. Our annual production capacity can be more than 5 million units in water dispenser, water purifier, fan and cooling fan. Also we are in the leading position on the research and development for water dispenser and water purifier.

► Authentication



ROHS

SASO



Water Dispenser

Features/Description

- ◆ Hot and cold water
- ◆ Uploading type
- ◆ With storage cabinet
- ◆ NEW ABS material of plastic parts
- ◆ Rated voltage: **220-240V**
- ◆ Rated frequency: **50/60Hz**
- ◆ R134a compressor cooling
- ◆ Refrigerant: **R134a/45g**
- ◆ Heating power:**550W**
- ◆ Cooling power: **100W**
- ◆ Cooling rated current: **0.65A**
- ◆ Cooling tank: **2.0L**
- ◆ Heating tank: **1.0L**
- ◆ Cooling capability: $\geq 2L/h, 5\sim 10^{\circ}C$
- ◆ Heating capability: $\geq 5L/h, 85\sim 95^{\circ}C$
- ◆ Water tank material: **stainless steel**
- ◆ Silicon water outlet pipe
- ◆ 3*0.75mm² cable with 1.5M length

WD-1001S

- ◆ N.W./G.W.: 13.5kg/15.5kg
- ◆ Packing Size: 330x340x1020mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 238/476/580



Features/Description

- ◆ Hot and cold water
- ◆ Uploading type
- ◆ With storage cabinet
- ◆ NEW ABS material of plastic parts
- ◆ Rated voltage: **220-240V**
- ◆ Rated frequency: **50/60Hz**
- ◆ R134a compressor cooling
- ◆ Refrigerant: **R134a/45g**
- ◆ Heating power:**550W**
- ◆ Cooling power: **100W**
- ◆ Cooling rated current: **0.65A**
- ◆ Cooling tank: **2.0L**
- ◆ Heating tank: **1.0L**
- ◆ Cooling capability: $\geq 2L/h, 5\sim 10^{\circ}C$
- ◆ Heating capability: $\geq 5L/h, 85\sim 95^{\circ}C$
- ◆ Water tank material: **stainless steel**
- ◆ Silicon water outlet pipe
- ◆ 3*0.75mm² cable with 1.5M length



WD-1005S

- ◆ N.W./G.W.: 11.0kg/12.0kg
- ◆ Packing Size: 320x310x850mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 290/580/780



WD-1003S

- ◆ N.W./G.W.: 11.0kg/12.0kg
- ◆ Packing Size: 320x310x850mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 290/580/780



WD-1004S

- ◆ N.W./G.W.: 11.0kg/12.0kg
- ◆ Packing Size: 320x310x850mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 290/580/780



WD-1007S

- ◆ N.W./G.W.: 11.0kg/12.0kg
- ◆ Packing Size: 320x310x850mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 290/580/780



WD-1006S

- ◆ N.W./G.W.: 11.0kg/12.0kg
- ◆ Packing Size: 320x310x850mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 290/580/780

Features/Description

- ◆ Hot and cold water
- ◆ Uploading type
- ◆ With storage cabinet
- ◆ NEW ABS material of plastic parts
- ◆ Rated voltage: **220-240V**
- ◆ Rated frequency: **50/60Hz**
- ◆ R134a compressor cooling
- ◆ Refrigerant: **R134a/45g**
- ◆ Heating power: **550W**
- ◆ Cooling power: **100W**
- ◆ Cooling rated current: **0.65A**
- ◆ Cooling tank: **2.0L**
- ◆ Heating tank: **1.0L**
- ◆ Cooling capability: $\geq 2\text{L}/\text{h}, 5\sim 10^\circ\text{C}$
- ◆ Heating capability: $\geq 5\text{L}/\text{h}, 85\sim 95^\circ\text{C}$
- ◆ Water tank material: **stainless steel**
- ◆ Silicon water outlet pipe
- ◆ 3*0.75mm² cable with 1.5M length

**WD-1008S****WD-1009S****WD-1010S****WD-1011S****WD-1008S-X3****WD-1011S-X3**

- ◆ N.W./G.W.: 13.5kg/15.5kg
- ◆ Packing Size: 330x330x990mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 238/476/625

- ◆ N.W./G.W.: 13.5kg/15.5kg
- ◆ Packing Size: 330x330x990mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 238/476/625

- ◆ N.W./G.W.: 13.5kg/15.5kg
- ◆ Packing Size: 330x330x990mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 238/476/625

- ◆ N.W./G.W.: 13.5kg/15.5kg
- ◆ Packing Size: 330x330x990mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 238/476/625



Features/Description

- ◆ Hot and cold water
- ◆ Uploading type
- ◆ With storage cabinet
- ◆ NEW ABS material of plastic parts
- ◆ Rated voltage: **220-240V**
- ◆ Rated frequency: **50/60Hz**
- ◆ R134a compressor cooling
- ◆ Refrigerant: **R134a/45g**
- ◆ Heating power:**550W**
- ◆ Cooling power: **100W**
- ◆ Cooling rated current: **0.65A**
- ◆ Cooling tank: **2.0L**
- ◆ Heating tank: **1.0L**
- ◆ Cooling capability: $\geq 2\text{L}/\text{h}, 5\sim 10^\circ\text{C}$
- ◆ Heating capability: $\geq 5\text{L}/\text{h}, 85\sim 95^\circ\text{C}$
- ◆ Water tank material: **stainless steel**
- ◆ Silicon water outlet pipe
- ◆ 3*0.75mm² cable with 1.5M length

**WD-1003T****WD-1004T****Features/Description**

- ◆ Hot and cold water
- ◆ Uploading type
- ◆ With storage cabinet
- ◆ NEW ABS material of plastic parts
- ◆ Rated voltage: **220-240V**
- ◆ Rated frequency: **50/60Hz**
- ◆ R134a compressor cooling
- ◆ Refrigerant: **R134a/45g**
- ◆ Heating power:**550W**
- ◆ Cooling power: **100W**
- ◆ Cooling rated current: **0.65A**
- ◆ Cooling tank: **2.0L**
- ◆ Heating tank: **1.0L**
- ◆ Cooling capability: $\geq 2\text{L}/\text{h}, 5\sim 10^\circ\text{C}$
- ◆ Heating capability: $\geq 5\text{L}/\text{h}, 85\sim 95^\circ\text{C}$
- ◆ Water tank material: **stainless steel**
- ◆ Silicon water outlet pipe
- ◆ 3*0.75mm² cable with 1.5M length

**WD-1008T****WD-1009T****WD-1005T****WD-1006T****WD-1007T****WD-1011T****WD-1011T-X3****WD-2001T****WD-2002T**

- ◆ N.W./G.W.: 7.0kg/8.0kg
- ◆ Packing Size: 320x310x450mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 650/1300/1500

- ◆ N.W./G.W.: 7.0kg/8.0kg
- ◆ Packing Size: 320x310x450mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 650/1300/1500

- ◆ N.W./G.W.: 7.0kg/8.0kg
- ◆ Packing Size: 320x310x450mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 650/1300/1500

- ◆ N.W./G.W.: 8.1kg/9.3kg
- ◆ Packing Size: 340x325x565mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 510/950/1020

- ◆ N.W./G.W.: 8.1kg/9.3kg
- ◆ Packing Size: 340x325x565mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'FT/40'HQ: 510/950/1020

- ◆ N.W./G.W.: 4.0kg/5.0kg
- ◆ Packing Size: 280x280x380mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'HQ: 1000/2200

- ◆ N.W./G.W.: 4.0kg/5.0kg
- ◆ Packing Size: 280x280x380mm
- ◆ Loading Qty(pcs): 1PC/CTN
- ◆ 20'FT/40'HQ: 1000/2200

Industrial Air Cooler

Have more powerful wind and enjoy a better summer



FKJ-JH05

FKJ-JH05R

FKJ-JH06

FKJ-JH06R



JDM-L80A

JDM-L60A

Features/Description

Air purifier function
Water filter system
High air flow with 3 speed
Automatic horizontal and vertical swing
Water Shortage Alarm also with purifier function
Water Evaporation heat absorption, Ice-crystal cooling, Ice cooling



JDM-L40B



JDM-L40A

Model	Voltage/Frequency	Refrigerating Output	Air Flow Volume(m³)	Effective Area(m²)	Moisture Storage Capacity(L)	Proudクト Size(mm)	Packing Size(mm)	N.W. (kg)	G.W. (kg)	40'QH (pcs)
FKJ-JH05	220V-240V,50Hz	250W	9000	60~70	55L	610X410X1170	660X410X1170	20.5	22	194
FKJ-JH05R	220V-240V,50Hz	250W	9000	60~70	55L	610X410X1170	660X410X1170	20.5	22	194
FKJ-JH06	220V-240V,50Hz	130W	5000	30~50	35L	520X360X930	570X380X890	17.5	19	346
FKJ-JH06R	220V-240V,50Hz	130W	5000	30~50	35L	520X360X930	570X380X890	17.5	19	346

Model	Voltage/Frequency	Refrigerating Output	Air Flow Volume(m³)	Effective Area(m²)	Moisture Storage Capacity(L)	Proudクト Size(mm)	Packing Size(mm)	N.W. (kg)	G.W. (kg)	40'QH (pcs)
JDM-L40A	220V-240V,50Hz	100W	3500	10~20	14	410x380x880	410x380x880	7.8	8.8	425
JDM-L40B	220V-240V,50Hz	100W	4000	15~30	14	460x405x860	460x405x860	7.8	8.8	370
JDM-L60A	220V-240V,50Hz	200W	6000	30~50	25	610x430x1000	640x450x950	15.5	18.5	240
JDM-L80A	220V-240V,50Hz	300W	8000	40~60	38	610x430x1140	640x450x1100	16.5	19.4	210

Features/Description

3 In 1 Air Cooler/ Air Purifier/ Humidifier
Water Evaporation heat absorption,
Ice-crystal cooling,Ice cooling



JDAC60



JDAC61



JDAC62



JDAC63

Features/Description

3 In 1 Air Cooler/ Air Purifier/ Humidifier
Water Evaporation heat absorption,
Ice-crystal cooling,Ice cooling
3 fan models: sleep/normal/natural

Features/Description

3 In 1 Air Cooler/ Air Purifier/ Humidifier
Water Evaporation heat absorption,
Ice-crystal cooling,Ice cooling



JDAC64



JDAC65

NEW



JDAC64R

NEW



JDAC65R

Features/Description

3 In 1 Air Cooler/ Air Purifier/ Humidifier
Water Evaporation heat absorption,
Ice-crystal cooling,Ice cooling
3 fan models: sleep/normal/natural

Model	Voltage/ Frequency	Refrigerating Output Power	Anion Amount (cm³)	Control Panel	Timer (h)	Remote Controller	Water Tank Capacity(L)	Ice box (pcs)	Packing Size(mm)	N.W / G.W (kg)	Loading Qty(pcs) (40'HQ)
JDAC60	220V-240V,50Hz	60W	2*10n	mechanical switch	NO	NO	3.5	2	300x300x600	4.1/5.2	1092
JDAC61	220V-240V,50Hz	60W	2*10n	mechanical switch	NO	NO	3.5	2	300x300x600	4.1/5.2	1092
JDAC62	220V-240V,50Hz	60W	2*10n	digital switch	0-7 hours	YES	3.5	2	300x300x610	4.1/5.2	1064
JDAC63	220V-240V,50Hz	60W	2*10n	digital switch	0-7 hours	YES	3.5	2	300x300x610	4.1/5.2	1064

Model	Voltage/ Frequency	Refrigerating Output Power	Anion Amount (cm³)	Control Panel	Timer (h)	Remote Controller	Water Tank Capacity(L)	Ice box (pcs)	Packing Size(mm)	N.W / G.W (kg)	Loading Qty(pcs) (40'HQ)
JDAC64	220V-240V,50Hz	60W	2*10n	mechanical switch	NO	NO	3.5	2	310X265X585	3.8/4.8	1400
JDAC64R	220V-240V,50Hz	60W	2*10n	mechanical switch	0-7 hours	YES	3.5	2	310X265X585	3.8/4.8	1400
JDAC65	220V-240V,50Hz	60W	2*10n	digital switch	NO	NO	3.5	2	285X260X600	3.6/4.6	1520
JDAC65R	220V-240V,50Hz	60W	2*10n	digital switch	0-7 hours	YES	3.5	2	285X260X600	3.6/4.6	1520

Features/Description

3 In 1 Air Cooler/ Air Purifier/ Humidifier
Water Evaporation heat absorption,
Ice-crystal cooling,Ice cooling

NEW



JDAC66

NEW



JDAC66R

Features/Description

3 In 1 Air Cooler/ Air Purifier/ Humidifier
Water Evaporation heat absorption,
Ice-crystal cooling,Ice cooling



JDAC70



JDAC71



JDAC80



JDAC80R

Features/Description

3 In 1 Air Cooler/ Air Purifier/ Humidifier
Water Evaporation heat absorption,
Ice-crystal cooling,Ice cooling
3 fan models: sleep/normal/natural



JDAC72



JDAC73

Features/Description

3 In 1 Air Cooler/ Air Purifier/ Humidifier
Water Evaporation heat absorption,
Ice-crystal cooling,Ice cooling
3 fan models: sleep/normal/natural

Model	Voltage/ Frequency	Refrigerating Output Power	Anion Amount (cm³)	Control Panel	Timer (h)	Remote Controller	Water Tank Capacity(L)	Ice box (pcs)	Packing Size(mm)	N.W / G.W (kg)	Loading Qty(pcs) (40'HQ)
JDAC66	220V-240V,50Hz	60W	2*10n	mechanical switch	NO	NO	3.5	2	310X265X585	3.8/4.8	1400
JDAC66R	220V-240V,50Hz	60W	2*10n	digital switch	0-7 hours	YES	3.5	2	310X265X585	3.8/4.8	1400
JDAC80	220V-240V,50Hz	80W	2*10n	mechanical switch	NO	NO	14	4	430X345X745	6.0/7.6	615
JDAC80R	220V-240V,50Hz	80W	2*10n	digital switch	0-7 hours	YES	14	4	430X345X745	6.0/7.6	615

Model	Voltage/ Frequency	Refrigerating Output Power	Anion Amount (cm³)	Control Panel	Timer (h)	Remote Controller	Water Tank Capacity(L)	Ice box (pcs)	Packing Size(mm)	N.W / G.W (kg)	Loading Qty(pcs) (40'HQ)
JDAC70	220V-240V,50Hz	70W	2*10n	mechanical switch	NO	NO	7	2	355X355X760	6.5/7.9	680
JDAC71	220V-240V,50Hz	70W	2*10n	mechanical switch	NO	NO	7	2	355X355X760	6.5/7.9	680
JDAC72	220V-240V,50Hz	70W	2*10n	panel control and remote control	0-7 hours	YES	7	2	355X355X760	6.5/7.9	680
JDAC73	220V-240V,50Hz	70W	2*10n	panel control and remote control	0-7 hours	YES	7	2	355X355X760	6.5/7.9	680

Features/Description

Water Evaporation heat absorption,Ice-crystal cooling,Ice cooling
 3 fan models: sleep/normal/natural
 Automatic horizontal and vertical swing
 Water tank with level indicator
 Ice box holder in water tank,easy-pulling away, the pump automatic up and down
 Water filter system
 With ionizer
 Ionizer/dust gauze

**KFF1901D****KFF1901**

Model	Voltage/ Frequency	Refrigerating Output Power	Control Panel	Timer (h)	Packing Size(mm)	N.W / G.W (kg)	Loading Qty(pcs) (20'FT/40'FT/40'HQ)
KFK1901J	220V-240V,50Hz	80W	mechanical switch	NO	350X210x595	3.5/4.3	1540
KFK1901D	220V-240V,50Hz	80W	panel control and remote control	0~7.5	350X210x595	3.5/4.3	1540

Features/Description

3 In 1(Air Cooler/ Air Purifier/ Humidifier)
 Water Evaporation heat absorption,Ice-crystal cooling,Ice cooling
 3 fan models: sleep/normal/natural
 Automatic horizontal and vertical swing
 Water tank with level indicator
 Ice box holder in water tank,easy-pulling away, the pump automatic up and down
 Water filter system
 With ionizer
 Ionizer/dust gauze
 Air purificationfunction

**KFK1901****KFK1901D****KFK1903J****KFK1903D**

Model	Voltage/ Frequency	Refrigerating Output Power	Control Panel	Timer (h)	Water Tank Capacity(L)	Ice box (pcs)	Packing Size(mm)	N.W / G.W (kg)	Loading Qty(pcs) (40'HQ)
KFK1901J	220V-240V,50Hz	80W	mechanical switch	NO	4	2	350X250X710	4.2/5.3	1030
KFK1901D	220V-240V,50Hz	80W	mechanical switch	0~7.5	4	2	350X250X710	4.2/5.3	1030
KFK1903J	220V-240V,50Hz	80W	panel control and remote control	NO	4	2	350X250X750	4.2/5.3	1000
KFK1903D	220V-240V,50Hz	80W	panel control and remote control	0~7.5	4	2	350X250X750	4.2/5.3	1000

Electric Fan

Have more powerful wind and enjoy a better summer



FS4002(16")

FS4002R(16")

Features/Description

5 PP blades,Steel guard
3 fan models: High/Middle/Low
Adjustable height
Wide-angle air supply
Aluminum motor,Low-noise
Easy installation



FS4003(16")

FS4003R(16")

Features/Description

5 PP blades,Steel guard
3 fan models: High/Middle/Low
Adjustable height
Wide-angle air supply
Aluminum motor,Low-noise
Easy installation



Model	Voltage/Frequency	Output power	Rotating Speed(rpm)	Guard Size(mm)	Motor Size(t)	Height (m)	Timer (h)	Packing Size(mm)	N.W. (kg)	G.W. (kg)	Loading Qty(pcs) (20'FT/40'FT/40'HQ)
FS4002	220V-240V,50Hz	60W	1200	415	66x14	1.35	0~1	500x150x440	4.8	5.4	960/1700/1980
FS4002R	220V-240V,50Hz	60W	1200	415	66x14	1.35	0~7.5	500x150x440	4.8	5.4	960/1700/1980
FS4003	220V-240V,50Hz	60W	1200	415	66x14	1.35	0~1	500x150x440	4.8	5.4	960/1700/1980
FS4003R	220V-240V,50Hz	60W	1200	415	66x14	1.35	0~7.5	500x150x440	4.8	5.4	960/1700/1980



FS4004(16")



FS4004R(16")

Features/Description

5 AS blades
Adjustable height
Aluminum motor
Easy installation



3 fan models: High/Middle/Low
Wide-angle air supply
Low-noise
Steel guard



FS4005(16")

FS4005R(16")

Features/Description

5 PP blades(big)
Adjustable height
Aluminum motor
Easy installation



3 fan models: High/Middle/Low
Wide-angle air supply
Low-noise
Steel guard

**Features/Description**

5 PP blades,steel guard
3 fan models: High/Middle/Low
Adjustable height
Wide-angle air supply
Aluminum motor,Low-noise
Easy installation



FS4006



FS4007



FS4008

Features/Description

5 PP blades(big)
Adjustable height
Aluminum motor
Easy installation



3 fan models: High/Middle/Low
Wide-angle air supply
Low-noise
Steel guard



Model	Voltage/ Frequency	Output power	Rotating Speed(rpm)	Guard Size(mm)	Motor Size(t)	Height (m)	Timer (h)	Packing Size(mm)	N.W. (kg)	G.W. (kg)	Loading Qty(pcs) (20'FT/40'FT/40'HQ)
FS4001	220V-240V,50Hz	60W	1200	415	66x14	1.35	0~1	500x150x440	4.8	5.4	960/1700/1980
FS4004	220V-240V,50Hz	60W	1200	415	66x14	1.35	0~1	500x150x440	4.8	5.4	560/1280/1380
FS4004R	220V-240V,50Hz	60W	1200	415	66x14	1.35	0~7.5	500x150x440	4.8	5.4	560/1280/1380

Model	Voltage/ Frequency	Output power	Rotating Speed(rpm)	Guard Size(mm)	Motor Size(t)	Height (m)	Timer (h)	Packing Size(mm)	N.W. (kg)	G.W. (kg)	Loading Qty(pcs) (20'FT/40'FT/40'HQ)
FS4006	220V-240V,50Hz	60W	1200	445	71x16	1.35	0~1	520x150x480	5.2	5.8	860/1500/1780
FS4007	220V-240V,50Hz	60W	1200	445	71x16	1.35	0~1	520x150x480	5.2	5.8	860/1500/1780
FS4008	220V-240V,50Hz	60W	1200	445	71x16	1.35	0~1	520x150x480	5.2	5.8	860/1500/1780



FB-40A(16")



FB-40AR(16")

- 3** 3 Speed
- 5** 5 PP blades(big)
- ↔** Swing 90 degrees
- ↑↓** Swing 35 degrees



FB-45A(18")



FB-45AR(18")

- 3** 3 Speed
- 5** 5 AS blades(big)
- ↔** Swing 90 degrees
- ↑↓** Swing 35 degrees



FT1001



FZ2501



FT1002



FT1003



FZ2502

Model	Voltage/ Frequency	Output power	Rotating Speed(rpm)	Guard Size(mm)	Motor Size	Timer (h)	Packing Size(mm)	N.W. (kg)	G.W. (kg)	Loading Qty(pcs) (20'FT/40'FT/40'HQ)
FB-40A	220V-240V,50Hz	60W	1200	415	66x14B	NO	425x210x425	2.4	3.3	875/1480/1750
FB-40AR	220V-240V,50Hz	60W	1200	415	66x14B	0~4	425x210x425	2.4	3.3	875/1480/1750
FB-45A	220V-240V,50Hz	60W	1200	500	74x22B	NO	500x210x500	2.9	3.8	630/1080/1260
FB-45AR	220V-240V,50Hz	60W	1200	500	74x22B	0~4	500x210x500	2.9	3.8	630/1080/1260

Model	Voltage/ Frequency	Output power	Rotating Speed(rpm)	Motor Size	Packing Size(mm)	N.W. (kg)	G.W. (kg)	Loading Qty(pcs) (20'FT/40'FT/40'HQ)
FT1001	220V-240V,50Hz	45W	1200	66x10B	345x130x360	2.8	1.7	1900/3800/4250
FT1002	220V-240V,50Hz	45W	1200	66x10B	345X130X360	2.8	1.7	1900/3800/4250
FT1003	220V-240V,50Hz	45W	1200	66x10B	345X130X360	2.8	1.7	1900/3800/4250
FZ2501	220V-240V,50Hz	45W	1200	66x10B	330X142X385	2.1	1.4	1860/3180/3720
FZ2502	220V-240V,50Hz	45W	1200	66x10B	330X142X385	2.1	1.4	1860/3180/3720

Tower Fan

It will brings to you a whole new enjoyment



JTF-02-R

JTF-05-RL

30 inch tower fan


Features/Description

3 fan models: sleep/normal/natural
ABS blades,plastic guard,ABS body
With oscillation
LCD Display



JTF-03

JTF-03-R




TIMING

When you make an appointment, your time is up to you.
Healthy, energy-saving and worry-saving.Timing switch,
easy to operate, easy to control.




Powerful Motor

High sealability, low electromagnetic interference, low noise, small size, operation and maintenance stable, low power consumption, strong power, wide and efficient operation range.



Wind-angel wind

Large angle air supply, enjoy the whole body comfort.
Extra-long outlet, matchingSmart air supply design, make air distribution more uniform, air supply styleMore extensive.



Vortex cross flow design

Through precise scientific verification, the exhaust air of air duct is more smooth and smooth, and effectively reduced. Air loss, while effectively reducing wind resistance noise.

Model	Voltage/ Frequency	Power	Fan Flow Rate(m ³ /min)	Rotating Speed(rpm)	Timer (h)	Height (mm)	Product Size(mm)	Packing Size(mm)	N.W. (kg)	G.W. (kg)	Loading Qty(pcs) (20'FT/40' FT/40' HQ)
JTF-03	220V-240V,50/60Hz	45W	4.4	1250	NO	770	220x220x770	780x160x190	2.4	2.9	1260/2250/2520
JTF-03-R	220V-240V,50/60Hz	45W	4.4	1250	0.5~7.5	770	220x220x770	780x160x190	2.4	2.9	1260/2250/2520

36 inch tower fan

Features/Description

3 fan models: sleep/normal/natural
 ABS blades,plastic guard,ABS body
 With oscillation
 LCD Display



JTF-01



JTF-01-R



JTF-02



JTF-02-R

47 inch tower fan

Features/Description

3 fan models: sleep/normal/natural
 ABS blades,plastic guard,ABS body
 With oscillation
 LCD Display



JTF-05-L



JTF-05-RL



JTF-02-L



JTF-02-RL

Model	Voltage/ Frequency	Power	Fan Flow Rate(m³/min)	Rotating Speed(rpm)	Timer (h)	Height (mm)	Product Size(mm)	Packing Size(mm)	N.W. (kg)	G.W. (kg)	Loading Qty(pcs) (20'FT/40'FT/40'HQ)
JTF-01	220V-240V,50/60Hz	45W	4.4	1250	0~1	920	260x260x920	970x220x180	3.4	4.4	780/1400/1560
JTF-01-R	220V-240V,50/60Hz	45W	4.4	1250	1~12	920	260x260x920	970x220x180	3.4	4.4	780/1400/1560
JTF-02	220V-240V,50/60Hz	45W	4.4	1250	NO	910	260x260x920	970x220x180	3.2	4.2	780/1400/1560
JTF-02-R	220V-240V,50/60Hz	45W	4.4	1250	1~15	910	260x260x920	970x220x180	3.2	4.2	780/1400/1560

Model	Voltage/ Frequency	Power	Fan Flow Rate(m³/min)	Rotating Speed(rpm)	Timer (h)	Height (mm)	Product Size(mm)	Packing Size(mm)	N.W. (kg)	G.W. (kg)	Loading Qty(pcs) (20'FT/40'FT/40'HQ)
JTF-05-L	220V-240V,50/60Hz	45W	4.4	1250	0~1	1200	340x340x1200	1240x220x190	4.0	5.2	540/960/1080
JTF-05-RL	220V-240V,50/60Hz	45W	4.4	1250	1~12	1200	340x340x1200	1240x220x190	4.0	5.2	540/960/1080
JTF-02-L	220V-240V,50/60Hz	45W	4.4	1250	NO	1200	340x340x1200	1240x220x190	4.0	5.2	540/960/1080
JTF-02-RL	220V-240V,50/60Hz	45W	4.4	1250	1~15	1200	340x340x1200	1240x220x190	4.0	5.2	540/960/1080



PTC Heater

**NSB-200-A**

- ◆ 220-240V/50-60Hz
- ◆ Cool/Warm/Hot wind for selection
- ◆ Wire heating elements.
- ◆ 2 heat setting: 1000W/2000W
- ◆ Adjustable thermostat control
- ◆ Power indicator light
- ◆ Overheat safety cut-out
- ◆ Cool airflow for summer use
- ◆ portable design
- ◆ N.W./G./W.: **1.2kg/1.5kg**
- ◆ Pack size(Inner pack): **225x90x245mm**
(Outside pack): **435x240x560mm**
- ◆ 20'FT/40'FT/40'HQ(pcs): **3300/6720/7980**

**NQ1607**

- ◆ 220-240V/50-60Hz
- ◆ 360° Air-out Ceramic Heate
- ◆ 2 heat setting: 750W/1500W
- ◆ Adjustable thermostat control
- ◆ 3 settings: Fan/Low/high
- ◆ Overheat safety cut-out
- ◆ Cool airflow for summer use
- ◆ portable design
- ◆ High temperature resistant housing
- ◆ N.W./G./W.: **1.6kg/1.9kg**
- ◆ Pack size(Inner pack): **210x195x290mm**
(Outside pack): **430x400x305mm**
- ◆ 20'FT/40'FT/40'HQ(pcs): **2120/4720/5000**

**NQ1607R**

- ◆ 220-240V/50-60Hz
- ◆ 360° Air-out Ceramic Heate
- ◆ 2 heat setting: 750W/1500W
- ◆ Adjustable thermostat control
- ◆ 3 settings: Fan/Low/high
- ◆ Overheat safety cut-out
- ◆ Cool airflow for summer use
- ◆ portable design
- ◆ High temperature resistant housing
- ◆ Digital version touch control with remote
- ◆ 12 hours timer
- ◆ N.W./G./W.: **1.6kg/1.9kg**
- ◆ Pack size(Inner pack): **210x195x290mm**
(Outside pack): **430x400x305mm**
- ◆ 20'FT/40'FT/40'HQ(pcs): **2120/4720/5000**

**NQ612**

- ◆ 220-240V/50-60Hz
- ◆ PTC fan heater, ceramic heating elements
- ◆ 2 heat setting: 750W/1500W
- ◆ Cool /Warm/Hot wind for selection
- ◆ Power indicator light
- ◆ Overheat safety cut-out
- ◆ Adjustable room thermostat
- ◆ Automatic control temperature
- ◆ portable design.
- ◆ High temperature resistant housing
- ◆ N.W./G./W.:**1.5kg/1.8kg**
- ◆ Pack size(Inner pack):**230x170x220mm**
(Outside pack):**530x475x455mm**
- ◆ 20'FT/40'FT/40'HQ(pcs):**2880/6000/7072**

**NQ1666R**

- ◆ 220-240V/50-60Hz.
- ◆ PTC fan heater, ceramic heating elements
- ◆ 2 heat setting: 750W/1500W.
- ◆ Adjustable thermostat control.
- ◆ Power indicator light.
- ◆ Overheat safety cut-out.
- ◆ Cool airflow for summer use.
- ◆ portable design.
- ◆ High temperature resistant housing.
- ◆ With remote controller
- ◆ N.W./G./W.:**1.2kg/1.4kg**
- ◆ Pack size(Inner pack):**180x125x280mm**
(Outside pack):**370x255x280mm**
- ◆ 20'FT/40'FT/40'HQ(pcs):**5300/9100/10600**

**NQ1615**

- ◆ 220-240V/50-60Hz
- ◆ Oscillating Ceramic Tower Heater
- ◆ 2 heat setting: 750W/1500W
- ◆ 3 setting: Fan/Low/High
- ◆ With remote controller
- ◆ Overheat safety cut-out
- ◆ Cool airflow for summer use
- ◆ Portable design
- ◆ High temperature resistant housing
- ◆ N.W./G./W.:**2.0kg/2.4kg**
- ◆ Pack size:**235x235x370mm**
- ◆ 20'FT/40'FT/40'HQ(pcs):**1500/3000/3400**

**NQ1616**

- ◆ 220-240V/50-60Hz
- ◆ Oscillating Ceramic Tower Heater
- ◆ 2 heat setting: 750W/1500W
- ◆ 3 setting: Fan/Low/High
- ◆ With remote controller
- ◆ Overheat safety cut-out
- ◆ Cool airflow for summer use
- ◆ Portable design
- ◆ High temperature resistant housing
- ◆ N.W./G./W.:**1.6kg/2.0kg**
- ◆ Pack size:**220x175x310mm**
- ◆ 20'FT/40'FT/40'HQ(pcs):**2500/5000/5600**

**NQ1605**

- ◆ 220-240V/50-60Hz.
- ◆ Oscillating Ceramic Tower Heater
- ◆ 2 heat setting: 750W/1500W.
- ◆ 3 setting: Fan/Low/High
- ◆ Mechanical version
- ◆ Overheat safety cut-out.
- ◆ Cool airflow for summer use.
- ◆ Portable design.
- ◆ High temperature resistant housing.
- ◆ N.W./G./W.:**1.5kg/1.8kg**
- ◆ Pack size(Inner pack):**205x205x505mm**
(Outside pack):**420x420x515mm**
- ◆ 20'FT/40'FT/40'HQ(pcs):**1240/2520/3360**

**NQ1605R**

- ◆ 220-240V/50-60Hz
- ◆ Oscillating Ceramic Tower Heater
- ◆ 2 heat setting: 750W/1500W
- ◆ 3 setting: Fan/Low/High
- ◆ With remote controller
- ◆ Overheat safety cut-out
- ◆ Cool airflow for summer use
- ◆ Portable design
- ◆ High temperature resistant housing
- ◆ N.W./G./W.:**1.6kg/1.9kg**
- ◆ Pack size(Inner pack):**205x205x505mm**
(Outside pack):**420x420x515mm**
- ◆ 20'FT/40'FT/40'HQ(pcs):**1240/2520/3360**

**NQ1617**

- ◆ 220-240V/50-60Hz
- ◆ Oscillating Ceramic Tower Heater
- ◆ 2 heat setting: 750W/1500W
- ◆ 3 setting: Fan/Low/High
- ◆ With remote controller
- ◆ Overheat safety cut-out
- ◆ Cool airflow for summer use
- ◆ Portable design
- ◆ High temperature resistant housing
- ◆ N.W./G./W.:**4.6kg/5.6kg**
- ◆ Pack size:**240x260x940mm**
- ◆ 20'FT/40'FT/40'HQ(pcs):**505/1010/1150**

**NQ1666**

- ◆ 220-240V/50-60Hz
- ◆ Oscillating Ceramic Tower Heater
- ◆ 2 heat setting: 600W/1200W
- ◆ 3 setting: Fan/Low/High
- ◆ With remote controller
- ◆ Overheat safety cut-out
- ◆ Cool airflow for summer use
- ◆ Portable design
- ◆ High temperature resistant housing
- ◆ N.W./G./W.:**4.6kg/5.6kg**
- ◆ Pack size:**185x195x260mm**
- ◆ 20'FT/40'FT/40'HQ(pcs):**505/1010/1150**