

NPLinker 2: a modular and customizable framework for paired omics analyses

Cunliang Geng¹, Giulia Crocioni¹, Helge Hecht², Arjan Draisma³, Annette Lien³, Laura Rosina Torres Ortega³, Dora Ferreira⁴, Pablo Lopez-Tarifa¹, Katherine R. Duncan⁵, Marnix H. Medema³, and Justin J. J. van der Hooft^{3,6}

¹ Netherlands eScience Center, Netherlands ² RECETOX, Faculty of Science, Masaryk University, Kotlářská 2, 60200, Brno, Czech Republic ³ Bioinformatics Group, Wageningen University & Research, Netherlands ⁴ Naicons Srl, Milan, Italy ⁵ Newcastle University, Biosciences Institute, Newcastle upon Tyne, UK ⁶ Department of Biochemistry, University of Johannesburg, 2006 Johannesburg, South Africa
✉ Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Open Journals](#)

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#))

Summary

Natural product discovery increasingly relies on the integration of multi-omics data to explore and prioritize biochemical diversity. To advance these efforts, we present NPLinker 2, a redesigned Python framework to do paired omics analyses by prioritizing genomics-metabolomics links. It provides a modular workflow that allows defining custom modules for data preparation, data loading and scoring methods. In addition, NPLinker 2 includes a web application for the interactive analysis and visualisation of promising links.

Statement of need

Omics datasets have become a key resource for natural products discovery, enabling the systematic exploration of specialized metabolites, the refinement of knowledge of known natural products, and the identification of novel bioactive compounds or metabolic enzymes. Paired omics analyses combine complementary genomics (e.g., biosynthetic gene clusters (BGCs)) and metabolomics (e.g., mass spectra) datasets to elucidate gene-metabolite relationships, accelerating the discovery process (Goering et al., 2016; Hooft et al., 2020; Leão et al., 2022). Several computational strategies have been developed to propose such gene cluster-mass spectral links, including i) feature-based approaches that match predicted structural or substructure information between genomes and MS/MS (e.g., Pep2Path, MetaRiPPquest, MetaMiner, DeepRiPP) (Cao et al., 2019; Medema et al., 2014; Merwin et al., 2020; Mohimani et al., 2017), ii) correlation-based “metabologenomics” that infer co-occurrence patterns across strains or samples (Goering et al., 2016), and iii) hybrid frameworks such as NPLinker and the machine learning classifier-based NPOmix (Eldjárn et al., 2021; Leão et al., 2022), with recently proposed phylogeny-aware extensions to reduce false positive associations (Boldt et al., 2026). However, the connected omics data structures, preprocessing pipelines, resources, and annotation tools are constantly being improved: curated BGC repositories such as MIBiG are continually expanded with new entries and annotation fields (Zdouc et al., 2025), while community MS/MS resources such as GNPS spectral libraries keep growing (Wang et al., 2016). Together with the constant expansion of experimental datasets, this puts a strain on downstream frameworks that integrate processed omics data and link results. Hence, natural products discovery would benefit from up-to-date and user-friendly software packages that parse processed omics data and connect it with algorithms returning ranked, queryable gene cluster - mass spectra links to prioritize links to further investigate manually. Here, we redesigned

NPLinker to provide such an integrative omics tool that guides both users and developers in paired omics mining with its modular setup. For example, recent developments in omics processing, annotation tools, and ranking metrics could be added to the framework (Louwen, Medema, et al., 2023; Louwen, Kautsar, et al., 2023). Moreover, several of such linking scores could then be used together with the currently implemented strain correlation score to further improve ranking results.




Figure 1: The NPLinker 2 framework. The current pipeline consists of five main components: 1. Initiating an analysis with an input block that includes configuration file and optional input data; 2. Preparing dataset by automatically downloading or generating data; 3. Loading and parsing data from data files; 4. Scoring and linking data; 5. Creating an output for analysis and visualization of results.

Features of NPLinker 2

NPLinker 2 is redesigned based on NPLinker version 1.x (Eldjárn et al., 2021) to provide a more flexible, modular and extensible framework for linking BGCs to mass spectra. The pipeline is shown in the Figure 1, and the key features are highlighted below.

Installation ease

NPLinker 2 is distributed as a Python package, but it relies on several third-party tools and databases that are not available via PyPi, which can make the installation more complex. To simplify the setup process, NPLinker 2 includes an installation script that automatically installs the required non-PyPi dependencies and databases.

To install NPLinker 2 and its dependencies, users can run the following commands:

```
# Install the NPLinker package
pip install --pre nplinker

# Install non-PyPi dependencies and required databases
install-nplinker-deps
```

Configurable

NPLinker 2 can be easily configured using the file `nplinker.yaml`, which is required to customise the pipeline according to users' needs, e.g., by selecting the run mode, choosing scoring methods. A friendly template is available on the doc website to help users create and fill in their configuration file from scratch.

Local mode and PODP mode

NPLinker 2 supports both local and remote data sources through two operational modes: **local mode** and **PODP mode**. In local mode, users provide their local data files, e.g., AntiSMASH (Blin et al., 2025) output files and mass spectral data (Wang et al., 2016) supported by matchms (Huber et al., 2020), as input. In contrast, the Paired Omics Data Platform (PODP) (Schorn et al., 2021) mode requires no input data files from the user, as the pipeline automatically downloads necessary data files from the PODP (Paired Omics Data Platform) server using the

71 PODP ID specified in the `nplinker.yaml` file. This dual-mode support enables private and
72 public data analysis using the same pipeline.

73 Modular and extensible

74 Modularity and extensibility are key features of NPLinker 2, which provides a set of interfaces
75 and data models that users can extend.

76 **“Prepare Data” component:** The core class of this component, `DatasetArranger`, orchestrates
77 various downloaders and runners to automatically download and generate the required data
78 files. These files are then stored in the local working directory specified in the `nplinker.yaml`
79 configuration file. Users can extend this component by adding new downloaders or runners,
80 e.g., to download BGC data from a new source or generate data files using a different method
81 or tool.

82 **“Load Data” component:** The `DatasetLoader` class manages data loaders responsible for
83 loading and parsing genomics, metabolomics, and strain data files. Users can add new data
84 loaders to support additional sources or formats. For example, to load BGC data from a new
85 source, one can define a Python class `NewBGCLoader` that inherits from the `BGCLoaderBase`
86 interface and implements the `get_files` and `get_bgcs` methods, then register it within the
87 `DatasetLoader` class.

88 **“Scoring” component:** This component handles the linking of data and the scoring of those
89 links. A undirected graph is used to store the linked data, with nodes corresponding to genomics
90 or metabolomics data items and edges representing the links between them with scoring values,
91 as illustrated in Figure 2. The `ScoringBase` interface is provided to allow the implementation
92 of custom scoring methods.




Figure 2: Graph representation of linkings.

93 New documentation website

94 A dedicated documentation website is available to help users and developers understand how
95 to use and extend NPLinker 2. It includes tutorials, conceptual overviews, pipeline diagrams,
96 and an API reference. The documentation is available at <https://nplinker.github.io/nplinker>.

97 New unit tests and integration tests

98 Unit and integration tests are included in NPLinker 2 to ensure the codebase and the overall
99 pipeline is correct. The tests can be run in parallel to speed up the testing process.

Forced static typing

NPLinker 2 is developed with forced static typing, which means that all functions and methods have type hints to specify the input and output types. This helps developers to understand the code better and catch type errors early when dealing with complex genomic and metabolomic data and the processed and annotated data derived thereof.

User-friendly webapp

The [NPLinker web application](#) (webapp) is an interactive dashboard built with [Plotly Dash](#), designed to make NPLinker's linking results accessible through a user-friendly web interface. A [publicly hosted demo](#) allows immediate testing: users can load a sample dataset with a single click and start exploring. To enable full functionality with larger datasets, the webapp can be installed locally or run via Docker (using the [nplinker-webapp image](#)). Notably, the webapp focuses on visualization and post-analysis; link scoring between genomic and metabolomic entries is performed beforehand by the NPLinker backend.

The linking is currently provided starting from both omics views: from Gene Cluster Families (GCFs) clustered by BiG-SCAPE ([Navarro-Muñoz et al., 2020](#)) to mass spectra or molecular families (MFs) clustered by molecular networking ([Wang et al., 2016](#)) or vice versa. Once the data is loaded, the interface provides two complementary views: genomics-to-metabolomics and metabolomics-to-genomics. This dual-tab layout allows users to begin from either data type and inspect associated links in the other domain. Each view presents the input data and predicted links in sortable, filterable tables, with support for multiple filtering criteria (e.g., GCF, MF, spectrum IDs, BGC classes, score thresholds). This enables rapid prioritization of promising BGC–metabolite links. Results can also be exported as Excel files for downstream analysis and record-keeping, allowing smooth integration into existing workflows.

Acknowledgements

This work was supported by the Netherlands eScience Center under grant number NLESC.OEC.2021.002 (M.H. Medema and J.J.J. van der Hooft). A. Lien, L. R. Torres Ortega, D. Ferreira, K.R. Duncan, M.H. Medema and J. J. J. van der Hooft acknowledge the MAGIC-MOLFUN Doctoral Training Network that has received funding from the European Union's Horizon Europe programme under the Marie Skłodowska-Curie grant agreement No. 101072485 (M.H. Medema and J.J.J. van der Hooft) and and UKRI EP/X03142X/2 (K.R. Duncan).

Conflict of Interest

JJJvdH is member of the Scientific Advisory Board of NAICONS Srl., Milano, Italy and consults for Corteva Agriscience, Indianapolis, IN, USA. MHM is a member of the scientific advisory boards of Hexagon Bio and Hothouse Therapeutics Ltd. All other authors declare to have no competing interests.

Reference

- Blin, K., Shaw, S., Vader, L., Szenei, J., Reitz, Z. L., Augustijn, H. E., Cediël-Becerra, J. D. D., Crécy-Lagard, V. de, Koetsier, R. A., Williams, S. E., Cruz-Morales, P., Wongwas, S., Segurado Luchsinger, A. E., Biermann, F., Korenskaia, A., Zdouc, M. M., Meijer, D., Terlouw, B. R., Hooft, J. J. J. van der, ... Weber, T. (2025). antiSMASH 8.0: Extended gene cluster detection capabilities and analyses of chemistry, enzymology, and regulation. *Nucleic Acids Research*, 53, W32–W38. <https://doi.org/10.1093/nar/gkaf334>

- 143 Boldt, J., Porten, C., Haeckl, F. J., Hug, J. J., Panter, F., Steglich, M., Wink, J., Overmann,
144 J., Göker, M., Krug, D., & others. (2026). Phylogeny-aware metabologenomics accurately
145 assigns natural products to biosynthetic gene clusters. *Microbial Biotechnology*, 19(1),
146 e70298.
- 147 Cao, L., Gurevich, A., Alexander, K. L., Naman, C. B., Leão, T., Glukhov, E., Luzzatto-Knaan,
148 T., Vargas, F., Quinn, R., Bouslimani, A., & others. (2019). MetaMiner: A scalable
149 peptidogenomics approach for discovery of ribosomal peptide natural products with blind
150 modifications from microbial communities. *Cell Systems*, 9(6), 600–608.
- 151 Eldjárn, G. H., Ramsay, A., Hooft, J. J. J. van der, Duncan, K. R., Soldatou, S., Rousu, J., Daly,
152 R., Wandy, J., & Rogers, S. (2021). Ranking microbial metabolomic and genomic links in
153 the NPLinker framework using complementary scoring functions. *PLOS Computational
154 Biology*, 17, e1008920. <https://doi.org/10.1371/journal.pcbi.1008920>
- 155 Goering, A. W., McClure, R. A., Doroghazi, J. R., Albright, J. C., Haverland, N. A., Zhang, Y.,
156 Ju, K.-S., Thomson, R. J., Metcalf, W. W., & Kelleher, N. L. (2016). Metabologenomics:
157 Correlation of Microbial Gene Clusters with Metabolites Drives Discovery of a Nonribosomal
158 Peptide with an Unusual Amino Acid Monomer. *ACS Central Science*, 2, 99–108. <https://doi.org/10.1021/acscentsci.5b00331>
- 160 Hooft, J. J. J. van der, Mohimani, H., Bauermeister, A., Dorrestein, P. C., Duncan, K. R., &
161 Medema, M. H. (2020). Linking genomics and metabolomics to chart specialized metabolic
162 diversity. *Chemical Society Reviews*, 49, 3297–3314. <https://doi.org/10.1039/D0CS00162G>
- 163 Huber, F., Verhoeven, S., Meijer, C., Spreeuw, H., Castilla, E. M. V., Geng, C., Hooft, J.
164 J. j van der, Rogers, S., Belloum, A., Diblen, F., & Spaaks, J. H. (2020). Matchms -
165 processing and similarity evaluation of mass spectrometry data. *Journal of Open Source
166 Software*, 5, 2411. <https://doi.org/10.21105/joss.02411>
- 167 Leão, T. F., Wang, M., Silva, R. da, Gurevich, A., Bauermeister, A., Gomes, P. W. P.,
168 Brejnrod, A., Glukhov, E., Aron, A. T., Louwen, J. J. R., Kim, H. W., Reher, R., Fiore,
169 M. F., Hooft, J. J. J. van der, Gerwick, L., Gerwick, W. H., Bandeira, N., & Dorrestein,
170 P. C. (2022). NPOMix: A machine learning classifier to connect mass spectrometry
171 fragmentation data to biosynthetic gene clusters. *PNAS Nexus*, 1, pgac257. <https://doi.org/10.1093/pnasnexus/pgac257>
- 173 Louwen, J. J. R., Kautsar, S. A., Burg, S. van der, Medema, M. H., & Hooft, J. J. J.
174 van der. (2023). iPRESTO: Automated discovery of biosynthetic sub-clusters linked
175 to specific natural product substructures. *PLOS Computational Biology*, 19, e1010462.
176 <https://doi.org/10.1371/journal.pcbi.1010462>
- 177 Louwen, J. J. R., Medema, M. H., & Hooft, J. J. J. van der. (2023). Enhanced correlation-
178 based linking of biosynthetic gene clusters to their metabolic products through chemical
179 class matching. *Microbiome*, 11, 13. <https://doi.org/10.1186/s40168-022-01444-3>
- 180 Medema, M. H., Paalvast, Y., Nguyen, D. D., Melnik, A., Dorrestein, P. C., Takano, E., &
181 Breitling, R. (2014). Pep2Path: Automated mass spectrometry-guided genome mining of
182 peptidic natural products. *PLoS Computational Biology*, 10(9), e1003822.
- 183 Merwin, N. J., Mousa, W. K., Dejong, C. A., Skinnider, M. A., Cannon, M. J., Li, H., Dial,
184 K., Gunabalasingam, M., Johnston, C., & Magarvey, N. A. (2020). DeepRiPP integrates
185 multiomics data to automate discovery of novel ribosomally synthesized natural products.
186 *Proceedings of the National Academy of Sciences*, 117(1), 371–380.
- 187 Mohimani, H., Gurevich, A., Alexander, K. L., Naman, C. B., Leao, T., Glukhov, E., Moss, N.
188 A., Luzzatto-Knaan, T., Vargas, F., Nothias, L.-F., & others. (2017). MetaRiPPquest:
189 A peptidogenomics approach for the discovery of ribosomally synthesized and post-
190 translationally modified peptides. *BioRxiv*, 227504.
- 191 Navarro-Muñoz, J. C., Selem-Mojica, N., Mullowney, M. W., Kautsar, S. A., Tryon, J. H.,

- 192 Parkinson, E. I., De Los Santos, E. L. C., Yeong, M., Cruz-Morales, P., Abubucker, S.,
193 Roeters, A., Lokhorst, W., Fernandez-Guerra, A., Cappelini, L. T. D., Goering, A. W.,
194 Thomson, R. J., Metcalf, W. W., Kelleher, N. L., Barona-Gomez, F., & Medema, M. H.
195 (2020). A computational framework to explore large-scale biosynthetic diversity. *Nature*
196 *Chemical Biology*, 16, 60–68. <https://doi.org/10.1038/s41589-019-0400-9>
- 197 Schorn, M. A., Verhoeven, S., Ridder, L., Huber, F., Acharya, D. D., Aksenov, A. A.,
198 Aleti, G., Moghaddam, J. A., Aron, A. T., Aziz, S., Bauermeister, A., Bauman, K. D.,
199 Baunach, M., Beemelmans, C., Beman, J. M., Berlanga-Clavero, M. V., Blacutt, A. A.,
200 Bode, H. B., Boullie, A., ... Hooft, J. J. J. van der. (2021). A community resource for
201 paired genomic and metabolomic data mining. *Nature Chemical Biology*, 17, 363–368.
202 <https://doi.org/10.1038/s41589-020-00724-z>
- 203 Wang, M., Carver, J. J., Phelan, V. V., Sanchez, L. M., Garg, N., Peng, Y., Nguyen, D.
204 D., Watrous, J., Kapon, C. A., Luzzatto-Knaan, T., Porto, C., Bouslimani, A., Melnik,
205 A. V., Meehan, M. J., Liu, W.-T., Crusemann, M., Boudreau, P. D., Esquenazi, E.,
206 Sandoval-Calderón, M., ... Bandeira, N. (2016). Sharing and community curation of mass
207 spectrometry data with Global Natural Products Social Molecular Networking. *Nature*
208 *Biotechnology*, 34, 828–837. <https://doi.org/10.1038/nbt.3597>
- 209 Zdouc, M. M., Blin, K., Louwen, N. L. L., Navarro, J., Loureiro, C., Bader, C. D., Bailey, C.
210 B., Barra, L., Booth, T. J., Bozhuyuk, K. A. J., Cedié-Becerra, J. D. D., Charlop-Powers,
211 Z., Chevrette, M. G., Chooi, Y. H., D'Agostino, P. M., Rond, T. de, Del Pup, E., Duncan,
212 K. R., Gu, W., ... Medema, M. H. (2025). MIBiG 4.0: Advancing biosynthetic gene
213 cluster curation through global collaboration. *Nucleic Acids Research*, 53, D678–D690.
214 <https://doi.org/10.1093/nar/gkaf115>