

Aremco's refractory paint systems offer the ultimate protection of high temperature structures used in the processing of metals, glasses and plastics.

PRODUCT HIGHLIGHTS

Graphi-Coat™ 623

This coating system, originally patented by Aremco, is a two-part, silica-bonded, titanium diboride filled, oxidation resistant coating for protecting graphite from oxidation to 2000 °F (1093 °C). Used on graphite crucibles, heat-treating fixtures, and electrodes in the metallurgical industry.

Pyro-Paint™ 634-AS and 634-AS1

These alumina-silica based advanced coatings are rated for continuous service temperatures up to 2300 °F. Provides excellent adhesion to ceramic fiber blankets, modules and boards and resists wetting by nonferrous molten metals, increasing the durability and erosion resistance of the underlying material. High dry film thicknesses from 10-50 mils can be achieved with this coating. Select 634-AS for thin coating applications and 634-AS1 for high build applications.

Pyro-Paint™ 634-AL

This pure, alumina based compound creates a hard, high temperature resistant coating for refractory fiber boards and shapes, providing exceptional resistance to molten metals and open flames to 3200 °F (1760 °C). Increases heat reflectivity in furnaces to improve efficiency and ramp up temperatures more rapidly.

Pyro-Paint™ 634-ALP

This phosphate-bonded, alumina coating system bonds exceptionally well to dense refractory ceramics, providing high abrasion and corrosion resistance for operating temperatures to 3200 °F (1760 °C).

Pyro-Paint™ 634-BN and 634-BN(SC)

These highly-filled boron nitride solutions are extremely lubricious and inert. They are non-wetted by molten salts, glasses, plastics, and most metals including aluminum and magnesium. Select 634-BN for hard coat; 634-BN(SC) for softer, lubricious coat.

Pyro-Paint™ 634-CA and 634-GR

These carbon and graphite based coatings are formulated for parting of aluminum permanent molds, non-sticking in glass forming applications, and lubrication and stop-off in metalworking and wire drawing. Provides superior release, surface finish and mold protection.

Pyro-Paint™ 634-SIC

This advanced silicon carbide, water-based coating reduces significantly the oxidation of graphite and carbon components and structures at temperatures to 2550 °F (1400 °C). Provides a hard surface and withstands thermal cycling.

Pyro-Paint™ 634-YO

This ultra high temperature yttrium oxide coating provides exceptional protection of graphite, ceramic and metal components exposed to reactive molten metals such as titanium, uranium and their alloys. Usable in vacuum and inert atmospheres to 2732 °F (1500 °C).

Pyro-Paint™ 634-ZO

This highly-filled zirconium oxide-based coating produces a hard, chemically-resistant protective layer which is stable with aluminum, molybdenum, platinum, rhodium, and titanium. It is ideal for sealing porous ceramics and protecting other ceramic, graphite and metal structures up to 3270 °F. Exceptional for coating resistance wire heating elements in furnaces, protecting them from residue buildup which causes arcing and reduced element life.

Features

Ultra Hi-Temp Resistance

Non-Wetted by Molten Metals, Salts, Glass & Plastics

High Lubricity for Easy Part Release

Minimizes Cast Surface Defects

Increases Mold & Die Life

For Use in Oxidizing, Reducing & Vacuum Atmospheres

Applications

Composite Forming

Glass Forming

Metal Casting

Injection Molding

Ceramic Hot-Pressing

Metal Powder Sintering

Welding

Brazing



PROPERTIES

Part Number	623	634-AL	634-ALP	634-AS	634-AS-1	634-BN	634-BNSC	634-CA	634-GR	634-SIC	634-YO	634-ZO
Tradename	Graphi-Coat™	Pyro-Paint™	Pyro-Paint™	Pyro-Paint™	Pyro-Paint™	Pyro-Paint™	Pyro-Paint™	Pyro-Paint™	Pyro-Paint™	Pyro-Paint™	Pyro-Paint™	Pyro-Paint™
Major Constituent	Titanium DiBoride	Aluminum Oxide	Alumina-Silica	Alumina-Silica	Boron Nitride	Carbon	Carbon	Carbon	Carbon	Silicon Carbide	Yttrium Oxide	Zirconium Oxide
Temp. Limit, °F (°C)	2000 (1093)	3200 (1760)	3200 (1760)	2300 (1260)	2300 (1260)	1560 (850) ^①	1560 (850) ^①	2200 (1200)	2200 (1200)	2550 (1400)	2732 (1500)	3270 (1800)
% Solids by Weight	78.0	76.8	75.8	61.2	77.0	38.6	28.5	25.4	45.5	74.5	42.7	65.0
% Solids by Volume	57.7	66.0	73.5	63.3	70.0	21.6	27.5	18.4	29.7	53.0	23.0	35.5
Theoretical Coverage ft ² /Gal @ 1 Mil DFT	890	1060	1180	1015	1120	345	440	295	475	850	370	570
Application Temp., °F	50-90	50-90	50-90	50-90	50-90	50-90	50-90	50-90	50-90	50-90	50-90	50-90
Recommend Curing Min Air Set, Hours Cure, °F/Hours ^②	1 1400/0.25	2 200/2	1 200/2, 800/1	2 200/2	2 200/2	2 200/2	2 200/2	2 200/2	2 200/2	1 200/2, 800/1	0.5 200/1	2 200/2
Color	Gray	White	White	Off-White	White	White	White	Black	Black	Gray	Off-White	Tan
No. Components	2	2	1	1	1	1	1	1	1	1	1	1
Mix Ratio ^③	60 : 40	75 : 25	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Viscosity, cP	1,000 - 2,500	7,000 - 8,000	5,000 - 7,000	600 - 800	1,600 - 1,800	18,000 - 22,000	Paste	700 - 1,000	750 - 1,250	12,000 - 16,000	4,000 - 5,500	1,000 - 1,400
Thinner ^④	623-T	634-AL-T	634-ALP-T	634-AS-T	634-AS-T	634-BN-T	634-BNSC-T	634-CA-T	634-GR-T	634-SIC-T	634-YO-T	634-ZO-T
Specific Gravity, g/cc	2.00	2.27	2.38	1.59	1.70	1.34	1.20	1.15	1.32	2.30	1.31	2.02
Coating pH	7-8	4-5	2-3	7-8	7-8	11-12	4-5	8-9	8-9	2-3	7-8	11-12
Flash Point, °F	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	75	N/A
Shelf Life, months	6	6	6	6	6	6	6	6	6	6	6	6
Storage, °F	40-90	40-90	40-90	40-90	40-90	40-90	40-90	40-90	40-90	40-90	40-90	40-90
Weight/Gallon, lbs ^⑤	12.5	12.0	16.5	12.0	12.5	9.5	9.5	8.5	9.5	16.5	12.0	23.5

^① Temperature limit applies to oxidizing atmospheres only. Can be used in vacuum/inert atmospheres to 2000 °C.

^② A short cure is recommended, however, most of these products can be air set them ramped up to operating temperature immediately.

^③ Mix ratio is Powder : Liquid. Ratios may be altered as required to adjust viscosity.

^④ Distilled water may also be used to thin all products. Use 1-2% distilled water by weight.

^⑤ For two-part systems, this only refers to the weight per gallon for the powder portion of the mixture.

Refer to Price List for complete order information.

Aremco Products makes no warranty express or implied concerning the use of this product.

The user assumes all risk of use or handling whether or not in accordance with directions or suggestions, or used singly or in combination with other products.