

DS Written Homework 3

Student ID: b10201054

May 1, 2025

1 Splay Tree




Figure 1: Splaytree(a)

(a)




Figure 2: Splaytree(b)

(b)




Figure 3: Splaytree(c)

(c)

2 Time complexity of AVL tree and Splay tree

The worst case of BST and Splay tree is a sorted single linked-list, hence the time complexity is $O(n)$.

Since the AVL tree is self-balanced tree, the tree height is at most $O(\log n)$, which means the worst case of searching is $O(\log n)$.

The average(amortized) cost of Splay tree is $O(\log n)$, which is proved in the Splay tree handout.

The average(amortized) cost of AVL tree is $O(\log n)$. Since it is self-balanced, the tree height is at most $O(\log n)$, the successful search and unsuccessful search are limited by the tree height. Hence the searching time complexity is $O(\log n)$.

Search	Binary Search Tree	Splay Tree	AVL Tree
Worst Case	$O(n)$	$O(n)$	$O(\log n)$
Average	$O(n)$	$O(\log n)$	$O(\log n)$

Table 1: Time complexity of search in different trees

3 Data Structure for Different Scenarios

- (a) Splay tree; The root of splay tree is last accessed node. Since it frequently accesses a few popular keywords, the height of those keywords will be near the root, which helps us find them quickly.
- (b) Queue; Queue has the property 'first in first out'. Since we need to print jobs in the order they are received, 'first in first out' is what we need the most.
- (c) AVL tree; AVL tree is a balanced BST, whose search, insert, delete have the steady time complexity $O(\log n)$ even in the worst case.

- (d) Stack; Undo means to cancel the last step we have done. Stack has the property 'last-in, first-out', which matches the undo function needs.

4 AVL Tree




Figure 4: AVL Tree

The AVL tree we consider is in Figure 4.

Before insertion, the height of each subtree/node named $h_{tree_name/node_name}$.

After insertion, the height of each subtree/node named $h'_{tree_name/node_name}$.

After we balance the tree, the height of each subtree/node named $h''_{tree_name/node_name}$.

There are four unbalanced cases in AVL Tree after an insertion: LL, LR, RL, RR.

1. LL type: Before insertion, tree height $h_x = h_A + 2$. After insertion, $h'_A = h_A + 1$. After right rotation, the tree is balanced. Compute the tree height after balanced, $h''_y = h'_A + 1 = h_x$. Hence, no extra rotation needed to balance the tree.
2. LR type: Before insertion, tree height $h_x = h_A + 2$. Since the tree is unbalanced at node x after insertion, we have $h_A = \max(h_B, h_C) + 1$ and $h_D = \max(h_B, h_C)$. After we balance the tree, the new tree height

$$h''_z = \max(\max(h_A, h_B + 1) + 1, \max(h_C + 1, h_D) + 1) + 1 = h_A + 2 = h_x$$

Hence, no extra rotation needed to balance the tree.

3. RL type: Before insertion, tree height $h_x = h_D + 2$. Since the tree is unbalanced at node x after insertion, we have $h_D = \max(h_B, h_C) + 1$ and $h_A = \max(h_B, h_C)$. After we balance the tree, the new tree height

$$h''_z = \max(\max(h_A, h_B + 1) + 1, \max(h_C + 1, h_D) + 1) + 1 = h_D + 2 = h_x$$

Hence, no extra rotation needed to balance the tree.

4. RR type: Before insertion, tree height $h_x = h_A + 2$. After insertion, $h'_C = h_C + 1$. After left rotation, the tree is balanced. Compute the tree height after balanced, $h''_y = h'_C + 1 = h_x$. Hence, no extra rotation needed to balance the tree.

From the above four cases, we can find that after a single/double rotation, no extra rotation needed to balance the tree.

5 Amortized Analysis

First we named the stack S , with its size $|S| = n$.

- (a) The worst case time complexity of MultiPop is $\min(n, k)$. We know that the time complexity of Pop is $O(1)$. MultiPop(k) repeats $\min(n, k)$ times Pop, hence the time complexity of MultiPop(k) is $\min(n, k) \times O(1) = O(\min(n, k))$
- (b) Suppose that there are $n_{push}, n_{pop}, n_{multipop}$ times of Push, Pop, MultiPop to execute. Note that the legal Pop or MultiPop can only execute when the stack is not empty, we can find that the Push operation needs to be executed same as or more than Pop + MultiPop. That is, $n_{pop} + n_{multipop} \leq n_{push}$.
The total time complexity is $T(n) = n_{push} + n_{pop} + n_{multipop} \leq 2 \cdot n_{push} = O(n)$
Hence, the amortized time complexity of an operation is $O(n)/n = O(1)$

6 Algorithm Design

Input: x , $T.root$
Output: the successor of x

```

1  $n = T.root$   $succ = None$  while  $n$  is not  $None$  do
2   if  $x < n.value$  then
3      $succ = n.value$ 
4      $n = n.left$ 
5   else if  $x \geq n.value$  then
6      $n = n.right$ 
7 end
8 if  $succ$  is not  $None$  then
9   return  $succ$ 
10 else
11   return "cannot find successor in the tree"
```

Algorithm 1: Find successor