

Decompositions


Sophie Woodward

2023-06-08

Generate Data

First let's generate some data using the spectral decomposition. Note that the covariance between X and Z is decreasing with spatial scale by construction (see ρ_{XZ} - things are flipped since spectral decomp projects in order of highest to lowest freq). We assume Y is a linear function of X and Z with coefficients 2 and -1 respectively.

```
par(mfrow = c(1,3))
outsim = sim(5, outcome = 'linear', rhox = seq(0,1, by = 1/(5^4-1)),
             decomposition = 'spectral')
scatterplot3d(x = outsim$coord[,1], outsim$coord[,2], outsim$X,
              color = outsim$state, pch = 20, angle = 60, main = 'Exposure X')
scatterplot3d(x = outsim$coord[,1], outsim$coord[,2], outsim$Y,
              color = outsim$state, pch = 20, angle = 60, main = 'Outcome Y')
scatterplot3d(x = outsim$coord[,1], outsim$coord[,2], outsim$Z,
              main = 'Confounder Z',
              color = outsim$state, pch = 20, angle = 60)
```




Analysis

```

par(mfrow = c(1,2))
testnested = analysis(A = outsim$A,
                      X = outsim$X,
                      Y = outsim$Y,
                      Z = outsim$Z,
                      state = outsim$state,
                      decomposition = 'nested')
plot(1:2, testnested, xlab = 'Spatial Scale', ylab = 'betahat', pch = 19, type = 'l',
     main = 'Nested', xaxp = c(1,2,1), ylim = c(1,3))
points(1:2, testnested, pch = 19)
legend('topright', legend = 'True Beta', col = 'red', lty = 1)
abline(h = 2, col = 'red')

testspectral = analysis(A = outsim$A,
                       X = outsim$X,
                       Y = outsim$Y,
                       Z = outsim$Z,
                       state = outsim$state,
                       decomposition = 'spectral')
plot(1:5, testspectral, xlab = 'Spatial Scale', ylab = 'betahat', pch = 19,
     type = 'l', ylim = c(1,3), main = 'Spectral')
points(1:5, testspectral, pch = 19)
legend('topright', legend = 'True Beta', col = 'red', lty = 1)
abline(h = 2, col = 'red')

```




Below we see that the bias of the $\hat{\beta}_x$ estimates obtained from the spectral decomposition indeed decreases with smaller spatial scale, as desired. This is also true for the nested decomposition but the bias is pretty bad

for both scales.

Repeat this with Nested DGM

Let's generate some data using the nested decomposition. The covariance between X and Z is decreasing with spatial scale by construction (see ρ_{XZ}). Note that we consider only two spatial scales for now. We assume Y is a linear function of X and Z with coefficients 2 and -1 respectively.

```
par(mfrow = c(1,3))
outsim = sim(5, outcome = 'linear', rhox = c(0.9, 0.001),
             decomposition = 'nested')
scatterplot3d(x = outsim$coord[,1], outsim$coord[,2], outsim$X,
              color = outsim$state, pch = 20, angle = 60, main = 'Exposure X')
scatterplot3d(x = outsim$coord[,1], outsim$coord[,2], outsim$Y,
              color = outsim$state, pch = 20, angle = 60, main = 'Outcome Y')
scatterplot3d(x = outsim$coord[,1], outsim$coord[,2], outsim$Z,
              main = 'Confounder Z',
              color = outsim$state, pch = 20, angle = 60)
```



Repeat the analysis

Below we see that the bias of the $\hat{\beta}_x$ estimates obtained from the nested decomposition indeed decreases with smaller spatial scale, as desired. This is also true for the spectral decomposition.

```
par(mfrow = c(1,2))
testnested = analysis(A = outsim$A,
                     X = outsim$X,
```

```

Y = outsim$Y,
Z = outsim$Z,
state = outsim$state,
decomposition = 'nested')

plot(1:2, testnested, xlab = 'Spatial Scale', ylab = 'betahat', pch = 19, type = 'l',
     main = 'Nested', xaxp = c(1,2,1), ylim = c(1,3))
points(1:2, testnested, pch = 19)
legend('topright', legend = 'True Beta', col = 'red', lty = 1)
abline(h = 2, col = 'red')

testspectral = analysis(A = outsim$A,
X = outsim$X,
Y = outsim$Y,
Z = outsim$Z,
state = outsim$state,
decomposition = 'spectral')

plot(1:5, testspectral, xlab = 'Spatial Scale', ylab = 'betahat', pch = 19,
     type = 'l', ylim = c(1,3), main = 'Spectral')
points(1:5, testspectral, pch = 19)
legend('topright', legend = 'True Beta', col = 'red', lty = 1)
abline(h = 2, col = 'red')

```

