◀◀ rewind

Draft · live Vultr demonstration pending

SELECTIVE DATABASE RECOVERY

Restore damaged prices. Keep today’s work.

A bad import changes 120 invoice prices. Your backup has the right prices, but it is missing newer invoices and payment updates.

120
damaged prices to restore

127
current invoices to retain

20
newer payment updates to keep

Fictional invoice example · 6 November 2026

◀◀ rewind

THE DECISION BEFORE RECOVERY

Choose only the damaged cells.

Upload a good backup and today’s consistent snapshot. Select damaged columns and records, then review the exact recovery plan.

APPROACH	INVOICES	NEWER INVOICES	PAYMENT UPDATES
Replace with the whole backup	120	7 lost	20 reset
Restore selected price cells	**127 retained**	**7 retained**	**20 retained**

The comparison and selection plan have passed actual browser checks. These outcomes are also verified by labelled reference recovery tests; a live model recovery remains pending.

The first version handles small SQLite snapshots. It does not write to a production database.

◀◀ rewind

VULTR DEPLOYMENT DESIGN

Try the recovery on copies. Check every change.

1. Inspect

Fixed gVisor workers read the two database snapshots.

2. Generate

Vultr Serverless Inference receives schema and selection metadata, then writes an attempt.

3. Execute

A separate gVisor container runs the attempt on read-only inputs and a temporary output.

4. Verify

A fresh trusted worker reads the output. The controller checks selected and protected values.

The generated program does not receive the acceptance checks. Database rows, files, and actual selected IDs are not sent to the model.

No network · nonroot user · pinned image/runtime · CPU, memory, PID, time and output limits

Download requires a matching recovery contract and confirmed removal of every sandbox. The deploy package targets an existing Vultr VM; live deployment and model execution are pending.

◀◀ rewind

OBSERVED PROOF AND REMAINING WORK

Local recovery checks pass.

- ✓ 17 focused unit tests
- ✓ 10 actual bounded gVisor runs
- ✓ Whole-backup replacement rejected
- ✓ Selected recovery contract passed
- ✓ Every test sandbox removed
- ✓ Desktop/mobile selection workflow

Before submission

Authorize SSH access to the Vultr VM, deploy the reviewed release, run one genuine Vultr recovery, and record a narrated demonstration.

The prototype accepts one matching SQLite table, up to 1,000 records and 256 KiB per snapshot. The user chooses the damaged cells. This is containment evidence, not a security audit.

No independent customer or production-recovery claim is made.