


Final Exam (Graph Mining – Spring 2023)

Full Name:


Student ID:

- The formula and solution process should be presented with the answer.
- All the codes must include detail comments in English.

1. Consider an undirected graph G of eight nodes given in the following figure. There are two communities in the graph: $A = \{0,1,2,3\}$ and $B = \{4,5,6,7\}$. Calculate Min-cut and Normalized cut measurements. (10pt)




2. Consider an undirected graph G of six nodes given in the following figure with two communities: $A = \{1, 2, 3\}$ and $B = \{4, 5, 6\}$. Apply the Equation (1) to calculate the modularity Q of the two communities. (10pt)




$$Q = \frac{1}{2m} \sum_{i,j} \left(A_{ij} - \frac{d_i d_j}{2m} \right) \cdot \delta(v_i, v_j) \quad (1)$$
$$\delta(v_i, v_j) = \begin{cases} 1 & \text{if } v_i \text{ and } v_j \text{ are in the same community.} \\ 0 & \text{otherwise.} \end{cases}$$

where m is the number of edges, A is the adjacency matrix of G, d_i is the degree of node v_i

3. Consider an undirected graph of seven nodes in the following figure. Calculate the edge betweenness of an edge (1,2). (10pt)




4. Consider an undirected graph G of four nodes in the following figure. (10pt)





$$score(i, j) = \beta \tilde{A}_{ij} + \beta^2 \tilde{A}_{ij}^2 \quad (2)$$

Where \tilde{A}_{ij} is the element (i, j) in the normalized adjacency matrix of G , $\beta = 1$ is a parameter of the predictor.


- Calculate the adjacency matrix A , the degree-normalized adjacency matrix \tilde{A} , and 2-step adjacency matrix \tilde{A}^2 of the graph G .
 - The Equation (2) presents the Katz score measurement between two nodes (i, j) . Apply the Equation (2) to calculate the Katz score between two nodes $(1, 2)$.
5. Calculate the graph edit distance between two graphs G_1 and G_2 . The set of elementary graph edit operators includes: vertex insertion, vertex deletion, edge insertion, and edge deletion. In addition, the cost of deletion and insertion operators is 2 and 1, respectively. (5pt)




6. Consider an undirected graph G of seven nodes in the following figure. There are four graphlets g_1, g_2, g_3 , and g_4 . (5pt)
- Count the number of the kernel sub-graphs of limited size 3.
 - Make a feature vector for graph G based on these graphlet kernels.



7. Consider two undirected graphs in the following figure. (10pt)
- Conduct Weisfeiler-Lehman (WL) relabeling process with the maximum degree, 3. Then, using the Weisfeiler-Lehman isomorphism testing, determine whether two graphs are isomorphic or not?
 - Make feature vectors for the graphs based on frequency of node degrees.
 - Make feature vectors for the graphs based on frequency of the WL subgraphs.



8. Consider an undirected graph with eight nodes in the following figure. A biased random walk (Node2Vec algorithm) has the return parameter $p = 0.5$ and the in-out parameter $q = 0.5$. Assume that all edge weights of the graph are 1 and the walker is currently on node G by departing from node E. Calculate transition probabilities from node G to its neighbors. (10pt)



9. Write a python function to compute the degree-normalized adjacency matrix. (10pt)

#Input: a dense adjacency A.

#Output: X, a degree-normalized adjacency matrix ($\tilde{A} = D^{-1}A$, where D is the degree matrix of the graph)

#Note: Students can only use Python code (without using inbuilt functions, such as min, max, sum, etc.). In the NetworkX library, students can use functions 'degree()', 'nodes()', 'has_edge()'.

```
def Normalized(A):
    #YOUR CODE HERE.
    return X
```

10. The bellow function is designed to calculate an Eigenvector centrality for a given graph.

Write codes to fill the blank "YOUR CODE HERE". (20pt)

- Complete the code to measure the Katz centrality.
- Complete the code to measure the PageRank centrality.

```
#Input:
#G: A networkx graph.
#max_iter: integer, maximum number of iterations.
#tol: float, error to check convergence.
#nstart: dictionary, starting value of eigenvector iteration.
#weight: None or string, all edge weights are considered equal.
#alpha: float, attenuation factor
#alpha_pg: float, damping parameter for PageRank, default=0.85.
#beta: scalar, (default=1.0), controls the initial centrality
#Output:
#nodes: dictionary, Dictionary of nodes with centralities as the
value.
```

```
def Eigenvector(G,alpha=0.1,beta=1.0,max_iter=100,tol=1e-4, nstart,
weight, alpha_pg):
    if len(G) == 0:
        print ("cannot compute centrality for the null graph")
        # If no initial vector is provided, start with the all-ones
        vector.
    if nstart is None:
        nstart = {v: 1 for v in G}
    if all(v == 0 for v in nstart.values()):
        print("initial vector cannot have all zero values")
    nstart_sum = sum(nstart.values())
    x = {k: v / nstart_sum for k, v in nstart.items()}
    nnodes = G.number_of_nodes()
    # <For page_rank information>
    D = G.to_directed()
    # Create a copy in (right) stochastic form
    W = nx.stochastic_graph(D, weight=weight)
    # Assign uniform personalization vector if not given
    dangling_weights = dict.fromkeys(W, 1.0 / N)
    dangling_nodes = [n for n in W if W.out_degree(n, weight)== 0.0]
    # </For page_rank information>
    for _ in range(max_iter):
        xlast = x
        x = xlast.copy()
        danglesum = alpha_pg * sum(xlast[n] for n in dangling_nodes)
        # Start with xlast times I to iterate with (A+I)
        # do the multiplication  $y^T = x^T A$  (left eigenvector)
        for n in x:
            for nbr in G[n]:
                w = G[n][nbr].get(weight, 1) if weight else 1
                x[nbr] += xlast[n] * w
            #YOUR CODE HERE
        norm = math.hypot(*x.values()) or 1
        x = {k: v / norm for k, v in x.items()}
        if sum(abs(x[n] - xlast[n]) for n in x) < nnodes * tol:
            return x
```