



CONTENTS

<hr/>	
CHAPTER 1	SolCon User Guide 1
	Introduction 1
	Installing the SolCon Converter 1
	Installing Compiled Binary 1
	Installing and Running from Source 2
	Troubleshooting and Diagnostics 2
	Automating PYTHONPATH 3
<hr/>	
CHAPTER 2	Appendix 5
	Sources 5
	TOML Configuration Files 5
	config-esc.toml 5
	config-sol6.toml 8



CHAPTER

1

SolCon User Guide

Introduction

This document outlines how to use the SolCon tool to convert TOSCA YAML SOL001 files to JSON SOL006 files to be able to load merge into NCS in Rel3 with the SOL6 VNFD model.

Installing the SolCon Converter

You can install the converter in any of the following ways:

- 1 Install the compiled binary on your system and run the converter
- 2 Install and run the converter from the source code

The following sections provide detailed descriptions. This documentation uses solcon-OSX-0.6 download version to provide examples. Be sure to replace `-OSX-0.6` in the commands listed in this documentation with your appropriate operating system and version for the converter tool.

Installing Compiled Binary

- 1 Download the most recent version of SolCon for your operating system (either Mac or Linux) from [here](#).
- 2 Make sure you are able to run the executable file to confirm installation.

```
chmod +x solcon-OSX-0.6
```
- 3 Ensure the input and configuration files are present on your machine.
 - Input files are TOSCA specified YAML files, such as `altiostar_vCU.yaml`.
 - Configuration files are in TOML format
 - TOSCA configuration for ESC VNFDs: [config-esc.toml](#)
 - SOL6 output configuration: [config-sol6.toml](#)

Note: `config-esc.toml` determines how the YAML VNFD is read, and `config-sol6.toml` specifies how the JSON SOL6 VNFD is output.

These are default files and do not need to be modified.

- 4 Run the compiled program from the terminal:

```
./solcon-OSX-0.6 -f altiostar_vCU.yaml -o output_altiostar.json -c config-esc.toml -s config-sol6.toml
```

The argument `-o output_altiostar.json` determines the location and name of the JSON file.

If the program fails to run, download and run the package from the source code. See [the section called “Installing and Running from Source”](#) for more information.

- 5 Load merge the JSON file into NCS.

Instead of entering NCS, run the following terminal command

```
ncs_load -lm -F o altiostar_vCU.json
```

- -lm stands for load merge
- -F is the format
- o is the flag for JSON format

If the file to be load merged is not properly formatted, or is missing some required fields, the ncs_load program will display an error. See [the section called “Troubleshooting and Diagnostics”](#) for more information.

Installing and Running from Source

You can install and run SolCon from the source code if you are unable to install and run from the compiled binary, or if you wish to make changes on your own.

- 1 Download the source code from the repository see [the section called “Sources”](#).
- 2 Download and install Python3 based on your OS.
- 3 Once python3 is installed, run the following command to install the PyYAML and toml packages
`sh tools/setup-script.sh`
- 4 Run the following command to set up the PYTHONPATH variable

```
PYTHONPATH=python/nfvo_solcon_tosca
```

Running the command without a bash script requires that with every unique terminal instance, you must run the command from inside the repository directory. However, you can automate this command to set up the variable and run the program simultaneously. See [the section called “Automating PYTHONPATH”](#) for more information.

- 5 Run the SolCon program

```
python3 solcon.py -f altiostar_vCU.yaml -o output_altiostar.json -c  
config-esc.toml -s config-sol6.toml
```

- 6 Load merge the JSON file into NCS.

Instead of entering NCS, run the following terminal command

```
ncs_load -lm -F o altiostar_vCU.json
```

- -lm stands for load merge
- -F is the format
- o is the flag for JSON format

If the file to be load merged is not properly formatted, or is missing some required fields, the ncs_load program will display an error. See [the section called “Troubleshooting and Diagnostics”](#) for more information.

Troubleshooting and Diagnostics

Run the SolCon converter program with the log-level set to debug.

```
./solcon-OSX-0.6 (...) --log-level DEBUG
```

This helps to capture more log information than running the program in the info mode. Use the log information stored in the logs/ folder to troubleshoot and diagnose any problems that you may encounter with the tool.

Automating PYTHONPATH

Create a bash script as follows to set the PYTHONPATH and run the program simultaneously.

```
#!/usr/bin/env bash
export PYTHONPATH=python/nfvo_solcon_tosca

python3 solcon.py -f altiostar_vCU.yaml -o output_altiostar.json -c config-es
```

This will set the PYTHONPATH and run the program at the same time.

Introduction This document outlines how to use the SolCon tool to convert TOSCA YAML SOL001 files to JSON SOL006 files to be able to load merge into NCS in Rel3 with the SOL6 VNFD model.

Installing the SolCon Converter You can install the converter in any of the following ways: Install the compiled binary on your system and run the converter. Install and run the converter from the source code. The following sections provide detailed descriptions. This documentation uses solcon-OSX-0.6 download version to provide examples. Be sure to replace -OSX-0.6 in the commands listed in this documentation with your appropriate operating system and version for the converter tool.

Installing Compiled Binary Download the most recent version of SolCon for your operating system (either Mac or Linux) from here. Make sure you are able to run the executable file to confirm installation. `chmod +x solcon-OSX-0.6` Ensure the input and configuration files are present on your machine. Input files are TOSCA specified YAML files, such as altiostar_vCU.yaml. Configuration files are in TOML format. TOSCA configuration for ESC VNFDs: config-esc.toml. SOL6 output configuration: config-sol6.toml. Note: config-esc.toml determines how the YAML VNFD is read, and config-sol6.toml specifies how the JSON SOL6 VNFD is output. These are default files and do not need to be modified.

Run the compiled program from the terminal: `./solcon-OSX-0.6 -f altiostar_vCU.yaml -o output_altiostar.json -c config-esc.toml -s config-sol6.toml` The argument `-o output_altiostar.json` determines the location and name of the JSON file. If the program fails to run, download and run the package from the source code. See for more information.

Load merge the JSON file into NCS. Instead of entering NCS, run the following terminal command `ncs_load -lm -F o altiostar_vCU.json -lm` stands for load merge. `-F` is the format. `o` is the flag for JSON format. If the file to be load merged is not properly formatted, or is missing some required fields, the ncs_load program will display an error. See for more information.

Installing and Running from Source You can install and run SolCon from the source code if you are unable to install and run from the compiled binary, or if you wish to make changes on your own. Download the source code from the repository see . Download and install Python3 based on your OS. Once python3 is installed, run the following command to install the PyYAML and toml packages `sh tools/setup-script.sh` Run the following command to set up the PYTHONPATH variable `PYTHONPATH=python/nfvo_solcon_tosca` Running the command without a bash script requires that with every unique terminal instance, you must run the command from inside the repository directory. However, you can automate this command to set up the variable and run the program simultaneously. See for more information.

Run the SolCon program `python3 solcon.py -f altiostar_vCU.yaml -o output_altiostar.json -c config-esc.toml -s config-sol6.toml` Load merge the JSON file into NCS. Instead of entering NCS, run the following terminal command `ncs_load -lm -F o altiostar_vCU.json -lm` stands for load merge. `-F` is the format. `o` is the flag for JSON format. If the file to be load merged is not properly formatted, or is missing some required fields, the ncs_load program will display an error. See for more information.

Troubleshooting and Diagnostics Run the SolCon converter program with the log-level set to debug. `./solcon-OSX-0.6 (...) --log-level DEBUG` This helps to capture more log information than running the program in the info mode. Use the log information stored in the logs/ folder to troubleshoot and diagnose any problems that you may encounter with the tool.

Automating PYTHONPATH Create a bash script as follows to set the PYTHONPATH and run the program simultaneously. `#!/usr/bin/env bash export PYTHONPATH=python/nfvo_solcon_tosca python3`

`solcon.py -f altiostar_vCU.yaml -o output_altiostar.json -c config-esc.toml -s config-sol6.toml` This will set the PYTHONPATH and run the program at the same time.



CHAPTER 2

Appendix

Sources

[Here](#) is the link to the source code for the converter.

If you are installing from the source code, this is where you need to download it. You are free to make modifications to the source code (check the license for specifics.)

TOML Configuration Files

config-esc.toml

```
# These must match with 'provider-identifiers.{'
# If the given provider for a VNFD matches with one of these, then it will automatically
# take the identifiers from this file
providers=["cisco"]

version = "0.1.0"

# All of the identifiers must be the same for all instances of that object,
# multiple IDs for a single type are not supported
[provider_identifiers.cisco]
    vdu = ["type", "cisco.nodes.nfv.Vdu.Compute"]
    int_cpd = ["type", "cisco.nodes.nfv.VduCp"]
    int_cpd_mgmt = ["type", "cisco.nodes.nfv.VduCp"]
    instantiation_level = ["type", "tosca.policies.nfv.VduInstantiationLevels"]
    scaling_aspects = ["type", "tosca.policies.nfv.ScalingAspects"]
    scaling_aspects_deltas = ["type", "tosca.policies.nfv.VduScalingAspectDeltas"]
    virtual_storage = ["type", "cisco.nodes.nfv.Vdu.VirtualBlockStorage"]
    security_group = ["type", "cisco.policies.nfv.SecurityGroupRule"]
    anti_affinity_rule = ["type", "tosca.policies.nfv.AntiAffinityRule"]
    affinity_rule = ["type", "tosca.policies.nfv.AffinityRule"]
    placement_group = ["type", "tosca.groups.nfv.PlacementGroup"]

# Note: If there is a variable with "path_VAL", that means it will not be parsed for the path
# heirarchy, but will instead just be set with the value
# The structure of the TOSCA file, in paths
[tosca]
    topology_template = "topology_template"
    node_templates = ["topology_template", "node_templates"]
    substitution_map = ["topology_template", "substitution_mappings"]
    substitution_req = ["substitution_map", "requirements"]
```

```

policies                = ["topology_template", "policies"]
groups                  = ["topology_template", "groups"]
inputs                  = ["topology_template", "inputs"]
desc                    = "description"
input_key                = "get_input"

# ** VNF Metadata **
vnf                     = ["node_templates", "vnf"]
vnf_prop                = ["vnf", "properties"]
vnf_desc_id             = ["vnf_prop", "descriptor_id"]
vnf_desc_ver            = ["vnf_prop", "descriptor_version"]
vnf_provider            = ["vnf_prop", "provider"]
vnf_product_name        = ["vnf_prop", "product_name"]
vnf_software_ver        = ["vnf_prop", "software_version"]
vnf_product_info_name   = ["vnf_prop", "product_info_name"]
vnf_vnfm_info           = ["vnf_prop", "vnfm_info"]
vnf_conf_props          = ["vnf_prop", "configurable_properties"]
vnf_conf_autoheal       = ["vnf_conf_props", "is_autoheal_enabled"]
vnf_conf_autoscale      = ["vnf_conf_props", "is_autoscale_enabled"]
vnf_lcm_conf            = ["vnf_prop", "lcm_operations_configuration"]
vnf_lcm_heal            = ["vnf_lcm_conf", "heal"]
vnf_lcm_heal_item       = ["vnf_lcm_heal", "{}"]
# Additional configurable parameters
vnf_interfaces          = ["vnf", "interfaces"]
vnf_vnflcm              = ["vnf_interfaces", "Vnflcm"]
vnf_instantiate         = ["vnf_vnflcm", "instantiate"]
vnf_inst_inputs         = ["vnf_instantiate", "inputs"]
vnf_additional_param_list = ["vnf_inst_inputs", "additional_parameters"]
vnf_add_parameter       = ["vnf_additional_param_list", "parameters"]
vnf_add_param_elem      = ["vnf_add_parameter", "{}"]
# These are the variables that will be taken from parameters_list and put into the sol6 VNFD
ADD_PARAMS_VAL          = ["BOOTUP_TIME_SF", "BOOTUP_TIME_CF", "CHASSIS_KEY"]

# ** VDU **
vdu                     = ["node_templates", "{}"]
vdu_props               = ["vdu", "properties"]
vdu_name                = ["vdu_props", "name"]
vdu_boot               = ["vdu_props", "boot_order"]
vdu_desc               = ["vdu_props", "description"]
vdu_conf_props_base     = ["vdu_props", "configurable_properties"]
vdu_conf_props          = ["vdu_conf_props_base", "additional_vnfc_configurable_properties"]

vdu_vim_flavor          = ["vdu_conf_props", "vim_flavor"]
vdu_cap                 = ["vdu", "capabilities"]
vdu_cap_vc              = ["vdu_cap", "virtual_compute"]
vdu_cap_props           = ["vdu_cap_vc", "properties"]
vdu_virt_cpu            = ["vdu_cap_props", "virtual_cpu"]
vdu_virt_cpu_num        = ["vdu_virt_cpu", "num_virtual_cpu"]
vdu_virt_mem            = ["vdu_cap_props", "virtual_memory"]
vdu_virt_mem_size       = ["vdu_virt_mem", "virtual_mem_size"]

vdu_profile             = ["vdu_props", "vdu_profile"]
vdu_prof_inst_min       = ["vdu_profile", "min_number_of_instances"]
vdu_prof_inst_max       = ["vdu_profile", "max_number_of_instances"]

vdu_vendor              = ["vdu_props", "vendor_section"]
vdu_cisco_esc           = ["vdu_vendor", "cisco_esc"]
vdu_day0_list           = ["vdu_cisco_esc", "config_data"]
vdu_day0                = ["vdu_day0_list", "{}"]
vdu_day0_file           = ["vdu_day0", "file"]
vdu_day0_variables      = ["vdu_day0", "variables"]
vdu_day0_variable       = ["vdu_day0_variables", "{}"]

```



```

# ** Do not modify **
vdu_day0_custom_id      = ["vdu_day0", "custom_id"]
# ** End **

# ** Internal Connection Points **
int_cpd                  = ["node_templates", "{}"]
int_cpd_props            = ["int_cpd", "properties"]
int_cpd_req              = ["int_cpd", "requirements"]
int_cpd_virt_binding     = ["int_cpd_req", "virtual_binding"]
int_cpd_virt_link        = ["int_cpd_req", "virtual_link"]
int_cpd_layer_prot       = ["int_cpd_props", "layer_protocols"]
int_cpd_allowed_pair     = ["int_cpd_props", "allowed_address_pairs"]
int_cpd_ip_allowed_addr  = ["int_cpd_allowed_pair", "ip_address"]
int_cpd_ip_addr          = ["int_cpd_props", "ip_address"]
int_cpd_vl_profile       = ["int_cpd_props", "vl_profile"]
int_cpd_virt_prot_data   = ["int_cpd_vl_profile", "virtual_link_protocol_data"]
int_cpd_l3_data          = ["int_cpd_virt_prot_data", "l3_protocol_data"]
int_cpd_cidr             = ["int_cpd_l3_data", "cidr"]
int_cpd_dhcp             = ["int_cpd_l3_data", "dhcp_enabled"]

virt_storage             = ["node_templates", "{}"]

virt_props               = ["virt_storage", "properties"]
virt_artifacts           = ["virt_storage", "artifacts"]
virt_vsb                 = ["virt_props", "virtual_block_storage_data"]
virt_size                = ["virt_vsb", "size_of_storage"]
virt_storage_req         = ["virt_vsb", "vdu_storage_requirements"]
virt_type                = ["virt_storage_req", "type"]

sw_image_data            = ["virt_props", "sw_image_data"]
sw_name                  = ["sw_image_data", "name"]
sw_version               = ["sw_image_data", "version"]
sw_checksum              = ["sw_image_data", "checksum"]
sw_container_fmt         = ["sw_image_data", "container_format"]
sw_disk_fmt              = ["sw_image_data", "disk_format"]
sw_min_disk              = ["sw_image_data", "min_disk"]
sw_size                  = ["sw_image_data", "size"]
sw_image                 = ["virt_artifacts", "sw_image"]
sw_image_file            = ["sw_image", "file"]

# ** Deployment Flavor **
df_id                    = ["vnf_prop", "flavour_id"]
df_desc                  = ["vnf_prop", "flavour_description"]

def_inst_level           = ["policies", "instantiation_levels"]
def_inst_key             = ["default"]
def_inst_prop            = ["def_inst_level", "properties"]
def_inst_p_levels        = ["def_inst_prop", "levels"]
def_inst_def             = ["def_inst_p_levels", "default"]
def_inst_desc            = ["def_inst_def", "description"] # Matches def_inst_key
inst_level               = ["policies", "{}"]
inst_level_targets       = ["inst_level", "targets"]
inst_level_props         = ["inst_level", "properties"]
inst_level_levels        = ["inst_level_props", "levels"]
inst_level_def           = ["inst_level_levels", "default"]
inst_level_num_instances = ["inst_level_def", "number_of_instances"]

# ** Scaling Aspects **

```

```

scaling_aspects          = ["policies", "{}"]
scaling_props            = ["scaling_aspects", "properties"]
scaling_aspect_item_list = ["scaling_props", "aspects"]
scaling_aspect_item      = ["scaling_aspect_item_list", "{}"]
scaling_aspect_name      = ["scaling_aspect_item", "name"]
scaling_aspect_desc      = ["scaling_aspect_item", "description"]
scaling_aspect_level     = ["scaling_aspect_item", "max_scale_level"]
scaling_aspect_deltas    = ["scaling_aspect_item", "step_deltas"]

# For use in the deltas definition block
deltas_aspects          = ["policies", "{}"]
deltas_props            = ["deltas_aspects", "properties"]
deltas_list             = ["deltas_props", "deltas"]
deltas_elem             = ["deltas_list", "{}"]
deltas_num_instances    = ["deltas_elem", "number_of_instances"]
deltas_targets          = ["deltas_aspects", "targets"]
deltas_target           = ["deltas_targets", "{}"]

# ** Security Groups **
security_group          = ["policies", "{}"]
security_group_name     = ["security_group", "group_name"]
security_group_targets  = ["security_group", "targets"]

# ** Affinity/Anti Groups **
affinity_group          = ["policies", "{}"]
affinity_group_props    = ["affinity_group", "properties"]
affinity_group_scope    = ["affinity_group_props", "scope"]
affinity_group_targets  = ["affinity_group", "targets"]

placement_group         = ["groups", "{}"]
placement_members       = ["placement_group", "members"]

[tosca.input_values]
VIM_FLAVOR = "VIM_FLAVOR_INPUT"

```

config-sol6.toml

```

# Sol6 Path configurations

[sol6]
# *****
# ** VNFD **
# *****
vnfd              = "vnfd"
vnfd_id           = ["vnfd", "id"]
vnfd_provider     = ["vnfd", "provider"]
vnfd_product      = ["vnfd", "product-name"]
vnfd_software_ver = ["vnfd", "software-version"]
vnfd_ver          = ["vnfd", "version"]
vnfd_info_name    = ["vnfd", "product-info-name"]
vnfd_info_desc    = ["vnfd", "product-info-description"]
vnfd_vnfm_info    = ["vnfd", "vnfm-info"]

vnfd_config_props = ["vnfd", "configurable-properties"]
vnfd_config_autoheal = ["vnfd_config_props", "is-auto-heal-enabled"]
vnfd_config_autoscale = ["vnfd_config_props", "is-auto-scalable-enabled"]
vnfd_config_additional = ["vnfd_config_props", "additional-configurable-property"]
vnfd_config_add_elem = ["vnfd_config_additional", "{}"]
vnfd_config_add_key  = ["vnfd_config_add_elem", "key"]
vnfd_config_add_value = ["vnfd_config_add_elem", "value"]

PROTOCOLS_PREFIX_VAL = "etsi-nfv-descriptors:"

```

```

VALID_PROTOCOLS_VAL      = ["ethernet", "ipv4", "ipv6", "mpls", "odu2", "pseudo-wire"]
VALID_DISK_FORMATS_VAL   = ["qcow2", "raw", "vmdk"]
VALID_CONTAINER_FORMATS_VAL = ["aki", "ami", "ari", "bare", "docker", "ova", "ovf"]
VALID_AFF_SCOPES_VAL     = ["nfvi-node", "nfvi-pop", "zone", "zone-group"]
VALID_STORAGE_TYPES_VAL  = ["ephemeral-storage", "root-storage", "swap-storage", "cisco"]

# *****
# ** Virtual Compute Descriptor **
# *****
vnfd_virt_compute_desc_base = ["vnfd", "virtual-compute-desc"]
vnfd_virt_compute_desc      = ["vnfd_virt_compute_desc_base", "{}"]
vnfd_vcd_id                 = ["vnfd_virt_compute_desc", "id"]
vnfd_vcd_flavor_name        = ["vnfd_virt_compute_desc", "cisco-etsi-nfvo-soll-vnfd-extended"]
vnfd_virtual_cpu            = ["vnfd_virt_compute_desc", "virtual-cpu"]
vnfd_vcd_cpu_num            = ["vnfd_virtual_cpu", "num-virtual-cpu"]
vnfd_vcd_cpu_clock          = ["vnfd_virtual_cpu", "clock"]
vnfd_vcd_cpu_arch           = ["vnfd_virtual_cpu", "cpu-architecture"]
vnfd_vcd_cpu_oversub        = ["vnfd_virtual_cpu", "oversubscription-policy"]
vnfd_vcd_vdu_cpu_req        = ["vnfd_virtual_cpu", "vdu-cpu-requirements"]
vnfd_vcd_mem                = ["vnfd_virt_compute_desc", "virtual-memory"]
vnfd_vcd_mem_size           = ["vnfd_vcd_mem", "size"]

# *****
# ** Virtual Storage Descriptor **
# *****
vnfd_virt_storage_desc_base = ["vnfd", "virtual-storage-desc"]
vnfd_virt_storage_desc      = ["vnfd_virt_storage_desc_base", "{}"]
vnfd_virt_storage_id        = ["vnfd_virt_storage_desc", "id"]
vnfd_virt_storage_type      = ["vnfd_virt_storage_desc", "type-of-storage"]
VIRT_STORAGE_DEFAULT_VAL    = "root-storage"
vnfd_virt_storage_size      = ["vnfd_virt_storage_desc", "size-of-storage"]
vnfd_virt_storage_sw_image  = ["vnfd_virt_storage_desc", "sw-image-desc"]

# *****
# ** Deployment Flavor **
# *****
deployment_flavor           = ["vnfd", "df"]
df_id                       = ["deployment_flavor", "id"]
df_desc                     = ["deployment_flavor", "description"]
df_inst_level_default       = ["deployment_flavor", "default-instantiation-level"]
df_vdu_profile_list         = ["deployment_flavor", "vdu-profile"]
df_vdu_profile              = ["df_vdu_profile_list", "{}"]
df_vdu_prof_id              = ["df_vdu_profile", "id"]
df_vdu_prof_inst_min        = ["df_vdu_profile", "min-number-of-instances"]
df_vdu_prof_inst_max        = ["df_vdu_profile", "max-number-of-instances"]
df_vdu_prof_aff_group_list  = ["df_vdu_profile", "affinity-or-anti-affinity-group"]
df_vdu_prof_aff_group       = ["df_vdu_prof_aff_group_list", "{}"]
df_vdu_prof_aff_group_id    = ["df_vdu_prof_aff_group", "id"]

# -- Instantiation Level
df_inst_level_base          = ["deployment_flavor", "instantiation-level"]
df_inst_level               = ["df_inst_level_base", "{}"]
df_inst_level_id            = ["df_inst_level", "id"]
df_inst_level_desc          = ["df_inst_level", "description"]
df_inst_level_vdu_level_lst = ["df_inst_level", "vdu-level"]
df_inst_level_vdu_level     = ["df_inst_level_vdu_level_lst", "{}"]
df_inst_level_vdu_vdu       = ["df_inst_level_vdu_level", "vdu-id"]
df_inst_level_vdu_num        = ["df_inst_level_vdu_level", "number-of-instances"]
# -- Scaling Info
df_inst_scaling_info_list   = ["df_inst_level", "scaling-info"]
df_inst_scaling_info        = ["df_inst_scaling_info_list", "{}"]
df_inst_scaling_aspect      = ["df_inst_scaling_info", "id"]

```

```

df_inst_scaling_level      = ["df_inst_scaling_info", "scale-level"]

df_scale_aspect_list      = ["deployment_flavor", "scaling-aspect"]
df_scale_aspect           = ["df_scale_aspect_list", "{}"]
df_scale_aspect_id        = ["df_scale_aspect", "id"]
df_scale_aspect_name      = ["df_scale_aspect", "name"]
df_scale_aspect_desc      = ["df_scale_aspect", "description"]
df_scale_aspect_max_level = ["df_scale_aspect", "max-scale-level"]
df_scale_aspect_delta_det = ["df_scale_aspect", "aspect-delta-details"]
df_scale_aspect_deltas_list = ["df_scale_aspect_delta_det", "deltas"]
df_scale_aspect_deltas    = ["df_scale_aspect_deltas_list", "{}"]
df_scale_aspect_deltas_id = ["df_scale_aspect_deltas", "id"]
df_scale_aspect_vdu_delta_lst = ["df_scale_aspect_deltas", "vdu-delta"]
df_scale_aspect_vdu_delta = ["df_scale_aspect_vdu_delta_lst", "{}"]
df_scale_aspect_vdu_id    = ["df_scale_aspect_vdu_delta", "id"]
df_scale_aspect_vdu_num   = ["df_scale_aspect_vdu_delta", "number-of-instances"]
df_scale_aspect_no_delta_VAL = "unknown"

df_affinity_group_list    = ["deployment_flavor", "affinity-or-anti-affinity-group"]
df_affinity_group         = ["df_affinity_group_list", "{}"]
df_affinity_id            = ["df_affinity_group", "id"]
df_affinity_type          = ["df_affinity_group", "type"]
df_affinity_scope         = ["df_affinity_group", "scope"]
affinity_VAL              = "affinity"
anti_affinity_VAL         = "anti-affinity"

df_lcm_config              = ["deployment_flavor", "lcm-operations-configuration"]
df_lcm_heal_config        = ["df_lcm_config", "heal-vnf-op-config"]
df_heal_param_base        = ["df_lcm_heal_config", "parameter"]
df_heal_param             = ["df_heal_param_base", "{}"]
df_heal_param_key         = ["df_heal_param", "key"]
df_heal_param_value       = ["df_heal_param", "value"]

# *****
# ** Virtual/External Links **
# *****
virt_link_desc_base       = ["vnfd", "int-virtual-link-desc"]
virt_link_desc            = ["virt_link_desc_base", "{}"]
virt_link_desc_id         = ["virt_link_desc", "id"]
virt_link_desc_desc       = ["virt_link_desc", "description"]
virt_link_desc_conn       = ["virt_link_desc", "connectivity-type"]
virt_link_desc_protocol   = ["virt_link_desc_conn", "layer-protocol"]
virt_link_desc_flow       = ["virt_link_desc_conn", "flow-pattern"]
virt_link_desc_add_params = ["virt_link_desc", "cisco-etsi-nfvo-soll-vnfd-extensions:addit"]
virt_link_desc_cidr       = ["virt_link_desc_add_params", "cidr-variable"]
virt_link_desc_dhcp       = ["virt_link_desc_add_params", "dhcp-enabled-variable"]

ext_cpd_base              = ["vnfd", "ext-cpd"]
ext_cpd                   = ["ext_cpd_base", "{}"]
ext_cpd_id                = ["ext_cpd", "id"]
ext_cpd_protocol          = ["ext_cpd", "layer-protocol"]
ext_cpd_virt_link         = ["ext_cpd", "int-virtual-link-desc"]
ext_cpd_role              = ["ext_cpd", "role"]
ext_cpd_vdu               = ["ext_cpd", "int-cpd"]
ext_cpd_vdu_id            = ["ext_cpd_vdu", "vdu-id"]
ext_cpd_int_cpd_id        = ["ext_cpd_vdu", "cpd"]

#ext_cpd_int_cpd          = ["ext_cpd", "int-cpd"]
#ext_cpd_icp_vdu          = ["ext_cpd_int_cpd", "vdu"]
#ext_cpd_icp_cpd          = ["ext_cpd_int_cpd", "cpd"]

```

```

# *****
# ** VDU **
# *****
vdus = ["vnfd", "vdu"]
vdu = ["vdus", "{}"]
vdu_name = ["vdu", "name"]
vdu_desc = ["vdu", "description"]
vdu_id = ["vdu", "id"]
vdu_boot_order_list = ["vdu", "boot-order"]
vdu_boot_order = ["vdu_boot_order_list", "{}"]
vdu_boot_key = ["vdu_boot_order", "key"]
vdu_boot_value = ["vdu_boot_order", "value"]
vdu_vc_desc_list = ["vdu", "virtual-compute-desc"]
vdu_vc_desc = ["vdu_vc_desc_list", "{}"]
vdu_vs_desc_list = ["vdu", "virtual-storage-desc"]
vdu_vs_desc = ["vdu_vs_desc_list", "{}"]
vdu_sw_image_desc_list = ["vdu", "sw-image-desc"]
vdu_sw_image_desc = ["vdu_sw_image_desc_list", "{}"]

vdu_artifact = ["vdu", "cisco-etsi-nfvo:artifact"]

# *****
# ** Internal Connection Points **
# *****
int_cpd_list = ["vdu", "int-cpd"]
int_cpd = ["int_cpd_list", "{}"]
int_cpd_id = ["int_cpd", "id"]
int_cpd_layer_prot = ["int_cpd", "layer-protocol"]
int_cpd_virt_link_desc = ["int_cpd", "int-virtual-link-desc"]
int_cpd_role = ["int_cpd", "role"]
int_cpd_interface_id = ["int_cpd", "cisco-etsi-nfvo:interface-id"]
int_cpd_management = ["int_cpd", "cisco-etsi-nfvo:management"]
int_cpd_management_VAL = ["null"]
int_cpd_additional_params = ["int_cpd", "cisco-etsi-nfvo-soll-vnfd-extensions:additional-params"]
int_cpd_allowed_addr = ["int_cpd_additional_params", "allowed-address-variable"]
int_cpd_ip_addr = ["int_cpd_additional_params", "ip-address-variable"]
int_cpd_security = ["int_cpd_additional_params", "security-group-variable"]

KEY_VIRT_LINK_MGMT_VAL = "VIM_NETWORK_MANAGEMENT-VL"
KEY_VIRT_LINK_MGMT_PROT_VAL = "etsi-nfv-descriptors:ipv4"
KEY_VIRT_LINK_ORCH_VAL = "VIM_NETWORK_ORCHESTRATION-VL"
KEY_VIRT_LINK_ORCH_PROT_VAL = "etsi-nfv-descriptors:ipv4"
KEY_EXT_CP_MGMT_VAL = "VIM_NETWORK_MANAGEMENT"
KEY_EXT_CP_MGMT_PROT_VAL = "etsi-nfv-descriptors:ipv4"
KEY_EXT_CP_ORCH_VAL = "VIM_NETWORK_ORCHESTRATION"
KEY_EXT_CP_ORCH_PROT_VAL = "etsi-nfv-descriptors:ipv4"

# *****
# ** Software Image Descriptor **
# *****
sw_img_desc_base = ["vnfd", "sw-image-desc"]
sw_img_desc = ["sw_img_desc_base", "{}"]
sw_id = ["sw_img_desc", "id"]
sw_name = ["sw_img_desc", "name"]
sw_image_name_var = ["sw_img_desc", "cisco-etsi-nfvo-soll-vnfd-extensions:image-name"]
sw_version = ["sw_img_desc", "version"]
sw_checksum = ["sw_img_desc", "checksum"]
sw_checksum_hash = ["sw_checksum", "hash"]
sw_checksum_algorithm = ["sw_checksum", "algorithm"]
sw_checksum_algorithm_VAL = "sha-256"
sw_container_format = ["sw_img_desc", "container-format"]

```

```

sw_disk_format          = ["sw_img_desc", "disk-format"]
sw_min_disk             = ["sw_img_desc", "min-disk"]
sw_min_ram              = ["sw_img_desc", "min-ram"]
sw_size                 = ["sw_img_desc", "size"]
sw_image                = ["sw_img_desc", "image"]
sw_operating_sys        = ["sw_img_desc", "operating-system"]
sw_supp_virt_envIRON    = ["sw_img_desc", "supported-virtualization-environment"]

# *****
# ** Artifact **
# *****
artifact_base           = ["vnfd", "cisco-etsi-nfvo:artifact"]
artifact                = ["artifact_base", "{}"]
artifact_id             = ["artifact", "id"]
artifact_dest           = ["artifact", "destination-name"]
artifact_url            = ["artifact", "url"]
artifact_variable_list  = ["artifact", "variable"]
artifact_variable       = ["artifact_variable_list", "{}"]
artifact_variable_id    = ["artifact_variable", "id"]
artifact_variable_desc  = ["artifact_variable", "description"]
artifact_checksum       = ["artifact", "checksum"]
artifact_hash           = ["artifact_checksum", "hash"]
artifact_algorithm      = ["artifact_checksum", "algorithm"]
artifact_hash_DUMMY_VAL = "9af30fce37a4c5c831e095745744d6d2"
artifact_algorithm_DUMMY_VAL = "etsi-nfv-descriptors:sha-256"

```

Sources Here is the link to the source code for the converter. If you are installing from the source code, this is where you need to download it. You are free to make modifications to the source code (check the license for specifics.) TOML Configuration Files

```

config-esc.toml # These must match with 'provider-identifiers.{' # If the given provider for a VNFD matches with one of these, then it will automatically # take the identifiers from this file providers=["cisco"] version = "0.1.0" # All of the identifiers must be the same for all instances of that object, # multiple IDs for a single type are not supported [provider_identifiers.cisco] vdu = ["type", "cisco.nodes.nfv.Vdu.Compute"] int_cpd = ["type", "cisco.nodes.nfv.VduCp"] int_cpd_mgmt = ["type", "cisco.nodes.nfv.VduCp"] instantiation_level = ["type", "tosca.policies.nfv.VduInstantiationLevels"] scaling_aspects = ["type", "tosca.policies.nfv.ScalingAspects"] scaling_aspects_deltas = ["type", "tosca.policies.nfv.VduScalingAspectDeltas"] virtual_storage = ["type", "cisco.nodes.nfv.Vdu.VirtualBlockStorage"] security_group = ["type", "cisco.policies.nfv.SecurityGroupRule"] anti_affinity_rule = ["type", "tosca.policies.nfv.AntiAffinityRule"] affinity_rule = ["type", "tosca.policies.nfv.AffinityRule"] placement_group = ["type", "tosca.groups.nfv.PlacementGroup"] # Note: If there is a variable with "path_VAL", that means it will not be parsed for the path # heirarchy, but will instead just be set with the value # The structure of the TOSCA file, in paths [tosca] topology_template = "topology_template" node_templates = ["topology_template", "node_templates"] substitution_map = ["topology_template", "substitution_mappings"] substitution_req = ["substitution_map", "requirements"] policies = ["topology_template", "policies"] groups = ["topology_template", "groups"] inputs = ["topology_template", "inputs"] desc = "description" input_key = "get_input" # ** VNF Metadata ** vnf = ["node_templates", "vnf"] vnf_prop = ["vnf", "properties"] vnf_desc_id = ["vnf_prop", "descriptor_id"] vnf_desc_ver = ["vnf_prop", "descriptor_version"] vnf_provider = ["vnf_prop", "provider"] vnf_product_name = ["vnf_prop", "product_name"] vnf_software_ver = ["vnf_prop", "software_version"] vnf_product_info_name = ["vnf_prop", "product_info_name"] vnf_vnfm_info = ["vnf_prop", "vnfm_info"] vnf_conf_props = ["vnf_prop", "configurable_properties"] vnf_conf_autoheal = ["vnf_conf_props", "is_autoheal_enabled"] vnf_conf_autoscale = ["vnf_conf_props", "is_autoscale_enabled"] vnf_lcm_conf = ["vnf_prop", "lcm_operations_configuration"] vnf_lcm_heal = ["vnf_lcm_conf", "heal"] vnf_lcm_heal_item = ["vnf_lcm_heal", "{}"] # Additional configurable parameters vnf_interfaces = ["vnf", "interfaces"] vnf_vnflcm = ["vnf_interfaces", "Vnflcm"]

```

```

vnf_instantiate = ["vnf_vnflcm", "instantiate"] vnf_inst_inputs = ["vnf_instantiate", "inputs"]
vnf_additional_param_list = ["vnf_inst_inputs", "additional_parameters"] vnf_add_parameter
= ["vnf_additional_param_list", "parameters"] vnf_add_param_elem = ["vnf_add_parameter",
"{ }"] # These are the variables that will be taken from parameters_list and put into the sol6 VNFD
ADD_PARAMS_VAL = ["BOOTUP_TIME_SF", "BOOTUP_TIME_CF", "CHASSIS_KEY"] # ** VDU
** vdu = ["node_templates", "{ }"] vdu_props = ["vdu", "properties"] vdu_name = ["vdu_props", "name"]
vdu_boot = ["vdu_props", "boot_order"] vdu_desc = ["vdu_props", "description"] vdu_conf_props_base
= ["vdu_props", "configurable_properties"] vdu_conf_props = ["vdu_conf_props_base",
"additional_vnfc_configurable_properties"] vdu_vim_flavor = ["vdu_conf_props", "vim_flavor"]
vdu_cap = ["vdu", "capabilities"] vdu_cap_vc = ["vdu_cap", "virtual_compute"] vdu_cap_props =
["vdu_cap_vc", "properties"] vdu_virt_cpu = ["vdu_cap_props", "virtual_cpu"] vdu_virt_cpu_num
= ["vdu_virt_cpu", "num_virtual_cpu"] vdu_virt_mem = ["vdu_cap_props", "virtual_memory"]
vdu_virt_mem_size = ["vdu_virt_mem", "virtual_mem_size"] vdu_profile = ["vdu_props",
"vdu_profile"] vdu_prof_inst_min = ["vdu_profile", "min_number_of_instances"] vdu_prof_inst_max
= ["vdu_profile", "max_number_of_instances"] vdu_vendor = ["vdu_props", "vendor_section"]
vdu_cisco_esc = ["vdu_vendor", "cisco_esc"] vdu_day0_list = ["vdu_cisco_esc", "config_data"]
vdu_day0 = ["vdu_day0_list", "{ }"] vdu_day0_file = ["vdu_day0", "file"] vdu_day0_variables =
["vdu_day0", "variables"] vdu_day0_variable = ["vdu_day0_variables", "{ }"] # ** Do not modify
** vdu_day0_custom_id = ["vdu_day0", "custom_id"] # ** End ** # ** Internal Connection Points
** int_cpd = ["node_templates", "{ }"] int_cpd_props = ["int_cpd", "properties"] int_cpd_req =
["int_cpd", "requirements"] int_cpd_virt_binding = ["int_cpd_req", "virtual_binding"] int_cpd_virt_link
= ["int_cpd_req", "virtual_link"] int_cpd_layer_prot = ["int_cpd_props", "layer_protocols"]
int_cpd_allowed_pair = ["int_cpd_props", "allowed_address_pairs"] int_cpd_ip_allowed_addr
= ["int_cpd_allowed_pair", "ip_address"] int_cpd_ip_addr = ["int_cpd_props", "ip_address"]
int_cpd_vl_profile = ["int_cpd_props", "vl_profile"] int_cpd_virt_prot_data = ["int_cpd_vl_profile",
"virtual_link_protocol_data"] int_cpd_l3_data = ["int_cpd_virt_prot_data", "l3_protocol_data"]
int_cpd_cidr = ["int_cpd_l3_data", "cidr"] int_cpd_dhcp = ["int_cpd_l3_data", "dhcp_enabled"]
virt_storage = ["node_templates", "{ }"] virt_props = ["virt_storage", "properties"] virt_artifacts
= ["virt_storage", "artifacts"] virt_vsb = ["virt_props", "virtual_block_storage_data"] virt_size
= ["virt_vsb", "size_of_storage"] virt_storage_req = ["virt_vsb", "vdu_storage_requirements"]
virt_type = ["virt_storage_req", "type"] sw_image_data = ["virt_props", "sw_image_data"]
sw_name = ["sw_image_data", "name"] sw_version = ["sw_image_data", "version"] sw_checksum
= ["sw_image_data", "checksum"] sw_container_fmt = ["sw_image_data", "container_format"]
sw_disk_fmt = ["sw_image_data", "disk_format"] sw_min_disk = ["sw_image_data", "min_disk"]
sw_size = ["sw_image_data", "size"] sw_image = ["virt_artifacts", "sw_image"] sw_image_file
= ["sw_image", "file"] # ** Deployment Flavor ** df_id = ["vnf_prop", "flavour_id"] df_desc =
["vnf_prop", "flavour_description"] def_inst_level = ["policies", "instantiation_levels"] def_inst_key =
"default" def_inst_prop = ["def_inst_level", "properties"] def_inst_p_levels = ["def_inst_prop", "levels"]
def_inst_def = ["def_inst_p_levels", "default"] def_inst_desc = ["def_inst_def", "description"] # Matches
def_inst_key inst_level = ["policies", "{ }"] inst_level_targets = ["inst_level", "targets"] inst_level_props
= ["inst_level", "properties"] inst_level_levels = ["inst_level_props", "levels"] inst_level_def =
["inst_level_levels", "default"] inst_level_num_instances = ["inst_level_def", "number_of_instances"] # **
Scaling Aspects ** scaling_aspects = ["policies", "{ }"] scaling_props = ["scaling_aspects", "properties"]
scaling_aspect_item_list = ["scaling_props", "aspects"] scaling_aspect_item = ["scaling_aspect_item_list",
"{ }"] scaling_aspect_name = ["scaling_aspect_item", "name"] scaling_aspect_desc =
["scaling_aspect_item", "description"] scaling_aspect_level = ["scaling_aspect_item", "max_scale_level"]
scaling_aspect_deltas = ["scaling_aspect_item", "step_deltas"] # For use in the deltas definition
block deltas_aspects = ["policies", "{ }"] deltas_props = ["deltas_aspects", "properties"] deltas_list =
["deltas_props", "deltas"] deltas_elem = ["deltas_list", "{ }"] deltas_num_instances = ["deltas_elem",
"number_of_instances"] deltas_targets = ["deltas_aspects", "targets"] deltas_target = ["deltas_targets",
"{ }"] # ** Security Groups ** security_group = ["policies", "{ }"] security_group_name =
["security_group", "group_name"] security_group_targets = ["security_group", "targets"] # ** Affinity/

```

```

Anti Groups ** affinity_group = ["policies", "{}"] affinity_group_props = ["affinity_group", "properties"]
affinity_group_scope = ["affinity_group_props", "scope"] affinity_group_targets = ["affinity_group",
"targets"] placement_group = ["groups", "{}"] placement_members = ["placement_group", "members"]
[osca.input_values] VIM_FLAVOR = "VIM_FLAVOR_INPUT" config-sol6.toml # Sol6 Path
configurations [sol6] # ***** # ** VNFD ** # ***** vnfd = "vnfd" vnfd_id = ["vnfd",
"id"] vnfd_provider = ["vnfd", "provider"] vnfd_product = ["vnfd", "product-name"] vnfd_software_ver
= ["vnfd", "software-version"] vnfd_ver = ["vnfd", "version"] vnfd_info_name = ["vnfd", "product-
info-name"] vnfd_info_desc = ["vnfd", "product-info-description"] vnfd_vnfm_info = ["vnfd",
"vnfm-info"] vnfd_config_props = ["vnfd", "configurable-properties"] vnfd_config_autoheal =
["vnfd_config_props", "is-auto-heal-enabled"] vnfd_config_autoscale = ["vnfd_config_props", "is-
auto-scalable-enabled"] vnfd_config_additional = ["vnfd_config_props", "additional-configurable-
property"] vnfd_config_add_elem = ["vnfd_config_additional", "{}"] vnfd_config_add_key =
["vnfd_config_add_elem", "key"] vnfd_config_add_value = ["vnfd_config_add_elem", "value"]
PROTOCOLS_PREFIX_VAL = "etsi-nfv-descriptors:" VALID_PROTOCOLS_VAL = ["ethernet",
"ipv4", "ipv6", "mpls", "odu2", "pseudo-wire"] VALID_DISK_FORMATS_VAL = ["qcow2",
"raw", "vmdk"] VALID_CONTAINER_FORMATS_VAL = ["aki", "ami", "ari", "bare", "docker",
"ova", "ovf"] VALID_AFF_SCOPES_VAL = ["nfvi-node", "nfvi-pop", "zone", "zone-group"]
VALID_STORAGE_TYPES_VAL = ["ephemeral-storage", "root-storage", "swap-storage", "cisco-
etsi-nfvo:volume-storage"] # ***** # ** Virtual Compute Descriptor
** # ***** vnfd_virt_compute_desc_base = ["vnfd", "virtual-
compute-desc"] vnfd_virt_compute_desc = ["vnfd_virt_compute_desc_base", "{}"] vnfd_vcd_id =
["vnfd_virt_compute_desc", "id"] vnfd_vcd_flavor_name = ["vnfd_virt_compute_desc", "cisco-etsi-
nfvo-sol1-vnfd-extensions:flavour-name-variable"] vnfd_virtual_cpu = ["vnfd_virt_compute_desc",
"virtual-cpu"] vnfd_vcd_cpu_num = ["vnfd_virtual_cpu", "num-virtual-cpu"] vnfd_vcd_cpu_clock
= ["vnfd_virtual_cpu", "clock"] vnfd_vcd_cpu_arch = ["vnfd_virtual_cpu", "cpu-architecture"]
vnfd_vcd_cpu_oversub = ["vnfd_virtual_cpu", "oversubscription-policy"] vnfd_vcd_vdu_cpu_req =
["vnfd_virtual_cpu", "vdu-cpu-requirements"] vnfd_vcd_mem = ["vnfd_virt_compute_desc", "virtual-
memory"] vnfd_vcd_mem_size = ["vnfd_vcd_mem", "size"] # ***** #
** Virtual Storage Descriptor ** # ***** vnfd_virt_storage_desc_base
= ["vnfd", "virtual-storage-desc"] vnfd_virt_storage_desc = ["vnfd_virt_storage_desc_base",
"{}"] vnfd_virt_storage_id = ["vnfd_virt_storage_desc", "id"] vnfd_virt_storage_type =
["vnfd_virt_storage_desc", "type-of-storage"] VIRT_STORAGE_DEFAULT_VAL = "root-storage"
vnfd_virt_storage_size = ["vnfd_virt_storage_desc", "size-of-storage"] vnfd_virt_storage_sw_image =
["vnfd_virt_storage_desc", "sw-image-desc"] # ***** # ** Deployment Flavor
** # ***** deployment_flavor = ["vnfd", "df"] df_id = ["deployment_flavor",
"id"] df_desc = ["deployment_flavor", "description"] df_inst_level_default = ["deployment_flavor",
"default-instantiation-level"] df_vdu_profile_list = ["deployment_flavor", "vdu-profile"] df_vdu_profile
= ["df_vdu_profile_list", "{}"] df_vdu_prof_id = ["df_vdu_profile", "id"] df_vdu_prof_inst_min =
["df_vdu_profile", "min-number-of-instances"] df_vdu_prof_inst_max = ["df_vdu_profile", "max-
number-of-instances"] df_vdu_prof_aff_group_list = ["df_vdu_profile", "affinity-or-anti-affinity-
group"] df_vdu_prof_aff_group = ["df_vdu_prof_aff_group_list", "{}"] df_vdu_prof_aff_group_id =
["df_vdu_prof_aff_group", "id"] # -- Instantiation Level df_inst_level_base = ["deployment_flavor",
"instantiation-level"] df_inst_level = ["df_inst_level_base", "{}"] df_inst_level_id = ["df_inst_level",
"id"] df_inst_level_desc = ["df_inst_level", "description"] df_inst_level_vdu_level_list = ["df_inst_level",
"vdu-level"] df_inst_level_vdu_level = ["df_inst_level_vdu_level_list", "{}"] df_inst_level_vdu_vdu
= ["df_inst_level_vdu_level", "vdu-id"] df_inst_level_vdu_num = ["df_inst_level_vdu_level",
"number-of-instances"] # -- Scaling Info df_inst_scaling_info_list = ["df_inst_level", "scaling-
info"] df_inst_scaling_info = ["df_inst_scaling_info_list", "{}"] df_inst_scaling_aspect =
["df_inst_scaling_info", "id"] df_inst_scaling_level = ["df_inst_scaling_info", "scale-level"]
df_scale_aspect_list = ["deployment_flavor", "scaling-aspect"] df_scale_aspect = ["df_scale_aspect_list",
"{}"] df_scale_aspect_id = ["df_scale_aspect", "id"] df_scale_aspect_name = ["df_scale_aspect",
"name"] df_scale_aspect_desc = ["df_scale_aspect", "description"] df_scale_aspect_max_level =

```



```

["df_scale_aspect", "max-scale-level"] df_scale_aspect_delta_det = ["df_scale_aspect", "aspect-delta-
details"] df_scale_aspect_deltas_list = ["df_scale_aspect_delta_det", "deltas"] df_scale_aspect_deltas
= ["df_scale_aspect_deltas_list", "{}"] df_scale_aspect_deltas_id = ["df_scale_aspect_deltas", "id"]
df_scale_aspect_vdu_delta_list = ["df_scale_aspect_deltas", "vdu-delta"] df_scale_aspect_vdu_delta
= ["df_scale_aspect_vdu_delta_list", "{}"] df_scale_aspect_vdu_id = ["df_scale_aspect_vdu_delta",
"id"] df_scale_aspect_vdu_num = ["df_scale_aspect_vdu_delta", "number-of-instances"]
df_scale_aspect_no_delta_VAL = "unknown" df_affinity_group_list = ["deployment_flavor",
"affinity-or-anti-affinity-group"] df_affinity_group = ["df_affinity_group_list", "{}"] df_affinity_id
= ["df_affinity_group", "id"] df_affinity_type = ["df_affinity_group", "type"] df_affinity_scope
= ["df_affinity_group", "scope"] affinity_VAL = "affinity" anti_affinity_VAL = "anti-affinity"
df_lcm_config = ["deployment_flavor", "lcm-operations-configuration"] df_lcm_heal_config =
["df_lcm_config", "heal-vnf-op-config"] df_heal_param_base = ["df_lcm_heal_config", "parameter"]
df_heal_param = ["df_heal_param_base", "{}"] df_heal_param_key = ["df_heal_param", "key"]
df_heal_param_value = ["df_heal_param", "value"] # ***** # **
Virtual/External Links ** # ***** virt_link_desc_base = ["vnfd",
"int-virtual-link-desc"] virt_link_desc = ["virt_link_desc_base", "{}"] virt_link_desc_id =
["virt_link_desc", "id"] virt_link_desc_desc = ["virt_link_desc", "description"] virt_link_desc_conn
= ["virt_link_desc", "connectivity-type"] virt_link_desc_protocol = ["virt_link_desc_conn", "layer-
protocol"] virt_link_desc_flow = ["virt_link_desc_conn", "flow-pattern"] virt_link_desc_add_params
= ["virt_link_desc", "cisco-etsi-nfvo-sol1-vnfd-extensions:additional-sol1-parameters"]
virt_link_desc_cidr = ["virt_link_desc_add_params", "cidr-variable"] virt_link_desc_dhcp =
["virt_link_desc_add_params", "dhcp-enabled-variable"] ext_cpd_base = ["vnfd", "ext-cpd"] ext_cpd
= ["ext_cpd_base", "{}"] ext_cpd_id = ["ext_cpd", "id"] ext_cpd_protocol = ["ext_cpd", "layer-
protocol"] ext_cpd_virt_link = ["ext_cpd", "int-virtual-link-desc"] ext_cpd_role = ["ext_cpd", "role"]
ext_cpd_vdu = ["ext_cpd", "int-cpd"] ext_cpd_vdu_id = ["ext_cpd_vdu", "vdu-id"] ext_cpd_int_cpd_id
= ["ext_cpd_vdu", "cpd"] #ext_cpd_int_cpd = ["ext_cpd", "int-cpd"] #ext_cpd_icp_vdu =
["ext_cpd_int_cpd", "vdu"] #ext_cpd_icp_cpd = ["ext_cpd_int_cpd", "cpd"] # ***** # **
VDU ** # ***** vdus = ["vnfd", "vdu"] vdu = ["vdus", "{}"] vdu_name = ["vdu", "name"]
vdu_desc = ["vdu", "description"] vdu_id = ["vdu", "id"] vdu_boot_order_list = ["vdu", "boot-
order"] vdu_boot_order = ["vdu_boot_order_list", "{}"] vdu_boot_key = ["vdu_boot_order", "key"]
vdu_boot_value = ["vdu_boot_order", "value"] vdu_vc_desc_list = ["vdu", "virtual-compute-
desc"] vdu_vc_desc = ["vdu_vc_desc_list", "{}"] vdu_vs_desc_list = ["vdu", "virtual-storage-
desc"] vdu_vs_desc = ["vdu_vs_desc_list", "{}"] vdu_sw_image_desc_list = ["vdu", "sw-image-
desc"] vdu_sw_image_desc = ["vdu_sw_image_desc_list", "{}"] vdu_artifact = ["vdu", "cisco-
etsi-nfvo:artifact"] # ***** # ** Internal Connection Points ** #
***** int_cpd_list = ["vdu", "int-cpd"] int_cpd = ["int_cpd_list", "{}"]
int_cpd_id = ["int_cpd", "id"] int_cpd_layer_prot = ["int_cpd", "layer-protocol"] int_cpd_virt_link_desc
= ["int_cpd", "int-virtual-link-desc"] int_cpd_role = ["int_cpd", "role"] int_cpd_interface_id = ["int_cpd",
"cisco-etsi-nfvo:interface-id"] int_cpd_management = ["int_cpd", "cisco-etsi-nfvo:management"]
int_cpd_management_VAL = "[null]" int_cpd_additional_params = ["int_cpd", "cisco-etsi-nfvo-sol1-
vnfd-extensions:additional-sol1-parameters"] int_cpd_allowed_addr = ["int_cpd_additional_params",
"allowed-address-variable"] int_cpd_ip_addr = ["int_cpd_additional_params", "ip-
address-variable"] int_cpd_security = ["int_cpd_additional_params", "security-group-
variable"] KEY_VIRT_LINK_MGMT_VAL = "VIM_NETWORK_MANAGEMENT-VL"
KEY_VIRT_LINK_MGMT_PROT_VAL = "etsi-nfv-descriptors:ipv4" KEY_VIRT_LINK_ORCH_VAL
= "VIM_NETWORK_ORCHESTRATION-VL" KEY_VIRT_LINK_ORCH_PROT_VAL = "etsi-
nfv-descriptors:ipv4" KEY_EXT_CP_MGMT_VAL = "VIM_NETWORK_MANAGEMENT"
KEY_EXT_CP_MGMT_PROT_VAL = "etsi-nfv-descriptors:ipv4" KEY_EXT_CP_ORCH_VAL
= "VIM_NETWORK_ORCHESTRATION" KEY_EXT_CP_ORCH_PROT_VAL = "etsi-nfv-
descriptors:ipv4" # ***** # ** Software Image Descriptor ** #
***** sw_img_desc_base = ["vnfd", "sw-image-desc"] sw_img_desc
= ["sw_img_desc_base", "{}"] sw_id = ["sw_img_desc", "id"] sw_name = ["sw_img_desc", "name"]

```

```

sw_image_name_var = ["sw_img_desc", "cisco-etsi-nfvo-sol1-vnfd-extensions:image-name-
variable"] sw_version = ["sw_img_desc", "version"] sw_checksum = ["sw_img_desc", "checksum"]
sw_checksum_hash = ["sw_checksum", "hash"] sw_checksum_algorithm = ["sw_checksum",
"algorithm"] sw_checksum_algorithm_VAL = "sha-256" sw_container_format = ["sw_img_desc",
"container-format"] sw_disk_format = ["sw_img_desc", "disk-format"] sw_min_disk = ["sw_img_desc",
"min-disk"] sw_min_ram = ["sw_img_desc", "min-ram"] sw_size = ["sw_img_desc", "size"]
sw_image = ["sw_img_desc", "image"] sw_operating_sys = ["sw_img_desc", "operating-
system"] sw_supp_virt_envIRON = ["sw_img_desc", "supported-virtualization-environment"]
# ***** # ** Artifact ** # ***** artifact_base = ["vnfd", "cisco-etsi-
nfvo:artifact"] artifact = ["artifact_base", "{}"] artifact_id = ["artifact", "id"] artifact_dest = ["artifact",
"destination-name"] artifact_url = ["artifact", "url"] artifact_variable_list = ["artifact", "variable"]
artifact_variable = ["artifact_variable_list", "{}"] artifact_variable_id = ["artifact_variable",
"id"] artifact_variable_desc = ["artifact_variable", "description"] artifact_checksum = ["artifact",
"checksum"] artifact_hash = ["artifact_checksum", "hash"] artifact_algorithm = ["artifact_checksum",
"algorithm"] artifact_hash_DUMMY_VAL = "9af30fce37a4c5c831e095745744d6d2"
artifact_algorithm_DUMMY_VAL = "etsi-nfv-descriptors:sha-256"

```