

Analytics Jumpstart

Intro to commonly used *pandas* methods

Nashville Software School



Goals for today

- Learn about the *pandas* library
- See some common *pandas* methods
- Work on coding tasks



Introduction



Python is a a general purpose programming language and is widely used for web applications, scientific computing, machine learning, and data analysis.

We'll be making use of the [pandas](#) library, an open source data analysis and manipulation tool.

In Python, a **library** bundles together functions and objects that have a common functionality (like data analysis).

The *pandas* library was installed when you installed Anaconda.




Introduction

The primary tool for working with data in *pandas* is the **DataFrame**, an object which can hold tabular data.



DataFrame




Introduction




The primary tool for working with data in *pandas* is the **DataFrame**, an object which can hold tabular data.

DataFrame



Each column of a DataFrame is a *pandas* **Series**.

Series



Introduction



	<i>Name</i>	<i>Team</i>	<i>Number</i>	<i>Position</i>	<i>Age</i>
0	Avery Bradley	Boston Celtics	0.0	PG	25.0
1	John Holland	Boston Celtics	30.0	SG	27.0
2	Jonas Jerebko	Boston Celtics	8.0	PF	29.0
3	Jordan Mickey	Boston Celtics	NaN	PF	21.0
4	Terry Rozier	Boston Celtics	12.0	PG	22.0
5	Jared Sullinger	Boston Celtics	7.0	C	NaN
6	Evan Turner	Boston Celtics	11.0	SG	27.0

Data



<https://www.geeksforgeeks.org/python-pandas-dataframe/>



Introduction



Rows

	<i>Name</i>	<i>Team</i>	<i>Number</i>	<i>Position</i>	<i>Age</i>
0	Avery Bradley	Boston Celtics	0.0	PG	25.0
1	John Holland	Boston Celtics	30.0	SG	27.0
2	Jonas Jerebko	Boston Celtics	8.0	PF	29.0
3	Jordan Mickey	Boston Celtics	NaN	PF	21.0
4	Terry Rozier	Boston Celtics	12.0	PG	22.0
5	Jared Sullinger	Boston Celtics	7.0	C	NaN
6	Evan Turner	Boston Celtics	11.0	SG	27.0

Data



Introduction



Diagram illustrating the structure of a pandas DataFrame. The word "Columns" is at the top, with arrows pointing to the column headers: *Name*, *Team*, *Number*, *Position*, and *Age*. The word "Rows" is on the left, with arrows pointing to the row indices: 0, 1, 2, 3, 4, 5, and 6. The word "Data" is at the bottom, with a bracket pointing to the data cells in the rows.

	<i>Name</i>	<i>Team</i>	<i>Number</i>	<i>Position</i>	<i>Age</i>
0	Avery Bradley	Boston Celtics	0.0	PG	25.0
1	John Holland	Boston Celtics	30.0	SG	27.0
2	Jonas Jerebko	Boston Celtics	8.0	PF	29.0
3	Jordan Mickey	Boston Celtics	NaN	PF	21.0
4	Terry Rozier	Boston Celtics	12.0	PG	22.0
5	Jared Sullinger	Boston Celtics	7.0	C	NaN
6	Evan Turner	Boston Celtics	11.0	SG	27.0



Introduction



Diagram illustrating the structure of a pandas DataFrame. The table is labeled with **Index** (rows) and **Columns** (headers). The data is organized into rows and columns, with specific cells highlighted to show data access.

	<i>Name</i>	<i>Team</i>	<i>Number</i>	<i>Position</i>	<i>Age</i>
0	Avery Bradley	Boston Celtics	0.0	PG	25.0
1	John Holland	Boston Celtics	30.0	SG	27.0
2	Jonas Jerebko	Boston Celtics	8.0	PF	29.0
3	Jordan Mickey	Boston Celtics	NaN	PF	21.0
4	Terry Rozier	Boston Celtics	12.0	PG	22.0
5	Jared Sullinger	Boston Celtics	7.0	C	NaN
6	Evan Turner	Boston Celtics	11.0	SG	27.0

The diagram highlights the following data access patterns:

- Index:** A red arrow points to the index values (0, 1, 2, 3, 4, 5, 6).
- Columns:** Blue arrows point from the "Columns" label to the column headers (Name, Team, Number, Position, Age).
- Rows:** Brown arrows point from the "Rows" label to the row indices (0, 1, 2, 3, 4, 5, 6).
- Data:** A purple box highlights the data cells (e.g., Jonas Jerebko, Boston Celtics, 8.0, PF, 29.0) and is labeled "Data".



Introduction

To make use of *pandas*, we'll import it using the command

```
import pandas as pd
```



Introduction

To make use of *pandas*, we'll import it using the command

```
import pandas as pd
```



Allows us to use
the components
of *pandas*.



Introduction

To make use of *pandas*, we'll import it using the command

```
import pandas as pd
```

This is an **alias**, meaning that when referring to *pandas* objects, we will use the abbreviation *pd* instead of the full word.



Introduction

We will make use of **functions**, which you can think of as a way to direct Python to do certain actions, like read data in or modify a DataFrame.



Introduction

We will make use of **functions**, which you can think of as a way to direct Python to do certain actions, like read data in or modify a DataFrame.

When calling a function, you give the name of the function followed by a set of parentheses, which includes any **arguments** that you need to pass in.



Introduction

We will make use of **functions**, which you can think of as a way to direct Python to do certain actions, like read data in or modify a DataFrame.

When calling a function, you give the name of the function followed by a set of parentheses, which includes any **arguments** that you need to pass in.

```
pd.read_csv('../data/public_art.csv')
```



Introduction

We will make use of **functions**, which you can think of as a way to direct Python to do certain actions, like read data in or modify a DataFrame.

When calling a function, you give the name of the function followed by a set of parentheses, which includes any **arguments** that you need to pass in.

```
pd.read_csv('../data/public_art.csv')
```



The name of the function
is *read_csv*.

This function reads in data from a **csv (comma separated values)** file into a *pandas* DataFrame.



Introduction

We will make use of **functions**, which you can think of as a way to direct Python to do certain actions, like read data in or modify a DataFrame.

When calling a function, you give the name of the function followed by a set of parentheses, which includes any **arguments** that you need to pass in.

```
pd.read_csv('../data/public_art.csv')
```

It is part of the *pandas*
library.



Introduction

We will make use of **functions**, which you can think of as a way to direct Python to do certain actions, like read data in or modify a DataFrame.

When calling a function, you give the name of the function followed by a set of parentheses, which includes any **arguments** that you need to pass in.

```
pd.read_csv('../data/public_art.csv')
```

We need parentheses
since we're calling a
function.




Introduction

We will make use of **functions**, which you can think of as a way to direct Python to do certain actions, like read data in or modify a DataFrame.

When calling a function, you give the name of the function followed by a set of parentheses, which includes any **arguments** that you need to pass in.

```
pd.read_csv('../data/public_art.csv')
```



Here, we need an argument, which tells the function where to find our data.



Introduction

We will make use of **functions**, which you can think of as a way to direct Python to do certain actions, like read data in or modify a DataFrame.

When calling a function, you give the name of the function followed by a set of parentheses, which includes any **arguments** that you need to pass in.

```
art = pd.read_csv('../data/public_art.csv')
```



We can **assign** the result of this function to a **variable** named **art** which will allow us to reuse it.



Introduction

Function can be part of a library (like *pd.read_csv()*) or they can be built in to objects. In this case, we call them **methods**.



Introduction

Function can be part of a library (like *pd.read_csv()*) or they can be built in to objects. In this case, we call them **methods**.

```
art.head()
```



Introduction

Function can be part of a library (like `pd.read_csv()`) or they can be built in to objects. In this case, we call them **methods**.

```
art.head()
```



The name of the method.

This function returns the first five rows of a DataFrame.



Introduction

Function can be part of a library (like *pd.read_csv()*) or they can be built in to objects. In this case, we call them **methods**.

```
art.head()
```



It is a built-in function of *pandas* DataFrames. This is the name of the DataFrame we are working with.



Introduction

Function can be part of a library (like *pd.read_csv()*) or they can be built in to objects. In this case, we call them **methods**.

```
art.head()
```



It does not require any arguments, but still needs parentheses since it is a function.



Introduction

Dataframes also have additional characteristics called **attributes** or **properties** which are also accessed with a period but do not require parentheses.



Introduction

Dataframes also have additional characteristics called **attributes** or **properties** which are also accessed with a period but do not require parentheses.

For example, the *shape* attribute contains the dimensions (number of rows and number of columns) of a DataFrame.

```
art.shape
```



Now, let's look at some commonly-used *pandas* tools which we'll practice in our first notebook.



pandas – <https://pandas.pydata.org/pandas-docs/stable/reference/index.html>

Importing Data

- **pd.read_csv()** – read a comma delimited file; good practice is to look at the raw file in a text editor (like Visual Studio Code, not Excel); additional arguments may be needed to handle extra rows at the top and extra data (footnotes) at the bottom.



pandas – <https://pandas.pydata.org/pandas-docs/stable/reference/index.html>

Importing Data

- **pd.read_csv()** – read a comma delimited file; good practice is to look at the raw file in a text editor (like Visual Studio Code, not Excel); additional arguments may be needed to handle extra rows at the top and extra data (footnotes) at the bottom.

Inspecting

- **df.head()** – looks at the top of the DataFrame; 5 rows by default
- **df.tail()** - looks at the bottom of the DataFrame; 5 rows by default
- **df.shape** – returns the dimensions of a DataFrame: (number of rows, number of columns)
- **df.info()** – method to get information about the DataFrame



pandas – <https://pandas.pydata.org/pandas-docs/stable/reference/index.html>

Modifying

- **df.columns** – column labels attribute
- **df.rename()** – rename values (can pass in a dictionary with existing columns as the key and new ones as the values)
- **df.drop()** – drop the specified labels (either rows or columns) from the DataFrame



pandas – <https://pandas.pydata.org/pandas-docs/stable/reference/index.html>

Modifying

- **df.columns** – column labels attribute
- **df.rename()** – rename values (can pass in a dictionary with existing columns as the key and new ones as the values)
- **df.drop()** – drop the specified labels (either rows or columns) from the DataFrame

Summarizing

- **series.unique()** – returns the unique values in a column
- **series.nunique()** - returns the *number* of unique elements in a column
- **series.value_counts()** - returns the unique elements in a column and the number of appearances of each



pandas – <https://pandas.pydata.org/pandas-docs/stable/reference/index.html>

Modifying

- **df.columns** – column labels attribute
- **df.rename()** – rename values (can pass in a dictionary with existing columns as the key and new ones as the values)
- **df.drop()** – drop the specified labels (either rows or columns) from the DataFrame

Summarizing

- **series.unique()** – returns the unique values in a column
- **series.nunique()** - returns the *number* of unique elements in a column
- **series.value_counts()** - returns the unique elements in a column and the number of appearances of each

Slicing/Filtering

- **df.loc[]** – pass in row name and column name to access data at that location
- **df[[]]** - creates a slice (subset) of the DataFrame including just the columns passed in

Notice that these last **accessors** use square brackets instead of parentheses.



Let's open our first shared notebook so we can see these in action:

notebook_01_public_art_part_1.ipynb

