



ĐẠI HỌC BÁCH KHOA HÀ NỘI
VIỆN CÔNG NGHỆ THÔNG TIN VÀ TRUYỀN THÔNG

Introduction to C programming language

Department of Information System
SoICT, HUST


High level language

```
#include <stdio.h>

int main()
{
    printf("Hello World");

    return 0;
}
```

Source code



```
10100110 01110110
00100110 00000000
11111010 11111010
01001110 10100110
11100110 10010110
11001110 00101110
10100110 01001110
11111010 01100110
01001110 10000110
etc...
```

Machine code

- Compiler translates a program in high level programming language into machine language

Why C?

- Flexible language
 - Structured language
 - Low level activities possible
- Standard library exists, allowing portability
- It can produce lean and efficient code
- Wide availability on a variety of computers and widely used
- It is the foundation for other languages (C++, Java, Perl, awk)

History of C

- **CPL** Combined Programming Language (Barron et al., 1963)
- **BCPL** Basic CPL (Richards, 1969)
- **B** (Thompson, 1970)
- **C** K&R C (Ritchie, 1972)
- **ANSI C** American National Standards Institute C (X3J11, 1989)
- **C99** (JTC1/SC22/WG14, ISO/IEC 9899, 1999)

The first C program

Hello World

Algorithm

output “Hello World!”

C program

```
#include <stdio.h>

int main()
{
    printf("Hello World!");

    return 0;
}
```

C Language Structure

- `#include <stdio.h>`
 - To declare using the standard I/O library. Other libraries: string, time, math...
- `int main()`
 - To declare the `main()` function. An C program must declare only one `main()` function. The first line in the `main()` will implement when the program starts.
- `{ ... }`
 - The syntax to open and close a block of codes.
- `printf`
 - the `printf()` function sends the output to standard output (monitor). This function will be taught in the next week.
- `return 0;`
 - Stop the program.

Syntax of C programs

- A C program is written using:
 - Keywords: reserved words for specific meaning in a program, e.g., main, if, do, while, ...
 - User's names: names defined by user to specify a variable, a function, etc. in a program.
 - Specific characters: to represent expressions in a program and make the program have structure, for example:
 - Create a block of instructions { }
 - Create a string “ “

Keywords of C

- Flow control (6) – `if`, `else`, `return`, `switch`, `case`, `default`
- Loops (5) – `for`, `do`, `while`, `break`, `continue`
- Common types (5) – `int`, `float`, `double`, `char`, `void`
- structures (3) – `struct`, `typedef`, `union`
- Counting and sizing things (2) – `enum`, `sizeof`
- Rare but still useful types (7) – `extern`, `signed`, `unsigned`, `long`, `short`, `static`, `const`
- Evil keywords which we avoid (1) – `goto`
- Weirdies (3) – `auto`, `register`, `volatile`

Common characters used in a program

- `{...}` create a block of instructions
- `"..."` create a string to display
- `/* ... */` create a block of comment in the program
- `;` End of an instruction
- other characters for formulas such as `+`, `-`, `*`, `/`, `()`, `...`

Identifiers

- When declare a variable or a procedure, we need to identify it
- Principles:
 - Only use alphabetic letters, numbers, underscore _ character to name an identify
 - Identify must begin with an alphabetic letter
 - Upper case and lower case are different
- Which identities are illegal:
 - tong, 2k, trung binh, %totnghiep

Example of writing a program

print number from 0 to 9

```
dem = 0
while (dem < 10)
do
{
    output dem
    dem = dem + 1
}
```

Create the main
function for the
program

```
int main()
{

    return 0;
}
```

Example ...

print number from 0 to 9

```
dem = 0
while (dem < 10)
do
{
    output dem
    dem = dem + 1
}
```

```
#include <stdio.h>
```

```
int main()
{
```

Declare the
standard
input/output
library

```
    return 0;
```

```
}
```

Example ...

print number from 0 to 9

```
dem = 0
while (dem < 10)
do
{
    output dem
    dem = dem + 1
}
```

```
#include <stdio.h>
```

```
/* In tu 0 toi 9 */
```

```
int main()
```

```
{
```

Comment

```
    return 0;
```

```
}
```

Example ...

print number from 0 to 9

```
dem = 0
while (dem < 10)
do
{
    output dem
    dem = dem + 1
}
```

```
#include <stdio.h>
```

```
/* In tu 0 toi 9 */
```

```
int main()
```

```
{
```

```
    int dem;
```



Declare a variable

```
    return 0;
```

```
}
```

Example ...

print number from 0 to 9

```
dem = 0
while (dem < 10)
do
{
    output dem
    dem = dem + 1
}
```

```
#include <stdio.h>
```

```
/* In tu 0 toi 9 */
```

```
int main()
```

```
{
```

```
    int dem;
```

```
    dem = 0;
```

Assign a
value to dem

```
    return 0;
```

```
}
```

Example ...

print number from 0 to 9

```
dem = 0
while (dem < 10)
do
{
    output dem
    dem = dem + 1
}
```

```
#include <stdio.h>

/* In tu 0 toi 9 */
int main()
{
    int dem;
    dem = 0;
    while ( dem < 10 )
    {
        // Create a loop
    }
    return 0;
}
```


Example ...

print number from 0 to 9

```
dem = 0
while (dem < 10)
do
{
    output dem
    dem = dem + 1
}
```

```
#include <stdio.h>

/* In tu 0 toi 9 */
int main()
{
    int dem;
    dem = 0;
    while ( dem < 10 )
    {
        printf("%d\n", dem) ;

    }
    return 0;
}
```

Example ...

print number from 0 to 9

```
dem = 0
while (dem < 10)
do
{
    output dem
    dem = dem + 1
}
```

```
#include <stdio.h>

/* In tu 0 toi 9 */
int main()
{
    int dem;
    dem = 0;
    while ( dem < 10 )
    {
        printf("%d\n", dem) ;
        dem = dem + 1;
    }
    return 0;
}
```

What does this program do?

```
#include <stdio.h>

int main() {
    float num;

    printf("Enter a number: ");
    scanf("%f", &num);

    if ( num < 0 ) {
        printf("%f is negative", num);
    } else {
        printf("%f is positive", num);
    }

    return 0;
}
```

Algorithm of the program

/ Find the sign of a number */*

input num

if (num < 0) then

{

 output “negative number”

}


else

{

 output “positive number”

}

Compile a C program



Error can appear at compiling phrase or link phrase

Compiler

- To translate a program, we need a compiler, for example: gcc
- The compiler of C always supports parameter to perform two phrases of the compiling process. For example, gcc -c to do the compiling phrase, gcc -o to do the link phrase.
- If your program is written in only one file, a single Unix command can help to make an executable program from the source code.
 - \$ gcc -o *program-name filename*
 - Ex: \$gcc -o hello hello.c


IDE: Integrated Development Environment

- Programming is a process that repeatedly carries out operations: source code editing, compiling, debugging.
- These operations can carry out independently by different tools. For example, edit by emacs, compile by gcc.
- However, a more convenient way is to integrate all programming tools to an unique environment to support the programming. This environment is called IDE.
- IDE - an environment of 3 in 1: editor, compiler, debugger


Products of IDE

- On Linux:
 - KDevelop
- On Window:
 - Dev-C++,
 - Turbo C++,
 - Visual C++,
 - etc.


KDevelop



Dev-C++



Visual C++





25 YEARS ANNIVERSARY
SOICT

VIỆN CÔNG NGHỆ THÔNG TIN VÀ TRUYỀN THÔNG
SCHOOL OF INFORMATION AND COMMUNICATION TECHNOLOGY

**Thank you
for your
attentions!**



soict.hust.edu.vn/



fb.com/groups/soict

