

# Contents

<b>1 Basic</b>	<b>1</b>
1.1 .vimrc	1
1.2 Misc	1
1.3 python-related	1
<b>2 flow</b>	<b>1</b>
2.1 ISAP	1
2.2 MinCostFlow	2
2.3 Dinic	2
2.4 Kuhn Munkres	2
2.5 DMST	3
2.6 SW min-cut	3
2.7 Max Cost Circulation	4
2.8 Max flow with lower/upper bound	4
2.9 Relabel to Front	4
2.10Flow Method	5
<b>3 Math</b>	<b>5</b>
3.1 FFT	5
3.2 NTT	5
3.3 Fast Walsh Transform	6
3.4 Poly operator	6
3.5 Linear Recurrence	7
3.6 Miller Rabin	7
3.7 Simplex	8
3.8 Faulhaber	8
3.9 Chinese Remainder	8
3.10Pollard Rho	8
3.11Poly Generator	9
3.12Matrix Pseudo Inverse	9
3.13ax+by=gcd	9
3.14Discrete sqrt	9
3.15SchreierSims	9
3.16Romberg	10
3.17Prefix Inverse	10
3.18Roots of Polynomial	10
3.19Primes and $\mu$ function	10
3.20Result	11
<b>4 Geometry</b>	<b>11</b>
4.1 halfPlaneIntersection	11
4.2 Intersection of 2 lines	11
4.3 Intersection of 2 segments	11
4.4 Intersection of circle and segment	11
4.5 Intersection of 2 circles	11
4.6 Circle cover	11
4.7 Li Chao Segment Tree	12
4.8 Convex Hull trick	12
4.9 Tangent line of two circles	13
4.10KD Tree	13
4.11Lower Concave Hull	14
4.12Min Enclosing Circle	14
4.13Minkowski sum	15
4.14Heart of Triangle	15
<b>5 Graph</b>	<b>15</b>
5.1 HeavyLightDecomp	15
5.2 DominatorTree	16
5.3 MaxClique	16
5.4 Number of Maximal Clique	16
5.5 Strongly Connected Component	17
5.6 Dynamic MST	17
5.7 Maximum General graph Matching	17
5.8 Minimum General Weighted Matching	18
5.9 Maximum General Weighted Matching	18
5.10Minimum Steiner Tree	20
5.11BCC based on vertex	20
5.12Min Mean Cycle	20
5.13Graph Hash	21
<b>6 String</b>	<b>21</b>
6.1 PalTree	21
6.2 SAIS	21
6.3 SuffixAutomata	22
6.4 Aho-Corasick	22
6.5 Z Value	22
6.6 BWT	22
6.7 ZValue Palindrome	23
6.8 Smallest Rotation	23
6.9 Cyclic LCS	23
<b>7 Data Structure</b>	<b>23</b>
7.1 Treap	23
7.2 Link-Cut Tree	24
7.3 Black Magic	24
<b>8 Others</b>	<b>25</b>
8.1 Find max tangent(x,y is increasing)	25

## 1 Basic

### 1.1 .vimrc

```
syn on
se ai nu ru cul mouse=a
se cin et ts=2 sw=2 sts=2
so $VIMRUNTIME/mswin.vim
colo desert
se gfn=Monospace\ 14
```

### 1.2 Misc

```
#include <random>
mt19937 rng(0x5EED);
int randint(int lb, int ub)
{ return uniform_int_distribution<int>(lb, ub)(rng); }

#define SECS (clock() / CLOCKS_PER_SEC)

struct KeyHasher {
    size_t operator()(const Key& k) const {
        return k.first + k.second * 100000;
    }
};
typedef unordered_map<Key,int,KeyHasher> map_t;
```

### 1.3 python-related

```
from fractions import Fraction
from decimal import Decimal, getcontext
getcontext().prec = 250 # set precision

itwo = Decimal(0.5)
two = Decimal(2)

N = 200
def angle(cosT):
    """given cos(theta) in decimal return theta"""
    for i in range(N):
        cosT = ((cosT + 1) / two) ** itwo
        sinT = (1 - cosT * cosT) ** itwo
        return sinT * (2 ** N)
pi = angle(Decimal(-1))
```

## 2 flow

### 2.1 ISAP

```
#define SZ(c) ((int)(c).size())
struct Maxflow {
    static const int MAXV = 20010;
    static const int INF = 1000000;
    struct Edge {
        int v, c, r;
        Edge(int _v, int _c, int _r):
            v(_v), c(_c), r(_r) {}
    };
    int s, t;
    vector<Edge> G[MAXV*2];
    int iter[MAXV*2], d[MAXV*2], gap[MAXV*2], tot;
    void init(int x) {
        tot = x+2;
        s = x+1, t = x+2;
        for(int i = 0; i <= tot; i++) {
            G[i].clear();
            iter[i] = d[i] = gap[i] = 0;
        }
    }
    void addEdge(int u, int v, int c) {
        G[u].push_back(Edge(v, c, SZ(G[v])));
        G[v].push_back(Edge(u, 0, SZ(G[u]) - 1));
    }
};
```

```

struct MinCostMaxFlow{
typedef int Tcost;
    static const int MAXV = 20010;
    static const int INFf = 1000000;
    static const Tcost INFc = 1e9;
    struct Edge{
        int v, cap;
        Tcost w;
        int rev;
        Edge(){}
        Edge(int t2, int t3, Tcost t4, int t5)
            : v(t2), cap(t3), w(t4), rev(t5) {}
    };
    int V, s, t;
    vector<Edge> g[MAXV];
    void init(int n){
        V = n+2;
        s = n+1, t = n+2;
        for(int i = 0; i <= V; i++) g[i].clear();
    }
    void addEdge(int a, int b, int cap, Tcost w){
        g[a].push_back(Edge(b, cap, w, (int)g[b].size()));
        g[b].push_back(Edge(a, 0, -w, (int)g[a].size()-1));
    }
    Tcost d[MAXV];
    int id[MAXV], mom[MAXV];
    bool inqu[MAXV];
    queue<int> q;
    Tcost solve(){
        int mxf = 0; Tcost mnc = 0;
        while(1){
            fill(d, d+V, INFc);
            fill(inqu, inqu+V, 0);
            fill(mom, mom+V, -1);
            mom[s] = s;
            d[s] = 0;
            q.push(s); inqu[s] = 1;
            while(q.size()){
                int u = q.front(); q.pop();
                inqu[u] = 0;
                for(int i = 0; i < (int) g[u].size(); i++){
                    Edge &e = g[u][i];
                    int v = e.v;
                    if(e.cap > 0 && d[v] > d[u]+e.w){
                        d[v] = d[u]+e.w;
                        mom[v] = u;
                        id[v] = i;
                        if(!inqu[v]) q.push(v), inqu[v] = 1;
                    }
                }
            }
            if(mom[t] == -1) break;
            mxf += mom[t];
            mnc -= d[t];
            int v = t;
            while(v != s){
                int u = mom[v];
                g[u][id[v]].cap--;
                g[v][id[u]].cap++;
                v = u;
            }
        }
        return mxf;
    }
};

```

```

    }
}
if(mom[t] == -1) break ;
int df = INFf;
for(int u = t; u != s; u = mom[u])
    df = min(df, g[mom[u]][id[u]].cap);
for(int u = t; u != s; u = mom[u]){
    Edge &e = g[mom[u]][id[u]];
    e.cap -= df;
    g[e.v][e.rev].cap += df;
}
mxf += df;
mnc += df*d[t];
}
return mnc;
}
} flow;

```

```

struct Dinic{
    static const int MXN = 10000;
    struct Edge{ int v,f,re; };
    int n,s,t,level[MXN];
    vector<Edge> E[MXN];
    void init(int _n, int _s, int _t){
        n = _n; s = _s; t = _t;
        for (int i=0; i<n; i++) E[i].clear();
    }
    void add_edge(int u, int v, int f){
        E[u].PB({v,f,SZ(E[v])});
        E[v].PB({u,0,SZ(E[u])-1});
    }
    bool BFS(){
        for (int i=0; i<n; i++) level[i] = -1;
        queue<int> que;
        que.push(s);
        level[s] = 0;
        while (!que.empty()){
            int u = que.front(); que.pop();
            for (auto it : E[u]){
                if (it.f > 0 && level[it.v] == -1){
                    level[it.v] = level[u]+1;
                    que.push(it.v);
                }
            }
        }
        return level[t] != -1;
    }
    int DFS(int u, int nf){
        if (u == t) return nf;
        int res = 0;
        for (auto &it : E[u]){
            if (it.f > 0 && level[it.v] == level[u]+1){
                int tf = DFS(it.v, min(nf,it.f));
                res += tf; nf -= tf; it.f -= tf;
                E[it.v][it.re].f += tf;
                if (nf == 0) return res;
            }
        }
        if (!res) level[u] = -1;
        return res;
    }
    int flow(int res=0){
        while ( BFS() )
            res += DFS(s,2147483647);
        return res;
    }
}flow;

```

```
struct KM{
// Maximum Bipartite Weighted Matching (Perfect Match)
static const int MXN = 650;
static const int INF = 2147483647; // long long
int n, match[MXN], vx[MXN], vy[MXN];
```

```

int edge[MXN][MXN],lx[MXN],ly[MXN],slack[MXN];
// **** long long
void init(int _n){
    n = _n;
    for (int i=0; i<n; i++)
        for (int j=0; j<n; j++)
            edge[i][j] = 0;
}
void add_edge(int x, int y, int w){ // long long
    edge[x][y] = w;
}
bool DFS(int x){
    vx[x] = 1;
    for (int y=0; y<n; y++){
        if (vy[y]) continue;
        if (lx[x]+ly[y] > edge[x][y]){
            slack[y] = min(slack[y], lx[x]+ly[y]-edge[x][y]);
        } else {
            vy[y] = 1;
            if (match[y] == -1 || DFS(match[y])){
                match[y] = x;
                return true;
            }
        }
    }
    return false;
}
int solve(){
    fill(match,match+n,-1);
    fill(lx,lx+n,-INF);
    fill(ly,ly+n,0);
    for (int i=0; i<n; i++)
        for (int j=0; j<n; j++)
            lx[i] = max(lx[i], edge[i][j]);
    for (int i=0; i<n; i++){
        fill(slack,slack+n,INF);
        while (true){
            fill(vx,vx+n,0);
            fill(vy,vy+n,0);
            if ( DFS(i) ) break;
            int d = INF; // long long
            for (int j=0; j<n; j++)
                if (!vy[j]) d = min(d, slack[j]);
            for (int j=0; j<n; j++){
                if (vx[j]) lx[j] -= d;
                if (vy[j]) ly[j] += d;
                else slack[j] -= d;
            }
        }
    }
    int res=0;
    for (int i=0; i<n; i++)
        res += edge[match[i]][i];
    return res;
}
}graph;

```

## 2.5 DMST

```

/*
 * Edmond's algoirthm for Directed MST
 * runs in O(VE)
 */
const int MAXV = 10010;
const int MAXE = 10010;
const int INF = 2147483647;
struct Edge{
    int u, v, c;
    Edge(){}
    Edge(int x, int y, int z) :
        u(x), v(y), c(z){}
};
int V, E, root;
Edge edges[MAXE];
inline int newV(){
    V++;
    return V;
}
inline void addEdge(int u, int v, int c){

```

```

    E++;
    edges[E] = Edge(u, v, c);
}
bool con[MAXV];
int mnInW[MAXV], prv[MAXV], cyc[MAXV], vis[MAXV];
inline int DMST(){
    fill(con, con+V+1, 0);
    int r1 = 0, r2 = 0;
    while(1){
        fill(mnInW, mnInW+V+1, INF);
        fill(prv, prv+V+1, -1);
        REP(i, 1, E){
            int u=edges[i].u, v=edges[i].v, c=edges[i].c;
            if(u != v && v != root && c < mnInW[v])
                mnInW[v] = c, prv[v] = u;
        }
        fill(vis, vis+V+1, -1);
        fill(cyc, cyc+V+1, -1);
        r1 = 0;
        bool jf = 0;
        REP(i, 1, V){
            if(con[i]) continue;
            if(prv[i] == -1 && i != root) return -1;
            if(prv[i] > 0) r1 += mnInW[i];
            int s;
            for(s = i; s != -1 && vis[s] == -1; s = prv[s])
                vis[s] = i;
            if(s > 0 && vis[s] == i){
                // get a cycle
                jf = 1;
                int v = s;
                do{
                    cyc[v] = s, con[v] = 1;
                    r2 += mnInW[v];
                    v = prv[v];
                }while(v != s);
                con[s] = 0;
            }
        }
        if(!jf) break;
        REP(i, 1, E){
            int &u = edges[i].u;
            int &v = edges[i].v;
            if(cyc[v] > 0) edges[i].c -= mnInW[edges[i].v];
            if(cyc[u] > 0) edges[i].u = cyc[edges[i].u];
            if(cyc[v] > 0) edges[i].v = cyc[edges[i].v];
            if(u == v) edges[i--] = edges[E--];
        }
    }
    return r1+r2;
}

```

## 2.6 SW min-cut

```

// global min cut
struct SW{ // O(V^3)
    static const int MXN = 514;
    int n,vst[MXN],del[MXN];
    int edge[MXN][MXN],wei[MXN];
    void init(int _n){
        n = _n;
        FZ(edge);
        FZ(del);
    }
    void add_edge(int u, int v, int w){
        edge[u][v] += w;
        edge[v][u] += w;
    }
    void search(int &s, int &t){
        FZ(vst); FZ(wei);
        s = t = -1;
        while (true){
            int mx=-1, cur=0;
            for (int i=0; i<n; i++)
                if (!del[i] && !vst[i] && mx<wei[i])
                    cur = i, mx = wei[i];
            if (mx == -1) break;
            vst[cur] = 1;
            s = t;
            t = cur;
        }
    }

```

```

    for (int i=0; i<n; i++)
        if (!vst[i] && !del[i]) wei[i] += edge[cur][i];
    }
}
int solve(){
    int res = 2147483647;
    for (int i=0,x,y; i<n-1; i++){
        search(x,y);
        res = min(res,wei[y]);
        del[y] = 1;
        for (int j=0; j<n; j++){
            edge[x][j] = (edge[j][x] += edge[y][j]);
        }
        return res;
    }
}
}graph;

```

## 2.7 Max Cost Circulation

```

struct MaxCostCirc {
    static const int MAXN = 33;
    int n , m;
    struct Edge {
        int v , w , c , r;
    };
    vector<Edge> g[ MAXN ];
    int dis[ MAXN ] , prv[ MAXN ] , prve[ MAXN ];
    bool vis[ MAXN ];
    int ans;
    void init( int _n , int _m ) : n(_n), m(_m) {}
    void adde( int u , int v , int w , int c ) {
        g[ u ].push_back( { v , w , c , SZ( g[ v ] ) } );
        g[ v ].push_back( { u , -w , 0 , SZ( g[ u ] )-1 } );
    }
    bool poscyc() {
        fill( dis , dis+n+1 , 0 );
        fill( prv , prv+n+1 , 0 );
        fill( vis , vis+n+1 , 0 );
        int tmp = -1;
        FOR( t , n+1 ) {
            REP( i , 1 , n ) {
                FOR( j , SZ( g[ i ] ) ) {
                    Edge& e = g[ i ][ j ];
                    if( e.c && dis[ e.v ] < dis[ i ]+e.w ) {
                        dis[ e.v ] = dis[ i ]+e.w;
                        prv[ e.v ] = i;
                        prve[ e.v ] = j;
                        if( t == n ) {
                            tmp = i;
                            break;
                        }
                    }
                }
            }
        }
        if( tmp == -1 ) return 0;
        int cur = tmp;
        while( !vis[ cur ] ) {
            vis[ cur ] = 1;
            cur = prv[ cur ];
        }
        int now = cur;
        int cost = 0 , df = 100000;
        do{
            Edge &e = g[ prv[ now ] ][ prve[ now ] ];
            df = min( df , e.c );
            cost += e.w;
            now = prv[ now ];
        }while( now != cur );
        ans += df*cost;
        now = cur;
        do{
            Edge &e = g[ prv[ now ] ][ prve[ now ] ];
            Edge &re = g[ now ][ e.r ];
            e.c -= df;
            re.c += df;
            now = prv[ now ];
        }while( now != cur );
        return 1;
    }
}

```

## 2.8 Max flow with lower/upper bound

```

// Max flow with lower/upper bound on edges
// source = 1 , sink = n
int in[ N ] , out[ N ];
int l[ M ] , r[ M ] , a[ M ] , b[ M ];
int solve(){
    flow.init( n );
    for( int i = 0 ; i < m ; i ++ ){
        in[ r[ i ] ] += a[ i ];
        out[ l[ i ] ] += a[ i ];
        flow.addEdge( l[ i ] , r[ i ] , b[ i ] - a[ i ] );
        // flow on edge from l[ i ] to r[ i ] should
        // be in [a[ i ], b[ i ]].
    }
    int nd = 0;
    for( int i = 1 ; i <= n ; i ++ ){
        if( in[ i ] < out[ i ] ){
            flow.addEdge( i , flow.t , out[ i ] - in[ i ] );
            nd += out[ i ] - in[ i ];
        }
        if( out[ i ] < in[ i ] ){
            flow.addEdge( flow.s , i , in[ i ] - out[ i ] );
        }
    }
    // original sink to source
    flow.addEdge( n , 1 , INF );
    if( flow.maxflow() != nd )
        // no solution
        return -1;
    int ans = flow.G[ 1 ].back().c; // source to sink
    flow.G[ 1 ].back().c = flow.G[ n ].back().c = 0;
    // take out super source and super sink
    for( size_t i = 0 ; i < flow.G[ flow.s ].size() ; i
        ++ ){
        flow.G[ flow.s ][ i ].c = 0;
        Edge &e = flow.G[ flow.s ][ i ];
        flow.G[ e.v ][ e.r ].c = 0;
    }
    for( size_t i = 0 ; i < flow.G[ flow.t ].size() ; i
        ++ ){
        flow.G[ flow.t ][ i ].c = 0;
        Edge &e = flow.G[ flow.t ][ i ];
        flow.G[ e.v ][ e.r ].c = 0;
    }
    flow.addEdge( flow.s , 1 , INF );
    flow.addEdge( n , flow.t , INF );
    flow.reset();
    return ans + flow.maxflow();
}

```

## 2.9 Relabel to Front

```

// O(N^3), 0-base
struct Edge{
    int from, to, cap, flow;
    Edge(int _from, int _to, int _cap, int _flow = 0):
        from(_from), to(_to), cap(_cap), flow(_flow) {}
};
struct PushRelabel{
    int n;
    vector<Edge> edges;
    vector<int> count;
    vector<vector<int>> G;
    vector<int> h, inQ, excess;
    queue<int> Q;
    PushRelabel(int _n):
        n(_n), count(_n<<1), G(_n), h(_n), inQ(_n), excess(
            _n) {}
    void addEdge(int from, int to, int cap) {
        G[from].push_back(edges.size());
        edges.push_back(Edge(from, to, cap));
        G[to].push_back(edges.size());
        edges.push_back(Edge(to, from, 0));
    }
    void enqueue(int u) {

```

```

    if(!inQ[u] && excess[u] > 0) Q.push(u), inQ[u] =
        true;
}
void Push(int EdgeIdx) {
    Edge & e = edges[EdgeIdx];
    int toPush = min<int>(e.cap - e.flow, excess[e.from]
    );
    if(toPush > 0 && h[e.from] > h[e.to]) {
        e.flow += toPush;
        excess[e.to] += toPush;
        excess[e.from] -= toPush;
        edges[EdgeIdx^1].flow -= toPush;
        enqueue(e.to);
    }
}
void Relabel(int u) {
    count[h[u]] -= 1; h[u] = 2*n-2;
    for (size_t i = 0; i < G[u].size(); ++i) {
        Edge & e = edges[G[u][i]];
        if(e.cap > e.flow) h[u] = min(h[u], h[e.to]);
    }
    count[++h[u]] += 1;
}
void gapReLabel(int height) {
    for (int u = 0; u < n; ++u) if(h[u] >= height && h[
        u] < n) {
        count[h[u]] -= 1;
        count[h[u] = n] += 1;
        enqueue(u);
    }
}
void Discharge(int u) {
    for (size_t i = 0; excess[u] > 0 && i < G[u].size()
        ; ++i)
        Push(G[u][i]);
    if(excess[u] > 0) {
        if(h[u] < n && count[h[u]] < 2) gapReLabel(h[u]);
        else Relabel(u);
    }
    else if(!Q.empty()) { // dequeue
        Q.pop();
        inQ[u] = false;
    }
}
int solve(int src, int snk) {
    h[src] = n; inQ[src] = inQ[snk] = true;
    count[0] = n - (count[n] = 1);
    for (size_t i = 0; i < G[src].size(); ++i) {
        excess[src] += edges[G[src][i]].cap;
        Push(G[src][i]);
    }
    while (!Q.empty())
        Discharge(Q.front());
    return excess[snk];
}
};

```

## 2.10 Flow Method

Maximize  $c^T x$  subject to  $Ax \leq b$ ,  $x \geq 0$ ;  
 with the corresponding symmetric dual problem,  
 Minimize  $b^T y$  subject to  $A^T y \geq c$ ,  $y \geq 0$ .

Maximize  $c^T x$  subject to  $Ax \leq b$ ;  
 with the corresponding asymmetric dual problem,  
 Minimize  $b^T y$  subject to  $A^T y = c$ ,  $y \geq 0$ .

Minimum vertex cover on bipartite graph =  
 Maximum matching on bipartite graph =  
 Max flow with source to one side, other side to sink

To reconstruct the minimum vertex cover, dfs from each  
 unmatched vertex on the left side **and** with unused edges  
 only. Equivalently, dfs from source with unused edges  
 only **and** without visiting sink. Then, a vertex is  
 chosen

iff. it is on the left side **and** without visited **or** on  
 the right side **and** visited through dfs.

Maximum density subgraph (  $\sum W_e + \sum W_v$  ) /  $|V|$

Binary search on answer:

For a fixed  $D$ , construct a Max flow model as follow:

Let  $S$  be Sum of all weight( **or** inf)

1. from source to each node with cap =  $S$

2. For each  $(u,v,w)$  in  $E$ ,  $(u \rightarrow v, \text{cap}=w)$ ,  $(v \rightarrow u, \text{cap}=w)$

3. For each node  $v$ , from  $v$  to sink with cap =  $S + 2 * D$   
 $- \deg[v] - 2 * (W \text{ of } v)$

where  $\deg[v] = \sum \text{weight of edge associated with } v$

If maxflow <  $S * |V|$ ,  $D$  is an answer.

Requiring subgraph: all vertex can be reached from  
 source with  
 edge whose cap > 0.

## 3 Math

### 3.1 FFT

```

// const int MAXN = 262144;
// (must be 2^k)
// before any usage, run pre_fft() first
//
// To implement poly. multiply:
//
// fft( n , a );
// fft( n , b );
// for( int i = 0 ; i < n ; i++ )
//   c[ i ] = a[ i ] * b[ i ];
// fft( n , c , 1 );
//
// then you have the result in c :: [cplx]
typedef long double ld;
typedef complex<ld> cplx;
const ld PI = acos(-1);
const cplx I(0, 1);
cplx omega[MAXN+1];
void pre_fft(){
    for(int i=0; i<=MAXN; i++)
        omega[i] = exp(i * 2 * PI / MAXN * I);
}
// n must be 2^k
void fft(int n, cplx a[], bool inv=false){
    int basic = MAXN / n;
    int theta = basic;
    for (int m = n; m >= 2; m >= 1) {
        int mh = m >> 1;
        for (int i = 0; i < mh; i++) {
            cplx w = omega[inv ? MAXN-(i*theta%MAXN)
                : i*theta%MAXN];
            for (int j = i; j < n; j += m) {
                int k = j + mh;
                cplx x = a[j] - a[k];
                a[j] += a[k];
                a[k] = w * x;
            }
        }
        theta = (theta * 2) % MAXN;
    }
    int i = 0;
    for (int j = 1; j < n - 1; j++) {
        for (int k = n >> 1; k > (i ^ k); k >= 1);
        if (j < i) swap(a[i], a[j]);
    }
    if (inv)
        for (i = 0; i < n; i++)
            a[i] /= n;
}

```

### 3.2 NTT

```

typedef long long LL;
// Remember coefficient are mod P
/* p=a*2^n+1

```

```

n      2^n      p      a      root
5      32      97      3      5
6      64      193     3      5
7      128     257     2      3
8      256     257     1      3
9      512     7681    15     17
10     1024    12289    12     11
11     2048    12289     6     11
12     4096    12289     3     11
13     8192    40961     5      3
14    16384    65537     4      3
15    32768    65537     2      3
16    65536    65537     1      3
17   131072    786433    6     10
18   262144    786433    3     10 (605028353,
    2308, 3)
19   524288    5767169   11     3
20  1048576    7340033    7      3
21  2097152    23068673   11     3
22  4194304    104857601  25     3
23  8388608    167772161  20     3
24  16777216    167772161 10      3
25  33554432    167772161 5      3 (1107296257, 33,
    10)
26  67108864    469762049 7      3
27 134217728    2013265921 15     31 */
// (must be 2^k)
// To implement poly. multiply:
// NTT<P, root, MAXN> ntt;
// ntt( n , a ); // or ntt.tran( n , a );
// ntt( n , b );
// for( int i = 0 ; i < n ; i++ )
//   c[ i ] = a[ i ] * b[ i ];
// ntt( n , c , 1 );
//
// then you have the result in c :: [LL]
template<LL P, LL root, int MAXN>
struct NTT{
    static LL bigmod(LL a, LL b) {
        LL res = 1;
        for (LL bs = a; b; b >>= 1, bs = (bs * bs) % P) {
            if(b&1) res=(res*bs)%P;
        }
        return res;
    }
    static LL inv(LL a, LL b) {
        if(a==1)return 1;
        return (((LL)(a-inv(b%a,a))*b+1)/a)%b;
    }
    LL omega[MAXN+1];
    NTT() {
        omega[0] = 1;
        LL r = bigmod(root, (P-1)/MAXN);
        for (int i=1; i<=MAXN; i++)
            omega[i] = (omega[i-1]*r)%P;
    }
    // n must be 2^k
    void tran(int n, LL a[], bool inv_ntt=false){
        int basic = MAXN / n;
        int theta = basic;
        for (int m = n; m >= 2; m >>= 1) {
            int mh = m >> 1;
            for (int i = 0; i < mh; i++) {
                LL w = omega[i*theta%MAXN];
                for (int j = i; j < n; j += m) {
                    int k = j + mh;
                    LL x = a[j] - a[k];
                    if (x < 0) x += P;
                    a[j] += a[k];
                    if (a[j] > P) a[j] -= P;
                    a[k] = (w * x) % P;
                }
            }
            theta = (theta * 2) % MAXN;
        }
        int i = 0;
        for (int j = 1; j < n - 1; j++) {
            for (int k = n >> 1; k > (i ^ k); k >>= 1);
            if (j < i) swap(a[i], a[j]);
        }
        if (inv_ntt) {
            LL ni = inv(n,P);

```

```

        reverse( a+1 , a+n );
        for (i = 0; i < n; i++)
            a[i] = (a[i] * ni) % P;
    }
}

void operator()(int n, LL a[], bool inv_ntt=false) {
    tran(n, a, inv_ntt);
}

};
const LL P=2013265921,root=31;
const int MAXN=4194304;
NTT<P, root, MAXN> ntt;

```

### 3.3 Fast Walsh Transform

```

/* xor convolution:
 * x = (x0,x1) , y = (y0,y1)
 * z = ( x0y0 + x1y1 , x0y1 + x1y0 )
 * =>
 * x' = ( x0+x1 , x0-x1 ) , y' = ( y0+y1 , y0-y1 )
 * z' = ( ( x0+x1 )( y0+y1 ) , ( x0-x1 )( y0-y1 ) )
 * z = (1/2) * z''
 * or convolution:
 * x = (x0, x0+x1), inv = (x0, x1-x0) w/o final div
 * and convolution:
 * x = (x0+x1, x1), inv = (x0-x1, x1) w/o final div */
typedef long long LL;
const int MAXN = (1<<20)+10;
const LL MOD = 1e9+7;
inline LL pw( LL x , LL k ) {
    LL res = 1;
    for( LL bs = x ; k ; k >>= 1, bs = (bs * bs)%MOD ){
        if( k&1 ) res = ( res * bs ) % MOD;
    }
    return res;
}
inline LL inv( LL x ) {
    return pw( x , MOD-2 );
}
inline void fwt( LL x[ MAXN ] , int N , bool inv=0 ) {
    for( int d = 1 ; d < N ; d <= 1 ) {
        int d2 = d<<1;
        for( int s = 0 ; s < N ; s += d2 ) {
            for( int i = s , j = s+d ; i < s+d ; i++, j++ ){
                LL ta = x[ i ] , tb = x[ j ];
                x[ i ] = ta+tb;
                x[ j ] = ta-tb;
                if( x[ i ] >= MOD ) x[ i ] -= MOD;
                if( x[ j ] < 0 ) x[ j ] += MOD;
            }
        }
    }
    if( inv )
        for( int i = 0 ; i < N ; i++ ) {
            x[ i ] *= inv( N );
            x[ i ] %= MOD;
        }
}

```

### 3.4 Poly operator

```

struct PolyOp {
#define FOR(i, c) for (int i = 0; i < (c); ++i)
    NTT<P, root, MAXN> ntt;
    static int nxt2k(int x) {
        int i = 1; for (; i < x; i <= 1); return i;
    }
    void Mul(int n, LL a[], int m, LL b[], LL c[]) {
        static LL aa[MAXN], bb[MAXN];
        int N = nxt2k(n+m);
        copy(a, a+n, aa); fill(aa+n, aa+N, 0);
        copy(b, b+m, bb); fill(bb+m, bb+N, 0);
        ntt(N, aa); ntt(N, bb);
        FOR(i, N) c[i] = aa[i] * bb[i] % P;
        ntt(N, c, 1);
    }
    void Inv(int n, LL a[], LL b[]) {
        // ab = aa^-1 = 1 mod x^(n/2)

```



```

// (b - a^{n-1})^2 = 0 mod x^n
// bb - a^{n-2} + 2ba^{n-1} = 0
// bba - a^{n-1} + 2b = 0
// bba + 2b = a^{n-1}
static LL tmp[MAXN];
if (n == 1) {b[0] = ntt.inv(a[0], P); return;}
Inv((n+1)/2, a, b);
int N = n*2;
copy(a, a+n, tmp);
fill(tmp+n, tmp+N, 0);
fill(b+n, b+N, 0);
ntt(N, tmp); ntt(N, b);
FOR(i, N) {
    LL t1 = (2 - b[i] * tmp[i]) % P; if (t1 < 0) t1
        += P;
    b[i] = b[i] * t1 % P;
}
ntt(N, b, 1);
fill(b+n, b+N, 0);
}
void Div(int n, LL a[], int m, LL b[], LL d[], LL r
    []) {
    // Ra = Rb * Rd mod x^{(n-m+1)}
    // Rd = Ra * Rb^{n-m+1} mod
    static LL aa[MAXN], bb[MAXN], ta[MAXN], tb[MAXN];
    if (n < m) {copy(a, a+n, r); fill(r+n, r+m, 0);
        return;}
    // d: n-1 - (m-1) = n-m (n-m+1 terms)
    copy(a, a+n, aa); copy(b, b+m, bb);
    reverse(aa, aa+n); reverse(bb, bb+m);
    Inv(n-m+1, bb, tb);
    Mul(n-m+1, ta, n-m+1, tb, d);
    fill(d+n-m+1, d+n, 0); reverse(d, d+n-m+1);
    // r: m-1 - 1 = m-2 (m-1 terms)
    Mul(m, b, n-m+1, d, ta);
    FOR(i, n) { r[i] = a[i] - ta[i]; if (r[i] < 0) r[i]
        += P; }
}
void dx(int n, LL a[], LL b[]) { REP(i, 1, n-1) b[i]
    -1] = i * a[i] % P; }
void Sx(int n, LL a[], LL b[]) {
    b[0] = 0;
    FOR(i, n) b[i+1] = a[i] * ntt.inv[i+1] % P;
}
void Ln(int n, LL a[], LL b[]) {
    // Integral a' a^{n-1} dx
    static LL a1[MAXN], a2[MAXN], b1[MAXN];
    int N = n*2;
    dx(n, a, a1); Inv(n, a, a2);
    Mul(n-1, a1, n, a2, b1);
    Sx(n+n-1-1, b1, b);
    fill(b+n, b+N, 0);
}
void Exp(int n, LL a[], LL b[]) {
    // Newton method to solve g(a(x)) = ln b(x) - a(x)
    // = 0
    // b' = b - g(b(x)) / g'(b(x))
    // b' = b (1 - ln b + a)
    static LL lnb[MAXN], c[MAXN], tmp[MAXN];
    assert(a[0] == 0); // dont know exp(a[0]) mod P
    if (n == 1) {b[0] = 1; return;}
    Exp((n+1)/2, a, b);
    fill(b+(n+1)/2, b+n, 0);
    Ln(n, b, lnb);
    fill(c, c+n, 0); c[0] = 1;
    FOR(i, n) {
        c[i] += a[i] - lnb[i];
        if (c[i] < 0) c[i] += P;
        if (c[i] >= P) c[i] -= P;
    }
    Mul(n, b, n, c, tmp);
    copy(tmp, tmp+n, b);
}
} polyop;

```

### 3.5 Linear Recurrence

```

LL n, m;
LL dp[ N + N ];
void pre_dp(){

```

```

dp[ 0 ] = 1;
LL bdr = min( m + m , n );
for( LL i = 1 ; i <= bdr ; i ++ )
    for( LL j = i - 1 ; j >= max(0LL, i - m) ; j -- )
        dp[ i ] = add( dp[ i ] , dp[ j ] );
}
vector<LL> Mul( vector<LL>& v1, vector<LL>& v2 ){
    int _sz1 = (int)v1.size();
    int _sz2 = (int)v2.size();
    assert( _sz1 == m );
    assert( _sz2 == m );
    vector<LL> _v( m + m );
    for( int i = 0 ; i < m + m ; i ++ ) _v[ i ] = 0;
    // expand
    for( int i = 0 ; i < _sz1 ; i ++ )
        for( int j = 0 ; j < _sz2 ; j ++ )
            _v[ i + j + 1 ] = add( _v[ i + j + 1 ] ,
                mul(v1[ i ] , v2[ j ] ) );
    // shrink
    for( int i = 0 ; i < m ; i ++ )
        for( int j = 1 ; j <= m ; j ++ )
            _v[ i + j ] = add( _v[ i + j ] , _v[ i ] );
    for( int i = 0 ; i < m ; i ++ )
        _v[ i ] = _v[ i + m ];
    _v.resize( m );
    return _v;
}
vector<LL> I, A;
void solve(){
    pre_dp();
    if( n <= m + m )
        { printf( "%lld\n" , dp[ n ] ); exit( 0 ); }
    I.resize( m ); A.resize( m );
    for( int i = 0 ; i < m ; i ++ ) I[ i ] = A[ i ] = 1;
    // dp[ n ] = /Sum_{i=0}^{m-1} A_i * dp[ n - i - 1 ]
    LL dlt = ( n - m ) / m, rdlt = dlt * m;
    while( dlt ){
        if( dlt & 1LL ) I = Mul( I , A );
        A = Mul( A , A );
        dlt >>= 1;
    }
    LL ans = 0;
    for( int i = 0 ; i < m ; i ++ )
        ans = add(ans, mul(I[i], dp[n - i - 1 - rdlt]));
    printf( "%lld\n" , ans );
}

```

### 3.6 Miller Rabin

```

// n < 4,759,123,141      3 : 2, 7, 61
// n < 1,122,004,669,633  4 : 2, 13, 23, 1662803
// n < 3,474,749,660,383  6 : pirmes <= 13
// n < 2^64               7 :
// 2, 325, 9375, 28178, 450775, 9780504, 1795265022
// Make sure testing integer is in range [2, n-2] if
// you want to use magic.
bool witness(LL a, LL n, LL u, int t){
    LL x = mypow(a, u, n);
    for(int i=0; i<t; i++){
        LL nx = mul(x, x, n);
        if(nx==1&&x!=1&&x!=n-1) return 1;
        x=nx;
    }
    return x!=1;
}
bool miller_rabin(LL n, int s=100) {
    // iterate s times of witness on n
    // return 1 if prime, 0 otherwise
    if(n<2) return 0;
    if(!(n&1)) return n == 2;
    LL u=n-1; int t=0;
    // n-1 = u*2^t
    while(!(u&1)) u>>=1, t++;
    while(s--){
        LL a=randll()%(n-1)+1;
        if(witness(a,n,u,t)) return 0;
    }
    return 1;
}

```

### 3.7 Simplex

```
const int MAXN = 111;
const int MAXM = 111;
const double eps = 1E-10;
double a[MAXN][MAXM], b[MAXN], c[MAXM], d[MAXN][MAXM];
double x[MAXM];
int ix[MAXN + MAXM]; // !!! array all indexed from 0
// max{cx} subject to {Ax<=b, x>=0}
// n: constraints, m: vars !!!
// x[] is the optimal solution vector
// usage :
// value = simplex(a, b, c, N, M);
double simplex(double a[MAXN][MAXM], double b[MAXN],
               double c[MAXM], int n, int m){
    ++m;
    int r = n, s = m - 1;
    memset(d, 0, sizeof(d));
    for (int i = 0; i < n + m; ++i) ix[i] = i;
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < m - 1; ++j) d[i][j] = -a[i][j];
        d[i][m - 1] = 1;
        d[i][m] = b[i];
        if (d[r][m] > d[i][m]) r = i;
    }
    for (int j = 0; j < m - 1; ++j) d[n][j] = c[j];
    d[n + 1][m - 1] = -1;
    for (double dd;; ) {
        if (r < n) {
            int t = ix[s]; ix[s] = ix[r + m]; ix[r + m] = t;
            d[r][s] = 1.0 / d[r][s];
            for (int j = 0; j <= m; ++j)
                if (j != s) d[r][j] *= -d[r][s];
            for (int i = 0; i <= n + 1; ++i) if (i != r) {
                for (int j = 0; j <= m; ++j) if (j != s)
                    d[i][j] += d[r][j] * d[i][s];
                d[i][s] *= d[r][s];
            }
        }
        r = -1; s = -1;
        for (int j = 0; j < m; ++j)
            if (s < 0 || ix[s] > ix[j]) {
                if (d[n + 1][j] > eps ||
                    (d[n + 1][j] > -eps && d[n][j] > eps))
                    s = j;
            }
        if (s < 0) break;
        for (int i = 0; i < n; ++i) if (d[i][s] < -eps) {
            if (r < 0 ||
                (dd = d[r][m] / d[r][s] - d[i][m] / d[i][s]) <
                 -eps ||
                (dd < eps && ix[r + m] > ix[i + m]))
                r = i;
        }
        if (r < 0) return -1; // not bounded
    }
    if (d[n + 1][m] < -eps) return -1; // not executable
    double ans = 0;
    for (int i = 0; i < m; ++i) x[i] = 0;
    for (int i = m; i < n + m; ++i) { // the missing
        enumerated x[i] = 0
        if (ix[i] < m - 1) {
            ans += d[i - m][m] * c[ix[i]];
            x[ix[i]] = d[i - m][m];
        }
    }
    return ans;
}
```

### 3.8 Faulhaber

```
/* faulhaber 's formula -
 * cal power sum formula of all p=1~k in O(k^2) */
#define MAXK 2500
const int mod = 1000000007;
int b[MAXK];
// bernoulli number
int inv[MAXK+1];
// inverse
```

```
int cm[MAXK+1][MAXK+1]; // combinactories
int co[MAXK][MAXK+2];
// coefficient of x^j when p=i
inline int getinv(int x) {
    int a=x, b=mod, a0=1, a1=0, b0=0, b1=1;
    while(b) {
        int q,t;
        q=a/b; t=b; b=a-b*q; a=t;
        t=b0; b0=a0-b0*q; a0=t;
        t=b1; b1=a1-b1*q; a1=t;
    }
    return a0<0?a0+mod:a0;
}
inline void pre() {
    /* combinational */
    for (int i=0; i<=MAXK; i++) {
        cm[i][0]=cm[i][i]=1;
        for (int j=1; j<i; j++)
            cm[i][j]=add(cm[i-1][j-1], cm[i-1][j]);
    }
    /* inverse */
    for (int i=1; i<=MAXK; i++) inv[i]=getinv(i);
    /* bernoulli */
    b[0]=1; b[1]=getinv(2); // with b[1] = 1/2
    for (int i=2; i<=MAXK; i++) {
        if (i&1) { b[i]=0; continue; }
        b[i]=1;
        for (int j=0; j<i; j++)
            b[i]=sub(b[i], mul(cm[i][j], mul(b[j], inv[i-j+1])));
    }
    /* faulhaber */
    // sigma_x=1~n {x^p} = 1/(p+1) * sigma_j=0~p { C(p+1, j) * B_j * n^(p-j+1) }
    for (int i=1; i<=MAXK; i++) {
        co[i][0]=0;
        for (int j=0; j<=i; j++)
            co[i][i-j+1]= mul(inv[i+1], mul(cm[i+1][j], b[j]));
    }
}
/* sample usage: return f(n,p) = sigma_x=1~n (x^p) */
inline int solve(int n, int p) {
    int sol=0, m=n;
    for (int i=1; i<=p+1; i++) {
        sol=add(sol, mul(co[p][i], m));
        m = mul(m, n);
    }
    return sol;
}
```

### 3.9 Chinese Remainder

```
LL solve(LL x1, LL m1, LL x2, LL m2) {
    LL g = __gcd(m1, m2);
    if ((x2 - x1) % g) return -1; // no sol
    m1 /= g; m2 /= g;
    pair<LL, LL> p = gcd(m1, m2);
    LL lcm = m1 * m2 * g;
    LL res = p.first * (x2 - x1) * m1 + x1;
    return (res % lcm + lcm) % lcm;
}
```

### 3.10 Pollard Rho

```
// does not work when n is prime
LL f(LL x, LL mod){
    return add(mul(x, x, mod), 1, mod);
}
LL pollard_rho(LL n) {
    if (!n&1) return 2;
    while(true){
        LL y=2, x=rand()%(n-1)+1, res=1;
        for (int sz=2; res==1; sz*=2) {
            for (int i=0; i<sz && res==1; i++) {
                x = f(x, n);
                res = __gcd(abs(x-y), n);
            }
        }
    }
}
```



```

    y = x;
  }
  if (res!=0 && res!=n) return res;
}
}

```

### 3.11 Poly Generator

```

struct PolyGen{
  /* for a nth-order polynomial f(x), *
   * given f(0), f(1), ..., f(n) *
   * express f(x) as sigma_i{c_i*C(x,i)} */
  int n;
  vector<LL> coef;
  // initialize and calculate f(x), vector _fx should
  // be filled with f(0) to f(n)
  PolyGen(int _n,vector<LL> _fx):n(_n),coef(_fx){
    for(int i=0;i<n;i++){
      for(int j=n;j>i;j--){
        coef[j]-=coef[j-1];
      }
    }
    // evaluate f(x), runs in O(n)
    LL eval(int x){
      LL m=1, ret=0;
      for(int i=0;i<=n;i++){
        ret+=coef[i]*m;
        m=m*(x-i)/(i+1);
      }
      return ret;
    }
  }
};

```

### 3.12 Matrix Pseudo Inverse

```

Mat pinv( Mat m ){
  Mat res = I;
  FZ( used );
  for( int i = 0 ; i < W ; i ++ ){
    int piv = -1;
    for( int j = 0 ; j < W ; j ++ ){
      if( used[ j ] ) continue;
      if( abs( m.v[ j ][ i ] ) > EPS ){
        piv = j;
        break;
      }
    }
    if( piv == -1 ) continue;
    used[ i ] = true;
    swap( m.v[ piv ], m.v[ i ] );
    swap( res.v[ piv ], res.v[ i ] );
    LD rat = m.v[ i ][ i ];
    for( int j = 0 ; j < W ; j ++ ){
      m.v[ i ][ j ] /= rat;
      res.v[ i ][ j ] /= rat;
    }
    for( int j = 0 ; j < W ; j ++ ){
      if( j == i ) continue;
      rat = m.v[ j ][ i ];
      for( int k = 0 ; k < W ; k ++ ){
        m.v[ j ][ k ] -= rat * m.v[ i ][ k ];
        res.v[ j ][ k ] -= rat * res.v[ i ][ k ];
      }
    }
  }
  for( int i = 0 ; i < W ; i ++ ){
    if( used[ i ] ) continue;
    for( int j = 0 ; j < W ; j ++ )
      res.v[ i ][ j ] = 0;
  }
  return res;
}

```

### 3.13 ax+by=gcd

```

PII gcd(int a, int b){
  if(b == 0) return {1, 0};
  PII q = gcd(b, a % b);
  return {q.second, q.first - q.second * (a / b)};
}

```

### 3.14 Discrete sqrt

```

void calcH(int &t, int &h, const int p) {
  int tmp=p-1; for(t=0;(tmp&1)==0;tmp/=2) t++; h=tmp;
}
// solve equation x^2 mod p = a
bool solve(int a, int p, int &x, int &y) {
  if(p == 2) { x = y = 1; return true; }
  int p2 = p / 2, tmp = mypow(a, p2, p);
  if (tmp == p - 1) return false;
  if ((p + 1) % 4 == 0) {
    x=mypow(a,(p+1)/4,p); y=p-x; return true;
  } else {
    int t, h, b, pb; calcH(t, h, p);
    if (t >= 2) {
      do {b = rand() % (p - 2) + 2;
        } while (mypow(b, p / 2, p) != p - 1);
      pb = mypow(b, h, p);
    } int s = mypow(a, h / 2, p);
    for (int step = 2; step <= t; step++) {
      int ss = (((LL)(s * s) % p) * a) % p;
      for(int i=0;i<t-step;i++) ss=mul(ss,ss,p);
      if (ss + 1 == p) s = (s * pb) % p;
      pb = ((LL)pb * pb) % p;
    } x = ((LL)s * a) % p; y = p - x;
  } return true;
}

```

### 3.15 SchreierSims

```

// time: O(n^2 lg^3 |G| + t n lg |G|)
// mem : O(n^2 lg |G| + tn)
// t : number of generator
namespace SchreierSimsAlgorithm{
  typedef vector<int> Permu;
  Permu inv( const Permu& p ){
    Permu ret( p.size() );
    for( int i = 0; i < (int)p.size(); i ++ )
      ret[ p[ i ] ] = i;
    return ret;
  }
  Permu operator*( const Permu& a, const Permu& b ){
    Permu ret( a.size() );
    for( int i = 0 ; i < (int)a.size(); i ++ )
      ret[ i ] = b[ a[ i ] ];
    return ret;
  }
  typedef vector<Permu> Bucket;
  typedef vector<int> Table;
  typedef pair<int,int> pii;
  int n, m;
  vector<Bucket> bkts, bktsInv;
  vector<Table> lookup;
  int fastFilter( const Permu &g, bool addToG = 1 ){
    n = bkts.size();
    Permu p;
    for( int i = 0 ; i < n ; i ++ ){
      int res = lookup[ i ][ p[ i ] ];
      if( res == -1 ){
        if( addToG ){
          bkts[ i ].push_back( p );
          bktsInv[ i ].push_back( inv( p ) );
          lookup[ i ][ p[ i ] ] = (int)bkts[i].size()-1;
        }
        return i;
      }
      p = p * bktsInv[i][res];
    }
    return -1;
  }
  long long calcTotalSize(){
    long long ret = 1;

```

```

for( int i = 0 ; i < n ; i ++ )
    ret *= bkts[i].size();
return ret;
}
bool inGroup( const Permu &g ){
    return fastFilter( g, false ) == -1;
}
void solve( const Bucket &gen, int _n ){
    n = _n, m = gen.size(); // m perm[0..n-1]s
    //clear all
    bkts.clear();
    bktsInv.clear();
    lookup.clear();
}
for(int i = 0 ; i < n ; i ++ ){
    lookup[i].resize(n);
    fill(lookup[i].begin(), lookup[i].end(), -1);
}
Permu id( n );
for(int i = 0 ; i < n ; i ++ ) id[i] = i;
for(int i = 0 ; i < n ; i ++ ){
    bkts[i].push_back(id);
    bktsInv[i].push_back(id);
    lookup[i][i] = 0;
}
for(int i = 0 ; i < m ; i ++ )
    fastFilter( gen[i] );
queue< pair<pii,pii> > toUpd;
for(int i = 0 ; i < n ; i ++ )
    for(int j = i ; j < n ; j ++ )
        for(int k = 0 ; k < (int)bkts[i].size(); k ++ )
            for(int l = 0 ; l < (int)bkts[j].size(); l ++ )
                toUpd.push( {pii(i,k), pii(j,l)} );
while( !toUpd.empty() ){
    pii a = toUpd.front().first;
    pii b = toUpd.front().second;
    toUpd.pop();
    int res = fastFilter(bkts[a.first][a.second] *
                        bkts[b.first][b.second]);
    if(res == -1) continue;
    pii newPair(res, (int)bkts[res].size() - 1);
    for(int i = 0 ; i < n ; i ++ )
        for(int j = 0 ; j < (int)bkts[i].size(); ++j){
            if(i <= res)
                toUpd.push(make_pair(pii(i, j), newPair));
            if(res <= i)
                toUpd.push(make_pair(newPair, pii(i, j)));
        }
}
}
}
}

```

### 3.16 Romberg

```

// Estimates the definite integral of
// \int_a^b f(x) dx
template<class T>
double romberg( T& f, double a, double b, double eps=1e-8){
    vector<double> t; double h=b-a, last, curr; int k=1, i=1;
    t.push_back(h*(f(a)+f(b))/2);
    do{ last=t.back(); curr=0; double x=a+h/2;
        for(int j=0; j<k; j++) curr+=f(x), x+=h;
        curr=(t[0] + h*curr)/2; double k1=4.0/3.0, k2
            =1.0/3.0;
        for(int j=0; j<i; j++){ double temp=k1*curr-k2*t[j];
            t[j]=curr; curr=temp; k2/=4*k1-k2; k1=k2+1;
        } t.push_back(curr); k*=2; h/=2; i++;
    }while( fabs(last-curr) > eps);
    return t.back();
}

```

### 3.17 Prefix Inverse

```

void solve( int m ){
    inv[ 1 ] = 1;
    for( int i = 2 ; i < m ; i ++ )
        inv[ i ] = ((LL)(m - m / i) * inv[m % i]) % m;
}

```

```

}

```

### 3.18 Roots of Polynomial

```

const double eps = 1e-12;
const double inf = 1e+12;
double a[ 10 ], x[ 10 ];
int n;
int sign( double x ){
    return (x < -eps)?(-1):(x>eps);
}
double f(double a[], int n, double x){
    double tmp=1, sum=0;
    for(int i=0; i<=n; i++){
        sum=sum+a[i]*tmp;
        tmp=tmp*x;
    }
    return sum;
}
double binary(double l, double r, double a[], int n){
    int sl=sign(f(a,n,l)), sr=sign(f(a,n,r));
    if(sl==0) return l;
    if(sr==0) return r;
    if(sl*sr>0) return inf;
    while(r-l>eps){
        double mid=(l+r)/2;
        int ss=sign(f(a,n,mid));
        if(ss==0) return mid;
        if(ss*sl>0) l=mid; else r=mid;
    }
    return l;
}
void solve(int n, double a[], double x[], int &nx){
    if(n==1){
        x[1]=-a[0]/a[1];
        nx=1;
        return;
    }
    double da[10], dx[10];
    int ndx;
    for(int i=n; i>=1; i--) da[i-1]=a[i]*i;
    solve(n-1, da, dx, ndx);
    nx=0;
    if(ndx==0){
        double tmp=binary(-inf, inf, a, n);
        if (tmp<inf) x[++nx]=tmp;
        return;
    }
    double tmp;
    tmp=binary(-inf, dx[1], a, n);
    if(tmp<inf) x[++nx]=tmp;
    for(int i=1; i<=ndx-1; i++){
        tmp=binary(dx[i], dx[i+1], a, n);
        if(tmp<inf) x[++nx]=tmp;
    }
    tmp=binary(dx[ndx], inf, a, n);
    if(tmp<inf) x[++nx]=tmp;
}
int main() {
    scanf("%d", &n);
    for(int i=n; i>=0; i--) scanf("%lf", &a[i]);
    int nx;
    solve(n, a, x, nx);
    for(int i=1; i<=nx; i++) printf("%.6f\n", x[i]);
}

```

### 3.19 Primes and $\mu$ function

```

/* 12721, 13331, 14341, 75577, 123457, 222557, 556679
 * 999983, 1097774749, 1076767633, 100102021, 999997771
 * 1001010013, 1000512343, 987654361, 999991231
 * 999888733, 98789101, 98777733, 999991921, 1010101333
 * 1010102101, 1000000000039, 100000000000037
 * 2305843009213693951, 4611686018427387847
 * 9223372036854775783, 18446744073709551557 */
int mu[ N ], p_tbl[ N ];
vector<int> primes;
void sieve() {

```

```

mu[ 1 ] = p_tbl[ 1 ] = 1;
for( int i = 2 ; i < N ; i ++ ){
    if( !p_tbl[ i ] ){
        p_tbl[ i ] = i;
        primes.push_back( i );
        mu[ i ] = -1;
    }
    for( int p : primes ){
        int x = i * p;
        if( x >= M ) break;
        p_tbl[ x ] = p;
        mu[ x ] = -mu[ i ];
        if( i % p == 0 ){
            mu[ x ] = 0;
            break;
        }
    }
}
}
vector<int> factor( int x ){
    vector<int> fac{ 1 };
    while( x > 1 ){
        int fn = SZ(fac), p = p_tbl[ x ], pos = 0;
        while( x % p == 0 ){
            x /= p;
            for( int i = 0 ; i < fn ; i ++ )
                fac.PB( fac[ pos ++ ] * p );
        }
    }
    return fac;
}

```

### 3.20 Result

- Lucas' Theorem :  
For  $n, m \in \mathbb{Z}^*$  and prime  $P$ ,  $C(m, n) \bmod P = \prod(C(m_i, n_i))$  where  $m_i$  is the  $i$ -th digit of  $m$  in base  $P$ .
- Pick's Theorem :  $A = i + b/2 - 1$
- Kirchhoff's theorem :  
 $A_{ii} = \deg(i), A_{ij} = (i, j) \in E ? -1 : 0$ , Deleting any one row, one column, and cal the  $\det(A)$

## 4 Geometry

### 4.1 halfPlaneIntersection

### 4.2 Intersection of 2 lines

```

Pt interPnt( Line l1, Line l2, bool &res ){
    Pt p1, p2, q1, q2;
    tie(p1, p2) = l1;
    tie(q1, q2) = l2;
    double f1 = (p2 - p1) ^ (q1 - p1);
    double f2 = (p2 - p1) ^ (p1 - q2);
    double f = (f1 + f2);
    if( fabs(f) < eps )
        { res = false; return {0, 0}; }
    res = true;
    return q1 * (f2 / f) + q2 * (f1 / f);
}
bool isin( Line l0, Line l1, Line l2 ){
    // Check inter(l1, l2) in l0
    bool res;
    Pt p = interPnt(l1, l2, res);
    return ( (l0.SE - l0.FI) ^ (p - l0.FI) ) > eps;
}
/* If no solution, check: 1. ret.size() < 3
 * Or more precisely, 2. interPnt(ret[0], ret[1])
 * in all the lines. (use (l.S - l.F) ^ (p - l.F) > 0
 */
/* --- Line.FI --- Line.SE --- */
vector<Line> halfPlaneInter( vector<Line> lines ){
    int sz = lines.size();
    vector<double> ata(sz), ord(sz);
    for( int i=0; i<sz; i++ ) {
        ord[i] = i;
        Pt d = lines[i].SE - lines[i].FI;

```

```

        ata[i] = atan2(d.Y, d.X);
    }
    sort( ord.begin(), ord.end(), [&](int i, int j) {
        if( fabs(ata[i] - ata[j]) < eps )
            return ( (lines[i].SE - lines[i].FI) ^
                    (lines[j].SE - lines[j].FI) ) < 0;
        return ata[i] < ata[j];
    });
    vector<Line> fin;
    for( int i=0; i<sz; i++ )
        if ( !i or fabs(ata[ord[i]] - ata[ord[i-1]]) > eps )
            fin.PB(lines[ord[i]]);
    deque<Line> dq;
    for( int i=0; i<(int)(fin.size()); i++ ) {
        while((int)(dq.size()) >= 2 and
            not isin(fin[i], dq[(int)(dq.size())-2],
                    dq[(int)(dq.size())-1]))
            dq.pop_back();
        while((int)(dq.size()) >= 2 and
            not isin(fin[i], dq[0], dq[1]))
            dq.pop_front();
        dq.push_back(fin[i]);
    }
    while( (int)(dq.size()) >= 3 and
        not isin(dq[0], dq[(int)(dq.size())-2],
                dq[(int)(dq.size())-1]))
        dq.pop_back();
    while( (int)(dq.size()) >= 3 and
        not isin(dq[(int)(dq.size())-1], dq[0], dq[1]))
        dq.pop_front();
    vector<Line> res(dq.begin(), dq.end());
    return res;
}

```

### 4.3 Intersection of 2 segments

```

int ori( const Pt& o , const Pt& a , const Pt& b ){
    LL ret = ( a - o ) ^ ( b - o );
    return (ret > 0) - (ret < 0);
}
// p1 == p2 || q1 == q2 need to be handled
bool banana( const Pt& p1 , const Pt& p2 ,
              const Pt& q1 , const Pt& q2 ){
    if( ( ( p2 - p1 ) ^ ( q2 - q1 ) ) == 0 ){ // parallel
        if( ori( p1 , p2 , q1 ) ) return false;
        return ( ( p1 - q1 ) * ( p2 - q1 ) ) <= 0 ||
            ( ( p1 - q2 ) * ( p2 - q2 ) ) <= 0 ||
            ( ( q1 - p1 ) * ( q2 - p1 ) ) <= 0 ||
            ( ( q1 - p2 ) * ( q2 - p2 ) ) <= 0;
    }
    return (ori( p1, p2, q1 ) * ori( p1, p2, q2 ) <= 0) &&
        (ori( q1, q2, p1 ) * ori( q1, q2, p2 ) <= 0);
}

```

### 4.4 Intersection of circle and segment

```

bool Inter( const Pt& p1 , const Pt& p2 , Circle& cc ){
    Pt dp = p2 - p1;
    double a = dp * dp;
    double b = 2 * ( dp * ( p1 - cc.O ) );
    double c = cc.O * cc.O + p1 * p1 - 2 * ( cc.O * p1 )
        - cc.R * cc.R;
    double bb4ac = b * b - 4 * a * c;
    return !( fabs( a ) < eps or bb4ac < 0 );
}

```

### 4.5 Intersection of 2 circles

### 4.6 Circle cover

```

#define N 1021
struct CircleCover{
    int C; Circle c[ N ];
    bool g[ N ][ N ], overlap[ N ][ N ];
    // Area[i] : area covered by at least i circles

```

```

D Area[ N ];
void init( int _C ){ C = _C; }
bool CCinter( Circle& a , Circle& b , Pt& p1 , Pt& p2 )
{
    Pt o1 = a.O , o2 = b.O;
    D r1 = a.R , r2 = b.R;
    if( norm( o1 - o2 ) > r1 + r2 ) return {};
    if( norm( o1 - o2 ) < max(r1, r2) - min(r1, r2) )
        return {};
    D d2 = ( o1 - o2 ) * ( o1 - o2 );
    D d = sqrt(d2);
    if( d > r1 + r2 ) return false;
    Pt u = (o1+o2)*0.5 + (o1-o2)*((r2*r2-r1*r1)/(2*d2));
    D A = sqrt((r1+r2+d)*(r1-r2+d)*(r1+r2-d)*(-r1+r2+d));
    Pt v = Pt( o1.Y-o2.Y , -o1.X + o2.X ) * A / (2*d2);
    p1 = u + v; p2 = u - v;
    return true;
}
struct Tevent {
    Pt p; D ang; int add;
    Tevent() {}
    Tevent(Pt _a, D _b, int _c): p(_a), ang(_b), add(_c) {}
    bool operator<(const Tevent &a)const
    {return ang < a.ang;}
}eve[ N * 2 ];
// strict: x = 0, otherwise x = -1
bool disjunct( Circle& a, Circle& b, int x ){
    return sign( norm( a.O - b.O ) - a.R - b.R ) > x;
}
bool contain( Circle& a, Circle& b, int x ){
    return sign( a.R - b.R - norm( a.O - b.O ) ) > x;
}
bool contain(int i, int j){ /* c[j] is non-strictly
    in c[i]. */
    return (sign(c[i].R - c[j].R) > 0 ||
        (sign(c[i].R - c[j].R) == 0 && i < j) ) &&
        contain(c[i], c[j], -1);
}
void solve(){
    for( int i = 0 ; i <= C + 1 ; i ++ )
        Area[ i ] = 0;
    for( int i = 0 ; i < C ; i ++ )
        for( int j = 0 ; j < C ; j ++ )
            overlap[i][j] = contain(i, j);
    for( int i = 0 ; i < C ; i ++ )
        for( int j = 0 ; j < C ; j ++ )
            g[i][j] = !(overlap[i][j] || overlap[j][i] ||
                disjunct(c[i], c[j], -1));
    for( int i = 0 ; i < C ; i ++ ){
        int E = 0, cnt = 1;
        for( int j = 0 ; j < C ; j ++ )
            if( j != i && overlap[j][i] )
                cnt ++;
        for( int j = 0 ; j < C ; j ++ )
            if( i != j && g[i][j] ){
                Pt aa, bb;
                CCinter(c[i], c[j], aa, bb);
                D A = atan2(aa.Y - c[i].O.Y, aa.X - c[i].O.X);
                D B = atan2(bb.Y - c[i].O.Y, bb.X - c[i].O.X);
                eve[E ++] = Tevent(bb, B, 1);
                eve[E ++] = Tevent(aa, A, -1);
                if(B > A) cnt ++;
            }
        if( E == 0 ) Area[ cnt ] += pi * c[i].R * c[i].R;
        else{
            sort( eve , eve + E );
            eve[E] = eve[0];
            for( int j = 0 ; j < E ; j ++ ){
                cnt += eve[j].add;
                Area[cnt] += (eve[j].p ^ eve[j + 1].p) * .5;
                D theta = eve[j + 1].ang - eve[j].ang;
                if( theta < 0 ) theta += 2. * pi;
                Area[cnt] += ( theta - sin(theta) ) * c[i].R
                    * c[i].R * .5;
            }
        }
    }
}

```

```

}
};

```

## 4.7 Li Chao Segment Tree

```

struct LiChao_min{
    struct line{
        LL m, c;
        line(LL _m=0, LL _c=0) { m = _m; c = _c; }
        LL eval(LL x) { return m * x + c; }
    };
    struct node{
        node *l, *r; line f;
        node(line v) { f = v; l = r = NULL; }
    };
    typedef node* pnode;
    pnode root; int sz;
#define mid ((l+r)>>1)
    void insert(line &v, int l, int r, pnode &nd){
        if(!nd) { nd = new node(v); return; }
        LL trl = nd->f.eval(l), trr = nd->f.eval(r);
        LL vl = v.eval(l), vr = v.eval(r);
        if(trl <= vl && trr <= vr) return;
        if(trl > vl && trr > vr) { nd->f = v; return; }
        if(trl > vl) swap(nd->f, v);
        if(nd->f.eval(mid) < v.eval(mid)) insert(v, mid +
            1, r, nd->r);
        else swap(nd->f, v), insert(v, l, mid, nd->l);
    }
    LL query(int x, int l, int r, pnode &nd){
        if(!nd) return LLONG_MAX;
        if(l == r) return nd->f.eval(x);
        if(mid >= x) return min(nd->f.eval(x), query(x, l,
            mid, nd->l));
        return min(nd->f.eval(x), query(x, mid + 1, r, nd->
            r));
    }
    /* -sz <= query_x <= sz */
    void init(int _sz){ sz = _sz + 1; root = NULL; }
    void add_line(LL m, LL c){ line v(m, c); insert(v, -
        sz, sz, root); }
    LL query(LL x) { return query(x, -sz, sz, root); }
};

```

## 4.8 Convex Hull trick

```

/* Given a convexhull, answer queries in O(\lg N)
CH should not contain identical points, the area should
be > 0, min pair(x, y) should be listed first */
double det( const Pt& p1 , const Pt& p2 )
{ return p1.X * p2.Y - p1.Y * p2.X; }
struct Conv{
    int n;
    vector<Pt> a;
    vector<Pt> upper, lower;
    Conv(vector<Pt> _a) : a(_a){
        n = a.size();
        int ptr = 0;
        for(int i=1; i<n; ++i) if (a[ptr] < a[i]) ptr = i;
        for(int i=0; i<=ptr; ++i) lower.push_back(a[i]);
        for(int i=ptr; i<n; ++i) upper.push_back(a[i]);
        upper.push_back(a[0]);
    }
    int sign( LL x ){ // fixed when changed to double
        return x < 0 ? -1 : x > 0 }
    pair<LL,int> get_tang(vector<Pt> &conv, Pt vec){
        int l = 0, r = (int)conv.size() - 2;
        for( ; l + 1 < r; ){
            int mid = (l + r) / 2;
            if(sign(det(conv[mid+1]-conv[mid],vec))>0)r=mid;
            else l = mid;
        }
        return max(make_pair(det(vec, conv[r]), r),
            make_pair(det(vec, conv[0]), 0));
    }
    void upd_tang(const Pt &p, int id, int &i0, int &i1){
        if(det(a[i0] - p, a[id] - p) > 0) i0 = id;
        if(det(a[i1] - p, a[id] - p) < 0) i1 = id;
    }
};

```

```

}
void bi_search(int l, int r, Pt p, int &i0, int &i1){
    if(l == r) return;
    upd_tang(p, l % n, i0, i1);
    int sl=sign(det(a[l % n] - p, a[(l + 1) % n] - p));
    for( ; l + 1 < r; ) {
        int mid = (l + r) / 2;
        int smid=sign(det(a[mid%n]-p, a[(mid+1)%n]-p));
        if (smid == sl) l = mid;
        else r = mid;
    }
    upd_tang(p, r % n, i0, i1);
}
int bi_search(Pt u, Pt v, int l, int r) {
    int sl = sign(det(v - u, a[l % n] - u));
    for( ; l + 1 < r; ) {
        int mid = (l + r) / 2;
        int smid = sign(det(v - u, a[mid % n] - u));
        if (smid == sl) l = mid;
        else r = mid;
    }
    return l % n;
}
// 1. whether a given point is inside the CH
bool contain(Pt p) {
    if (p.X < lower[0].X || p.X > lower.back().X)
        return 0;
    int id = lower_bound(lower.begin(), lower.end(), Pt
        (p.X, -INF)) - lower.begin();
    if (lower[id].X == p.X) {
        if (lower[id].Y > p.Y) return 0;
    }else if(det(lower[id-1]-p, lower[id]-p)<0)return 0;
    id = lower_bound(upper.begin(), upper.end(), Pt(p.X
        , INF), greater<Pt>()) - upper.begin();
    if (upper[id].X == p.X) {
        if (upper[id].Y < p.Y) return 0;
    }else if(det(upper[id-1]-p, upper[id]-p)<0)return 0;
    return 1;
}
// 2. Find 2 tang pts on CH of a given outside point
// return true with i0, i1 as index of tangent points
// return false if inside CH
bool get_tang(Pt p, int &i0, int &i1) {
    if (contain(p)) return false;
    i0 = i1 = 0;
    int id = lower_bound(lower.begin(), lower.end(), p)
        - lower.begin();
    bi_search(0, id, p, i0, i1);
    bi_search(id, (int)lower.size(), p, i0, i1);
    id = lower_bound(upper.begin(), upper.end(), p,
        greater<Pt>()) - upper.begin();
    bi_search((int)lower.size() - 1, (int)lower.size()
        - 1 + id, p, i0, i1);
    bi_search((int)lower.size() - 1 + id, (int)lower.
        size() - 1 + (int)upper.size(), p, i0, i1);
    return true;
}
// 3. Find tangent points of a given vector
// ret the idx of vertex has max cross value with vec
int get_tang(Pt vec){
    pair<LL, int> ret = get_tang(upper, vec);
    ret.second = (ret.second+(int)lower.size()-1)%n;
    ret = max(ret, get_tang(lower, vec));
    return ret.second;
}
// 4. Find intersection point of a given line
// return 1 and intersection is on edge (i, next(i))
// return 0 if no strictly intersection
bool get_intersection(Pt u, Pt v, int &i0, int &i1){
    int p0 = get_tang(u - v), p1 = get_tang(v - u);
    if(sign(det(v-u, a[p0]-u))*sign(det(v-u, a[p1]-u))<0){
        if (p0 > p1) swap(p0, p1);
        i0 = bi_search(u, v, p0, p1);
        i1 = bi_search(u, v, p1, p0 + n);
        return 1;
    }
    return 0;
}
}
};

```

## 4.9 Tangent line of two circles

```

vector<Line> go( const Cir& c1 , const Cir& c2 , int
    sign1 ){
    // sign1 = 1 for outer tang, -1 for inter tang
    vector<Line> ret;
    double d_sq = norm2( c1.0 - c2.0 );
    if( d_sq < eps ) return ret;
    double d = sqrt( d_sq );
    Pt v = ( c2.0 - c1.0 ) / d;
    double c = ( c1.R - sign1 * c2.R ) / d;
    if( c * c > 1 ) return ret;
    double h = sqrt( max( 0.0 , 1.0 - c * c ) );
    for( int sign2 = 1 ; sign2 >= -1 ; sign2 -= 2 ){
        Pt n = { v.X * c - sign2 * h * v.Y ,
            v.Y * c + sign2 * h * v.X };
        Pt p1 = c1.0 + n * c1.R;
        Pt p2 = c2.0 + n * ( c2.R * sign1 );
        if( fabs( p1.X - p2.X ) < eps and
            fabs( p1.Y - p2.Y ) < eps )
            p2 = p1 + perp( c2.0 - c1.0 );
        ret.push_back( { p1 , p2 } );
    }
    return ret;
}

```

## 4.10 KD Tree

```

const int MXN = 100005;

struct KDTree {
    struct Node {
        int x,y,x1,y1,x2,y2;
        int id,f;
        Node *L, *R;
    }tree[MXN];
    int n;
    Node *root;

    long long dis2(int x1, int y1, int x2, int y2) {
        long long dx = x1-x2;
        long long dy = y1-y2;
        return dx*dx+dy*dy;
    }
    static bool cmpx(Node& a, Node& b){ return a.x<b.x; }
    static bool cmpy(Node& a, Node& b){ return a.y<b.y; }
    void init(vector<pair<int,int>> ip) {
        n = ip.size();
        for (int i=0; i<n; i++) {
            tree[i].id = i;
            tree[i].x = ip[i].first;
            tree[i].y = ip[i].second;
        }
        root = build_tree(0, n-1, 0);
    }
    Node* build_tree(int L, int R, int dep) {
        if (L>R) return nullptr;
        int M = (L+R)/2;
        tree[M].f = dep%2;
        nth_element(tree+L, tree+M, tree+R+1, tree[M].f ?
            cmpy : cmpx);
        tree[M].x1 = tree[M].x2 = tree[M].x;
        tree[M].y1 = tree[M].y2 = tree[M].y;

        tree[M].L = build_tree(L, M-1, dep+1);
        if (tree[M].L) {
            tree[M].x1 = min(tree[M].x1, tree[M].L->x1);
            tree[M].x2 = max(tree[M].x2, tree[M].L->x2);
            tree[M].y1 = min(tree[M].y1, tree[M].L->y1);
            tree[M].y2 = max(tree[M].y2, tree[M].L->y2);
        }

        tree[M].R = build_tree(M+1, R, dep+1);
        if (tree[M].R) {
            tree[M].x1 = min(tree[M].x1, tree[M].R->x1);
            tree[M].x2 = max(tree[M].x2, tree[M].R->x2);
            tree[M].y1 = min(tree[M].y1, tree[M].R->y1);
            tree[M].y2 = max(tree[M].y2, tree[M].R->y2);
        }
    }
}

```



```

    return tree+M;
}
int touch(Node* r, int x, int y, long long d2){
    long long dis = sqrt(d2)+1;
    if (x<r->x1-dis || x>r->x2+dis || y<r->y1-dis || y>
        r->y2+dis)
        return 0;
    return 1;
}
void nearest(Node* r, int x, int y, int &mID, long
    long &md2) {
    if (!r || !touch(r, x, y, md2)) return;
    long long d2 = dis2(r->x, r->y, x, y);
    if (d2 < md2 || (d2 == md2 && mID < r->id)) {
        mID = r->id;
        md2 = d2;
    }
    // search order depends on split dim
    if ((r->f == 0 && x < r->x) ||
        (r->f == 1 && y < r->y)) {
        nearest(r->L, x, y, mID, md2);
        nearest(r->R, x, y, mID, md2);
    } else {
        nearest(r->R, x, y, mID, md2);
        nearest(r->L, x, y, mID, md2);
    }
}
int query(int x, int y) {
    int id = 1029384756;
    long long d2 = 102938475612345678LL;
    nearest(root, x, y, id, d2);
    return id;
}
}tree;

```

#### 4.11 Lower Concave Hull

```

/****
maintain a "concave hull" that support the following
1. insertion of a line
2. query of height(y) on specific x on the hull
****/
/* set as needed */
typedef long double LD;
const LD eps=1e-9;
const LD inf=1e19;
class Seg {
public:
    LD m,c,x1,x2; // y=mx+c
    bool flag;
    Seg(
        LD _m,LD _c,LD _x1=-inf,LD _x2=inf,bool _flag=0)
        :m(_m),c(_c),x1(_x1),x2(_x2),flag(_flag) {}
    LD evaly(LD x) const {
        return m*x+c;
    }
    const bool operator<(LD x) const {
        return x2-eps<x;
    }
    const bool operator<(const Seg &b) const {
        if(flag||b.flag) return *this<b.x1;
        return m+eps<b.m;
    }
};
class LowerConcaveHull { // maintain a hull like: \_/_/
public:
    set<Seg> hull;
    /* functions */
    LD xintersection(Seg a,Seg b) {
        return (a.c-b.c)/(b.m-a.m);
    }
    inline set<Seg>::iterator replace(set<Seg> &
        hull,set<Seg>::iterator it,Seg s) {
        hull.erase(it);
        return hull.insert(s).first;
    }
    void insert(Seg s) {
        // insert a line and update hull
        set<Seg>::iterator it=hull.find(s);

```

```

// check for same slope
if(it!=hull.end()) {
    if(it->c+eps>=s.c) return;
    hull.erase(it);
}
// check if below whole hull
it=hull.lower_bound(s);
if(it!=hull.end()&&
    s.evaly(it->x1)<=it->evaly(it->x1)+eps) return;
// update right hull
while(it!=hull.end()) {
    LD x=xintersection(s,*it);
    if(x>it->x2-eps) hull.erase(it++);
    else {
        s.x2=x;
        it=replace(hull,it,Seg(it->m,it->c,x,it->x2));
        break;
    }
}
// update left hull
while(it!=hull.begin()) {
    LD x=xintersection(s,*(--it));
    if(x<it->x1+eps) hull.erase(it++);
    else {
        s.x1=x;
        it=replace(hull,it,Seg(it->m,it->c,it->x1,x));
        break;
    }
}
// insert s
hull.insert(s);
}
void insert(LD m,LD c) { insert(Seg(m,c)); }
LD query(LD x) { // return y @ given x
    set<Seg>::iterator it =
        hull.lower_bound(Seg(0.0,0.0,x,x,1));
    return it->evaly(x);
}
};

```

#### 4.12 Min Enclosing Circle

```

struct Mec{
    // return pair of center and r
    static const int N = 101010;
    int n;
    Pt p[ N ], cen;
    double r2;
    void init( int _n , Pt _p[] ){
        n = _n;
        memcpy( p , _p , sizeof(Pt) * n );
    }
    double sqr(double a){ return a*a; }
    Pt center(Pt p0, Pt p1, Pt p2) {
        Pt a = p1-p0;
        Pt b = p2-p0;
        double c1=norm2( a ) * 0.5;
        double c2=norm2( b ) * 0.5;
        double d = a ^ b;
        double x = p0.X + (c1 * b.Y - c2 * a.Y) / d;
        double y = p0.Y + (a.X * c2 - b.X * c1) / d;
        return Pt(x,y);
    }
    pair<Pt,double> solve(){
        random_shuffle(p,p+n);
        r2=0;
        for (int i=0; i<n; i++){
            if (norm2(cen-p[i]) <= r2) continue;
            cen = p[i];
            r2 = 0;
            for (int j=0; j<i; j++){
                if (norm2(cen-p[j]) <= r2) continue;
                cen=Pt((p[i].X+p[j].X)/2,(p[i].Y+p[j].Y)/2);
                r2 = norm2(cen-p[j]);
                for (int k=0; k<j; k++){
                    if (norm2(cen-p[k]) <= r2) continue;
                    cen = center(p[i],p[j],p[k]);
                    r2 = norm2(cen-p[k]);
                }
            }
        }
    }
};

```



```

    }
    return {cen,sqrt(r2)};
}
} mec;

```

#### 4.13 Minkowski sum

```

vector<Pt> minkowski(vector<Pt> p, vector<Pt> q){
    int n = p.size() , m = q.size();
    Pt c = Pt(0, 0);
    for( int i = 0; i < m; i ++ ) c = c + q[i];
    c = c / m;
    for( int i = 0; i < m; i ++ ) q[i] = q[i] - c;
    int cur = -1;
    for( int i = 0; i < m; i ++ )
        if( (q[i] ^ (p[0] - p[n-1])) > -eps)
            if( cur == -1 ||
                (q[i] ^ (p[0] - p[n-1])) >
                (q[cur] ^ (p[0] - p[n-1])) )
                cur = i;
    vector<Pt> h;
    p.push_back(p[0]);
    for( int i = 0; i < n; i ++ )
        while( true ){
            h.push_back(p[i] + q[cur]);
            int nxt = (cur + 1 == m ? 0 : cur + 1);
            if((q[cur] ^ (p[i+1] - p[i])) < -eps) cur = nxt;
            else if( (q[nxt] ^ (p[i+1] - p[i])) >
                    (q[cur] ^ (p[i+1] - p[i])) ) cur = nxt;
            else break;
        }
    for(auto &&i : h) i = i + c;
    return convex_hull(h);
}

```

#### 4.14 Heart of Triangle

```

Pt inCenter( Pt &A, Pt &B, Pt &C) { // 内心
    double a = norm(B-C), b = norm(C-A), c = norm(A-B);
    return (A * a + B * b + C * c) / (a + b + c);
}
Pt circumCenter( Pt &a, Pt &b, Pt &c) { // 外心
    Pt bb = b - a, cc = c - a;
    double db=norm2(bb), dc=norm2(cc), d=2*(bb ^ cc);
    return a-Pt(bb.Y*dc-cc.Y*db, cc.X*db-bb.X*dc) / d;
}
Pt othroCenter( Pt &a, Pt &b, Pt &c) { // 垂心
    Pt ba = b - a, ca = c - a, bc = b - c;
    double Y = ba.Y * ca.Y * bc.Y,
           A = ca.X * ba.Y - ba.X * ca.Y,
           x0= (Y+ca.X*ba.Y*b.X-ba.X*ca.Y*c.X) / A,
           y0= -ba.X * (x0 - c.X) / ba.Y + ca.Y;
    return Pt(x0, y0);
}

```

## 5 Graph

### 5.1 HeavyLightDecomp

```

#define SZ(c) (int)(c).size()
#define ALL(c) (c).begin(), (c).end()
#define REP(i, s, e) for(int i = (s); i <= (e); i++)
#define REPD(i, s, e) for(int i = (s); i >= (e); i--)
typedef pair< int , int > PII;
const int MAXN = 100010;
const int LOG = 19;
struct HLD{
    int n;
    vector<int> g[MAXN];
    int sz[MAXN], dep[MAXN];
    int ts, tid[MAXN], tdi[MAXN], tl[MAXN], tr[MAXN];
    // ts : timestamp , useless after yutruli
    // tid[ u ] : pos. of node u in the seq.
    // tdi[ i ] : node at pos i of the seq.
}

```

```

// tl , tr[ u ] : subtree interval in the seq. of
// node u
int mom[MAXN][LOG], head[MAXN];
// head[ u ] : head of the chain contains u
void dfssz(int u, int p){
    dep[u] = dep[p] + 1;
    mom[u][0] = p;
    sz[u] = 1;
    head[u] = u;
    for(int& v:g[u]) if(v != p){
        dep[v] = dep[u] + 1;
        dfssz(v, u);
        sz[u] += sz[v];
    }
}
void dfshl(int u){
    ts++;
    tid[u] = tl[u] = tr[u] = ts;
    tdi[tid[u]] = u;
    sort(ALL(g[u]),
        [&](int a, int b){return sz[a] > sz[b];});
    bool flag = 1;
    for(int& v:g[u]) if(v != mom[u][0]){
        if(flag) head[v] = head[u], flag = 0;
        dfshl(v);
        tr[u] = tr[v];
    }
}
inline int lca(int a, int b){
    if(dep[a] > dep[b]) swap(a, b);
    int diff = dep[b] - dep[a];
    REPD(k, LOG-1, 0) if(diff & (1<<k)){
        b = mom[b][k];
    }
    if(a == b) return a;
    REPD(k, LOG-1, 0) if(mom[a][k] != mom[b][k]){
        a = mom[a][k];
        b = mom[b][k];
    }
    return mom[a][0];
}
void init( int _n ){
    n = _n;
    REP( i , 1 , n ) g[ i ].clear();
}
void addEdge( int u , int v ){
    g[ u ].push_back( v );
    g[ v ].push_back( u );
}
void yutruli(){
    dfssz(1, 0);
    ts = 0;
    dfshl(1);
    REP(k, 1, LOG-1) REP(i, 1, n)
        mom[i][k] = mom[mom[i][k-1]][k-1];
}
vector< PII > getPath( int u , int v ){
    vector< PII > res;
    while( tid[ u ] < tid[ head[ v ] ] ){
        res.push_back( PII(tid[ head[ v ] ] , tid[ v ] ) );
        v = mom[ head[ v ] ][ 0 ];
    }
    res.push_back( PII( tid[ u ] , tid[ v ] ) );
    reverse( ALL( res ) );
    return res;
}
/* res : list of intervals from u to v
 * u must be ancestor of v
 * usage :
 * vector< PII >& path = tree.getPath( u , v )
 * for( PII tp : path ) {
 *     int l , r;tie( l , r ) = tp;
 *     upd( l , r );
 *     uu = tree.tdi[ l ] , vv = tree.tdi[ r ];
 *     uu ~> vv is a heavy path on tree
 * }
 */
} tree;

```

## 5.2 DominatorTree

```

const int MAXN = 100010;
struct DominatorTree{
#define REP(i,s,e) for(int i=(s);i<=(e);i++)
#define REPD(i,s,e) for(int i=(s);i>=(e);i--)
    int n , m , s;
    vector< int > g[ MAXN ] , pred[ MAXN ];
    vector< int > cov[ MAXN ];
    int dfn[ MAXN ] , nfd[ MAXN ] , ts;
    int par[ MAXN ];
    int sdom[ MAXN ] , idom[ MAXN ];
    int mom[ MAXN ] , mn[ MAXN ];
    inline bool cmp( int u , int v )
    { return dfn[ u ] < dfn[ v ]; }
    int eval( int u ){
        if( mom[ u ] == u ) return u;
        int res = eval( mom[ u ] );
        if( cmp( sdom[ mn[ mom[ u ] ] ] , sdom[ mn[ u ] ] ) )
            mn[ u ] = mn[ mom[ u ] ];
        return mom[ u ] = res;
    }
    void init( int _n , int _m , int _s ){
        ts = 0; n = _n; m = _m; s = _s;
        REP( i , 1 , n ) g[ i ].clear(), pred[ i ].clear();
    }
    void addEdge( int u , int v ){
        g[ u ].push_back( v );
        pred[ v ].push_back( u );
    }
    void dfs( int u ){
        ts++;
        dfn[ u ] = ts;
        nfd[ ts ] = u;
        for( int v : g[ u ] ) if( dfn[ v ] == 0 ){
            par[ v ] = u;
            dfs( v );
        }
    }
    void build(){
        REP( i , 1 , n ){
            dfn[ i ] = nfd[ i ] = 0;
            cov[ i ].clear();
            mom[ i ] = mn[ i ] = sdom[ i ] = i;
        }
        dfs( s );
        REPD( i , n , 2 ){
            int u = nfd[ i ];
            if( u == 0 ) continue;
            for( int v : pred[ u ] ) if( dfn[ v ] ){
                eval( v );
                if( cmp( sdom[ mn[ v ] ] , sdom[ u ] ) )
                    sdom[ u ] = sdom[ mn[ v ] ];
            }
            cov[ sdom[ u ] ].push_back( u );
            mom[ u ] = par[ u ];
            for( int w : cov[ par[ u ] ] ){
                eval( w );
                if( cmp( sdom[ mn[ w ] ] , par[ u ] ) )
                    idom[ w ] = mn[ w ];
                else idom[ w ] = par[ u ];
            }
            cov[ par[ u ] ].clear();
        }
        REP( i , 2 , n ){
            int u = nfd[ i ];
            if( u == 0 ) continue;
            if( idom[ u ] != sdom[ u ] )
                idom[ u ] = idom[ idom[ u ] ];
        }
    }
} domT;

```

## 5.3 MaxClique

```

#define N 111
struct MaxClique{ // 0-base
    typedef bitset< N > Int;
    Int linkto[ N ] , v[ N ];

```

```

    int n;
    void init( int _n ){
        n = _n;
        for( int i = 0 ; i < n ; i ++ ){
            linkto[ i ].reset();
            v[ i ].reset();
        }
    }
    void addEdge( int a , int b ){
        v[ a ][ b ] = v[ b ][ a ] = 1;
    }
    int popcount( const Int& val )
    { return val.count(); }
    int lowbit( const Int& val )
    { return val._Find_first(); }
    int ans , stk[ N ];
    int id[ N ] , di[ N ] , deg[ N ];
    Int cans;
    void maxclique( int elem_num , Int candi ){
        if( elem_num > ans ){
            ans = elem_num;
            cans.reset();
            for( int i = 0 ; i < elem_num ; i ++ )
                cans[ id[ stk[ i ] ] ] = 1;
        }
        int potential = elem_num + popcount( candi );
        if( potential <= ans ) return;
        int pivot = lowbit( candi );
        Int smaller_candi = candi & (~linkto[pivot]);
        while( smaller_candi.count() && potential > ans ){
            int next = lowbit( smaller_candi );

            candi[next] = !candi[next];
            smaller_candi[ next ] = !smaller_candi[ next ];
            potential --;

            if( next == pivot || (smaller_candi & linkto[next]
                ).count() ){
                stk[ elem_num ] = next;
                maxclique( elem_num + 1 , candi & linkto[next] );
            }
        }
    }
    int solve(){
        for( int i = 0 ; i < n ; i ++ ){
            id[ i ] = i;
            deg[ i ] = v[ i ].count();
        }
        sort( id , id + n , [&]( int id1 , int id2 ){
            return deg[id1] > deg[id2]; } );
        for( int i = 0 ; i < n ; i ++ )
            di[ id[ i ] ] = i;
        for( int i = 0 ; i < n ; i ++ )
            for( int j = 0 ; j < n ; j ++ )
                if( v[ id[ i ] ][ id[ j ] ] )
                    linkto[ di[ i ] ][ di[ j ] ] = 1;
        Int cand; cand.reset();
        for( int i = 0 ; i < n ; i ++ )
            cand[ i ] = 1;
        ans = 1;
        cans.reset(); cans[ 0 ] = 1;
        maxclique( 0 , cand );
        return ans;
    }
} solver;

```

## 5.4 Number of Maximal Clique

```

// bool g[][] : adjacent array indexed from 1 to n
void dfs( int sz ){
    int i , j , k , t , cnt , best = 0;
    if( ne[sz] == ce[sz] ){ if( ce[sz] == 0 ) ++ans; return; }
    for( t=0 , i=1 ; i<=ne[sz] ; ++i ){
        for( cnt=0 , j=ne[sz]+1 ; j<=ce[sz] ; ++j )
            if( !g[lst[sz][i]][lst[sz][j]] ) ++cnt;
        if( t==0 || cnt<best ) t=i , best=cnt;
    } if( t && best<=0 ) return;
    for( k=ne[sz]+1 ; k<=ce[sz] ; ++k ) {
        if( t>0 ){ for( i=k ; i<=ce[sz] ; ++i )
            if( !g[lst[sz][t]][lst[sz][i]] ) break;

```

```

    swap(lst[sz][k], lst[sz][i]);
} i=lst[sz][k]; ne[sz+1]=ce[sz+1]=0;
for (j=1; j<k; ++j) if (g[i][lst[sz][j]])
    lst[sz+1][++ne[sz+1]]=lst[sz][j];
for (ce[sz+1]=ne[sz+1], j=k+1; j<=ce[sz]; ++j)
    if (g[i][lst[sz][j]]) lst[sz+1][++ce[sz+1]]=lst[sz][j];
dfs(sz+1); ++ne[sz]; --best;
for (j=k+1, cnt=0; j<=ce[sz]; ++j) if (!g[i][lst[sz][j]]) ++cnt;
if (t==0 || cnt<best) t=k, best=cnt;
if (t && best<=0) break;
}
void work(){
    ne[0]=0; ce[0]=0;
    for(int i=1; i<=n; ++i) lst[0][++ce[0]]=i;
    ans=0; dfs(0);
}

```

## 5.5 Strongly Connected Component

```

struct Scc{
    int n, nScc, vst[MXN], bln[MXN];
    vector<int> E[MXN], rE[MXN], vec;
    void init(int _n){
        n = _n;
        for (int i=0; i<MXN; i++){
            E[i].clear();
            rE[i].clear();
        }
    }
    void add_edge(int u, int v){
        E[u].PB(v);
        rE[v].PB(u);
    }
    void DFS(int u){
        vst[u]=1;
        for (auto v : E[u])
            if (!vst[v]) DFS(v);
        vec.PB(u);
    }
    void rDFS(int u){
        vst[u] = 1;
        bln[u] = nScc;
        for (auto v : rE[u])
            if (!vst[v]) rDFS(v);
    }
    void solve(){
        nScc = 0;
        vec.clear();
        FZ(vst);
        for (int i=0; i<n; i++)
            if (!vst[i]) DFS(i);
        reverse(vec.begin(), vec.end());
        FZ(vst);
        for (auto v : vec){
            if (!vst[v]){
                rDFS(v);
                nScc++;
            }
        }
    }
};

```

## 5.6 Dynamic MST

```

/* Dynamic MST  $O(Q \lg^2 Q)$ 
(qx[i], qy[i]) -> chg weight of edge No.qx[i] to qy[i]
delete an edge: (i, \infty)
add an edge: change from \infty to specific value
*/
const int SZ=M+3*MXQ;
int a[N],*tz;
int find(int xx){
    int root=xx; while(a[root]) root=a[root];
    int next; while((next=a[xx])){a[xx]=root; xx=next; }
    return root;
}

```

```

bool cmp(int aa,int bb){ return tz[aa]<tz[bb]; }
int kx[N],ky[N],kt, vd[N],id[M], app[M];
bool extra[M];
void solve(int *qx,int *qy,int Q,int n,int *x,int *y,
    int *z,int m1,long long ans){
    if(Q==1){
        for(int i=1;i<=n;i++) a[i]=0;
        z[ qx[0] ]=qy[0]; tz = z;
        for(int i=0;i<m1;i++) id[i]=i;
        sort(id,id+m1,cmp); int ri,rj;
        for(int i=0;i<m1;i++){
            ri=find(x[id[i]]); rj=find(y[id[i]]);
            if(ri!=rj){ ans+=z[id[i]]; a[ri]=rj; }
        }
        printf("%lld\n",ans);
        return;
    }
    int ri,rj;
    //contract
    kt=0;
    for(int i=1;i<=n;i++) a[i]=0;
    for(int i=0;i<Q;i++){
        ri=find(x[qx[i]]); rj=find(y[qx[i]]); if(ri!=rj) a[ri]=rj;
    }
    int tm=0;
    for(int i=0;i<m1;i++) extra[i]=true;
    for(int i=0;i<Q;i++) extra[ qx[i] ]=false;
    for(int i=0;i<m1;i++) if(extra[i]) id[tm++]=i;
    tz=z; sort(id,id+tm,cmp);
    for(int i=0;i<tm;i++){
        ri=find(x[id[i]]); rj=find(y[id[i]]);
        if(ri!=rj){
            a[ri]=rj; ans += z[id[i]];
            kx[kt]=x[id[i]]; ky[kt]=y[id[i]]; kt++;
        }
    }
    for(int i=1;i<=n;i++) a[i]=0;
    for(int i=0;i<kt;i++) a[ find(kx[i]) ]=find(ky[i]);
    int n2=0;
    for(int i=1;i<=n;i++) if(a[i]==0)
        vd[i]=++n2;
    for(int i=1;i<=n;i++) if(a[i])
        vd[i]=vd[find(i)];
    int m2=0, *Nx=x+m1, *Ny=y+m1, *Nz=z+m1;
    for(int i=0;i<m1;i++) app[i]=-1;
    for(int i=0;i<Q;i++) if(app[qx[i]]==-1){
        Nx[m2]=vd[ x[ qx[i] ] ]; Ny[m2]=vd[ y[ qx[i] ] ];
        Nz[m2]=z[ qx[i] ];
        app[qx[i]]=m2; m2++;
    }
    for(int i=0;i<Q;i++){ z[ qx[i] ]=qy[i]; qx[i]=app[qx[i]]; }
    for(int i=1;i<=n2;i++) a[i]=0;
    for(int i=0;i<tm;i++){
        ri=find(vd[ x[id[i]] ]); rj=find(vd[ y[id[i]] ]);
        if(ri!=rj){
            a[ri]=rj; Nx[m2]=vd[ x[id[i]] ];
            Ny[m2]=vd[ y[id[i]] ]; Nz[m2]=z[id[i]]; m2++;
        }
    }
    int mid=Q/2;
    solve(qx,qy,mid,n2,Nx,Ny,Nz,m2,ans);
    solve(qx+mid,qy+mid,Q-mid,n2,Nx,Ny,Nz,m2,ans);
}
int x[SZ],y[SZ],z[SZ],qx[MXQ],qy[MXQ],n,m,Q;
void init(){
    scanf("%d%d",&n,&m);
    for(int i=0;i<m;i++) scanf("%d%d%d",x+i,y+i,z+i);
    scanf("%d",&Q);
    for(int i=0;i<Q;i++){ scanf("%d%d",qx+i,qy+i); qx[i]--; }
}
void work(){ if(Q) solve(qx,qy,Q,n,x,y,z,m,0); }
int main(){init(); work(); }

```

## 5.7 Maximum General graph Matching

```

const int N = 514, E = (2e5) * 2;
struct Graph{

```

```

int to[E],bro[E],head[N],e;
int lnk[N],vis[N],stp,n;
void init( int _n ){
    stp = 0; e = 1; n = _n;
    for( int i = 1 ; i <= n ; i ++ )
        lnk[i] = vis[i] = 0;
}
void add_edge(int u,int v){
    to[e]=v,bro[e]=head[u],head[u]=e++;
    to[e]=u,bro[e]=head[v],head[v]=e++;
}
bool dfs(int x){
    vis[x]=stp;
    for(int i=head[x];i;i=bro[i]){
        int v=to[i];
        if(!lnk[v]){
            lnk[x]=v,lnk[v]=x;
            return true;
        }else if(vis[lnk[v]]<stp){
            int w=lnk[v];
            lnk[x]=v,lnk[v]=x,lnk[w]=0;
            if(dfs(w)){
                return true;
            }
            lnk[w]=v,lnk[v]=w,lnk[x]=0;
        }
    }
    return false;
}
int solve(){
    int ans = 0;
    for(int i=1;i<=n;i++){
        if(!lnk[i]){
            stp++; ans += dfs(i);
        }
    }
    return ans;
}
} graph;

```

## 5.8 Minimum General Weighted Matching

```

struct Graph {
    // Minimum General Weighted Matching (Perfect Match)
    static const int MXN = 105;
    int n, edge[MXN][MXN];
    int match[MXN],dis[MXN],onstk[MXN];
    vector<int> stk;
    void init(int _n) {
        n = _n;
        for( int i = 0 ; i < n ; i ++ )
            for( int j = 0 ; j < n ; j ++ )
                edge[ i ][ j ] = 0;
    }
    void add_edge(int u, int v, int w)
    { edge[u][v] = edge[v][u] = w; }
    bool SPFA(int u){
        if (onstk[u]) return true;
        stk.PB(u);
        onstk[u] = 1;
        for (int v=0; v<n; v++){
            if (u != v && match[u] != v && !onstk[v]){
                int m = match[v];
                if (dis[m] > dis[u] - edge[v][m] + edge[u][v]){
                    dis[m] = dis[u] - edge[v][m] + edge[u][v];
                    onstk[v] = 1;
                    stk.PB(v);
                    if (SPFA(m)) return true;
                    stk.pop_back();
                    onstk[v] = 0;
                }
            }
        }
        onstk[u] = 0;
        stk.pop_back();
        return false;
    }
    int solve() {
        // find a match
        for (int i=0; i<n; i+=2){
            match[i] = i+1;

```

```

            match[i+1] = i;
        }
        while (true){
            int found = 0;
            for( int i = 0 ; i < n ; i ++ )
                onstk[ i ] = dis[ i ] = 0;
            for (int i=0; i<n; i++){
                stk.clear();
                if (!onstk[i] && SPFA(i)){
                    found = 1;
                    while (SZ(stk)>=2){
                        int u = stk.back(); stk.pop_back();
                        int v = stk.back(); stk.pop_back();
                        match[u] = v;
                        match[v] = u;
                    }
                }
                if (!found) break;
            }
            int ret = 0;
            for (int i=0; i<n; i++)
                ret += edge[i][match[i]];
            ret /= 2;
            return ret;
        }
    }
}graph;

```

## 5.9 Maximum General Weighted Matching

```

struct WeightGraph {
    static const int INF = INT_MAX;
    static const int N = 514;
    struct edge{
        int u,v,w; edge(){}
        edge(int ui,int vi,int wi)
            :u(ui),v(vi),w(wi){}
    };
    int n,n_x;
    edge g[N*2][N*2];
    int lab[N*2];
    int match[N*2],slack[N*2],st[N*2],pa[N*2];
    int flo_from[N*2][N+1],S[N*2],vis[N*2];
    vector<int> flo[N*2];
    queue<int> q;
    int e_delta(const edge &e){
        return lab[e.u]+lab[e.v]-g[e.u][e.v].w*2;
    }
    void update_slack(int u,int x){
        if(!slack[x]||e_delta(g[u][x])<e_delta(g[slack[x]][x]))slack[x]=u;
    }
    void set_slack(int x){
        slack[x]=0;
        for(int u=1;u<=n;++u)
            if(g[u][x].w>0&&st[u]!=x&&S[st[u]]==0)
                update_slack(u,x);
    }
    void q_push(int x){
        if(x<=n)q.push(x);
        else for(size_t i=0;i<flo[x].size();i++)
            q_push(flo[x][i]);
    }
    void set_st(int x,int b){
        st[x]=b;
        if(x>n)for(size_t i=0;i<flo[x].size();++i)
            set_st(flo[x][i],b);
    }
    int get_pr(int b,int xr){
        int pr=find(flo[b].begin(),flo[b].end(),xr)-flo[b].begin();
        if(pr%2==1){
            reverse(flo[b].begin()+1,flo[b].end());
            return (int)flo[b].size()-pr;
        }else return pr;
    }
    void set_match(int u,int v){
        match[u]=g[u][v].v;
        if(u<=n) return;
        edge e=g[u][v];

```

```

int xr=flo_from[u][e.u],pr=get_pr(u,xr);
for(int i=0;i<pr;++i)set_match(flo[u][i],flo[u][i
^1]);
set_match(xr,v);
rotate(flo[u].begin(),flo[u].begin()+pr,flo[u].end
());
}
void augment(int u,int v){
for(;;){
int xnv=st[match[u]];
set_match(u,v);
if(!xnv)return;
set_match(xnv,st[pa[xnv]]);
u=st[pa[xnv]],v=xnv;
}
}
int get_lca(int u,int v){
static int t=0;
for(++t;u!=v;swap(u,v)){
if(u==0)continue;
if(vis[u]==t)return u;
vis[u]=t;
u=st[match[u]];
if(u==st[pa[u]]);
}
return 0;
}
void add_blossom(int u,int lca,int v){
int b=n+1;
while(b<=n_x&&st[b]++b;
if(b>n_x)++n_x;
lab[b]=0,S[b]=0;
match[b]=match[lca];
flo[b].clear();
flo[b].push_back(lca);
for(int x=u,y; x!=lca; x=st[pa[y]])
flo[b].push_back(x),flo[b].push_back(y=st[match[x
]]),q_push(y);
reverse(flo[b].begin()+1,flo[b].end());
for(int x=v,y; x!=lca; x=st[pa[y]])
flo[b].push_back(x),flo[b].push_back(y=st[match[x
]]),q_push(y);
set_st(b,b);
for(int x=1;x<=n_x;++x)g[b][x].w=g[x][b].w=0;
for(int x=1;x<=n;++x)flo_from[b][x]=0;
for(size_t i=0;i<flo[b].size();++i){
int xs=flo[b][i];
for(int x=1;x<=n_x;++x)
if(g[b][x].w==0||e_delta(g[xs][x])<e_delta(g[b
][x]))
g[b][x]=g[xs][x],g[x][b]=g[x][xs];
for(int x=1;x<=n;++x)
if(flo_from[xs][x])flo_from[b][x]=xs;
}
set_slack(b);
}
void expand_blossom(int b){
for(size_t i=0;i<flo[b].size();++i)
set_st(flo[b][i],flo[b][i]);
int xr=flo_from[b][g[b][pa[b]].u],pr=get_pr(b,xr);
for(int i=0;i<pr;i+=2){
int xs=flo[b][i],xns=flo[b][i+1];
pa[xs]=g[xns][xs].u;
S[xs]=1,S[xns]=0;
slack[xs]=0,set_slack(xns);
q_push(xns);
}
S[xr]=1,pa[xr]=pa[b];
for(size_t i=pr+1;i<flo[b].size();++i){
int xs=flo[b][i];
S[xs]=-1,set_slack(xs);
}
st[b]=0;
}
bool on_found_edge(const edge &e){
int u=st[e.u],v=st[e.v];
if(S[v]==-1){
pa[v]=e.u,S[v]=1;
int nu=st[match[v]];
slack[v]=slack[nu]=0;
S[nu]=0,q_push(nu);
}else if(S[v]==0){

```

```

int lca=get_lca(u,v);
if(!lca)return augment(u,v),augment(v,u),true;
else add_blossom(u,lca,v);
}
return false;
}
bool matching(){
memset(S+1,-1,sizeof(int)*n_x);
memset(slack+1,0,sizeof(int)*n_x);
q=queue<int>();
for(int x=1;x<=n_x;++x)
if(st[x]==x&&!match[x])pa[x]=0,S[x]=0,q_push(x);
if(q.empty())return false;
for(;;){
while(q.size()){
int u=q.front();q.pop();
if(S[st[u]]==1)continue;
for(int v=1;v<=n;++v)
if(g[u][v].w>0&&st[u]!=st[v]){
if(e_delta(g[u][v])==0){
if(on_found_edge(g[u][v]))return true;
}else update_slack(u,st[v]);
}
}
int d=INF;
for(int b=n+1;b<=n_x;++b)
if(st[b]==b&&S[b]==1)d=min(d,lab[b]/2);
for(int x=1;x<=n_x;++x)
if(st[x]==x&&slack[x]){
if(S[x]==-1)d=min(d,e_delta(g[slack[x]][x]));
else if(S[x]==0)d=min(d,e_delta(g[slack[x]][x
])/2);
}
for(int u=1;u<=n;++u){
if(S[st[u]]==0){
if(lab[u]<=d)return 0;
lab[u]-=d;
}else if(S[st[u]]==1)lab[u]+=d;
}
for(int b=n+1;b<=n_x;++b)
if(st[b]==b){
if(S[st[b]]==0)lab[b]+=d*2;
else if(S[st[b]]==1)lab[b]-=d*2;
}
q=queue<int>();
for(int x=1;x<=n_x;++x)
if(st[x]==x&&slack[x]&&st[slack[x]]!=x&&e_delta
(g[slack[x]][x])==0)
if(on_found_edge(g[slack[x]][x]))return true;
for(int b=n+1;b<=n_x;++b)
if(st[b]==b&&S[b]==1&&lab[b]==0)expand_blossom(
b);
}
return false;
}
pair<long long,int> solve(){
memset(match+1,0,sizeof(int)*n);
n_x=n;
int n_matches=0;
long long tot_weight=0;
for(int u=0;u<=n;++u)st[u]=u,flo[u].clear();
int w_max=0;
for(int u=1;u<=n;++u)
for(int v=1;v<=n;++v){
flo_from[u][v]=(u==v?u:0);
w_max=max(w_max,g[u][v].w);
}
for(int u=1;u<=n;++u)lab[u]=w_max;
while(matching())++n_matches;
for(int u=1;u<=n;++u)
if(match[u]&&match[u]<u)
tot_weight+=g[u][match[u]].w;
return make_pair(tot_weight,n_matches);
}
void add_edge( int ui , int vi , int wi ){
g[ui][vi].w = g[vi][ui].w = wi;
}
void init( int _n ){
n = _n;
for(int u=1;u<=n;++u)
for(int v=1;v<=n;++v)
g[u][v]=edge(u,v,0);
}

```

```

}
} graph;

```

## 5.10 Minimum Steiner Tree

```

// Minimum Steiner Tree
// O(V 3^T + V^2 2^T)
struct SteinerTree{
#define V 33
#define T 8
#define INF 1023456789
    int n, dst[V][V], dp[1 << T][V], tdst[V];
    void init( int _n ){
        n = _n;
        for( int i = 0 ; i < n ; i ++ ){
            for( int j = 0 ; j < n ; j ++ ){
                dst[ i ][ j ] = INF;
                dst[ i ][ i ] = 0;
            }
        }
        void add_edge( int ui , int vi , int wi ){
            dst[ ui ][ vi ] = min( dst[ ui ][ vi ] , wi );
            dst[ vi ][ ui ] = min( dst[ vi ][ ui ] , wi );
        }
        void shortest_path(){
            for( int k = 0 ; k < n ; k ++ )
                for( int i = 0 ; i < n ; i ++ )
                    for( int j = 0 ; j < n ; j ++ )
                        dst[ i ][ j ] = min( dst[ i ][ j ],
                            dst[ i ][ k ] + dst[ k ][ j ] );
        }
        int solve( const vector<int>& ter ){
            int t = (int)ter.size();
            for( int i = 0 ; i < ( 1 << t ) ; i ++ )
                for( int j = 0 ; j < n ; j ++ )
                    dp[ i ][ j ] = INF;
            for( int i = 0 ; i < n ; i ++ )
                dp[ 0 ][ i ] = 0;
            for( int msk = 1 ; msk < ( 1 << t ) ; msk ++ ){
                if( msk == ( msk & (-msk) ) ){
                    int who = __lg( msk );
                    for( int i = 0 ; i < n ; i ++ )
                        dp[ msk ][ i ] = dst[ ter[ who ] ][ i ];
                    continue;
                }
                for( int i = 0 ; i < n ; i ++ )
                    for( int submsk = ( msk - 1 ) & msk ; submsk ;
                        submsk = ( submsk - 1 ) & msk )
                        dp[ msk ][ i ] = min( dp[ msk ][ i ],
                            dp[ submsk ][ i ] +
                            dp[ msk ^ submsk ][ i ] );
                for( int i = 0 ; i < n ; i ++ ){
                    tdst[ i ] = INF;
                    for( int j = 0 ; j < n ; j ++ )
                        tdst[ i ] = min( tdst[ i ],
                            dp[ msk ][ j ] + dst[ j ][ i ] );
                }
                for( int i = 0 ; i < n ; i ++ )
                    dp[ msk ][ i ] = tdst[ i ];
            }
            int ans = INF;
            for( int i = 0 ; i < n ; i ++ )
                ans = min( ans , dp[ ( 1 << t ) - 1 ][ i ] );
            return ans;
        }
    } solver;
}

```

## 5.11 BCC based on vertex

```

struct BccVertex {
    int n, nScc, step, dfn[MAXN], low[MAXN];
    vector<int> E[MAXN], sccv[MAXN];
    int top, stk[MAXN];
    void init( int _n ) {
        n = _n;
        nScc = step = 0;
        for( int i=0; i<n; i++) E[i].clear();
    }
}

```

```

void add_edge( int u, int v ) {
    E[u].PB(v);
    E[v].PB(u);
}
void DFS( int u, int f ) {
    dfn[u] = low[u] = step++;
    stk[top++] = u;
    for( auto v: E[u] ) {
        if( v == f ) continue;
        if( dfn[v] == -1 ) {
            DFS(v, u);
            low[u] = min( low[u], low[v] );
            if( low[v] >= dfn[u] ) {
                int z;
                sccv[nScc].clear();
                do {
                    z = stk[--top];
                    sccv[nScc].PB(z);
                } while( z != v );
                sccv[nScc].PB(u);
                nScc++;
            }
        } else {
            low[u] = min( low[u], dfn[v] );
        }
    }
}
vector<vector<int>>> solve() {
    vector<vector<int>>> res;
    for( int i=0; i<n; i++) {
        dfn[i] = low[i] = -1;
    }
    for( int i=0; i<n; i++) {
        if( dfn[i] == -1 ) {
            top = 0;
            DFS(i, i);
        }
    }
    REP(i, nScc) res.PB(sccv[i]);
    return res;
}
} graph;

```

## 5.12 Min Mean Cycle

```

/* minimum mean cycle O(VE) */
struct MMC{
#define MAXE 101010
#define MAXN 1021
#define inf 1e9
#define eps 1e-6
    struct Edge {
        int v, u;
        double c;
    };
    int n, m, prv[MAXN][MAXN], prve[MAXN][MAXN], vst[MAXN];
    Edge e[MAXE];
    vector<int> edgeID, cycle, rho;
    double d[MAXN][MAXN];
    void init( int _n ){
        n = _n; m = 0;
    }
    // WARNING: TYPE matters
    void add_edge( int vi , int ui , double ci ){
        e[ m ++ ] = { vi , ui , ci };
    }
    void bellman_ford() {
        for( int i=0; i<n; i++) d[0][i]=0;
        for( int i=0; i<n; i++) {
            fill( d[i+1], d[i+1]+n, inf );
            for( int j=0; j<m; j++) {
                int v = e[j].v, u = e[j].u;
                if( d[i][v] < inf && d[i+1][u] > d[i][v] + e[j].c ) {
                    d[i+1][u] = d[i][v] + e[j].c;
                    prv[i+1][u] = v;
                    prve[i+1][u] = j;
                }
            }
        }
    }
}

```



```

}
double solve(){
    // returns inf if no cycle, mmc otherwise
    double mmc=inf;
    int st = -1;
    bellman_ford();
    for(int i=0; i<n; i++) {
        double avg=-inf;
        for(int k=0; k<n; k++) {
            if(d[n][i]<inf-eps) avg=max(avg,(d[n][i]-d[k][i])/(n-k));
            else avg=max(avg,inf);
        }
        if (avg < mmc) tie(mmc, st) = tie(avg, i);
    }
    FZ(vst); edgeID.clear(); cycle.clear(); rho.clear();
    for (int i=n; !vst[st]; st=prv[i--][st]) {
        vst[st]++;
        edgeID.PB(prve[i][st]);
        rho.PB(st);
    }
    while (vst[st] != 2) {
        int v = rho.back(); rho.pop_back();
        cycle.PB(v);
        vst[v]++;
    }
    reverse(ALL(edgeID));
    edgeID.resize(SZ(cycle));
    return mmc;
}
} mmc;

```

### 5.13 Graph Hash

$$F_t(i) = (F_{t-1}(i) \times A + \sum_{i \rightarrow j} F_{t-1}(j) \times B + \sum_{j \rightarrow i} F_{t-1}(j) \times C + D \times (i = a)) \bmod P$$

for each node  $i$ , iterate  $t$  times.  $t, A, B, C, D, P$  are hash parameter

## 6 String

### 6.1 PalTree

```

/*
 * sfail: compressed fail links with same diff
 * 0(lgn): length of sfail link path
 */
const int MAXN = 1e6+10;
struct PalT{
    int tot,lst;
    int nxt[MAXN][26], len[MAXN];
    int fail[MAXN], diff[MAXN], sfail[MAXN];
    char* s;
    int newNode(int l, int _fail) {
        int res = ++tot;
        fill(nxt[res], nxt[res]+26, 0);
        len[res] = l, fail[res] = _fail;
        diff[res] = l - len[_fail];
        if (diff[res] == diff[_fail]) {
            sfail[res] = sfail[_fail];
        } else {
            sfail[res] = _fail;
        }
        return res;
    }
    void push(int p) {
        int np = lst;
        int c = s[p]-'a';
        while (p-len[np]-1 < 0 || s[p] != s[p-len[np]-1])
            np = fail[np];
        if ((lst=nxt[np][c])) {
            return;
        }
        int nq_f = 0;
        if (len[np]+2 == 1) {
            nq_f = 2;
        } else {

```

```

            int tf = fail[np];
            while (p-len[tf]-1 < 0 || s[p] != s[p-len[tf]-1])
                tf = fail[tf];
            nq_f = nxt[tf][c];
        }
        int nq = newNode(len[np]+2, nq_f);
        nxt[np][c] = nq;
        lst=nq;
    }
    void init(char* _s){
        s = _s;
        tot = 0;
        newNode(-1, 1);
        newNode(0, 1);
        diff[2] = 0;
        lst = 2;
    }
} palt;

```

### 6.2 SAIS

```

const int N = 300010;
struct SA{
#define REP(i,n) for ( int i=0; i<int(n); i++ )
#define REP1(i,a,b) for ( int i=(a); i<=int(b); i++ )
    bool _t[N*2];
    int _s[N*2], _sa[N*2], _c[N*2], x[N], _p[N], _q[N*2],
        hei[N], r[N];
    int operator [] (int i){ return _sa[i]; }
    void build(int *s, int n, int m){
        memcpy(_s, s, sizeof(int) * n);
        sais(_s, _sa, _p, _q, _t, _c, n, m);
        mkhei(n);
    }
    void mkhei(int n){
        REP(i,n) r[_sa[i]] = i;
        hei[0] = 0;
        REP(i,n) if(r[i]) {
            int ans = i>0 ? max(hei[r[i-1]] - 1, 0) : 0;
            while(_s[i+ans] == _s[_sa[r[i]-1]+ans]) ans++;
            hei[r[i]] = ans;
        }
    }
    void sais(int *s, int *sa, int *p, int *q, bool *t,
        int *c, int n, int z){
        bool uniq = t[n-1] = true, neq;
        int nn = 0, nmzx = -1, *nsa = sa + n, *ns = s + n,
            lst = -1;
#define MS0(x,n) memset((x),0,n*sizeof(*(x)))
#define MAGIC(XD) MS0(sa, n); \
        memcpy(x, c, sizeof(int) * z); \
        XD; \
        memcpy(x + 1, c, sizeof(int) * (z - 1)); \
        REP(i,n) if(sa[i] && !t[sa[i]-1]) sa[x[sa[i]-1]++] = sa[i]-1; \
        memcpy(x, c, sizeof(int) * z); \
        for(int i = n - 1; i >= 0; i--) if(sa[i] && t[sa[i]-1]) sa[--x[sa[i]-1]] = sa[i]-1;
        MS0(c, z);
        REP(i,n) uniq &= ++c[s[i]] < 2;
        REP(i,z-1) c[i+1] += c[i];
        if (uniq) { REP(i,n) sa[--c[s[i]]] = i; return; }
        for(int i = n - 2; i >= 0; i--) t[i] = (s[i]==s[i+1] ? t[i+1] : s[i]<s[i+1]);
        MAGIC(REP1(i,1,n-1) if(t[i] && !t[i-1]) sa[--x[s[i]]]=p[q[i]=nn++]=i);
        REP(i, n) if (sa[i] && t[sa[i]] && !t[sa[i]-1]) {
            neq=lst<0||memcmp(s+sa[i],s+lst,(p[q[sa[i]]+1]-sa[i])*sizeof(int));
            ns[q[lst=sa[i]]]=nmzx+=neq;
        }
        sais(ns, nsa, p + nn, q + n, t + n, c + z, nn, nmzx + 1);
        MAGIC(for(int i = nn - 1; i >= 0; i--) sa[--x[s[p[nsa[i]]]]] = p[nsa[i]]);
    }
}sa;
int H[ N ], SA[ N ];
void suffix_array(int* ip, int len) {
    // should padding a zero in the back

```

```
// ip is int array, len is array length
// ip[0..n-1] != 0, and ip[len] = 0
ip[len++] = 0;
sa.build(ip, len, 128);
for (int i=0; i<len; i++) {
    H[i] = sa.hei[i + 1];
    SA[i] = sa._sa[i + 1];
}
// resulting height, sa array \in [0,len)
}
```

### 6.3 SuffixAutomata

```
const int MAXM = 1000010;
struct SAM{
    int tot, root, lst, mom[MAXM], mx[MAXM];
    int acc[MAXM], nxt[MAXM][33];
    int newNode(){
        int res = ++tot;
        fill(nxt[res], nxt[res]+33, 0);
        mom[res] = mx[res] = acc[res] = 0;
        return res;
    }
    void init(){
        tot = 0;
        root = newNode();
        mom[root] = 0, mx[root] = 0;
        lst = root;
    }
    void push(int c){
        int p = lst;
        int np = newNode();
        mx[np] = mx[p]+1;
        for(; p && nxt[p][c] == 0; p = mom[p])
            nxt[p][c] = np;
        if(p == 0) mom[np] = root;
        else{
            int q = nxt[p][c];
            if(mx[p]+1 == mx[q]) mom[np] = q;
            else{
                int nq = newNode();
                mx[nq] = mx[p]+1;
                for(int i = 0; i < 33; i++)
                    nxt[nq][i] = nxt[q][i];
                mom[nq] = mom[q];
                mom[q] = nq;
                mom[np] = nq;
                for(; p && nxt[p][c] == q; p = mom[p])
                    nxt[p][c] = nq;
            }
        }
        lst = np;
    }
    void push(char *str){
        for(int i = 0; i < strlen(str); i++)
            push(str[i] - 'a' + 1);
    }
} sam;
```

### 6.4 Aho-Corasick

```
struct ACautomata{
    struct Node{
        int cnt, dp;
        Node *go[26], *fail;
        Node(){
            cnt = 0; dp = -1; fail = 0;
            memset(go, 0, sizeof(go));
        }
    };
    Node *root, pool[1048576];
    int nMem;
    Node* new_Node(){
        pool[nMem] = Node();
        return &pool[nMem++];
    }
    void init()
    { nMem = 0; root = new_Node(); }
```

```
void add(const string &str)
{ insert(root, str, 0); }
void insert(Node *cur, const string &str, int pos){
    if (pos >= (int)str.size())
        { cur->cnt++; return; }
    int c = str[pos] - 'a';
    if (cur->go[c] == 0)
        cur->go[c] = new_Node();
    insert(cur->go[c], str, pos+1);
}
void make_fail(){
    queue<Node*> que;
    que.push(root);
    while (!que.empty()){
        Node* fr=que.front();
        que.pop();
        for (int i=0; i<26; i++){
            if (fr->go[i]){
                Node *ptr = fr->fail;
                while (ptr && !ptr->go[i]) ptr = ptr->fail;
                if (!ptr) fr->go[i]->fail = root;
                else fr->go[i]->fail = ptr->go[i];
                que.push(fr->go[i]);
            }
        }
    }
};
```

### 6.5 Z Value

```
char s[MAXN];
int len, z[MAXN];
void Z_value() {
    int i, j, left, right;
    left=right=0; z[0]=len;
    for(i=1; i<len; i++){
        j=max(min(z[i-left], right-i), 0);
        for(; i+j<len && s[i+j]==s[j]; j++);
        z[i]=j;
        if(i+z[i]>right) {
            right=i+z[i];
            left=i;
        }
    }
}
```

### 6.6 BWT

```
struct BurrowsWheeler{
#define SIGMA 26
#define BASE 'a'
    vector<int> v[ SIGMA ];
    void BWT(char* ori, char* res){
        // make ori -> ori + ori
        // then build suffix array
    }
    void iBWT(char* ori, char* res){
        for( int i = 0 ; i < SIGMA ; i ++ )
            v[ i ].clear();
        int len = strlen( ori );
        for( int i = 0 ; i < len ; i ++ )
            v[ ori[i] - BASE ].push_back( i );
        vector<int> a;
        for( int i = 0 , ptr = 0 ; i < SIGMA ; i ++ )
            for( auto j : v[ i ] ){
                a.push_back( j );
                ori[ ptr ++ ] = BASE + i;
            }
        for( int i = 0 , ptr = 0 ; i < len ; i ++ ){
            res[ i ] = ori[ a[ ptr ] ];
            ptr = a[ ptr ];
        }
        res[ len ] = 0;
    }
} bwt;
```

## 6.7 ZValue Palindrome

```
int len, zv[MAX*2];
char ip[MAX], op[MAX*2];
int main(){
    cin >> ip; len = strlen(ip);
    int l2 = len*2 - 1;
    for(int i=0; i<l2; i++)
        if(i&1) op[i] = '@';
        else op[i] = ip[i/2];
    int l=0, r=0; zv[0] = 1;
    for(int i=1; i<l2; i++){
        if( i > r ){
            l = r = i;
            while( l>0 && r<l2-1 && op[l-1] == op[r+1] )
                l --, r ++;
            zv[i] = (r-l+1);
        }else{
            int md = (l+r)/2, j = md + md - i;
            zv[i] = zv[j];
            int q = zv[i] / 2, nr = i + q;
            if( nr == r ){
                l = i + i - r;
                while( l>0 && r<l2-1 && op[l-1] == op[r+1] )
                    l --, r ++;
                zv[i] = r - l + 1;
            }else if( nr > r ){
                zv[i] = (r - i) * 2 + 1;
            }
        }
    }
}
```

## 6.8 Smallest Rotation

```
string mcp(string s){
    int n = s.length();
    s += s;
    int i=0, j=1;
    while (i<n && j<n){
        int k = 0;
        while (k < n && s[i+k] == s[j+k]) k++;
        if (s[i+k] <= s[j+k]) j += k+1;
        else i += k+1;
        if (i == j) j++;
    }
    int ans = i < n ? i : j;
    return s.substr(ans, n);
}
```

## 6.9 Cyclic LCS

```
#define L 0
#define LU 1
#define U 2
const int mov[3][2]={0,-1, -1,-1, -1,0};
int al,bl;
char a[MAXL*2],b[MAXL*2]; // 0-indexed
int dp[MAXL*2][MAXL];
char pred[MAXL*2][MAXL];
inline int lcs_length(int r) {
    int i=r+al,j=bl,l=0;
    while(i>r) {
        char dir=pred[i][j];
        if(dir==LU) l++;
        i+=mov[dir][0];
        j+=mov[dir][1];
    }
    return l;
}
inline void reroot(int r) { // r = new base row
    int i=r,j=1;
    while(j<=bl&&pred[i][j]!=LU) j++;
    if(j>bl) return;
    pred[i][j]=L;
    while(i<2*al&&j<=bl) {
        if(pred[i+1][j]==U) {
            i++;

```

```
        pred[i][j]=L;
    } else if(j<bl&&pred[i+1][j+1]==LU) {
        i++;
        j++;
        pred[i][j]=L;
    } else {
        j++;
    }
}
int cyclic_lcs() {
    // a, b, al, bl should be properly filled
    // note: a WILL be altered in process
    // -- concatenated after itself
    char tmp[MAXL];
    if(al>bl) {
        swap(al,bl);
        strcpy(tmp,a);
        strcpy(a,b);
        strcpy(b,tmp);
    }
    strcpy(tmp,a);
    strcat(a,tmp);
    // basic lcs
    for(int i=0;i<=2*al;i++) {
        dp[i][0]=0;
        pred[i][0]=U;
    }
    for(int j=0;j<=bl;j++) {
        dp[0][j]=0;
        pred[0][j]=L;
    }
    for(int i=1;i<=2*al;i++) {
        for(int j=1;j<=bl;j++) {
            if(a[i-1]==b[j-1]) dp[i][j]=dp[i-1][j-1]+1;
            else dp[i][j]=max(dp[i-1][j],dp[i][j-1]);
            if(dp[i][j-1]==dp[i][j]) pred[i][j]=L;
            else if(a[i-1]==b[j-1]) pred[i][j]=LU;
            else pred[i][j]=U;
        }
    }
    // do cyclic lcs
    int clcs=0;
    for(int i=0;i<al;i++) {
        clcs=max(clcs,lcs_length(i));
        reroot(i+1);
    }
    // recover a
    a[al]='\0';
    return clcs;
}
```

## 7 Data Structure

### 7.1 Treap

```
struct Treap{
    int sz, val, pri, tag;
    Treap *l, *r;
    Treap( int _val ){
        val = _val; sz = 1;
        pri = rand(); l = r = NULL; tag = 0;
    }
};
void push( Treap * a ){
    if( a->tag ){
        Treap *swp = a->l; a->l = a->r; a->r = swp;
        int swp2;
        if( a->l ) a->l->tag ^= 1;
        if( a->r ) a->r->tag ^= 1;
        a->tag = 0;
    }
}
int Size( Treap * a ){ return a ? a->sz : 0; }
void pull( Treap * a ){
    a->sz = Size( a->l ) + Size( a->r ) + 1;
}
Treap* merge( Treap *a, Treap *b ){

```

```

if( !a || !b ) return a ? a : b;
if( a->pri > b->pri ){
    push( a );
    a->r = merge( a->r , b );
    pull( a );
    return a;
}else{
    push( b );
    b->l = merge( a , b->l );
    pull( b );
    return b;
}
}
void split( Treap *t , int k , Treap*&a , Treap*&b ){
    if( !t ){ a = b = NULL; return; }
    push( t );
    if( Size( t->l ) + 1 <= k ){
        a = t;
        split( t->r , k - Size( t->l ) - 1 , a->r , b );
        pull( a );
    }else{
        b = t;
        split( t->l , k , a , b->l );
        pull( b );
    }
}
}

```

## 7.2 Link-Cut Tree

```

const int MXN = 100005;
const int MEM = 100005;
struct Splay {
    static Splay nil, mem[MEM], *pmem;
    Splay *ch[2], *f;
    int val, rev, size;
    Splay (int _val=-1) : val(_val), rev(0), size(1)
    { f = ch[0] = ch[1] = &nil; }
    bool isr()
    { return f->ch[0] != this && f->ch[1] != this; }
    int dir()
    { return f->ch[0] == this ? 0 : 1; }
    void setCh(Splay *c, int d){
        ch[d] = c;
        if (c != &nil) c->f = this;
        pull();
    }
    void push(){
        if( !rev ) return;
        swap(ch[0], ch[1]);
        if (ch[0] != &nil) ch[0]->rev ^= 1;
        if (ch[1] != &nil) ch[1]->rev ^= 1;
        rev=0;
    }
    void pull(){
        size = ch[0]->size + ch[1]->size + 1;
        if (ch[0] != &nil) ch[0]->f = this;
        if (ch[1] != &nil) ch[1]->f = this;
    }
} Splay::nil, Splay::mem[MEM], *Splay::pmem = Splay::
mem;
Splay *nil = &Splay::nil;
void rotate(Splay *x){
    Splay *p = x->f;
    int d = x->dir();
    if (!p->isr()) p->f->setCh(x, p->dir());
    else x->f = p->f;
    p->setCh(x->ch[d], d);
    x->setCh(p, !d);
    p->pull(); x->pull();
}
vector<Splay*> splayVec;
void splay(Splay *x){
    splayVec.clear();
    for (Splay *q=x; q=q->f){
        splayVec.push_back(q);
        if (q->isr()) break;
    }
    reverse(begin(splayVec), end(splayVec));
    for (auto it : splayVec) it->push();
    while (!x->isr()) {

```

```

        if (x->f->isr()) rotate(x);
        else if (x->dir()==x->f->dir())
            rotate(x->f), rotate(x);
        else rotate(x), rotate(x);
    }
}
int id(Splay *x) { return x - Splay::mem + 1; }
Splay* access(Splay *x){
    Splay *q = nil;
    for (;x!=nil;x=x->f){
        splay(x);
        x->setCh(q, 1);
        q = x;
    }
    return q;
}
void chroot(Splay *x){
    access(x);
    splay(x);
    x->rev ^= 1;
    x->push(); x->pull();
}
void link(Splay *x, Splay *y){
    access(x);
    splay(x);
    chroot(y);
    x->setCh(y, 1);
}
void cut_p(Splay *y) {
    access(y);
    splay(y);
    y->push();
    y->ch[0] = y->ch[0]->f = nil;
}
void cut(Splay *x, Splay *y){
    chroot(x);
    cut_p(y);
}
Splay* get_root(Splay *x) {
    access(x);
    splay(x);
    for(; x->ch[0] != nil; x = x->ch[0])
        x->push();
    splay(x);
    return x;
}
bool conn(Splay *x, Splay *y) {
    x = get_root(x);
    y = get_root(y);
    return x == y;
}
Splay* lca(Splay *x, Splay *y) {
    access(x);
    access(y);
    splay(x);
    if (x->f == nil) return x;
    else return x->f;
}
}

```

## 7.3 Black Magic

```

#include <bits/extc++.h>
using namespace __gnu_pbds;
typedef tree<int,null_type,less<int>,rb_tree_tag,
    tree_order_statistics_node_update> set_t;
#include <ext/pb_ds/assoc_container.hpp>
typedef cc_hash_table<int,int> umap_t;
typedef priority_queue<int> heap;
#include<ext/rope>
using namespace __gnu_cxx;
int main(){
    // Insert some entries into s.
    set_t s; s.insert(12); s.insert(505);
    // The order of the keys should be: 12, 505.
    assert(*s.find_by_order(0) == 12);
    assert(*s.find_by_order(3) == 505);
    // The order of the keys should be: 12, 505.
    assert(s.order_of_key(12) == 0);
    assert(s.order_of_key(505) == 1);
    // Erase an entry.

```

```

s.erase(12);
// The order of the keys should be: 505.
assert(*s.find_by_order(0) == 505);
// The order of the keys should be: 505.
assert(s.order_of_key(505) == 0);

heap h1 , h2; h1.join( h2 );

rope<char> r[ 2 ];
r[ 1 ] = r[ 0 ]; // persistenet
string t = "abc";
r[ 1 ].insert( 0 , t.c_str() );
r[ 1 ].erase( 1 , 1 );
cout << r[ 1 ].substr( 0 , 2 );
}

```

## 8 Others

### 8.1 Find max tangent(x,y is increasing)

```

typedef long long LL;
const int MAXN = 100010;
struct Coord{
    LL x, y;
    Coord operator - (Coord ag) const{
        Coord res;
        res.x = x - ag.x;
        res.y = y - ag.y;
        return res;
    }
}sum[MAXN], pnt[MAXN], ans, calc;

inline bool cross(Coord a, Coord b, Coord c){
    return (c.y-a.y)*(c.x-b.x) > (c.x-a.x)*(c.y-b.y);
}

int main(){
    int n, l, np, st, ed, now;
    scanf("%d %d\n", &n, &l);
    sum[0].x = sum[0].y = np = st = ed = 0;
    for (int i = 1, v; i <= n; i++){
        scanf("%d", &v);
        sum[i].y = sum[i - 1].y + v;
        sum[i].x = i;
    }
    ans.x = now = 1;
    ans.y = -1;
    for (int i = 0; i <= n - 1; i++){
        while (np > 1 &&
            cross(pnt[np - 2], pnt[np - 1], sum[i]))
            np--;
        if (np < now && np != 0) now = np;
        pnt[np++] = sum[i];
        while (now < np &&
            !cross(pnt[now - 1], pnt[now], sum[i + 1]))
            now++;
        calc = sum[i + 1] - pnt[now - 1];
        if (ans.y * calc.x < ans.x * calc.y){
            ans = calc;
            st = pnt[now - 1].x;
            ed = i + 1;
        }
    }
    double res = (sum[ed].y - sum[st].y) /
        (sum[ed].x - sum[st].x);
    printf("%f\n", res);
    return 0;
}

```