

Contents

1 Basic	1
1.1 .vimrc	1
1.2 Increase Stack Size	1
1.3 Misc	1
2 flow	1
2.1 ISAP	1
2.2 MinCostFlow	2
2.3 Hungarian	2
2.4 Hungarian Unbalanced	3
2.5 DMST	3
2.6 SW min-cut	4
2.7 Max Cost Circulation	4
2.8 Max flow with lower/upper bound	4
2.9 Flow Method	5
3 Math	5
3.1 FFT	5
3.2 NTT	5
3.3 Fast Walsh Transform	6
3.4 BigInt	6
3.5 Linear Recurrence	7
3.6 Miller Rabin	7
3.7 Simplex	8
3.8 Faulhaber	8
3.9 Chinese Remainder	8
3.10 Pollard Rho	9
3.11 Poly Generator	9
3.12 Matrix Pseudo Inverse	9
3.13 $ax+by=gcd$	9
3.14 Discrete sqrt	9
3.15 SchreierSims	10
3.16 Discrete K-th sqrt	10
3.17 Prefix Inverse	11
3.18 Roots of Polynomial	11
3.19 Mod	11
3.20 Primes and μ function	11
3.21 Result	12
4 Geometry	12
4.1 halfPlaneIntersection	12
4.2 Intersection of 2 lines	12
4.3 Intersection of 2 segments	12
4.4 Intersection of polygon and circle	12
4.5 Intersection of 2 circles	13
4.6 Circle cover	13
4.7 Convex Hull trick	13
4.8 KD Tree	14
4.9 Lower Concave Hull	14
4.10 Delaunay Triangulation	15
4.11 Min Enclosing Circle	16
4.12 Min Enclosing Ball	16
4.13 Minkowski sum	17
4.14 Heart of Triangle	17
5 Graph	17
5.1 HeavyLightDecomp	17
5.2 DominatorTree	18
5.3 MaxClique	19
5.4 Number of Maximal Clique	19
5.5 Strongly Connected Component	19
5.6 Dynamic MST	19
5.7 Minimum General Weighted Matching	20
5.8 Minimum Steiner Tree	20
5.9 BCC based on vertex	21
5.10 Graph Hash	21
6 String	21
6.1 PalTree	21
6.2 SuffixArray	22
6.3 SAIS	22
6.4 SuffixAutomata	22
6.5 Aho-Corasick	23
6.6 Z Value	23
6.7 ZValue Palindrome	23
6.8 Smallest Rotation	23
7 Data Structure	23
7.1 Treap	23
7.2 Link-Cut Tree	24
7.3 Disjoint Set	25
7.4 Leftist Heap	25
7.5 Black Magic	25
8 Others	25
8.1 Exact Cover Set	25

1 Basic

1.1 .vimrc

```
syn on
se ai nu ru cul mouse=a
se cin et ts=2 sw=2 sts=2
so $VIMRUNTIME/mswin.vim
colo desert
se gfn=Monospace\ 14
```

1.2 Increase Stack Size

```
//stack resize
asm( "mov %0,%esp\n" ::"g"(mem+10000000) );
//change esp to rsp if 64-bit system

//stack resize (linux)
#include <sys/resource.h>
void increase_stack_size() {
    const rlim_t ks = 64*1024*1024;
    struct rlimit rl;
    int res=getrlimit(RLIMIT_STACK, &rl);
    if(res==0){
        if(rl.rlim_cur<ks){
            rl.rlim_cur=ks;
            res=setrlimit(RLIMIT_STACK, &rl);
        }
    }
}
```

1.3 Misc

```
#include <random>
mt19937 rng(0x5EED);
int randint(int lb, int ub)
{ return uniform_int_distribution<int>(lb, ub)(rng); }

#define SECS (clock() / CLOCKS_PER_SEC)

struct KeyHasher {
    size_t operator()(const Key& k) const {
        return k.first + k.second * 100000;
    }
};
typedef unordered_map<Key,int,KeyHasher> map_t;
```

2 flow

2.1 ISAP

```
#define SZ(c) ((int)(c).size())
struct Maxflow {
    static const int MAXV = 20010;
    static const int INF = 1000000;
    struct Edge {
        int v, c, r;
        Edge(int _v, int _c, int _r):
            v(_v), c(_c), r(_r) {}
    };
    int s, t;
    vector<Edge> G[MAXV*2];
    int iter[MAXV*2], d[MAXV*2], gap[MAXV*2], tot;
    void flowinit(int x) {
        tot = x+2;
        s = x+1, t = x+2;
        for(int i = 0; i <= tot; i++) {
            G[i].clear();
            iter[i] = d[i] = gap[i] = 0;
        }
    }
    void addEdge(int u, int v, int c) {
```

```

    G[u].push_back(Edge(v, c, SZ(G[v]) ));
    G[v].push_back(Edge(u, 0, SZ(G[u]) - 1));
}
int dfs(int p, int flow) {
    if(p == t) return flow;
    for(int &i = iter[p]; i < SZ(G[p]); i++) {
        Edge &e = G[p][i];
        if(e.c > 0 && d[p] == d[e.v]+1) {
            int f = dfs(e.v, min(flow, e.c));
            if(f) {
                e.c -= f;
                G[e.v][e.r].c += f;
                return f;
            }
        }
    }
    if( (--gap[d[p]]) == 0) d[s] = tot;
    else {
        d[p]++;
        iter[p] = 0;
        ++gap[d[p]];
    }
    return 0;
}
int maxflow() {
    //puts("MF");
    int res = 0;
    gap[0] = tot;
    for(res = 0; d[s] < tot; res += dfs(s, INF));
    return res;
}
} flow;
MaxFlow::Edge e(1, 1, 1);

```

2.2 MinCostFlow

```

/*
    A template for Min Cost Max Flow
    tested with TIOJ 1724
*/
struct MinCostMaxFlow{
    static const int MAXV = 20010;
    static const int INF = 1000000000;
    struct Edge{
        int v, cap, w, rev;
        Edge(){}
        Edge(int t2, int t3, int t4, int t5)
            : v(t2), cap(t3), w(t4), rev(t5) {}
    };
    int V, s, t;
    vector<Edge> g[MAXV];
    void init(int n){
        V = n+2;
        s = n+1, t = n+2;
        for(int i = 1; i <= V; i++) g[i].clear();
    }
    void addEdge(int a, int b, int cap, int w){
        g[a].push_back(Edge(b, cap, w, (int)g[b].size()));
        g[b].push_back(Edge(a, 0, -w, (int)g[a].size()-1));
    }
    int d[MAXV], id[MAXV], mom[MAXV];
    bool inqu[MAXV];
    int qu[2000000], ql, qr;
    //the size of qu should be much large than MAXV
    int mncmxf(){
        int mxf = 0, mnc = 0;
        while(1){
            fill(d+1, d+1+V, INF);
            fill(inqu+1, inqu+1+V, 0);
            fill(mom+1, mom+1+V, -1);
            mom[s] = s;
            d[s] = 0;
            ql = 1, qr = 0;
            qu[++qr] = s;
            inqu[s] = 1;
            while(ql <= qr){
                int u = qu[ql++];
                inqu[u] = 0;
                for(int i = 0; i < (int) g[u].size(); i++){
                    Edge &e = g[u][i];

```

```

                    int v = e.v;
                    if(e.cap > 0 && d[v] > d[u]+e.w){
                        d[v] = d[u]+e.w;
                        mom[v] = u;
                        id[v] = i;
                        if(!inqu[v]) qu[++qr] = v, inqu[v] = 1;
                    }
                }
            }
            if(mom[t] == -1) break;
            int df = INF;
            for(int u = t; u != s; u = mom[u])
                df = min(df, g[mom[u]][id[u]].cap);
            for(int u = t; u != s; u = mom[u]){
                Edge &e = g[mom[u]][id[u]];
                e.cap -= df;
                g[e.v][e.rev].cap += df;
            }
            mxf += df;
            mnc += df*d[t];
        }
        return mnc;
    }
} flow;

```

2.3 Hungarian

```

#define NIL -1
#define INF 100000000
int n, matched;
int cost[MAXN][MAXN];
bool sets[MAXN]; // whether x is in set S
bool sett[MAXN]; // whether y is in set T
int xlabel[MAXN], ylabel[MAXN];
int xy[MAXN], yx[MAXN]; // matched with whom
int slack[MAXN]; // given y: min{xlabel[x]+ylabel[y]-cost[x][y]} | x not in S
int prev[MAXN]; // for augmenting matching
inline void relabel() {
    int i, delta=INF;
    for(i=0; i<n; i++) if(!sett[i]) delta=min(slack[i], delta);
    for(i=0; i<n; i++) if(sets[i]) xlabel[i]-=delta;
    for(i=0; i<n; i++) {
        if(sett[i]) ylabel[i]+=delta;
        else slack[i]-=delta;
    }
}
inline void add_sets(int x) {
    int i;
    sets[x]=1;
    for(i=0; i<n; i++) {
        if(xlabel[x]+ylabel[i]-cost[x][i]<slack[i]) {
            slack[i]=xlabel[x]+ylabel[i]-cost[x][i];
            prev[i]=x;
        }
    }
}
inline void augment(int final) {
    int x=prev[final], y=final, tmp;
    matched++;
    while(1) {
        tmp=xy[x]; xy[x]=y; yx[y]=x; y=tmp;
        if(y==NIL) return;
        x=prev[y];
    }
}
inline void phase() {
    int i, y, root;
    for(i=0; i<n; i++) { sets[i]=sett[i]=0; slack[i]=INF; }
    for(root=0; root<n&&xy[root]!=NIL; root++);
    add_sets(root);
    while(1) {
        relabel();
        for(y=0; y<n; y++) if(!sett[y]&&slack[y]==0) break;
        if(yx[y]==NIL) { augment(y); return; }
        else { add_sets(yx[y]); sett[y]=1; }
    }
}
inline int hungarian() {

```

```

int i,j,c=0;
for(i=0;i<n;i++) {
    xy[i]=yx[i]=NIL;
    xlabel[i]=ylabel[i]=0;
    for(j=0;j<n;j++) xlabel[i]=max(cost[i][j],xlabel[i]
    });
}
for(i=0;i<n;i++) phase();
for(i=0;i<n;i++) c+=cost[i][xy[i]];
return c;
}

```

2.4 Hungarian Unbalanced

```

const int nil = -1;
const int inf = 1000000000;
int xn,yn,matched;
int cost[MAXN][MAXN];
bool sets[MAXN]; // whether x is in set S
bool sett[MAXN]; // whether y is in set T
int xlabel[MAXN],ylabel[MAXN];
int xy[MAXN],yx[MAXN]; // matched with whom
int slack[MAXN]; // given y: min{xlabel[x]+ylabel[y]-
cost[x][y]} | x not in S
int prev[MAXN]; // for augmenting matching
inline void relabel() {
    int i,delta=inf;
    for(i=0;i<yn;i++) if(!sett[i]) delta=min(slack[i],
    delta);
    for(i=0;i<xn;i++) if(sets[i]) xlabel[i]-=delta;
    for(i=0;i<yn;i++) {
        if(sett[i]) ylabel[i]+=delta;
        else slack[i]-=delta;
    }
}
inline void add_sets(int x) {
    int i;
    sets[x]=1;
    for(i=0;i<yn;i++) {
        if(xlabel[x]+ylabel[i]-cost[x][i]<slack[i]) {
            slack[i]=xlabel[x]+ylabel[i]-cost[x][i];
            prev[i]=x;
        }
    }
}
inline void augment(int final) {
    int x=prev[final],y=final,tmp;
    matched++;
    while(1) {
        tmp=xy[x]; xy[x]=y; yx[y]=x; y=tmp;
        if(y==nil) return;
        x=prev[y];
    }
}
inline void phase() {
    int i,y,root;
    for(i=0;i<xn;i++) sets[i]=0;
    for(i=0;i<yn;i++) { sett[i]=0; slack[i]=inf; }
    for(root=0;root<xn&&xy[root]!=nil;root++);
    add_sets(root);
    while(1) {
        relabel();
        for(y=0;y<yn;y++) if(!sett[y]&&slack[y]==0) break;
        if(yx[y]==nil) { augment(y); return; }
        else { add_sets(yx[y]); sett[y]=1; }
    }
}
inline int hungarian() {
    int i,j,c=0;
    matched=0;
    // we must have "xn<yn"
    bool swapxy=0;
    if(xn>yn) {
        swapxy=1;
        int mn=max(xn,yn);
        swap(xn,yn);
        for(int i=0;i<mn;i++)
            for(int j=0;j<i;j++)
                swap(cost[i][j],cost[j][i]);
    }
}

```

```

for(i=0;i<xn;i++) {
    xy[i]=nil;
    xlabel[i]=0;
    for(j=0;j<yn;j++) xlabel[i]=max(cost[i][j],xlabel[i]
    });
}
for(i=0;i<yn;i++) {
    yx[i]=nil;
    ylabel[i]=0;
}
for(i=0;i<xn;i++) phase();
for(i=0;i<xn;i++) c+=cost[i][xy[i]];
// recover cost matrix (if necessary)
if(swapxy) {
    int mn=max(xn,yn);
    swap(xn,yn);
    for(int i=0;i<mn;i++)
        for(int j=0;j<i;j++)
            swap(cost[i][j],cost[j][i]);
}
// need special recovery if we want more info than
// matching value
return c;
}

```

2.5 DMST

```

/*
 * Edmond's algoirthm for Directed MST
 * runs in O(VE)
 */
const int MAXV = 10010;
const int MAXE = 10010;
const int INF = 2147483647;
struct Edge{
    int u, v, c;
    Edge(){}
    Edge(int x, int y, int z) :
        u(x), v(y), c(z){}
};
int V, E, root;
Edge edges[MAXE];
inline int newV(){
    V++;
    return V;
}
inline void addEdge(int u, int v, int c){
    E++;
    edges[E] = Edge(u, v, c);
}
bool con[MAXV];
int mnInW[MAXV], prv[MAXV], cyc[MAXV], vis[MAXV];
inline int DMST(){
    fill(con, con+V+1, 0);
    int r1 = 0, r2 = 0;
    while(1){
        fill(mnInW, mnInW+V+1, INF);
        fill(prv, prv+V+1, -1);
        REP(i, 1, E){
            int u=edges[i].u, v=edges[i].v, c=edges[i].c;
            if(u != v && v != root && c < mnInW[v])
                mnInW[v] = c, prv[v] = u;
        }
        fill(vis, vis+V+1, -1);
        fill(cyc, cyc+V+1, -1);
        r1 = 0;
        bool jf = 0;
        REP(i, 1, V){
            if(con[i]) continue;
            if(prv[i] == -1 && i != root) return -1;
            if(prv[i] > 0) r1 += mnInW[i];
            int s;
            for(s = i; s != -1 && vis[s] == -1; s = prv[s])
                vis[s] = i;
            if(s > 0 && vis[s] == i){
                // get a cycle
                jf = 1;
                int v = s;
                do{
                    cyc[v] = s, con[v] = 1;

```

```

        r2 += mnInW[v];
        v = prv[v];
    }while(v != s);
    con[s] = 0;
}
}
if(!jf) break ;
REP(i, 1, E){
    int &u = edges[i].u;
    int &v = edges[i].v;
    if(cyc[v] > 0) edges[i].c -= mnInW[edges[i].v];
    if(cyc[u] > 0) edges[i].u = cyc[edges[i].u];
    if(cyc[v] > 0) edges[i].v = cyc[edges[i].v];
    if(u == v) edges[i--] = edges[E--];
}
}
return r1+r2;
}

```

2.6 SW min-cut

```

// global min cut
struct SW{ // O(V^3)
    static const int MXN = 514;
    int n,vst[MXN],del[MXN];
    int edge[MXN][MXN],wei[MXN];
    void init(int _n){
        n = _n;
        FZ(edge);
        FZ(del);
    }
    void add_edge(int u, int v, int w){
        edge[u][v] += w;
        edge[v][u] += w;
    }
    void search(int &s, int &t){
        FZ(vst); FZ(wei);
        s = t = -1;
        while (true){
            int mx=-1, cur=0;
            for (int i=0; i<n; i++){
                if (!del[i] && !vst[i] && mx<wei[i])
                    cur = i, mx = wei[i];
            }
            if (mx == -1) break;
            vst[cur] = 1;
            s = t;
            t = cur;
            for (int i=0; i<n; i++){
                if (!vst[i] && !del[i]) wei[i] += edge[cur][i];
            }
        }
    }
    int solve(){
        int res = 2147483647;
        for (int i=0,x,y; i<n-1; i++){
            search(x,y);
            res = min(res,wei[y]);
            del[y] = 1;
            for (int j=0; j<n; j++){
                edge[x][j] = (edge[j][x] += edge[y][j]);
            }
        }
        return res;
    }
}graph;

```

2.7 Max Cost Circulation

```

struct MaxCostCirc {
    static const int MAXN = 33;
    int n, m;
    struct Edge {
        int v, w, c, r;
    };
    vector<Edge> g[ MAXN ];
    int dis[ MAXN ], prv[ MAXN ], prve[ MAXN ];
    bool vis[ MAXN ];
    int ans;
    void init( int _n, int _m ) : n(_n), m(_m) {}
    void adde( int u, int v, int w, int c ) {

```

```

        g[ u ].push_back( { v, w, c, SZ( g[ v ] ) } );
        g[ v ].push_back( { u, -w, 0, SZ( g[ u ] )-1 } );
    }
    bool poscyc() {
        fill( dis, dis+n+1, 0 );
        fill( prv, prv+n+1, 0 );
        fill( vis, vis+n+1, 0 );
        int tmp = -1;
        FOR( t, n+1 ) {
            REP( i, 1, n ) {
                FOR( j, SZ( g[ i ] ) ) {
                    Edge& e = g[ i ][ j ];
                    if( e.c && dis[ e.v ] < dis[ i ]+e.w ) {
                        dis[ e.v ] = dis[ i ]+e.w;
                        prv[ e.v ] = i;
                        prve[ e.v ] = j;
                        if( t == n ) {
                            tmp = i;
                            break;
                        }
                    }
                }
            }
        }
        if( tmp == -1 ) return 0;
        int cur = tmp;
        while( !vis[ cur ] ) {
            vis[ cur ] = 1;
            cur = prv[ cur ];
        }
        int now = cur;
        int cost = 0, df = 100000;
        do{
            Edge &e = g[ prv[ now ] ][ prve[ now ] ];
            df = min( df, e.c );
            cost += e.w;
            now = prv[ now ];
        }while( now != cur );
        ans += df*cost;
        now = cur;
        do{
            Edge &e = g[ prv[ now ] ][ prve[ now ] ];
            Edge &re = g[ now ][ e.r ];
            e.c -= df;
            re.c += df;
            now = prv[ now ];
        }while( now != cur );
        return 1;
    }
} circ;

```

2.8 Max flow with lower/upper bound

```

// Max flow with lower/upper bound on edges
// source = 1, sink = n
int in[ N ], out[ N ];
int l[ M ], r[ M ], a[ M ], b[ M ];
int solve(){
    flow.init( n );
    for( int i = 0 ; i < m ; i ++ ){
        in[ r[ i ] ] += a[ i ];
        out[ l[ i ] ] += a[ i ];
        flow.addEdge( l[ i ], r[ i ], b[ i ] - a[ i ] );
        // flow on edge from l[ i ] to r[ i ] should
        // be in [a[ i ], b[ i ]].
    }
    int nd = 0;
    for( int i = 1 ; i <= n ; i ++ ){
        if( in[ i ] < out[ i ] ){
            flow.addEdge( i, flow.t, out[ i ] - in[ i ] );
            nd += out[ i ] - in[ i ];
        }
        if( out[ i ] < in[ i ] )
            flow.addEdge( flow.s, i, in[ i ] - out[ i ] );
    }
    // original sink to source
    flow.addEdge( n, 1, INF );
    if( flow.maxflow() != nd )

```

```

// no solution
return -1;
int ans = flow.G[ 1 ].back().c; // source to sink
flow.G[ 1 ].back().c = flow.G[ n ].back().c = 0;
// take out super source and super sink
for( size_t i = 0 ; i < flow.G[ flow.s ].size() ; i
    ++ ){
    flow.G[ flow.s ][ i ].c = 0;
    Edge &e = flow.G[ flow.s ][ i ];
    flow.G[ e.v ][ e.r ].c = 0;
}
for( size_t i = 0 ; i < flow.G[ flow.t ].size() ; i
    ++ ){
    flow.G[ flow.t ][ i ].c = 0;
    Edge &e = flow.G[ flow.t ][ i ];
    flow.G[ e.v ][ e.r ].c = 0;
}
flow.addEdge( flow.s , 1 , INF );
flow.addEdge( n , flow.t , INF );
flow.reset();
return ans + flow.maxflow();
}

```

2.9 Flow Method

Maximize $c^T x$ subject to $Ax \leq b, x \geq 0$;
 with the corresponding symmetric dual problem,
 Minimize $b^T y$ subject to $A^T y \geq c, y \geq 0$.

Maximize $c^T x$ subject to $Ax \leq b$;
 with the corresponding asymmetric dual problem,
 Minimize $b^T y$ subject to $A^T y = c, y \geq 0$.

Minimum vertex cover on bipartite graph =
 Maximum matching on bipartite graph =
 Max flow with source to one side, other side to sink

To reconstruct the minimum vertex cover, dfs from each
 unmatched vertex on the left side **and** with unused edges
 only. Equivalently, dfs from source with unused edges
 only **and** without visiting sink. Then, a vertex is
 chosen
 iff. it is on the left side **and** without visited **or** on
 the right side **and** visited through dfs.

Maximum density subgraph $(\sum W_e + \sum W_v) / |V|$

Binary search on answer:
 For a fixed D, construct a Max flow model as follow:
 Let S be Sum of all weight(**or** inf)
 1. from source to each node with cap = S
 2. For each (u,v,w) in E, $(u \rightarrow v, \text{cap}=w)$, $(v \rightarrow u, \text{cap}=w)$
 3. For each node v, from v to sink with cap = $S + 2 * D$
 - $\text{deg}[v] - 2 * (W \text{ of } v)$
 where $\text{deg}[v] = \sum \text{weight of edge associated with } v$
 If $\text{maxflow} < S * |V|$, D is an answer.

Requiring subgraph: all vertex can be reached from
 source with
 edge whose cap > 0 .

有源匯，有下界，最大流，無費用。

先從t連向s，容量設為無限大。這樣就變成了無源匯的情況。
 將每條有下界的邊先滿上下界的流量，然後更新盈餘量（入
 的流量-出的流量）。新建超級源ss和超級匯tt，若某個點u
 的盈餘量 >0 則 $ss \rightarrow u$ ，容量為u的盈餘量。否則 $u \rightarrow tt$ ，容
 量為u的盈餘量的相反數。如果一個點的盈餘量 >0 ，則它是一
 定要流出去的，所以要從ss連向它，使它去找這些流量的出
 路。建完了圖以後求一遍最大流，如果從ss連出的所有邊都
 滿流，則有解。在得到的殘留網路（原圖）上再求一次最大
 流即可。

3 Math

3.1 FFT

```

// const int MAXN = 262144;
// (must be 2^k)
// before any usage, run pre_fft() first
//
// To implement poly. multiply:
//
// fft( n , a );
// fft( n , b );
// for( int i = 0 ; i < n ; i++ )
//     c[ i ] = a[ i ] * b[ i ];
// fft( n , c , 1 );
//
// then you have the result in c :: [cplx]
typedef long double ld;
typedef complex<ld> cplx;
const ld PI = acos(-1);
const cplx I(0, 1);
cplx omega[MAXN+1];
void pre_fft(){
    for(int i=0; i<=MAXN; i++)
        omega[i] = exp(i * 2 * PI / MAXN * I);
}
// n must be 2^k
void fft(int n, cplx a[], bool inv=false){
    int basic = MAXN / n;
    int theta = basic;
    for (int m = n; m >= 2; m >= 1) {
        int mh = m >> 1;
        for (int i = 0; i < mh; i++) {
            cplx w = omega[inv ? MAXN-(i*theta%MAXN)
                : i*theta%MAXN];
            for (int j = i; j < n; j += m) {
                int k = j + mh;
                cplx x = a[j] - a[k];
                a[j] += a[k];
                a[k] = w * x;
            }
        }
        theta = (theta * 2) % MAXN;
    }
    int i = 0;
    for (int j = 1; j < n - 1; j++) {
        for (int k = n >> 1; k > (i ^= k); k >= 1);
        if (j < i) swap(a[i], a[j]);
    }
    if (inv)
        for (i = 0; i < n; i++)
            a[i] /= n;
}

```

3.2 NTT

```

typedef long long LL;
// Remember coefficient are mod P
/* p=a*2^n+1
n    2^n    p    a    root
5    32    97    3    5
6    64    193    3    5
7    128    257    2    3
8    256    257    1    3
9    512    7681    15    17
10   1024    12289    12    11
11   2048    12289    6    11
12   4096    12289    3    11
13   8192    40961    5    3
14   16384    65537    4    3
15   32768    65537    2    3
16   65536    65537    1    3
17   131072    786433    6    10
18   262144    786433    3    10 (605028353,
    2308, 3)
19   524288    5767169    11    3
20   1048576    7340033    7    3
21   2097152    23068673    11    3

```

```

22 4194304 104857601 25 3
23 8388608 167772161 20 3
24 16777216 167772161 10 3
25 33554432 167772161 5 3 (1107296257, 33,
    10)
26 67108864 469762049 7 3
27 134217728 2013265921 15 31 */
// (must be 2^k)
// To implement poly. multiply:
// NTT<P, root, MAXN> ntt;
// ntt( n , a ); // or ntt.tran( n , a );
// ntt( n , b );
// for( int i = 0 ; i < n ; i++ )
//   c[ i ] = a[ i ] * b[ i ];
// ntt( n , c , 1 );
//
// then you have the result in c :: [LL]

template<LL P, LL root, int MAXN>
struct NTT{
    static LL bigmod(LL a, LL b) {
        LL res = 1;
        for (LL bs = a; b; b >>= 1, bs = (bs * bs) % P) {
            if(b&1) res=(res*bs)%P;
        }
        return res;
    }
    static LL inv(LL a, LL b) {
        if(a==1)return 1;
        return (((LL)(a-inv(b%a,a))*b+1)/a)%b;
    }
    LL omega[MAXN+1];
    NTT() {
        omega[0] = 1;
        LL r = bigmod(root, (P-1)/MAXN);
        for (int i=1; i<=MAXN; i++)
            omega[i] = (omega[i-1]*r)%P;
    }
    // n must be 2^k
    void tran(int n, LL a[], bool inv_ntt=false){
        int basic = MAXN / n;
        int theta = basic;
        for (int m = n; m >= 2; m >>= 1) {
            int mh = m >> 1;
            for (int i = 0; i < mh; i++) {
                LL w = omega[i*theta%MAXN];
                for (int j = i; j < n; j += m) {
                    int k = j + mh;
                    LL x = a[j] - a[k];
                    if (x < 0) x += P;
                    a[j] += a[k];
                    if (a[j] > P) a[j] -= P;
                    a[k] = (w * x) % P;
                }
            }
            theta = (theta * 2) % MAXN;
        }
        int i = 0;
        for (int j = 1; j < n - 1; j++) {
            for (int k = n >> 1; k > (i ^ k); k >>= 1);
            if (j < i) swap(a[i], a[j]);
        }
        if (inv_ntt) {
            LL ni = inv(n,P);
            reverse( a+1 , a+n );
            for (i = 0; i < n; i++)
                a[i] = (a[i] * ni) % P;
        }
    }
    void operator()(int n, LL a[], bool inv_ntt=false) {
        tran(n, a, inv_ntt);
    }
};

const LL P=2013265921,root=31;
const int MAXN=4194304;
NTT<P, root, MAXN> ntt;

```

3.3 Fast Walsh Transform

```

/* xor convolution:
* x = (x0,x1) , y = (y0,y1)
* z = ( x0y0 + x1y1 , x0y1 + x1y0 )
* =>
* x' = ( x0+x1 , x0-x1 ) , y' = ( y0+y1 , y0-y1 )
* z' = ( ( x0+x1 )( y0+y1 ) , ( x0-x1 )( y0-y1 ) )
* z = (1/2) * z''
* or convolution:
* x = (x0, x0+x1), inv = (x0, x1-x0) w/o final div
* and convolution:
* x = (x0+x1, x1), inv = (x0-x1, x1) w/o final div */
typedef long long LL;
const int MAXN = (1<<20)+10;
const LL MOD = 1e9+7;
inline LL pw( LL x , LL k ) {
    LL res = 1;
    for( LL bs = x ; k ; k >>= 1, bs = (bs * bs)%MOD ){
        if( k&1 ) res = ( res * bs ) % MOD;
    }
    return res;
}
inline LL inv( LL x ) {
    return pw( x , MOD-2 );
}
inline void fwt( LL x[ MAXN ] , int N , bool inv=0 ) {
    for( int d = 1 ; d < N ; d <= 1 ) {
        int d2 = d<<1;
        for( int s = 0 ; s < N ; s += d2 ) {
            for( int i = s , j = s+d ; i < s+d ; i++, j++ ){
                LL ta = x[ i ] , tb = x[ j ];
                x[ i ] = ta+tb;
                x[ j ] = ta-tb;
                if( x[ i ] >= MOD ) x[ i ] -= MOD;
                if( x[ j ] < 0 ) x[ j ] += MOD;
            }
        }
    }
    if( inv )
        for( int i = 0 ; i < N ; i++ ) {
            x[ i ] *= inv( N );
            x[ i ] %= MOD;
        }
}

```

3.4 BigInt

```

struct BigInt{
    static const int LEN = 60;
    static const int BIGMOD = 10000;
    int s, vl, v[LEN];
    // vector<int> v;
    BigInt() : s(1) { vl = 0; }
    BigInt(long long a) {
        s = 1; vl = 0;
        if (a < 0) { s = -1; a = -a; }
        while(a)
            push_back(a % BIGMOD),
            a /= BIGMOD;
    }
    BigInt(string str) {
        s = 1; vl = 0;
        int stPos = 0, num = 0;
        if (!str.empty() && str[0] == '-')
            stPos = 1, s = -1;
        for (int i=SZ(str)-1, q=1; i>=stPos; i--) {
            num += (str[i] - '0') * q;
            if ((q *= 10) >= BIGMOD)
                push_back(num), num = 0, q = 1;
        }
        if (num) push_back(num);
        n();
    }
    int len() const { return vl; } // return SZ(v);
    bool empty() const { return len() == 0; }
    void push_back(int x) { v[vl++] = x; } // v.PB(x);
    void pop_back() { vl--; } // v.pop_back();
    int back() const { return v[vl-1]; } // return v.back();
    void n(){ while (!empty() && !back()) pop_back(); }
    void resize(int nl) {

```



```

    vl = nl; fill(v, v+vl, 0);
    // v.resize(nl); fill(ALL(v), 0);
}
void print() const {
    if (empty()) { putchar('0'); return; }
    if (s == -1) putchar('-');
    printf("%d", back());
    for(int i=len()-2; i>=0; i--) printf("%.4d",v[i]);
}
int cp3(const Bigint &b)const {
    if (s != b.s) return s - b.s;
    if (s == -1) return -(*this).cp3(-b);
    if (len() != b.len()) return len()-b.len(); //int
    for (int i=len()-1; i>=0; i--)
        if (v[i]!=b.v[i]) return v[i]-b.v[i];
    return 0;
}
bool operator<(const Bigint &b)const
{ return cp3(b)<0; }
bool operator<=(const Bigint &b)const
{ return cp3(b)<=0; }
bool operator==(const Bigint &b)const
{ return cp3(b)==0; }
bool operator!=(const Bigint &b)const
{ return cp3(b)!=0; }
bool operator>(const Bigint &b)const
{ return cp3(b)>0; }
bool operator>=(const Bigint &b)const
{ return cp3(b)>=0; }
Bigint operator - () const {
    Bigint r = (*this); r.s = -r.s; return r;
}
Bigint operator + (const Bigint &b) const {
    if (s == -1) return -(-(*this)+(-b));
    if (b.s == -1) return (*this)-(-b);
    Bigint r;
    int nl = max(len(), b.len());
    r.resize(nl + 1);
    // directly add TODO
    r.n(); return r;
}
Bigint operator - (const Bigint &b) const {
    if (s == -1) return -(-(*this)-(-b));
    if (b.s == -1) return (*this)+(-b);
    if ((*this) < b) return -(b-(*this));
    Bigint r;
    r.resize(len());
    // directly sub TODO
    r.n(); return r;
}
Bigint operator * (const Bigint &b) {
    Bigint r;
    r.resize(len() + b.len() + 1);
    r.s = s * b.s;
    // directly mul TODO
    r.n(); return r;
}
Bigint operator / (const Bigint &b) {
    Bigint r;
    r.resize(max(1, len()-b.len()+1));
    int oriS = s;
    Bigint b2 = b; // b2 = abs(b)
    s = b2.s = r.s = 1;
    for (int i=r.len()-1; i>=0; i--) {
        int d=0, u=BIGMOD-1;
        while(d<u) {
            int m = (d+u+1)>>1;
            r.v[i] = m;
            if((r*b2) > (*this)) u = m-1;
            else d = m;
        }
        r.v[i] = d;
    }
    s = oriS; r.s = s * b.s;
    r.n(); return r;
}
Bigint operator % (const Bigint &b)
{ return (*this)-(*this)/b*b; }
};

```

3.5 Linear Recurrence

```

LL n, m;
LL dp[ N + N ];
void pre_dp(){
    dp[ 0 ] = 1;
    LL bdr = min( m + m , n );
    for( LL i = 1 ; i <= bdr ; i ++ )
        for( LL j = i - 1 ; j >= max(0LL, i - m) ; j -- )
            dp[ i ] = add( dp[ i ] , dp[ j ] );
}
vector<LL> Mul( vector<LL>& v1, vector<LL>& v2 ){
    int _sz1 = (int)v1.size();
    int _sz2 = (int)v2.size();
    assert( _sz1 == m );
    assert( _sz2 == m );
    vector<LL> _v( m + m );
    for( int i = 0 ; i < m + m ; i ++ ) _v[ i ] = 0;
    // expand
    for( int i = 0 ; i < _sz1 ; i ++ )
        for( int j = 0 ; j < _sz2 ; j ++ )
            _v[ i + j + 1 ] = add( _v[ i + j + 1 ] ,
                                mul(v1[ i ] , v2[ j ] ) );
    // shrink
    for( int i = 0 ; i < m ; i ++ )
        for( int j = 1 ; j <= m ; j ++ )
            _v[ i + j ] = add( _v[ i + j ] , _v[ i ] );
    for( int i = 0 ; i < m ; i ++ )
        _v[ i ] = _v[ i + m ];
    _v.resize( m );
    return _v;
}
vector<LL> I, A;
void solve(){
    pre_dp();
    if( n <= m + m )
        { printf( "%lld\n" , dp[ n ] ); exit( 0 ); }
    I.resize( m ); A.resize( m );
    for( int i = 0 ; i < m ; i ++ ) I[ i ] = A[ i ] = 1;
    // dp[ n ] = /Sum_{i=0}^{m-1} A_i * dp[ n - i - 1 ]
    LL dlt = ( n - m ) / m, rdlt = dlt * m;
    while( dlt ){
        if( dlt & 1LL ) I = Mul( I , A );
        A = Mul( A , A );
        dlt >>= 1;
    }
    LL ans = 0;
    for( int i = 0 ; i < m ; i ++ )
        ans = add(ans, mul(I[i], dp[n - i - 1 - rdlt]));
    printf( "%lld\n" , ans );
}

```

3.6 Miller Rabin

```

// n < 4,759,123,141      3 : 2, 7, 61
// n < 1,122,004,669,633  4 : 2, 13, 23, 1662803
// n < 3,474,749,660,383  6 : pimes <= 13
// n < 2^64              7 :
// 2, 325, 9375, 28178, 450775, 9780504, 1795265022
// Make sure testing integer is in range [2, n-2] if
// you want to use magic.
bool witness(LL a,LL n,LL u,int t){
    LL x=mypow(a,u,n);
    for(int i=0;i<t;i++){
        LL nx=mul(x,x,n);
        if(nx==1&&x!=1&&x!=n-1) return 1;
        x=nx;
    }
    return x!=1;
}
bool miller_rabin(LL n,int s=100) {
    // iterate s times of witness on n
    // return 1 if prime, 0 otherwise
    if(n<2) return 0;
    if(!(n&1)) return n == 2;
    LL u=n-1; int t=0;
    // n-1 = u*2^t
    while(!(u&1)) u>>=1, t++;
    while(s--){

```

```

    LL a=randll()%(n-1)+1;
    if(witness(a,n,u,t)) return 0;
}
return 1;
}

```

3.7 Simplex

```

const int MAXN = 111;
const int MAXM = 111;
const double eps = 1E-10;
double a[MAXN][MAXM], b[MAXN], c[MAXM], d[MAXN][MAXM];
double x[MAXM];
int ix[MAXN + MAXM]; // !!! array all indexed from 0
// max{cx} subject to {Ax<=b,x<=0}
// n: constraints, m: vars !!!
// x[] is the optimal solution vector
// usage :
// value = simplex(a, b, c, N, M);
double simplex(double a[MAXN][MAXM], double b[MAXN],
               double c[MAXM], int n, int m){
    ++m;
    int r = n, s = m - 1;
    memset(d, 0, sizeof(d));
    for (int i = 0; i < n + m; ++i) ix[i] = i;
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < m - 1; ++j) d[i][j] = -a[i][j];
        d[i][m - 1] = 1;
        d[i][m] = b[i];
        if (d[r][m] > d[i][m]) r = i;
    }
    for (int j = 0; j < m - 1; ++j) d[n][j] = c[j];
    d[n + 1][m - 1] = -1;
    for (double dd;; ) {
        if (r < n) {
            int t = ix[s]; ix[s] = ix[r + m]; ix[r + m] = t;
            d[r][s] = 1.0 / d[r][s];
            for (int j = 0; j <= m; ++j)
                if (j != s) d[r][j] *= -d[r][s];
            for (int i = 0; i <= n + 1; ++i) if (i != r) {
                for (int j = 0; j <= m; ++j) if (j != s)
                    d[i][j] += d[r][j] * d[i][s];
                d[i][s] *= d[r][s];
            }
        }
        r = -1; s = -1;
        for (int j = 0; j < m; ++j)
            if (s < 0 || ix[s] > ix[j]) {
                if (d[n + 1][j] > eps ||
                    (d[n + 1][j] > -eps && d[n][j] > eps))
                    s = j;
            }
        if (s < 0) break;
        for (int i = 0; i < n; ++i) if (d[i][s] < -eps) {
            if (r < 0 ||
                (dd = d[r][m] / d[r][s] - d[i][m] / d[i][s]) <
                 -eps ||
                (dd < eps && ix[r + m] > ix[i + m]))
                r = i;
        }
        if (r < 0) return -1; // not bounded
    }
    if (d[n + 1][m] < -eps) return -1; // not executable
    double ans = 0;
    for (int i = 0; i < m; i++) x[i] = 0;
    for (int i = m; i < n + m; ++i) { // the missing
        enumerated x[i] = 0
        if (ix[i] < m - 1) {
            ans += d[i - m][m] * c[ix[i]];
            x[ix[i]] = d[i - m][m];
        }
    }
    return ans;
}

```

3.8 Faulhaber

```

/* faulhaber 's formula -
 * cal power sum formula of all p=1~k in O(k^2) */
#define MAXK 2500
const int mod = 1000000007;
int b[MAXK];
// bernoulli number
int inv[MAXK+1];
// inverse
int cm[MAXK+1][MAXK+1]; // combinactories
int co[MAXK][MAXK+2];
// coeeficient of x^j when p=i
inline int getinv(int x) {
    int a=x,b=mod,a0=1,a1=0,b0=0,b1=1;
    while(b) {
        int q,t;
        q=a/b; t=b; b=a-b*q; a=t;
        t=b0; b0=a0-b0*q; a0=t;
        t=b1; b1=a1-b1*q; a1=t;
    }
    return a0<0?a0+mod:a0;
}
inline void pre() {
    /* combinational */
    for (int i=0;i<=MAXK;i++) {
        cm[i][0]=cm[i][i]=1;
        for (int j=1;j<i;j++)
            cm[i][j]=add(cm[i-1][j-1],cm[i-1][j]);
    }
    /* inverse */
    for (int i=1;i<=MAXK;i++) inv[i]=getinv(i);
    /* bernoulli */
    b[0]=1; b[1]=getinv(2); // with b[1] = 1/2
    for (int i=2;i<=MAXK;i++) {
        if (i&1) { b[i]=0; continue; }
        b[i]=1;
        for (int j=0;j<i;j++)
            b[i]=sub(b[i], mul(cm[i][j],mul(b[j], inv[i-j+1])));
    }
    /* faulhaber */
    // sigma_x=1~n {x^p} = 1/(p+1) * sigma_j=0~p { C(p+1,
    // j) * B_j * n^(p-j+1)}
    for (int i=1;i<=MAXK;i++) {
        co[i][0]=0;
        for (int j=0;j<=i;j++)
            co[i][i-j+1]= mul(inv[i+1], mul(cm[i+1][j], b[j]))
    }
}
/* sample usage: return f(n,p) = sigma_x=1~n (x^p) */
inline int solve(int n,int p) {
    int sol=0,m=n;
    for (int i=1;i<=p+1;i++) {
        sol=add(sol,mul(co[p][i],m));
        m = mul(m, n);
    }
    return sol;
}

```

3.9 Chinese Remainder

```

int pfn;
// number of distinct prime factors
int pf[MAXN]; // prime factor powers
int rem[MAXN]; // corresponding remainder
int pm[MAXN];
inline void generate_primes() {
    int i,j;
    pnum=1;
    prime[0]=2;
    for (i=3;i<=MAXVAL;i+=2) {
        if (nprime[i]) continue;
        prime[pnum++]=i;
        for (j=i*i;j<=MAXVAL;j+=i) nprime[j]=1;
    }
}
inline int inverse(int x,int p) {
    int q,tmp,a=x,b=p;
    int a0=1,a1=0,b0=0,b1=1;
    while(b) {

```



```

    q=a/b; tmp=b; b=a-b*q; a=tmp;
    tmp=b0; b0=a0-b0*q; a0=tmp;
    tmp=b1; b1=a1-b1*q; a1=tmp;
}
return a0;
}
inline void decompose_mod() {
    int i,p,t=mod;
    pfn=0;
    for(i=0;i<pnum&&prime[i]<=t;i++) {
        p=prime[i];
        if(t%p==0) {
            pf[pfn]=1;
            while(t%p==0) {
                t/=p;
                pf[pfn]*=p;
            }
            pfn++;
        }
    }
    if(t>1) pf[pfn++]=t;
}
inline int chinese_remainder() {
    int i,m,s=0;
    for(i=0;i<pfn;i++) {
        m=mod/pf[i];
        pm[i]=(LL)m*inverse(m,pf[i])%mod;
        s=(s+(LL)pm[i]*rem[i])%mod;
    }
    return s;
}

```

3.10 Pollard Rho

```

// does not work when n is prime
LL f(LL x, LL mod){
    return add(mul(x,x,mod),1,mod);
}
LL pollard_rho(LL n) {
    if(!(n&1)) return 2;
    while(true){
        LL y=2, x=rand()%(n-1)+1, res=1;
        for(int sz=2; res==1; sz*=2) {
            for(int i=0; i<sz && res<=1; i++) {
                x = f(x, n);
                res = __gcd(abs(x-y), n);
            }
            y = x;
        }
        if (res!=0 && res!=n) return res;
    }
}

```

3.11 Poly Generator

```

struct PolyGen{
    /* for a nth-order polynomial f(x), *
    * given f(0), f(1), ..., f(n) *
    * express f(x) as sigma_i{c_i*C(x,i)} */
    int n;
    vector<LL> coef;
    // initialize and calculate f(x), vector _fx should
    // be filled with f(0) to f(n)
    PolyGen(int _n,vector<LL> _fx):n(_n),coef(_fx){
        for(int i=0;i<n;i++)
            for(int j=n;j>i;j--)
                coef[j]-=coef[j-1];
    }
    // evaluate f(x), runs in O(n)
    LL eval(int x){
        LL m=1, ret=0;
        for(int i=0;i<=n;i++){
            ret+=coef[i]*m;
            m=m*(x-i)/(i+1);
        }
        return ret;
    }
};

```

3.12 Matrix Pseudo Inverse

```

Mat pinv( Mat m ){
    Mat res = I;
    FZ( used );
    for( int i = 0 ; i < W ; i ++ ){
        int piv = -1;
        for( int j = 0 ; j < W ; j ++ ){
            if( used[ j ] ) continue;
            if( abs( m.v[ j ][ i ] ) > EPS ){
                piv = j;
                break;
            }
        }
        if( piv == -1 ) continue;
        used[ i ] = true;
        swap( m.v[ piv ], m.v[ i ] );
        swap( res.v[ piv ], res.v[ i ] );
        LD rat = m.v[ i ][ i ];
        for( int j = 0 ; j < W ; j ++ ){
            m.v[ i ][ j ] /= rat;
            res.v[ i ][ j ] /= rat;
        }
        for( int j = 0 ; j < W ; j ++ ){
            if( j == i ) continue;
            rat = m.v[ j ][ i ];
            for( int k = 0 ; k < W ; k ++ ){
                m.v[ j ][ k ] -= rat * m.v[ i ][ k ];
                res.v[ j ][ k ] -= rat * res.v[ i ][ k ];
            }
        }
    }
    for( int i = 0 ; i < W ; i ++ ){
        if( used[ i ] ) continue;
        for( int j = 0 ; j < W ; j ++ )
            res.v[ i ][ j ] = 0;
    }
    return res;
}

```

3.13 ax+by=gcd

```

PII gcd(int a, int b){
    if(b == 0) return {1, 0};
    PII q = gcd(b, a % b);
    return {q.second, q.first - q.second * (a / b)};
}

```

3.14 Discrete sqrt

```

void calch(int &t, int &h, const int p) {
    int tmp=p-1; for(t=0;(tmp&1)==0;tmp/=2) t++; h=tmp;
}
// solve equation x^2 mod p = a
bool solve(int a, int p, int &x, int &y) {
    if(p == 2) { x = y = 1; return true; }
    int p2 = p / 2, tmp = mypow(a, p2, p);
    if (tmp == p - 1) return false;
    if ((p + 1) % 4 == 0) {
        x=myspow(a,(p+1)/4,p); y=p-x; return true;
    } else {
        int t, h, b, pb; calch(t, h, p);
        if (t >= 2) {
            do {b = rand() % (p - 2) + 2;
                while (mypow(b, p / 2, p) != p - 1);
                pb = mypow(b, h, p);
            } int s = mypow(a, h / 2, p);
            for (int step = 2; step <= t; step++) {
                int ss = (((LL)(s * s) % p) * a) % p;
                for(int i=0;i<t-step;i++) ss=mul(ss,ss,p);
                if (ss + 1 == p) s = (s * pb) % p;
                pb = ((LL)pb * pb) % p;
            } x = ((LL)s * a) % p; y = p - x;
        } return true;
    }
}

```

3.15 SchreierSims

```
// time:  $O(n^2 \lg^3 |G| + t n \lg |G|)$ 
// mem :  $O(n^2 \lg |G| + tn)$ 
// t : number of generator
namespace SchreierSimsAlgorithm{
    typedef vector<int> Permu;
    Permu inv( const Permu& p ){
        Permu ret( p.size() );
        for( int i = 0; i < (int)p.size(); i ++ )
            ret[ p[ i ] ] = i;
        return ret;
    }
    Permu operator*( const Permu& a, const Permu& b ){
        Permu ret( a.size() );
        for( int i = 0; i < (int)a.size(); i ++ )
            ret[ i ] = b[ a[ i ] ];
        return ret;
    }
    typedef vector<Permu> Bucket;
    typedef vector<int> Table;
    typedef pair<int,int> pii;
    int n, m;
    vector<Bucket> bkts, bktsInv;
    vector<Table> lookup;
    int fastFilter( const Permu &g, bool addToG = 1 ){
        n = bkts.size();
        Permu p;
        for( int i = 0; i < n; i ++ ){
            int res = lookup[ i ][ p[ i ] ];
            if( res == -1 ){
                if( addToG ){
                    bkts[ i ].push_back( p );
                    bktsInv[ i ].push_back( inv( p ) );
                    lookup[ i ][ p[ i ] ] = (int)bkts[i].size()-1;
                }
                return i;
            }
        }
        p = p * bktsInv[i][res];
        return -1;
    }
    long long calcTotalSize(){
        long long ret = 1;
        for( int i = 0; i < n; i ++ )
            ret *= bkts[i].size();
        return ret;
    }
    bool inGroup( const Permu &g ){
        return fastFilter( g, false ) == -1;
    }
    void solve( const Bucket &gen, int _n ){
        n = _n, m = gen.size(); // m perm[0..n-1]s
        //clear all
        bkts.clear();
        bktsInv.clear();
        lookup.clear();
    }
    for( int i = 0; i < n; i ++ ){
        lookup[i].resize(n);
        fill(lookup[i].begin(), lookup[i].end(), -1);
    }
    Permu id( n );
    for( int i = 0; i < n; i ++ ) id[i] = i;
    for( int i = 0; i < n; i ++ ){
        bkts[i].push_back(id);
        bktsInv[i].push_back(id);
        lookup[i][i] = 0;
    }
    for( int i = 0; i < m; i ++ )
        fastFilter( gen[i] );
    queue< pair<pii,pii> > toUpd;
    for( int i = 0; i < n; i ++ )
        for( int j = i; j < n; j ++ )
            for( int k = 0; k < (int)bkts[i].size(); k ++ )
                for( int l = 0; l < (int)bkts[j].size(); l ++ )
                    toUpd.push( {pii(i,k), pii(j,l)} );
    while( !toUpd.empty() ){
        pii a = toUpd.front().first;
        pii b = toUpd.front().second;
        toUpd.pop();

```

```
int res = fastFilter(bkts[a.first][a.second] *
                    bkts[b.first][b.second]);
if( res == -1 ) continue;
pii newPair(res, (int)bkts[res].size() - 1);
for( int i = 0; i < n; i ++ )
    for( int j = 0; j < (int)bkts[i].size(); ++j ){
        if( i <= res )
            toUpd.push( make_pair( pii(i, j), newPair ) );
        if( res <= i )
            toUpd.push( make_pair( newPair, pii(i, j) ) );
    }
}
}
```

3.16 Discrete K-th sqrt

```
//  $x^K \bmod P = A$ 
const int LimitSave = 100000;
LL _mod( LL a, LL mo ){ return ( a % mo + mo ) % mo; }
bool ext_gcd( LL A, LL B, LL C, LL &x, LL &y, LL &gn ){
    LL t;
    if( A == 0 ){
        gn = B;
        if( _mod(C, B) == 0 )
            { x = 0; y = C / B; return true; }
        return false;
    }
    if( ext_gcd( _mod(B, A), A, C, y, t, gn ) )
        { x = t - LL(B / A) * y; return true; }
    return false;
}
LL Division( LL A, LL B, LL modular ){
    LL gcdnum, K, Y;
    ext_gcd(modular, B, A, K, Y, gcdnum);
    Y = _mod(Y, modular);
    return Y < 0 ? Y + modular : Y;
}
struct tp{
    LL expo, res;
}data[ LimitSave + 100 ];
bool compareab( const tp &a, const tp &b )
{ return a.res < b.res; }
bool Binary_Search( LL key, LL &pos ){
    LL start, stop;
    start=1; stop=LimitSave;
    while( start <= stop ){
        pos = (start + stop)/2;
        if( data[pos].res == key ) return true;
        if( data[pos].res < key ) start = pos + 1;
        else stop = pos - 1;
    }
    return false;
}
LL get_log( LL root, LL A, LL mod ){
    LL i, j, times, XD, XT, position;
    if( mod - 1 < LimitSave ){
        LL now = 1;
        for( i = 0; i < mod; i ++ ){
            if( now == A ) return i;
            now = _mod( now * root, mod );
        }
    }
    data[1].expo = 0; data[1].res = 1;
    for( i = 1; i < LimitSave; i ++ ){
        data[i+1].expo=i;
        data[i+1].res=_mod(data[i].res*root,mod);
    }
    sort(data+1,data+LimitSave+1,compareab);
    times=myspow(root,LimitSave,mod);
    j=0; XD=1;
    while( 1 ){
        XT = Division(A, XD, mod);
        if( Binary_Search( XT, position ) )
            return j + data[position].expo;
        j = j + LimitSave;
        XD = _mod(XD * times, mod);
    }
}
LL P, K, A;
```

```

vector<LL> ans;
LL get_originroot( LL p ){
    LL primes[ 100 ];
    LL tot = 0, tp = P - 1;
    for( LL i = 2 ; i * i <= P - 1 ; i ++ )
        if( _mod( tp , i ) == 0 ){
            primes[ ++ tot ] = i;
            while( _mod( tp, i ) == 0 ) tp /= i;
        }
    if( tp != 1 ) primes[ ++ tot ] = tp;
    for( LL i = 2 ; ; i ++ ){
        bool ok = true;
        for( LL j = 1 ; j <= tot ; j ++ )
            if( mypow(i, (P-1)/primes[j], P) == 1 )
                { ok = false; break; }
        if( ok ) return i;
    }
}
//x^K mod P = A
void work_ans() {
    cin>>P>>K>>A;
    A = A % P;
    ans.clear(); // roots in ans
    if( A == 0 )
        { ans.push_back( 0 ); return; }
    LL root, logs, delta, deltapower, now, gcdnum, x, y;
    root=get_originroot(P);
    logs=get_log(root,A,P);
    if( ext_gcd(K, P-1, logs, x, y, gcdnum) ){
        delta=(P-1) / gcdnum;
        x = _mod(x, delta);
        if(x < 0) x += delta;
        now = mypow(root, x, P);
        deltapower = mypow(root, delta, P);
        while(x < P-1){
            ans.push_back(now);
            now=_mod(now * deltapower, P);
            x=x+delta;
        }
    }
}

```

3.17 Prefix Inverse

```

void solve( int m ){
    inv[ 1 ] = 1;
    for( int i = 2 ; i < m ; i ++ )
        inv[ i ] = ((LL)(m - m / i) * inv[m % i]) % m;
}

```

3.18 Roots of Polynomial

```

const double eps = 1e-12;
const double inf = 1e+12;
double a[ 10 ], x[ 10 ];
int n;
int sign( double x ){
    return (x < -eps)?(-1):(x>eps);
}
double f(double a[], int n, double x){
    double tmp=1, sum=0;
    for(int i=0; i<=n; i++){
        sum=sum+a[i]*tmp;
        tmp=tmp*x;
    }
    return sum;
}
double binary(double l, double r, double a[], int n){
    int sl=sign(f(a,n,l)), sr=sign(f(a,n,r));
    if(sl==0) return l;
    if(sr==0) return r;
    if(sl*sr>0) return inf;
    while(r-l>eps){
        double mid=(l+r)/2;
        int ss=sign(f(a,n,mid));
        if(ss==0) return mid;
        if(ss*sl>0) l=mid; else r=mid;
    }
}

```

```

return l;
}
void solve(int n, double a[], double x[], int &nx){
    if(n==1){
        x[1]=-a[0]/a[1];
        nx=1;
        return;
    }
    double da[10], dx[10];
    int ndx;
    for(int i=n; i>=1; i--) da[i-1]=a[i]*i;
    solve(n-1, da, dx, ndx);
    nx=0;
    if(ndx==0){
        double tmp=binary(-inf, inf, a, n);
        if (tmp<inf) x[++nx]=tmp;
        return;
    }
    double tmp;
    tmp=binary(-inf, dx[1], a, n);
    if(tmp<inf) x[++nx]=tmp;
    for(int i=1; i<=ndx-1; i++){
        tmp=binary(dx[i], dx[i+1], a, n);
        if(tmp<inf) x[++nx]=tmp;
    }
    tmp=binary(dx[ndx], inf, a, n);
    if(tmp<inf) x[++nx]=tmp;
}
int main() {
    scanf("%d", &n);
    for(int i=n; i>=0; i--) scanf("%lf", &a[i]);
    int nx;
    solve(n, a, x, nx);
    for(int i=1; i<=nx; i++) printf("%.6f\n", x[i]);
}

```

3.19 Mod

```

/// _fd(a,b) floor(a/b).
/// _rd(a,m) a-floor(a/m)*m.
/// _pv(a,m,r) largest x s.t x<=a && x%m == r.
/// _nx(a,m,r) smallest x s.t x>=a && x%m == r.
/// _ct(a,b,m,r) |A| , A = { x : a<=x<=b && x%m == r }.
int _fd(int a, int b){ return a<0?(-~a/b-1):a/b; }
int _rd(int a, int m){ return a-_fd(a,m)*m; }
int _pv(int a, int m, int r){
    r=(r%m+m)%m;
    return _fd(a-r,m)*m+r;
}
int _nt(int a, int m, int r){
    m=abs(m);
    r=(r%m+m)%m;
    return _fd(a-r-1,m)*m+r+m;
}
int _ct(int a, int b, int m, int r){
    m=abs(m);
    a=_nt(a,m,r);
    b=_pv(b,m,r);
    return (a>b)?0:((b-a+m)/m);
}

```

3.20 Primes and μ function

```

/* 12721, 13331, 14341, 75577, 123457, 222557, 556679
 * 999983, 1097774749, 1076767633, 100102021, 999997771
 * 1001010013, 1000512343, 987654361, 999991231
 * 999888733, 98789101, 987777733, 999991921, 1010101333
 * 1010102101, 1000000000039, 100000000000037
 * 2305843009213693951, 4611686018427387847
 * 9223372036854775783, 18446744073709551557 */
int mu[ N ], p_tbl[ N ];
vector<int> primes;
void sieve() {
    mu[ 1 ] = p_tbl[ 1 ] = 1;
    for( int i = 2 ; i < N ; i ++ ){
        if( !p_tbl[ i ] ){
            p_tbl[ i ] = i;
            primes.push_back( i );

```

```

    mu[ i ] = -1;
}
for( int p : primes ){
    int x = i * p;
    if( x >= M ) break;
    p_tbl[ x ] = p;
    mu[ x ] = -mu[ i ];
    if( i % p == 0 ){
        mu[ x ] = 0;
        break;
    }
}
}
}
vector<int> factor( int x ){
    vector<int> fac{ 1 };
    while( x > 1 ){
        int fn = SZ(fac), p = p_tbl[ x ], pos = 0;
        while( x % p == 0 ){
            x /= p;
            for( int i = 0 ; i < fn ; i ++ )
                fac.PB( fac[ pos ++ ] * p );
        }
    }
    return fac;
}

```

3.21 Result

```

/*
Lucas ' Theorem:
For non-negative integer n,m and prime P,
 $C(m,n) \bmod P = C(m/M,n/M) * C(m \% M,n \% M) \bmod P$ 
= mult_i ( C(m_i,n_i) )
where m_i is the i-th digit of m in base P.

Pick ' s Theorem
 $A = i + b/2 - 1$ 

Kirchhoff's theorem
 $A_{\{ii\}} = \deg(i)$ ,  $A_{\{ij\}} = (i,j) \setminus \text{in } E ? -1 : 0$ 
Deleting any one row, one column, and cal the det(A)
*/

```

4 Geometry

4.1 halfPlaneIntersection

4.2 Intersection of 2 lines

```

Pt interPnt( Line l1, Line l2, bool &res ){
    Pt p1, p2, q1, q2;
    tie(p1, p2) = l1;
    tie(q1, q2) = l2;
    double f1 = (p2 - p1) ^ (q1 - p1);
    double f2 = (p2 - p1) ^ (p1 - q2);
    double f = (f1 + f2);
    if( fabs(f) < eps )
    { res = false; return {0, 0}; }
    res = true;
    return q1 * (f2 / f) + q2 * (f1 / f);
}
bool isin( Line l0, Line l1, Line l2 ){
    // Check inter(l1, l2) in l0
    bool res;
    Pt p = interPnt(l1, l2, res);
    return ( (l0.SE - l0.FI) ^ (p - l0.FI) ) > eps;
}
/* If no solution, check: 1. ret.size() < 3
* Or more precisely, 2. interPnt(ret[0], ret[1])
* in all the lines. (use (l.S - l.F) ^ (p - l.F) > 0
*/
/* --^-- Line.FI --^-- Line.SE --^-- */
vector<Line> halfPlaneInter( vector<Line> lines ){
    int sz = lines.size();
    vector<double> ata(sz), ord(sz);

```

```

for( int i=0; i<sz; i++) {
    ord[i] = i;
    Pt d = lines[i].SE - lines[i].FI;
    ata[i] = atan2(d.Y, d.X);
}
sort( ord.begin(), ord.end(), [&](int i, int j) {
    if( fabs(ata[i] - ata[j]) < eps )
        return ( (lines[i].SE - lines[i].FI) ^
                (lines[j].SE - lines[i].FI) ) < 0;
    return ata[i] < ata[j];
});
vector<Line> fin;
for( int i=0; i<sz; i++)
    if( (!i or fabs(ata[ord[i]] - ata[ord[i-1]]) > eps)
        fin.PB(lines[ord[i]]);
deque<Line> dq;
for( int i=0; i<(int)(fin.size()); i++) {
    while((int)(dq.size()) >= 2 and
        not isin(fin[i], dq[(int)(dq.size()-2)],
                dq[(int)(dq.size()-1)]))
        dq.pop_back();
    while((int)(dq.size()) >= 2 and
        not isin(fin[i], dq[0], dq[1]))
        dq.pop_front();
    dq.push_back(fin[i]);
}
while( (int)(dq.size()) >= 3 and
    not isin(dq[0], dq[(int)(dq.size()-2)],
            dq[(int)(dq.size()-1)]))
    dq.pop_back();
while( (int)(dq.size()) >= 3 and
    not isin(dq[(int)(dq.size()-1)], dq[0], dq[1]))
    dq.pop_front();
vector<Line> res(dq.begin(), dq.end());
return res;
}

```

4.3 Intersection of 2 segments

```

int ori( const PLL& o , const PLL& a , const PLL& b ){
    LL ret = ( a - o ) ^ ( b - o );
    return ret / max( 1ll , abs( ret ) );
}
// p1 == p2 || q1 == q2 need to be handled
bool banana( const PLL& p1 , const PLL& p2 ,
              const PLL& q1 , const PLL& q2 ){
    if( ( ( p2 - p1 ) ^ ( q2 - q1 ) ) == 0 ){ // parallel
        if( ori( p1 , p2 , q1 ) ) return false;
        return ( ( p1 - q1 ) * ( p2 - q1 ) ) <= 0 ||
               ( ( p1 - q2 ) * ( p2 - q2 ) ) <= 0 ||
               ( ( q1 - p1 ) * ( q2 - p1 ) ) <= 0 ||
               ( ( q1 - p2 ) * ( q2 - p2 ) ) <= 0;
    }
    return (ori( p1, p2, q1 ) * ori( p1, p2, q2 ) <= 0) &&
           (ori( q1, q2, p1 ) * ori( q1, q2, p2 ) <= 0);
}

```

4.4 Intersection of polygon and circle

```

Pt ORI , info[ N ];
D r; int n;
// Divides into multiple triangle, and sum up
// oriented area
D area2(Pt pa, Pt pb){
    if( norm(pa) < norm(pb) ) swap(pa, pb);
    if( norm(pb) < eps ) return 0;
    D S, h, theta;
    D a = norm( pb ), b = norm( pa ), c = norm(pb - pa);
    D cosB = (pb * (pb - pa)) / a / c, B = acos(cosB);
    D cosC = (pa * pb) / a / b, C = acos(cosC);
    if( a > r ){
        S = (C/2)*r*r;
        h = a*b*sin(C)/c;
        if( h < r && B < PI/2 ) S -= (acos(h/r)*r*r - h*sqrt(
            r*r-h*h));
    }
    else if( b > r ){
        theta = PI - B - asin(sin(B)/r*a);
        S = .5*a*r*sin(theta) + (C-theta)/2*r*r;
    }
}

```

```

} else S = .5*sin(C)*a*b;
return S;
}
D area() {
    D S = 0;
    for(int i = 0; i < n; ++i)
        S += abs( area2(info[i], info[i + 1]) * sign( det(
            info[i], info[i + 1])));
    return fabs(S);
}

```

4.5 Intersection of 2 circles

4.6 Circle cover

```

#define N 1021
struct CircleCover{
    int C; Circle c[ N ];
    bool g[ N ][ N ], overlap[ N ][ N ];
    // Area[i] : area covered by at least i circles
    D Area[ N ];
    void init( int _C ){ C = _C; }
    bool Cinter( Circle& a , Circle& b , Pt& p1 , Pt& p2 )
    {
        Pt o1 = a.O , o2 = b.O;
        D r1 = a.R , r2 = b.R;
        D d2 = ( o1 - o2 ) * ( o1 - o2 );
        D d = sqrt(d2);
        if( d > r1 + r2 ) return false;
        Pt u = (o1+o2)*0.5 + (o1-o2)*((r2*r2-r1*r1)/(2*d2))
            ;
        D A = sqrt((r1+r2+d)*(r1-r2+d)*(r1+r2-d)*(-r1+r2+d)
            );
        Pt v = Pt( o1.Y-o2.Y , -o1.X + o2.X ) * A / (2*d2);
        p1 = u + v; p2 = u - v;
        return true;
    }
    struct Tevent {
        Pt p; D ang; int add;
        Tevent() {}
        Tevent(Pt _a, D _b, int _c): p(_a), ang(_b), add(_c)
        {}
        bool operator<(const Tevent &a)const
        {return ang < a.ang;}
    } eve[ N * 2 ];
    // strict: x = 0, otherwise x = -1
    bool disjunct( Circle& a, Circle& b, int x ){
        return sign( norm( a.O - b.O ) - a.R - b.R ) > x;
    }
    bool contain( Circle& a, Circle& b, int x ){
        return sign( a.R - b.R - norm( a.O - b.O ) ) > x;
    }
    bool contain(int i, int j){ /* c[j] is non-strictly
        in c[i]. */
        return (sign(c[i].R - c[j].R) > 0 ||
            (sign(c[i].R - c[j].R) == 0 && i < j) ) &&
            contain(c[i], c[j], -1);
    }
    void solve(){
        for( int i = 0 ; i <= C + 1 ; i ++ )
            Area[ i ] = 0;
        for( int i = 0 ; i < C ; i ++ )
            for( int j = 0 ; j < C ; j ++ )
                overlap[i][j] = contain(i, j);
        for( int i = 0 ; i < C ; i ++ )
            for( int j = 0 ; j < C ; j ++ )
                g[i][j] = !(overlap[i][j] || overlap[j][i] ||
                    disjunct(c[i], c[j], -1));
        for( int i = 0 ; i < C ; i ++ ){
            int E = 0, cnt = 1;
            for( int j = 0 ; j < C ; j ++ )
                if( j != i && overlap[j][i] )
                    cnt ++;
            for( int j = 0 ; j < C ; j ++ )
                if( i != j && g[i][j] ){
                    Pt aa, bb;
                    Cinter(c[i], c[j], aa, bb);
                    D A = atan2(aa.Y - c[i].O.Y, aa.X - c[i].O.X)
                        ;

```

```

                    D B = atan2(bb.Y - c[i].O.Y, bb.X - c[i].O.X)
                        ;
                    eve[E ++] = Tevent(bb, B, 1);
                    eve[E ++] = Tevent(aa, A, -1);
                    if(B > A) cnt ++;
                }
            if( E == 0 ) Area[ cnt ] += pi * c[i].R * c[i].R;
            else{
                sort( eve , eve + E );
                eve[E] = eve[0];
                for( int j = 0 ; j < E ; j ++ ){
                    cnt += eve[j].add;
                    Area[cnt] += (eve[j].p ^ eve[j + 1].p) * .5;
                    D theta = eve[j + 1].ang - eve[j].ang;
                    if (theta < 0) theta += 2. * pi;
                    Area[cnt] += ( theta - sin(theta) ) * c[i].R
                        * c[i].R * .5;
                }
            }
        }
    }
};

```

4.7 Convex Hull trick

```

/* Given a convexhull, answer queries in O(\lg N)
CH should not contain identical points, the area should
be > 0, min pair(x, y) should be listed first */
double det( const Pt& p1 , const Pt& p2 )
{ return p1.X * p2.Y - p1.Y * p2.X; }
struct Conv{
    int n;
    vector<Pt> a;
    vector<Pt> upper, lower;
    Conv(vector<Pt> _a) : a(_a){
        n = a.size();
        int ptr = 0;
        for(int i=1; i<n; ++i) if (a[ptr] < a[i]) ptr = i;
        for(int i=0; i<=ptr; ++i) lower.push_back(a[i]);
        for(int i=ptr; i<n; ++i) upper.push_back(a[i]);
        upper.push_back(a[0]);
    }
    int sign( LL x ){ // fixed when changed to double
        return x < 0 ? -1 : x > 0 }
    pair<LL, int> get_tang(vector<Pt> &conv, Pt vec){
        int l = 0, r = (int)conv.size() - 2;
        for( ; l + 1 < r; ){
            int mid = (l + r) / 2;
            if(sign(det(conv[mid+1]-conv[mid], vec))>0)r=mid;
            else l = mid;
        }
        return max(make_pair(det(vec, conv[r]), r),
            make_pair(det(vec, conv[0]), 0));
    }
    void upd_tang(const Pt &p, int id, int &i0, int &i1){
        if(det(a[i0] - p, a[id] - p) > 0) i0 = id;
        if(det(a[i1] - p, a[id] - p) < 0) i1 = id;
    }
    void bi_search(int l, int r, Pt p, int &i0, int &i1){
        if(l == r) return;
        upd_tang(p, l % n, i0, i1);
        int sl=sign(det(a[l % n] - p, a[(l + 1) % n] - p));
        for( ; l + 1 < r; ){
            int mid = (l + r) / 2;
            int smid=sign(det(a[mid%n]-p, a[(mid+1)%n]-p));
            if (smid == sl) l = mid;
            else r = mid;
        }
        upd_tang(p, r % n, i0, i1);
    }
    int bi_search(Pt u, Pt v, int l, int r) {
        int sl = sign(det(v - u, a[l % n] - u));
        for( ; l + 1 < r; ){
            int mid = (l + r) / 2;
            int smid = sign(det(v - u, a[mid % n] - u));
            if (smid == sl) l = mid;
            else r = mid;
        }
        return l % n;
    }
};

```



```
// 1. whether a given point is inside the CH
bool contain(Pt p) {
    if (p.X < lower[0].X || p.X > lower.back().X)
        return 0;
    int id = lower_bound(lower.begin(), lower.end(), Pt
        (p.X, -INF)) - lower.begin();
    if (lower[id].X == p.X) {
        if (lower[id].Y > p.Y) return 0;
    } else if (det(lower[id-1]-p, lower[id]-p) < 0) return 0;
    id = lower_bound(upper.begin(), upper.end(), Pt(p.X
        , INF), greater<Pt>()) - upper.begin();
    if (upper[id].X == p.X) {
        if (upper[id].Y < p.Y) return 0;
    } else if (det(upper[id-1]-p, upper[id]-p) < 0) return 0;
    return 1;
}

// 2. Find 2 tang pts on CH of a given outside point
// return true with i0, i1 as index of tangent points
// return false if inside CH
bool get_tang(Pt p, int &i0, int &i1) {
    if (contain(p)) return false;
    i0 = i1 = 0;
    int id = lower_bound(lower.begin(), lower.end(), p)
        - lower.begin();
    bi_search(0, id, p, i0, i1);
    bi_search(id, (int)lower.size(), p, i0, i1);
    id = lower_bound(upper.begin(), upper.end(), p,
        greater<Pt>()) - upper.begin();
    bi_search((int)lower.size() - 1, (int)lower.size()
        - 1 + id, p, i0, i1);
    bi_search((int)lower.size() - 1 + id, (int)lower.
        size() - 1 + (int)upper.size(), p, i0, i1);
    return true;
}

// 3. Find tangent points of a given vector
// ret the idx of vertex has max cross value with vec
int get_tang(Pt vec) {
    pair<LL, int> ret = get_tang(upper, vec);
    ret.second = (ret.second + (int)lower.size() - 1) % n;
    ret = max(ret, get_tang(lower, vec));
    return ret.second;
}

// 4. Find intersection point of a given line
// return 1 and intersection is on edge (i, next(i))
// return 0 if no strictly intersection
bool get_intersection(Pt u, Pt v, int &i0, int &i1) {
    int p0 = get_tang(u - v), p1 = get_tang(v - u);
    if (sign(det(v-u, a[p0]-u)) * sign(det(v-u, a[p1]-u)) < 0) {
        if (p0 > p1) swap(p0, p1);
        i0 = bi_search(u, v, p0, p1);
        i1 = bi_search(u, v, p1, p0 + n);
        return 1;
    }
    return 0;
}
};
```

4.8 KD Tree

```
const int MXN = 100005;

struct KDTree {
    struct Node {
        int x, y, x1, y1, x2, y2;
        int id, f;
        Node *L, *R;
    } tree[MXN];
    int n;
    Node *root;

    long long dis2(int x1, int y1, int x2, int y2) {
        long long dx = x1 - x2;
        long long dy = y1 - y2;
        return dx * dx + dy * dy;
    }

    static bool cmpx(Node& a, Node& b) { return a.x < b.x; }
    static bool cmpy(Node& a, Node& b) { return a.y < b.y; }
    void init(vector<pair<int, int>> ip) {
        n = ip.size();
        for (int i = 0; i < n; i++) {
```

```
        tree[i].id = i;
        tree[i].x = ip[i].first;
        tree[i].y = ip[i].second;
    }
    root = build_tree(0, n-1, 0);
}

Node* build_tree(int L, int R, int dep) {
    if (L > R) return nullptr;
    int M = (L+R)/2;
    tree[M].f = dep%2;
    nth_element(tree+L, tree+M, tree+R+1, tree[M].f ?
        cmpx : cmpy);
    tree[M].x1 = tree[M].x2 = tree[M].x;
    tree[M].y1 = tree[M].y2 = tree[M].y;

    tree[M].L = build_tree(L, M-1, dep+1);
    if (tree[M].L) {
        tree[M].x1 = min(tree[M].x1, tree[M].L->x1);
        tree[M].x2 = max(tree[M].x2, tree[M].L->x2);
        tree[M].y1 = min(tree[M].y1, tree[M].L->y1);
        tree[M].y2 = max(tree[M].y2, tree[M].L->y2);
    }

    tree[M].R = build_tree(M+1, R, dep+1);
    if (tree[M].R) {
        tree[M].x1 = min(tree[M].x1, tree[M].R->x1);
        tree[M].x2 = max(tree[M].x2, tree[M].R->x2);
        tree[M].y1 = min(tree[M].y1, tree[M].R->y1);
        tree[M].y2 = max(tree[M].y2, tree[M].R->y2);
    }

    return tree+M;
}

int touch(Node* r, int x, int y, long long d2) {
    long long dis = sqrt(d2)+1;
    if (x < r->x1-dis || x > r->x2+dis || y < r->y1-dis || y >
        r->y2+dis)
        return 0;
    return 1;
}

void nearest(Node* r, int x, int y, int &mID, long
    long &md2) {
    if (!r || !touch(r, x, y, md2)) return;
    long long d2 = dis2(r->x, r->y, x, y);
    if (d2 < md2 || (d2 == md2 && mID < r->id)) {
        mID = r->id;
        md2 = d2;
    }
    // search order depends on split dim
    if ((r->f == 0 && x < r->x) ||
        (r->f == 1 && y < r->y)) {
        nearest(r->L, x, y, mID, md2);
        nearest(r->R, x, y, mID, md2);
    } else {
        nearest(r->R, x, y, mID, md2);
        nearest(r->L, x, y, mID, md2);
    }
}

int query(int x, int y) {
    int id = 1029384756;
    long long d2 = 102938475612345678LL;
    nearest(root, x, y, id, d2);
    return id;
}
};
```

4.9 Lower Concave Hull

```
/*
****
maintain a "concave hull" that support the following
1. insertion of a line
2. query of height(y) on specific x on the hull
****
/* set as needed */
typedef long double LD;
const LD eps = 1e-9;
const LD inf = 1e19;
class Seg {
public:
    LD m, c, x1, x2; // y = mx + c
```



```

bool flag;
Seg(
    LD _m, LD _c, LD _x1=-inf, LD _x2=inf, bool _flag=0)
:m(_m), c(_c), x1(_x1), x2(_x2), flag(_flag) {}
LD evaly(LD x) const {
    return m*x+c;
}
const bool operator<(LD x) const {
    return x2-eps<x;
}
const bool operator<(const Seg &b) const {
    if(flag|b.flag) return *this<b.x1;
    return m+eps<b.m;
}
};
class LowerConcaveHull { // maintain a hull like: \_/_/
public:
    set<Seg> hull;
    /* functions */
    LD xintersection(Seg a, Seg b) {
        return (a.c-b.c)/(b.m-a.m);
    }
    inline set<Seg>::iterator replace(set<Seg> &
        hull, set<Seg>::iterator it, Seg s) {
        hull.erase(it);
        return hull.insert(s).first;
    }
    void insert(Seg s) {
        // insert a line and update hull
        set<Seg>::iterator it=hull.find(s);
        // check for same slope
        if(it!=hull.end()) {
            if(it->c+eps>=s.c) return;
            hull.erase(it);
        }
        // check if below whole hull
        it=hull.lower_bound(s);
        if(it!=hull.end()&&
            s.evaly(it->x1)<=it->evaly(it->x1)+eps) return;
        // update right hull
        while(it!=hull.end()) {
            LD x=xintersection(s,*it);
            if(x>=it->x2-eps) hull.erase(it++);
            else {
                s.x2=x;
                it=replace(hull,it,Seg(it->m,it->c,x,it->x2));
                break;
            }
        }
        // update left hull
        while(it!=hull.begin()) {
            LD x=xintersection(s,*(--it));
            if(x<=it->x1+eps) hull.erase(it++);
            else {
                s.x1=x;
                it=replace(hull,it,Seg(it->m,it->c,it->x1,x));
                break;
            }
        }
        // insert s
        hull.insert(s);
    }
    void insert(LD m, LD c) { insert(Seg(m,c)); }
    LD query(LD x) { // return y @ given x
        set<Seg>::iterator it =
            hull.lower_bound(Seg(0.0,0.0,x,x,1));
        return it->evaly(x);
    }
};

```

4.10 Delaunay Triangulation

/*
Delaunay Triangulation:
Given a sets of points on 2D plane, find a
triangulation
such that no points will strictly inside circumcircle
of any triangle.

find : return a triangle contain given point

add_point : add a point into triangulation

A Triangle is in triangulation iff. its has_chd is 0.
Region of triangle u: iterate each u.edge[i].tri,
each points are u.p[(i+1)%3], u.p[(i+2)%3]

```

*/
const int N = 100000 + 5;
const int MAX_TRIS = N * 6;
double eps = 1e-6;
double sqr(double x) { return x*x; }
bool in_cc(const Pt& p1, const Pt& p2, const Pt& p3,
    const Pt& p4){
// return p4 is in circumcircle of tri(p1,p2,p3)
double u11 = p1.X - p4.X;
double u21 = p2.X - p4.X;
double u31 = p3.X - p4.X;
double u12 = p1.Y - p4.Y;
double u22 = p2.Y - p4.Y;
double u32 = p3.Y - p4.Y;
double u13 = sqr(p1.X)-sqr(p4.X)+sqr(p1.Y)-sqr(p4.Y);
double u23 = sqr(p2.X)-sqr(p4.X)+sqr(p2.Y)-sqr(p4.Y);
double u33 = sqr(p3.X)-sqr(p4.X)+sqr(p3.Y)-sqr(p4.Y);
double det = -u13*u22*u31 + u12*u23*u31 + u13*u21*u32
    - u11*u23*u32 - u12*u21*u33 + u11*u22*u33;
return det > eps;
}
double side(const Pt& a, const Pt& b, const Pt& p)
{ return (b - a) ^ (p - a); }
typedef int SdRef;
struct Tri;
typedef Tri* TriRef;
struct Edge {
    TriRef tri;
    SdRef side;
    Edge() : tri(0), side(0) {}
    Edge(TriRef _tri, SdRef _side) : tri(_tri), side(
        _side) {}
};
struct Tri {
    Pt p[3];
    Edge edge[3];
    TriRef chd[3];
    Tri() {}
    Tri(const Pt& p0, const Pt& p1, const Pt& p2) {
        p[0] = p0; p[1] = p1; p[2] = p2;
        chd[0] = chd[1] = chd[2] = 0;
    }
    bool has_chd() const
    { return chd[0] != 0; }
    int num_chd() const {
        return chd[0] == 0 ? 0
            : chd[1] == 0 ? 1
            : chd[2] == 0 ? 2 : 3;
    }
    bool contains(Pt const& q) const {
        double a = side(p[0],p[1],q);
        double b = side(p[1],p[2],q);
        double c = side(p[2],p[0],q);
        return a >= -eps && b >= -eps && c >= -eps;
    }
}
triange_pool[MAX_TRIS], *tot_tris;
void edge(Edge a, Edge b) {
    if(a.tri) a.tri->edge[a.side] = b;
    if(b.tri) b.tri->edge[b.side] = a;
}
struct Trig { // Triangulation
    Trig() {
        const double LOTS = 1e6;
        the_root = new(tot_tris++) Tri(Pt(-LOTS,-LOTS),Pt(+
            LOTS,-LOTS),Pt(0,+LOTS));
    }
// tools
    TriRef find(Pt p) const
    { return find(the_root,p); }
    void add_point(const Pt& p)
    { add_point(find(the_root,p),p); }
// tools
    TriRef the_root;
    static TriRef find(TriRef root, const Pt& p) {
        for(;;) {
            if (!root->has_chd())
                return root;

```

```

    for (int i = 0; i < 3 && root->chd[i] ; ++i)
        if (root->chd[i]->contains(p)) {
            root = root->chd[i];
            break;
        }
    // "point not found"
}
}
void add_point(TriRef root, Pt const& p) {
    TriRef tab, tbc, tca;
    /* split it into three triangles */
    tab=new(tot_tris++) Tri(root->p[0],root->p[1],p);
    tbc=new(tot_tris++) Tri(root->p[1],root->p[2],p);
    tca=new(tot_tris++) Tri(root->p[2],root->p[0],p);
    edge(Edge(tab,0), Edge(tbc,1));
    edge(Edge(tbc,0), Edge(tca,1));
    edge(Edge(tca,0), Edge(tab,1));
    edge(Edge(tab,2), root->edge[2]);
    edge(Edge(tbc,2), root->edge[0]);
    edge(Edge(tca,2), root->edge[1]);
    root->chd[0] = tab;
    root->chd[1] = tbc;
    root->chd[2] = tca;
    flip(tab,2);
    flip(tbc,2);
    flip(tca,2);
}
void flip(TriRef tri, SdRef pi) {
    TriRef trj = tri->edge[pi].tri;
    int pj = tri->edge[pi].side;
    if (!trj) return;
    if (!in_cc(tri->p[0],tri->p[1],tri->p[2],trj->p[pj])) return;
    /* flip edge between tri,trj */
    TriRef trk = new(tot_tris++) Tri(tri->p[(pi+1)%3],
        trj->p[pj], tri->p[pi]);
    TriRef trl = new(tot_tris++) Tri(trj->p[(pj+1)%3],
        tri->p[pi], trj->p[pj]);
    edge(Edge(trk,0), Edge(trl,0));
    edge(Edge(trk,1), tri->edge[(pi+2)%3]);
    edge(Edge(trk,2), trj->edge[(pj+1)%3]);
    edge(Edge(trl,1), trj->edge[(pj+2)%3]);
    edge(Edge(trl,2), tri->edge[(pi+1)%3]);
    tri->chd[0]=trk; tri->chd[1]=trl; tri->chd[2]=0;
    trj->chd[0]=trk; trj->chd[1]=trl; trj->chd[2]=0;
    flip(trk,1); flip(trk,2);
    flip(trl,1); flip(trl,2);
}
};
int n;
Pt ps[N];
void build(){
    tot_tris = triange_pool;
    scanf( "%d" , &n );
    for(int i = 0; i < n; ++ i) {
        int x, y;
        scanf("%d%d", &x, &y);
        ps[ i ] = { x , y };
    }
    random_shuffle(ps, ps + n);
    Trig tri;
    for(int i = 0; i < n; ++ i)
        tri.add_point(ps[i]);
}

```

4.11 Min Enclosing Circle

```

struct Mec{
    // return pair of center and r
    static const int N = 101010;
    int n;
    Pt p[ N ], cen;
    double r2;
    void init( int _n , Pt _p[] ){
        n = _n;
        memcpy( p , _p , sizeof(Pt) * n );
    }
    double sqr(double a){ return a*a; }
    Pt center(Pt p0, Pt p1, Pt p2) {
        Pt a = p1-p0;

```

```

        Pt b = p2-p0;
        double c1=norm2( a ) * 0.5;
        double c2=norm2( b ) * 0.5;
        double d = a ^ b;
        double x = p0.X + (c1 * b.Y - c2 * a.Y) / d;
        double y = p0.Y + (a.X * c2 - b.X * c1) / d;
        return Pt(x,y);
    }
    pair<Pt,double> solve(){
        random_shuffle(p,p+n);
        r2=0;
        for (int i=0; i<n; i++){
            if (norm2(cen-p[i]) <= r2) continue;
            cen = p[i];
            r2 = 0;
            for (int j=0; j<i; j++){
                if (norm2(cen-p[j]) <= r2) continue;
                cen=Pt((p[i].X+p[j].X)/2,(p[i].Y+p[j].Y)/2);
                r2 = norm2(cen-p[j]);
                for (int k=0; k<j; k++){
                    if (norm2(cen-p[k]) <= r2) continue;
                    cen = center(p[i],p[j],p[k]);
                    r2 = norm2(cen-p[k]);
                }
            }
            return {cen,sqrt(r2)};
        }
    }
} mec;

```

4.12 Min Enclosing Ball

```

// Pt : { x , y , z }
#define N 202020
int n, nouter; Pt pt[ N ], outer[4], res;
double radius,tmp;
void ball() {
    Pt q[3]; double m[3][3], sol[3], L[3], det;
    int i,j; res.x = res.y = res.z = radius = 0;
    switch ( nouter ) {
        case 1: res=outer[0]; break;
        case 2: res=(outer[0]+outer[1])/2; radius=norm2(res, outer[0]); break;
        case 3:
            for (i=0; i<2; ++i) q[i]=outer[i+1]-outer[0];
            for (i=0; i<2; ++i) for(j=0; j<2; ++j) m[i][j]=(q[i] * q[j])*2;
            for (i=0; i<2; ++i) sol[i]=(q[i] * q[i]);
            if (fabs(det=m[0][0]*m[1][1]-m[0][1]*m[1][0])<eps) return;
            L[0]=(sol[0]*m[1][1]-sol[1]*m[0][1])/det;
            L[1]=(sol[1]*m[0][0]-sol[0]*m[1][0])/det;
            res=outer[0]+q[0]*L[0]+q[1]*L[1];
            radius=norm2(res, outer[0]);
            break;
        case 4:
            for (i=0; i<3; ++i) q[i]=outer[i+1]-outer[0], sol[i]=(q[i] * q[i]);
            for (i=0; i<3; ++i) for(j=0; j<3; ++j) m[i][j]=(q[i] * q[j])*2;
            det= m[0][0]*m[1][1]*m[2][2]
                + m[0][1]*m[1][2]*m[2][0]
                + m[0][2]*m[1][0]*m[2][1]
                - m[0][2]*m[1][1]*m[2][0]
                - m[0][1]*m[1][0]*m[2][2]
                - m[0][0]*m[1][2]*m[2][1];
            if ( fabs(det)<eps ) return;
            for (j=0; j<3; ++j) {
                for (i=0; i<3; ++i) m[i][j]=sol[i];
                L[j]=( m[0][0]*m[1][1]*m[2][2]
                    + m[0][1]*m[1][2]*m[2][0]
                    + m[0][2]*m[1][0]*m[2][1]
                    - m[0][2]*m[1][1]*m[2][0]
                    - m[0][1]*m[1][0]*m[2][2]
                    - m[0][0]*m[1][2]*m[2][1]
                    ) / det;
                for (i=0; i<3; ++i) m[i][j]=(q[i] * q[j])*2;
            }
            res=outer[0];
            for (i=0; i<3; ++i) res = res + q[i] * L[i];
            radius=norm2(res, outer[0]);
    }
}

```

```

}}
void minball(int n){ ball();
  if( nouter < 4 ) for( int i = 0 ; i < n ; i ++ )
    if( norm2(res, pt[i]) - radius > eps ){
      outer[ nouter ++ ] = pt[ i ]; minball(i); --
      nouter;
      if(i>0){ Pt Tt = pt[i];
        memmove(&pt[1], &pt[0], sizeof(Pt)*i); pt[0]=Tt
        ;
      }
    }
}
void solve{
  // n points in pt
  random_shuffle(pt, pt+n); radius=-1;
  for(int i=0;i<n;i++) if(norm2(res,pt[i])-radius>eps)
    nouter=1, outer[0]=pt[i], minball(i);
  printf("%.5f\n",sqrt(radius));
}

```

4.13 Minkowski sum

```

/* convex hull Minkowski Sum*/
#define INF 1000000000000000LL
int pos( const Pt& tp ){
  if( tp.Y == 0 ) return tp.X > 0 ? 0 : 1;
  return tp.Y > 0 ? 0 : 1;
}
#define N 300030
Pt pt[ N ], qt[ N ], rt[ N ];
LL Lx,Rx;
int dn,un;
inline bool cmp( Pt a, Pt b ){
  int pa=pos( a ),pb=pos( b );
  if(pa==pb) return (a^b)>0;
  return pa<pb;
}
int minkowskiSum(int n,int m){
  int i,j,r,p,q,fi,fj;
  for(i=1,p=0;i<n;i++){
    if( pt[i].Y<pt[p].Y ||
      (pt[i].Y==pt[p].Y && pt[i].X<pt[p].X) ) p=i; }
  for(i=1,q=0;i<m;i++){
    if( qt[i].Y<qt[q].Y ||
      (qt[i].Y==qt[q].Y && qt[i].X<qt[q].X) ) q=i; }
  rt[0]=pt[p]+qt[q];
  r=1; i=p; j=q; fi=fj=0;
  while(1){
    if((fj&&j==q) ||
      ( (!fj || i!=p) &&
        cmp(pt[(p+1)%n]-pt[p],qt[(q+1)%m]-qt[q]) ) ){
      rt[r]=rt[r-1]+pt[(p+1)%n]-pt[p];
      p=(p+1)%n;
      fi=1;
    }else{
      rt[r]=rt[r-1]+qt[(q+1)%m]-qt[q];
      q=(q+1)%m;
      fj=1;
    }
    if(r<=1 || ((rt[r]-rt[r-1])^(rt[r-1]-rt[r-2]))!=0)
      r++;
    else rt[r-1]=rt[r];
    if(i==p && j==q) break;
  }
  return r-1;
}
void initInConvex(int n){
  int i,p,q;
  LL Ly,Ry;
  Lx=INF; Rx=-INF;
  for(i=0;i<n;i++){
    if(pt[i].X<Lx) Lx=pt[i].X;
    if(pt[i].X>Rx) Rx=pt[i].X;
  }
  Ly=Ry=INF;
  for(i=0;i<n;i++){
    if(pt[i].X==Lx && pt[i].Y<Ly){ Ly=pt[i].Y; p=i; }
    if(pt[i].X==Rx && pt[i].Y>Ry){ Ry=pt[i].Y; q=i; }
  }
  for(dn=0,i=p;i!=q;i=(i+1)%n){ qt[dn++]=pt[i]; }
  qt[dn]=pt[q];Ly=Ry=-INF;
  for(i=0;i<n;i++){

```

```

    if(pt[i].X==Lx && pt[i].Y>Ly){ Ly=pt[i].Y; p=i; }
    if(pt[i].X==Rx && pt[i].Y>Ry){ Ry=pt[i].Y; q=i; }
  }
  for(un=0,i=p;i!=q;i=(i+n-1)%n){ rt[un++]=pt[i]; }
  rt[un]=pt[q];
}
inline int inConvex(Pt p){
  int L,R,M;
  if(p.X<Lx || p.X>Rx) return 0;
  L=0;R=dn;
  while(L<R-1){ M=(L+R)/2;
    if(p.X<qt[M].X) R=M; else L=M; }
  if(tri(qt[L],qt[R],p)<0) return 0;
  L=0;R=un;
  while(L<R-1){ M=(L+R)/2;
    if(p.X<rt[M].X) R=M; else L=M; }
  if(tri(rt[L],rt[R],p)>0) return 0;
  return 1;
}
int main(){
  int n,m,i;
  Pt p;
  scanf("%d",&n);
  for(i=0;i<n;i++) scanf("%lld%lld",&pt[i].X,&pt[i].Y);
  scanf("%d",&m);
  for(i=0;i<m;i++) scanf("%lld%lld",&qt[i].X,&qt[i].Y);
  n=minkowskiSum(n,m);
  for(i=0;i<n;i++) pt[i]=rt[i];
  scanf("%d",&m);
  for(i=0;i<m;i++) scanf("%lld%lld",&qt[i].X,&qt[i].Y);
  n=minkowskiSum(n,m);
  for(i=0;i<n;i++) pt[i]=rt[i];
  initInConvex(n);
  scanf("%d",&m);
  for(i=0;i<m;i++){
    scanf("%lld %lld",&p.X,&p.Y);
    p.X*=3; p.Y*=3;
    puts(inConvex(p)? "YES": "NO");
  }
}

```

4.14 Heart of Triangle

```

Pt inCenter( Pt &A, Pt &B, Pt &C) { // 內心
  double a = norm(B-C), b = norm(C-A), c = norm(A-B);
  return (A * a + B * b + C * c) / (a + b + c);
}
Pt circumCenter( Pt &a, Pt &b, Pt &c) { // 外心
  Pt bb = b - a, cc = c - a;
  double db=norm2(bb), dc=norm2(cc), d=2*(bb ^ cc);
  return a+Pt(bb.Y*dc-cc.Y*db, cc.X*db-bb.X*dc) / d;
}
Pt othroCenter( Pt &a, Pt &b, Pt &c) { // 垂心
  Pt ba = b - a, ca = c - a, bc = b - c;
  double Y = ba.Y * ca.Y * bc.Y,
    A = ca.X * ba.Y - ba.X * ca.Y,
    x0= (Y+ca.X*ba.Y*b.X-ba.X*ca.Y*c.X) / A,
    y0= -ba.X * (x0 - c.X) / ba.Y + ca.Y;
  return Pt(x0, y0);
}

```

5 Graph

5.1 HeavyLightDecomp

```

#define SZ(c) (int)(c).size()
#define ALL(c) (c).begin(), (c).end()
#define REP(i, s, e) for(int i = (s); i <= (e); i++)
#define REPD(i, s, e) for(int i = (s); i >= (e); i--)
typedef tuple< int , int > tii;
const int MAXN = 100010;
const int LOG = 19;
struct HLD{
  int n;
  vector<int> g[MAXN];
  int sz[MAXN], dep[MAXN];

```

```

int ts, tid[MAXN], tdi[MAXN], tl[MAXN], tr[MAXN];
// ts : timestamp , useless after yutruli
// tid[ u ] : pos. of node u in the seq.
// tdi[ i ] : node at pos i of the seq.
// tl , tr[ u ] : subtree interval in the seq. of
// node u
int mom[MAXN][LOG], head[MAXN];
// head[ u ] : head of the chain contains u
void dfssz(int u, int p){
    dep[u] = dep[p] + 1;
    mom[u][0] = p;
    sz[u] = 1;
    head[u] = u;
    for(int& v:g[u]) if(v != p){
        dep[v] = dep[u] + 1;
        dfssz(v, u);
        sz[u] += sz[v];
    }
}
void dfshl(int u){
    //printf("dfshl %d\n", u);
    ts++;
    tid[u] = tl[u] = tr[u] = ts;
    tdi[tid[u]] = u;
    sort(ALL(g[u]),
        [&](int a, int b){return sz[a] > sz[b];});
    bool flag = 1;
    for(int& v:g[u]) if(v != mom[u][0]){
        if(flag) head[v] = head[u], flag = 0;
        dfshl(v);
        tr[u] = tr[v];
    }
}
inline int lca(int a, int b){
    if(dep[a] > dep[b]) swap(a, b);
    //printf("lca %d %d\n", a, b);
    int diff = dep[b] - dep[a];
    REPD(k, LOG-1, 0) if(diff & (1<<k)){
        //printf("b %d\n", mom[b][k]);
        b = mom[b][k];
    }
    if(a == b) return a;
    REPD(k, LOG-1, 0) if(mom[a][k] != mom[b][k]){
        a = mom[a][k];
        b = mom[b][k];
    }
    return mom[a][0];
}
void init(int _n){
    n = _n;
    REP(i, 1, n) g[i].clear();
}
void addEdge(int u, int v){
    g[u].push_back(v);
    g[v].push_back(u);
}
void yutruli(){
    dfssz(1, 0);
    ts = 0;
    dfshl(1);
    REP(k, 1, LOG-1) REP(i, 1, n)
        mom[i][k] = mom[mom[i][k-1]][k-1];
}
vector<tii> getPath(int u, int v){
    vector<tii> res;
    while(tid[u] < tid[head[v]]){
        res.push_back(tii(tid[head[v]], tid[v]));
        v = mom[head[v]][0];
    }
    res.push_back(tii(tid[u], tid[v]));
    reverse(ALL(res));
    return res;
}
/*
 * res : list of intervals from u to v
 * u must be ancestor of v
 * usage :
 * vector<tii> path = tree.getPath(u, v)
 * for(tii tp : path){
 *     int l, r; tie(l, r) = tp;
 *     upd(l, r);
 *     uu = tree.tdi[l], vv = tree.tdi[r];

```

```

    * uu ~> vv is a heavy path on tree
    * }
    */
}
} tree;

```

5.2 DominatorTree

```

const int MAXN = 100010;
struct DominatorTree{
#define REP(i,s,e) for(int i=(s);i<=(e);i++)
#define REPD(i,s,e) for(int i=(s);i>=(e);i--)
    int n, m, s;
    vector<int> g[ MAXN ], pred[ MAXN ];
    vector<int> cov[ MAXN ];
    int dfn[ MAXN ], nfd[ MAXN ], ts;
    int par[ MAXN ];
    int sdom[ MAXN ], idom[ MAXN ];
    int mom[ MAXN ], mn[ MAXN ];
    inline bool cmp(int u, int v){
        return dfn[u] < dfn[v];
    }
    int eval(int u){
        if(mom[u] == u) return u;
        int res = eval(mom[u]);
        if(cmp(sdom[mn[mom[u]]], sdom[mn[u]]))
            mn[u] = mn[mom[u]];
        return mom[u] = res;
    }
    void init(int _n, int _m, int _s){
        ts = 0; n = _n; m = _m; s = _s;
        REP(i, 1, n) g[i].clear(), pred[i].clear();
    }
    void addEdge(int u, int v){
        g[u].push_back(v);
        pred[v].push_back(u);
    }
    void dfs(int u){
        ts++;
        dfn[u] = ts;
        nfd[ts] = u;
        for(int v : g[u]) if(dfn[v] == 0){
            par[v] = u;
            dfs(v);
        }
    }
    void build(){
        REP(i, 1, n){
            dfn[i] = nfd[i] = 0;
            cov[i].clear();
            mom[i] = mn[i] = sdom[i] = i;
        }
        dfs(s);
        REPD(i, n, 2){
            int u = nfd[i];
            if(u == 0) continue;
            for(int v : pred[u]) if(dfn[v]){
                eval(v);
                if(cmp(sdom[mn[v]], sdom[u]))
                    sdom[u] = sdom[mn[v]];
            }
            cov[sdom[u]].push_back(u);
            mom[u] = par[u];
            for(int w : cov[par[u]]){
                eval(w);
                if(cmp(sdom[mn[w]], par[u]))
                    idom[w] = mn[w];
                else idom[w] = par[u];
            }
            cov[par[u]].clear();
        }
        REP(i, 2, n){
            int u = nfd[i];
            if(u == 0) continue;
            if(idom[u] != sdom[u])
                idom[u] = idom[idom[u]];
        }
    }
} domT;

```

5.3 MaxClique

```

struct MaxClique {
    static const int MV = 210;
    int V, ans, dp[MV];
    int el[MV][MV/30+1], s[MV][MV/30+1];
    vector<int> sol;
    void init(int v) {
        V = v; ans = 0;
        FZ(el); FZ(dp);
    }
    /* Zero Base */
    void addEdge(int u, int v) {
        if(u > v) swap(u, v);
        if(u == v) return;
        el[u][v/32] |= (1<<(v%32));
    }
    bool dfs(int v, int k) {
        int c = 0, d = 0;
        for(int i=0; i<(V+31)/32; i++) {
            s[k][i] = el[v][i];
            if(k != 1) s[k][i] &= s[k-1][i];
            c += __builtin_popcount(s[k][i]);
        }
        if(c == 0) {
            if(k > ans) {
                ans = k;
                sol.clear();
                sol.push_back(v);
                return 1;
            }
            return 0;
        }
        for(int i=0; i<(V+31)/32; i++) {
            for(int a = s[k][i]; a; a += d) {
                if(k + (c-d) <= ans) return 0;
                int lb = a&(-a), lg = 0;
                a ^= lb;
                while(lb!=1) {
                    lb = (unsigned int)(lb) >> 1;
                    lg++;
                }
                int u = i*32 + lg;
                if(k + dp[u] <= ans) return 0;
                if(dfs(u, k+1)) {
                    sol.push_back(v);
                    return 1;
                }
            }
        }
        return 0;
    }
    int solve() {
        for(int i=V-1; i>=0; i--) {
            dfs(i, 1);
            dp[i] = ans;
        }
        return ans;
    }
};

```

5.4 Number of Maximal Clique

```

// bool g[][] : adjacent array indexed from 1 to n
void dfs(int sz){
    int i, j, k, t, cnt, best = 0;
    if(ne[sz]==ce[sz]){ if (ce[sz]==0) ++ans; return; }
    for(t=0, i=1; i<=ne[sz]; ++i){
        for(cnt=0, j=ne[sz]+1; j<=ce[sz]; ++j)
            if (!g[lst[sz][i]][lst[sz][j]]) ++cnt;
        if (t==0 || cnt<best) t=i, best=cnt;
    } if (t && best<=0) return;
    for (k=ne[sz]+1; k<=ce[sz]; ++k) {
        if (t>0){ for (i=k; i<=ce[sz]; ++i)
            if (!g[lst[sz][t]][lst[sz][i]]) break;
            swap(lst[sz][k], lst[sz][i]);
        } i=lst[sz][k]; ne[sz+1]=ce[sz+1]=0;
        for (j=1; j<k; ++j)if (g[i][lst[sz][j]])
            lst[sz+1][++ne[sz+1]]=lst[sz][j];
    }
}

```

```

    for (ce[sz+1]=ne[sz+1], j=k+1; j<=ce[sz]; ++j)
        if (g[i][lst[sz][j]]) lst[sz+1][++ce[sz+1]]=lst[sz][j];
    dfs(sz+1); ++ne[sz]; --best;
    for (j=k+1, cnt=0; j<=ce[sz]; ++j) if (!g[i][lst[sz][j]]) ++cnt;
    if (t==0 || cnt<best) t=k, best=cnt;
    if (t && best<=0) break;
}
void work(){
    ne[0]=0; ce[0]=0;
    for(int i=1; i<=n; ++i) lst[0][++ce[0]]=i;
    ans=0; dfs(0);
}

```

5.5 Strongly Connected Component

```

struct Scc{
    int n, nScc, vst[MXN], bln[MXN];
    vector<int> E[MXN], rE[MXN], vec;
    void init(int _n){
        n = _n;
        for (int i=0; i<MXN; i++){
            E[i].clear();
            rE[i].clear();
        }
    }
    void add_edge(int u, int v){
        E[u].PB(v);
        rE[v].PB(u);
    }
    void DFS(int u){
        vst[u]=1;
        for (auto v : E[u])
            if (!vst[v]) DFS(v);
        vec.PB(u);
    }
    void rDFS(int u){
        vst[u] = 1;
        bln[u] = nScc;
        for (auto v : rE[u])
            if (!vst[v]) rDFS(v);
    }
    void solve(){
        nScc = 0;
        vec.clear();
        FZ(vst);
        for (int i=0; i<n; i++)
            if (!vst[i]) DFS(i);
        reverse(vec.begin(), vec.end());
        FZ(vst);
        for (auto v : vec){
            if (!vst[v]){
                rDFS(v);
                nScc++;
            }
        }
    }
};

```

5.6 Dynamic MST

```

/* Dynamic MST O( Q lg^2 Q )
(qx[i], qy[i]) -> chg weight of edge No.qx[i] to qy[i]
delete an edge: (i, \infty)
add an edge: change from \infty to specific value
*/
const int SZ=M+3*MXQ;
int a[N],*tz;
int find(int xx){
    int root=xx; while(a[root]) root=a[root];
    int next; while((next=a[xx])){a[xx]=root; xx=next;}
    return root;
}
bool cmp(int aa,int bb){ return tz[aa]<tz[bb]; }
int kx[N],ky[N],kt, vd[N],id[M], app[M];
bool extra[M];

```



```

void solve(int *qx,int *qy,int Q,int n,int *x,int *y,
int *z,int m1,long long ans){
if(Q==1){
for(int i=1;i<=n;i++) a[i]=0;
z[ qx[0] ]=qy[0]; tz = z;
for(int i=0;i<m1;i++) id[i]=i;
sort(id,id+m1,cmp); int ri,rj;
for(int i=0;i<m1;i++){
ri=find(x[id[i]]); rj=find(y[id[i]]);
if(ri!=rj){ ans+=z[id[i]]; a[ri]=rj; }
}
printf("%lld\n",ans);
return;
}
int ri,rj;
//contract
kt=0;
for(int i=1;i<=n;i++) a[i]=0;
for(int i=0;i<Q;i++){
ri=find(x[qx[i]]); rj=find(y[qx[i]]); if(ri!=rj) a[ri]=rj;
}
int tm=0;
for(int i=0;i<m1;i++) extra[i]=true;
for(int i=0;i<Q;i++) extra[ qx[i] ]=false;
for(int i=0;i<m1;i++) if(extra[i]) id[tm++]=i;
tz=z; sort(id,id+tm,cmp);
for(int i=0;i<tm;i++){
ri=find(x[id[i]]); rj=find(y[id[i]]);
if(ri!=rj){
a[ri]=rj; ans += z[id[i]];
kx[kt]=x[id[i]]; ky[kt]=y[id[i]]; kt++;
}
}
for(int i=1;i<=n;i++) a[i]=0;
for(int i=0;i<kt;i++) a[ find(kx[i]) ]=find(ky[i]);
int n2=0;
for(int i=1;i<=n;i++) if(a[i]==0)
vd[i]++;n2;
for(int i=1;i<=n;i++) if(a[i])
vd[i]=vd[find(i)];
int m2=0, *Nx=x+m1, *Ny=y+m1, *Nz=z+m1;
for(int i=0;i<m1;i++) app[i]=-1;
for(int i=0;i<Q;i++) if(app[qx[i]]==-1){
Nx[m2]=vd[ x[ qx[i] ] ]; Ny[m2]=vd[ y[ qx[i] ] ];
Nz[m2]=z[ qx[i] ];
app[qx[i]]=m2; m2++;
}
for(int i=0;i<Q;i++){ z[ qx[i] ]=qy[i]; qx[i]=app[qx[i]]; }
for(int i=1;i<=n2;i++) a[i]=0;
for(int i=0;i<tm;i++){
ri=find(vd[ x[id[i]] ]); rj=find(vd[ y[id[i]] ]);
if(ri!=rj){
a[ri]=rj; Nx[m2]=vd[ x[id[i]] ];
Ny[m2]=vd[ y[id[i]] ]; Nz[m2]=z[id[i]]; m2++;
}
}
int mid=Q/2;
solve(qx,qy,mid,n2,Nx,Ny,Nz,m2,ans);
solve(qx+mid,qy+mid,Q-mid,n2,Nx,Ny,Nz,m2,ans);
}
int x[SZ],y[SZ],z[SZ],qx[MXQ],qy[MXQ],n,m,Q;
void init(){
scanf("%d%d",&n,&m);
for(int i=0;i<m;i++) scanf("%d%d%d",x+i,y+i,z+i);
scanf("%d",&Q);
for(int i=0;i<Q;i++){ scanf("%d%d",qx+i,qy+i); qx[i]--; }
}
void work(){ if(Q) solve(qx,qy,Q,n,x,y,z,m,0); }
int main(){init(); work(); }

```

5.7 Minimum General Weighted Matching

```

struct Graph {
// Minimum General Weighted Matching (Perfect Match)
static const int MXN = 105;
int n, edge[MXN][MXN];
int match[MXN],dis[MXN],onstk[MXN];

```

```

vector<int> stk;
void init(int _n) {
n = _n;
for( int i = 0 ; i < n ; i ++ )
for( int j = 0 ; j < n ; j ++ )
edge[ i ][ j ] = 0;
}
void add_edge(int u, int v, int w)
{ edge[u][v] = edge[v][u] = w; }
bool SPFA(int u){
if (onstk[u]) return true;
stk.PB(u);
onstk[u] = 1;
for (int v=0; v<n; v++){
if (u != v && match[u] != v && !onstk[v]){
int m = match[v];
if (dis[m] > dis[u] - edge[v][m] + edge[u][v]){
dis[m] = dis[u] - edge[v][m] + edge[u][v];
onstk[v] = 1;
stk.PB(v);
if (SPFA(m)) return true;
stk.pop_back();
onstk[v] = 0;
}
}
}
onstk[u] = 0;
stk.pop_back();
return false;
}
int solve() {
// find a match
for (int i=0; i<n; i+=2){
match[i] = i+1;
match[i+1] = i;
}
while (true){
int found = 0;
for( int i = 0 ; i < n ; i ++ )
onstk[ i ] = dis[ i ] = 0;
for (int i=0; i<n; i++){
stk.clear();
if (!onstk[i] && SPFA(i)){
found = 1;
while (SZ(stk)>=2){
int u = stk.back(); stk.pop_back();
int v = stk.back(); stk.pop_back();
match[u] = v;
match[v] = u;
}
}
}
if (!found) break;
}
int ret = 0;
for (int i=0; i<n; i++){
ret += edge[i][match[i]];
ret /= 2;
return ret;
}
}graph;

```

5.8 Minimum Steiner Tree

```

// Minimum Steiner Tree
//  $O(V \cdot 3^T + V^2 \cdot 2^T)$ 
struct SteinerTree{
#define V 33
#define T 8
#define INF 1023456789
int n, dst[V][V], dp[1<<T][V], tdst[V];
void init( int _n ){
n = _n;
for( int i = 0 ; i < n ; i ++ ){
for( int j = 0 ; j < n ; j ++ )
dst[ i ][ j ] = INF;
dst[ i ][ i ] = 0;
}
}
void add_edge( int ui , int vi , int wi ){

```



```

    dst[ ui ][ vi ] = min( dst[ ui ][ vi ], wi );
    dst[ vi ][ ui ] = min( dst[ vi ][ ui ], wi );
}
void shortest_path(){
    for( int k = 0 ; k < n ; k ++ )
        for( int i = 0 ; i < n ; i ++ )
            for( int j = 0 ; j < n ; j ++ )
                dst[ i ][ j ] = min( dst[ i ][ j ],
                    dst[ i ][ k ] + dst[ k ][ j ] );
}
int solve( const vector<int>& ter ){
    int t = (int)ter.size();
    for( int i = 0 ; i < ( 1 << t ) ; i ++ )
        for( int j = 0 ; j < n ; j ++ )
            dp[ i ][ j ] = INF;
    for( int i = 0 ; i < n ; i ++ )
        dp[ 0 ][ i ] = 0;
    for( int msk = 1 ; msk < ( 1 << t ) ; msk ++ ){
        if( msk == ( msk & (-msk) ) ){
            int who = __lg( msk );
            for( int i = 0 ; i < n ; i ++ )
                dp[ msk ][ i ] = dst[ ter[ who ] ][ i ];
            continue;
        }
        for( int i = 0 ; i < n ; i ++ )
            for( int submsk = ( msk - 1 ) & msk ; submsk ;
                submsk = ( submsk - 1 ) & msk )
                dp[ msk ][ i ] = min( dp[ msk ][ i ],
                    dp[ submsk ][ i ] +
                    dp[ msk ^ submsk ][ i ] );
        for( int i = 0 ; i < n ; i ++ ){
            tdst[ i ] = INF;
            for( int j = 0 ; j < n ; j ++ )
                tdst[ i ] = min( tdst[ i ],
                    dp[ msk ][ j ] + dst[ j ][ i ] );
        }
        for( int i = 0 ; i < n ; i ++ )
            dp[ msk ][ i ] = tdst[ i ];
    }
    int ans = INF;
    for( int i = 0 ; i < n ; i ++ )
        ans = min( ans , dp[ ( 1 << t ) - 1 ][ i ] );
    return ans;
}
} solver;

```

5.9 BCC based on vertex

```

struct BccVertex {
    int n,nScc,step,dfn[MXN],low[MXN];
    vector<int> E[MXN],sccv[MXN];
    int top,stk[MXN];
    void init(int _n) {
        n = _n;
        nScc = step = 0;
        for( int i=0; i<n; i++) E[i].clear();
    }
    void add_edge(int u, int v) {
        E[u].PB(v);
        E[v].PB(u);
    }
    void DFS(int u, int f) {
        dfn[u] = low[u] = step++;
        stk[top++] = u;
        for( auto v:E[u] ) {
            if( v == f ) continue;
            if( dfn[v] == -1 ) {
                DFS(v,u);
                low[u] = min(low[u], low[v]);
                if( low[v] >= dfn[u] ) {
                    int z;
                    sccv[nScc].clear();
                    do {
                        z = stk[--top];
                        sccv[nScc].PB(z);
                    } while( z != v );
                    sccv[nScc].PB(u);
                    nScc++;
                }
            } else {

```

```

                low[u] = min(low[u],dfn[v]);
            }
        }
    }
    vector<vector<int>>> solve() {
        vector<vector<int>>> res;
        for( int i=0; i<n; i++) {
            dfn[i] = low[i] = -1;
        }
        for( int i=0; i<n; i++) {
            if( dfn[i] == -1 ) {
                top = 0;
                DFS(i,i);
            }
        }
        REP(i,nScc) res.PB(sccv[i]);
        return res;
    }
} graph;

```

5.10 Graph Hash

```

$$F_t(i) =
(F_{t-1}(i) \times A +
\sum_{i \rightarrow j} F_{t-1}(j) \times B +
\sum_{j \rightarrow i} F_{t-1}(j) \times C +
D \times (i = a)) \bmod P
$$
for each node i, iterate t times.
t, A, B, C, D, P are hash parameter

```

6 String

6.1 PalTree

```

const int MAXN = 200010;
struct PalT{
    struct Node{
        int nxt[ 33 ], len , fail;
        ll cnt;
    };
    int tot , lst;
    Node nd[ MAXN * 2 ];
    char* s;
    int newNode( int l , int _fail ){
        int res = ++tot;
        memset( nd[ res ].nxt , 0 , sizeof nd[ res ].nxt );
        nd[ res ].len = l;
        nd[ res ].cnt = 0;
        nd[ res ].fail = _fail;
        return res;
    }
    void push( int p ){
        int np = lst;
        int c = s[ p ] - 'a';
        while( p - nd[ np ].len - 1 < 0
            || s[ p ] != s[ p - nd[ np ].len - 1 ] )
            np = nd[ np ].fail;
        if( nd[ np ].nxt[ c ] ){
            nd[ nd[ np ].nxt[ c ] ].cnt++;
            lst = nd[ np ].nxt[ c ];
            return;
        }
        int nq = newNode( nd[ np ].len + 2 , 0 );
        nd[ nq ].cnt++;
        nd[ np ].nxt[ c ] = nq;
        lst = nq;
        if( nd[ nq ].len == 1 ){
            nd[ nq ].fail = 2;
            return;
        }
        int tf = nd[ np ].fail;
        while( p - nd[ tf ].len - 1 < 0
            || s[ p ] != s[ p - nd[ tf ].len - 1 ] )
            tf = nd[ tf ].fail;

```

```

    nd[ nq ].fail = nd[ tf ].nxt[ c ];
    return ;
}
void init( char* _s ){
    s = _s;
    tot = 0;
    newNode( -1 , 1 );
    newNode( 0 , 1 );
    lst = 2;
    for( int i = 0 ; s[ i ] ; i++ )
        push( i );
}
void yutru1i(){
#define REPD(i, s, e) for(int i = (s); i >= (e); i--)
    REPD( i , tot , 1 )
        nd[ nd[ i ].fail ].cnt += nd[ i ].cnt;
        nd[ 1 ].cnt = nd[ 2 ].cnt = 0ll;
}
} pA;
int main(){ pA.init( sa ); }

```

6.2 SuffixArray

```

const int MAX = 1020304;
int ct[MAX], he[MAX], rk[MAX];
int sa[MAX], tsa[MAX], tp[MAX][2];
void suffix_array(char *ip){
    int len = strlen(ip);
    int alp = 256;
    memset(ct, 0, sizeof(ct));
    for(int i=0; i<len; i++) ct[ip[i]+1]++;
    for(int i=1; i<alp; i++) ct[i]+=ct[i-1];
    for(int i=0; i<len; i++) rk[i]=ct[ip[i]];
    for(int i=1; i<len; i*=2){
        for(int j=0; j<len; j++){
            if(j+i>len) tp[j][1]=0;
            else tp[j][1]=rk[j+i]+1;
            tp[j][0]=rk[j];
        }
        memset(ct, 0, sizeof(ct));
        for(int j=0; j<len; j++) ct[tp[j][1]+1]++;
        for(int j=1; j<len+2; j++) ct[j]+=ct[j-1];
        for(int j=0; j<len; j++) tsa[ct[tp[j][1]]+j]=j;
        memset(ct, 0, sizeof(ct));
        for(int j=0; j<len; j++) ct[tp[j][0]+1]++;
        for(int j=1; j<len+1; j++) ct[j]+=ct[j-1];
        for(int j=0; j<len; j++)
            sa[ct[tp[tsa[j]][0]]+j]=tsa[j];
        rk[sa[0]]=0;
        for(int j=1; j<len; j++){
            if( tp[sa[j]][0] == tp[sa[j-1]][0] &&
                tp[sa[j]][1] == tp[sa[j-1]][1] )
                rk[sa[j]] = rk[sa[j-1]];
            else
                rk[sa[j]] = j;
        }
    }
    for(int i=0, h=0; i<len; i++){
        if(rk[i]==0) h=0;
        else{
            int j=sa[rk[i]-1];
            h=max(0, h-1);
            for(; ip[i+h]==ip[j+h]; h++);
        }
        he[rk[i]]=h;
    }
}

```

6.3 SAIS

```

const int N = 300010;
struct SA{
#define REP(i,n) for ( int i=0; i<int(n); i++ )
#define REP1(i,a,b) for ( int i=(a); i<=int(b); i++ )
    bool _t[N*2];
    int _s[N*2], _sa[N*2], _c[N*2], x[N], _p[N], _q[N*2],
        hei[N], r[N];
}

```

```

int operator [] (int i){ return _sa[i]; }
void build(int *s, int n, int m){
    memcpy(_s, s, sizeof(int) * n);
    sais(_s, _sa, _p, _q, _t, _c, n, m);
    mkhei(n);
}
void mkhei(int n){
    REP(i,n) r[_sa[i]] = i;
    hei[0] = 0;
    REP(i,n) if(r[i]) {
        int ans = i>0 ? max(hei[r[i-1]] - 1, 0) : 0;
        while(_s[i+ans] == _s[_sa[r[i]-1]+ans]) ans++;
        hei[r[i]] = ans;
    }
}
void sais(int *s, int *sa, int *p, int *q, bool *t,
    int *c, int n, int z){
    bool uniq = t[n-1] = true, neq;
    int nn = 0, nmzx = -1, *nsa = sa + n, *ns = s + n,
        lst = -1;
#define MS0(x,n) memset((x),0,n*sizeof(*(x)))
#define MAGIC(XD) MS0(sa, n); \
    memcpy(x, c, sizeof(int) * z); \
    XD; \
    memcpy(x + 1, c, sizeof(int) * (z - 1)); \
    REP(i,n) if(sa[i] && !t[sa[i]-1]) sa[x[s[sa[i]
        ]-1]]++ = sa[i]-1; \
    memcpy(x, c, sizeof(int) * z); \
    for(int i = n - 1; i >= 0; i--) if(sa[i] && t[sa[i]
        ]-1]) sa[-x[s[sa[i]-1]]] = sa[i]-1;
    MS0(c, z);
    REP(i,n) uniq &= ++c[s[i]] < 2;
    REP(i,z-1) c[i+1] += c[i];
    if (uniq) { REP(i,n) sa[--c[s[i]]] = i; return; }
    for(int i = n - 2; i >= 0; i--) t[i] = (s[i]==s[i
        +1] ? t[i+1] : s[i]<s[i+1]);
    MAGIC(REP1(i,1,n-1) if(t[i] && !t[i-1]) sa[-x[s[i
        ]]] = p[q[i]=nn++] = i);
    REP(i, n) if (sa[i] && t[sa[i]] && !t[sa[i]-1]) {
        neq=lst<0 || memcmp(s+sa[i], s+lst, (p[q[sa[i]]+1]-sa
            [i])*sizeof(int));
        ns[q[lst=sa[i]]]=nmzx+=neq;
    }
    sais(ns, nsa, p + nn, q + n, t + n, c + z, nn, nmzx
        + 1);
    MAGIC(for(int i = nn - 1; i >= 0; i--) sa[-x[s[p[
        nsa[i]]]] = p[nsa[i]]);
}
} sa;
int H[ N ], SA[ N ];
void suffix_array(int* ip, int len) {
    // should padding a zero in the back
    // ip is int array, len is array length
    // ip[0..n-1] != 0, and ip[len] = 0
    ip[len++] = 0;
    sa.build(ip, len, 128);
    for (int i=0; i<len; i++) {
        H[i] = sa.hei[i + 1];
        SA[i] = sa._sa[i + 1];
    }
    // resulting height, sa array \in [0,len)
}

```

6.4 SuffixAutomata

```

const int MAXM = 1000010;
struct SAM{
    int tot, root, lst, mom[MAXM], mx[MAXM];
    int acc[MAXM], nxt[MAXM][33];
    int newNode(){
        int res = ++tot;
        fill(nxt[res], nxt[res]+33, 0);
        mom[res] = mx[res] = acc[res] = 0;
        return res;
    }
    void init(){
        tot = 0;
        root = newNode();
        mom[root] = 0, mx[root] = 0;
        lst = root;
    }
}

```

```

}
void push(int c){
    int p = lst;
    int np = newNode();
    mx[np] = mx[p]+1;
    for(; p && nxt[p][c] == 0; p = mom[p])
        nxt[p][c] = np;
    if(p == 0) mom[np] = root;
    else{
        int q = nxt[p][c];
        if(mx[p]+1 == mx[q]) mom[np] = q;
        else{
            int nq = newNode();
            mx[nq] = mx[p]+1;
            for(int i = 0; i < 33; i++)
                nxt[nq][i] = nxt[q][i];
            mom[nq] = mom[q];
            mom[q] = nq;
            mom[np] = nq;
            for(; p && nxt[p][c] == q; p = mom[p])
                nxt[p][c] = nq;
        }
    }
    lst = np;
}
void push(char *str){
    for(int i = 0; str[i]; i++)
        push(str[i]-'a'+1);
}
} sam;

```

6.5 Aho-Corasick

```

struct AAutomata{
    struct Node{
        int cnt,dp;
        Node *go[26], *fail;
        Node (){
            cnt = 0; dp = -1; fail = 0;
            memset(go,0,sizeof(go));
        }
    };
    Node *root, pool[1048576];
    int nMem;
    Node* new_Node(){
        pool[nMem] = Node();
        return &pool[nMem++];
    }
    void init()
    { nMem = 0; root = new_Node(); }
    void add(const string &str)
    { insert(root,str,0); }
    void insert(Node *cur, const string &str, int pos){
        if (pos >= (int)str.size())
            { cur->cnt++; return; }
        int c = str[pos]-'a';
        if (cur->go[c] == 0)
            cur->go[c] = new_Node();
        insert(cur->go[c],str,pos+1);
    }
    void make_fail(){
        queue<Node*> que;
        que.push(root);
        while (!que.empty()){
            Node* fr=que.front();
            que.pop();
            for (int i=0; i<26; i++){
                if (fr->go[i]){
                    Node *ptr = fr->fail;
                    while (ptr && !ptr->go[i]) ptr = ptr->fail;
                    if (!ptr) fr->go[i]->fail = root;
                    else fr->go[i]->fail = ptr->go[i];
                    que.push(fr->go[i]);
                }
            }
        }
    }
};

```

6.6 Z Value

```

char s[MAXN];
int len,z[MAXN];
void Z_value() {
    int i,j,left,right;
    left=right=0; z[0]=len;
    for(i=1;i<len;i++) {
        j=max(min(z[i-left],right-i),0);
        for(;i+j<len&&s[i+j]==s[j];j++);
        z[i]=j;
        if(i+z[i]>right) {
            right=i+z[i];
            left=i;
        }
    }
}

```

6.7 ZValue Palindrome

```

int len, zv[MAX*2];
char ip[MAX], op[MAX*2];
int main(){
    cin >> ip; len = strlen(ip);
    int l2 = len*2 - 1;
    for(int i=0; i<l2; i++){
        if(i&1) op[i] = '@';
        else op[i] = ip[i/2];
    }
    int l=0, r=0; zv[0] = 1;
    for(int i=1; i<l2; i++){
        if( i > r ){
            l = r = i;
            while( l>0 && r<l2-1 && op[l-1] == op[r+1] )
                l--, r++;
            zv[i] = (r-l+1);
        }else{
            int md = (l+r)/2, j = md + md - i;
            zv[i] = zv[j];
            int q = zv[i] / 2, nr = i + q;
            if( nr == r ){
                l = i + i - r;
                while( l>0 && r<l2-1 && op[l-1] == op[r+1] )
                    l--, r++;
                zv[i] = r - l + 1;
            }else if( nr > r )
                zv[i] = (r - i) * 2 + 1;
        }
    }
}

```

6.8 Smallest Rotation

```

string mcp(string s){
    int n = s.length();
    s += s;
    int i=0, j=1;
    while (i<n && j<n){
        int k = 0;
        while (k < n && s[i+k] == s[j+k]) k++;
        if (s[i+k] <= s[j+k]) j += k+1;
        else i += k+1;
        if (i == j) j++;
    }
    int ans = i < n ? i : j;
    return s.substr(ans, n);
}

```

7 Data Structure

7.1 Treap

```

struct Treap{
    int sz, val, pri, tag;
    Treap *l, *r;
};

```

```

Treap( int _val ){
    val = _val; sz = 1;
    pri = rand(); l = r = NULL; tag = 0;
}
};
void push( Treap * a ){
    if( a->tag ){
        Treap *swp = a->l; a->l = a->r; a->r = swp;
        int swp2;
        if( a->l ) a->l->tag ^= 1;
        if( a->r ) a->r->tag ^= 1;
        a->tag = 0;
    }
}
int Size( Treap * a ){ return a ? a->sz : 0; }
void pull( Treap * a ){
    a->sz = Size( a->l ) + Size( a->r ) + 1;
}
Treap* merge( Treap *a , Treap *b ){
    if( !a || !b ) return a ? a : b;
    if( a->pri > b->pri ){
        push( a );
        a->r = merge( a->r , b );
        pull( a );
        return a;
    }else{
        push( b );
        b->l = merge( a , b->l );
        pull( b );
        return b;
    }
}
void split( Treap *t , int k , Treap*&a , Treap*&b ){
    if( !t ){ a = b = NULL; return; }
    push( t );
    if( Size( t->l ) + 1 <= k ){
        a = t;
        split( t->r , k - Size( t->l ) - 1 , a->r , b );
        pull( a );
    }else{
        b = t;
        split( t->l , k , a , b->l );
        pull( b );
    }
}
}

```

7.2 Link-Cut Tree

```

const int MXN = 100005;
const int MEM = 100005;
struct Splay {
    static Splay nil, mem[MEM], *pmem;
    Splay *ch[2], *f;
    int val, rev, size;
    Splay () : val(-1), rev(0), size(0)
    { f = ch[0] = ch[1] = &nil; }
    Splay (int _val) : val(_val), rev(0), size(1)
    { f = ch[0] = ch[1] = &nil; }
    bool isr()
    { return f->ch[0] != this && f->ch[1] != this; }
    int dir()
    { return f->ch[0] == this ? 0 : 1; }
    void setCh(Splay *c, int d){
        ch[d] = c;
        if (c != &nil) c->f = this;
        pull();
    }
    void push(){
        if( !rev ) return;
        swap(ch[0], ch[1]);
        if (ch[0] != &nil) ch[0]->rev ^= 1;
        if (ch[1] != &nil) ch[1]->rev ^= 1;
        rev=0;
    }
    void pull(){
        size = ch[0]->size + ch[1]->size + 1;
        if (ch[0] != &nil) ch[0]->f = this;
        if (ch[1] != &nil) ch[1]->f = this;
    }
}

```

```

} Splay::nil, Splay::mem[MEM], *Splay::pmem = Splay::
    mem;
Splay *nil = &Splay::nil;
void rotate(Splay *x){
    Splay *p = x->f;
    int d = x->dir();
    if (!p->isr()) p->f->setCh(x, p->dir());
    else x->f = p->f;
    p->setCh(x->ch[!d], d);
    x->setCh(p, !d);
    p->pull(); x->pull();
}
vector<Splay*> splayVec;
void splay(Splay *x){
    splayVec.clear();
    for (Splay *q=x; q=q->f){
        splayVec.push_back(q);
        if (q->isr()) break;
    }
    reverse(begin(splayVec), end(splayVec));
    for (auto it : splayVec) it->push();
    while (!x->isr()) {
        if (x->f->isr()) rotate(x);
        else if (x->dir()==x->f->dir())
            rotate(x->f), rotate(x);
        else rotate(x), rotate(x);
    }
}
Splay* access(Splay *x){
    Splay *q = nil;
    for (;x!=nil;x=x->f){
        splay(x);
        x->setCh(q, 1);
        q = x;
    }
    return q;
}
void evert(Splay *x){
    access(x);
    splay(x);
    x->rev ^= 1;
    x->push(); x->pull();
}
void link(Splay *x, Splay *y){
    // evert(x);
    access(x);
    splay(x);
    evert(y);
    x->setCh(y, 1);
}
void cut(Splay *x, Splay *y){
    // evert(x);
    access(y);
    splay(y);
    y->push();
    y->ch[0] = y->ch[0]->f = nil;
}
int N, Q;
Splay *vt[MXN];
int ask(Splay *x, Splay *y){
    access(x);
    access(y);
    splay(x);
    int res = x->f->val;
    if (res == -1) res=x->val;
    return res;
}
int main(int argc, char** argv){
    scanf("%d%d", &N, &Q);
    for (int i=1; i<=N; i++)
        vt[i] = new (Splay::pmem++) Splay(i);
    while (Q--) {
        char cmd[105];
        int u, v;
        scanf("%s", cmd);
        if (cmd[1] == 'i') {
            scanf("%d%d", &u, &v);
            link(vt[u], vt[v]);
        } else if (cmd[0] == 'c') {
            scanf("%d", &v);
            cut(vt[1], vt[v]);
        } else {

```

```

scanf("%d%d", &u, &v);
int res=ask(vt[u], vt[v]);
printf("%d\n", res);
}
}
}

```

7.3 Disjoint Set

```

struct DisjointSet{
    // save() is like recursive
    // undo() is like return
    int n, fa[ N ], sz[ N ];
    vector< pair<int*,int> > h;
    vector<int> sp;
    void init( int tn ){
        n=tn;
        for( int i = 0 ; i < n ; i ++ ){
            fa[ i ]=i;
            sz[ i ]=1;
        }
        sp.clear(); h.clear();
    }
    void assign( int *k, int v ){
        h.PB( {k, *k} );
        *k = v;
    }
    void save(){ sp.PB(SZ(h)); }
    void undo(){
        assert(!sp.empty());
        int last=sp.back(); sp.pop_back();
        while( SZ(h)!=last ){
            auto x=h.back(); h.pop_back();
            *x.first = x.second;
        }
    }
    int f( int x ){
        while( fa[ x ] != x ) x = fa[ x ];
        return x;
    }
    void uni( int x , int y ){
        x = f( x ); y = f( y );
        if( x == y ) return;
        if( sz[ x ] < sz[ y ] ) swap( x, y );
        assign( &sz[ x ], sz[ x ] + sz[ y ] );
        assign( &fa[ y ], x );
    }
}djs;

```

7.4 Leftist Heap

```

const int MAXN = 10000;
struct Node{
    int num,lc,rc;
    Node() : num(0), lc(-1), rc(-1){}
    Node( int _v ) : num(_v), lc(-1), rc(-1){}
}tree[ MAXN ];
int merge( int x, int y ){
    if( x == -1 ) return y;
    if( y == -1 ) return x;
    if( tree[ x ].num < tree[ y ].num )
        swap(x, y);
    tree[ x ].rc = merge(tree[ x ].rc, y);
    swap(tree[ x ].lc, tree[ x ].rc);
    return x;
}
/* Usage
merge: root = merge(x, y)
delmin: root = merge(root.lc, root.rc)
*/

```

7.5 Black Magic

```

#include <bits/extc++.h>
using namespace __gnu_pbds;

```

```

typedef tree<int,null_type,less<int>,rb_tree_tag,
    tree_order_statistics_node_update> set_t;
#include <ext/pb_ds/assoc_container.hpp>
typedef cc_hash_table<int,int> umap_t;
typedef priority_queue<int> heap;
int main(){
    // Insert some entries into s.
    set_t s; s.insert(12); s.insert(505);
    // The order of the keys should be: 12, 505.
    assert(*s.find_by_order(0) == 12);
    assert(*s.find_by_order(3) == 505);
    // The order of the keys should be: 12, 505.
    assert(s.order_of_key(12) == 0);
    assert(s.order_of_key(505) == 1);
    // Erase an entry.
    s.erase(12);
    // The order of the keys should be: 505.
    assert(*s.find_by_order(0) == 505);
    // The order of the keys should be: 505.
    assert(s.order_of_key(505) == 0);

    heap h1 , h2; h1.join( h2 );
}

```

8 Others

8.1 Exact Cover Set

```

// given n*m 0-1 matrix
// find a set of rows s.t.
// for each column, there's exactly one 1
#include <stdio.h>
#include <string.h>
#define N 1024 //row
#define M 1024 //column
#define NM ((N+2)*(M+2))
char A[N][M]; //n*m 0-1 matrix
int used[N]; //answer: the row used
int id[N][M];
int L[NM],R[NM],D[NM],U[NM],C[NM],S[NM],ROW[NM];
void remove(int c){
    L[R[c]]=L[c]; R[L[c]]=R[c];
    for( int i=D[c]; i!=c; i=D[i] )
        for( int j=R[i]; j!=i; j=R[j] ){
            U[D[j]]=U[j]; D[U[j]]=D[j]; S[C[j]]--;
        }
}
void resume(int c){
    for( int i=D[c]; i!=c; i=D[i] )
        for( int j=L[i]; j!=i; j=L[j] ){
            U[D[j]]=D[U[j]]=j; S[C[j]]++;
        }
    L[R[c]]=R[L[c]]=c;
}
int dfs(){
    if(R[0]==0) return 1;
    int md=100000000,c;
    for( int i=R[0]; i!=0; i=R[i] )
        if(S[i]<md){ md=S[i]; c=i; }
    if(md==0) return 0;
    remove(c);
    for( int i=D[c]; i!=c; i=D[i] ){
        used[ROW[i]]=1;
        for( int j=R[i]; j!=i; j=R[j] ) remove(C[j]);
        if(dfs()) return 1;
        for( int j=L[i]; j!=i; j=L[j] ) resume(C[j]);
        used[ROW[i]]=0;
    }
    resume(c);
    return 0;
}
int exact_cover(int n,int m){
    for( int i=0; i<=m; i++ ){
        R[i]=i+1; L[i]=i-1; U[i]=D[i]=i;
        S[i]=0; C[i]=i;
    }
    R[m]=0; L[0]=m;
    int t=m+1;
}

```

```
for( int i=0; i<n; i++ ){
    int k=-1;
    for( int j=0; j<m; j++ ){
        if(!A[i][j]) continue;
        if(k==-1) L[t]=R[t]=t;
        else{ L[t]=k; R[t]=R[k]; }
        k=t; D[t]=j+1; U[t]=U[j+1];
        L[R[t]]=R[L[t]]=U[D[t]]=D[U[t]]=t;
        C[t]=j+1; S[C[t]]++; ROW[t]=i; id[i][j]=t++;
    }
}
for( int i=0; i<n; i++ ) used[i]=0;
return dfs();
}
```