

Contents

1 Basic	1
1.1 .vimrc	1
1.2 Increase Stack Size	1
1.3 Misc	1
2 flow	1
2.1 ISAP	1
2.2 MinCostFlow	2
2.3 Dinic	2
2.4 Kuhn Munkres	3
2.5 DMST	3
2.6 SW min-cut	3
2.7 Max Cost Circulation	4
2.8 Max flow with lower/upper bound	4
2.9 Flow Method	4
3 Math	5
3.1 FFT	5
3.2 NTT	5
3.3 Fast Walsh Transform	6
3.4 Linear Recurrence	6
3.5 Miller Rabin	6
3.6 Simplex	6
3.7 Faulhaber	6
3.8 Chinese Remainder	7
3.9 Pollard Rho	7
3.10Poly Generator	8
3.11Matrix Pseudo Inverse	8
3.12ax+by=gcd	8
3.13Discrete sqrt	8
3.14SchreierSims	8
3.15Prefix Inverse	9
3.16Roots of Polynomial	9
3.17Mod	9
3.18Primes and μ function	10
3.19Result	10
4 Geometry	10
4.1 halfPlaneIntersection	10
4.2 Intersection of 2 lines	10
4.3 Intersection of 2 segments	10
4.4 Intersection of 2 circles	11
4.5 Circle cover	11
4.6 Convex Hull trick	11
4.7 Tangent line of two circles	11
4.8 KD Tree	12
4.9 Lower Concave Hull	13
4.10DeLaunay Triangulation	13
4.11Min Enclosing Circle	14
4.12Min Enclosing Ball	14
4.13Minkowski sum	15
4.14Heart of Triangle	15
5 Graph	15
5.1 HeavyLightDecomp	15
5.2 DominatorTree	16
5.3 MaxClique	16
5.4 Number of Maximal Clique	17
5.5 Strongly Connected Component	17
5.6 Dynamic MST	17
5.7 Maximum General graph Matching	18
5.8 Minimum General Weighted Matching	18
5.9 Maximum General Weighted Matching	18
5.10Minimum Steiner Tree	20
5.11BCC based on vertex	20
5.12Graph Hash	20
6 String	21
6.1 PalTree	21
6.2 SAIS	21
6.3 SuffixAutomata	21
6.4 Aho-Corasick	22
6.5 Z Value	22
6.6 BWT	22
6.7 ZValue Palindrome	22
6.8 Smallest Rotation	23
7 Data Structure	23
7.1 Treap	23
7.2 Link-Cut Tree	23
7.3 Black Magic	24
8 Others	24
8.1 # of Intersection of segments	24

1 Basic

1.1 .vimrc

```
syn on
se ai nu ru cul mouse=a
se cin et ts=2 sw=2 sts=2
so $VIMRUNTIME/mswin.vim
colo desert
se gfn=Monospace\ 14
```

1.2 Increase Stack Size

```
//stack resize
asm( "mov %0,%esp\n" ::"g"(mem+10000000) );
//change esp to rsp if 64-bit system

//stack resize (linux)
#include <sys/resource.h>
void increase_stack_size() {
    const rlim_t ks = 64*1024*1024;
    struct rlimit rl;
    int res=getrlimit(RLIMIT_STACK, &rl);
    if(res==0){
        if(rl.rlim_cur<ks){
            rl.rlim_cur=ks;
            res=setrlimit(RLIMIT_STACK, &rl);
        }
    }
}
```

1.3 Misc

```
#include <random>
mt19937 rng(0x5EED);
int randint(int lb, int ub)
{ return uniform_int_distribution<int>(lb, ub)(rng); }

#define SECS (clock() / CLOCKS_PER_SEC)

struct KeyHasher {
    size_t operator()(const Key& k) const {
        return k.first + k.second * 100000;
    }
};
typedef unordered_map<Key,int,KeyHasher> map_t;
```

2 flow

2.1 ISAP

```
#define SZ(c) ((int)(c).size())
struct Maxflow {
    static const int MAXV = 20010;
    static const int INF = 1000000;
    struct Edge {
        int v, c, r;
        Edge(int _v, int _c, int _r):
            v(_v), c(_c), r(_r) {}
    };
    int s, t;
    vector<Edge> G[MAXV*2];
    int iter[MAXV*2], d[MAXV*2], gap[MAXV*2], tot;
    void init(int x) {
        tot = x+2;
        s = x+1, t = x+2;
        for(int i = 0; i <= tot; i++) {
            G[i].clear();
            iter[i] = d[i] = gap[i] = 0;
        }
    }
    void addEdge(int u, int v, int c) {
```

```

    G[u].push_back(Edge(v, c, SZ(G[v])));
    G[v].push_back(Edge(u, 0, SZ(G[u]) - 1));
}
int dfs(int p, int flow) {
    if(p == t) return flow;
    for(int &i = iter[p]; i < SZ(G[p]); i++) {
        Edge &e = G[p][i];
        if(e.c > 0 && d[p] == d[e.v]+1) {
            int f = dfs(e.v, min(flow, e.c));
            if(f) {
                e.c -= f;
                G[e.v][e.r].c += f;
                return f;
            }
        }
    }
    if( (--gap[d[p]]) == 0) d[s] = tot;
    else {
        d[p]++;
        iter[p] = 0;
        ++gap[d[p]];
    }
    return 0;
}
int solve() {
    int res = 0;
    gap[0] = tot;
    for(res = 0; d[s] < tot; res += dfs(s, INF));
    return res;
}
} flow;

```

2.2 MinCostFlow

```

struct MinCostMaxFlow{
    typedef int Tcost;
    static const int MAXV = 20010;
    static const int INFf = 1000000;
    static const Tcost INFc = 1e9;
    struct Edge{
        int v, cap;
        Tcost w;
        int rev;
        Edge(){}
        Edge(int t2, int t3, Tcost t4, int t5)
        : v(t2), cap(t3), w(t4), rev(t5) {}
    };
    int V, s, t;
    vector<Edge> g[MAXV];
    void init(int n){
        V = n+2;
        s = n+1, t = n+2;
        for(int i = 0; i <= V; i++) g[i].clear();
    }
    void addEdge(int a, int b, int cap, Tcost w){
        g[a].push_back(Edge(b, cap, w, (int)g[b].size()));
        g[b].push_back(Edge(a, 0, -w, (int)g[a].size()-1));
    }
    Tcost d[MAXV];
    int id[MAXV], mom[MAXV];
    bool inqu[MAXV];
    queue<int> q;
    Tcost solve(){
        int mxf = 0; Tcost mnc = 0;
        while(1){
            fill(d, d+1+V, INFc);
            fill(inqu, inqu+1+V, 0);
            fill(mom, mom+1+V, -1);
            mom[s] = s;
            d[s] = 0;
            q.push(s); inqu[s] = 1;
            while(q.size()){
                int u = q.front(); q.pop();
                inqu[u] = 0;
                for(int i = 0; i < (int) g[u].size(); i++){
                    Edge &e = g[u][i];
                    int v = e.v;
                    if(e.cap > 0 && d[v] > d[u]+e.w){
                        d[v] = d[u]+e.w;
                        mom[v] = u;

```

```

                        id[v] = i;
                        if(!inqu[v]) q.push(v), inqu[v] = 1;
                    }
                }
            }
            if(mom[t] == -1) break;
            int df = INFf;
            for(int u = t; u != s; u = mom[u])
                df = min(df, g[mom[u]][id[u]].cap);
            for(int u = t; u != s; u = mom[u]){
                Edge &e = g[mom[u]][id[u]];
                e.cap -= df;
                g[e.v][e.rev].cap += df;
            }
            mxf += df;
            mnc += df*d[t];
        }
        return mnc;
    }
} flow;

```

2.3 Dinic

```

struct Dinic{
    static const int MXN = 10000;
    struct Edge{ int v,f,re; };
    int n,s,t,level[MXN];
    vector<Edge> E[MXN];
    void init(int _n, int _s, int _t){
        n = _n; s = _s; t = _t;
        for (int i=0; i<n; i++) E[i].clear();
    }
    void add_edge(int u, int v, int f){
        E[u].PB({v,f,SZ(E[v])});
        E[v].PB({u,0,SZ(E[u])-1});
    }
    bool BFS(){
        for (int i=0; i<n; i++) level[i] = -1;
        queue<int> que;
        que.push(s);
        level[s] = 0;
        while (!que.empty()){
            int u = que.front(); que.pop();
            for (auto it : E[u]){
                if (it.f > 0 && level[it.v] == -1){
                    level[it.v] = level[u]+1;
                    que.push(it.v);
                }
            }
        }
        return level[t] != -1;
    }
    int DFS(int u, int nf){
        if (u == t) return nf;
        int res = 0;
        for (auto &it : E[u]){
            if (it.f > 0 && level[it.v] == level[u]+1){
                int tf = DFS(it.v, min(nf,it.f));
                res += tf; nf -= tf; it.f -= tf;
                E[it.v][it.re].f += tf;
                if (nf == 0) return res;
            }
        }
        return 0;
    }
    int flow(int res=0){
        while (BFS())
            res += DFS(s,2147483647);
        return res;
    }
}flow;

```

2.4 Kuhn Munkres

```

struct KM{
// Maximum Bipartite Weighted Matching (Perfect Match)
static const int MXN = 650;
static const int INF = 2147483647; // long long
int n, match[MXN], vx[MXN], vy[MXN];
int edge[MXN][MXN], lx[MXN], ly[MXN], slack[MXN];
// ^^^^ long long
void init(int _n){
    n = _n;
    for (int i=0; i<n; i++){
        for (int j=0; j<n; j++){
            edge[i][j] = 0;
        }
    }
void add_edge(int x, int y, int w){ // long long
    edge[x][y] = w;
}
bool DFS(int x){
    vx[x] = 1;
    for (int y=0; y<n; y++){
        if (vy[y]) continue;
        if (lx[x]+ly[y] > edge[x][y]){
            slack[y] = min(slack[y], lx[x]+ly[y]-edge[x][y]);
        } else {
            vy[y] = 1;
            if (match[y] == -1 || DFS(match[y])){
                match[y] = x;
                return true;
            }
        }
    }
    return false;
}
int solve(){
    fill(match, match+n, -1);
    fill(lx, lx+n, -INF);
    fill(ly, ly+n, 0);
    for (int i=0; i<n; i++){
        for (int j=0; j<n; j++){
            lx[i] = max(lx[i], edge[i][j]);
        }
    }
    for (int i=0; i<n; i++){
        fill(slack, slack+n, INF);
        while (true){
            fill(vx, vx+n, 0);
            fill(vy, vy+n, 0);
            if (DFS(i)) break;
            int d = INF; // long long
            for (int j=0; j<n; j++){
                if (!vy[j]) d = min(d, slack[j]);
            }
            for (int j=0; j<n; j++){
                if (vx[j]) lx[j] -= d;
                if (vy[j]) ly[j] += d;
                else slack[j] -= d;
            }
        }
    }
    int res=0;
    for (int i=0; i<n; i++){
        res += edge[match[i]][i];
    }
    return res;
}
}graph;

```

2.5 DMST

```

/*
 * Edmond's algorithm for Directed MST
 * runs in O(VE)
 */
const int MAXV = 10010;
const int MAXE = 10010;
const int INF = 2147483647;
struct Edge{
    int u, v, c;
    Edge(){
    }
    Edge(int x, int y, int z) :
        u(x), v(y), c(z){
    }
}

```

```

};
int V, E, root;
Edge edges[MAXE];
inline int newV(){
    V++;
    return V;
}
inline void addEdge(int u, int v, int c){
    E++;
    edges[E] = Edge(u, v, c);
}
bool con[MAXV];
int mnInW[MAXV], prv[MAXV], cyc[MAXV], vis[MAXV];
inline int DMST(){
    fill(con, con+V+1, 0);
    int r1 = 0, r2 = 0;
    while(1){
        fill(mnInW, mnInW+V+1, INF);
        fill(prv, prv+V+1, -1);
        REP(i, 1, E){
            int u=edges[i].u, v=edges[i].v, c=edges[i].c;
            if(u != v && v != root && c < mnInW[v]){
                mnInW[v] = c, prv[v] = u;
            }
        }
        fill(vis, vis+V+1, -1);
        fill(cyc, cyc+V+1, -1);
        r1 = 0;
        bool jf = 0;
        REP(i, 1, V){
            if(con[i]) continue;
            if(prv[i] == -1 && i != root) return -1;
            if(prv[i] > 0) r1 += mnInW[i];
            int s;
            for(s = i; s != -1 && vis[s] == -1; s = prv[s]){
                vis[s] = i;
            }
            if(s > 0 && vis[s] == i){
                // get a cycle
                jf = 1;
                int v = s;
                do{
                    cyc[v] = s, con[v] = 1;
                    r2 += mnInW[v];
                    v = prv[v];
                }while(v != s);
                con[s] = 0;
            }
        }
        if(!jf) break;
        REP(i, 1, E){
            int &u = edges[i].u;
            int &v = edges[i].v;
            if(cyc[v] > 0) edges[i].c -= mnInW[edges[i].v];
            if(cyc[u] > 0) edges[i].u = cyc[edges[i].u];
            if(cyc[v] > 0) edges[i].v = cyc[edges[i].v];
            if(u == v) edges[i--] = edges[E--];
        }
    }
    return r1+r2;
}

```

2.6 SW min-cut

```

// global min cut
struct SW{ // O(V^3)
static const int MXN = 514;
int n, vst[MXN], del[MXN];
int edge[MXN][MXN], wei[MXN];
void init(int _n){
    n = _n;
    FZ(edge);
    FZ(del);
}
void add_edge(int u, int v, int w){
    edge[u][v] += w;
    edge[v][u] += w;
}
void search(int &s, int &t){
    FZ(vst); FZ(wei);
    s = t = -1;
    while (true){

```

```

int mx=-1, cur=0;
for (int i=0; i<n; i++){
    if (!del[i] && !vst[i] && mx<wei[i])
        cur = i, mx = wei[i];
    if (mx == -1) break;
    vst[cur] = 1;
    s = t;
    t = cur;
    for (int i=0; i<n; i++){
        if (!vst[i] && !del[i]) wei[i] += edge[cur][i];
    }
}
int solve(){
    int res = 2147483647;
    for (int i=0,x,y; i<n-1; i++){
        search(x,y);
        res = min(res,wei[y]);
        del[y] = 1;
        for (int j=0; j<n; j++){
            edge[x][j] = (edge[j][x] += edge[y][j]);
        }
    }
    return res;
}
}graph;

```

2.7 Max Cost Circulation

```

struct MaxCostCirc {
    static const int MAXN = 33;
    int n, m;
    struct Edge {
        int v, w, c, r;
    };
    vector<Edge> g[ MAXN ];
    int dis[ MAXN ], prv[ MAXN ], prve[ MAXN ];
    bool vis[ MAXN ];
    int ans;
    void init( int _n, int _m ) : n(_n), m(_m) {}
    void adde( int u, int v, int w, int c ) {
        g[ u ].push_back( { v, w, c, SZ( g[ v ] ) } );
        g[ v ].push_back( { u, -w, 0, SZ( g[ u ] )-1 } );
    }
    bool poscyc() {
        fill( dis, dis+n+1, 0 );
        fill( prv, prv+n+1, 0 );
        fill( vis, vis+n+1, 0 );
        int tmp = -1;
        FOR( t, n+1 ) {
            REP( i, 1, n ) {
                FOR( j, SZ( g[ i ] ) ) {
                    Edge& e = g[ i ][ j ];
                    if( e.c && dis[ e.v ] < dis[ i ]+e.w ) {
                        dis[ e.v ] = dis[ i ]+e.w;
                        prv[ e.v ] = i;
                        prve[ e.v ] = j;
                        if( t == n ) {
                            tmp = i;
                            break;
                        }
                    }
                }
            }
        }
        if( tmp == -1 ) return 0;
        int cur = tmp;
        while( !vis[ cur ] ) {
            vis[ cur ] = 1;
            cur = prv[ cur ];
        }
        int now = cur;
        int cost = 0, df = 100000;
        do{
            Edge &e = g[ prv[ now ] ][ prve[ now ] ];
            df = min( df, e.c );
            cost += e.w;
            now = prv[ now ];
        }while( now != cur );
        ans += df*cost;
        now = cur;
    }
};

```

```

do{
    Edge &e = g[ prv[ now ] ][ prve[ now ] ];
    Edge &re = g[ now ][ e.r ];
    e.c -= df;
    re.c += df;
    now = prv[ now ];
}while( now != cur );
return 1;
}
} circ;

```

2.8 Max flow with lower/upper bound

```

// Max flow with lower/upper bound on edges
// source = 1, sink = n
int in[ N ], out[ N ];
int l[ M ], r[ M ], a[ M ], b[ M ];
int solve(){
    flow.init( n );
    for( int i = 0 ; i < m ; i ++ ){
        in[ r[ i ] ] += a[ i ];
        out[ l[ i ] ] += a[ i ];
        flow.addEdge( l[ i ], r[ i ], b[ i ] - a[ i ] );
        // flow on edge from l[ i ] to r[ i ] should
        // be in [a[ i ], b[ i ]].
    }
    int nd = 0;
    for( int i = 1 ; i <= n ; i ++ ){
        if( in[ i ] < out[ i ] ){
            flow.addEdge( i, flow.t, out[ i ] - in[ i ] );
            nd += out[ i ] - in[ i ];
        }
        if( out[ i ] < in[ i ] ){
            flow.addEdge( flow.s, i, in[ i ] - out[ i ] );
        }
    }
    // original sink to source
    flow.addEdge( n, 1, INF );
    if( flow.maxflow() != nd )
        // no solution
        return -1;
    int ans = flow.G[ 1 ].back().c; // source to sink
    flow.G[ 1 ].back().c = flow.G[ n ].back().c = 0;
    // take out super source and super sink
    for( size_t i = 0 ; i < flow.G[ flow.s ].size() ; i
        ++ ){
        flow.G[ flow.s ][ i ].c = 0;
        Edge &e = flow.G[ flow.s ][ i ];
        flow.G[ e.v ][ e.r ].c = 0;
    }
    for( size_t i = 0 ; i < flow.G[ flow.t ].size() ; i
        ++ ){
        flow.G[ flow.t ][ i ].c = 0;
        Edge &e = flow.G[ flow.t ][ i ];
        flow.G[ e.v ][ e.r ].c = 0;
    }
    flow.addEdge( flow.s, 1, INF );
    flow.addEdge( n, flow.t, INF );
    flow.reset();
    return ans + flow.maxflow();
}

```

2.9 Flow Method

Maximize $c^T x$ subject to $Ax \leq b, x \geq 0$;
with the corresponding symmetric dual problem,
Minimize $b^T y$ subject to $A^T y \geq c, y \geq 0$.

Maximize $c^T x$ subject to $Ax \leq b$;
with the corresponding asymmetric dual problem,
Minimize $b^T y$ subject to $A^T y = c, y \geq 0$.

Minimum vertex cover on bipartite graph =
Maximum matching on bipartite graph =
Max flow with source to one side, other side to sink

To reconstruct the minimum vertex cover, dfs from each unmatched vertex on the left side and with unused edges

only. Equivalently, dfs from source with unused edges only **and** without visiting sink. Then, a vertex is chosen
 iff. it is on the left side **and** without visited **or** on the right side **and** visited through dfs.

Maximum density subgraph ($\sum W_e + \sum W_v$) / $|V|$

Binary search on answer:

For a fixed D, construct a Max flow model as follow:

Let S be Sum of all weight(**or** inf)

1. from source to each node with cap = S
2. For each (u,v,w) in E, (u→v, cap=w), (v→u, cap=w)
3. For each node v, from v to sink with cap = S + 2 * D - deg[v] - 2 * (W of v)

where deg[v] = \sum weight of edge associated with v

If maxflow < S * |V|, D is an answer.

Requiring subgraph: all vertex can be reached from source with edge whose cap > 0.

3 Math

3.1 FFT

```
// const int MAXN = 262144;
// (must be 2^k)
// before any usage, run pre_fft() first
//
// To implement poly. multiply:
//
// fft( n , a );
// fft( n , b );
// for( int i = 0 ; i < n ; i++ )
//   c[ i ] = a[ i ] * b[ i ];
// fft( n , c , 1 );
//
// then you have the result in c :: [cplx]
typedef long double ld;
typedef complex<ld> cplx;
const ld PI = acos(-1);
const cplx I(0, 1);
cplx omega[MAXN+1];
void pre_fft(){
    for(int i=0; i<=MAXN; i++)
        omega[i] = exp(i * 2 * PI / MAXN * I);
}
// n must be 2^k
void fft(int n, cplx a[], bool inv=false){
    int basic = MAXN / n;
    int theta = basic;
    for (int m = n; m >= 2; m >= 1) {
        int mh = m >> 1;
        for (int i = 0; i < mh; i++) {
            cplx w = omega[inv ? MAXN-(i*theta%MAXN) : i*theta%MAXN];
            for (int j = i; j < n; j += m) {
                int k = j + mh;
                cplx x = a[j] - a[k];
                a[j] += a[k];
                a[k] = w * x;
            }
        }
        theta = (theta * 2) % MAXN;
    }
    int i = 0;
    for (int j = 1; j < n - 1; j++) {
        for (int k = n >> 1; k > (i ^= k); k >= 1);
        if (j < i) swap(a[i], a[j]);
    }
    if (inv)
        for (i = 0; i < n; i++)
            a[i] /= n;
}
```

3.2 NTT

```
typedef long long LL;
// Remember coefficient are mod P
/* p=a*2^n+1
n  2^n      p      a      root
5   32      97      3      5
6   64      193     3      5
7  128      257     2      3
8  256      257     1      3
9  512      7681    15     17
10 1024     12289    12     11
11 2048     12289     6     11
12 4096     12289     3     11
13 8192     40961     5      3
14 16384    65537     4      3
15 32768    65537     2      3
16 65536    65537     1      3
17 131072   786433    6     10
18 262144   786433     3     10 (605028353,
2308, 3)
19 524288   5767169   11      3
20 1048576  7340033    7      3
21 2097152  23068673   11      3
22 4194304  104857601  25      3
23 8388608  167772161  20      3
24 16777216 167772161  10      3
25 33554432 167772161  5       3 (1107296257, 33,
10)
26 67108864 469762049  7       3
27 134217728 2013265921 15      31 */
// (must be 2^k)
// To implement poly. multiply:
// ntt( n , a ); // or ntt.tran( n , a );
// ntt( n , b );
// for( int i = 0 ; i < n ; i++ )
//   c[ i ] = a[ i ] * b[ i ];
// ntt( n , c , 1 );
//
// then you have the result in c :: [LL]
template<LL P, LL root, int MAXN>
struct NTT{
    static LL bigmod(LL a, LL b) {
        LL res = 1;
        for (LL bs = a; b; b >= 1, bs = (bs * bs) % P) {
            if(b&1) res=(res*bs)%P;
        }
        return res;
    }
    static LL inv(LL a, LL b) {
        if(a==1)return 1;
        return (((LL)(a-inv(b*a,a))*b+1)/a)%b;
    }
    LL omega[MAXN+1];
    NTT() {
        omega[0] = 1;
        LL r = bigmod(root, (P-1)/MAXN);
        for (int i=1; i<=MAXN; i++)
            omega[i] = (omega[i-1]*r)%P;
    }
    // n must be 2^k
    void tran(int n, LL a[], bool inv_ntt=false){
        int basic = MAXN / n;
        int theta = basic;
        for (int m = n; m >= 2; m >= 1) {
            int mh = m >> 1;
            for (int i = 0; i < mh; i++) {
                LL w = omega[i*theta%MAXN];
                for (int j = i; j < n; j += m) {
                    int k = j + mh;
                    LL x = a[j] - a[k];
                    if (x < 0) x += P;
                    a[j] += a[k];
                    if (a[j] > P) a[j] -= P;
                    a[k] = (w * x) % P;
                }
            }
            theta = (theta * 2) % MAXN;
        }
        int i = 0;
```

```

    for (int j = 1; j < n - 1; j++) {
        for (int k = n >> 1; k > (i ^ k); k >= 1);
        if (j < i) swap(a[i], a[j]);
    }
    if (inv_ntt) {
        LL ni = inv(n,P);
        reverse(a+1, a+n);
        for (i = 0; i < n; i++)
            a[i] = (a[i] * ni) % P;
    }
}
void operator()(int n, LL a[], bool inv_ntt=false) {
    tran(n, a, inv_ntt);
}
};
const LL P=2013265921, root=31;
const int MAXN=4194304;
NTT<P, root, MAXN> ntt;

```

3.3 Fast Walsh Transform

```

/* xor convolution:
 * x = (x0,x1), y = (y0,y1)
 * z = (x0y0 + x1y1, x0y1 + x1y0)
 * =>
 * x' = (x0+x1, x0-x1), y' = (y0+y1, y0-y1)
 * z' = ((x0+x1)(y0+y1), (x0-x1)(y0-y1))
 * z = (1/2) * z'
 * or convolution:
 * x = (x0, x0+x1), inv = (x0, x1-x0) w/o final div
 * and convolution:
 * x = (x0+x1, x1), inv = (x0-x1, x1) w/o final div */
typedef long long LL;
const int MAXN = (1<<20)+10;
const LL MOD = 1e9+7;
inline LL pw(LL x, LL k) {
    LL res = 1;
    for (LL bs = x; k; k >>= 1, bs = (bs * bs) % MOD) {
        if (k&1) res = (res * bs) % MOD;
    }
    return res;
}
inline LL inv(LL x) {
    return pw(x, MOD-2);
}
inline void fwt(LL x[ MAXN ], int N, bool inv=0) {
    for (int d = 1; d < N; d <= 1) {
        int d2 = d<<1;
        for (int s = 0; s < N; s += d2) {
            for (int i = s, j = s+d; i < s+d; i++, j++) {
                LL ta = x[i], tb = x[j];
                x[i] = ta+tb;
                x[j] = ta-tb;
                if (x[i] >= MOD) x[i] -= MOD;
                if (x[j] < 0) x[j] += MOD;
            }
        }
    }
    if (inv)
        for (int i = 0; i < N; i++) {
            x[i] *= inv(N);
            x[i] %= MOD;
        }
}

```

3.4 Linear Recurrence

```

LL n, m;
LL dp[ N + N ];
void pre_dp() {
    dp[0] = 1;
    LL bdr = min(m + m, n);
    for (LL i = 1; i <= bdr; i++)
        for (LL j = i - 1; j >= max(0LL, i - m); j--)
            dp[i] = add(dp[i], dp[j]);
}
vector<LL> Mul(vector<LL>& v1, vector<LL>& v2) {
    int _sz1 = (int)v1.size();

```

```

    int _sz2 = (int)v2.size();
    assert(_sz1 == m);
    assert(_sz2 == m);
    vector<LL> _v(m + m);
    for (int i = 0; i < m + m; i++) _v[i] = 0;
    // expand
    for (int i = 0; i < _sz1; i++)
        for (int j = 0; j < _sz2; j++)
            _v[i + j + 1] = add(_v[i + j + 1], mul(v1[i], v2[j]));
    // shrink
    for (int i = 0; i < m; i++)
        for (int j = 1; j <= m; j++)
            _v[i + j] = add(_v[i + j], _v[i]);
    for (int i = 0; i < m; i++)
        _v[i] = _v[i + m];
    _v.resize(m);
    return _v;
}
vector<LL> I, A;
void solve() {
    pre_dp();
    if (n <= m + m) {
        printf("%lld\n", dp[n]); exit(0);
    }
    I.resize(m); A.resize(m);
    for (int i = 0; i < m; i++) I[i] = A[i] = 1;
    // dp[n] = Sum_{i=0}^{m-1} A_i * dp[n - i - 1]
    LL dlt = (n - m) / m, rdl = dlt * m;
    while (dlt) {
        if (dlt & 1LL) I = Mul(I, A);
        A = Mul(A, A);
        dlt >>= 1;
    }
    LL ans = 0;
    for (int i = 0; i < m; i++)
        ans = add(ans, mul(I[i], dp[n - i - 1 - rdl]));
    printf("%lld\n", ans);
}

```

3.5 Miller Rabin

```

// n < 4,759,123,141      3 : 2, 7, 61
// n < 1,122,004,669,633  4 : 2, 13, 23, 1662803
// n < 3,474,749,660,383  6 : pimes <= 13
// n < 2^64               7 :
// 2, 325, 9375, 28178, 450775, 9780504, 1795265022
// Make sure testing integer is in range [2, n-2] if
// you want to use magic.
bool witness(LL a, LL n, LL u, int t) {
    LL x = mypow(a, u, n);
    for (int i = 0; i < t; i++) {
        LL nx = mul(x, x, n);
        if (nx == 1 && x != 1 && x != n-1) return 1;
        x = nx;
    }
    return x != 1;
}
bool miller_rabin(LL n, int s=100) {
    // iterate s times of witness on n
    // return 1 if prime, 0 otherwise
    if (n < 2) return 0;
    if (!(n&1)) return n == 2;
    LL u = n-1; int t = 0;
    // n-1 = u*2^t
    while (!(u&1)) u >>= 1, t++;
    while (s--) {
        LL a = randll() % (n-1) + 1;
        if (witness(a, n, u, t)) return 0;
    }
    return 1;
}

```

3.6 Simplex

```

const int MAXN = 111;
const int MAXM = 111;
const double eps = 1E-10;
double a[MAXN][MAXM], b[MAXN], c[MAXN], d[MAXN][MAXM];

```



```

double x[MAXM];
int ix[MAXN + MAXM]; // !!! array all indexed from 0
// max{cx} subject to {Ax<=b,x>=0}
// n: constraints, m: vars !!!
// x[] is the optimal solution vector
// usage :
// value = simplex(a, b, c, N, M);
double simplex(double a[MAXN][MAXM], double b[MAXN],
               double c[MAXM], int n, int m){
    ++m;
    int r = n, s = m - 1;
    memset(d, 0, sizeof(d));
    for (int i = 0; i < n + m; ++i) ix[i] = i;
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < m - 1; ++j) d[i][j] = -a[i][j];
        d[i][m - 1] = 1;
        d[i][m] = b[i];
        if (d[r][m] > d[i][m]) r = i;
    }
    for (int j = 0; j < m - 1; ++j) d[n][j] = c[j];
    d[n + 1][m - 1] = -1;
    for (double dd;; ) {
        if (r < n) {
            int t = ix[s]; ix[s] = ix[r + m]; ix[r + m] = t;
            d[r][s] = 1.0 / d[r][s];
            for (int j = 0; j <= m; ++j)
                if (j != s) d[r][j] *= -d[r][s];
            for (int i = 0; i <= n + 1; ++i) if (i != r) {
                for (int j = 0; j <= m; ++j) if (j != s)
                    d[i][j] += d[r][j] * d[i][s];
                d[i][s] *= d[r][s];
            }
        }
        r = -1; s = -1;
        for (int j = 0; j < m; ++j)
            if (s < 0 || ix[s] > ix[j]) {
                if (d[n + 1][j] > eps ||
                    (d[n + 1][j] > -eps && d[n][j] > eps))
                    s = j;
            }
        if (s < 0) break;
        for (int i = 0; i < n; ++i) if (d[i][s] < -eps) {
            if (r < 0 ||
                (dd = d[r][m] / d[r][s] - d[i][m] / d[i][s]) < -eps ||
                (dd < eps && ix[r + m] > ix[i + m]))
                r = i;
        }
        if (r < 0) return -1; // not bounded
    }
    if (d[n + 1][m] < -eps) return -1; // not executable
    double ans = 0;
    for (int i = 0; i < m; ++i) x[i] = 0;
    for (int i = m; i < n + m; ++i) { // the missing
        enumerated x[i] = 0
        if (ix[i] < m - 1) {
            ans += d[i - m][m] * c[ix[i]];
            x[ix[i]] = d[i - m][m];
        }
    }
    return ans;
}

```

3.7 Faulhaber

```

/* faulhaber 's formula -
 * cal power sum formula of all p=1~k in O(k^2) */
#define MAXK 2500
const int mod = 1000000007;
int b[MAXK];
// bernoulli number
int inv[MAXK+1];
// inverse
int cm[MAXK+1][MAXK+1]; // combinatorics
int co[MAXK][MAXK+2];
// coeeficient of x^j when p=i
inline int getinv(int x) {
    int a=x, b=mod, a0=1, a1=0, b0=0, b1=1;
    while(b) {
        int q,t;

```

```

        q=a/b; t=b; b=a-b*q; a=t;
        t=b0; b0=a0-b0*q; a0=t;
        t=b1; b1=a1-b1*q; a1=t;
    }
    return a0<0?a0+mod:a0;
}
inline void pre() {
    /* combinational */
    for (int i=0; i<=MAXK; i++) {
        cm[i][0]=cm[i][i]=1;
        for (int j=1; j<i; j++)
            cm[i][j]=add(cm[i-1][j-1], cm[i-1][j]);
    }
    /* inverse */
    for (int i=1; i<=MAXK; i++) inv[i]=getinv(i);
    /* bernoulli */
    b[0]=1; b[1]=getinv(2); // with b[1] = 1/2
    for (int i=2; i<=MAXK; i++) {
        if (i&1) { b[i]=0; continue; }
        b[i]=1;
        for (int j=0; j<i; j++)
            b[i]=sub(b[i], mul(cm[i][j], mul(b[j], inv[i-j+1])));
    }
    /* faulhaber */
    // sigma_x=1~n {x^p} = 1/(p+1) * sigma_j=0~p { C(p+1, j) * B_j * n^(p-j+1) }
    for (int i=1; i<=MAXK; i++) {
        co[i][0]=0;
        for (int j=0; j<=i; j++)
            co[i][i-j+1]= mul(inv[i+1], mul(cm[i+1][j], b[j]));
    }
}
/* sample usage: return f(n,p) = sigma_x=1~n (x^p) */
inline int solve(int n, int p) {
    int sol=0, m=n;
    for (int i=1; i<=p+1; i++) {
        sol=add(sol, mul(co[p][i], m));
        m = mul(m, n);
    }
    return sol;
}

```

3.8 Chinese Remainder

```

int pfn;
// number of distinct prime factors
int pf[MAXN]; // prime factor powers
int rem[MAXN]; // corresponding remainder
int pm[MAXN];
inline void generate_primes() {
    int i, j;
    pnum=1;
    prime[0]=2;
    for (i=3; i<=MAXVAL; i+=2) {
        if (nprime[i]) continue;
        prime[pnum++] = i;
        for (j=i*i; j<=MAXVAL; j+=i) nprime[j]=1;
    }
}
inline int inverse(int x, int p) {
    int q, tmp, a=x, b=p;
    int a0=1, a1=0, b0=0, b1=1;
    while(b) {
        q=a/b; tmp=b; b=a-b*q; a=tmp;
        tmp=b0; b0=a0-b0*q; a0=tmp;
        tmp=b1; b1=a1-b1*q; a1=tmp;
    }
    return a0;
}
inline void decompose_mod() {
    int i, p, t=mod;
    pfn=0;
    for (i=0; i<pnum && prime[i]<=t; i++) {
        p=prime[i];
        if (t%p==0) {
            pf[pfn]=1;
            while (t%p==0) {
                t/=p;

```

```

        pf[pfn]*=p;
    }
    pfn++;
}
if(t>1) pf[pfn++]=t;
}
inline int chinese_remainder() {
    int i,m,s=0;
    for(i=0;i<pfn;i++) {
        m=mod/pf[i];
        pm[i]=(LL)m*inverse(m,pf[i])%mod;
        s=(s+(LL)pm[i]*rem[i])%mod;
    }
    return s;
}

```

3.9 Pollard Rho

```

// does not work when n is prime
LL f(LL x, LL mod){
    return add(mul(x,x,mod),1,mod);
}
LL pollard_rho(LL n) {
    if(!(n&1)) return 2;
    while(true){
        LL y=2, x=rand()%(n-1)+1, res=1;
        for(int sz=2; res==1; sz*=2) {
            for(int i=0; i<sz && res<=1; i++) {
                x = f(x, n);
                res = __gcd(abs(x-y), n);
            }
            y = x;
        }
        if (res!=0 && res!=n) return res;
    }
}

```

3.10 Poly Generator

```

struct PolyGen{
    /* for a nth-order polynomial f(x), *
    * given f(0), f(1), ..., f(n) *
    * express f(x) as sigma_i{c_i*C(x,i)} */
    int n;
    vector<LL> coef;
    // initialize and calculate f(x), vector _fx should
    // be filled with f(0) to f(n)
    PolyGen(int _n,vector<LL> _fx):n(_n),coef(_fx){
        for(int i=0;i<n;i++){
            for(int j=n;j>i;j--){
                coef[j]-=coef[j-1];
            }
        }
        // evaluate f(x), runs in O(n)
        LL eval(int x){
            LL m=1, ret=0;
            for(int i=0;i<=n;i++){
                ret+=coef[i]*m;
                m=m*(x-i)/(i+1);
            }
            return ret;
        }
    }
};

```

3.11 Matrix Pseudo Inverse

```

Mat pinv( Mat m ){
    Mat res = I;
    FZ( used );
    for( int i = 0 ; i < W ; i ++ ){
        int piv = -1;
        for( int j = 0 ; j < W ; j ++ ){
            if( used[ j ] ) continue;
            if( abs( m.v[ j ][ i ] ) > EPS ){
                piv = j;
                break;
            }
        }
    }
}

```

```

    }
}
if( piv == -1 ) continue;
used[ i ] = true;
swap( m.v[ piv ], m.v[ i ] );
swap( res.v[ piv ], res.v[ i ] );
LD rat = m.v[ i ][ i ];
for( int j = 0 ; j < W ; j ++ ){
    m.v[ i ][ j ] /= rat;
    res.v[ i ][ j ] /= rat;
}
for( int j = 0 ; j < W ; j ++ ){
    if( j == i ) continue;
    rat = m.v[ j ][ i ];
    for( int k = 0 ; k < W ; k ++ ){
        m.v[ j ][ k ] -= rat * m.v[ i ][ k ];
        res.v[ j ][ k ] -= rat * res.v[ i ][ k ];
    }
}
}
for( int i = 0 ; i < W ; i ++ ){
    if( used[ i ] ) continue;
    for( int j = 0 ; j < W ; j ++ )
        res.v[ i ][ j ] = 0;
}
return res;
}

```

3.12 ax+by=gcd

```

PII gcd(int a, int b){
    if(b == 0) return {1, 0};
    PII q = gcd(b, a % b);
    return {q.second, q.first - q.second * (a / b)};
}

```

3.13 Discrete sqrt

```

void calch(int &t, int &h, const int p) {
    int tmp=p-1; for(t=0;(tmp&1)==0;tmp/=2) t++; h=tmp;
}
// solve equation x^2 mod p = a
bool solve(int a, int p, int &x, int &y) {
    if(p == 2) { x = y = 1; return true; }
    int p2 = p / 2, tmp = mypow(a, p2, p);
    if (tmp == p - 1) return false;
    if ((p + 1) % 4 == 0) {
        x=mypow(a,(p+1)/4,p); y=p-x; return true;
    } else {
        int t, h, b, pb; calch(t, h, p);
        if (t >= 2) {
            do {b = rand() % (p - 2) + 2;
                while (mypow(b, p / 2, p) != p - 1);
                pb = mypow(b, h, p);
            } int s = mypow(a, h / 2, p);
            for (int step = 2; step <= t; step++) {
                int ss = (((LL)(s * s) % p) * a) % p;
                for(int i=0;i<t-step;i++) ss=mul(ss,ss,p);
                if (ss + 1 == p) s = (s * pb) % p;
                pb = ((LL)pb * pb) % p;
            } x = ((LL)s * a) % p; y = p - x;
        } return true;
    }
}

```

3.14 SchreierSims

```

// time: O(n^2 lg^3 |G| + t n lg |G|)
// mem : O(n^2 lg |G| + tn)
// t : number of generator
namespace SchreierSimsAlgorithm{
    typedef vector<int> Permu;
    Permu inv( const Permu& p ){
        Permu ret( p.size() );
        for( int i = 0 ; i < int(p.size()); i ++ )
            ret[ p[ i ] ] = i;
        return ret;
    }
}

```



```

}
Permu operator*( const Permu& a, const Permu& b ){
    Permu ret( a.size() );
    for( int i = 0 ; i < (int)a.size(); i ++ )
        ret[ i ] = b[ a[ i ] ];
    return ret;
}
typedef vector<Permu> Bucket;
typedef vector<int> Table;
typedef pair<int,int> pii;
int n, m;
vector<Bucket> bkts, bktsInv;
vector<Table> lookup;
int fastFilter( const Permu &g, bool addToG = 1 ){
    n = bkts.size();
    Permu p;
    for( int i = 0 ; i < n ; i ++ ){
        int res = lookup[ i ][ p[ i ] ];
        if( res == -1 ){
            if( addToG ){
                bkts[ i ].push_back( p );
                bktsInv[ i ].push_back( inv( p ) );
                lookup[ i ][ p[ i ] ] = (int)bkts[i].size()-1;
            }
            return i;
        }
        p = p * bktsInv[i][res];
    }
    return -1;
}
long long calcTotalSize(){
    long long ret = 1;
    for( int i = 0 ; i < n ; i ++ )
        ret *= bkts[i].size();
    return ret;
}
bool inGroup( const Permu &g ){
    return fastFilter( g, false ) == -1;
}
void solve( const Bucket &gen, int _n ){
    n = _n, m = gen.size(); // m perm[0..n-1]s
    //clear all
    bkts.clear();
    bktsInv.clear();
    lookup.clear();
    for(int i = 0 ; i < n ; i ++ ){
        lookup[i].resize(n);
        fill(lookup[i].begin(), lookup[i].end(), -1);
    }
    Permu id( n );
    for(int i = 0 ; i < n ; i ++ ) id[i] = i;
    for(int i = 0 ; i < n ; i ++ ){
        bkts[i].push_back(id);
        bktsInv[i].push_back(id);
        lookup[i][i] = 0;
    }
    for(int i = 0 ; i < m ; i ++ )
        fastFilter( gen[i] );
    queue< pair<pii,pii> > toUpd;
    for(int i = 0; i < n; i ++ )
        for(int j = i; j < n; j ++ )
            for(int k = 0; k < (int)bkts[i].size(); k ++ )
                for(int l = 0; l < (int)bkts[j].size(); l ++ )
                    toUpd.push( {pii(i,k), pii(j,l)} );
    while( !toUpd.empty() ){
        pii a = toUpd.front().first;
        pii b = toUpd.front().second;
        toUpd.pop();
        int res = fastFilter(bkts[a.first][a.second] *
                            bkts[b.first][b.second]);
        if(res == -1) continue;
        pii newPair(res, (int)bkts[res].size() - 1);
        for(int i = 0; i < n; i ++ )
            for(int j = 0; j < (int)bkts[i].size(); ++j){
                if(i <= res)
                    toUpd.push(make_pair(pii(i, j), newPair));
                if(res <= i)
                    toUpd.push(make_pair(newPair, pii(i, j)));
            }
    }
}
}

```

```

|}

```

3.15 Prefix Inverse

```

void solve( int m ){
    inv[ 1 ] = 1;
    for( int i = 2 ; i < m ; i ++ )
        inv[ i ] = ((LL)(m - m / i) * inv[m % i]) % m;
}

```

3.16 Roots of Polynomial

```

const double eps = 1e-12;
const double inf = 1e+12;
double a[ 10 ], x[ 10 ];
int n;
int sign( double x ){
    return (x < -eps)?(-1):(x>eps);
}
double f(double a[], int n, double x){
    double tmp=1,sum=0;
    for(int i=0;i<=n;i++){
        sum=sum+a[i]*tmp;
        tmp=tmp*x;
    }
    return sum;
}
double binary(double l,double r,double a[],int n){
    int sl=sign(f(a,n,l)),sr=sign(f(a,n,r));
    if(sl==0) return l;
    if(sr==0) return r;
    if(sl*sr>0) return inf;
    while(r-l>eps){
        double mid=(l+r)/2;
        int ss=sign(f(a,n,mid));
        if(ss==0) return mid;
        if(ss*sl>0) l=mid; else r=mid;
    }
    return l;
}
void solve(int n,double a[],double x[],int &nx){
    if(n==1){
        x[1]=-a[0]/a[1];
        nx=1;
        return;
    }
    double da[10], dx[10];
    int ndx;
    for(int i=n;i>=1;i--) da[i-1]=a[i]*i;
    solve(n-1,da,dx,ndx);
    nx=0;
    if(ndx==0){
        double tmp=binary(-inf,inf,a,n);
        if (tmp<inf) x[++nx]=tmp;
        return;
    }
    double tmp;
    tmp=binary(-inf,dx[1],a,n);
    if(tmp<inf) x[++nx]=tmp;
    for(int i=1;i<=ndx-1;i++){
        tmp=binary(dx[i],dx[i+1],a,n);
        if(tmp<inf) x[++nx]=tmp;
    }
    tmp=binary(dx[ndx],inf,a,n);
    if(tmp<inf) x[++nx]=tmp;
}
int main() {
    scanf("%d",&n);
    for(int i=n;i>=0;i--) scanf("%lf",&a[i]);
    int nx;
    solve(n,a,x,nx);
    for(int i=1;i<=nx;i++) printf("%.6f\n",x[i]);
}

```

3.17 Mod

```

/// _fd(a,b) floor(a/b).
/// _rd(a,m) a-floor(a/m)*m.
/// _pv(a,m,r) largest x s.t x<=a && x%m == r.
/// _nx(a,m,r) smallest x s.t x>=a && x%m == r.
/// _ct(a,b,m,r) |A| , A = { x : a<=x<=b && x%m == r }.
int _fd(int a,int b){ return a<0?(-~a/b-1):a/b; }
int _rd(int a,int m){ return a-_fd(a,m)*m; }
int _pv(int a,int m,int r){
    r=(r%m+m)%m;
    return _fd(a-r,m)*m+r;
}
int _nt(int a,int m,int r){
    m=abs(m);
    r=(r%m+m)%m;
    return _fd(a-r-1,m)*m+r+m;
}
int _ct(int a,int b,int m,int r){
    m=abs(m);
    a=_nt(a,m,r);
    b=_pv(b,m,r);
    return (a>b)?0:((b-a+m)/m);
}

```

3.18 Primes and μ function

```

/* 12721, 13331, 14341, 75577, 123457, 222557, 556679
* 999983, 1097774749, 1076767633, 100102021, 999997771
* 1001010013, 1000512343, 987654361, 999991231
* 999888733, 98789101, 987777733, 999991921, 1010101333
* 1010102101, 1000000000039, 100000000000037
* 2305843009213693951, 4611686018427387847
* 9223372036854775783, 18446744073709551557 */
int mu[ N ] , p_tbl[ N ];
vector<int> primes;
void sieve() {
    mu[ 1 ] = p_tbl[ 1 ] = 1;
    for( int i = 2 ; i < N ; i ++ ){
        if( !p_tbl[ i ] ){
            p_tbl[ i ] = i;
            primes.push_back( i );
            mu[ i ] = -1;
        }
        for( int p : primes ){
            int x = i * p;
            if( x >= M ) break;
            p_tbl[ x ] = p;
            mu[ x ] = -mu[ i ];
            if( i % p == 0 ){
                mu[ x ] = 0;
                break;
            }
        }
    }
}
vector<int> factor( int x ){
    vector<int> fac{ 1 };
    while( x > 1 ){
        int fn = SZ(fac), p = p_tbl[ x ], pos = 0;
        while( x % p == 0 ){
            x /= p;
            for( int i = 0 ; i < fn ; i ++ )
                fac.PB( fac[ pos ++ ] * p );
        }
    }
    return fac;
}

```

3.19 Result

```

/*
Lucas ' Theorem:
For non-negative integer n,m and prime P,
C(m,n) mod P = C(m/M,n/M) * C(m%M,n%M) mod P
= mult_i ( C(m_i,n_i) )
where m_i is the i-th digit of m in base P.

```

```

Pick ' s Theorem
A = i + b/2 - 1

```

Kirchhoff's theorem

```

A_{ii} = deg(i), A_{ij} = (i,j) \in E ? -1 : 0
Deleting any one row, one column, and cal the det(A)
*/

```

4 Geometry

4.1 halfPlaneIntersection

4.2 Intersection of 2 lines

```

Pt interPnt( Line l1, Line l2, bool &res ){
    Pt p1, p2, q1, q2;
    tie(p1, p2) = l1;
    tie(q1, q2) = l2;
    double f1 = (p2 - p1) ^ (q1 - p1);
    double f2 = (p2 - p1) ^ (p1 - q2);
    double f = (f1 + f2);
    if( fabs(f) < eps)
        { res = false; return {0, 0}; }
    res = true;
    return q1 * (f2 / f) + q2 * (f1 / f);
}
bool isin( Line l0, Line l1, Line l2 ){
    // Check inter(l1, l2) in l0
    bool res;
    Pt p = interPnt(l1, l2, res);
    return ( (l0.SE - l0.FI) ^ (p - l0.FI) ) > eps;
}
/* If no solution, check: 1. ret.size() < 3
* Or more precisely, 2. interPnt(ret[0], ret[1])
* in all the lines. (use (l.S - l.F) ^ (p - l.F) > 0
*/
/* --^-- Line.FI --^-- Line.SE --^-- */
vector<Line> halfPlaneInter( vector<Line> lines ){
    int sz = lines.size();
    vector<double> ata(sz), ord(sz);
    for( int i=0; i<sz; i++) {
        ord[i] = i;
        Pt d = lines[i].SE - lines[i].FI;
        ata[i] = atan2(d.Y, d.X);
    }
    sort( ord.begin(), ord.end(), [&](int i, int j) {
        if( fabs(ata[i] - ata[j]) < eps )
            return ( (lines[i].SE - lines[i].FI) ^
                    (lines[j].SE - lines[i].FI) ) < 0;
        return ata[i] < ata[j];
    });
    vector<Line> fin;
    for( int i=0; i<sz; i++)
        if ( !i or fabs(ata[ord[i]] - ata[ord[i-1]]) > eps )
            fin.PB(lines[ord[i]]);
    deque<Line> dq;
    for( int i=0; i<(int)(fin.size()); i++) {
        while((int)(dq.size()) >= 2 and
            not isin(fin[i], dq[(int)(dq.size())-2],
                    dq[(int)(dq.size())-1]))
            dq.pop_back();
        while((int)(dq.size()) >= 2 and
            not isin(fin[i], dq[0], dq[1]))
            dq.pop_front();
        dq.push_back(fin[i]);
    }
    while( (int)(dq.size()) >= 3 and
        not isin(dq[0], dq[(int)(dq.size())-2],
                dq[(int)(dq.size())-1]))
        dq.pop_back();
    while( (int)(dq.size()) >= 3 and
        not isin(dq[(int)(dq.size())-1], dq[0], dq[1]))
        dq.pop_front();
    vector<Line> res(dq.begin(), dq.end());
    return res;
}

```

4.3 Intersection of 2 segments

```

int ori( const PLL& o , const PLL& a , const PLL& b ){
    LL ret = ( a - o ) ^ ( b - o );
    return ret / max( 1ll , abs( ret ) );
}
// p1 == p2 || q1 == q2 need to be handled
bool banana( const PLL& p1 , const PLL& p2 ,
              const PLL& q1 , const PLL& q2 ){
    if( ( ( p2 - p1 ) ^ ( q2 - q1 ) ) == 0 ){ // parallel
        if( ori( p1 , p2 , q1 ) ) return false;
        return ( ( p1 - q1 ) * ( p2 - q1 ) ) <= 0 ||
               ( ( p1 - q2 ) * ( p2 - q2 ) ) <= 0 ||
               ( ( q1 - p1 ) * ( q2 - p1 ) ) <= 0 ||
               ( ( q1 - p2 ) * ( q2 - p2 ) ) <= 0 ;
    }
    return (ori( p1, p2, q1 ) * ori( p1, p2, q2 )<=0) &&
           (ori( q1, q2, p1 ) * ori( q1, q2, p2 )<=0);
}

```

4.4 Intersection of 2 circles

4.5 Circle cover

```

#define N 1021
struct CircleCover{
    int C; Circle c[ N ];
    bool g[ N ][ N ], overlap[ N ][ N ];
    // Area[i] : area covered by at least i circles
    D Area[ N ];
    void init( int _C ){ C = _C; }
    bool CCinter( Circle& a , Circle& b , Pt& p1 , Pt& p2
    ){
        Pt o1 = a.o , o2 = b.o;
        D r1 = a.R , r2 = b.R;
        D d2 = ( o1 - o2 ) * ( o1 - o2 );
        D d = sqrt(d2);
        if( d > r1 + r2 ) return false;
        Pt u = (o1+o2)*0.5 + (o1-o2)*((r2*r2-r1*r1)/(2*d2))
        ;
        D A = sqrt((r1+r2+d)*(r1-r2+d)*(r1+r2-d)*(-r1+r2+d)
        );
        Pt v = Pt( o1.Y-o2.Y , -o1.X + o2.X ) * A / (2*d2);
        p1 = u + v; p2 = u - v;
        return true;
    }
    struct Tevent {
        Pt p; D ang; int add;
        Tevent() {}
        Tevent(Pt _a, D _b, int _c): p(_a), ang(_b), add(_c)
        {}
        bool operator<(const Tevent &a)const
        {return ang < a.ang;}
    }eve[ N * 2 ];
    // strict: x = 0, otherwise x = -1
    bool disjunct( Circle& a, Circle& b, int x ){
        return sign( norm( a.o - b.o ) - a.R - b.R ) > x;
    }
    bool contain( Circle& a, Circle& b, int x ){
        return sign( a.R - b.R - norm( a.o - b.o ) ) > x;
    }
    bool contain(int i, int j){ /* c[j] is non-strictly
        in c[i]. */
        return (sign(c[i].R - c[j].R) > 0 ||
                (sign(c[i].R - c[j].R) == 0 && i < j) ) &&
                contain(c[i], c[j], -1);
    }
    void solve(){
        for( int i = 0 ; i <= C + 1 ; i ++ )
            Area[ i ] = 0;
        for( int i = 0 ; i < C ; i ++ )
            for( int j = 0 ; j < C ; j ++ )
                overlap[i][j] = contain(i, j);
        for( int i = 0 ; i < C ; i ++ )
            for( int j = 0 ; j < C ; j ++ )
                g[i][j] = !(overlap[i][j] || overlap[j][i] ||
                    disjunct(c[i], c[j], -1));
        for( int i = 0 ; i < C ; i ++ ){
            int E = 0, cnt = 1;
            for( int j = 0 ; j < C ; j ++ )
                if( j != i && overlap[j][i] )
                    cnt ++;

```

```

for( int j = 0 ; j < C ; j ++ )
    if( i != j && g[i][j] ){
        Pt aa, bb;
        CCinter(c[i], c[j], aa, bb);
        D A = atan2(aa.Y - c[i].O.Y, aa.X - c[i].O.X)
        ;
        D B = atan2(bb.Y - c[i].O.Y, bb.X - c[i].O.X)
        ;
        eve[E ++] = Tevent(bb, B, 1);
        eve[E ++] = Tevent(aa, A, -1);
        if(B > A) cnt ++;
    }
    if( E == 0 ) Area[ cnt ] += pi * c[i].R * c[i].R;
    else{
        sort( eve , eve + E );
        eve[E] = eve[0];
        for( int j = 0 ; j < E ; j ++ ){
            cnt += eve[j].add;
            Area[cnt] += (eve[j].p ^ eve[j + 1].p) * .5;
            D theta = eve[j + 1].ang - eve[j].ang;
            if( theta < 0 ) theta += 2. * pi;
            Area[cnt] += ( theta - sin(theta) ) * c[i].R
                * c[i].R * .5;
        }
    }
}
}
};

```

4.6 Convex Hull trick

```

/* Given a convexhull, answer queries in O(\lg N)
CH should not contain identical points, the area should
be > 0, min pair(x, y) should be listed first */
double det( const Pt& p1 , const Pt& p2 )
{ return p1.X * p2.Y - p1.Y * p2.X; }
struct Conv{
    int n;
    vector<Pt> a;
    vector<Pt> upper, lower;
    Conv(vector<Pt> _a) : a(_a){
        n = a.size();
        int ptr = 0;
        for(int i=1; i<n; ++i) if (a[ptr] < a[i]) ptr = i;
        for(int i=0; i<=ptr; ++i) lower.push_back(a[i]);
        for(int i=ptr; i<n; ++i) upper.push_back(a[i]);
        upper.push_back(a[0]);
    }
    int sign( LL x ){ // fixed when changed to double
        return x < 0 ? -1 : x > 0 ;
    }
    pair<LL,int> get_tang(vector<Pt> &conv, Pt vec){
        int l = 0, r = (int)conv.size() - 2;
        for( ; l + 1 < r; ){
            int mid = (l + r) / 2;
            if(sign(det(conv[mid+1]-conv[mid],vec))>0)r=mid;
            else l = mid;
        }
        return max(make_pair(det(vec, conv[r]), r),
            make_pair(det(vec, conv[0]), 0));
    }
    void upd_tang(const Pt &p, int id, int &i0, int &i1){
        if(det(a[i0] - p, a[id] - p) > 0) i0 = id;
        if(det(a[i1] - p, a[id] - p) < 0) i1 = id;
    }
    void bi_search(int l, int r, Pt p, int &i0, int &i1){
        if(l == r) return;
        upd_tang(p, l % n, i0, i1);
        int sl=sign(det(a[l % n] - p, a[(l + 1) % n] - p));
        for( ; l + 1 < r; ){
            int mid = (l + r) / 2;
            int smid=sign(det(a[mid%n]-p, a[(mid+1)%n]-p));
            if (smid == sl) l = mid;
            else r = mid;
        }
        upd_tang(p, r % n, i0, i1);
    }
    int bi_search(Pt u, Pt v, int l, int r) {
        int sl = sign(det(v - u, a[l % n] - u));
        for( ; l + 1 < r; ){
            int mid = (l + r) / 2;

```

```

    int smid = sign(det(v - u, a[mid % n] - u));
    if (smid == sl) l = mid;
    else r = mid;
}
return l % n;
}
// 1. whether a given point is inside the CH
bool contain(Pt p) {
    if (p.X < lower[0].X || p.X > lower.back().X)
        return 0;
    int id = lower_bound(lower.begin(), lower.end(), Pt
        (p.X, -INF)) - lower.begin();
    if (lower[id].X == p.X) {
        if (lower[id].Y > p.Y) return 0;
    } else if (det(lower[id-1]-p, lower[id]-p) < 0) return 0;
    id = lower_bound(upper.begin(), upper.end(), Pt(p.X
        , INF), greater<Pt>()) - upper.begin();
    if (upper[id].X == p.X) {
        if (upper[id].Y < p.Y) return 0;
    } else if (det(upper[id-1]-p, upper[id]-p) < 0) return 0;
    return 1;
}
// 2. Find 2 tang pts on CH of a given outside point
// return true with i0, i1 as index of tangent points
// return false if inside CH
bool get_tang(Pt p, int &i0, int &i1) {
    if (contain(p)) return false;
    i0 = i1 = 0;
    int id = lower_bound(lower.begin(), lower.end(), p)
        - lower.begin();
    bi_search(0, id, p, i0, i1);
    bi_search(id, (int)lower.size(), p, i0, i1);
    id = lower_bound(upper.begin(), upper.end(), p,
        greater<Pt>()) - upper.begin();
    bi_search((int)lower.size() - 1, (int)lower.size()
        - 1 + id, p, i0, i1);
    bi_search((int)lower.size() - 1 + id, (int)lower.
        size() - 1 + (int)upper.size(), p, i0, i1);
    return true;
}
// 3. Find tangent points of a given vector
// ret the idx of vertex has max cross value with vec
int get_tang(Pt vec) {
    pair<LL, int> ret = get_tang(upper, vec);
    ret.second = (ret.second + (int)lower.size() - 1) % n;
    ret = max(ret, get_tang(lower, vec));
    return ret.second;
}
// 4. Find intersection point of a given line
// return 1 and intersection is on edge (i, next(i))
// return 0 if no strictly intersection
bool get_intersection(Pt u, Pt v, int &i0, int &i1) {
    int p0 = get_tang(u - v), p1 = get_tang(v - u);
    if (sign(det(v-u, a[p0]-u)) * sign(det(v-u, a[p1]-u)) < 0) {
        if (p0 > p1) swap(p0, p1);
        i0 = bi_search(u, v, p0, p1);
        i1 = bi_search(u, v, p1, p0 + n);
        return 1;
    }
    return 0;
}
};

```

4.7 Tangent line of two circles

```

vector<Line> go( const Circle& c1 , const Circle& c2 ){
    vector<Line> ret;
    double d_sq = norm2( c1.0 - c2.0 );
    if( d_sq < eps ) return ret;
    double d = sqrt( d_sq );
    Pt v = ( c2.0 - c1.0 ) / d;
    for( int sign1 = 1 ; sign1 >= -1 ; sign1 -= 2 ){
        double c = ( c1.R - sign1 * c2.R ) / d;
        if( c * c > 1 ) continue;
        double h = sqrt( max( 0.0 , 1.0 - c * c ) );
        for( int sign2 = 1 ; sign2 >= -1 ; sign2 -= 2 ){
            Pt n;
            n.X = v.X * c - sign2 * h * v.Y;
            n.Y = v.Y * c + sign2 * h * v.X;
            Pt p1 = c1.0 + n * c1.R;

```

```

            Pt p2 = c2.0 + n * ( c2.R * sign1 );
            if( fabs( p1.X - p2.X ) < eps and
                fabs( p1.Y - p2.Y ) < eps )
                p2 = p1 + perp( c2.0 - c1.0 );
            ret.push_back( { p1 , p2 } );
        }
    }
    return ret;
}

```

4.8 KD Tree

```

const int MXN = 100005;

struct KDTree {
    struct Node {
        int x,y,x1,y1,x2,y2;
        int id,f;
        Node *L, *R;
    } tree[MXN];
    int n;
    Node *root;

    long long dis2(int x1, int y1, int x2, int y2) {
        long long dx = x1-x2;
        long long dy = y1-y2;
        return dx*dx+dy*dy;
    }

    static bool cmpx(Node& a, Node& b){ return a.x<b.x; }
    static bool cmpy(Node& a, Node& b){ return a.y<b.y; }
    void init(vector<pair<int,int>> ip) {
        n = ip.size();
        for (int i=0; i<n; i++) {
            tree[i].id = i;
            tree[i].x = ip[i].first;
            tree[i].y = ip[i].second;
        }
        root = build_tree(0, n-1, 0);
    }

    Node* build_tree(int L, int R, int dep) {
        if (L>R) return nullptr;
        int M = (L+R)/2;
        tree[M].f = dep%2;
        nth_element(tree+L, tree+M, tree+R+1, tree[M].f ?
            cmpy : cmpx);
        tree[M].x1 = tree[M].x2 = tree[M].x;
        tree[M].y1 = tree[M].y2 = tree[M].y;

        tree[M].L = build_tree(L, M-1, dep+1);
        if (tree[M].L) {
            tree[M].x1 = min(tree[M].x1, tree[M].L->x1);
            tree[M].x2 = max(tree[M].x2, tree[M].L->x2);
            tree[M].y1 = min(tree[M].y1, tree[M].L->y1);
            tree[M].y2 = max(tree[M].y2, tree[M].L->y2);
        }

        tree[M].R = build_tree(M+1, R, dep+1);
        if (tree[M].R) {
            tree[M].x1 = min(tree[M].x1, tree[M].R->x1);
            tree[M].x2 = max(tree[M].x2, tree[M].R->x2);
            tree[M].y1 = min(tree[M].y1, tree[M].R->y1);
            tree[M].y2 = max(tree[M].y2, tree[M].R->y2);
        }

        return tree+M;
    }

    int touch(Node* r, int x, int y, long long d2){
        long long dis = sqrt(d2)+1;
        if (x<r->x1-dis || x>r->x2+dis || y<r->y1-dis || y>
            r->y2+dis)
            return 0;
        return 1;
    }
}

```

```

void nearest(Node* r, int x, int y, int &mID, long
    long &md2) {
    if (!r || !touch(r, x, y, md2)) return;
    long long d2 = dis2(r->x, r->y, x, y);
    if (d2 < md2 || (d2 == md2 && mID < r->id)) {
        mID = r->id;
        md2 = d2;
    }
}

```

```

    }
    // search order depends on split dim
    if ((r->f == 0 && x < r->x) ||
        (r->f == 1 && y < r->y)) {
        nearest(r->L, x, y, mID, md2);
        nearest(r->R, x, y, mID, md2);
    } else {
        nearest(r->R, x, y, mID, md2);
        nearest(r->L, x, y, mID, md2);
    }
}
int query(int x, int y) {
    int id = 1029384756;
    long long d2 = 102938475612345678LL;
    nearest(root, x, y, id, d2);
    return id;
}
}tree;

```

4.9 Lower Concave Hull

```

/****
maintain a "concave hull" that support the following
1. insertion of a line
2. query of height(y) on specific x on the hull
****/
/* set as needed */
typedef long double LD;
const LD eps=1e-9;
const LD inf=1e19;
class Seg {
public:
    LD m,c,x1,x2; // y=mx+c
    bool flag;
    Seg(
        LD _m,LD _c,LD _x1=-inf,LD _x2=inf,bool _flag=0)
        :m(_m),c(_c),x1(_x1),x2(_x2),flag(_flag) {}
    LD evaly(LD x) const {
        return m*x+c;
    }
    const bool operator<(LD x) const {
        return x2-eps<x;
    }
    const bool operator<(const Seg &b) const {
        if(flag||b.flag) return *this<b.x1;
        return m+eps<b.m;
    }
};
class LowerConcaveHull { // maintain a hull like: \_/_/
public:
    set<Seg> hull;
    /* functions */
    LD xintersection(Seg a,Seg b) {
        return (a.c-b.c)/(b.m-a.m);
    }
    inline set<Seg>::iterator replace(set<Seg> &
        hull,set<Seg>::iterator it,Seg s) {
        hull.erase(it);
        return hull.insert(s).first;
    }
    void insert(Seg s) {
        // insert a line and update hull
        set<Seg>::iterator it=hull.find(s);
        // check for same slope
        if(it!=hull.end()) {
            if(it->c+eps>=s.c) return;
            hull.erase(it);
        }
        // check if below whole hull
        it=hull.lower_bound(s);
        if(it!=hull.end()&&
            s.evaly(it->x1)<=it->evaly(it->x1)+eps) return;
        // update right hull
        while(it!=hull.end()) {
            LD x=xintersection(s,*it);
            if(x>=it->x2-eps) hull.erase(it++);
            else {
                s.x2=x;
                it=replace(hull,it,Seg(it->m,it->c,x,it->x2));
                break;
            }
        }
    }
};

```

```

    }
    // update left hull
    while(it!=hull.begin()) {
        LD x=xintersection(s,*(--it));
        if(x<=it->x1+eps) hull.erase(it++);
        else {
            s.x1=x;
            it=replace(hull,it,Seg(it->m,it->c,it->x1,x));
            break;
        }
    }
    // insert s
    hull.insert(s);
}
void insert(LD m,LD c) { insert(Seg(m,c)); }
LD query(LD x) { // return y @ given x
    set<Seg>::iterator it =
        hull.lower_bound(Seg(0.0,0.0,x,x,1));
    return it->evaly(x);
}
};

```

4.10 Delaunay Triangulation

```

/* Delaunay Triangulation:
Given a sets of points in 2D plane, find a
triangulation such that no points will strictly
inside circumcircle of any triangle.

find : return a triangle contain given point
add_point : add a point into triangulation

A Triangle is in triangulation iff. its has_chd is 0.
Region of triangle u: iterate each u.edge[i].tri,
each points are u.p[(i+1)%3], u.p[(i+2)%3]

calculation involves O(|V|^6) */
const int N = 100000 + 5;
const type inf = 2e3;
type eps = 1e-6; // 0 when integer
type sqr(type x) { return x*x; }
// return p4 is in circumcircle of tri(p1,p2,p3)
bool in_cc(const Pt& p1, const Pt& p2, const Pt& p3,
    const Pt& p4){
    type u11 = p1.X - p4.X; type u12 = p1.Y - p4.Y;
    type u21 = p2.X - p4.X; type u22 = p2.Y - p4.Y;
    type u31 = p3.X - p4.X; type u32 = p3.Y - p4.Y;
    type u13 = sqr(p1.X)-sqr(p4.X)+sqr(p1.Y)-sqr(p4.Y);
    type u23 = sqr(p2.X)-sqr(p4.X)+sqr(p2.Y)-sqr(p4.Y);
    type u33 = sqr(p3.X)-sqr(p4.X)+sqr(p3.Y)-sqr(p4.Y);
    type det = -u13*u22*u31 + u12*u23*u31 + u13*u21*u32
        -u11*u23*u32 - u12*u21*u33 + u11*u22*u33;
    return det > eps;
}
type side(const Pt& a, const Pt& b, const Pt& p)
{ return (b - a) ^ (p - a); }
typedef int SdRef;
struct Tri;
typedef Tri* TriRef;
struct Edge {
    TriRef tri; SdRef side;
    Edge():tri(0), side(0){}
    Edge(TriRef _tri, SdRef _side):tri(_tri), side(_side)
    {}
};
struct Tri {
    Pt p[3];
    Edge edge[3];
    TriRef chd[3];
    Tri() {}
    Tri(const Pt& p0, const Pt& p1, const Pt& p2) {
        p[0] = p0; p[1] = p1; p[2] = p2;
        chd[0] = chd[1] = chd[2] = 0;
    }
    bool has_chd() const { return chd[0] != 0; }
    int num_chd() const {
        return chd[0] == 0 ? 0
            : chd[1] == 0 ? 1
            : chd[2] == 0 ? 2 : 3;
    }
};

```



```

}
bool contains(Pt const& q) const {
    for( int i = 0 ; i < 3 ; i ++ )
        if( side(p[i], p[(i + 1) % 3] , q) < -eps )
            return false;
    return true;
}
} pool[ N * 10 ], *tris;
void edge( Edge a, Edge b ){
    if(a.tri) a.tri->edge[a.side] = b;
    if(b.tri) b.tri->edge[b.side] = a;
}
struct Trig { // Triangulation
    Trig(){
        the_root = // Tri should at least contain all
                    points
                    new(tris++)Tri(Pt(-inf,-inf),Pt(+inf+inf,-inf),Pt
                    (-inf,+inf+inf));
    }
    TriRef find(Pt p)const{ return find(the_root,p); }
    void add_point(const Pt& p){ add_point(find(the_root,
        p),p); }
    TriRef the_root;
    static TriRef find(TriRef root, const Pt& p) {
        while( true ){
            if( !root->has_chd() )
                return root;
            for( int i = 0; i < 3 && root->chd[i] ; ++i )
                if (root->chd[i]->contains(p)) {
                    root = root->chd[i];
                    break;
                }
        }
        assert( false ); // "point not found"
    }
    void add_point(TriRef root, Pt const& p) {
        TriRef tab,tbc,tca;
        /* split it into three triangles */
        tab=new(tris++) Tri(root->p[0],root->p[1],p);
        tbc=new(tris++) Tri(root->p[1],root->p[2],p);
        tca=new(tris++) Tri(root->p[2],root->p[0],p);
        edge(Edge(tab,0), Edge(tbc,1));
        edge(Edge(tbc,0), Edge(tca,1));
        edge(Edge(tca,0), Edge(tab,1));
        edge(Edge(tab,2), root->edge[2]);
        edge(Edge(tbc,2), root->edge[0]);
        edge(Edge(tca,2), root->edge[1]);
        root->chd[0] = tab;
        root->chd[1] = tbc;
        root->chd[2] = tca;
        flip(tab,2);
        flip(tbc,2);
        flip(tca,2);
    }
    void flip(TriRef tri, SdRef pi) {
        TriRef trj = tri->edge[pi].tri;
        int pj = tri->edge[pi].side;
        if (!trj) return;
        if (!in_cc(tri->p[0],tri->p[1],tri->p[2],trj->p[pj]
            )) return;
        /* flip edge between tri,trj */
        TriRef trk = new(tris++) Tri(tri->p[(pi+1)%3], trj
            ->p[pj], tri->p[pi]);
        TriRef trl = new(tris++) Tri(trj->p[(pj+1)%3], tri
            ->p[pi], trj->p[pj]);
        edge(Edge(trk,0), Edge(trl,0));
        edge(Edge(trk,1), tri->edge[(pi+2)%3]);
        edge(Edge(trk,2), trj->edge[(pj+1)%3]);
        edge(Edge(trl,1), trj->edge[(pj+2)%3]);
        edge(Edge(trl,2), tri->edge[(pi+1)%3]);
        tri->chd[0]=trk; tri->chd[1]=trl; tri->chd[2]=0;
        trj->chd[0]=trk; trj->chd[1]=trl; trj->chd[2]=0;
        flip(trk,1); flip(trk,2);
        flip(trl,1); flip(trl,2);
    }
};
vector<TriRef> triang;
set<TriRef> vst;
void go( TriRef now ){
    if( vst.find( now ) != vst.end() )
        return;
    vst.insert( now );

```

```

if( !now->has_chd() ){
    triang.push_back( now );
    return;
}
for( int i = 0 ; i < now->num_chd() ; i ++ )
    go( now->chd[ i ] );
}
void build( int n , Pt* ps ){
    tris = pool;
    random_shuffle(ps, ps + n);
    Trig tri;
    for(int i = 0; i < n; ++ i)
        tri.add_point(ps[i]);
    go( tri.the_root );
}

```

4.11 Min Enclosing Circle

```

struct Mec{
    // return pair of center and r
    static const int N = 101010;
    int n;
    Pt p[ N ], cen;
    double r2;
    void init( int _n , Pt _p[] ){
        n = _n;
        memcpy( p , _p , sizeof(Pt) * n );
    }
    double sqr(double a){ return a*a; }
    Pt center(Pt p0, Pt p1, Pt p2) {
        Pt a = p1-p0;
        Pt b = p2-p0;
        double c1=norm2( a ) * 0.5;
        double c2=norm2( b ) * 0.5;
        double d = a ^ b;
        double x = p0.X + (c1 * b.Y - c2 * a.Y) / d;
        double y = p0.Y + (a.X * c2 - b.X * c1) / d;
        return Pt(x,y);
    }
    pair<Pt,double> solve(){
        random_shuffle(p,p+n);
        r2=0;
        for (int i=0; i<n; i++){
            if (norm2(cen-p[i]) <= r2) continue;
            cen = p[i];
            r2 = 0;
            for (int j=0; j<i; j++){
                if (norm2(cen-p[j]) <= r2) continue;
                cen=Pt((p[i].X+p[j].X)/2,(p[i].Y+p[j].Y)/2);
                r2 = norm2(cen-p[j]);
                for (int k=0; k<j; k++){
                    if (norm2(cen-p[k]) <= r2) continue;
                    cen = center(p[i],p[j],p[k]);
                    r2 = norm2(cen-p[k]);
                }
            }
        }
        return {cen,sqrt(r2)};
    }
} mec;

```

4.12 Min Enclosing Ball

```

// Pt : { x , y , z }
#define N 202020
int n, nouter; Pt pt[ N ], outer[4], res;
double radius,tmp;
void ball() {
    Pt q[3]; double m[3][3], sol[3], L[3], det;
    int i,j; res.x = res.y = res.z = radius = 0;
    switch ( nouter ) {
        case 1: res=outer[0]; break;
        case 2: res=(outer[0]+outer[1])/2; radius=norm2(res,
            outer[0]); break;
        case 3:
            for (i=0; i<2; ++i) q[i]=outer[i+1]-outer[0];
            for (i=0; i<2; ++i) for(j=0; j<2; ++j) m[i][j]=(q
                [i] * q[j])*2;

```



```

for (i=0; i<2; ++i) sol[i]=(q[i] * q[i]);
if (fabs(det=m[0][0]*m[1][1]-m[0][1]*m[1][0])<eps)
    return;
L[0]=(sol[0]*m[1][1]-sol[1]*m[0][1])/det;
L[1]=(sol[1]*m[0][0]-sol[0]*m[1][0])/det;
res=outer[0]+q[0]*L[0]+q[1]*L[1];
radius=norm2(res, outer[0]);
break;
case 4:
for (i=0; i<3; ++i) q[i]=outer[i+1]-outer[0], sol
[i]=(q[i] * q[i]);
for (i=0; i<3; ++i) for (j=0; j<3; ++j) m[i][j]=(q[i]
* q[j])*2;
det= m[0][0]*m[1][1]*m[2][2]
+ m[0][1]*m[1][2]*m[2][0]
+ m[0][2]*m[1][0]*m[2][1]
- m[0][2]*m[1][1]*m[2][0]
- m[0][1]*m[1][0]*m[2][2]
- m[0][0]*m[1][2]*m[2][1];
if ( fabs(det)<eps ) return;
for (j=0; j<3; ++j) {
for (i=0; i<3; ++i) m[i][j]=sol[i];
L[j]=( m[0][0]*m[1][1]*m[2][2]
+ m[0][1]*m[1][2]*m[2][0]
+ m[0][2]*m[1][0]*m[2][1]
- m[0][2]*m[1][1]*m[2][0]
- m[0][1]*m[1][0]*m[2][2]
- m[0][0]*m[1][2]*m[2][1]
) / det;
for (i=0; i<3; ++i) m[i][j]=(q[i] * q[j])*2;
} res=outer[0];
for (i=0; i<3; ++i) res = res + q[i] * L[i];
radius=norm2(res, outer[0]);
}
}
void minball(int n){ ball();
if( nouter < 4 ) for( int i = 0 ; i < n ; i ++ )
if( norm2(res, pt[i]) - radius > eps ){
outer[ nouter ++ ] = pt[ i ]; minball(i); --
nouter;
if(i>0){ Pt Tt = pt[i];
memmove(&pt[1], &pt[0], sizeof(Pt)*i); pt[0]=Tt
;
}
}
}
void solve{
// n points in pt
random_shuffle(pt, pt+n); radius=-1;
for(int i=0; i<n; i++) if(norm2(res, pt[i])-radius>eps)
nouter=1, outer[0]=pt[i], minball(i);
printf("%.5f\n", sqrt(radius));
}
}

```

4.13 Minkowski sum

```

vector<Pt> minkowski(vector<Pt> p, vector<Pt> q){
int n = p.size(), m = q.size();
Pt c = Pt(0, 0);
for( int i = 0; i < m; i ++ ) c = c + q[i];
c = c / m;
for( int i = 0; i < m; i ++ ) q[i] = q[i] - c;
int cur = -1;
for( int i = 0; i < m; i ++ )
if( (q[i] ^ (p[0] - p[n-1])) > -eps)
if( cur == -1 ||
(q[i] ^ (p[0] - p[n-1])) >
(q[cur] ^ (p[0] - p[n-1])) )
cur = i;
vector<Pt> h;
p.push_back(p[0]);
for( int i = 0; i < n; i ++ )
while( true ){
h.push_back(p[i] + q[cur]);
int nxt = (cur + 1 == m ? 0 : cur + 1);
if((q[cur] ^ (p[i+1] - p[i])) < -eps) cur = nxt;
else if( (q[nxt] ^ (p[i+1] - p[i])) >
(q[cur] ^ (p[i+1] - p[i])) ) cur = nxt;
else break;
}
for(auto &&i : h) i = i + c;
return convex_hull(h);
}
}

```

4.14 Heart of Triangle

```

Pt inCenter( Pt &A, Pt &B, Pt &C) { // 内心
double a = norm(B-C), b = norm(C-A), c = norm(A-B);
return (A * a + B * b + C * c) / (a + b + c);
}
Pt circumCenter( Pt &a, Pt &b, Pt &c) { // 外心
Pt bb = b - a, cc = c - a;
double db=norm2(bb), dc=norm2(cc), d=2*(bb ^ cc);
return a-Pt(bb.Y*dc-cc.Y*db, cc.X*db-bb.X*dc) / d;
}
Pt orthoCenter( Pt &a, Pt &b, Pt &c) { // 垂心
Pt ba = b - a, ca = c - a, bc = b - c;
double Y = ba.Y * ca.Y * bc.Y,
A = ca.X * ba.Y - ba.X * ca.Y,
x0= (Y+ca.X*ba.Y*b.X-ba.X*ca.Y*c.X) / A,
y0= -ba.X * (x0 - c.X) / ba.Y + ca.Y;
return Pt(x0, y0);
}
}

```

5 Graph

5.1 HeavyLightDecomp

```

#define SZ(c) (int)(c).size()
#define ALL(c) (c).begin(), (c).end()
#define REP(i, s, e) for(int i = (s); i <= (e); i++)
#define REPD(i, s, e) for(int i = (s); i >= (e); i--)
typedef tuple< int, int > tii;
const int MAXN = 100010;
const int LOG = 19;
struct HLD{
int n;
vector<int> g[MAXN];
int sz[MAXN], dep[MAXN];
int ts, tid[MAXN], tdi[MAXN], tl[MAXN], tr[MAXN];
// ts : timestamp, useless after yutruLi
// tid[ u ] : pos. of node u in the seq.
// tdi[ i ] : node at pos i of the seq.
// tl, tr[ u ] : subtree interval in the seq. of
node u
int mom[MAXN][LOG], head[MAXN];
// head[ u ] : head of the chain contains u
void dfsz(int u, int p){
dep[u] = dep[p] + 1;
mom[u][0] = p;
sz[u] = 1;
head[u] = u;
for(int& v:g[u]) if(v != p){
dep[v] = dep[u] + 1;
dfsz(v, u);
sz[u] += sz[v];
}
}
void dfsHl(int u){
//printf("dfsHl %d\n", u);
ts++;
tid[u] = tl[u] = tr[u] = ts;
tdi[tid[u]] = u;
sort(ALL(g[u]),
[&](int a, int b){return sz[a] > sz[b];});
bool flag = 1;
for(int& v:g[u]) if(v != mom[u][0]){
if(flag) head[v] = head[u], flag = 0;
dfshl(v);
tr[u] = tr[v];
}
}
inline int lca(int a, int b){
if(dep[a] > dep[b]) swap(a, b);
//printf("lca %d %d\n", a, b);
int diff = dep[b] - dep[a];
REPD(k, LOG-1, 0) if(diff & (1<<k)){
//printf("b %d\n", mom[b][k]);
b = mom[b][k];
}
if(a == b) return a;
REPD(k, LOG-1, 0) if(mom[a][k] != mom[b][k]){

```

```

    a = mom[a][k];
    b = mom[b][k];
}
return mom[a][0];
}
void init( int _n ){
    n = _n;
    REP( i , 1 , n ) g[ i ].clear();
}
void addEdge( int u , int v ){
    g[ u ].push_back( v );
    g[ v ].push_back( u );
}
void yutruli(){
    dfssz(1, 0);
    ts = 0;
    dfshl(1);
    REP(k, 1, LOG-1) REP(i, 1, n)
        mom[i][k] = mom[mom[i][k-1]][k-1];
}
vector< tii > getPath( int u , int v ){
    vector< tii > res;
    while( tid[ u ] < tid[ head[ v ] ] ){
        res.push_back( tii(tid[ head[ v ] ] , tid[ v ] ) );
        v = mom[ head[ v ] ][ 0 ];
    }
    res.push_back( tii( tid[ u ] , tid[ v ] ) );
    reverse( ALL( res ) );
    return res;
}
/*
 * res : list of intervals from u to v
 * u must be ancestor of v
 * usage :
 * vector< tii > path = tree.getPath( u , v )
 * for( tii tp : path ) {
 *     int l , r; tie( l , r ) = tp;
 *     upd( l , r );
 *     uu = tree.tdi[ l ] , vv = tree.tdi[ r ];
 *     uu ~> vv is a heavy path on tree
 * }
 */
}
} tree;

```

5.2 DominatorTree

```

const int MAXN = 100010;
struct DominatorTree{
#define REP(i,s,e) for(int i=(s);i<=(e);i++)
#define REPD(i,s,e) for(int i=(s);i>=(e);i--)
    int n , m , s;
    vector< int > g[ MAXN ] , pred[ MAXN ];
    vector< int > cov[ MAXN ];
    int dfn[ MAXN ] , nfd[ MAXN ] , ts;
    int par[ MAXN ];
    int sdom[ MAXN ] , idom[ MAXN ];
    int mom[ MAXN ] , mn[ MAXN ];
    inline bool cmp( int u , int v )
    { return dfn[ u ] < dfn[ v ]; }
    int eval( int u ){
        if( mom[ u ] == u ) return u;
        int res = eval( mom[ u ] );
        if( cmp( sdom[ mn[ mom[ u ] ] ] , sdom[ mn[ u ] ] ) )
            mn[ u ] = mn[ mom[ u ] ];
        return mom[ u ] = res;
    }
    void init( int _n , int _m , int _s ){
        ts = 0; n = _n; m = _m; s = _s;
        REP( i , 1 , n ) g[ i ].clear(), pred[ i ].clear();
    }
    void addEdge( int u , int v ){
        g[ u ].push_back( v );
        pred[ v ].push_back( u );
    }
    void dfs( int u ){
        ts++;
        dfn[ u ] = ts;
        nfd[ ts ] = u;
        for( int v : g[ u ] ) if( dfn[ v ] == 0 ){

```

```

            par[ v ] = u;
            dfs( v );
        }
    }
    void build(){
        REP( i , 1 , n ){
            dfn[ i ] = nfd[ i ] = 0;
            cov[ i ].clear();
            mom[ i ] = mn[ i ] = sdom[ i ] = i;
        }
        dfs( s );
        REPD( i , n , 2 ){
            int u = nfd[ i ];
            if( u == 0 ) continue;
            for( int v : pred[ u ] ) if( dfn[ v ] ){
                eval( v );
                if( cmp( sdom[ mn[ v ] ] , sdom[ u ] ) )
                    sdom[ u ] = sdom[ mn[ v ] ];
            }
            cov[ sdom[ u ] ].push_back( u );
            mom[ u ] = par[ u ];
            for( int w : cov[ par[ u ] ] ){
                eval( w );
                if( cmp( sdom[ mn[ w ] ] , par[ u ] ) )
                    idom[ w ] = mn[ w ];
                else idom[ w ] = par[ u ];
            }
            cov[ par[ u ] ].clear();
        }
        REP( i , 2 , n ){
            int u = nfd[ i ];
            if( u == 0 ) continue;
            if( idom[ u ] != sdom[ u ] )
                idom[ u ] = idom[ idom[ u ] ];
        }
    }
} domT;

```

5.3 MaxClique

```

struct MaxClique {
    static const int MV = 210;
    int V , ans , dp[MV];
    int el[MV][MV/30+1], s[MV][MV/30+1];
    vector<int> sol;
    void init(int v) {
        V = v; ans = 0;
        FZ(el); FZ(dp);
    }
    /* Zero Base */
    void addEdge(int u, int v) {
        if(u > v) swap(u, v);
        if(u == v) return;
        el[u][v/32] |= (1<<(v%32));
    }
    bool dfs(int v, int k) {
        int c = 0, d = 0;
        for(int i=0; i<(V+31)/32; i++) {
            s[k][i] = el[v][i];
            if(k != 1) s[k][i] &= s[k-1][i];
            c += __builtin_popcount(s[k][i]);
        }
        if(c == 0) {
            if(k > ans) {
                ans = k;
                sol.clear();
                sol.push_back(v);
                return 1;
            }
            return 0;
        }
        for(int i=0; i<(V+31)/32; i++) {
            for(int a = s[k][i]; a; a++) {
                if(k + (c-d) <= ans) return 0;
                int lb = a&(-a), lg = 0;
                a ^= lb;
                while(lb!=1) {
                    lb = (unsigned int)(lb) >> 1;
                    lg++;
                }
            }

```

```

    int u = i*32 + lg;
    if(k + dp[u] <= ans) return 0;
    if(dfs(u, k+1)) {
        sol.push_back(v);
        return 1;
    }
}
}
return 0;
}
int solve() {
    for(int i=V-1; i>=0; i--) {
        dfs(i, 1);
        dp[i] = ans;
    }
    return ans;
}
};

```

```

    if (!vst[v]) rDFS(v);
}
void solve(){
    nScc = 0;
    vec.clear();
    FZ(vst);
    for (int i=0; i<n; i++)
        if (!vst[i]) DFS(i);
    reverse(vec.begin(),vec.end());
    FZ(vst);
    for (auto v : vec){
        if (!vst[v]){
            rDFS(v);
            nScc++;
        }
    }
}
};

```

5.4 Number of Maximal Clique

```

// bool g[][] : adjacent array indexed from 1 to n
void dfs(int sz){
    int i, j, k, t, cnt, best = 0;
    if(ne[sz]==ce[sz]){ if (ce[sz]==0) ++ans; return; }
    for(t=0, i=1; i<=ne[sz]; ++i){
        for(cnt=0, j=ne[sz]+1; j<=ce[sz]; ++j)
            if (!g[lst[sz][i]][lst[sz][j]]) ++cnt;
        if (t==0 || cnt<best) t=i, best=cnt;
    } if (t && best<=0) return;
    for (k=ne[sz]+1; k<=ce[sz]; ++k) {
        if (t>0){ for (i=k; i<=ce[sz]; ++i)
            if (!g[lst[sz][t]][lst[sz][i]]) break;
        swap(lst[sz][k], lst[sz][i]);
        i=lst[sz][k]; ne[sz+1]=ce[sz+1]=0;
        for (j=1; j<k; ++j)if (g[i][lst[sz][j]])
            lst[sz+1][++ne[sz+1]]=lst[sz][j];
        for (ce[sz+1]=ne[sz+1], j=k+1; j<=ce[sz]; ++j)
            if (g[i][lst[sz][j]]) lst[sz+1][++ce[sz+1]]=lst[sz][j];
        dfs(sz+1); ++ne[sz]; --best;
        for (j=k+1, cnt=0; j<=ce[sz]; ++j) if (!g[i][lst[sz][j]]) ++cnt;
        if (t==0 || cnt<best) t=k, best=cnt;
        if (t && best<=0) break;
    }
}
void work(){
    ne[0]=0; ce[0]=0;
    for(int i=1; i<=n; ++i) lst[0][++ce[0]]=i;
    ans=0; dfs(0);
}

```

5.5 Strongly Connected Component

```

struct Scc{
    int n, nScc, vst[MXN], bln[MXN];
    vector<int> E[MXN], rE[MXN], vec;
    void init(int _n){
        n = _n;
        for (int i=0; i<MXN; i++){
            E[i].clear();
            rE[i].clear();
        }
    }
    void add_edge(int u, int v){
        E[u].PB(v);
        rE[v].PB(u);
    }
    void DFS(int u){
        vst[u]=1;
        for (auto v : E[u])
            if (!vst[v]) DFS(v);
        vec.PB(u);
    }
    void rDFS(int u){
        vst[u] = 1;
        bln[u] = nScc;
        for (auto v : rE[u])

```

5.6 Dynamic MST

```

/* Dynamic MST O( Q lg^2 Q )
(qx[i], qy[i])->chg weight of edge No.qx[i] to qy[i]
delete an edge: (i, \infy)
add an edge: change from \infy to specific value
*/
const int SZ=M+3*MXQ;
int a[N],*tz;
int find(int xx){
    int root=xx; while(a[root]) root=a[root];
    int next; while((next=a[xx])){a[xx]=root; xx=next; }
    return root;
}
bool cmp(int aa,int bb){ return tz[aa]<tz[bb]; }
int kx[N],ky[N],kt, vd[N],id[M], app[M];
bool extra[M];
void solve(int *qx,int *qy,int Q,int n,int *x,int *y,
    int *z,int m1,long long ans){
    if(Q==1){
        for(int i=1;i<=n;i++) a[i]=0;
        z[ qx[0] ]=qy[0]; tz = z;
        for(int i=0;i<m1;i++) id[i]=i;
        sort(id,id+m1,cmp); int ri,rj;
        for(int i=0;i<m1;i++){
            ri=find(x[id[i]]); rj=find(y[id[i]]);
            if(ri!=rj){ ans+=z[id[i]]; a[ri]=rj; }
        }
        printf("%lld\n",ans);
        return;
    }
    int ri,rj;
    //contract
    kt=0;
    for(int i=1;i<=n;i++) a[i]=0;
    for(int i=0;i<Q;i++){
        ri=find(x[qx[i]]); rj=find(y[qx[i]]); if(ri!=rj) a[ri]=rj;
    }
    int tm=0;
    for(int i=0;i<m1;i++) extra[i]=true;
    for(int i=0;i<Q;i++) extra[ qx[i] ]=false;
    for(int i=0;i<m1;i++) if(extra[i]) id[tm++]=i;
    tz=z; sort(id,id+tm,cmp);
    for(int i=0;i<tm;i++){
        ri=find(x[id[i]]); rj=find(y[id[i]]);
        if(ri!=rj){
            a[ri]=rj; ans += z[id[i]];
            kx[kt]=x[id[i]]; ky[kt]=y[id[i]]; kt++;
        }
    }
    for(int i=1;i<=n;i++) a[i]=0;
    for(int i=0;i<kt;i++) a[ find(kx[i]) ]=find(ky[i]);
    int n2=0;
    for(int i=1;i<=n;i++) if(a[i]==0)
        vd[i]=++n2;
    for(int i=1;i<=n;i++) if(a[i])
        vd[i]=vd[find(i)];
    int m2=0, *Nx=x+m1, *Ny=y+m1, *Nz=z+m1;
    for(int i=0;i<m1;i++) app[i]=-1;
    for(int i=0;i<Q;i++) if(app[qx[i]]==-1){

```

```

    Nx[m2]=vd[ x[ qx[i] ] ]; Ny[m2]=vd[ y[ qx[i] ] ];
    Nz[m2]=z[ qx[i] ];
    app[qx[i]]=m2; m2++;
}
for(int i=0;i<Q;i++){ z[ qx[i] ]=qy[i]; qx[i]=app[qx[i]
    i]]; }
for(int i=1;i<=n2;i++) a[i]=0;
for(int i=0;i<tm;i++){
    ri=find(vd[ x[id[i]] ]); rj=find(vd[ y[id[i]] ]);
    if(ri!=rj){
        a[ri]=rj; Nx[m2]=vd[ x[id[i]] ];
        Ny[m2]=vd[ y[id[i]] ]; Nz[m2]=z[id[i]]; m2++;
    }
}
int mid=Q/2;
solve(qx,qy,mid,n2,Nx,Ny,Nz,m2,ans);
solve(qx+mid,qy+mid,Q-mid,n2,Nx,Ny,Nz,m2,ans);
}
int x[SZ],y[SZ],z[SZ],qx[MXQ],qy[MXQ],n,m,Q;
void init(){
    scanf("%d%d",&n,&m);
    for(int i=0;i<m;i++) scanf("%d%d%d",x+i,y+i,z+i);
    scanf("%d",&Q);
    for(int i=0;i<Q;i++){ scanf("%d%d",qx+i,qy+i); qx[i]
        ]--; }
}
void work(){ if(Q) solve(qx,qy,Q,n,x,y,z,m,0); }
int main(){init(); work(); }

```

5.7 Maximum General graph Matching

```

const int N = 514, E = (2e5) * 2;
struct Graph{
    int to[E],bro[E],head[N],e;
    int lnk[N],vis[N],stp,n;
    void init( int _n ){
        stp = 0; e = 1; n = _n;
        for( int i = 1 ; i <= n ; i ++ )
            lnk[i] = vis[i] = 0;
    }
    void add_edge(int u,int v){
        to[e]=v,bro[e]=head[u],head[u]=e++;
        to[e]=u,bro[e]=head[v],head[v]=e++;
    }
    bool dfs(int x){
        vis[x]=stp;
        for(int i=head[x];i;i=bro[i]){
            int v=to[i];
            if(!lnk[v]){
                lnk[x]=v,lnk[v]=x;
                return true;
            }else if(vis[lnk[v]]<stp){
                int w=lnk[v];
                lnk[x]=v,lnk[v]=x,lnk[w]=0;
                if(dfs(w)){
                    return true;
                }
                lnk[w]=v,lnk[v]=w,lnk[x]=0;
            }
        }
        return false;
    }
    int solve(){
        int ans = 0;
        for(int i=1;i<=n;i++)
            if(!lnk[i]){
                stp++; ans += dfs(i);
            }
        return ans;
    }
} graph;

```

5.8 Minimum General Weighted Matching

```

struct Graph {
    // Minimum General Weighted Matching (Perfect Match)
    static const int MXN = 105;
    int n, edge[MXN][MXN];

```

```

    int match[MXN],dis[MXN],onstk[MXN];
    vector<int> stk;
    void init(int _n) {
        n = _n;
        for( int i = 0 ; i < n ; i ++ )
            for( int j = 0 ; j < n ; j ++ )
                edge[ i ][ j ] = 0;
    }
    void add_edge(int u, int v, int w)
    { edge[u][v] = edge[v][u] = w; }
    bool SPFA(int u){
        if (onstk[u]) return true;
        stk.PB(u);
        onstk[u] = 1;
        for (int v=0; v<n; v++){
            if (u != v && match[u] != v && !onstk[v]){
                int m = match[v];
                if (dis[m] > dis[u] - edge[v][m] + edge[u][v]){
                    dis[m] = dis[u] - edge[v][m] + edge[u][v];
                    onstk[v] = 1;
                    stk.PB(v);
                    if (SPFA(m)) return true;
                    stk.pop_back();
                    onstk[v] = 0;
                }
            }
        }
        onstk[u] = 0;
        stk.pop_back();
        return false;
    }
    int solve() {
        // find a match
        for (int i=0; i<n; i+=2){
            match[i] = i+1;
            match[i+1] = i;
        }
        while (true){
            int found = 0;
            for( int i = 0 ; i < n ; i ++ )
                onstk[ i ] = dis[ i ] = 0;
            for (int i=0; i<n; i++){
                stk.clear();
                if (!onstk[i] && SPFA(i)){
                    found = 1;
                    while (SZ(stk)>=2){
                        int u = stk.back(); stk.pop_back();
                        int v = stk.back(); stk.pop_back();
                        match[u] = v;
                        match[v] = u;
                    }
                }
            }
            if (!found) break;
        }
        int ret = 0;
        for (int i=0; i<n; i++)
            ret += edge[i][match[i]];
        ret /= 2;
        return ret;
    }
}graph;

```

5.9 Maximum General Weighted Matching

```

struct WeightGraph {
    static const int INF = INT_MAX;
    static const int N = 514;
    struct edge{
        int u,v,w; edge(){}
        edge(int ui,int vi,int wi)
            :u(ui),v(vi),w(wi){}
    };
    int n,n_x;
    edge g[N*2][N*2];
    int lab[N*2];
    int match[N*2],slack[N*2],st[N*2],pa[N*2];
    int flo_from[N*2][N+1],S[N*2],vis[N*2];
    vector<int> flo[N*2];
    queue<int> q;

```

```

int e_delta(const edge &e){
    return lab[e.u]+lab[e.v]-g[e.u][e.v].w*2;
}
void update_slack(int u,int x){
    if(!slack[x]||e_delta(g[u][x])<e_delta(g[slack[x]][x]))slack[x]=u;
}
void set_slack(int x){
    slack[x]=0;
    for(int u=1;u<=n;++u)
        if(g[u][x].w>0&&st[u]!=x&&S[st[u]]==0)
            update_slack(u,x);
}
void q_push(int x){
    if(x<=n)q.push(x);
    else for(size_t i=0;i<flo[x].size();i++)
        q_push(flo[x][i]);
}
void set_st(int x,int b){
    st[x]=b;
    if(x>n)for(size_t i=0;i<flo[x].size();++i)
        set_st(flo[x][i],b);
}
int get_pr(int b,int xr){
    int pr=find(flo[b].begin(),flo[b].end(),xr)-flo[b].begin();
    if(pr%2==1){
        reverse(flo[b].begin()+1,flo[b].end());
        return (int)flo[b].size()-pr;
    }else return pr;
}
void set_match(int u,int v){
    match[u]=g[u][v].v;
    if(u<=n) return;
    edge e=g[u][v];
    int xr=flo_from[u][e.u],pr=get_pr(u,xr);
    for(int i=0;i<pr;++i)set_match(flo[u][i],flo[u][i+1]);
    set_match(xr,v);
    rotate(flo[u].begin(),flo[u].begin()+pr,flo[u].end());
}
void augment(int u,int v){
    for(;;){
        int xnv=st[match[u]];
        set_match(u,v);
        if(!xnv)return;
        set_match(xnv,st[pa[xnv]]);
        u=st[pa[xnv]],v=xnv;
    }
}
int get_lca(int u,int v){
    static int t=0;
    for(++t;u||v;swap(u,v)){
        if(u==0)continue;
        if(vis[u]==t)return u;
        vis[u]=t;
        u=st[match[u]];
        if(u)u=st[pa[u]];
    }
    return 0;
}
void add_blossom(int u,int lca,int v){
    int b=n+1;
    while(b<=n_x&&st[b])++b;
    if(b>n_x)++n_x;
    lab[b]=0,S[b]=0;
    match[b]=match[lca];
    flo[b].clear();
    flo[b].push_back(lca);
    for(int x=u,y,x!=lca;x=st[pa[y]])
        flo[b].push_back(x),flo[b].push_back(y=st[match[x]]),q_push(y);
    reverse(flo[b].begin()+1,flo[b].end());
    for(int x=v,y,x!=lca;x=st[pa[y]])
        flo[b].push_back(x),flo[b].push_back(y=st[match[x]]),q_push(y);
    set_st(b,b);
    for(int x=1;x<=n_x;++x)g[b][x].w=g[x][b].w=0;
    for(int x=1;x<=n_x;++x)flo_from[b][x]=0;
    for(size_t i=0;i<flo[b].size();++i){
        int xs=flo[b][i];

```

```

        for(int x=1;x<=n_x;++x)
            if(g[b][x].w==0||e_delta(g[xs][x])<e_delta(g[b][x]))
                g[b][x]=g[xs][x],g[x][b]=g[x][xs];
        for(int x=1;x<=n_x;++x)
            if(flo_from[xs][x])flo_from[b][x]=xs;
    }
    set_slack(b);
}
void expand_blossom(int b){
    for(size_t i=0;i<flo[b].size();++i)
        set_st(flo[b][i],flo[b][i]);
    int xr=flo_from[b][g[b][pa[b]].u],pr=get_pr(b,xr);
    for(int i=0;i<pr;i+=2){
        int xs=flo[b][i],xns=flo[b][i+1];
        pa[xs]=g[xns][xs].u;
        S[xs]=1,S[xns]=0;
        slack[xs]=0,set_slack(xns);
        q_push(xns);
    }
    S[xr]=1,pa[xr]=pa[b];
    for(size_t i=pr+1;i<flo[b].size();++i){
        int xs=flo[b][i];
        S[xs]=-1,set_slack(xs);
    }
    st[b]=0;
}
bool on_found_edge(const edge &e){
    int u=st[e.u],v=st[e.v];
    if(S[v]==-1){
        pa[v]=e.u,S[v]=1;
        int nu=st[match[v]];
        slack[v]=slack[nu]=0;
        S[nu]=0,q_push(nu);
    }else if(S[v]==0){
        int lca=get_lca(u,v);
        if(!lca)return augment(u,v),augment(v,u),true;
        else add_blossom(u,lca,v);
    }
    return false;
}
bool matching(){
    memset(S+1,-1,sizeof(int)*n_x);
    memset(slack+1,0,sizeof(int)*n_x);
    q=queue<int>();
    for(int x=1;x<=n_x;++x)
        if(st[x]==x&&!match[x])pa[x]=0,S[x]=0,q_push(x);
    if(q.empty())return false;
    for(;;){
        while(q.size()){
            int u=q.front();q.pop();
            if(S[st[u]]==1)continue;
            for(int v=1;v<=n_x;++v)
                if(g[u][v].w>0&&st[u]!=st[v]){
                    if(e_delta(g[u][v])==0){
                        if(on_found_edge(g[u][v]))return true;
                    }else update_slack(u,st[v]);
                }
        }
        int d=INF;
        for(int b=n+1;b<=n_x;++b)
            if(st[b]==b&&S[b]==1)d=min(d,lab[b]/2);
        for(int x=1;x<=n_x;++x)
            if(st[x]==x&&slack[x]){
                if(S[x]==-1)d=min(d,e_delta(g[slack[x]][x]));
                else if(S[x]==0)d=min(d,e_delta(g[slack[x]][x])/2);
            }
        for(int u=1;u<=n_x;++u){
            if(S[st[u]]==0){
                if(lab[u]<=d)return 0;
                lab[u]-=d;
            }else if(S[st[u]]==1)lab[u]+=d;
        }
        for(int b=n+1;b<=n_x;++b)
            if(st[b]==b){
                if(S[st[b]]==0)lab[b]+=d*2;
                else if(S[st[b]]==1)lab[b]-=d*2;
            }
        q=queue<int>();
        for(int x=1;x<=n_x;++x)

```

```

        if(st[x]==x&&slack[x]&&st[slack[x]]!=x&&e_delta
           (g[slack[x]][x])==0)
            if(on_found_edge(g[slack[x]][x]))return true;
        for(int b=n+1;b<=n_x;++b)
            if(st[b]==b&&S[b]==1&&lab[b]==0)expand_blossom(
                b);
    }
    return false;
}
pair<long long,int> solve(){
    memset(match+1,0,sizeof(int)*n);
    n_x=n;
    int n_matches=0;
    long long tot_weight=0;
    for(int u=0;u<=n;++u)st[u]=u,flo[u].clear();
    int w_max=0;
    for(int u=1;u<=n;++u)
        for(int v=1;v<=n;++v){
            flo_from[u][v]=(u==v?u:0);
            w_max=max(w_max,g[u][v].w);
        }
    for(int u=1;u<=n;++u)lab[u]=w_max;
    while(matching())n_matches++;
    for(int u=1;u<=n;++u)
        if(match[u]&&match[u]<u)
            tot_weight+=g[u][match[u]].w;
    return make_pair(tot_weight,n_matches);
}
void add_edge( int ui , int vi , int wi ){
    g[ui][vi].w = g[vi][ui].w = wi;
}
void init( int _n ){
    n = _n;
    for(int u=1;u<=n;++u)
        for(int v=1;v<=n;++v)
            g[u][v]=edge(u,v,0);
}
} graph;

```

5.10 Minimum Steiner Tree

```

// Minimum Steiner Tree
//  $O(V^3AT + V^2 2AT)$ 
struct SteinerTree{
#define V 33
#define T 8
#define INF 1023456789
    int n , dst[V][V] , dp[1 << T][V] , tdst[V];
    void init( int _n ){
        n = _n;
        for( int i = 0 ; i < n ; i ++ ){
            for( int j = 0 ; j < n ; j ++ )
                dst[ i ][ j ] = INF;
            dst[ i ][ i ] = 0;
        }
    }
    void add_edge( int ui , int vi , int wi ){
        dst[ ui ][ vi ] = min( dst[ ui ][ vi ] , wi );
        dst[ vi ][ ui ] = min( dst[ vi ][ ui ] , wi );
    }
    void shortest_path(){
        for( int k = 0 ; k < n ; k ++ )
            for( int i = 0 ; i < n ; i ++ )
                for( int j = 0 ; j < n ; j ++ )
                    dst[ i ][ j ] = min( dst[ i ][ j ] ,
                        dst[ i ][ k ] + dst[ k ][ j ] );
    }
    int solve( const vector<int>& ter ){
        int t = (int)ter.size();
        for( int i = 0 ; i < ( 1 << t ) ; i ++ )
            for( int j = 0 ; j < n ; j ++ )
                dp[ i ][ j ] = INF;
        dp[ 0 ][ 0 ] = 0;
        for( int msk = 1 ; msk < ( 1 << t ) ; msk ++ ){
            if( msk == ( msk & (-msk) ) ){
                int who = __lg( msk );
                for( int i = 0 ; i < n ; i ++ )
                    dp[ msk ][ i ] = dst[ ter[ who ] ][ i ];
                continue;
            }
        }
    }
}

```

```

    }
    for( int i = 0 ; i < n ; i ++ )
        for( int submsk = ( msk - 1 ) & msk ; submsk ;
            submsk = ( submsk - 1 ) & msk )
            dp[ msk ][ i ] = min( dp[ msk ][ i ] ,
                dp[ submsk ][ i ] +
                dp[ msk ^ submsk ][ i ] );
    for( int i = 0 ; i < n ; i ++ ){
        tdst[ i ] = INF;
        for( int j = 0 ; j < n ; j ++ )
            tdst[ i ] = min( tdst[ i ] ,
                dp[ msk ][ j ] + dst[ j ][ i ] );
    }
    for( int i = 0 ; i < n ; i ++ )
        dp[ msk ][ i ] = tdst[ i ];
    }
    int ans = INF;
    for( int i = 0 ; i < n ; i ++ )
        ans = min( ans , dp[ ( 1 << t ) - 1 ][ i ] );
    return ans;
}
} solver;

```

5.11 BCC based on vertex

```

struct BccVertex {
    int n,nScc,step,dfn[MXN],low[MXN];
    vector<int> E[MXN],sccv[MXN];
    int top,stk[MXN];
    void init(int _n) {
        n = _n;
        nScc = step = 0;
        for (int i=0; i<n; i++) E[i].clear();
    }
    void add_edge(int u, int v) {
        E[u].PB(v);
        E[v].PB(u);
    }
    void DFS(int u, int f) {
        dfn[u] = low[u] = step++;
        stk[top++] = u;
        for (auto v:E[u]) {
            if (v == f) continue;
            if (dfn[v] == -1) {
                DFS(v,u);
                low[u] = min(low[u], low[v]);
                if (low[v] >= dfn[u]) {
                    int z;
                    sccv[nScc].clear();
                    do {
                        z = stk[--top];
                        sccv[nScc].PB(z);
                    } while (z != v);
                    sccv[nScc].PB(u);
                    nScc++;
                }
            } else {
                low[u] = min(low[u],dfn[v]);
            }
        }
    }
    vector<vector<int>>> solve() {
        vector<vector<int>>> res;
        for (int i=0; i<n; i++) {
            dfn[i] = low[i] = -1;
        }
        for (int i=0; i<n; i++) {
            if (dfn[i] == -1) {
                top = 0;
                DFS(i,i);
            }
        }
        REP(i,nScc) res.PB(sccv[i]);
        return res;
    }
} graph;

```

5.12 Graph Hash


```

$$F_t(i) =
(F_{t-1}(i) \times A +
\sum_{i \rightarrow j} F_{t-1}(j) \times B +
\sum_{j \rightarrow i} F_{t-1}(j) \times C +
D \times (i = a)) \bmod P
$$
for each node i, iterate t times.
t, A, B, C, D, P are hash parameter

```

6 String

6.1 PalTree

```

const int MAXN = 200010;
struct PalT{
    struct Node{
        int nxt[ 33 ], len , fail;
        ll cnt;
    };
    int tot , lst;
    Node nd[ MAXN * 2 ];
    char* s;
    int newNode( int l , int _fail ){
        int res = ++tot;
        memset( nd[ res ].nxt , 0 , sizeof nd[ res ].nxt );
        nd[ res ].len = l;
        nd[ res ].cnt = 0;
        nd[ res ].fail = _fail;
        return res;
    }
    void push( int p ){
        int np = lst;
        int c = s[ p ] - 'a';
        while( p - nd[ np ].len - 1 < 0
            || s[ p ] != s[ p - nd[ np ].len - 1 ] )
            np = nd[ np ].fail;

        if( nd[ np ].nxt[ c ] ){
            nd[ nd[ np ].nxt[ c ] ].cnt++;
            lst = nd[ np ].nxt[ c ];
            return ;
        }
        int nq = newNode( nd[ np ].len + 2 , 0 );
        nd[ nq ].cnt++;
        nd[ np ].nxt[ c ] = nq;
        lst = nq;
        if( nd[ nq ].len == 1 ){
            nd[ nq ].fail = 2;
            return ;
        }
        int tf = nd[ np ].fail;
        while( p - nd[ tf ].len - 1 < 0
            || s[ p ] != s[ p - nd[ tf ].len - 1 ] )
            tf = nd[ tf ].fail;

        nd[ nq ].fail = nd[ tf ].nxt[ c ];
        return ;
    }
    void init( char* _s ){
        s = _s;
        tot = 0;
        newNode( -1 , 1 );
        newNode( 0 , 1 );
        lst = 2;
        for( int i = 0 ; s[ i ] ; i++ )
            push( i );
    }
    void yutru1i(){
#define REPD(i, s, e) for(int i = (s); i >= (e); i--)
        REPD( i , tot , 1 )
            nd[ nd[ i ].fail ].cnt += nd[ i ].cnt;
            nd[ 1 ].cnt = nd[ 2 ].cnt = 0ll;
    }
} pA;
int main(){ pA.init( sa ); }

```

6.2 SAIS

```

const int N = 300010;
struct SA{
#define REP(i,n) for ( int i=0; i<int(n); i++ )
#define REP1(i,a,b) for ( int i=(a); i<=int(b); i++ )
    bool _t[N*2];
    int _s[N*2], _sa[N*2], _c[N*2], x[N], _p[N], _q[N*2],
        hei[N], r[N];
    int operator [] (int i){ return _sa[i]; }
    void build(int *s, int n, int m){
        memcpy(_s, s, sizeof(int) * n);
        sais(_s, _sa, _p, _q, _t, _c, n, m);
        mkhei(n);
    }
    void mkhei(int n){
        REP(i,n) r[_sa[i]] = i;
        hei[0] = 0;
        REP(i,n) if(r[i]) {
            int ans = i>0 ? max(hei[r[i-1]] - 1, 0) : 0;
            while(_s[i+ans] == _s[_sa[r[i]-1]+ans]) ans++;
            hei[r[i]] = ans;
        }
    }
    void sais(int *s, int *sa, int *p, int *q, bool *t,
        int *c, int n, int z){
        bool uniq = t[n-1] = true, neq;
        int nn = 0, nmzx = -1, *nsa = sa + n, *ns = s + n,
            lst = -1;
#define MS0(x,n) memset((x),0,n*sizeof(*(x)))
#define MAGIC(XD) MS0(sa, n); \
        memcpy(x, c, sizeof(int) * z); \
        XD; \
        memcpy(x + 1, c, sizeof(int) * (z - 1)); \
        REP(i,n) if(sa[i] && !t[sa[i]-1]) sa[x[s[sa[i]-1]]++] = sa[i]-1; \
        memcpy(x, c, sizeof(int) * z); \
        for(int i = n - 1; i >= 0; i--) if(sa[i] && t[sa[i]-1]) sa[--x[s[sa[i]-1]]] = sa[i]-1;
        MS0(c, z);
        REP(i,n) uniq &= ++c[s[i]] < 2;
        REP(i,z-1) c[i+1] += c[i];
        if (uniq) { REP(i,n) sa[--c[s[i]]] = i; return; }
        for(int i = n - 2; i >= 0; i--) t[i] = (s[i]==s[i+1] ? t[i+1] : s[i]<s[i+1]);
        MAGIC(REP1(i,1,n-1) if(t[i] && !t[i-1]) sa[--x[s[i]]]=p[q[i]=nn++]=i);
        REP(i, n) if (sa[i] && t[sa[i]] && !t[sa[i]-1]) {
            neq=lst<0||memcmp(s+sa[i],s+lst,(p[q[sa[i]]+1]-sa[i])*sizeof(int));
            ns[q[lst=sa[i]]]=nmzx+=neq;
        }
        sais(ns, nsa, p + nn, q + n, t + n, c + z, nn, nmzx + 1);
        MAGIC(for(int i = nn - 1; i >= 0; i--) sa[--x[s[p[nsa[i]]]]] = p[nsa[i]]);
    }
}sa;
int H[ N ], SA[ N ];
void suffix_array(int* ip, int len) {
    // should padding a zero in the back
    // ip is int array, len is array length
    // ip[0..n-1] != 0, and ip[len] = 0
    ip[len++] = 0;
    sa.build(ip, len, 128);
    for (int i=0; i<len; i++) {
        H[i] = sa.hei[i + 1];
        SA[i] = sa._sa[i + 1];
    }
    // resulting height, sa array \in [0,len)
}

```

6.3 SuffixAutomata

```

const int MAXM = 1000010;
struct SAM{
    int tot, root, lst, mom[MAXM], mx[MAXM];
    int acc[MAXM], nxt[MAXM][33];
    int newNode(){

```

```

    int res = ++tot;
    fill(nxt[res], nxt[res]+33, 0);
    mom[res] = mx[res] = acc[res] = 0;
    return res;
}
void init(){
    tot = 0;
    root = newNode();
    mom[root] = 0, mx[root] = 0;
    lst = root;
}
void push(int c){
    int p = lst;
    int np = newNode();
    mx[np] = mx[p]+1;
    for(; p && nxt[p][c] == 0; p = mom[p])
        nxt[p][c] = np;
    if(p == 0) mom[np] = root;
    else{
        int q = nxt[p][c];
        if(mx[p]+1 == mx[q]) mom[np] = q;
        else{
            int nq = newNode();
            mx[nq] = mx[p]+1;
            for(int i = 0; i < 33; i++)
                nxt[nq][i] = nxt[q][i];
            mom[nq] = mom[q];
            mom[q] = nq;
            mom[np] = nq;
            for(; p && nxt[p][c] == q; p = mom[p])
                nxt[p][c] = nq;
        }
    }
    lst = np;
}
void push(char *str){
    for(int i = 0; str[i]; i++)
        push(str[i]-'a'+1);
}
} sam;

```

6.4 Aho-Corasick

```

struct AAutomata{
    struct Node{
        int cnt, dp;
        Node *go[26], *fail;
        Node(){
            cnt = 0; dp = -1; fail = 0;
            memset(go, 0, sizeof(go));
        }
    };
    Node *root, pool[1048576];
    int nMem;
    Node* new_Node(){
        pool[nMem] = Node();
        return &pool[nMem++];
    }
    void init()
    { nMem = 0; root = new_Node(); }
    void add(const string &str)
    { insert(root, str, 0); }
    void insert(Node *cur, const string &str, int pos){
        if (pos >= (int)str.size())
            { cur->cnt++; return; }
        int c = str[pos]-'a';
        if (cur->go[c] == 0)
            cur->go[c] = new_Node();
        insert(cur->go[c], str, pos+1);
    }
    void make_fail(){
        queue<Node*> que;
        que.push(root);
        while (!que.empty()){
            Node* fr=que.front();
            que.pop();
            for (int i=0; i<26; i++){
                if (fr->go[i]){
                    Node *ptr = fr->fail;
                    while (ptr && !ptr->go[i]) ptr = ptr->fail;

```

```

                    if (!ptr) fr->go[i]->fail = root;
                    else fr->go[i]->fail = ptr->go[i];
                    que.push(fr->go[i]);
                }
            }
        }
    };
}

```

6.5 Z Value

```

char s[MAXN];
int len, z[MAXN];
void Z_value() {
    int i, j, left, right;
    left=right=0; z[0]=len;
    for(i=1; i<len; i++) {
        j=max(min(z[i-left], right-i), 0);
        for(; i+j<len&&s[i+j]==s[j]; j++);
        z[i]=j;
        if(i+z[i]>right) {
            right=i+z[i];
            left=i;
        }
    }
}

```

6.6 BWT

```

struct BurrowsWheeler{
#define SIGMA 26
#define BASE 'a'
    vector<int> v[ SIGMA ];
    void BWT(char* ori, char* res){
        // make ori -> ori + ori
        // then build suffix array
    }
    void iBWT(char* ori, char* res){
        for( int i = 0 ; i < SIGMA ; i ++ )
            v[ i ].clear();
        int len = strlen( ori );
        for( int i = 0 ; i < len ; i ++ )
            v[ ori[i] - BASE ].push_back( i );
        vector<int> a;
        for( int i = 0 , ptr = 0 ; i < SIGMA ; i ++ )
            for( auto j : v[ i ] ){
                a.push_back( j );
                ori[ ptr ++ ] = BASE + i;
            }
        for( int i = 0 , ptr = 0 ; i < len ; i ++ ){
            res[ i ] = ori[ a[ ptr ] ];
            ptr = a[ ptr ];
        }
        res[ len ] = 0;
    }
} bwt;

```

6.7 ZValue Palindrome

```

int len, zv[MAX*2];
char ip[MAX], op[MAX*2];
int main(){
    cin >> ip; len = strlen(ip);
    int l2 = len*2 - 1;
    for(int i=0; i<l2; i++){
        if(i&1) op[i] = '@';
        else op[i] = ip[i/2];
    }
    int l=0, r=0; zv[0] = 1;
    for(int i=1; i<l2; i++){
        if( i > r ){
            l = r = i;
            while( l>0 && r<l2-1 && op[l-1] == op[r+1] )
                l--, r++;
            zv[i] = (r-l+1);
        } else {
            int md = (l+r)/2, j = md + md - i;

```

```

    zv[i] = zv[j];
    int q = zv[i] / 2, nr = i + q;
    if( nr == r ){
        l = i + i - r;
        while( l>0 && r<l2-1 && op[l-1] == op[r+1] )
            l--, r++;
        zv[i] = r - l + 1;
    }else if( nr > r ){
        zv[i] = (r - i) * 2 + 1;
    }
}
}
}

```

6.8 Smallest Rotation

```

string mcp(string s){
    int n = s.length();
    s += s;
    int i=0, j=1;
    while (i<n && j<n){
        int k = 0;
        while (k < n && s[i+k] == s[j+k]) k++;
        if (s[i+k] <= s[j+k]) j += k+1;
        else i += k+1;
        if (i == j) j++;
    }
    int ans = i < n ? i : j;
    return s.substr(ans, n);
}

```

7 Data Structure

7.1 Treap

```

struct Treap{
    int sz, val, pri, tag;
    Treap *l, *r;
    Treap( int _val ){
        val = _val; sz = 1;
        pri = rand(); l = r = NULL; tag = 0;
    }
};
void push( Treap * a ){
    if( a->tag ){
        Treap *swp = a->l; a->l = a->r; a->r = swp;
        int swp2;
        if( a->l ) a->l->tag ^= 1;
        if( a->r ) a->r->tag ^= 1;
        a->tag = 0;
    }
}
int Size( Treap * a ){ return a ? a->sz : 0; }
void pull( Treap * a ){
    a->sz = Size( a->l ) + Size( a->r ) + 1;
}
Treap* merge( Treap *a, Treap *b ){
    if( !a || !b ) return a ? a : b;
    if( a->pri > b->pri ){
        push( a );
        a->r = merge( a->r, b );
        pull( a );
        return a;
    }else{
        push( b );
        b->l = merge( a, b->l );
        pull( b );
        return b;
    }
}
void split( Treap *t, int k, Treap*&a, Treap*&b ){
    if( !t ){ a = b = NULL; return; }
    push( t );
    if( Size( t->l ) + 1 <= k ){
        a = t;
        split( t->r, k - Size( t->l ) - 1, a->r, b );
        pull( a );
    }
}

```

```

}else{
    b = t;
    split( t->l, k, a, b->l );
    pull( b );
}
}

```

7.2 Link-Cut Tree

```

const int MXN = 100005;
const int MEM = 100005;
struct Splay {
    static Splay nil, mem[MEM], *pmem;
    Splay *ch[2], *f;
    int val, rev, size;
    Splay () : val(-1), rev(0), size(0)
    { f = ch[0] = ch[1] = &nil; }
    Splay( int _val ) : val(_val), rev(0), size(1)
    { f = ch[0] = ch[1] = &nil; }
    bool isr()
    { return f->ch[0] != this && f->ch[1] != this; }
    int dir()
    { return f->ch[0] == this ? 0 : 1; }
    void setCh(Splay *c, int d){
        ch[d] = c;
        if (c != &nil) c->f = this;
        pull();
    }
    void push(){
        if( !rev ) return;
        swap(ch[0], ch[1]);
        if (ch[0] != &nil) ch[0]->rev ^= 1;
        if (ch[1] != &nil) ch[1]->rev ^= 1;
        rev=0;
    }
    void pull(){
        size = ch[0]->size + ch[1]->size + 1;
        if (ch[0] != &nil) ch[0]->f = this;
        if (ch[1] != &nil) ch[1]->f = this;
    }
} Splay::nil, Splay::mem[MEM], *Splay::pmem = Splay::
mem;
Splay *nil = &Splay::nil;
void rotate(Splay *x){
    Splay *p = x->f;
    int d = x->dir();
    if (!p->isr()) p->f->setCh(x, p->dir());
    else x->f = p->f;
    p->setCh(x->ch[!d], d);
    x->setCh(p, !d);
    p->pull(); x->pull();
}
vector<Splay*> splayVec;
void splay(Splay *x){
    splayVec.clear();
    for (Splay *q=x; q=q->f){
        splayVec.push_back(q);
        if (q->isr()) break;
    }
    reverse(begin(splayVec), end(splayVec));
    for (auto it : splayVec) it->push();
    while (!x->isr()) {
        if (x->f->isr()) rotate(x);
        else if (x->dir()==x->f->dir())
            rotate(x->f), rotate(x);
        else rotate(x), rotate(x);
    }
}
Splay* access(Splay *x){
    Splay *q = nil;
    for (;x!=nil;x=x->f){
        splay(x);
        x->setCh(q, 1);
        q = x;
    }
    return q;
}
void evert(Splay *x){
    access(x);
    splay(x);
}

```

```

x->rev ^= 1;
x->push(); x->pull();
}
void link(Splay *x, Splay *y){
// evert(x);
access(x);
splay(x);
evert(y);
x->setCh(y, 1);
}
void cut(Splay *x, Splay *y){
// evert(x);
access(y);
splay(y);
y->push();
y->ch[0] = y->ch[0]->f = nil;
}
int N, Q;
Splay *vt[MXN];
int ask(Splay *x, Splay *y){
access(x);
access(y);
splay(x);
int res = x->f->val;
if (res == -1) res=x->val;
return res;
}
int main(int argc, char** argv){
scanf("%d%d", &N, &Q);
for (int i=1; i<=N; i++)
vt[i] = new (Splay::pmem++) Splay(i);
while (Q--){
char cmd[105];
int u, v;
scanf("%s", cmd);
if (cmd[1] == 'i') {
scanf("%d%d", &u, &v);
link(vt[u], vt[v]);
} else if (cmd[0] == 'c') {
scanf("%d", &v);
cut(vt[1], vt[v]);
} else {
scanf("%d%d", &u, &v);
int res=ask(vt[u], vt[v]);
printf("%d\n", res);
}
}
}

```

7.3 Black Magic

```

#include <bits/extc++.h>
using namespace __gnu_pbds;
typedef tree<int,null_type,less<int>,rb_tree_tag,
tree_order_statistics_node_update> set_t;
#include <ext/pb_ds/assoc_container.hpp>
typedef cc_hash_table<int,int> umap_t;
typedef priority_queue<int> heap;
#include<ext/rope>
using namespace __gnu_cxx;
int main(){
// Insert some entries into s.
set_t s; s.insert(12); s.insert(505);
// The order of the keys should be: 12, 505.
assert(*s.find_by_order(0) == 12);
assert(*s.find_by_order(3) == 505);
// The order of the keys should be: 12, 505.
assert(s.order_of_key(12) == 0);
assert(s.order_of_key(505) == 1);
// Erase an entry.
s.erase(12);
// The order of the keys should be: 505.
assert(*s.find_by_order(0) == 505);
// The order of the keys should be: 505.
assert(s.order_of_key(505) == 0);

heap h1, h2; h1.join( h2 );

rope<char> r[ 2 ];
r[ 1 ] = r[ 0 ]; // persistenet

```

```

string t = "abc";
r[ 1 ].insert( 0, t.c_str() );
r[ 1 ].erase( 1, 1 );
cout << r[ 1 ].substr( 0, 2 );
}

```

8 Others

8.1 # of Intersection of segments

```

#include<bits/stdc++.h>
using namespace std;
#define F first
#define S second
#define PB push_back
#define IOS ios_base::sync_with_stdio(0); cin.tie(0);
#define SZ(x) ((int)((x).size()))
#define ALL(x) begin(x),end(x)
#define REP(i,x) for (int i=0; i<(x); i++)
#define REP1(i,a,b) for (int i=(a); i<=(b); i++)

typedef long long ll;
typedef pair<ll,ll> pll;

typedef pll Point;
const int MXN = 100005;

Point operator + (const Point &a, const Point &b) {
return Point(a.F+b.F, a.S+b.S); }
Point operator - (const Point &a, const Point &b) {
return Point(a.F-b.F, a.S-b.S); }
ll operator * (const Point &a, const Point &b) { return
a.F*b.F + a.S*b.S; }
ll operator % (const Point &a, const Point &b) { return
a.F*b.S - a.S*b.F; }

struct Segment {
int v,id;
Point p,q;
Segment () {}
Segment (int _v, int _id, Point _p, Point _q) :
v(_v), id(_id), p(_p), q(_q) {}
};

bool operator < (const Segment &a, const Segment &b) {
if (a.p == b.q) return false;
if (a.q == b.p) return true;
if (a.p == b.p) return (a.q-a.p) % (b.q-a.p) > 0;
if (a.q == b.q) return (a.p-a.q) % (b.p-a.q) < 0;
if (a.p.F == b.p.F) return a.p.S < b.p.S;
if (a.q.F == b.q.F) return a.q.S < b.q.S;
if (a.p.F < b.p.F) return (a.q-a.p) % (b.p-a.p) > 0;
else return (b.q-b.p) % (a.p-b.p) < 0;
}

bool operator == (const Segment &a, const Segment &b) {
return tie(a.v,a.id,a.p,a.q) == tie(b.v,b.id,b.p,b.q)
;
}

struct Triangle {
Point pt[3];
}ip[MXN];

const int MEM = 350004;
struct Treap {
static Treap nil, mem[MEM], *pmem;
Treap *l, *r;
int sum,presum,size;
Segment seg;
Treap () : l(&nil), r(&nil), sum(0), presum(0), size
(0), seg() {}
Treap (Segment _val) :
l(&nil), r(&nil), sum(_val.v), presum(max(_val.v,0)
), size(1), seg(_val) {}
} Treap::nil, Treap::mem[MEM], *Treap::pmem = Treap::
mem;

int size(const Treap *t) { return t->size; }
void pull(Treap *t) {
if (!size(t)) return;

```

```

t->size = size(t->l) + size(t->r) + 1;
t->sum = t->l->sum + t->seg.v + t->r->sum;
t->presum = max(t->l->presum, t->l->sum + t->seg.v);
t->presum = max(t->presum, t->l->sum + t->seg.v + t->
    r->presum);
}
Treap* merge(Treap *a, Treap *b) {
    if (!size(a)) return b;
    if (!size(b)) return a;
    Treap *t;
    if (rand() % (size(a) + size(b)) < size(a)) {
        t = a;
        t->r = merge(a->r, b);
    } else {
        t = b;
        t->l = merge(a, b->l);
    }
    pull(t);
    return t;
}
void split(Treap *t, int k, Treap *&a, Treap *&b) {
    if (!size(t)) a = b = &Treap::nil;
    else if (size(t->l) + 1 <= k) {
        a = t;
        split(t->r, k - size(t->l) - 1, a->r, b);
        pull(a);
    } else {
        b = t;
        split(t->l, k, a, b->l);
        pull(b);
    }
}
int get_rank(Treap *t, Segment x) {
    if (!size(t)) return 0;
    if (x < t->seg) return get_rank(t->l, x);
    return get_rank(t->r, x) + size(t->l) + 1;
}
Treap* find_leftist(Treap *t) {
    while (size(t->l)) t = t->l;
    return t;
}
Treap* find_rightist(Treap *t) {
    while (size(t->r)) t = t->r;
    return t;
}

int N;
vector<int> allx;
vector<Segment> _seg[3*MXN];
#define seg(x) _seg[(x)+100000]

inline void add_seg(Segment s) {
    seg(s.p.F).PB(s);
    if (s.q.F != s.p.F) seg(s.q.F).PB(s);
}
void predo() {
    allx.clear();
    REP(i, N) REP(j, 3) {
        seg(ip[i].pt[j].F).clear();
        allx.PB(ip[i].pt[j].F);
    }
    sort(ALL(allx));
    allx.resize(unique(ALL(allx))-begin(allx));
    REP(i, N) {
        sort(ip[i].pt, ip[i].pt+3);
        Point *pt = ip[i].pt;
        Segment seg1 = Segment(1, i, pt[0], pt[1]);
        Segment seg2 = Segment(1, i, pt[0], pt[2]);
        Segment seg3 = Segment(1, i, pt[1], pt[2]);
        if (seg2 < seg1) seg1.v = -1;
        else seg2.v = -1;
        seg3.v = seg1.v;
        add_seg(seg1);
        add_seg(seg2);
        add_seg(seg3);
    }
}
inline int sgn(ll x) { return x < 0 ? -1 : x > 0; }
bool interPnt(Point p1, Point p2, Point q1, Point q2) {
    ll c1 = (p2-p1)*(q1-p1), c2 = (p2-p1)*(q2-p1);
    ll c3 = (q2-q1)*(p1-q1), c4 = (q2-q1)*(p2-q1);

```

```

    return sgn(c1) * sgn(c2) <= 0 and sgn(c3) * sgn(c4)
        <= 0;
}
bool check_error(Segment a, Segment b) {
    if (a.id == b.id) return false;
    return interPnt(a.p, a.q, b.p, b.q);
}
int solve() {
    Treap::pmem = Treap::mem;
    Treap *rt = &Treap::nil;
    int res = 0;
    for (auto i:allx) {
        for (auto l:seg(i)) {
            int k = get_rank(rt, l);
            Treap *t, *tl, *tm, *tr;
            split(rt, k, tl, tr);
            t = find_rightist(tl);
            if (size(t) and check_error(t->seg, l)) return -1;
            t = find_leftist(tr);
            if (size(t) and check_error(t->seg, l)) return -1;
            rt = merge(tl, tr);
            if (l.p.F == i and l.p.F != l.q.F) {
                k = get_rank(rt, l);
                split(rt, k, tl, tr);
                tm = new (Treap::pmem++) Treap(l);
                rt = merge(merge(tl, tm), tr);
            }
        }
        for (auto l:seg(i)) {
            if (l.q.F == i and l.p.F != l.q.F) {
                Treap *tl, *tm, *tr;
                int k = get_rank(rt, l);
                split(rt, k-1, tl, tm);
                split(tm, 1, tm, tr);
                Treap *t1=find_rightist(tl), *t2=find_leftist(tr);
                if (size(t1) and size(t2) and check_error(t1->
                    seg, t2->seg)) return -1;
                rt = merge(tl, tr);
            }
        }
        res = max(res, rt->presum);
    }
    res++;
    return res;
}
int main() {
    IOS;
    int cas = 0;
    while (cin >> N) {
        if (N == -1) break;
        REP(i, N) {
            REP(j, 3) cin >> ip[i].pt[j].F >> ip[i].pt[j].S;
        }
        predo();
        int ans = solve();
        cas++;
        cout << "Case " << cas << ": ";
        if (ans == -1) cout << "ERROR\n";
        else cout << ans << " shades\n";
    }
    return 0;
}

```