

Contents

1	Basic	1
1.1	.vimrc	1
2	flow	1
2.1	Dinic	1
2.2	DMST	2
2.3	ISAP	2
2.4	MinCostFlow	3
2.5	SW min-cut	3
2.6	HLPPA	3
2.7	Hungarian	4
2.8	Hungarian Unbalanced	4
2.9	Gusfield	5
2.10	Relabel to Front	6
2.11	Flow Method	6
3	Math	6
3.1	FFT	6
3.2	NTT	7
3.3	BigInt	8
3.4	Linear Recurrence	9
3.5	Miller Rabin	9
3.6	PollardRho	9
3.7	Simplex	10
3.8	Faulhaber	10
3.9	Chinese Remainder	10
3.10	Pollard Rho	11
3.11	Result	11
4	Geometry	12
4.1	halfPlaneIntersection	12
4.2	Convex Hull	13
4.3	Intersection of 2 lines	14
4.4	KD Tree	14
4.5	Poly Union	14
4.6	Lower Concave Hull	15
4.7	MCC	16
4.8	Minkowski sum	16
4.9	Min Enclosing Circle	16
4.10	Min/Max Enclosing Rectangle	17
5	Graph	18
5.1	HeavyLightDecomp	18
5.2	DominatorTree	19
5.3	generalWeightedGraphMaxmatching	19
5.4	MaxClique	20
6	String	20
6.1	PalTree	20
6.2	SuffixArray	21
6.3	SAIS	21
6.4	SuffixAutomata	22
6.5	Aho-Corasick	22
6.6	Z Value	22
6.7	ZValue Palindrome	22
6.8	Smallest Rotation	23
6.9	Baker Bird	23
6.10	Cyclic LCS	24
7	Data Structure	24
7.1	Treap	24
7.2	Black Magic	25

1 Basic

1.1 .vimrc

```
syn on
se ai nu ru cul mouse=a
se cin et ts=2 sw=2 sts=2
so $VIMRUNTIME/mswin.vim
colo desert
se gfn=Monospace\ 14
```

2 flow

2.1 Dinic

```
#include <bits/stdc++.h>
using namespace std;
#define N 5010
#define M 60010
#define ll long long
#define inf 1ll<<62
ll to[ M ], next[ M ], head[ M ];
ll cnt , ceng[ M ], que[ M ], w[ M ];
ll n , m , start , end;
void add( ll a , ll b , ll flow ){
    to[ cnt ] = b , next[ cnt ] = head[ a ] , w[ cnt ]
    = flow , head[ a ] = cnt ++;
    to[ cnt ] = a , next[ cnt ] = head[ b ] , w[ cnt ]
    = flow , head[ b ] = cnt ++;
}
void read(){
    memset(head,-1,sizeof head);
    //memset(next,-1,sizeof next);
    scanf( "%lld%lld" , &n , &m );
    ll a , b , flow;
    for( ll i = 1 ; i <= m ; i ++ ){
        scanf( "%lld%lld%lld" , &a , &b , &flow );
        add( a , b , flow );
    }
    end = n , start = 1;
}
bool bfs(){
    memset( ceng , -1 , sizeof(ceng) );
    ll h = 1 , t = 2;
    ceng[ start ] = 0;
    que[ 1 ] = start;
    while( h < t ){
        ll sta = que[ h ++ ];
        for( ll i = head[ sta ] ; ~i ; i = next[ i ] ){
            if( w[ i ] > 0 && ceng[ to[ i ] ] < 0 ){
                ceng[ to[ i ] ] = ceng[ sta ] + 1;
                que[ t ++ ] = to[ i ];
            }
        }
    }
    return ceng[ end ] != -1;
}
ll find( ll x , ll low ){
    ll tmp = 0 , result = 0;
    if( x == end ) return low;
    for( ll i = head[ x ] ; ~i && result < low ; i =
        next[ i ] ){
        if( w[ i ] > 0 && ceng[ to[ i ] ] == ceng[ x ]
            + 1 ){
            tmp = find( to[ i ] , min( w[ i ] , low -
                result ) );
            w[ i ] -= tmp;
            w[ i^1 ] += tmp;
            result += tmp;
        }
    }
    if( !result ) ceng[ x ] = -1;
    return result;
}
ll dinic(){
    ll ans = 0 , tmp;
    while( bfs() ) ans += find( start , inf );
    return ans;
}
```

```

}
int main(){
    read();
    cout << dinic() << endl;
}

```

2.2 DMST

```

/*
 * Edmond's algoirthm for Minimum Directed Spanning
 * Tree
 * runs in O(VE)
 */
// default code for competitive programming
// c2251393 ver 3.141 {{{
// Includes
#include <bits/stdc++.h>
// Defines
#define NAME(x) #x
#define SZ(c) ((int)(c).size())
#define ALL(c) (c).begin(), (c).end()
#define FOR(it, c) for(__typeof((c).begin()) it = (c).begin(); it != (c).end(); it++)
#define REP(i, s, e) for(int i = (s); i <= (e); i++)
#define REPD(i, s, e) for(int i = (s); i >= (e); i--)
#define DEBUG 1
#define fst first
#define snd second
using namespace std;
// Typedefs
typedef double real;
typedef long long ll;
typedef pair<ll, int> pli;
typedef pair<int, int> pii;
typedef unsigned long long ull;
// Some common const.
const double EPS = -1e8;
const double Pi = acos(-1);
// Equal for double
bool inline equ(double a, double b)
{return fabs(a - b) < EPS;}
// }}}
// start ~~~QAQ~~~
const int MAXV = 10010;
const int MAXE = 10010;
const int INF = 2147483647;
struct Edge{
    int u, v, c;
    Edge(){
        Edge(int x, int y, int z) :
            u(x), v(y), c(z){}
    };
    int V, E, root;
    Edge edges[MAXE];
    inline int newV(){
        V++;
        return V;
    }
    inline void addEdge(int u, int v, int c){
        E++;
        edges[E] = Edge(u, v, c);
    }
    bool con[MAXV];
    int mnInW[MAXV], prv[MAXV], cyc[MAXV], vis[MAXV];
    inline int DMST(){
        fill(con, con+V+1, 0);
        int r1 = 0, r2 = 0;
        while(1){
            fill(mnInW, mnInW+V+1, INF);
            fill(prv, prv+V+1, -1);
            REP(i, 1, E){
                int u = edges[i].u, v = edges[i].v, c = edges[i].c;
                if(u != v && v != root && c < mnInW[v])
                    mnInW[v] = c, prv[v] = u;
            }
            fill(vis, vis+V+1, -1);
            fill(cyc, cyc+V+1, -1);
            r1 = 0;
            bool jf = 0;

```

```

            REP(i, 1, V){
                if(con[i]) continue;
                if(prv[i] == -1 && i != root) return -1;
                if(prv[i] > 0) r1 += mnInW[i];
                int s;
                for(s = i; s != -1 && vis[s] == -1; s = prv[s])
                    vis[s] = i;
                if(s > 0 && vis[s] == i){
                    // get a cycle
                    jf = 1;
                    int v = s;
                    do{
                        cyc[v] = s, con[v] = 1;
                        r2 += mnInW[v];
                        v = prv[v];
                    }while(v != s);
                    con[s] = 0;
                }
            }
            if(!jf) break;
            REP(i, 1, E){
                int &u = edges[i].u;
                int &v = edges[i].v;
                if(cyc[v] > 0) edges[i].c -= mnInW[edges[i].v];
                if(cyc[u] > 0) edges[i].u = cyc[edges[i].u];
                if(cyc[v] > 0) edges[i].v = cyc[edges[i].v];
                if(u == v) edges[i--] = edges[E--];
            }
        }
        return r1+r2;
    }
}
int main(){
    ios_base::sync_with_stdio(0);
}

```

2.3 ISAP

```

#include <bits/stdc++.h>
#define SZ(c) ((int)(c).size())
using namespace std;
struct Maxflow {
    static const int MAXV = 20010;
    static const int INF = 1000000;
    struct Edge {
        int v, c, r;
        Edge(int _v, int _c, int _r) : v(_v), c(_c), r(_r) {}
    };
    int s, t;
    vector<Edge> G[MAXV*2];
    int iter[MAXV*2], d[MAXV*2], gap[MAXV*2], tot;
    void flowinit(int x) {
        tot = x+2;
        s = x+1, t = x+2;
        for(int i = 0; i <= tot; i++) {
            G[i].clear();
            iter[i] = d[i] = gap[i] = 0;
        }
    }
    void addEdge(int u, int v, int c) {
        G[u].push_back(Edge(v, c, SZ(G[v])));
        G[v].push_back(Edge(u, 0, SZ(G[u]) - 1));
    }
    int dfs(int p, int flow) {
        if(p == t) return flow;
        for(int &i = iter[p]; i < SZ(G[p]); i++) {
            Edge &e = G[p][i];
            if(e.c > 0 && d[p] == d[e.v]+1) {
                int f = dfs(e.v, min(flow, e.c));
                if(f) {
                    e.c -= f;
                    G[e.v][e.r].c += f;
                    return f;
                }
            }
        }
        if( (--gap[d[p]]) == 0) d[s] = tot;
        else {
            d[p]++;
            iter[p] = 0;
        }
    }
}

```

```

    ++gap[d[p]];
  }
  return 0;
}

int maxflow() {
  //puts("MF");
  int res = 0;
  gap[0] = tot;
  for(res = 0; d[s] < tot; res += dfs(s, INF));
  return res;
}
} flow;

Maxflow::Edge e(1, 1, 1);

```

2.4 MinCostFlow

```

/*
  A template for Min Cost Max Flow
  tested with TIOJ 1724
*/
#include <bits/stdc++.h>
using namespace std;
struct MinCostMaxFlow{
  static const int MAXV = 20010;
  static const int INF = 1000000000;
  struct Edge{
    int v, cap, w, rev;
    Edge(){}
    Edge(int t2, int t3, int t4, int t5)
      : v(t2), cap(t3), w(t4), rev(t5) {}
  };
  int V, s, t;
  vector<Edge> g[MAXV];
  void init(int n){
    V = n+2;
    s = n+1, t = n+2;
    for(int i = 1; i <= V; i++) g[i].clear();
  }
  void addEdge(int a, int b, int cap, int w){
    //printf("addEdge %d %d %d %d\n", a, b, cap, w);
    g[a].push_back(Edge(b, cap, w, (int) g[b].size()));
    g[b].push_back(Edge(a, 0, -w, ((int) g[a].size() - 1)));
  }
  int d[MAXV], id[MAXV], mom[MAXV];
  bool inqu[MAXV];
  int qu[2000000], ql, qr; //the size of qu should be
  much larger than MAXV
  int mncmxf(){
    int mxf = 0, mnc = 0;
    while(1){
      fill(d+1, d+1+V, -INF);
      fill(inqu+1, inqu+1+V, 0);
      fill(mom+1, mom+1+V, -1);
      mom[s] = s;
      d[s] = 0;
      ql = 1, qr = 0;
      qu[++qr] = s;
      inqu[s] = 1;
      while(ql <= qr){
        int u = qu[ql++];
        inqu[u] = 0;
        for(int i = 0; i < (int) g[u].size(); i++){
          Edge &e = g[u][i];
          int v = e.v;
          if(e.cap > 0 && d[v] < d[u]+e.w){
            // for min cost : d[v] > d[u]+e.w
            d[v] = d[u]+e.w;
            mom[v] = u;
            id[v] = i;
            if(!inqu[v]) qu[++qr] = v, inqu[v] = 1;
          }
        }
      }
      if(mom[t] == -1) break;
      int df = INF;
      for(int u = t; u != s; u = mom[u])
        df = min(df, g[mom[u]][id[u]].cap);
    }
  }
}

```

```

for(int u = t; u != s; u = mom[u]){
  Edge &e = g[mom[u]][id[u]];
  e.cap -= df;
  g[e.v][e.rev].cap += df;
}
//printf("mxf %d mnc %d\n", mxf, mnc);
mxf += df;
mnc += df*d[t];
//printf("mxf %d mnc %d\n", mxf, mnc);
}
return mnc;
}
} flow;

```

2.5 SW min-cut

```

struct SW{ // O(V^3)
  static const int MXN = 514;
  int n, vst[MXN], del[MXN];
  int edge[MXN][MXN], wei[MXN];
  void init(int _n){
    n = _n;
    FZ(edge);
    FZ(del);
  }
  void add_edge(int u, int v, int w){
    edge[u][v] += w;
    edge[v][u] += w;
  }
  void search(int &s, int &t){
    FZ(vst); FZ(wei);
    s = t = -1;
    while(true){
      int mx=-1, cur=0;
      for(int i=0; i<n; i++){
        if(!del[i] && !vst[i] && mx<wei[i])
          cur = i, mx = wei[i];
        if(mx == -1) break;
      }
      vst[cur] = 1;
      s = t;
      t = cur;
      for(int i=0; i<n; i++){
        if(!vst[i] && !del[i]) wei[i] += edge[cur][i];
      }
    }
  }
  int solve(){
    int res = 2147483647;
    for(int i=0, x, y; i<n-1; i++){
      search(x, y);
      res = min(res, wei[y]);
      del[y] = 1;
      for(int j=0; j<n; j++){
        edge[x][j] = (edge[j][x] += edge[y][j]);
      }
    }
    return res;
  }
} graph;

```

2.6 HLPPA

```

/* Highest-Label Preflow Push Algorithm */
// tested with sgu-212 (more testing suggested)
int n, m, src, sink;
int deg[MAXN], adj[MAXN][MAXN], res[MAXN][MAXN]; //
  residual
capacity
// graph (i.e. all things above) should be constructed
beforehand
int ef[MAXN], ht[MAXN]; // excess flow, height
int apt[MAXN]; // the next adj index to try push
int htodo;
// highest label to check with
int hcnt[MAXN*2];
// number of nodes with height h
queue<int> ovque[MAXN*2]; // used to implement highest-
  label
selection
bool inqu[MAXN];

```

```

inline void push(int v,int u) {
    int a=min(ef[v],res[v][u]);
    ef[v]-=a; ef[u]+=a;
    res[v][u]-=a; res[u][v]+=a;
    if(!inque[u]) {
        inque[u]=1;
        ovque[ht[u]].push(u);
    }
}

inline void relabel(int v) {
    int i,u,oldh;
    oldh=ht[v]; ht[v]=2*n;
    for(i=0;i<deg[v];i++) {
        u=adj[v][i];
        if(res[v][u]) ht[v]=min(ht[u]+1,ht[v]);
    }
    // gap speedup
    hcnt[oldh]--; hcnt[ht[v]]++;
    if(0<oldh&&oldh<n&&hcnt[oldh]==0) {
        for(i=0;i<n;i++) {
            if(ht[i]>oldh&&ht[i]<n) {
                hcnt[ht[i]]--;
                hcnt[n]++;
                ht[i]=n;
            }
        }
    }
    // update queue
    htodo=ht[v]; ovque[ht[v]].push(v); inque[v]=1;
}

inline void initPreflow() {
    int i,u;
    for(i=0;i<n;i++) {
        ht[i]=ef[i]=0;
        apt[i]=0; inque[i]=0;
    }
    ht[src]=n;
    for(i=0;i<deg[src];i++) {
        u=adj[src][i];
        ef[u]=res[src][u];
        ef[src]-=ef[u];
        res[u][src]=ef[u];
        res[src][u]=0;
    }
    htodo=n-1;
    for(i=0;i<2*n;i++) {
        hcnt[i]=0;
        while(!ovque[i].empty()) ovque[i].pop();
    }
    for(i=0;i<n;i++) {
        if(i==src||i==sink) continue;
        if(ef[i]) {
            inque[i]=1;
            ovque[ht[i]].push(i);
        }
        hcnt[ht[i]]++;
    }
    // to ensure src & sink is never added to queue
    inque[src]=inque[sink]=1;
}

inline void discharge(int v) {
    int u;
    while(ef[v]) {
        if(apt[v]==deg[v]) {
            relabel(v);
            apt[v]=0;
            continue;
        }
        u=adj[v][apt[v]];
        if(res[v][u]&&ht[v]==ht[u]+1) push(v,u);
        else apt[v]++;
    }
}

inline void hlppa() {
    int v;
    list<int>::iterator it;
    initPreflow();
    while(htodo>=0) {
        if(!ovque[htodo].size()) {
            htodo--;
            continue;
        }
}

```

```

        v=ovque[htodo].front();
        ovque[htodo].pop();
        inque[v]=0;
        discharge(v);
    }
}

```

2.7 Hungarian

```

#define NIL -1
#define INF 1000000000
int n,matched;
int cost[MAXNUM][MAXNUM];
bool sets[MAXNUM]; // whether x is in set S
bool sett[MAXNUM]; // whether y is in set T
int xlabel[MAXNUM],ylabel[MAXNUM];
int xy[MAXNUM],yx[MAXNUM]; // matched with whom
int slack[MAXNUM]; // given y: min{xlabel[x]+ylabel[y]-cost
[x][y]} | x not in S
int prev[MAXNUM]; // for augmenting matching
inline void relabel() {
    int i,delta=INF;
    for(i=0;i<n;i++) if(!sett[i]) delta=min(slack[i],delta);
    for(i=0;i<n;i++) if(sets[i]) xlabel[i]-=delta;
    for(i=0;i<n;i++) {
        if(sett[i]) ylabel[i]+=delta;
        else slack[i]-=delta;
    }
}

inline void add_sets(int x) {
    int i;
    sets[x]=1;
    for(i=0;i<n;i++) {
        if(xlabel[x]+ylabel[i]-cost[x][i]<slack[i]) {
            slack[i]=xlabel[x]+ylabel[i]-cost[x][i];
            prev[i]=x;
        }
    }
}

inline void augment(int final) {
    int x=prev[final],y=final,tmp;
    matched++;
    while(1) {
        tmp=xy[x]; xy[x]=y; yx[y]=x; y=tmp;
        if(y==NIL) return;
        x=prev[y];
    }
}

inline void phase() {
    int i,y,root;
    for(i=0;i<n;i++) { sets[i]=sett[i]=0; slack[i]=INF; }
    for(root=0;root<n&&xy[root]!=NIL;root++);
    add_sets(root);
    while(1) {
        relabel();
        for(y=0;y<n;y++) if(!sett[y]&&slack[y]==0) break;
        if(yx[y]==NIL) { augment(y); return; }
        else { add_sets(yx[y]); sett[y]=1; }
    }
}

inline int hungarian() {
    int i,j,c=0;
    for(i=0;i<n;i++) {
        xy[i]=yx[i]=NIL;
        xlabel[i]=ylabel[i]=0;
        for(j=0;j<n;j++) xlabel[i]=max(cost[i][j],xlabel[i]);
    }
    for(i=0;i<n;i++) phase();
    for(i=0;i<n;i++) c+=cost[i][xy[i]];
    return c;
}

```

2.8 Hungarian Unbalanced

```

const int nil = -1;
const int inf = 1000000000;
int xn,yn,matched;
int cost[MAXN][MAXN];
bool sets[MAXN]; // whether x is in set S
bool sett[MAXN]; // whether y is in set T
int xlabel[MAXN],ylabel[MAXN];
int xy[MAXN],yx[MAXN]; // matched with whom
int slack[MAXN]; // given y: min{xlabel[x]+ylabel[y]-cost[x
][y]} | x not in S
int prev[MAXN]; // for augmenting matching
inline void relabel() {
    int i,delta=inf;
    for(i=0;i<yn;i++) if(!sett[i]) delta=min(slack[i],delta);
    for(i=0;i<xn;i++) if(sets[i]) xlabel[i]-=delta;
    for(i=0;i<yn;i++) {
        if(sett[i]) ylabel[i]+=delta;
        else slack[i]-=delta;
    }
}
inline void add_sets(int x) {
    int i;
    sets[x]=1;
    for(i=0;i<yn;i++) {
        if(xlabel[x]+ylabel[i]-cost[x][i]<slack[i]) {
            slack[i]=xlabel[x]+ylabel[i]-cost[x][i];
            prev[i]=x;
        }
    }
}
inline void augment(int final) {
    int x=prev[final],y=final,tmp;
    matched++;
    while(1) {
        tmp=xy[x]; xy[x]=y; yx[y]=x; y=tmp;
        if(y==nil) return;
        x=prev[y];
    }
}
inline void phase() {
    int i,y,root;
    for(i=0;i<xn;i++) sets[i]=0;
    for(i=0;i<yn;i++) { sett[i]=0; slack[i]=inf; }
    for(root=0;root<xn&&xy[root]!=nil;root++);
    add_sets(root);
    while(1) {
        relabel();
        for(y=0;y<yn;y++) if(!sett[y]&&slack[y]==0) break;
        if(yx[y]==nil) { augment(y); return; }
        else { add_sets(yx[y]); sett[y]=1; }
    }
}
inline int hungarian() {
    int i,j,c=0;
    matched=0;
    // we must have "xn<yn"
    bool swapxy=0;
    if(xn>yn) {
        swapxy=1;
        int mn=max(xn,yn);
        swap(xn,yn);
        for(int i=0;i<mn;i++)
            for(int j=0;j<i;j++)
                swap(cost[i][j],cost[j][i]);
    }
    for(i=0;i<xn;i++) {
        xy[i]=nil;
        xlabel[i]=0;
        for(j=0;j<yn;j++) xlabel[i]=max(cost[i][j],xlabel[i]);
    }
    for(i=0;i<yn;i++) {
        yx[i]=nil;
        ylabel[i]=0;
    }
    for(i=0;i<xn;i++) phase();
    for(i=0;i<xn;i++) c+=cost[i][xy[i]];
    // recover cost matrix (if necessary)
    if(swapxy) {
        int mn=max(xn,yn);

```

```

        swap(xn,yn);
        for(int i=0;i<mn;i++)
            for(int j=0;j<i;j++)
                swap(cost[i][j],cost[j][i]);
    }
    // need special recovery if we want more info than
    // matching value
    return c;
}

```

2.9 Gusfield

```

#define SOURCE 0
#define SINK 1
const unsigned int inf=4000000000u;
int n,m,deg[MAXNUM],adj[MAXNUM][MAXNUM];
unsigned int res[MAXNUM][MAXNUM],cap[MAXNUM][MAXNUM];
int nei[MAXNUM],gdeg[MAXNUM],gadj[MAXNUM][MAXNUM];
unsigned int gres[MAXNUM][MAXNUM];
unsigned int cut[MAXNUM][MAXNUM];
unsigned int cutarr[MAXNUM*MAXNUM];
int cutn,ql,q,r,que[MAXNUM],pred[MAXNUM];
unsigned int aug[MAXNUM];
bool cutset[MAXNUM];
int visited[MAXNUM],visid=0;
inline void augment(int src,int sink) {
    int v=sink; unsigned a=aug[sink];
    while(v!=src) {
        res[pred[v]][v]-=a;
        res[v][pred[v]]+=a;
        v=pred[v];
    }
}
inline bool bfs(int src,int sink) {
    int i,v,u; ++visid;
    ql=qr=0; que[qr++]=src;
    visited[src]=visid; aug[src]=inf;
    while(ql<qr) {
        v=que[ql++];
        for(i=0;i<deg[v];i++) {
            u=adj[v][i];
            if(visited[u]==visid||res[v][u]==0) continue;
            visited[u]=visid; pred[u]=v;
            aug[u]=min(aug[v],res[v][u]);
            que[qr++]=u;
            if(u==sink) return 1;
        }
    }
    return 0;
}
void dfs_src(int v) {
    int i,u;
    visited[v]=visid;
    cutset[v]=SOURCE;
    for(i=0;i<deg[v];i++) {
        u=adj[v][i];
        if(visited[u]<visid&&res[v][u]) dfs_src(u);
    }
}
inline unsigned int maxflow(int src,int sink) {
    int i,j;
    unsigned int f=0;
    for(i=0;i<n;i++) {
        for(j=0;j<deg[i];j++) res[i][adj[i][j]]=cap[i][adj[i][j]];
        cutset[i]=SINK;
    }
    while(bfs(src,sink)) {
        augment(src,sink);
        f+=aug[sink];
    }
    ++visid;
    dfs_src(src);
    return f;
}
inline void gusfield() {
    int i,j;
    unsigned int f;
    for(i=0;i<n;i++) { nei[i]=0; gdeg[i]=0; }

```

```

for(i=1;i<n;i++) {
    f=maxflow(i,nei[i]);
    gres[i][nei[i]]=gres[nei[i]][i]=f;
    gadj[i][gdeg[i]++]=nei[i];
    gadj[nei[i]][gdeg[nei[i]]++]=i;
    for(j=i+1;j<n;j++)
        if(nei[j]==nei[i]&&cutset[j]==SOURCE) nei[j]=i;
}
void dfs(int v,int pred,int src,unsigned int cur) {
    int i,u;
    cut[src][v]=cur;
    for(i=0;i<gdeg[v];i++) {
        u=gadj[v][i];
        if(u==pred) continue;
        dfs(u,v,src,min(cur,gres[v][u]));
    }
}
inline void find_all_cuts() {
    int i;
    cutn=0; gusfield();
    for(i=0;i<n;i++) dfs(i,-1,i,inf);
}

```

2.10 Relabel to Front

```

/* Relabel-to-Front */
// tested with sgu-212 (more testing suggested)
int n,m,layer,src,sink,lv1[MAXN];
Edge ed[MAXM];
int deg[MAXN],adj[MAXN][MAXN];
int res[MAXN][MAXN]; // residual capacity
// graph (i.e. all things above) should be constructed
beforehand
list<int> lst; // discharge list
int ef[MAXN],ht[MAXN];
// excess flow, height
int apt[MAXN]; // the next adj index to try push
inline void push(int v,int u) {
    int a=min(ef[v],res[v][u]);
    ef[v]-=a; ef[u]+=a;
    res[v][u]-=a; res[u][v]+=a;
}
inline void relabel(int v) {
    int i,u;
    ht[v]=2*n;
    for(i=0;i<deg[v];i++) {
        u=adj[v][i];
        if(res[v][u]) ht[v]=min(ht[u]+1,ht[v]);
    }
}
inline void initPreflow() {
    int i,u;
    lst.clear();
    for(i=0;i<n;i++) {
        ht[i]=ef[i]=0; apt[i]=0;
        if(i!=src&&i!=sink) lst.push_back(i);
    }
    ht[src]=n;
    for(i=0;i<deg[src];i++) {
        u=adj[src][i];
        ef[u]=res[src][u];
        ef[src]-=ef[u];
        res[u][src]=ef[u];
        res[src][u]=0;
    }
}
inline void discharge(int v) {
    int u;
    while(ef[v]) {
        if(apt[v]==deg[v]) {
            relabel(v);
            apt[v]=0;
            continue;
        }
        u=adj[v][apt[v]];
        if(res[v][u]&&ht[v]==ht[u]+1) push(v,u);
        else apt[v]++;
    }
}

```

```

inline void relabelToFront() {
    int oldh,v;
    list<int>::iterator it;
    initPreflow();
    for(it=lst.begin();it!=lst.end();it++) {
        v=*it; oldh=ht[v]; discharge(v);
        if(ht[v]>oldh) {
            lst.push_front(v);
            lst.erase(it);
            it=lst.begin();
        }
    }
}

```

2.11 Flow Method

Maximize $c^T x$ subject to $Ax \leq b$, $x \geq 0$;
with the corresponding symmetric dual problem,
Minimize $b^T y$ subject to $A^T y \geq c$, $y \geq 0$.

Maximize $c^T x$ subject to $Ax \leq b$;
with the corresponding asymmetric dual problem,
Minimize $b^T y$ subject to $A^T y = c$, $y \geq 0$.

有源匯，有下界，最大流，無費用。

先從 t 連向 s ，容量設為無限大。這樣就變成了無源匯的情況。將每條有下界的邊先滿上下界的流量，然後更新盈餘量（入的流量-出的流量）。新建超級源 ss 和超級匯 tt ，若某個點 u 的盈餘量 >0 則 $ss \rightarrow u$ ，容量為 u 的盈餘量。否則 $u \rightarrow tt$ ，容量為 u 的盈餘量的相反數。如果一個點的盈餘量 >0 ，則它是一定要流出去的，所以要從 ss 連向它，使它去找這些流量的出路。建完了圖以後求一遍最大流，如果從 ss 連出的所有邊都滿流，則有解。在得到的殘留網路（原圖）上再求一次最大流即可。

3 Math

3.1 FFT

```

#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
typedef unsigned int uint;
#define maxn 310010
#define nmaxn 141073
struct comp{
    double a , b ;
    comp( double a_ = 0.0 , double b_ = 0.0 ) : a( a_ )
    , b( b_ ){ }
} null ;
comp operator+ ( const comp &a , const comp &b ) {
    return comp(a.a+b.a,a.b+b.b); }
comp operator- ( const comp &a , const comp &b ) {
    return comp(a.a-b.a,a.b-b.b); }
comp operator* ( const comp &a , const comp &b ) {
    return comp(a.a*b.a-a.b*b.b,a.a*b.b+a.b*b.a); }
char s[ maxn ] ;
int n ;
comp A[ nmaxn ] , B[ nmaxn ] , C[ nmaxn ] ;
const double pi = acos( -1 ) ;
int L = 6 ;
ll base[ 10 ] , M = 1000000 ;
int get( comp *A ){
    if ( scanf( "%s" , s ) == EOF ) return 0 ;
    int a = 0 , p = 0 , l = 0 ;
    for ( register int i = strlen( s ) - 1 ; i >= 0 ; i -- ) {
        a += ( s[ i ] - '0' ) * base[ p ++ ] ;
        if( p == L ) A[ l ++ ] = comp( a , 0 ) , a = p = 0 ;
    }
    if ( a ) A[ l ++ ] = comp( a , 0 ) ;
    return l ;
}

```



```

bool init(){
    base[ 0 ] = 1 ;
    for ( register int i = 1 ; i <= L ; i ++ ) base[ i ]
        = base[ i - 1 ] * 10 ;
    int l = get( A ) + get( B );
    if ( l == 0 ) return false ;
    for ( n = 1 ; n < l ; n <= 1 );
    //printf( "%d\n" , n );
    return true ;
}
comp p[ 2 ][ nmaxn ]; int typ;
uint rev( uint a ){
    a = ( ( a & 0x55555555U ) << 1 ) | ( ( a & 0
        xAAAAAAAAU ) >> 1 );
    a = ( ( a & 0x33333333U ) << 2 ) | ( ( a & 0
        xCCCCCCCU ) >> 2 );
    a = ( ( a & 0x0F0F0F0FU ) << 4 ) | ( ( a & 0
        xF0F0F0FU ) >> 4 );
    a = ( ( a & 0x00FF00FFU ) << 8 ) | ( ( a & 0
        xFF00FF00U ) >> 8 );
    a = ( ( a & 0x0000FFFFU ) << 16 ) | ( ( a & 0
        xFFFF0000U ) >> 16 );
    return a;
}
void FFT( comp *s , comp *bac , int n ){
    register int d = log2( n );
    for ( register int i = 0 ; i < n ; i ++ ) s[ rev( i )
        >> ( 32 - d ) ] = bac[ i ];
    for ( register int i = 1 ; i <= d ; i ++ ) {
        int step = 1 << i , v = step >> 1 , rstep = n /
            step ;
        for ( register int j = 0 ; j <= n - 1 ; j += step )
            {
                comp *t = p[ typ ];
                for ( register int k = 0 ; k < v ; k ++ , t +=
                    rstep ) {
                    comp d = ( *t ) * s[ k + j + v ];
                    s[ k + j + v ] = s[ k + j ] - d ;
                    s[ k + j ] = s[ k + j ] + d ;
                }
            }
    }
}
ll ans[ 4 * maxn ];
bool work(){
    if ( !init() ) return false ;
    p[ 0 ][ 0 ] = comp( 1 , 0 ) , p[ 1 ][ 0 ] = comp( 1 ,
        0 );
    for ( register int i = 1 ; i < n ; i ++ ) {
        p[ 0 ][ i ] = comp( cos( 2 * i * pi / n ) , sin( 2
            * i * pi / n ) );
        p[ 1 ][ i ] = comp( cos( 2 * i * pi / n ) , -sin( 2
            * i * pi / n ) );
    }
    typ = 0 ; FFT( C , A , n ) , FFT( A , B , n );
    for ( register int i = 0 ; i < n ; i ++ ) A[ i ] = A[
        i ] * C[ i ];
    typ = 1 ; FFT( C , A , n );
    for ( register int i = 0 ; i < n ; i ++ )
        ans[ i ] = C[ i ].a / n + 0.1 , A[ i ] = null , B[
            i ] = null ;
    for ( register int i = 0 ; i < n ; i ++ )
        if ( ans[ i ] >= M ) ans[ i + 1 ] += ans[ i ] / M ,
            ans[ i ] %= M ;
    while ( n > 1 && ans[ n - 1 ] <= 0 ) n -- ;
    printf( "%lld" , ans[ n - 1 ] );
    for( register int i = n - 2 ; i >= 0 ; i -- ) printf(
        "%06lld" , ans[ i ] );
    puts( "" );
    return true ;
}
int main(){
    while ( work() );
}

```

```

/*
p=a*2^n+1
n 2^n      p      a      root
5 32      97      3      5
6 64      193     3      5
7 128     257     2      3
8 256     257     1      3
9 512     7681    15     17
10 1024    12289   12     11
11 2048    12289   6      11
12 4096    12289   3      11
13 8192    40961   5      3
14 16384   65537   4      3
15 32768   65537   2      3
16 65536   65537   1      3
17 131072  786433   6     10
18 262144  786433   3     10 (605028353,
    2308, 3)
19 524288  5767169  11     3
20 1048576 7340033   7      3
21 2097152 23068673  11     3
22 4194304 104857601 25     3
23 8388608 167772161 20     3
24 16777216 167772161 10     3
25 33554432 167772161 5      3 (1107296257, 33,
    10)
26 67108864 469762049 7      3
27 134217728 2013265921 15     31
*/
ll bigmod(ll a,ll b){
    if(b==0)return 1;
    return (bigmod((a*a)%P,b/2)*(b%2?a:1ll))%P;
}
ll inv(ll a,ll b){
    if(a==1)return 1;
    return (((long long)(a-inv(b%a,a))*b+1)/a)%b;
}
std::vector<ll> ps(MAXNUM);
std::vector<ll> rev(MAXNUM);
struct poly{
    std::vector<ll> co;
    int n;//polynomial degree = n
    poly(int d){n=d;co.resize(n+1,0);}
    void trans2(int NN){
        int r=0,st,N;
        unsigned int a,b;
        while((1<<r)<(NN>>1))++r;
        for(N=2;N<=NN;N<=1,--r){
            for(st=0;st<NN;st+=N){
                int i,ss=st+(N>>1);
                for(i=(N>>1)-1;i>=0;--i){
                    a=co[st+i]; b=(ps[i<<r]*co[ss+i])%P;
                    co[st+i]=a+b; if(co[st+i]>=P)co[st+i]-=P;
                    co[ss+i]=a-P-b; if(co[ss+i]>=P)co[ss+i]-=P;
                }
            }
        }
    }
}
void trans1(int NN){
    int r=0,st,N;
    unsigned int a,b;
    for(N=NN;N>1;N>=1,++r){
        for(st=0;st<NN;st+=N){
            int i,ss=st+(N>>1);
            for(i=(N>>1)-1;i>=0;--i){
                a=co[st+i]; b=co[ss+i];
                co[st+i]=a+b; if(co[st+i]>=P)co[st+i]-=P;
                co[ss+i]=(a+P-b)*ps[i<<r]%P;
            }
        }
    }
}
poly operator*(const poly& _b)const{
    poly a=*this,b=_b;
    int k=n+b.n,i,N=1;
    while(N<=k)N*=2;
    a.co.resize(N,0); b.co.resize(N,0);
    int r=bigmod(root,(P-1)/N),Ni=inv(N,P);
    ps[0]=1;
    for(i=1;i<N;++i)ps[i]=(ps[i-1]*r)%P;
    a.trans1(N);b.trans1(N);

```

3.2 NTT

```

ll P=2013265921,root=31;
int MAXNUM=4194304;
// Remember coefficient are mod P

```

```

    for(i=0;i<N;++i)a.co[i]=((long long)a.co[i]*b.co[i]
    ])%P;
    r=inv(r,P);
    for(i=1;i<N/2;++i)std::swap(ps[i],ps[N-i]);
    a.trans2(N);
    for(i=0;i<N;++i)a.co[i]=((long long)a.co[i]*Ni)%P;
    a.n=n+_b.n; return a;
}
};

```

3.3 BigInt

```

struct BigInt{
    static const int LEN = 60;
    static const int BIGMOD = 10000;

    int s;
    int vl, v[LEN];
    // vector<int> v;
    BigInt() : s(1) { vl = 0; }
    BigInt(long long a) {
        s = 1; vl = 0;
        if (a < 0) { s = -1; a = -a; }
        while (a) {
            push_back(a % BIGMOD);
            a /= BIGMOD;
        }
    }
    BigInt(string str) {
        s = 1; vl = 0;
        int stPos = 0, num = 0;
        if (!str.empty() && str[0] == '-') {
            stPos = 1;
            s = -1;
        }
        for (int i=SZ(str)-1, q=1; i>=stPos; i--) {
            num += (str[i] - '0') * q;
            if ((q *= 10) >= BIGMOD) {
                push_back(num);
                num = 0; q = 1;
            }
        }
        if (num) push_back(num);
    }

    int len() const {
        return vl;
        // return SZ(v);
    }
    bool empty() const { return len() == 0; }
    void push_back(int x) {
        v[vl++] = x;
        // v.PB(x);
    }
    void pop_back() {
        vl--;
        // v.pop_back();
    }
    int back() const {
        return v[vl-1];
        // return v.back();
    }
    void n() {
        while (!empty() && !back()) pop_back();
    }
    void resize(int nl) {
        vl = nl;
        fill(v, v+vl, 0);
        // v.resize(nl);
        // fill(ALL(v), 0);
    }

    void print() const {
        if (empty()) { putchar('0'); return; }
        if (s == -1) putchar('-');
        printf("%d", back());
        for (int i=len()-2; i>=0; i--) printf("%.4d",v[i]);
    }
    friend std::ostream& operator << (std::ostream& out,
        const BigInt &a) {

```

```

        if (a.empty()) { out << "0"; return out; }
        if (a.s == -1) out << "-";
        out << a.back();
        for (int i=a.len()-2; i>=0; i--) {
            char str[10];
            snprintf(str, 5, "%.4d", a.v[i]);
            out << str;
        }
        return out;
    }

    int cp3(const BigInt &b) const {
        if (s != b.s) return s > b.s;
        if (s == -1) return -(*this).cp3(-b);
        if (len() != b.len()) return len()>b.len()?1:-1;
        for (int i=len()-1; i>=0; i--)
            if (v[i]!=b.v[i]) return v[i]>b.v[i]?1:-1;
        return 0;
    }
    bool operator < (const BigInt &b) const { return cp3(b)
        ==-1; }
    bool operator == (const BigInt &b) const { return cp3(b)
        ==0; }
    bool operator > (const BigInt &b) const { return cp3(b)
        ==1; }

    BigInt operator - () const {
        BigInt r = (*this);
        r.s = -r.s;
        return r;
    }
    BigInt operator + (const BigInt &b) const {
        if (s == -1) return -(-(*this)+(-b));
        if (b.s == -1) return (*this)-(-b);
        BigInt r;
        int nl = max(len(), b.len());
        r.resize(nl + 1);
        for (int i=0; i<nl; i++) {
            if (i < len()) r.v[i] += v[i];
            if (i < b.len()) r.v[i] += b.v[i];
            if (r.v[i] >= BIGMOD) {
                r.v[i+1] += r.v[i] / BIGMOD;
                r.v[i] %= BIGMOD;
            }
        }
        r.n();
        return r;
    }
    BigInt operator - (const BigInt &b) const {
        if (s == -1) return -(-(*this)-(-b));
        if (b.s == -1) return (*this)+(-b);
        if ((*this) < b) return -(b-(*this));
        BigInt r;
        r.resize(len());
        for (int i=0; i<len(); i++) {
            r.v[i] += v[i];
            if (i < b.len()) r.v[i] -= b.v[i];
            if (r.v[i] < 0) {
                r.v[i] += BIGMOD;
                r.v[i+1]--;
            }
        }
        r.n();
        return r;
    }
    BigInt operator * (const BigInt &b) {
        BigInt r;
        r.resize(len() + b.len() + 1);
        r.s = s * b.s;
        for (int i=0; i<len(); i++) {
            for (int j=0; j<b.len(); j++) {
                r.v[i+j] += v[i] * b.v[j];
                if (r.v[i+j] >= BIGMOD) {
                    r.v[i+j+1] += r.v[i+j] / BIGMOD;
                    r.v[i+j] %= BIGMOD;
                }
            }
        }
        r.n();
        return r;
    }
    BigInt operator / (const BigInt &b) {

```



```

Bigint r;
r.resize(max(1, len()-b.len()+1));
int oriS = s;
Bigint b2 = b; // b2 = abs(b)
s = b2.s = r.s = 1;
for (int i=r.len()-1; i>=0; i--) {
    int d=0, u=BIGMOD-1;
    while(d<u) {
        int m = (d+u+1)>>1;
        r.v[i] = m;
        if((r*b2) > (*this)) u = m-1;
        else d = m;
    }
    r.v[i] = d;
}
s = oriS;
r.s = s * b.s;
r.n();
return r;
}
Bigint operator % (const Bigint &b) {
    return (*this)-(*this)/b*b;
}
};

```

3.4 Linear Recurrence

```

ll n, m;
ll dp[ N + N ];
void pre_dp(){
    dp[ 0 ] = 1;
    ll bdr = min( m + m , n );
    for( ll i = 1 ; i <= bdr ; i ++ )
        for( ll j = i - 1 ; j >= max( 0ll , i - m ) ; j -- )
            dp[ i ] = add( dp[ i ] , dp[ j ] );
}
vector<ll> Mul( const vector<ll>& v1, const vector<ll>&
v2 ){
    int _sz1 = (int)v1.size();
    int _sz2 = (int)v2.size();
    assert( _sz1 == m );
    assert( _sz2 == m );
    vector<ll> _v( m + m );
    for( int i = 0 ; i < m + m ; i ++ ) _v[ i ] = 0;
    // expand
    for( int i = 0 ; i < _sz1 ; i ++ )
        for( int j = 0 ; j < _sz2 ; j ++ )
            _v[ i + j + 1 ] = add( _v[ i + j + 1 ] , mul( v1[
i ] , v2[ j ] ) );
    // shrink
    for( int i = 0 ; i < m ; i ++ )
        for( int j = 1 ; j <= m ; j ++ )
            _v[ i + j ] = add( _v[ i + j ] , _v[ i ] );
    for( int i = 0 ; i < m ; i ++ )
        _v[ i ] = _v[ i + m ];
    _v.resize( m );
    return _v;
}
vector<ll> I, A;
void solve(){
    pre_dp();
    if( n <= m + m ){
        printf( "%lld\n" , dp[ n ] );
        exit( 0 );
    }
    I.resize( m );
    A.resize( m );
    for( int i = 0 ; i < m ; i ++ ) I[ i ] = A[ i ] = 1;
    // dp[ n ] = /Sum_{i=0}^{m-1} A_i * dp[ n - i - 1 ]
    ll dlt = ( n - m ) / m;
    ll rdl = dlt * m;
    while( dlt ){
        if( dlt & 1ll ) I = Mul( I , A );
        A = Mul( A , A );
        dlt >>= 1;
    }
    ll ans = 0;
    for( int i = 0 ; i < m ; i ++ )

```

```

        ans = add( ans , mul( I[ i ] , dp[ n - i - 1 - rdl
] ) );
    printf( "%lld\n" , ans );
}

```

3.5 Miller Rabin

```

// n < 4,759,123,141      3 : 2, 7, 61
// n < 1,122,004,669,633  4 : 2, 13, 23, 1662803
// n < 3,474,749,660,383  6 : pimes <= 13
// n < 3,825,123,056,546,413,051  9 : primes <= 23
long long power(long long x, long long p, long long mod){
    long long s=1, m=x;
    while(p) {
        if(p&1) s=mult(s, m, mod);
        p>>=1;
        m=mult(m, m, mod);
    }
    return s;
}
bool witness(long long a, long long n, long long u, int t)
{
    long long x=power(a, u, n);
    for(int i=0; i<t; i++) {
        long long nx=mult(x, x, n);
        if(nx==1&&x!=1&&x!=n-1) return 1;
        x=nx;
    }
    return x!=1;
}
bool miller_rabin(long long n, int s=100) {
    // iterate s times of witness on n
    // return 1 if prime, 0 otherwise
    if(n<2) return 0;
    if(!(n&1)) return n==2;
    long long u=n-1;
    int t=0;
    // n-1 = u*2^t
    while(u&1) {
        u>>=1;
        t++;
    }
    while(s--){
        long long a=randll()%(n-1)+1;
        if(witness(a, n, u, t)) return 0;
    }
    return 1;
}

```

3.6 PollardRho

```

/* pollard rho */
// does not work when n is prime
long long modit(long long x, long long mod) {
    if(x>=mod) x-=mod;
    //if(x<0) x+=mod;
    return x;
}
long long mult(long long x, long long y, long long mod) {
    long long s=0, m=x%mod;
    while(y) {
        if(y&1) s=modit(s+m, mod);
        y>>=1;
        m=modit(m+m, mod);
    }
    return s;
}
long long f(long long x, long long mod) {
    return modit(mult(x, x, mod)+1, mod);
}
long long pollard_rho(long long n) {
    long long x, x2;
    if(!(n&1)) return 2;
    //x=x2=randll()%n;
    x=x2=2;
    while(1) {
        x=f(x, n); x2=f(f(x2, n), n);
        long long d=__gcd(abs(x-x2), n);

```

```

    if(d!=1&&d!=n) return d;
}
}

```

3.7 Simplex

```

const int maxn = 111;
const int maxm = 111;
const double eps = 1E-10;

double a[maxn][maxm], b[maxn], c[maxm], d[maxn][maxm];
double x[maxm];
int ix[maxn + maxm]; // !!! array all indexed from 0
// max{cx} subject to {Ax<=b,x>=0}
// n: constraints, m: vars !!!
// x[] is the optimal solution vector
//
// usage :
// value = simplex(a, b, c, N, M);
double simplex(double a[maxn][maxm], double b[maxn],
    double c[maxm], int n, int m) {
    ++m;
    int r = n, s = m - 1;
    memset(d, 0, sizeof(d));
    for (int i = 0; i < n + m; ++i) ix[i] = i;
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < m - 1; ++j) d[i][j] = -a[i][j];
        d[i][m - 1] = 1;
        d[i][m] = b[i];
        if (d[r][m] > d[i][m]) r = i;
    }
    for (int j = 0; j < m - 1; ++j) d[n][j] = c[j];
    d[n + 1][m - 1] = -1;
    for (double dd;;) {
        if (r < n) {
            int t = ix[s]; ix[s] = ix[r + m]; ix[r + m] = t;
            d[r][s] = 1.0 / d[r][s];
            for (int j = 0; j <= m; ++j) if (j != s) d[r][j] *= -d[r][s];
            for (int i = 0; i <= n + 1; ++i) if (i != r) {
                for (int j = 0; j <= m; ++j) if (j != s)
                    d[i][j] += d[r][j] * d[i][s];
                d[i][s] *= d[r][s];
            }
        }
        r = -1; s = -1;
        for (int j = 0; j < m; ++j) if (s < 0 || ix[s] > ix[j]) {
            if (d[n + 1][j] > eps || (d[n + 1][j] > -eps && d[n][j] > eps)) s = j;
        }
        if (s < 0) break;
        for (int i = 0; i < n; ++i) if (d[i][s] < -eps) {
            if (r < 0 || (dd = d[r][m] / d[r][s] - d[i][m] / d[i][s]) < -eps || (dd < eps && ix[r + m] > ix[i + m])) r = i;
        }
        if (r < 0) return -1; // not bounded
    }
    if (d[n + 1][m] < -eps) return -1; // not executable
    double ans = 0;
    for (int i = 0; i < m; ++i) x[i] = 0;
    for (int i = m; i < n + m; ++i) { // the missing enumerated x[i] = 0
        if (ix[i] < m - 1) {
            ans += d[i - m][m] * c[ix[i]];
            x[ix[i]] = d[i - m][m];
        }
    }
    return ans;
}

```

3.8 Faulhaber

```

/* faulhaber 's formula -
 * calculate power sum formula of all p=1~k in O(k^2)
 */
#define MAXK 2500
const int mod = 1000000007;
int b[MAXK];
// bernoulli number
int inv[MAXK+1];
// inverse
int cm[MAXK+1][MAXK+1]; // combinactories
int co[MAXK][MAXK+2];
// coeeficient of x^j when p=i
inline int add(int a,int b) { return a+b<mod?a+b:a+b-mod; }
inline int sub(int a,int b) { return a<b?a-b+mod:a-b; }
inline int getinv(int x) {
    int a=x,b=mod,a0=1,a1=0,b0=0,b1=1;
    while(b) {
        int q,t;
        q=a/b; t=b; b=a-b*q; a=t;
        t=b0; b0=a0-b0*q; a0=t;
        t=b1; b1=a1-b1*q; a1=t;
    }
    return a0<0?a0+mod:a0;
}
inline void pre() {
    /* combinational */
    for (int i=0;i<=MAXK;i++) {
        cm[i][0]=cm[i][i]=1;
        for (int j=1;j<i;j++) cm[i][j]=add(cm[i-1][j-1],cm[i-1][j]);
    }
    /* inverse */
    for (int i=1;i<=MAXK;i++) inv[i]=getinv(i);
    /* bernoulli */
    b[0]=1; b[1]=getinv(2); // with b[1] = 1/2
    for (int i=2;i<=MAXK;i++) {
        if (i&1) { b[i]=0; continue; }
        b[i]=1;
        for (int j=0;j<i;j++)
            b[i]=sub(b[i],(long long)cm[i][j]*b[j]%mod*inv[i-j+1]%mod);
    }
    /* faulhaber */
    // sigma_x=1~n {x^p} = 1/(p+1) * sigma_j=0~p { C(p+1,j) *
    // Bj * n^(p-j+1)}
    for (int i=1;i<=MAXK;i++) {
        co[i][0]=0;
        for (int j=0;j<i;j++)
            co[i][i-j+1]=(long long)inv[i+1]%mod*cm[i+1][j]%mod*b[j]%mod;
    }
}
inline int power(int x,int p) {
    int s=1,m=x;
    while(p) {
        if (p&1) s=(long long)s*m%mod;
        p>>=1; m=(long long)m*m%mod;
    }
    return s;
}
/* sample usage: return f(n,p) = sigma_x=1~n (x^p) */
inline int solve(int n,int p) {
    int sol=0,m=n;
    for (int i=1;i<=p+1;i++) {
        sol=add(sol,(long long)co[p][i]*m%mod);
        m=(long long)m*n%mod;
    }
    return sol;
}

```

3.9 Chinese Remainder

```

int pfn;
// number of distinct prime factors

```

```

int pf[MAXNUM]; // prime factor powers
int rem[MAXNUM]; // corresponding remainder
int pm[MAXNUM];
inline void generate_primes() {
    int i,j;
    pnum=1;
    prime[0]=2;
    for(i=3;i<MAXVAL;i+=2) {
        if(nprime[i]) continue;
        prime[pnum++]=i;
        for(j=i*i;j<MAXVAL;j+=i) nprime[j]=1;
    }
}
inline int inverse(int x,int p) {
    int q,tmp,a=x,b=p;
    int a0=1,a1=0,b0=0,b1=1;
    while(b) {
        q=a/b; tmp=b; b=a-b*q; a=tmp;
        tmp=b0; b0=a0-b0*q; a0=tmp;
        tmp=b1; b1=a1-b1*q; a1=tmp;
    }
    return a0;
}
inline void decompose_mod() {
    int i,p,t=mod;
    pfn=0;
    for(i=0;i<pnum&&prime[i]<=t;i++) {
        p=prime[i];
        if(t%p==0) {
            pf[pfn]=1;
            while(t%p==0) {
                t/=p;
                pf[pfn]*=p;
            }
            pfn++;
        }
        if(t>1) pf[pfn++]=t;
    }
}
inline int chinese_remainder() {
    int i,m,s=0;
    for(i=0;i<pfn;i++) {
        m=mod/pf[i];
        pm[i]=(long long)m*inverse(m,pf[i])%mod;
        s=(s+(long long)pm[i]*rem[i])%mod;
    }
    return s;
}

```

3.10 Pollard Rho

```

/* pollard rho */
// does not work when n is prime
}
/* faulhaber */
// sigma_x=1~n {x^p} = 1/(p+1) * sigma_j=0~p { C(p+1,j)
// * n^(p-j+1) }
for(int i=1;i<MAXK;i++) {
    co[i][0]=0;
    for(int j=0;j<=i;j++)
        co[i][i-j+1]=(long long)inv[i+1]%mod*cm[i+1][j]%mod
        *b[j]%mod;
}
}
inline int power(int x,int p) {
    int s=1,m=x;
    while(p) {
        if(p&1) s=(long long)s*m%mod;
        p>>=1; m=(long long)m*m%mod;
    }
    return s;
}
/* sample usage: return f(n,p) = sigma_x=1~n (x^p) */
inline int solve(int n,int p) {
    int sol=0,m=n;
    for(int i=1;i<=p+1;i++) {
        sol=add(sol,(long long)co[p][i]*m%mod);
        m=(long long)m*n%mod;
    }
}

```

```

return sol;
}
5.3 MillerRabbin
/* miller rabin */
inline long long power(long long x,long long p,long
    long mod
    ) {
    long long s=1,m=x;
    while(p) {
        if(p&1) s=mult(s,m,mod);
        p>>=1;
        m=mult(m,m,mod);
    }
    return s;
}
inline bool witness(long long a,long long n,long long u
    ,int
    t) {
    long long x=power(a,u,n);
    for(int i=0;i<t;i++) {
        long long nx=mult(x,x,n);
        if(nx==1&&x!=1&&x!=n-1) return 1;
        x=nx;
    }
    return x!=1;
}
inline long long gcd(long long a,long long b) {
    while(b) {
        long long t=b;
        b=a%b;
        a=t;
    }
    return a;
}
inline long long modit(long long x,long long mod) {
    if(x>=mod) x-=mod;
    //if(x<0) x+=mod;
    return x;
}
inline long long mult(long long x,long long y,long long
    mod)
{
    long long s=0,m=x%mod;
    while(y) {
        if(y&1) s=modit(s+m,mod);
        y>>=1;
        m=modit(m+m,mod);
    }
    return s;
}
inline long long f(long long x,long long mod) {
    return modit(mult(x,x,mod)+1,mod);
}
inline long long randll() {
    return ((long long)rand()<<32)+rand();
}
inline long long pollard_rho(long long n) {
    long long x,x2;
    if(!(n&1)) return 2;
    //x=x2=randll()%n;
    x=x2=2;
    while(1) {
        x=f(x,n); x2=f(f(x2,n),n);
        long long d=gcd(abs(x-x2),n);
        if(d!=1&&d!=n) return d;
    }
}
}

```

3.11 Result

```

/*
Lucas' Theorem:
For non-negative integer n,m and prime P,
C(m,n) mod P = C(m/M,n/M) * C(m%M,n%M) mod P
= mult_i ( C(m_i,n_i) )
where m_i is the i-th digit of m in base P.
--
Sum of Two Squares Thm (Legendre)
For a given positive integer N, let

```

```

D1 = (# of positive integers d dividing N that d=1(
    mod 4))
D3 = (# of positive integers d dividing N that d=3(
    mod 4))
then N can be written as a sum of two squares in
    exactly
R(N) = 4(D1-D3) ways.
--
Difference of D1-D3 Thm
let N = 2^t * [p1^e1 * ... * pr^er] * [q1^f1 * ... *
    qs^fs]
    <- mod 4 = 1 prime ->    <- mod 4 = 3
    prime ->
then D1 - D3 = (e1+1)(e2+1)...(er+1) ... if (fi)s all
    even
    0 ... if any fi is odd
*/

/*
* primes list
* 1097774749
* 1076767633
* 100102021
* 999997771
* 1001010013
* 1000512343
* 987654361
* 999991231
* 999888733
* 98789101
* 987777733
* 999991921
* 1010101333
* 1010102101
*/

```

Pick's Theorem
 $A = i + b/2 - 1$

4 Geometry

4.1 halfPlaneIntersection

```

#include<bits/stdc++.h>

#define N 100010
#define EPS 1e-8
#define SIDE 10000000

using namespace std;

struct PO {
    double x, y;
} p[ N ], o;

struct LI {
    PO a, b;
    double angle;
    void in( double x1, double y1, double x2, double
        y2 ) {
        a.x = x1; a.y = y1; b.x = x2; b.y = y2;
    }
} li[ N ], deq[ N ];

int n, m, cnt;

inline int dc( double x ) {
    if ( x > EPS ) return 1;
    else if ( x < -EPS ) return -1;
    return 0;
}

inline PO operator - ( PO a, PO b ) {
    PO c;
    c.x = a.x - b.x; c.y = a.y - b.y;
    return c;
}

```

```

inline double cross( PO a, PO b, PO c ) {
    return ( b.x - a.x ) * ( c.y - a.y ) - ( b.y - a.y )
        * ( c.x - a.x );
}

inline bool cmp( const LI &a, const LI &b ) {
    if ( dc( a.angle - b.angle ) == 0 ) return dc( cross(
        a.a, a.b, b.a ) ) < 0;
    return a.angle > b.angle;
}

inline PO getpoint( LI &a, LI &b ) {
    double k1 = cross( a.a, b.b, b.a );
    double k2 = cross( a.b, b.a, b.b );
    PO tmp = a.b - a.a, ans;
    ans.x = a.a.x + tmp.x * k1 / ( k1 + k2 );
    ans.y = a.a.y + tmp.y * k1 / ( k1 + k2 );
    return ans;
}

inline void getcut() {
    sort( li + 1, li + 1 + n, cmp ); m = 1;
    for ( int i = 2; i <= n; i++ )
        if ( dc( li[ i ].angle - li[ m ].angle ) != 0 )
            li[ ++m ] = li[ i ];
    deq[ 1 ] = li[ 1 ]; deq[ 2 ] = li[ 2 ];
    int bot = 1, top = 2;
    for ( int i = 3; i <= m; i++ ) {
        while ( bot < top && dc( cross( li[ i ].a, li[ i
            ].b, getpoint( deq[ top ], deq[ top - 1 ] ) )
            ) < 0 ) top --;
        while ( bot < top && dc( cross( li[ i ].a, li[ i
            ].b, getpoint( deq[ bot ], deq[ bot + 1 ] ) )
            ) < 0 ) bot ++;
        deq[ ++top ] = li[ i ];
    }
    while ( bot < top && dc( cross( deq[ bot ].a, deq[
        bot ].b, getpoint( deq[ top ], deq[ top - 1 ] )
        ) ) < 0 ) top --;
    while ( bot < top && dc( cross( deq[ top ].a, deq[
        top ].b, getpoint( deq[ bot ], deq[ bot + 1 ] )
        ) ) < 0 ) bot ++;
    cnt = 0;
    if ( bot == top ) return;
    for ( int i = bot; i < top; i++ ) p[ ++cnt ] =
        getpoint( deq[ i ], deq[ i + 1 ] );
    if ( top - 1 > bot ) p[ ++cnt ] = getpoint( deq[ bot
        ], deq[ top ] );
}

double px[ N ], py[ N ];
void read( int rm ) {
    for ( int i = 1; i <= n; i++ ) px[ i + n ] = px[ i
        ], py[ i + n ] = py[ i ];
    for ( int i = 1; i <= n; i++ ) {
        // half-plane from li[ i ].a -> li[ i ].b
        li[ i ].a.x = px[ i + rm + 1 ]; li[ i ].a.y = py[ i
            + rm + 1 ];
        li[ i ].b.x = px[ i ]; li[ i ].b.y = py[ i ];
        li[ i ].angle = atan2( li[ i ].b.y - li[ i ].a.y,
            li[ i ].b.x - li[ i ].a.x );
    }
}

inline double getarea( int rm ) {
    read( rm ); getcut();
    double res = 0.0;
    p[ cnt + 1 ] = p[ 1 ];
    for ( int i = 1; i <= cnt; i++ ) res += cross( o,
        p[ i ], p[ i + 1 ] );
    if ( res < 0.0 ) res *= -1.0;
    return res;
}

int main() {
    return 0;
}

#include<bits/stdc++.h>

using namespace std;

#define PB push_back

```

```

#define _x first
#define _y second

const int MXL = 5000;
const double EPS = 1e-8;

typedef pair<double, double> pdd;
typedef pair<pdd, pdd> Line;

pdd operator + (const pdd p1, const pdd p2){
    return pdd(p1._x + p2._x, p1._y + p2._y);
}

pdd operator - (const pdd p1, const pdd p2){
    return pdd(p1._x - p2._x, p1._y - p2._y);
}

pdd operator * (const double c, const pdd p){
    return pdd(p._x * c, p._y * c);
}

double operator % (const pdd p1, const pdd p2){
    return p1._x * p2._y - p2._x * p1._y;
}

vector<Line> lnlst;
double atn[MXL];

bool lncmp(int l1, int l2){
    return atn[l1] < atn[l2];
}

pdd interPnt(pdd p1, pdd p2, pdd q1, pdd q2){
    double f1 = (p2 - p1) % (q1 - p1);
    double f2 = (p2 - p1) % (p1 - q2);
    double f = (f1 + f2);

    if(fabs(f) < EPS) return pdd(nan(""), nan(""));

    return (f2 / f) * q1 + (f1 / f) * q2;
}

deque<Line> dq;

void halfPlaneInter(){
    int n = lnlst.size();
    vector<int> stlst;
    for(int i=0; i<n; i++){
        stlst.PB(i);
        pdd d = lnlst[i].second - lnlst[i].first;
        atn[i] = atan2(d._y, d._x);
    }
    sort(stlst.begin(), stlst.end(), lncmp);
    vector<Line> lst;

    for(int i=0; i<n; i++){
        if(i) {
            int j = i-1;
            Line li = lnlst[stlst[i]];
            Line lj = lnlst[stlst[j]];
            pdd di = li.second - li.first;
            pdd dj = lj.second - lj.first;
            if(fabs(di%dj) < EPS){
                if(di % (lj.second - li.second) < 0) {
                    lst.pop_back();
                } else continue;
            }
        }
        lst.PB(lnlst[stlst[i]]);
    }

    dq.PB(lst[0]);
    dq.PB(lst[1]);
    for(int i=2; i<n; i++){
        int dsz = dq.size();
        Line l = lst[i];
        while(dsz >= 2){
            Line l1 = dq[dsz-1];
            Line l2 = dq[dsz-2];

            pdd it12 = interPnt(l1.first, l1.second, l2.first, l2.second);

            if((l.second - l.first) % (it12 - l.first) < 0){
                dq.pop_back();
                dsz--;
            } else break;
        }
    }
}

int main(){
    int N;
    cin >> N;
    for(int i=0; i<N; i++){
        double x1, x2, y1, y2;
        cin >> x1 >> y1 >> x2 >> y2;
        lnlst.PB({pdd(x1, y1), pdd(x2, y2)});
    }

    halfPlaneInter();

    int dsz = dq.size();
    cout << dsz << endl;
    for(int i=0; i<dsz; i++){
        int j = (i+1) % dsz;
        pdd it = interPnt(dq[i].first, dq[i].second, dq[j].first, dq[j].second);
        cout << it._x << " " << it._y << endl;
    }
}

```

```

        , l2.second);

        if((l.second - l.first) % (it12 - l.first) < 0){
            dq.pop_back();
            dsz--;
        } else break;
    }

    while(dsz >= 2){
        Line l1 = dq[0];
        Line l2 = dq[1];

        pdd it12 = interPnt(l1.first, l1.second, l2.first, l2.second);

        if((l.second - l.first) % (it12 - l.first) < 0){
            dq.pop_front();
            dsz--;
        } else break;
    }

    Line l1 = dq[dsz - 1];
    if(!std::isnan(interPnt(l1.first, l1.second, l1.first, l1.second)._x)){
        dq.PB(l1);
    }

    int dsz = dq.size();
    while(dsz >= 2){
        Line l1 = dq[dsz - 1];
        Line l2 = dq[dsz - 2];
        Line l = dq[0];
        pdd it12 = interPnt(l1.first, l1.second, l2.first, l2.second);
        if(std::isnan(it12._x)) {
            dq.pop_back();
            dq.pop_back();
            dsz -= 2;
        } else if((l.second - l.first) % (it12 - l.first) < 0){
            dq.pop_back();
            dsz--;
        } else break;
    }
}

int main(){
    int N;
    cin >> N;
    for(int i=0; i<N; i++){
        double x1, x2, y1, y2;
        cin >> x1 >> y1 >> x2 >> y2;
        lnlst.PB({pdd(x1, y1), pdd(x2, y2)});
    }

    halfPlaneInter();

    int dsz = dq.size();
    cout << dsz << endl;
    for(int i=0; i<dsz; i++){
        int j = (i+1) % dsz;
        pdd it = interPnt(dq[i].first, dq[i].second, dq[j].first, dq[j].second);
        cout << it._x << " " << it._y << endl;
    }
}

```

4.2 Convex Hull

```

double cross(Point o, Point a, Point b){
    return (a-o) % (b-o);
}

vector<Point> convex_hull(vector<Point> pt){
    sort(pt.begin(), pt.end());
    int top=0;

```

```
vector<Point> stk(2*pt.size());
for (int i=0; i<(int)pt.size(); i++){
    while (top >= 2 && cross(stk[top-2],stk[top-1],pt[i]) <= 0)
        top--;
    stk[top++] = pt[i];
}
for (int i=pt.size()-2, t=top+1; i>=0; i--){
    while (top >= t && cross(stk[top-2],stk[top-1],pt[i]) <= 0)
        top--;
    stk[top++] = pt[i];
}
stk.resize(top-1);
return stk;
}
```

4.3 Intersection of 2 lines

```
#include<bits/stdc++.h>

using namespace std;
const double EPS = 1e-9;

pdd interPnt(pdd p1, pdd p2, pdd q1, pdd q2){
    double f1 = (p2 - p1) ^ (q1 - p1); // cross
    double f2 = (p2 - p1) ^ (p1 - q2); // cross
    double f = (f1 + f2);

    if(fabs(f) < EPS) return pdd(nan(""), nan(""));

    return (f2 / f) * q1 + (f1 / f) * q2;
}
```

4.4 KD Tree

```
const INF = 1100000000;

class NODE{ public:
    int x,y,x1,x2,y1,y2;
    int i,f;
    NODE *L,*R;
};

inline long long dis(NODE& a,NODE& b){
    long long dx=a.x-b.x;
    long long dy=a.y-b.y;
    return dx*dx+dy*dy;
}

NODE node[100000];
bool cmpx(const NODE& a,const NODE& b){ return a.x<b.x; }
bool cmpy(const NODE& a,const NODE& b){ return a.y<b.y; }

NODE* KDTree(int L,int R,int dep){
    if(L>R) return 0;
    int M=(L+R)/2;
    if(dep%2==0){
        nth_element(node+L,node+M,node+R+1,cmpx);
        node[M].f=0;
    }else{
        nth_element(node+L,node+M,node+R+1,cmpy);
        node[M].f=1;
    }
    node[M].x1=node[M].x2=node[M].x;
    node[M].y1=node[M].y2=node[M].y;
    node[M].L=KDTree(L,M-1,dep+1);
    if(node[M].L){
        node[M].x1=min(node[M].x1,node[M].L->x1);
        node[M].x2=max(node[M].x2,node[M].L->x2);
        node[M].y1=min(node[M].y1,node[M].L->y1);
        node[M].y2=max(node[M].y2,node[M].L->y2);
    }
    node[M].R=KDTree(M+1,R,dep+1);
    if(node[M].R){
        node[M].x1=min(node[M].x1,node[M].R->x1);
        node[M].x2=max(node[M].x2,node[M].R->x2);
        node[M].y1=min(node[M].y1,node[M].R->y1);
        node[M].y2=max(node[M].y2,node[M].R->y2);
    }
}
```

```

}
return node+M;
}

inline int touch(NODE* r,int x,int y,long long d){
    long long d2;
    d2 = (long long)(sqrt(d)+1);
    if(x<r->x1-d2 || x>r->x2+d2 || y<r->y1-d2 || y>r->y2+d2)
        return 0;
    return 1;
}

void nearest(NODE* r,int z,long long &md){
    if(!r || !touch(r,node[z].x,node[z].y,md)) return;
    long long d;
    if(node[z].i!=r->i){
        d=dis(*r,node[z]);
        if(d<md) md=d;
    }
    if(r->f==0){
        if(node[z].x<r->x){
            nearest(r->L,z,md);
            nearest(r->R,z,md);
        }else{
            nearest(r->R,z,md);
            nearest(r->L,z,md);
        }
    }else{
        if(node[z].y<r->y){
            nearest(r->L,z,md);
            nearest(r->R,z,md);
        }else{
            nearest(r->R,z,md);
            nearest(r->L,z,md);
        }
    }
}

int main(){
    int TT,n,i;
    long long d;
    NODE* root;
    scanf("%d",&TT);
    while(TT--){
        scanf("%d",&n);
        for(i=0;i<n;i++){
            scanf("%d %d",&node[i].x,&node[i].y);
            node[i].i=i;
        }
        root=KDTree(0,n-1,0);
        for(i=0;i<n;i++){
            d=900000000000000000LL;
            nearest(root,i,d);
            ans[node[i].i]=d;
        }
    }
}
```

4.5 Poly Union

```
#define EPS 1E-8
class PT{ public: double x,y; };
class PY{ public:
    int n;
    PT pt[5];
    PT& operator[](const int x){ return pt[x]; }
    void input(){
        int i; n=4;
        for(i=0;i<n;i++) scanf("%lf %lf",&pt[i].x,&pt[i].y);
    }
    double getArea(){
        int i; double s=pt[n-1]^pt[0];
        for(i=0;i<n-1;i++) s+=pt[i]^pt[i+1];
        return s/2;
    }
};
PY py[500];
pair<double,int> c[5000];
inline double segP(PT &p,PT &p1,PT &p2){
    if(SG(p1.x-p2.x)==0) return (p.y-p1.y)/(p2.y-p1.y);
    return (p.x-p1.x)/(p2.x-p1.x);
}
```



```

}
double polyUnion(int n){
    int i,j,ii,jj,ta,tb,r,d;
    double z,w,s,sum,tc,td;
    for(i=0;i<n;i++) py[i][py[i].n]=py[i][0];
    sum=0;
    for(i=0;i<n;i++){
        for(ii=0;ii<py[i].n;ii++){
            r=0;
            c[r++]=make_pair(0.0,0);
            c[r++]=make_pair(1.0,0);
            for(j=0;j<n;j++){
                if(i==j) continue;
                for(jj=0;jj<py[j].n;jj++){
                    ta=SG(tri(py[i][ii],py[i][ii+1],py[j][jj]));
                    tb=SG(tri(py[i][ii],py[i][ii+1],py[j][jj+1]));
                    if(ta==0 && tb==0){
                        if((py[j][jj+1]-py[j][jj])*(py[i][ii+1]-py[i][ii])>0 && j<i){
                            c[r++]=make_pair(segP(py[j][jj],py[i][ii],py[i][ii+1]),1);
                            c[r++]=make_pair(segP(py[j][jj+1],py[i][ii],py[i][ii+1]),-1);
                        }
                    }
                    else if(ta>=0 && tb<0){
                        tc=tri(py[j][jj],py[j][jj+1],py[i][ii]);
                        td=tri(py[j][jj],py[j][jj+1],py[i][ii+1]);
                        c[r++]=make_pair(tc/(tc+td),1);
                    }
                    else if(ta<0 && tb>=0){
                        tc=tri(py[j][jj],py[j][jj+1],py[i][ii]);
                        td=tri(py[j][jj],py[j][jj+1],py[i][ii+1]);
                        c[r++]=make_pair(tc/(tc+td),-1);
                    }
                }
            }
            sort(c,c+r);
            z=min(max(c[0].first,0.0),1.0);
            d=c[0].second; s=0;
            for(j=1;j<r;j++){
                w=min(max(c[j].first,0.0),1.0);
                if(!d) s+=w-z;
                d+=c[j].second; z=w;
            }
            sum+=(py[i][ii]^py[i][ii+1])*s;
        }
    }
    return sum/2;
}

int main(){
    int n,i,j,k;
    double sum,ds;
    scanf("%d",&n); sum=0;
    for(i=0;i<n;i++){
        py[i].input();
        ds=py[i].getArea();
        if(ds<0){
            for(j=0,k=py[i].n-1;j<k;j++,k--) swap(py[i][j],py[i][k]);
            ds=-ds;
        }
        sum+=ds;
    }
    printf("%.9f\n",sum/polyUnion(n));
}

```

4.6 Lower Concave Hull

```

/****
    maintain a "concave hull" that support the following
    1. insertion of a line
    2. query of height(y) on specific x on the hull
****/
/* set as needed */
const long double eps=1e-9;
const long double inf=1e19;

```

```

class Segment {
public:
    long double m,c,x1,x2; // y=mx+c
    bool flag;
    Segment(long double _m,long double _c,long double _x1
            =-inf,long double _x2=inf,bool _flag=0)
        :m(_m),c(_c),x1(_x1),x2(_x2),flag(_flag) {}
    long double evaly(long double x) const {
        return m*x+c;
    }
    const bool operator<(long double x) const {
        return x2-eps<x;
    }
    const bool operator<(const Segment &b) const {
        if(flag||b.flag) return *this<b.x1;
        return m+eps<b.m;
    }
};

class LowerConcaveHull { // maintain a hull like: \__/_/
public:
    set<Segment> hull;
    /* functions */
    long double xintersection(Segment a,Segment b) {
        return (a.c-b.c)/(b.m-a.m);
    }
    inline set<Segment>::iterator replace(set<Segment> &
        hull,set<Segment>::iterator it,Segment s) {
        hull.erase(it);
        return hull.insert(s).first;
    }
    void insert(Segment s) { // insert a line and update hull
        set<Segment>::iterator it=hull.find(s);
        // check for same slope
        if(it!=hull.end()) {
            if(it->c+eps>=s.c) return;
            hull.erase(it);
        }
        // check if below whole hull
        it=hull.lower_bound(s);
        if(it!=hull.end()&&s.evaly(it->x1)<=it->evaly(it->x1)+eps) return;
        // update right hull
        while(it!=hull.end()) {
            long double x=xintersection(s,*it);
            if(x>=it->x2-eps) hull.erase(it++);
            else {
                s.x2=x;
                it=replace(hull,it,Segment(it->m,it->c,x,it->x2));
                break;
            }
        }
        // update left hull
        while(it!=hull.begin()) {
            long double x=xintersection(s,*(--it));
            if(x<=it->x1+eps) hull.erase(it++);
            else {
                s.x1=x;
                it=replace(hull,it,Segment(it->m,it->c,it->x1,x));
                break;
            }
        }
        // insert s
        hull.insert(s);
    }
    void insert(long double m,long double c) { insert(
        Segment(m,c)); }
    long double query(long double x) { // return y @
        given
        x
        set<Segment>::iterator it=hull.lower_bound(
            Segment
            (0.0,0.0,x,x,1));
        return it->evaly(x);
    }
};

```

4.7 MCC

```

struct Mcc{
    // return pair of center and r^2
    static const int MAXN = 1000100;
    int n;
    Point p[MAXN],cen;
    double r2;

    void init(int _n, Point _p[]){
        n = _n;
        memcpy(p,_p,sizeof(Point)*n);
    }
    double sqr(double a){ return a*a; }
    Point center(Point p0, Point p1, Point p2) {
        Point a = p1-p0;
        Point b = p2-p0;
        double c1=a.len2()*0.5;
        double c2=b.len2()*0.5;
        double d = a % b;
        double x = p0.x + (c1 * b.y - c2 * a.y) / d;
        double y = p0.y + (a.x * c2 - b.x * c1) / d;
        return Point(x,y);
    }

    pair<Point,double> solve(){
        random_shuffle(p,p+n);
        r2=0;
        for (int i=0; i<n; i++){
            if ((cen-p[i]).len2() <= r2) continue;
            cen = p[i];
            r2 = 0;
            for (int j=0; j<i; j++){
                if ((cen-p[j]).len2() <= r2) continue;
                cen = Point((p[i].x+p[j].x)*0.5, (p[i].y+p[j].y)
                    )*0.5);
                r2 = (cen-p[j]).len2();
            }
            for (int k=0; k<j; k++){
                if ((cen-p[k]).len2() <= r2) continue;
                cen = center(p[i],p[j],p[k]);
                r2 = (cen-p[k]).len2();
            }
        }
        return {cen,r2};
    }
}mcc;

```

4.8 Minkowski sum

```

/* convex hull Minkowski Sum */
#define INF 1000000000000000LL
class PT{ public:
    long long x,y;
    int POS(){
        if(y==0) return x>0?0:1;
        return y>0?0:1;
    }
};
PT pt[300000],qt[300000],rt[300000];
long long Lx,Rx;
int dn,un;
inline bool cmp(PT a,PT b){
    int pa=a.POS(),pb=b.POS();
    if(pa==pb) return (a^b)>0;
    return pa<pb;
}
int minkowskiSum(int n,int m){
    int i,j,r,p,q,fi,fj;
    for(i=1,p=0;i<n;i++){
        if(pt[i].y<pt[p].y || (pt[i].y==pt[p].y && pt[i].x<
            pt[p].x)) p=i; }
    for(i=1,q=0;i<m;i++){
        if(qt[i].y<qt[q].y || (qt[i].y==qt[q].y && qt[i].x<
            qt[q].x)) q=i; }
    rt[0]=pt[p]+qt[q];
    r=1; i=p; j=q; fi=fj=0;
    while(1){
        if((fj&&j==q) || (!fj||i!=p) && cmp(pt[(p+1)%n]-pt
            [

```

```

                p],qt[(q+1)%m]-qt[q])){
                    rt[r]=rt[r-1]+pt[(p+1)%n]-pt[p];
                    p=(p+1)%n;
                    fi=1;
                }else{
                    rt[r]=rt[r-1]+qt[(q+1)%m]-qt[q];
                    q=(q+1)%m;
                    fj=1;
                }
            }
            if(r<=1 || ((rt[r]-rt[r-1])^(rt[r-1]-rt[r-2]))!=0)
                r++;
            else rt[r-1]=rt[r];
            if(i==p && j==q) break;
        }
        return r-1;
    }
    void initInConvex(int n){
        int i,p,q;
        long long Ly,Ry;
        Lx=INF; Rx=-INF;
        for(i=0;i<n;i++){
            if(pt[i].x<Lx) Lx=pt[i].x;
            if(pt[i].x>Rx) Rx=pt[i].x;
        }
        Ly=Ry=INF;
        for(i=0;i<n;i++){
            if(pt[i].x==Lx && pt[i].y<Ly){ Ly=pt[i].y; p=i; }
            if(pt[i].x==Rx && pt[i].y>Ry){ Ry=pt[i].y; q=i; }
        }
        for(dn=0,i=p;i!=q;i=(i+1)%n){ qt[dn++]=pt[i]; }
        qt[dn]=pt[q]; Ly=Ry=-INF;
        for(i=0;i<n;i++){
            if(pt[i].x==Lx && pt[i].y>Ly){ Ly=pt[i].y; p=i; }
            if(pt[i].x==Rx && pt[i].y<Ry){ Ry=pt[i].y; q=i; }
        }
        for(un=0,i=p;i!=q;i=(i+n-1)%n){ rt[un++]=pt[i]; }
        rt[un]=pt[q];
    }
    inline int inConvex(PT p){
        int L,R,M;
        if(p.x<Lx || p.x>Rx) return 0;
        L=0;R=dn;
        while(L<R-1){ M=(L+R)/2;
            if(p.x<qt[M].x) R=M; else L=M; }
        if(tri(qt[L],qt[R],p)<0) return 0;
        L=0;R=un;
        while(L<R-1){ M=(L+R)/2;
            if(p.x<rt[M].x) R=M; else L=M; }
        if(tri(rt[L],rt[R],p)>0) return 0;
        return 1;
    }
}
int main(){
    int n,m,i;
    PT p;
    scanf("%d",&n);
    for(i=0;i<n;i++) scanf("%I64d %I64d",&pt[i].x,&pt[i].
        y);
    scanf("%d",&m);
    for(i=0;i<m;i++) scanf("%I64d %I64d",&qt[i].x,&qt[i].
        y);
    n=minkowskiSum(n,m);
    for(i=0;i<n;i++) pt[i]=rt[i];
    scanf("%d",&m);
    for(i=0;i<m;i++) scanf("%I64d %I64d",&qt[i].x,&qt[i].
        y);
    n=minkowskiSum(n,m);
    for(i=0;i<n;i++) pt[i]=rt[i];
    initInConvex(n);
    scanf("%d",&m);
    for(i=0;i<m;i++){
        scanf("%I64d %I64d",&p.x,&p.y);
        p.x*=3; p.y*=3;
        puts(inConvex(p)?"YES":"NO");
    }
}

```

4.9 Min Enclosing Circle

```

/* minimum enclosing circle */

```

```

int n;
Coor p[MAXNUM];
const Circle circumcircle(Coor a,Coor b,Coor c){
    Circle cir;
    double fa,fb,fc,fd,fe,ff,dx,dy,dd;
    if(iszero(cross(a,b,c))) {
        if(dot(a,b,c)<=0) return Circle((b+c)/2,(b-c).len()/2);
        if(dot(b,c,a)<=0) return Circle((c+a)/2,(c-a).len()/2);
        if(dot(c,a,b)<=0) return Circle((a+b)/2,(a-b).len()/2);
    } else {
        fa=2*(a.x-b.x);
        fb=2*(a.y-b.y);
        fc=a.len2()-b.len2();
        fd=2*(a.x-c.x);
        fe=2*(a.y-c.y);
        ff=a.len2()-c.len2();
        dx=fc*fe-ff*fb;
        dy=fa*ff-fd*fc;
        dd=fa*fe-fd*fb;
        cir.o=Coor(dx/dd,dy/dd);
        cir.r=(a-cir.o).len();
        return cir;
    }
}
inline Circle mec(int fixed,int num){
    int i;
    Circle cir;
    if(fixed==3) return circumcircle(p[0],p[1],p[2]);
    cir=circumcircle(p[0],p[0],p[1]);
    for(i=fixed;i<num;i++) {
        if(cir.inside(p[i])) continue;
        swap(p[i],p[fixed]);
        cir=mec(fixed+1,i+1);
    }
    return cir;
}
inline double min_radius() {
    if(n<=1) return 0.0;
    if(n==2) return (p[0]-p[1]).len()/2;
    scramble();
    return mec(0,n).r;
}

```

4.10 Min/Max Enclosing Rectangle

```

/***** NEED REVISION *****/
/* uva819 - gifts large and small */
#define MAXNUM 100005
const double eps=1e-8;
const double inf=1e15;
class Coor {
public:
    double x,y;
    Coor() {}
    Coor(double xi,double yi) { x=xi; y=yi; }
    Coor& operator+=(const Coor &b) { x+=b.x; y+=b.y; return *this; }
    const Coor operator+(const Coor &b) const { return (Coor)*this+b; }
    Coor& operator-=(const Coor &b) { x-=b.x; y-=b.y; return *this; }
    const Coor operator-(const Coor &b) const { return (Coor)*this-b; }
    Coor& operator*=(const double b) { x*=b; y*=b; return *this; }
    const Coor operator*(const double b) const { return (Coor)*this*b; }
    Coor& operator/=(const double b) { x/=b; y/=b; return *this; }
    const Coor operator/(const double b) const { return (Coor)*this/b; }
    const bool operator<(const Coor& b) const { return y<b.y-eps||fabs(y-b.y)<eps&&x<b.x; }
}

```

```

const double len2() const { return x*x+y*y; }
const double len() const { return sqrt(len2()); }
const Coor perp() const { return Coor(y,-x); }
Coor& standardize() {
    if(y<0||y==0&&x<0) {
        x=-x;
        y=-y;
    }
    return *this;
}
const Coor standardize() const {
    return ((Coor)*this).standardize();
}
};
double dot(const Coor &a,const Coor &b) { return a.x*b.x+a.y*b.y; }
double dot(const Coor &o,const Coor &a,const Coor &b) {
    return dot(a-o,b-o); }
double cross(const Coor &a,const Coor &b) { return a.x*b.y-a.y*b.x; }
double cross(const Coor &o,const Coor &a,const Coor &b) {
    return cross(a-o,b-o); }
Coor cmpo;
const bool cmpf(const Coor &a,const Coor &b) {
    return cross(cmpo,a,b)>eps||fabs(cross(cmpo,a,b))<eps&&dot(a,cmpo,b)<-eps;
}
class Polygon {
public:
    int pn;
    Coor p[MAXNUM];
    void convex_hull() {
        int i,tn=pn;
        for(i=1;i<pn;++i) if(p[i]<p[0]) swap(p[0],p[i]);
        cmpo=p[0];
        std::sort(p+1,p+pn,cmpf);
        for(i=pn=1;i<tn;++i) {
            while(pn>2&&cross(p[pn-2],p[pn-1],p[i])<=eps) --pn;
            p[pn++]=p[i];
        }
        p[pn]=p[0];
    }
};
Polygon pol;
double minarea,maxarea;
int slpn;
Coor slope[MAXNUM*2];
Coor lrec[MAXNUM*2],rrec[MAXNUM*2],trec[MAXNUM*2],brec[MAXNUM*2];
inline double xproject(Coor p,Coor slp) { return dot(p,slp)/slp.len(); }
inline double yproject(Coor p,Coor slp) { return cross(p,slp)/slp.len(); }
inline double calcaea(Coor lp,Coor rp,Coor bp,Coor tp,Coor slp) {
    return (xproject(rp,slp)-xproject(lp,slp))*(yproject(tp,slp)-yproject(bp,slp)); }
inline void solve(){
    int i,lind,rind,tind,bind,tn;
    double pro,area1,area2,l,r,m1,m2;
    Coor s1,s2;
    pol.convex_hull();
    slpn=0; /* generate all critical slope */
    slope[slpn++]=Coor(1.0,0.0);
    slope[slpn++]=Coor(0.0,1.0);
    for(i=0;i<pol.pn;i++) {
        slope[slpn]=(pol.p[i+1]-pol.p[i]).standardize();
        if(slope[slpn].x>0) slpn++;
        slope[slpn]=(pol.p[i+1]-pol.p[i]).perp().standardize();
        if(slope[slpn].x>0) slpn++;
    }
}

```

```

}
cmpo=Coor(0,0);
std::sort(slope,slope+slpn,cmpf);
tn=slpn;
for(i=slpn-1;i<tn;i++)
    if(cross(cmpo,slope[i-1],slope[i])>0) slope[
        slpn
        ++]=slope[i];
lind=rind=0; /* find critical touchpoints */
for(i=0;i<pol.pn;i++) {
    pro=xproject(pol.p[i],slope[0]);
    if(pro<xproject(pol.p[lind],slope[0])) lind=i;
    if(pro>xproject(pol.p[rind],slope[0])) rind=i;
}
tind=bind=0;
for(i=0;i<pol.pn;i++) {
    pro=yproject(pol.p[i],slope[0]);
    if(pro<yproject(pol.p[bind],slope[0])) bind=i;
    if(pro>yproject(pol.p[tind],slope[0])) tind=i;
}
for(i=0;i<slpn;i++) {
    while(xproject(pol.p[lind+1],slope[i])<=
        xproject(
            pol.p[lind],slope[i])+eps)
        lind=(lind==pol.pn-1?0:lind+1);
    while(xproject(pol.p[rind+1],slope[i])>=
        xproject(
            pol.p[rind],slope[i])-eps)
        rind=(rind==pol.pn-1?0:rind+1);
    while(yproject(pol.p[bind+1],slope[i])<=
        yproject(
            pol.p[bind],slope[i])+eps)
        bind=(bind==pol.pn-1?0:bind+1);
    while(yproject(pol.p[tind+1],slope[i])>=
        yproject(
            pol.p[tind],slope[i])-eps)
        tind=(tind==pol.pn-1?0:tind+1);
    lrec[i]=pol.p[lind];
    rrec[i]=pol.p[rind];
    brec[i]=pol.p[bind];
    trec[i]=pol.p[tind];
}
minarea=inf; /* find minimum area */
for(i=0;i<slpn;i++) {
    area1=calcareal(lrec[i],rrec[i],brec[i],trec[i],
        slope[i]);
    if(area1<minarea) minarea=area1;
}
maxarea=minarea; /* find maximum area */
for(i=0;i<slpn-1;i++) {
    l=0.0; r=1.0;
    while(l<r-eps) {
        m1=l+(r-l)/3;
        m2=l+(r-l)*2/3;
        s1=slope[i]*(1.0-m1)+slope[i+1]*m1;
        area1=calcareal(lrec[i],rrec[i],brec[i],trec[i],
            s1);
        s2=slope[i]*(1.0-m2)+slope[i+1]*m2;
        area2=calcareal(lrec[i],rrec[i],brec[i],trec[i],
            s2);
        if(area1<area2) l=m1;
        else r=m2;
    }
    s1=slope[i]*(1.0-l)+slope[i+1]*l;
    area1=calcareal(lrec[i],rrec[i],brec[i],trec[i],
        s1);
    if(area1>maxarea) maxarea=area1;
}
}
int main(void){
    int i,casenum=1;
    while(scanf("%d",&pol.pn)==1&&pol.pn) {
        for(i=0;i<pol.pn;i++)
            scanf("%lf %lf",&pol.p[i].x,&pol.p[i].y);
        solve();
        //minarea, maxarea
    }
}

```

5 Graph

5.1 HeavyLightDecomp

```

#include <bits/stdc++.h>
using namespace std;
#define SZ(c) (int)(c).size()
#define ALL(c) (c).begin(), (c).end()
#define REP(i, s, e) for(int i = (s); i <= (e); i++)
#define REPD(i, s, e) for(int i = (s); i >= (e); i--)

typedef tuple< int , int > tii;

const int MAXN = 100010;
const int LOG = 19;

struct HLD
{
    int n;
    vector<int> g[MAXN];
    int sz[MAXN], dep[MAXN];
    int ts, tid[MAXN], tdi[MAXN], tl[MAXN], tr[MAXN];
    // ts : timestamp , useless after yutruLi
    // tid[ u ] : pos. of node u in the seq.
    // tdi[ i ] : node at pos i of the seq.
    // tl , tr[ u ] : subtree interval in the seq. of
    // node u
    int mom[MAXN][LOG], head[MAXN];
    // head[ u ] : head of the chain contains u
    void dfsz(int u, int p)
    {
        dep[u] = dep[p] + 1;
        mom[u][0] = p;
        sz[u] = 1;
        head[u] = u;
        for(int& v:g[u]) if(v != p)
        {
            dep[v] = dep[u] + 1;
            dfsz(v, u);
            sz[u] += sz[v];
        }
    }
    void dfsHl(int u)
    {
        //printf("dfsHl %d\n", u);
        ts++;
        tid[u] = tl[u] = tr[u] = ts;
        tdi[tid[u]] = u;
        sort(ALL(g[u]), [&](int a, int b){return sz[a] > sz[b]});
        bool flag = 1;
        for(int& v:g[u]) if(v != mom[u][0])
        {
            if(flag) head[v] = head[u], flag = 0;
            dfsHl(v);
            tr[u] = tr[v];
        }
    }
    inline int lca(int a, int b)
    {
        if(dep[a] > dep[b]) swap(a, b);
        //printf("lca %d %d\n", a, b);
        int diff = dep[b] - dep[a];
        REPD(k, LOG-1, 0) if(diff & (1<<k))
        {
            //printf("b %d\n", mom[b][k]);
            b = mom[b][k];
        }
        if(a == b) return a;
        REPD(k, LOG-1, 0) if(mom[a][k] != mom[b][k])
        {
            a = mom[a][k];
            b = mom[b][k];
        }
        return mom[a][0];
    }
    void init( int _n )
    {
        n = _n;
        REP( i , 1 , n ) g[ i ].clear();
    }
}

```

```

}
void addEdge( int u , int v )
{
    g[ u ].push_back( v );
    g[ v ].push_back( u );
}
void yutruli()
{
    dfssz(1, 0);
    ts = 0;
    dfshl(1);
    REP(k, 1, LOG-1) REP(i, 1, n)
        mom[i][k] = mom[mom[i][k-1]][k-1];
}
vector< tii > getPath( int u , int v )
{
    vector< tii > res;
    while( tid[ u ] < tid[ head[ v ] ] )
    {
        res.push_back( tii( tid[ head[ v ] ] , tid[ v ] ) );
        v = mom[ head[ v ] ][ 0 ];
    }
    res.push_back( tii( tid[ u ] , tid[ v ] ) );
    reverse( ALL( res ) );
    return res;
}
/*
 * res : list of intervals from u to v
 * u must be ancestor of v
 * usage :
 * vector< tii > path = tree.getPath( u , v )
 * for( tii tp : path ) {
 *     int l , r; tie( l , r ) = tp;
 *     upd( l , r );
 *     uu = tree.tdi[ l ] , vv = tree.tdi[ r ];
 *     uu ~> vv is a heavy path on tree
 * }
 */
}
} tree;

```

```

for (vector<int>::iterator it = edge[u].begin();
     it != edge[u].end(); ++it) {
    int v = *it;
    if (label[u] != -1 && label[v] != -1) {
        succ[label[u]].push_back(label[v]);
        pred[label[v]].push_back(label[u]);
    }
}
}
for (int i = 1; i <= n; ++i) {
    semi[i] = best[i] = i;
    idom[i] = ancestor[i] = 0;
    bucket[i].clear();
}
for (int w = cnt; w >= 2; --w) {
    int p = label[parent[rea[w]]];
    for (vector<int>::iterator it = pred[w].begin();
         it != pred[w].end(); ++it) {
        int v = *it;
        int u = eval(v);
        if (semi[w] > semi[u]) semi[w] = semi[u];
    }
    bucket[semi[w]].push_back(w);
    link(p, w);
    while (!bucket[p].empty()) {
        int v = bucket[p].front();
        bucket[p].pop_front();
        int u = eval(v);
        idom[v] = (semi[u] < p ? u : p);
    }
}
for (int w = 2; w <= cnt; ++w) {
    if (idom[w] != semi[w]) idom[w] = idom[idom[w]];
}
idom[1] = 0;
for (int i = 1; i <= cnt; ++i) {
    int u = rea[idom[i]], v = rea[i];
    // ( u -> v )
}
}
} dom;

```

5.2 DominatorTree

```

// clear succ & pred, let cnt = 0 first
// need to set: n, edge
struct Dominator{
    int n, parent[maxn], label[maxn], cnt, rea[maxn];
    vector<int> edge[maxn], succ[maxn], pred[maxn];
    int semi[maxn], idom[maxn], ancestor[maxn], best[maxn];
    deque<int> bucket[maxn];
    void dfs(int u) {
        label[u] = ++cnt; rea[cnt] = u;
        for (vector<int>::iterator it = edge[u].begin(); it
             != edge[u].end(); ++it) {
            int v = *it;
            if (v == parent[u] || label[v] != -1) continue;
            parent[v] = u;
            dfs(v);
        }
    }
    void link(int v, int w) { ancestor[w] = v; }
    void compress(int v) {
        int a = ancestor[v];
        if (ancestor[a] == 0) return;
        compress(a);
        if (semi[best[v]] > semi[best[a]]) best[v] = best[a];
        ancestor[v] = ancestor[a];
    }
    int eval(int v) {
        if (ancestor[v] == 0) return v;
        compress(v);
        return best[v];
    }
    void dominator() {
        for (int i = 1; i <= n; ++i) label[i] = -1;
        dfs( 1 /* root */ );
        for (int u = 1; u <= n; ++u) {

```

5.3 generalWeightedGraphMaxmatching

```

#include <bits/stdc++.h>
using namespace std;
#define N 110
#define inf 0x3f3f3f3f
int G[ N ][ N ], ID[ N ];
int match[ N ], stk[ N ];
int vis[ N ], dis[ N ];
int n, m, k, top;
bool SPFA( int u ){
    stk[ top++ ] = u;
    if( vis[ u ] ) return true;
    vis[ u ] = true;
    for( int i = 1 ; i <= k ; i ++ ){
        if( i != u && i != match[ u ] && !vis[ i ] ){
            int v = match[ i ];
            if( dis[ v ] < dis[ u ] + G[ u ][ i ] - G[ i ][ v ] ){
                dis[ v ] = dis[ u ] + G[ u ][ i ] - G[ i ][ v ];
                if( SPFA( v ) ) return true;
            }
        }
    }
    top --; vis[ u ] = false;
    return false;
}
int MaxWeightMatch() {
    for( int i = 1 ; i <= k ; i ++ ) ID[ i ] = i;
    for( int i = 1 ; i <= k ; i += 2 ) match[ i ] = i + 1,
        match[ i + 1 ] = i;
    for( int times = 0 , flag ; times < 3 ; ){
        memset( dis , 0 , sizeof( dis ) );
        memset( vis , 0 , sizeof( vis ) );
        top = 0; flag = 0;
        for( int i = 1 ; i <= k ; i ++ ){
            if( SPFA( ID[ i ] ) ){

```

```

    flag = 1;
    int t = match[ stk[ top - 1 ] ], j = top - 2;
    while( stk[ j ] != stk[ top - 1 ] ){
        match[ t ] = stk[ j ];
        swap( t , match[ stk[ j ] ] );
        j --;
    }
    match[ t ] = stk[ j ]; match[ stk[ j ] ] = t;
    break;
}
}
if( !flag ) times ++;
if( !flag ) random_shuffle( ID + 1 , ID + k + 1 );
}
int ret = 0;
for( int i = 1 ; i <= k ; i ++ )
    if( i < match[ i ] ) ret += G[ i ][ match[ i ] ];
return ret;
}
int main(){
    int T; scanf("%d", &T);
    for ( int cs = 1 ; cs <= T ; cs ++ ){
        scanf( "%d%d%d", &n , &m , &k );
        memset( G , 0x3f , sizeof( G ) );
        for( int i = 1 ; i <= n ; i ++ ) G[ i ][ i ] = 0;
        for( int i = 0 ; i < m ; i ++ ){
            int u, v, w;
            scanf( "%d%d%d", &u , &v , &w );
            G[ u ][ v ] = G[ v ][ u ] = w;
        }
        printf( "Case %d: " , cs );
        if( k & 1 ){
            puts( "Impossible" );
            continue;
        }
        for( int tk = 1; tk <= n ; tk ++ )
            for( int i = 1 ; i <= n ; i ++ )
                for( int j = 1 ; j <= n ; j ++ )
                    G[ i ][ j ] = min( G[ i ][ j ] , G[ i ][ tk ]
                        + G[ tk ][ j ] );
        for( int i = 1 ; i <= k ; i ++ ){
            for( int j = 1 ; j <= k ; j ++ )
                G[ i ][ j ] = -G[ i ][ j ];
            G[ i ][ i ] = -inf;
        }
        printf( "%d\n" , -MaxWeightMatch() );
    }
}

```

5.4 MaxClique

```

#include <bits/stdc++.h>
using namespace std;
#define N 64
#define ll unsigned long long
ll nb[ N ];
ll getint(){
    ll x=0LLU; char c=getchar();
    while( c<'0' || c>'9' ) c=getchar();
    while(c>='0'&&c<='9') x*=10LLU,x+=(c-'0'),c=getchar();
    return x;
}
ll n , ans , tmp;
void init(){
    n = getint(); ans = 1LLU;
    for( ll i = 0LLU ; i < n ; i ++ ){
        nb[ i ] = 0LLU;
        for( ll j = 0LLU ; j < n ; j ++ ){
            tmp = getint();
            if( tmp ) nb[ i ] |= ( 1LLU << j );
        }
    }
}
void B( ll r , ll p , ll x , ll cnt , ll res ){
    if( cnt + res < ans ) return;
    if( p == 0LLU && x == 0LLU ){
        if( cnt > ans ) ans = cnt;
        return;
    }

```

```

    ll y = p | x; y &= -y;
    ll q = p & ( ~nb[ int( log2( y ) ) ] );
    while( q ){
        ll i = int( log2( q & (-q) ) );
        B( r | ( 1LLU << i ) , p & nb[ i ] , x & nb[ i ]
            , cnt + 1LLU , __builtin_popcountll( p & nb[ i ]
                ) );
        q &= ~( 1LLU << i );
        p &= ~( 1LLU << i );
        x |= ( 1LLU << i );
    }
}
void process(){
    if( n < 64LLU ) B( 0LLU , ( 1LLU << n ) - 1LLU , 0
        , 0LLU , n );
    else{
        ll b = 0LLU;
        for( ll i = 0LLU ; i < 64LLU ; i ++ )
            b |= ( 1LLU << i );
        B( 0LLU , b , 0LLU , 0LLU , n );
    }
    printf( "%llu\n" , ans );
}
int main(){
    ll t; t = getint(); while( t -- ){
        init(); process();
    }
}

```

6 String

6.1 PalTree

```

const int MAXN = 200010;
struct PalT{
    struct Node{
        int nxt[ 33 ] , len , fail;
        ll cnt;
    };
    int tot , lst;
    Node nd[ MAXN * 2 ];
    char* s;
    int newNode( int l , int _fail ){
        int res = ++tot;
        memset( nd[ res ].nxt , 0 , sizeof nd[ res ].
            nxt );
        nd[ res ].len = l;
        nd[ res ].cnt = 0;
        nd[ res ].fail = _fail;
        return res;
    }
    void push( int p ){
        int np = lst;
        int c = s[ p ] - 'a';
        while( p - nd[ np ].len - 1 < 0
            || s[ p ] != s[ p - nd[ np ].len - 1 ]
        )
            np = nd[ np ].fail;
        if( nd[ np ].nxt[ c ] ){
            nd[ nd[ np ].nxt[ c ] ].cnt++;
            lst = nd[ np ].nxt[ c ];
            return;
        }
        int nq = newNode( nd[ np ].len + 2 , 0 );
        nd[ nq ].cnt++;
        nd[ np ].nxt[ c ] = nq;
        lst = nq;
        if( nd[ nq ].len == 1 ){
            nd[ nq ].fail = 2;
            return;
        }
        int tf = nd[ np ].fail;

```



```

while( p - nd[ tf ].len - 1 < 0
    || s[ p ] != s[ p - nd[ tf ].len - 1 ]
)
    tf = nd[ tf ].fail;

nd[ nq ].fail = nd[ tf ].nxt[ c ];
return ;
}
void init( char* _s ){
    s = _s;
    tot = 0;
    newNode( -1 , 1 );
    newNode( 0 , 1 );
    lst = 2;
    for( int i = 0 ; s[ i ] ; i++ )
        push( i );
}
void yutruLi(){
#define REPD(i, s, e) for(int i = (s); i >= (e); i--)
    REPD( i , tot , 1 )
        nd[ nd[ i ].fail ].cnt += nd[ i ].cnt;
    nd[ 1 ].cnt = nd[ 2 ].cnt = 0ll;
}
} pA;

int main(){
    pA.init( sa );
}

```

6.2 SuffixArray

```

const int MAX = 1020304;
int ct[MAX], he[MAX], rk[MAX], sa[MAX], tsa[MAX], tp[
MAX][2];

void suffix_array(char *ip){
    int len = strlen(ip);
    int alp = 256;

    memset(ct, 0, sizeof(ct));
    for(int i=0;i<len;i++) ct[ip[i]+1]++;
    for(int i=1;i<alp;i++) ct[i]+=ct[i-1];
    for(int i=0;i<len;i++) rk[i]=ct[ip[i]];

    for(int i=1;i<len;i*=2){
        for(int j=0;j<len;j++){
            if(j+i>len) tp[j][1]=0;
            else tp[j][1]=rk[j+i]+1;

            tp[j][0]=rk[j];
        }
        memset(ct, 0, sizeof(ct));
        for(int j=0;j<len;j++) ct[tp[j][1]+1]++;
        for(int j=1;j<len+1;j++) ct[j]+=ct[j-1];
        for(int j=0;j<len;j++) tsa[ct[tp[j][1]]]=j;

        memset(ct, 0, sizeof(ct));
        for(int j=0;j<len;j++) ct[tp[j][0]+1]++;
        for(int j=1;j<len+1;j++) ct[j]+=ct[j-1];
        for(int j=0;j<len;j++) sa[ct[tp[j][0]]]=j;

        rk[sa[0]]=0;
        for(int j=1;j<len;j++){
            if( tp[sa[j]][0] == tp[sa[j-1]][0] &&
                tp[sa[j]][1] == tp[sa[j-1]][1] )
                rk[sa[j]] = rk[sa[j-1]];
            else
                rk[sa[j]] = j;
        }
    }

    for(int i=0,h=0;i<len;i++){
        if(rk[i]==0) h=0;
        else{
            int j=sa[rk[i]-1];
            h=max(0,h-1);
            for(;ip[i+h]==ip[j+h];h++);
        }
    }
}

```

```

    he[rk[i]]=h;
}
}

```

6.3 SAIS

```

// Suffix array by Induced-Sorting, O(n)
const int MAXL=200000+1000; // Max Length
// input: S[0..n-1], n; output: SA[0..n-1]
// S[n-1] MUST be an unique smallest item!!!!
// Max alphabet should be < MAXL.
int S[MAXL*2], SA[MAXL*2];
bool _iss[MAXL*2];
int _p[MAXL*2], _pb[MAXL*2], cnt[MAXL], qe[MAXL];
inline void isort(int n, int *s, int *sa, bool *iss, int *p
, int
pc){
    int a=0, i;
    for(i=0; i<n; i++) a=max(a, s[i]); a++;
    memset(cnt, 0, sizeof(int)*a);
    for(i=0; i<n; i++) cnt[s[i]]++;
    qe[0]=cnt[0]; for(i=1; i<a; i++) qe[i]=qe[i-1]+cnt[i];
    memset(sa, -1, sizeof(int)*n);
    for(i=pc-1; i>=0; i--) sa[--qe[s[p[i]]]] = p[i];
    qe[0]=0; for(i=1; i<a; i++) qe[i]=qe[i-1]+cnt[i-1];
    for(i=0; i<n; i++) if(sa[i]>0 && !iss[sa[i]-1]) sa[qe[s[sa
i
]-1]]++ = sa[i]-1;
    qe[0]=cnt[0]; for(i=1; i<a; i++) qe[i]=qe[i-1]+cnt[i];
    for(i=n-1; i>=0; i--) if(sa[i]>0 && !iss[sa[i]-1]) sa[--qe[s
sa
[i]-1]] = sa[i]-1;
}

inline bool eq(int *s, bool *iss, int *pp, int *pb, int pc,
int x
, int p){
    if(pb[p]==pc-1 || pb[x]==pc-1 || pp[pb[p]+1]-p!=pp[pb
x
]+1]-x) return 0;
    for(int j=0; j<pp[pb[p]+1]-p; j++) if(s[j+p]!=s[j+x] ||
iss[
j+p] != iss[j+x]) return 0;
    return 1;
}

void suffixArray(int n, int a1=0){
    int i;
    int *s=S+a1, *sa=SA+a1, *pp=_p+a1, *pb=_pb+a1;
    bool *iss=_iss+a1;
    iss[n-1]=1;
    for(i=n-2; i>=0; i--) iss[i]=s[i]<s[i+1] || (s[i]==s[i
+1] &&
iss[i+1]);
    int pc=0;
    for(i=1; i<n; i++) if(iss[i] && !iss[i-1]){ pp[pc]=i; pb[i
]=
pc; pc++; }
    isort(n, s, sa, iss, pp, pc);
    int p=-1, c=-1;
    for(i=0; i<n; i++){
        int x=sa[i];
        if(x && iss[x] && !iss[x-1]){
            if(p==-1 || !eq(s, iss, pp, pb, pc, x, p)) c++;
            s[n+pb[x]]=c;
            p=x;
        }
    }
    if(c==pc-1) for(i=0; i<pc; i++) sa[n+s[n+i]]=i;
    else suffixArray(pc, a1+n);
    for(i=0; i<pc; i++) pb[i]=pp[sa[n+i]];
    isort(n, s, sa, iss, pb, pc);
}

int rk[MAXL], DA[MAXL];
void depthArray(int n){
    int i, j;
    for(i=0; i<n; i++) rk[SA[i]]=i;
    for(i=j=0; i<n; i++){
        if(!rk[i]){ j=0; }
        else{
            if(j) j--;
            for(; S[i+j]==S[SA[rk[i]-1]+j]; j++);
        }
    }
}

```

```

    }
    DA[rk[i]]=j;
}
}

```

6.4 SuffixAutomata

```

const int MAXM = 1000010;
struct SAM{
    int tot, root, lst, mom[MAXM], mx[MAXM];
    int acc[MAXM], nxt[MAXM][33];
    int newNode(){
        int res = ++tot;
        fill(nxt[res], nxt[res]+33, 0);
        mom[res] = mx[res] = acc[res] = 0;
        return res;
    }
    void init(){
        tot = 0;
        root = newNode();
        mom[root] = 0, mx[root] = 0;
        lst = root;
    }
    void push(int c){
        int p = lst;
        int np = newNode();
        mx[np] = mx[p]+1;
        for(; p && nxt[p][c] == 0; p = mom[p])
            nxt[p][c] = np;
        if(p == 0) mom[np] = root;
        else{
            int q = nxt[p][c];
            if(mx[p]+1 == mx[q]) mom[np] = q;
            else{
                int nq = newNode();
                mx[nq] = mx[p]+1;
                for(int i = 0; i < 33; i++){
                    nxt[nq][i] = nxt[q][i];
                }
                mom[nq] = mom[q];
                mom[q] = nq;
                mom[np] = nq;
                for(; p && nxt[p][c] == q; p = mom[p])
                    nxt[p][c] = nq;
            }
        }
        lst = np;
    }
    void print(){
        REP(i, 1, tot){
            printf("node %d :\n", i);
            printf("mx %d, mom %d\n", mx[i], mom[i]);
            REP(j, 1, 26) if(nxt[i][j]){
                printf("nxt %c %d\n", 'a'+j-1, nxt[i][j]);
                puts("-----");
            }
        }
    }
    void push(char *str){
        for(int i = 0; str[i]; i++)
            push(str[i]-'a'+1);
    }
};

SAM sam;

```

6.5 Aho-Corasick

```

struct ACautomata{
    struct Node{
        int cnt, dp;
        Node *go[26], *fail;
        Node(){
            cnt = 0;
            dp = -1;
            memset(go, 0, sizeof(go));
            fail = 0;
        }
    };
};

```

```

Node *root, pool[1048576];
int nMem;

Node* new_Node(){
    pool[nMem] = Node();
    return &pool[nMem++];
}

void init(){
    nMem = 0;
    root = new_Node();
}

void add(const string &str){
    insert(root, str, 0);
}

void insert(Node *cur, const string &str, int pos){
    if (pos >= (int)str.size()){
        cur->cnt++;
        return;
    }
    int c = str[pos]-'a';
    if (cur->go[c] == 0){
        cur->go[c] = new_Node();
    }
    insert(cur->go[c], str, pos+1);
}

void make_fail(){
    queue<Node*> que;
    que.push(root);
    while (!que.empty()){
        Node* fr=que.front();
        que.pop();
        for (int i=0; i<26; i++){
            if (fr->go[i]){
                Node *ptr = fr->fail;
                while (ptr && !ptr->go[i]) ptr = ptr->fail;
                if (!ptr) fr->go[i]->fail = root;
                else fr->go[i]->fail = ptr->go[i];
                que.push(fr->go[i]);
            }
        }
    }
}

```

6.6 Z Value

```

char s[MAXLEN];
int len, z[MAXLEN];
void Z_value() {
    int i, j, left, right;
    left=right=0; z[0]=len;
    for(i=1; i<len; i++) {
        j=max(min(z[i-left], right-i), 0);
        for(; i+j<len&&s[i+j]==s[j]; j++);
        z[i]=j;
        if(i+z[i]>right) {
            right=i+z[i];
            left=i;
        }
    }
}

```

6.7 ZValue Palindrome

```

const int MAX = 1000;
int len;
char ip[MAX];
char op[MAX*2];
int zv[MAX*2];

int main(){
    cin >> ip;
    len = strlen(ip);

    int l2 = len*2 - 1;
    for(int i=0; i<l2; i++){
        if(i&1) op[i] = '@';
    }
}

```

```

    else op[i] = ip[i/2];
}
int l=0, r=0;
zv[0] = 1;
for(int i=1; i<l2; i++){
    if( i > r ){
        l = r = i;
        while( l>0 && r<l2-1 && op[l-1] == op[r+1] ){
            l --;
            r ++;
        }
        zv[i] = (r-l+1);
    }else{
        int md = (l+r)/2;
        int j = md + md - i;
        zv[i] = zv[j];
        int q = zv[i] / 2;
        int nr = i + q;
        if( nr == r ){
            l = i + i - r;
            while( l>0 && r<l2-1 && op[l-1] == op[r+1] ){
                l --;
                r ++;
            }
            zv[i] = r - l + 1;
        }else if( nr > r ){
            zv[i] = (r - i) * 2 + 1;
        }
    }
}
return 0;
}

```

6.8 Smallest Rotation

```

string mcp(string s){
    int n = s.length();
    s += s;
    int i=0, j=1, k=0;
    while (j<n && k<n){
        if (s[i+k] == s[j+k]) k++;
        else {
            if (s[i+k] < s[j+k]) {
                j += k + 1;
            } else {
                i = j;
                j = max(j+1, j+k);
            }
            k = 0;
        }
    }
    return s.substr(i, n);
}

```

6.9 Baker Bird

```

class Node { public:
    Node *fail;
    map<char, Node*> _next;
    int out;
    Node() { fail=NULL; out=-1; }
    ~Node() {
        for(map<char, Node*>::iterator it=_next.begin(); it!=
            _next.end(); it++){
            delete it->second;
        }
    }
    Node* build(char ch) {
        if(_next.find(ch)==_next.end()) _next[ch]=new Node;
        return _next[ch];
    }
    Node* next(char ch) {
        if(_next.find(ch)==_next.end()) return NULL;
        return _next[ch];
    }
};

```

```

int srn,scn,prn,pcn,mrn,mcn;
char s[MAXLEN][MAXLEN],p[MAXLEN][MAXLEN];
int rm[MAXLEN][MAXLEN]; // rank matrix
int maxrank;
int seq[MAXLEN]; // index of patterns for radix sort
int rank[MAXLEN]; // rank of pattern on row r
int cnt[SIGMA+1],tmp[MAXLEN];
int pre[MAXLEN]; // pre-matrix for kmp
int ql,q;
Node* que[MAXLEN*MAXLEN];
inline void radix_pass(int j,int *from,int *to) {
    int i;
    for(i=0;i<SIGMA;i++) cnt[i]=0;
    for(i=0;i<prn;i++) cnt[p[from[i]][j]+1]++;
    for(i=0;i<SIGMA;i++) cnt[i+1]+=cnt[i];
    for(i=0;i<prn;i++) to[cnt[p[from[i]][j]]]=from[i];
}
inline void radix_sort_patterns() {
    int i,j;
    for(i=0;i<prn;i++) ((pcn&1)?tmp[i]:seq[i])=i;
    for(j=pcn-1;j>=0;j--) {
        if(j&1) radix_pass(j,seq,tmp);
        else radix_pass(j,tmp,seq);
    }
    maxrank=0;
    for(i=0;i<prn;i++) {
        if(i&&strcmp(p[seq[i-1]],p[seq[i]])) ++maxrank;
        rank[seq[i]]=maxrank;
    }
}
inline void construct(Node *v,char *p,int ind) {
    while(*p) { v=v->build(*p); p++; }
    v->out=ind;
}
inline void construct_all(Node *ac) {
    for(int i=0;i<prn;i++) construct(ac,p[i],rank[i]);
}
inline void find_fail(Node *ac) {
    Node *v,*u,*f;
    map<char, Node*>::iterator it;
    char ch;
    ql=qr=0; ac->fail=ac;
    for(it=ac->_next.begin(); it!=ac->_next.end(); it++) {
        u=it->second;
        u->fail=ac;
        que[qr++]=u;
    }
    while(ql<qr) {
        v=que[ql++];
        for(it=v->_next.begin(); it!=v->_next.end(); it++) {
            ch=it->first; u=it->second;
            f=v->fail;
            while(f!=ac&&f->next(ch)==NULL) f=f->fail;
            if(f->next(ch)) u->fail=f->next(ch);
            else u->fail=ac;
            que[qr++]=u;
        }
    }
}
inline void ac_match(Node *ac,char *s,int *arr) {
    int i;
    Node *v=ac;
    for(i=0;i<scn;i++) {
        while(v!=ac&&v->next(s[i])==NULL) v=v->fail;
        if(v->next(s[i])) v=v->next(s[i]);
        if(i>=pcn-1) arr[i-pcn+1]=v->out;
    }
}
inline void find_rank_matrix() {
    Node ac;
    radix_sort_patterns();
    construct_all(&ac);
    find_fail(&ac);
    mrn=srn; mcen=scn-pcn+1;
    for(int i=0;i<srn;i++) ac_match(&ac,s[i],rm[i]);
}
inline void find_pre(int *p,int plen) {
    int i,x;
    x=pre[0]=-1;
    for(i=1;i<plen;i++) {
        while(x>=0&&p[x+1]!=p[i]) x=pre[x];
        if(p[x+1]==p[i]) x++;
    }
}

```

```

    pre[i]=x;
}
}
inline int kmp_match(int col,int *p,int plen) {
    int i,x=-1,occ=0;
    for(i=0;i<mrn;i++) {
        while(x>=0&&p[x+1]!=rm[i][col]) x=pre[x];
        if(p[x+1]==rm[i][col]) x++;
        if(x==plen-1) { occ++; x=pre[x]; }
    }
    return occ;
}
inline int baker_bird() {
    int i,occ=0;
    find_rank_matrix();
    find_pre(rank,prn);
    for(i=0;i<mcn;i++) occ+=kmp_match(i,rank,prn);
    return occ;
}
}

```

```

}
for(int i=1;i<=2*al;i++) {
    for(int j=1;j<=bl;j++) {
        if(a[i-1]==b[j-1]) dp[i][j]=dp[i-1][j-1]+1;
        else dp[i][j]=max(dp[i-1][j],dp[i][j-1]);
        if(dp[i][j-1]==dp[i][j]) pred[i][j]=L;
        else if(a[i-1]==b[j-1]) pred[i][j]=LU;
        else pred[i][j]=U;
    }
}
// do cyclic lcs
int clcs=0;
for(int i=0;i<al;i++) {
    clcs=max(clcs,lcs_length(i));
    reroot(i+1);
}
// recover a
a[al]=' \0 ' ;
return clcs;
}
}

```

6.10 Cyclic LCS

```

#define L 0
#define LU 1
#define U 2
const int mov[3][2]={0,-1, -1,-1, -1,0};
int al,bl;
char a[MAXL*2],b[MAXL*2]; // 0-indexed
int dp[MAXL*2][MAXL];
char pred[MAXL*2][MAXL];
inline int lcs_length(int r) {
    int i=r+al,j=bl,l=0;
    while(i>r) {
        char dir=pred[i][j];
        if(dir==LU) l++;
        i+=mov[dir][0];
        j+=mov[dir][1];
    }
    return l;
}
inline void reroot(int r) { // r = new base row
    int i=r,j=1;
    while(j<=bl&&pred[i][j]!=LU)
        j++;
    if(j>bl) return;
    pred[i][j]=L;
    while(i<2*al&&j<=bl) {
        if(pred[i+1][j]==U) {
            i++;
            pred[i][j]=L;
        } else if(j<bl&&pred[i+1][j+1]==LU) {
            i++;
            j++;
            pred[i][j]=L;
        } else {
            j++;
        }
    }
}
int cyclic_lcs() {
    // a, b, al, bl should be properly filled
    // note: a WILL be altered in process -- concatenated
    after itself
    char tmp[MAXL];
    if(al>bl) {
        swap(al,bl);
        strcpy(tmp,a);
        strcpy(a,b);
        strcpy(b,tmp);
    }
    strcpy(tmp,a);
    strcat(a,tmp);
    // basic lcs
    for(int i=0;i<=2*al;i++) {
        dp[i][0]=0;
        pred[i][0]=U;
    }
    for(int j=0;j<=bl;j++) {
        dp[0][j]=0;
        pred[0][j]=L;
    }
}

```

7 Data Structure

7.1 Treap

```

#include <bits/stdc++.h>
using namespace std;
#define inf 1023456789
int getint(){
    int x=0,tmp=1; char c=getchar();
    while( (c<'0' || c>'9') && c!='-' ) c=getchar();
    if( c == '-' ) c=getchar(), tmp=-1;
    while(c>='0' && c<='9') x*=10,x+=(c-'0'),c=getchar();
    return x*tmp;
}
struct Treap{
    int lsum, rsum, sum, maxsum;
    int sz, num, val, pri, tag;
    bool tagn; Treap *l, *r;
    Treap( int _val ){
        lsum = rsum = sum = maxsum = val = _val; sz = 1;
        pri = rand(); l = r = NULL; tag = 0; tagn = false;
    }
};
void push( Treap *a ){
    if( a->tagn ){
        a->val = a->num;
        if( a->l ){
            a->l->sum = a->num * a->l->sz;
            if( a->num >= 0 )
                a->l->lsum = a->l->rsum = a->l->maxsum = a->l->sum;
            else a->l->lsum = a->l->rsum = a->l->maxsum = a->num;
            a->l->tagn = true, a->l->num = a->num;
        }
        if( a->r ){
            a->r->sum = a->num * a->r->sz;
            if( a->num >= 0 )
                a->r->lsum = a->r->rsum = a->r->maxsum = a->r->sum;
            else a->r->lsum = a->r->rsum = a->r->maxsum = a->num;
            a->r->tagn = true, a->r->num = a->num;
        }
        a->tagn = false;
    }
}
if( a->tag ){
    Treap *swp = a->l; a->l = a->r; a->r = swp;
    int swp2;
    if( a->l ){
        a->l->tag ^= 1;
        swp2 = a->l->lsum; a->l->lsum = a->l->rsum; a->l->rsum = swp2;
    }
    if( a->r ){
        a->r->tag ^= 1;
        swp2 = a->r->lsum; a->r->lsum = a->r->rsum; a->r->rsum = swp2;
    }
}

```

```

    }
    a->tag = 0;
}
}
int Sum( Treap * a ){ return a ? a->sum : 0; }
int Size( Treap * a ){ return a ? a->sz : 0; }
int lSum( Treap * a ){ return a ? a->lsum : 0; }
int rSum( Treap * a ){ return a ? a->rsum : 0; }
int maxSum( Treap * a ){ return a ? a->maxsum : -inf; }
void pull( Treap * a ){
    a->sum = Sum( a->l ) + Sum( a->r ) + a->val;
    a->lsum = Sum( a->l ) + a->val + max( 0 , lSum( a->l ) );
    if( a->l ) a->lsum = max( lSum( a->l ) , a->lsum );
    a->rsum = Sum( a->r ) + a->val + max( 0 , rSum( a->r ) );
    if( a->r ) a->rsum = max( rSum( a->r ) , a->rsum );
    a->maxsum = max( 0 , rSum( a->l ) ) + a->val + max( 0 , lSum( a->r ) );
    a->maxsum = max( a->maxsum , max( maxSum( a->l ) , maxSum( a->r ) ) );
    a->sz = Size( a->l ) + Size( a->r ) + 1;
}
Treap* merge( Treap *a , Treap *b ){
    if( !a || !b ) return a ? a : b;
    if( a->pri > b->pri ){
        push( a );
        a->r = merge( a->r , b );
        pull( a );
        return a;
    }else{
        push( b );
        b->l = merge( a , b->l );
        pull( b );
        return b;
    }
}
void split( Treap *t , int k , Treap*&a , Treap*&b ){
    if( !t ){ a = b = NULL; return; }
    push( t );
    if( Size( t->l ) + 1 <= k ){
        a = t;
        split( t->r , k - Size( t->l ) - 1 , a->r , b );
        pull( a );
    }else{
        b = t;
        split( t->l , k , a , b->l );
        pull( b );
    }
}
void show( Treap *t ){
    if( t->l ) show( t->l );
    printf( " %d" , t->val );
    if( t->r ) show( t->r );
}
void Delete( Treap *t ){
    if( t->l ) Delete( t->l );
    if( t->r ) Delete( t->r );
    delete t;
}
char c[ 20 ]; int n , m;
void solve(){
    Treap *t = NULL , *tl = NULL , *tr = NULL;
    n = getint(); m = getint();
    for( int i = 0 ; i < n ; i ++ )
        t = merge( t , new Treap( getint() ) );
    while( m -- ){
        scanf( "%s" , c );
        if( c[ 0 ] == 'I' ){
            int p , k;
            p = getint(); k = getint();
            split( t , p , tl , tr );
            t = NULL;
            while( k -- )
                t = merge( t , new Treap( getint() ) );
            t = merge( t , tr );
            t = merge( tl , t );
        }else if( c[ 0 ] == 'D' ){
            int p , k;
            p = getint(); k = getint();
            split( t , p - 1 , tl , t );
            split( t , k , t , tr );
        }
    }
}

```

```

Delete( t );
t = merge( tl , tr );
}else if( c[ 0 ] == 'R' ){
    int p , k;
    p = getint(); k = getint();
    split( t , p - 1 , tl , t );
    split( t , k , t , tr );
    t->tag ^= 1;
    int swp = t->lsum; t->lsum = t->rsum; t->rsum = swp;
    t = merge( t , tr );
    t = merge( tl , t );
}else if( c[ 0 ] == 'G' ){
    int p , k;
    p = getint(); k = getint();
    split( t , p - 1 , tl , t );
    split( t , k , t , tr );
    printf( "%d\n" , Sum( t ) );
    t = merge( t , tr );
    t = merge( tl , t );
}else if( c[ 2 ] == 'K' ){
    int p , k;
    p = getint(); k = getint();
    split( t , p - 1 , tl , t );
    split( t , k , t , tr );
    t->tagn = true; t->num = getint();
    t->sum = t->num * t->sz;
    if( t->num >= 0 )
        t->lsum = t->rsum = t->maxsum = t->sum;
    else t->lsum = t->rsum = t->maxsum = t->num;
    t = merge( t , tr );
    t = merge( tl , t );
}else printf( "%d\n" , maxSum( t ) );
}
}
int main(){
    srand( time( 0 ) );
    solve();
}

```

7.2 Black Magic

```

#include <bits/extc++.h>
using namespace __gnu_pbds;
typedef tree<int,null_type,less<int>,rb_tree_tag,
tree_order_statistics_node_update> set_t;

int main()
{
    // Insert some entries into s.
    set_t s;
    s.insert(12);
    s.insert(505);

    // The order of the keys should be: 12, 505.
    assert(*s.find_by_order(0) == 12);
    assert(*s.find_by_order(3) == 505);

    // The order of the keys should be: 12, 505.
    assert(s.order_of_key(12) == 0);
    assert(s.order_of_key(505) == 1);

    // Erase an entry.
    s.erase(12);

    // The order of the keys should be: 505.
    assert(*s.find_by_order(0) == 505);

    // The order of the keys should be: 505.
    assert(s.order_of_key(505) == 0);
}

```