

Representation Learning: Autoencoder

Supervised Learning

- Give the data (x->y), x is the data, y is the label
- Goal: Learn the mapping: from x to y.

Stark Classification




Game of
Thrones




Iron Man

Unsupervised Learning


- Given the data x without labels
- Goal: Learn hidden structure(low dimension) from



Representation Learning
Data lies on a low-dimensional manifold



Clustering
Group data points based their similarity




Density Estimation
Estimate data probability $p(x)$ from data x_1, x_2, \dots, x_n

Autoencoder


Principal Component Analysis

PCA aims to find the directions of maximum variance in high-dimensional data and projects it onto a new subspace with equal or fewer dimensions than the original one

$$\begin{array}{c} \text{Original} \\ \text{Space} \end{array} \begin{bmatrix} x_{11} & x_{12} \\ x_{21} & x_{22} \\ \vdots & \vdots \\ x_{n1} & x_{n2} \end{bmatrix} \times \begin{array}{c} \text{Projection} \\ \text{Matrix} \end{array} \begin{bmatrix} w_{11} & w_{12} \\ w_{21} & w_{22} \end{bmatrix} = \begin{array}{c} \text{New/Latent} \\ \text{Space} \end{array} \begin{bmatrix} u_{11} & u_{12} \\ u_{21} & u_{22} \\ \vdots & \vdots \\ u_{n1} & u_{n2} \end{bmatrix}$$




MNIST Dataset

[illegible]


PCA for MNIST Visualization

- Each image has 28 by 28 pixels -> 28 by 28 matrix -> 784 dimensional vector
- Using PCA, find a project matrix $\mathbf{W} \in R^{784 \times 2}$
- After projection, each image can be encoded into a 2-Dimensional space




Principal Component Analysis

$$||x - \tilde{x}||^2$$




Autoencoder: NonLinear


$$||x - \tilde{x}||^2$$




Deep Autoencoder




Deep Autoencoder vs PCA



Deep Autoencoder vs PCA



Structure of Autoencoder




Undercomplete Autoencoder

- Simply copy input to output without learning anything useful
 - The autoencoder just mimic the identity function
 - Reconstruct the training data perfectly
 - Overfitting
- To avoid the above issue, we should use undercomplete autoencoder
 - The hidden layer size c is small compared to the original feature dimensionality

Sandwich Architecture in Autoencoder

- Forcing c (hidden layer size) is less than d (the input layer size)
 - Learn the important features
 - Information bottleneck:
 - A kind of trade-off between compression and retaining information




Original **6** Bricks

Can we use only **4** bricks to rebuild the previous shape?

Optimization Targets

- For Autoencoder, the training objective is to minimize $||x - \tilde{x}||^2$
- But we do not care the output layer \tilde{x}
- Hidden representation is what we really want to learn



Build Autoencoders in Keras


<https://blog.keras.io/building-autoencoders-in-keras.html>

Regularized Autoencoder

Add different constraints in case that we learn the identity transformation, i.e., overfitting

Sparse Autoencoders

- Constrain on c that penalizes it from dense
- Regularization **on output of encoder, not parameters**



$$L(x, g(f(x))) + \Omega(c)$$

- `kernel_regularizer` : instance of `keras.regularizers.Regularizer`
- `bias_regularizer` : instance of `keras.regularizers.Regularizer`
- `activity_regularizer` : instance of `keras.regularizers.Regularizer`

Example


```
from keras import regularizers
model.add(Dense(64, input_dim=64,
                kernel_regularizer=regularizers.l2(0.01),
                activity_regularizer=regularizers.l1(0.01)))
```

Denoising Autoencoders

- Add noise into original data points
- Still reconstruct original data points



$$L(x, g(f(\bar{x})))$$

Corrupted copy of x




Applications of Autoencoders

Better Representation




Pre-training Deep Neural Network

- Greedy Layer-wise Pre-training for W^1




Pre-training Deep Neural Network

- Greedy Layer-wise Pre-training for W^2




Pre-training Deep Neural Network

- Greedy Layer-wise Pre-training for W_3



Pre-training Deep Neural Network

- Fine-tune by backpropagation



Recommendation System



Arjun Narayan 

@narayanarjun

Follow



The two best performing public stocks of the decade - Netflix (+3700%) and Domino's Pizza (+3000%) - perfectly epitomize the 2010s. You either build the world's most advanced machine learning content recommender system, or make a better pizza sauce, there's no middle ground.

1:20 PM - 27 Dec 2019

3,926 Retweets 20,086 Likes



183





3.9K



20K

Rec. Sys. are Everywhere



amazon.com

Recommended for You

Amazon.com has new recommendations for you based on items you purchased or told us you own.



Recommended destinations

We've gathered the best deals in our most popular destinations.

Flic-en-Flac

Mauritius




8 Value Deals

from HK\$ 302

Take me there

Balule Game Reserve

South Africa




1 Value deal

from HK\$ 504

Take me there

Sorrento

Australia



2 Value Deals

from HK\$ 689

Take me there


Core Problem in Rec. Sys.

- Filter Information for users
- Personalization is the key:
 - Given a certain user, compute the score that quantifies how strongly a user u likes/prefer items i .




Content-based Method

- Define the similarity from items' content
 - Name: cosine similarity
 - Category
 - Rating
 - Description
 - Etc
- Combine them into a final score
- Ranked items based on their similar scores compared to users' purchased item




User Behavior

- Content-based methods: only look at the items' information
- The Insights behind the **huge** interaction behind users and items



Ratings in Netflix



Order History

User Behavior

- Content-based methods: only look at the items' information
- The Insights behind the interaction behind users and items

		Item Vector					
		Item 1	Item 2	Item 3	Item k-1	Imte k
User Vector	User 1	1	0	0		3	1
	User 2	0	3	1		0	2
	...						
	User n-1	0	2	0		1	1
	User n	0	0	0		0	0

User-based CF

- Find the similarity score between users
- Recommend products which these similar users have liked or bought previously

$$P_{u,i} = \frac{\sum_{v \in U} (r_{v,i} * s_{u,v})}{\sum_{v \in U} s_{i,v}}$$

The prediction of an item i for user u

The rating of item i given by user v

The similarity between users u and v

User Space

$$s_{u,v} = \cos(\vec{u}, \vec{v}) = \frac{\vec{u} * \vec{v}}{||\vec{u}|| ||\vec{v}||}$$

Cosine similarity used a lot in information retrieval

Item-based CF

- Find the similarity between each item pair
- Recommend similar items which were liked or purchased by the users in the past

$$P_{u,i} = \frac{\sum_{m \in I} (r_{u,m} * s_{i,m})}{\sum_{m \in I} s_{i,m}}$$

The prediction of an item i for user u

The rating of item m given by user u


The similarity between items i and m

Item Space

$$s_{i,m} = \cos(\vec{i}, \vec{m}) = \frac{\vec{i} * \vec{m}}{||\vec{i}|| ||\vec{m}||}$$

Data Sparsity



movieId	1	2	3	4	5	6	7	9	10	11	...	106487	106489	106782	106920	109374
userId																
316	-0.829457	NaN	NaN	NaN	NaN	NaN	-1.329457	NaN	-0.829457	NaN	...	NaN	NaN	NaN	NaN	NaN
320	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	NaN	...	NaN	NaN	NaN	NaN	NaN
359	1.314526	NaN	NaN	NaN	NaN	1.314526	NaN	NaN	0.314526	0.314526	...	NaN	NaN	NaN	NaN	NaN
370	0.705596	0.205596	NaN	NaN	NaN	1.205596	NaN	NaN	NaN	NaN	...	-1.294404	-0.794404	0.705596	0.205596	NaN
910	1.101920	0.101920	-0.39808	NaN	-0.39808	-0.398080	NaN	NaN	NaN	0.101920	...	NaN	NaN	-0.398080	NaN	NaN




Similarities
between users
and items are
zero

- Data Preprocessing:
 - Use the mean value of the row
 - Use the mean value of the column
- Matrix Factorization
 - Singular Value Decomposition
 - Non-Negative Matrix Factorization
 - Auto-encoder

NMF for Rec.



Autoencoder for Rec.



Pros & Cons of CF


- Pros:
 - Capture latent user and item factors
 - Can handle sparsity
 - Scalable computation (ALS)
- Cons:
 - Biases (Temporal and Popularity)
 - Cold Start Problem
 - No Context-awareness

How to evaluate Rec. Sys.

- Offline Evaluation:
 - Train/Test Splitting
 - RMSE
 - Recall
 - Etc
- Online Evaluation:
 - A/B Testing
 - Click-Through Rate (CTR)
 - Conversion Rate (CR)
 - Etc

Advanced Rec. Sys.

- Deep Learning for Rec.:



Wide & Deep model

- Reinforcement Learning for Rec.:

