

```
-- Nmap Scripting Engine
-- required packages for this script
--
local bin = require "bin"
local nmap = require "nmap"
local shortport = require "shortport"
local stdnse = require "stdnse"
local string = require "string"
local table = require "table"

--Usage:
--Identify MELSEC-Q Series PLC CPUINFO
--nmap -script melsecq-discover-udp.nse -sU -p 5006 <host>

--Output Example:
--PORT      STATE SERVICE          REASON
--5006/udp open  Mitsubishi/Melsoft udp syn-ack
--| melsecq-discover:
--|_ CPUINFO: Q03UDECPU

description = [[
discovery Mitsubishi Electric Q Series PLC
      GET CPUINFO
]]

author = "ICS Security Workspace(plcscan.org)"
license = "Same as Nmap--See http://nmap.org/book/man-legal.html"
categories = {"discovery","intrusive"}

function set_nmap(host, port)
    port.state = "open"
    port.version.name = "Mitsubishi/Melsoft Udp"
    port.version.product = "Mitsubishi Q PLC"
    nmap.set_port_version(host, port)
    nmap.set_port_state(host, port, "open")

end

function send_receive(socket, query)
    local sendstatus, senderr = socket:send(query)
    if(sendstatus == false) then
        return "Error Sending getcpuinfopack"
    end
    local rcvstatus,response = socket:receive()
    if(rcvstatus == false) then
        return "Error Reading getcpuinfopack"
    end
    return response
end

portrule = shortport.port_or_service(5006, "Melsoft/TCP", "udp")
action = function(host,port)
    local getcpuinfopack =
bin.pack("H","57000000001111070000ffff030000fe03000014001c080a080000000000000004" .. "0101" ..
"010000000001")
    local response
    local output = stdnse.output_table()
    local sock = nmap.new_socket()
    local constatus,conerr = sock:connect(host,port)
    if not constatus then
        stdnse.print_debug(1,
            'Error establishing connection for %s - %s', host,conerr

```

```
)
return nil
end
response = send_receive(sock, getcpuinfopack)
local mel, pack_head = bin.unpack("C", response, 1)
-- local mel, space_id = bin.unpack("C", response, 55)
local offset = 0
if ( pack_head == 0xd7) then
--   if ( space_id == 0x20) then
      local mel
      local mel, cpuinfo = bin.unpack("z", response, 42 + offset)
      output["CPUINFO"] = string.sub(cpuinfo, 1, 16)
      set_nmap(host, port)
      sock:close()
      return output
--   end
  else
    sock:close()
    return nil
  end
end

end
```