

# Tyre inflation pressures

Tread	Size	Bolt pattern	Pressure (bar)	Code
TR	23*8.50-12	4*100	3,4	64120
TR	23*8.50-12	6*120	3,4	65046
TR	23*8.50-12	5*140	3,4	65995
GR	23*8.50-12	4*100	4,6	64160
GR	23*8.50-12	6*120	4,6	65045
GR	23*8.50-12	5*140	4,6	65994
TR	23*10.50-12	4*100	2,5	64618
TR	23*10.50-12	6*120	2,5	65048
TR	23*10.50-12	5*140	2,5	65997
GR	23*10.50-12	4*100	3,0	64161
GR	23*10.50-12	6*120	3,0	65047
GR	23*10.50-12	5*140	3,0	65996
GR	18*7.50-8	4*100	1,9	63503
GR	20*8.00-10	4*100	1,9	64164
TR	27*8.50-15	6*120	4,2	65019
TR	27*8.50-15	10*140	4,2	65414
GR	26*12.00-12	4*100	3,4	64751
GR	26*12.00-12	6*120	3,4	64930
GR	26x12.00-12	10*140	3,4	65212
TR	26x12.00-12	4*100	2,1	64752
TR	26x12.00-12	6*120	2,1	64931
TR	26x12.00-12	10*140	2,1	65739
GR	320/55-12	10*140	2,8	65459
TR	320/60-12 HD	6*120	4,0	65028
TR	320/60-12 HD	10*140	4,0	65224
GR	26,5*14.00-12	6*120	1,8	65786
GR	26,5*14.00-12	10*140	1,8	65787
TR	400/50-15	10*140	3,0	65958
GR	400/50-15	10*140	3,0	66257
TR	320/55-15	10*140	3,0	65506
GR	31*15,5-15	10*140	3,1	65959