

Avant Power OptiTemp® Battery Pack and Module packing guide

The battery/module is packed in a separate wooden crate with cables (if included) in a separate electrically insulating bag:

- The battery is wrapped to be weather-tight with electrically insulating plastic material
- The base of the package is pallet with plywood or hardboard on top
- Plywood or collars side walls with wooden plywood lid and metal reinforced corners. Height of the walls at least 100 mm above the battery/module height
- Weather protective plastic on top of the lid, which is stapled to the sides
- The wrapped battery/module is securely attached to the pallet with screws at its own mounting points
- If cables are included, they are placed in a separate plastic bag in the space between the crate, so they cannot move
- Free spaces are filled with padding materials, including the space above the battery
- One side wall should have a vent cap for ventilation
- Necessary documents in a weatherproof pocket inside the package
- The lid is stapled, nailed, or screwed to the side walls
- Two plastic straps should be tighten around the package
- External markings shall be attached

Documents and markings

Following documents shall be included in the freight documents:

- 2023-1003 or 2023-1005 UN Test summary (depending the battery model)
- A466140 Battery safety datasheet
- A466139 Optitemp Fluid – safety datasheet

Following markings shall be attached to the package:

- No stacking symbol
- Center of mass (if unbalanced package)
- Lifting points
- Orientation arrow
- UN3480 marking, including phone number
 - +358 3 347 8800
- Package group 9 marking
- Cargo aircraft only – marking, if air transport
- Lithium ion Batteries – marking

