

OPTITEMP LI-ION BATTERY SAFE RECEIVING, HANDLING, STORAGE AND RECYCLING

1. GENERAL

The end-user can return the battery within the Avant loader for maintenance or as a waste. Avant service dealer makes the evaluation and decisions whether the battery can be serviced back in safe operation or handled as a waste.

If the battery condition is evaluated to be a waste, acc. to EU Battery regulation 2023/1542, Avant Tecno and so on authorized Avant service dealer located in European Union member state, shall take back all OptiTemp® waste batteries from end-users:

- regardless of their condition or origin,
- free of charge, (not including the costs of removing the battery from the loader)
- without an obligation on the end-user to buy a new OptiTemp® battery,
- nor to have bought the OptiTemp® battery from the receiver.

Avant Tecno is responsible party for recycling the OptiTemp® waste batteries. Avant Power is responsible for handing over the waste handling instructions and guidelines.

2. RECEIVING THE BATTERY

When receiving the battery from the end-user, following information needs to be asked if possible:

- Reason why the battery is considered to be faulty or waste
- Have there been any incidents, accidents or other abnormal behavior

Visual inspection of the battery needs to be carried out by the authorized Avant service dealer:

- Any damage in the battery casing and cover (ruptures, cracks, loose components)
- The battery case is not bulging or deformed
- Any leakage of fluids
- Any wear or damage in connection cables and connectors
- Any signs of fire or heat deformation
- What information or alarms the loader's Multi-function display includes concerning the battery
- Are identification and warranty labels attached and visible

Gather following information:

- Comments concerning reasons for battery is waste or faulty
- Comments concerning visual inspection
- Pictures of the battery
- Serial number of the battery

Send all gathered information by e-mail to sales@avanttecno.com.

3. OTHER SAFETY DOCUMENTS

To ensure safe handling of OPTITEMP batteries, read carefully following documents:

- A466140 EN Battery safety procedure
- A466139 EN Optitemp Fluid - SDS
- A465990 Optitemp LiION battery Operator's Manual

4. HANDLING OF THE WASTE OR FAULTY BATTERY

Precautions for safe handling

- Lift the battery only from dedicated lifting points acc. to Avant instructions
- Don't wash or rinse with water
- Do not expose the battery to strong oxidizing agents
- Do not damage or remove the battery cover

- Keep away from open flames, hot surfaces and sources of ignition
- Do not damage or deform the battery e.g. when lifting it
- Protect the connector poles from mechanical impact and short circuit by sealing them with electric resistant tape
- Cover the waste battery in to a plastic bag or film and place it on the wooden pallet. Ensure the battery cannot fall from the pallet.

5. STORAGING OF THE WASTE BATTERY

Following rules have to be followed to ensure safe storage:

- Do not store the waste batteries in dusty areas and avoid water, acid and oxidising agents
- Store indoors in separate storage container or room, between 0°C and +25°C in a dry environment, air humidity below 70%
- Avoid direct sunlight, high temperature and high humidity
- Do not store the waste batteries on top of each other. But if it is necessary, use shelves which can carry at least a load of 220 kg/battery
- Maximum amount of waste batteries in one container or room is 6 pcs
- Restrict access into the storage container or room from unauthorized persons
- Mark the storage container or room doors with following labels:



6. SAFETY PRECAUTIONS DURING STORAGING OF THE WASTE BATTERY

Following safety equipment have to be available and accessible near the storage area:

- Fire extinguisher of type AVD/10kg recommended, but at least ABC/10 kg
- Eye protection and safety gloves
- Respiratory protection

Remember to train how to use the extinguisher!



7. PICK-UP OF THE WASTE OR FAULTY BATTERY FOR RECYCLING

After Avant received the notification mentioned in chapter 2, the local recycling contract operator will pick-up the waste battery(ies). The time of pick-up will be informed by the contract recycling operator with possible notes how to do the packaging and if any package labels are needed.