

According to Regulation (EC) No 1907/2006

Antifreeze 774F NG Red -40°C



Version number: 1
Issued: 2025-05-13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Antifreeze 774F NG Red -40°C

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Anti-freeze. Refrigerants

1.3. Details of the supplier of the safety data sheet

Supplier

Arom-dekor Kemi Oy

Address

Halkotarhantie 1
FI-451 20 Kouvola
Finland

Telephone

+358 27 249990

Email

info@aromdekor.fi

Manufacturer

Arom-dekor Kemi AB

Address

Europavägen 1
51291 SEXDREGA
Sweden

Telephone

0320 60500

Email

sdb@aromdekor.se

Web site

<https://aromdekor.se/>

1.4. Emergency telephone number

0800 147 111 (toll-free); 09 471 977 (standard rate)

Available outside office hours

Yes

According to Regulation (EC) No 1907/2006

Antifreeze 774F NG Red -40°C



Version number: 1
Issued: 2025-05-13

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Classification

Specific Target Organ Toxicity — Repeated exposure, hazard category 2
Acute toxicity, oral, hazard category 4

Hazard statements

H302, H373

Description

The full text for all hazard statements is displayed in section 16.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Warning

Hazard statements

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P301 + P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P501 Dispose of contents/container to accordance with applicable local/regional/national/international regulations.

More information

Contains: Ethylene glycol

2.3. Other hazards

This product does not contain any PBT or vPvB substances.

Contains no substances with hormone-disrupting properties.

According to Regulation (EC) No 1907/2006

Antifreeze 774F NG Red -40°C



Version number: 1
Issued: 2025-05-13

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS No. EC No. REACH No. Index No.	Concentration	Classification	H-pharse M factor acute M factor chronic	Note
Ethylene glycol	107-21-1 203-473-3 01-2119456816-28-xxxx -	42.5 - <48.5%	Acute Tox. 4 - oral, STOT RE 2	H302, H373 - -	ATE oral: 500 mg/kg
Potassium isononanoate	84501-71-3 282-991-1 - -	<1.5%	Skin Irrit. 2, Eye Irrit. 2	H315, H319 - -	-
Methyl-1H-benzotriazole	29385-43-1 249-596-6 01-2119979081-35-XXXX -	<0.15%	Acute Tox. 4 - oral, Repr. 2, Aquatic Chronic 2	H302, H361d, H411 - -	ATE - 720 mg/kg bw

Substance additional information

For the complete text of H- / EUH-statements mentioned in this section, see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General first aid, rest, warmth and fresh air. If breathing is irregular or stopped, administer artificial respiration.

Inhalation

Remove person to fresh air and keep comfortable for breathing.

Skin contact

Wash skin with soap and water.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Drink plenty of water. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Ingestion may cause irritation of the gastrointestinal tract, vomiting and diarrhoea.

According to Regulation (EC) No 1907/2006

Antifreeze 774F NG Red -40°C



Version number: 1
Issued: 2025-05-13

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

During fire, toxic gases (CO, CO₂, NO_x) are formed.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Self-contained breathing apparatus.

Other

Measures in case of fire

Cool containers exposed to heat with water spray and remove container, if no risk is involved. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Use personal protective equipment as required.

6.2. Environmental precautions

Do not allow to enter drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
Dispose of in accordance with local regulations .

6.4. Reference to other sections

For personal protection, see section 8.
For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Preventive handling precautions

Provide adequate ventilation. Prevent aerosol formation or splashes. Avoid inhalation of vapours/spray and contact with skin and eyes.

According to Regulation (EC) No 1907/2006

Antifreeze 774F NG Red -40°C



Version number: 1
Issued: 2025-05-13

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place.
Store away from: Strong oxidising agents.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure limits

Ingredient	CAS No. EC No.	Exposure limit ppm / mg/m ³	Short-term exposure limit ppm / mg/m ³	Source	Remark	Year
Ethylene glycol	107-21-1 203-473-3	20 / 50 /	40 / 100 /	HTP-ARVOT 2020	skin	2002

DNEL/DMEL

Product/Substance name (CAS No./EC No.)	Type	Exposure	Value	Population	Effects
Methyl-1H-benzotriazole (29385-43-1/249-596-6)	DNEL	Chronic (long term) Oral	0.25 mg/kg bw/day	Consumers	Systemic
Methyl-1H-benzotriazole (29385-43-1/249-596-6)	DNEL	Acute (short term) Oral	0.25 mg/kg bw/day	Consumers	Systemic
Methyl-1H-benzotriazole (29385-43-1/249-596-6)	DNEL	Chronic (long term) Dermal	0.25 mg/kg bw/day	Consumers	Systemic
Methyl-1H-benzotriazole (29385-43-1/249-596-6)	DNEL	Chronic (long term) Dermal	0.5 mg/kg bw/day	Workers	Systemic
Methyl-1H-benzotriazole (29385-43-1/249-596-6)	DNEL	Chronic (long term) Inhalation	4.4 mg/m ³	Consumers	Systemic
Methyl-1H-benzotriazole (29385-43-1/249-596-6)	DNEL	Chronic (long term) Inhalation	8.8 mg/m ³	Workers	Systemic
Ethylene glycol (107-21-1/203-473-3)	DNEL	Chronic (long term) Inhalation	35 mg/m ³	Workers	Local
Ethylene glycol (107-21-1/203-473-3)	DNEL	Chronic (long term) Dermal	106 mg/kg	Workers	Systemic
Ethylene glycol (107-21-1/203-473-3)	DNEL	Chronic (long term) Inhalation	7 mg/m ³	Consumers	Local
Ethylene glycol (107-21-1/203-473-3)	DNEL	Chronic (long term) Dermal	53 mg/kg	Consumers	Systemic

According to Regulation (EC) No 1907/2006

Antifreeze 774F NG Red -40°C

Version number: 1
 Issued: 2025-05-13

PNEC/PEC

Product/Substance name (CAS No./EC No.)	Type	Environmental compartment	Value
Methyl-1H-benzotriazole (29385-43-1/249-596-6)	PNEC	Freshwater	0.008 mg/l
Methyl-1H-benzotriazole (29385-43-1/249-596-6)	PNEC	Sewage Treatment Plant	39.4 mg/l
Methyl-1H-benzotriazole (29385-43-1/249-596-6)	PNEC	Marine water	0.008 mg/l
Methyl-1H-benzotriazole (29385-43-1/249-596-6)	PNEC	Sediment (freshwater)	0.003 mg/kg sedi- ment dw
Methyl-1H-benzotriazole (29385-43-1/249-596-6)	PNEC	Sediment (marine water)	0.003 mg/kg sedi- ment dw
Methyl-1H-benzotriazole (29385-43-1/249-596-6)	PNEC	Soil	0.002 mg/kg soil dry weight
Ethylene glycol (107-21-1/203-473-3)	PNEC	Marine water	1 mg/l
Ethylene glycol (107-21-1/203-473-3)	PNEC	Sediment (marine water)	3.7 mg/kg
Ethylene glycol (107-21-1/203-473-3)	PNEC	Sediment (freshwater)	37 mg/kg
Ethylene glycol (107-21-1/203-473-3)	PNEC	Freshwater	10 mg/l
Ethylene glycol (107-21-1/203-473-3)	PNEC	Sewage Treatment Plant	199.5 mg/l
Ethylene glycol (107-21-1/203-473-3)	PNEC	Soil	1.53 mg/kg
Ethylene glycol (107-21-1/203-473-3)	PNEC	Intermittent releases	10 mg/l

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Provide easy access to water supply and eye wash facilities.

Eye / face protection

Use eye protection according to EN 166. If risk of splashing, wear safety goggles or face shield.

According to Regulation (EC) No 1907/2006

Antifreeze 774F NG Red -40°C



Version number: 1
Issued: 2025-05-13

Hand protection

Wear suitable gloves tested to EN 374.

Recommended material:

NBR (Nitrile rubber) - 0,35 mm

Butyl caoutchouc (butyl rubber) - 0,5 mm

Breakthrough time: > 480 min.

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Other skin protection

Wear suitable protective clothing as protection against splashing or contamination.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Filter type: A/P2, A/P3.

Thermal hazards

No data available.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

red

Odour

Odourless.

Melting point / freezing point

No data available

Boiling point or initial boiling point and boiling range

No data available

Flammability

No data available

Lower and upper explosion limit

No data available

Flash point

No data available

According to Regulation (EC) No 1907/2006

Antifreeze 774F NG Red -40°C



Version number: 1
Issued: 2025-05-13

Auto-ignition temperature

No data available

Decomposition temperature

No data available

pH

7.5 - 9

Kinematic viscosity

No data available

Solubility

No data available

Water solubility

Soluble in water.

Partition coefficient n-octanol/water

No data available

Vapour pressure

No data available

Density and/or relative density

1.06

Relative vapour density

No data available

Explosive properties

Not explosive

Particle characteristics

Not applicable.

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non-reactive under normal use conditions.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

According to Regulation (EC) No 1907/2006

Antifreeze 774F NG Red -40°C



Version number: 1
Issued: 2025-05-13

10.4. Conditions to avoid

Incompatible materials . High temperature .

10.5. Incompatible materials

Strong oxidising agents.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed.

ATEmix: 1033,06 mg/kg - Oral

Product / Substance name CAS / EC no.	Dose descriptor	Value / Dose	Exposure route	Duration of exposure	Test animals	Method / Guideline	Remarks
Ethylene glycol 107-21-1 / 203-473-3	ATE	500 mg/kg	Oral	-	-	-	-
Ethylene glycol 107-21-1 / 203-473-3	LD50	> 3500 mg/kg	Dermal	-	Mouse	-	-
Ethylene glycol 107-21-1 / 203-473-3	LC50	> 2,5 mg/l	Inhalation	6h	Rat	-	Aerosol
Methyl-1H-benzotriazole 29385-43-1 / 249-596-6	LD50	> 2000 mg/kg	Dermal	24h	Rabbit	OECD 402	-
Methyl-1H-benzotriazole 29385-43-1 / 249-596-6	LD50	720 mg/kg	Oral	-	Rat	OECD 401	-

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

According to Regulation (EC) No 1907/2006

Antifreeze 774F NG Red -40°C



Version number: 1
Issued: 2025-05-13

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if swallowed.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information

No data available.

SECTION 12: Ecological information

12.1. Toxicity

Acute fish toxicity

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species
Ethylene glycol 107-21-1 / 203-473-3	LC50	72860 mg/l	96h	Fathead minnow
Methyl-1H-benzotriazole 29385-43-1 / 249-596-6	LC50	180 mg/l	72h	Danio rerio (zebrafish)

Acute algae toxicity

According to Regulation (EC) No 1907/2006

Antifreeze 774F NG Red -40°C

Version number: 1
 Issued: 2025-05-13

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species	Method / Guideline
Methyl-1H-benzotriazole 29385-43-1 / 249-596-6	ErC50	75 mg/l	72h	Pseudokirchneriella subcapitata	-
Ethylene glycol 107-21-1 / 203-473-3	EC50	6500 - 13000 mg/L	96h	Pseudokirchneriella subcapitata	EPA 600/9-78-018

Acute crustacean toxicity

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species
Ethylene glycol 107-21-1 / 203-473-3	EC50	> 100 mg/l	48h	Daphnia magna
Methyl-1H-benzotriazole 29385-43-1 / 249-596-6	EC50	8,58 mg/l	48h	Daphnia galeata
Methyl-1H-benzotriazole 29385-43-1 / 249-596-6	LC50	55 mg/l	48h	Arcartia tonsa

Micro-/macro organism toxicity

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species	Method / Guideline
Ethylene glycol 107-21-1 / 203-473-3	EC20	> 1995 mg/L	0.5h	Bacteria	ISO 8192 , Activated sludge
Methyl-1H-benzotriazole 29385-43-1 / 249-596-6	EC50	1060 mg/L	24h	Bacteria	ISO 8192, Activated sludge

Chronical toxicity

Product / Substance name CAS / EC no.	Measurement type	Value / Result	Duration of exposure	Species	Method / Guideline
Ethylene glycol 107-21-1 / 203-473-3	NOEC	15380 mg/L	7 days	Pimephales promelas (fathead minnow)	EPA EPA 600/4-89/001

According to Regulation (EC) No 1907/2006

Antifreeze 774F NG Red -40°C



Version number: 1
Issued: 2025-05-13

Product / Sub- stance name CAS / EC no.	Measurement type	Value / Result	Duration of expos- ure	Species	Method / Guideline
Ethylene glycol 107-21-1 / 203-473-3	NOEC	8590 mg/L	-	Daphnia	EPA 600/4-89/001

12.2. Persistence and degradability

Methyl-1H-benzotriazole (CAS 29385-43-1) : 4 % (28d, EU Method C.4-D)

12.3. Bioaccumulative potential

Product / Substance name CAS / EC no.	LogKow / LogPow	Method / Guideline
Ethylene glycol 107-21-1 / 203-473-3	- 1,36 log Pow	-
Methyl-1H-benzotriazole 29385-43-1 / 249-596-6	1,079 - ≤ 1,083 logPow (25°C)	OECD Guideline 117

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or vPvB substances.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal considerations

Dispose of waste according to applicable legislation.

Packaging

Packing which cannot be properly cleaned must be disposed of.

Other

The waste code has to be identified in agreement with the disposal company or the competent authority.

According to Regulation (EC) No 1907/2006

Antifreeze 774F NG Red -40°C



Version number: 1
Issued: 2025-05-13

SECTION 14: Transport information

14.1. UN number

No dangerous good in sense of these transport regulations.

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

EU Regulation (EC) No. 1907/2006 (REACH)

SDS is prepared according to Regulation (EU) 2020/878.

CLP - Regulation (EC) No 1272/2008

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions) : 3

National regulations

The Decree of the Ministry of Social Affairs and Health on concentrations known to be harmful (654/2020).

Government Decree on Chemical Agents at Work 715/2001.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

According to Regulation (EC) No 1907/2006

Antifreeze 774F NG Red -40°C



Version number: 1
Issued: 2025-05-13

SECTION 16: Other information

Abbreviations

EC20: The concentration that causes the measured effect in 20% of the test organisms.

EC50 - The concentration of a substance that affects 50 % of a population over a given period of time

ErC50: The concentration of a test substance which results in 50 % reduction in growth rate relative to the control group within 72 hours exposure.

NOEC = No Observed Effect Concentration.

ATE = Acute Toxicity Estimate.

C&L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

DMEL - Derived Minimum Effect Level

DNEL - Derived No Effect Level

ECHA - European Chemicals Agency

GHS - Globally Harmonized System

Kow - octanol-water partition coefficient

LC50 - Lethal Concentration to 50 % of a test population

LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)

OEL - Occupational Exposure Limit

PBT - Persistent, Bioaccumulative and Toxic substance

PEC - Predicted Environmental Concentration

PNEC - Predicted No Effect Concentration(s)

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

STOT - Specific Target Organ Toxicity

vPvB - Very Persistent and Very Bioaccumulative

Evaluation methods for classification

Calculation method.

Phrase meaning

STOT RE 2 - Specific Target Organ Toxicity — Repeated exposure, hazard category 2

Acute Tox. 4 - oral - Acute toxicity, oral, hazard category 4

Skin Irrit. 2 - Skin irritation, hazard category 2

Eye Irrit. 2 - Eye irritation, hazard category 2

Repr. 2 - Reproductive toxicity, hazard category 2

Aquatic Chronic 2 - Hazardous to the aquatic environment — Chronic hazard category 2

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure .

H411 Toxic to aquatic life with long lasting effects.