

	INCHES		MILLIMETERS		
	MIN	MAX	MIN	MAX	
Α		0.180		4.572	
A1	0.015		0.38		
A2	0.125	0.175	3.18	4.45	
АЗ	0.055	0.080	1.40	2.03	
В	0.015	0.022	0.381	0.56	
B1	0.045	0.065	1.14	1.65	
С	0.008	0.014	0.2	0.355	
D1	0.005	0.080	0.13	2.03	
Ε	0.300	0.325	7.62	8,26	
E1	0.240	0.310	6.10	7.87	
е	0.100	BSC.	2.54	BSC.	
eΑ	0.300	BSC.	7.62	BSC.	
eВ	0.400	BSC.	10.16	BSC.	
L	0.115	0.150	2.921	3,81	

VARIATIONS:

	INCH	ES	MILLIMETERS				
	MIN	MAX	MIN	MAX	Ζ	MS001	PKG CODE
D	0.348	0.390	8.84	9.91	ω	ΑВ	P8-1, P8-3, P8-4, P8-5
D	0.735	0.765	18.67	19.43	14	AC	P14-3, P14-4, P14-6, P14-7 P14M-4, P14M-5, P14M-7
D	0.745	0.765	18.92	19.43	16	AA	P16-1, P16-2, P16-3, P164, P16-7F, P16-8, P16-9
D	0.885	0.915	22,48	23.24	18	AD	P18-2, P18-5, P18-6, P18-7, P18-9
D	1.015	1.045	25.78	26.54	20	ΑE	P20-2, P20-3, P20-4, P20M-1
D	1.14	1.265	28.96	32.13	24	AF	N24-1, N24-3, N24-4, N24-5, N24-8, N24-9F; N24M-1
D	1.360	1.380	34.54	35.05	28	*5	N28-1F, N28-2, N28-4, N28M-1

NOTES:

- 1. DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.
- 2. D&E DO NOT INCLUDE MOLD FLASH.
- 3. MOLD FLASH OR PROTRUSIONS NOT TO EXCEED 0.15mm (.006").
- 4. MMEETS JEDEC MS001-XX AS SHOWN IN ABOVE TABLE

SIDE VIEW

- 5. SIMILIAR TO JEDEC MO-058AB
- 6. N = NUMBER OF PINS
- 7. MATERIAL MUST COMPLY WITH BANNED AND RESTRICTED SUBSTANCES SPEC # 10-0131.

-b1

8. ALL DIMENSIONS APPLY TO BOTH LEADED (-) AND PHFREE (+) PKG. CODES.

TITLE:

PACKAGE DUTLINE, PDIP .300"

APPROVAL

DOCUMENT CONTROL NO. 21-0043

F

-DRAWING NOT TO SCALE-