GreenDroid: A Mobile Application Processor for a Future of Dark Silicon

Nathan Goulding, Jack Sampson, Ganesh Venkatesh,
Saturnino Garcia, Joe Auricchio, Jonathan Babb[+],
Michael B. Taylor, and Steven Swanson

Department of Computer Science and Engineering,
University of California, San Diego

[+] *CSAIL, Massachusetts Institute of Technology*

Where does dark silicon come from? (And how dark is it going to be?)

Utilization Wall:

With each successive process generation, the percentage of a chip that can actively switch drops exponentially due to power constraints.

We've Hit The Utilization Wall

Utilization Wall: With each successive process generation, the percentage of a chip that can actively switch drops exponentially due to power constraints.

- Scaling theory
  - Transistor and power budgets are no longer balanced
  - Exponentially increasing problem!
- Experimental results
  - Replicated a small datapath
  - More "dark silicon" than active
- Observations in the wild
  - Flat frequency curve
  - "Turbo Mode"
  - Increasing cache/processor ratio

We've Hit The Utilization Wall

Utilization Wall: With each successive process generation, the percentage of a chip that can actively switch drops exponentially due to power constraints.

- Scaling theory
  - Transistor and power budgets are no longer balanced
  - Exponentially increasing problem!
- Experimental results
  - Replicated a small datapath
  - More "dark silicon" than active
- Observations in the wild
  - Flat frequency curve
  - "Turbo Mode"
  - Increasing cache/processor ratio

Classical scaling

Device count	S^2
Device frequency	S
Device power (cap)	1/S
Device power (V_{dd})	$1/S^2$
Utilization	**1**

Leakage-limited scaling

Device count	S^2
Device frequency	S
Device power (cap)	1/S
Device power (V_{dd})	**~1**
Utilization	**$1/S^2$**

We've Hit The Utilization Wall

Utilization Wall: With each successive process generation, the percentage of a chip that can actively switch drops exponentially due to power constraints.

- Scaling theory
  - Transistor and power budgets are no longer balanced
  - Exponentially increasing problem!
- Experimental results
  - Replicated a small datapath
  - More "dark silicon" than active
- Observations in the wild
  - Flat frequency curve
  - "Turbo Mode"
  - Increasing cache/processor ratio



We've Hit The Utilization Wall

Utilization Wall: With each successive process generation, the percentage of a chip that can actively switch drops exponentially due to power constraints.

- Scaling theory
  - Transistor and power budgets are no longer balanced
  - Exponentially increasing problem!
- Experimental results
  - Replicated a small datapath
  - More "dark silicon" than active
- Observations in the wild
  - Flat frequency curve
  - "Turbo Mode"
  - Increasing cache/processor ratio



We've Hit The Utilization Wall

Utilization Wall: With each successive process generation, the percentage of a chip that can actively switch drops exponentially due to power constraints.

- Scaling theory
  - Transistor and power budgets are no longer balanced
  - Exponentially increasing problem!
- Experimental results
  - Replicated a small datapath
  - More "dark silicon" than active
- Observations in the wild
  - Flat frequency curve
  - "Turbo Mode"
  - Increasing cache/processor ratio



We've Hit The Utilization Wall

Utilization Wall: With each successive process generation, the percentage of a chip that can actively switch drops exponentially due to power constraints.

- Scaling theory
  - –
  - –
- E
  - –
  - – More "dark silicon" than active
- Observations in the wild
  - – Flat frequency curve
  - – "Turbo Mode"
  - – Increasing cache/processor ratio

The utilization wall will change the way everyone builds processors.



Utilization Wall: Dark Implications for Multicore

Spectrum of tradeoffs between # of cores and frequency

Example:
65 nm → 32 nm (S = 2)



What do we do with dark silicon?

- Goal: Leverage dark silicon to scale the utilization wall

- Insights:
  - Power is now more expensive than area
  - Specialized logic can improve energy efficiency (10–1000x)

- Our approach:
  - Fill dark silicon with specialized cores to save energy on common applications
  - Provide focused reconfigurability to handle evolving workloads

Conservation Cores

"Conservation Cores: Reducing the Energy of Mature Computations," Venkatesh et al., ASPLOS '10

- Specialized circuits for reducing energy
  - Automatically generated from hot regions of program source code
  - Patching support future-proofs the hardware
- Fully-automated toolchain
  - Drop-in replacements for code
  - Hot code implemented by c-cores, cold code runs on host CPU
  - HW generation/SW integration
- Energy-efficient
  - Up to 18x for targeted hot code



The C-core Life Cycle



Outline

- Utilization wall and dark silicon
- GreenDroid
- Conservation cores
- GreenDroid energy savings
- Conclusions

Emerging Trends

The *utilization wall* is exponentially worsening the dark silicon problem.

Specialized architectures are receiving more and more attention because of energy efficiency.

Mobile application processors are becoming a dominant computing platform for end users.



Mobile Application Processors Face the Utilization Wall

- The evolution of mobile application processors mirrors that of microprocessors

- Application processors face the utilization wall
  - Growing performance demands
  - Extreme power constraints



Android™

- Google's OS + app. environment for mobile devices
- Java applications run on the Dalvik virtual machine
- Apps share a set of libraries (libc, OpenGL, SQLite, etc.)



Applying C-cores to Android

- Android is well-suited for c-cores
  - Core set of commonly used applications
  - Libraries are hot code
  - Dalvik virtual machine is hot code
  - Libraries, Dalvik, and kernel & application hotspots → c-cores
  - Relatively short hardware replacement cycle



Android Workload Profile

- Profiled common Android apps to find the hot spots, including:
  - Google: Browser, Gallery, Mail, Maps, Music, Video
  - Pandora
  - Photoshop Mobile
  - Robo Defense game
- Broad-based c-cores
  - 72% code sharing
- Targeted c-cores
  - 95% coverage with just 43,000 static instructions (approx. 7 mm^2)



GreenDroid: Applying Massive Specialization to Mobile Application Processors

Android workload

Automatic c-core generator



Conservation cores (c-cores)



Low-power tiled multicore lattice

GreenDroid Tiled Architecture

- Tiled lattice of 16 cores
- Each tile contains
  - 6-10 Android c-cores (~125 total)
  - 32 KB D-cache (shared with CPU)
  - MIPS processor
    - 32 bit, in-order, 7-stage pipeline
    - 16 KB I-cache
    - Single-precision FPU
  - On-chip network router



GreenDroid Tile Floorplan

- 1.0 mm^2 per tile
- 50% C-cores
- 25% D-cache
- 25% MIPS core, I-cache, and on-chip network



GreenDroid Tile Skeleton

- 45 nm process
- 1.5 GHz
- ~30k instances

- Blank space is filled with a collection of c-cores
- Each tile contains different c-cores



Outline

- Utilization wall and dark silicon
- GreenDroid
- Conservation cores
- GreenDroid energy savings
- Conclusions

Constructing a C-core

- C-cores start with source code
  - Can be irregular, integer programs
  - Parallelism-agnostic
- Supports almost all of C:
  - Complex control flow
    e.g., goto, switch, function calls
  - Arbitrary memory structures
    e.g., pointers, structs, stack, heap
  - Arbitrary operators
    e.g., floating point, divide
  - Memory coherent with host CPU

```
sumArray(int *a, int n)
{
  int i = 0;
  int sum = 0;

  for (i = 0; i < n; i++) {
    sum += a[i];
  }

  return sum;
}
```

Constructing a C-core

- Compilation
  - C-core selection
  - SSA, infinite register, 3-address code
  - Direct mapping from CFG and DFG
  - Scan chain insertion



- Verilog → Place & Route
  - 45 nm process
  - Synopsys CAD flow
    - Synthesis
    - Placement
    - Clock tree generation
    - Routing



C-cores Experimental Data

- We automatically built 21 c-cores for 9 "hard" applications
  - 45 nm TSMC
  - Vary in size from 0.10 to 0.25 mm^2
  - Frequencies from 1.0 to 1.4 GHz

Application	# C-cores	Area (mm^2)	Frequency (MHz)
bzip2	1	0.18	1235
cjpeg	3	0.18	1451
djpeg	3	0.21	1460
mcf	3	0.17	1407
radix	1	0.10	1364
sat solver	2	0.20	1275
twolf	6	0.25	1426
viterbi	1	0.12	1264
vpr	1	0.24	1074

C-core Energy Efficiency: Non-cache Operations



- Up to 18x more energy-efficient (13.7x on average), compared to running on the MIPS processor

Where do the energy savings come from?



MIPS baseline
91 pJ/instr.



C-cores
8 pJ/instr.

Supporting Software Changes

- Software may change – HW must remain usable
  - C-cores unaffected by changes to cold regions
- Can support any changes, through *patching*
  - Arbitrary insertion of code – software exception mechanism
  - Changes to program constants – configurable registers
  - Changes to operators – configurable functional units
- Software exception mechanism
  - Scan in values from c-core
  - Execute in processor
  - Scan out values back to c-core to resume execution

Patchability Payoff: Longevity

- Graceful degradation
  - Lower initial efficiency
  - Much longer useful lifetime
- Increased viability
  - With patching, utility lasts ~10 years for 4 out of 5 applications
  - Decreases risks of specialization



Outline

- Utilization wall and dark silicon
- GreenDroid
- Conservation cores
- GreenDroid energy savings
- Conclusions

GreenDroid: Energy per Instruction

- More area dedicated to c-cores yields higher execution coverage and lower energy per instruction (EPI)



- 7 mm^2 of c-cores provides:
  - 95% execution coverage
  - 8x energy savings over MIPS core

What kinds of hotspots turn into GreenDroid c-cores?

C-core	Library	# Apps	Coverage (est., %)	Area (est., mm²)	Broad-based
dvmInterpretStd	libdvm	8	10.8	0.414	Y
scanObject	libdvm	8	3.6	0.061	Y
S32A_D565_Opaque_Dither	libskia	8	2.8	0.014	Y
src_aligned	libc	8	2.3	0.005	Y
S32_opaque_D32_filter_DXDY	libskia	1	2.2	0.013	N
less_than_32_left	libc	7	1.7	0.013	Y
cached_aligned32	libc	9	1.5	0.004	Y
.plt	<many>	8	1.4	0.043	Y
memcpy	libc	8	1.2	0.003	Y
S32A_Opaque_BlitRow32	libskia	7	1.2	0.005	Y
ClampX_ClampY_filter_affine	libskia	4	1.1	0.015	Y
DiagonalInterpMC	libomx	1	1.1	0.054	N
blitRect	libskia	1	1.1	0.008	N
calc_sbr_synfilterbank_LC	libomx	1	1.1	0.034	N
inflate	libz	4	0.9	0.055	Y
. . .	. . .	. . .	. . .	. . .	. . .

GreenDroid: Projected Energy

Aggressive mobile application processor (45 nm, 1.5 GHz)	91	pJ/instr.
GreenDroid c-cores	8	pJ/instr.
GreenDroid c-cores + cold code (est.)	12	pJ/instr.

- GreenDroid c-cores use 11x less energy per instruction than an aggressive mobile application processor
- Including cold code, GreenDroid will still save ~7.5x energy

Project Status

- Completed
  - Automatic generation of c-cores from source code to place & route
  - Cycle- and energy-accurate simulation (post place & route)
  - Tiled lattice, placed and routed
  - FPGA emulation of c-cores and tiled lattice

- Ongoing work
  - Finish full system Android emulation for more accurate workload modeling
  - Finalize c-core selection based on full system Android workload model
  - Timing closure and tapeout

GreenDroid Conclusions

- The utilization wall forces us to change how we build hardware
- Conservation cores use dark silicon to attack the utilization wall
- GreenDroid will demonstrate the benefits of c-cores for mobile application processors
- We are developing a 45 nm tiled prototype at UCSD

GreenDroid: A Mobile Application Processor for a Future of Dark Silicon

Nathan Goulding, Jack Sampson, Ganesh Venkatesh,
Saturnino Garcia, Joe Auricchio, Jonathan Babb[+],
Michael B. Taylor, and Steven Swanson

Department of Computer Science and Engineering,
University of California, San Diego

[+] *CSAIL, Massachusetts Institute of Technology*

Backup Slides

Automated Measurement Methodology

- C-core toolchain
  - Specification generator
  - Verilog generator
- Synopsys CAD flow
  - Design Compiler
  - IC Compiler
  - 45 nm library
- Simulation
  - Validated cycle-accurate c-core modules
  - Post-route gate-level simulation
- Power measurement
  - VCS + PrimeTime