Caches

Cache organization

Associativity

- **What if we could store data in any place in the cache?**
  - More complicated hardware = more power consumed and slower
- **So we *combine* two ideas:**
  - Each address maps to exactly one **set**
  - Each set can store block in more than one **way**



Cache Organization (3)



Example Placement

Example Placement

Block size (B)	16B
No of blocks (C/B)	8 blocks
Address (M)	16 bits

- Where would data from address 0x1833 be placed?
  - Binary: 0b 0001 1000 0011 0011

User for tag comparison I = $log_2(C/B/N)$ O = $log_2(B)$

M-bit address: | Tag (T) | Index (I) | Offset (O) |



Example Placement

Block size (B)	16B
No of blocks (C/B)	8 blocks
Address (M)	16 bits

- Where would data from address 0x1833 be placed?
  - Binary: 0b 0001 1000 0011 0011

User for tag comparison I = $log_2(C/B/N)$ O = $log_2(B)$

M-bit address: | Tag (T) | Index (I) | Offset (O) |



Example Placement

Block size	16B
No of blocks (C/B)	8 blocks
Address	16 bits

- Where would data from address 0x1833 be placed?
  - Binary: 0b 0001 1000 0011 0011



Block Replacement

- Any *empty* block in the correct set may be used to store block
- If there are no empty blocks, which one should we replace?
  - No choice for direct-mapped caches
  - Caches typically use something close to ***least recently used (LRU)*** (hardware usually implements "*not most recently used*")



General Cache Organisation `(S, N, B)`



Cache Read



Example: Direct-Mapped Cache ($N = 1$)

Direct-mapped: One line/block per set
Block size B = 8 bytes



Direct-mapped: One line/block per set
Block size B = 8 bytes



Direct-mapped: One line/block per set
Block size B = 8 bytes



No match?

- Then old line gets evicted and replaced

Example: Set-Associative Cache ($N = 2$)







No match?

- One line in set is selected for eviction and replacement
- Replacement policies: random, least frequency used (LFU), least recently used (LRU), …

Types of Cache Misses: 3 C's!

- **Compulsory** (cold) miss:
  - Occurs on first access to a block
- **Conflict** miss:
  - Conflict misses occur when the cache is large enough, but multiple data objects all map to the same slot.
    - E.g., referencing blocks 0, 8, 0, 8, … could miss every time
  - Direct-mapped caches have more conflict misses than N-way set-associative
- **Capacity** miss:
  - Occurs when the set of active cache blocks (the **working set**) is larger than the cache
  - Note: Fully-associative only has Compulsory and Capacity misses

What to do on a write hit?

- **Multiple copies of data exist. What is the problem with that?**
- **Write-through**
  - Write immediately to memory and all caches in between
  - Memory is always consistent with the cache copy
  - Slow: what if the same value (or line!) is written several times
- **Write-back**
  - Defer write to memory until line is evicted (replaced)
  - Need a dirty bit
    - Indicates line is different from memory
  - Higher performance (but more complex)

What to do on a write-miss?

- **Write-allocate** (load into cache, update line in cache)
  - Good if more writes to the location follow
  - More complex to implement
  - May evict an existing value
  - Common with write-back caches
- **No-write-allocate** (writes immediately to memory)
  - Simpler to implement
  - Slower code (bad if value consistently re-read)
  - Seen with write-through caches

Real caches: Intel Core i7-5960X (Haswell)

- **All caches have a block/line size of 64 bytes**
- **L1 i-cache and d-cache:**
  - 32 KiB, 8-way set-associative
  - i-cache: no writes, d-cache: write-back
  - Access: 4 cycles
- **L2 unified cache:**
  - 256 KiB, 8-way set-associative
  - private, write-back
  - Access: 11 cycles
- **L3 unified cache:** (shared among multiple cores)
  - 8 MiB, 16-way set-associative
  - shared, write-back
  - Access: 30-40 cycles

Slower, but more likely to hit

Software caches are more flexible

- **Examples:**
  - file system buffer caches, web browser caches, etc.
  - Content-delivery networks (CDN): cache for the internet (e.g., Netflix)

- **Some design differences:**
  - Almost always fully associative:
    - So, no placement restrictions
    - Index structures like hash tables are common
  - Often use complex replacement policies
    - Misses are very expensive when disk or network involved
    - Worth thousands of cycles to avoid them
  - Not necessarily constrained to single "block" transfers
    - May fetch or write-back in larger units, opportunistically

Program optimizations that consider caches

Optimizations for the memory hierarchy

- **Write code that has locality**
  - *Spatial*: access data contiguously
  - *Temporal*: make sure access to the same data is not too far apart in time
- **How to achieve this?**
  - Adjust memory access in *code* (software) to improve miss rate (MR)
    - Requires knowledge of *both* how caches work as well as your system's parameters
  - Proper choice of algorithm
  - Loop transformations

Example: Matrix Multiplication

```
/* Multiply n x n matrices a and b */
void mmm(double *a, double *b, double *c, int n) {
  int i, j, k;
  for (i = 0; i < n; i++) // move along rows of a
    for (j = 0; j < n; j++) // move along columns of b
       for (k = 0; k < n, k++)
         c[i*n + j] += a[i*n + k] * b[k*n + j];
}
```



Cache miss analysis

1. Read from `a(i,:)`
2. Read from `b(:,j)`

Ignoring matrix `c` for now

- **Assume:**
  - Square matrix ($n \times n$), elements are `doubles`
  - Cache block size B =64, 8 doubles in a block
  - Cache size C $\ll n$ (much smaller than n)
- **First iteration:**
  - $\frac{n}{8} + n = \frac{9n}{8}$ misses
  - Afterwards in cache: (schematic)
  - Total misses: $\frac{9n}{8} \times n^2 = \frac{9}{8}n^3$

Linear Algebra to the Rescue (1)

- Can get the same result of matrix multiplication by splitting the matrices into smaller submatrices (matrix "blocks")

- For example, multiply two 4×4 matrices:

$$A = \begin{bmatrix} a_{11} & a_{12} & a_{13} & a_{14} \\ a_{21} & a_{22} & a_{23} & a_{24} \\ a_{31} & a_{32} & a_{33} & a_{34} \\ a_{41} & a_{42} & a_{43} & a_{44} \end{bmatrix} = \begin{bmatrix} A_{11} & A_{12} \\ A_{21} & A_{22} \end{bmatrix}, \text{ with B defined similarly.}$$

$$AB = \begin{bmatrix} (A_{11}B_{11} + A_{12}B_{21}) & (A_{11}B_{12} + A_{12}B_{22}) \\ (A_{21}B_{11} + A_{22}B_{21}) & (A_{21}B_{12} + A_{22}B_{22}) \end{bmatrix}.$$

Linear Algebra to the Rescue (2)

C_{11}	C_{12}	C_{13}	C_{14}
C_{21}	C_{22}	C_{23}	C_{24}
C_{31}	C_{32}	C_{33}	C_{34}
C_{41}	C_{42}	C_{43}	C_{44}

A_{11}	A_{12}	A_{13}	A_{14}
A_{21}	A_{22}	A_{23}	A_{24}
A_{31}	A_{32}	A_{33}	A_{34}
A_{41}	A_{42}	A_{43}	A_{44}

B_{11}	B_{12}	B_{13}	B_{14}
B_{21}	B_{22}	B_{23}	B_{24}
B_{31}	B_{32}	B_{33}	B_{34}
B_{41}	B_{42}	B_{43}	B_{44}

- **Matrices of size $n \times n$, split into 4 blocks of size r $(n = 4r)$**

$$C_{22} = A_{21}B_{12} + A_{22}B_{22} + A_{23}B_{32} + A_{24}B_{42} = \sum_k A_{2k} \times B_{k2}$$

- **Multiplication operates on small "block" matrices**
  - Choose size so that they fit in the cache
  - This technique called "*cache blocking*"

Blocked Matrix Multiply

```
/* move by rxr BLOCKS now */
for (i = 0; i < n; i+=r)
  for (j = 0; j < n; j+=r)
    for (k = 0; k < n, k+=r)
      /* block matrix multiplication */
      for (ib = i; ib < i+r; ib++)
        for (jb = j; jb < j+r; jb++)
          for (kb = k; kb < k+r; kb++)
            c[ib*n + jb] += a[ib*n + kb] * b[kb*n + jb]
```

- **Blocked version of the naïve algorithm**
  - r = block matrix size (assume r divides n evenly)
- **6 nested loops may seem less efficient, but leads to a much faster code!!**

Cache Miss Analysis (Blocked)

- **Assume:**
  - Square matrix ($n \times n$), elements are `doubles`
  - Cache line size B =64 -> 8 elements in a cache line
  - Cache size C $\ll n$ (much smaller than n)
  - Three blocks ($r \times r$) fit into cache: $3r^2 < C$

r^2 elements per block, 8 blocks in cache

- **First (block) iteration:**
  - $\frac{r^2}{8}$ misses for each block
  - $\frac{2n}{r} \times \frac{r^2}{8} = \frac{nr}{4}$ (again omitting matrix c)

n/r blocks in row and column

  - Afterwards in cache (schematic):



8 doubles wide

- **Assume:**
  - Square matrix ($n \times n$), elements are `doubles`
  - Cache line size K =64 -> 8 doubles in a cache line
  - Cache size C $\ll n$ (much smaller than n)
  - Three blocks ($r \times r$) fit into cache: $3r^2 < C$
- **First (block) iteration:**
  - $\frac{r^2}{8}$ misses for each block
  - $\frac{2n}{r} \times \frac{r^2}{8} = \frac{nr}{4}$ (again omitting matrix c)
- **Total misses:**
  - $\frac{nr}{4} \times (\frac{n}{r})^2 = \frac{n^3}{(4r)}$.



Matrix Multiply Summary

- **Naïve:** $(9/8) \times n^3$
- **Blocked:** $1/(4r) \times n^3$
  - If $r = 8$, difference is $4 * 8 * \frac{9}{8} = 36$x
  - If $r = 16$, difference is $4 * 16 * \frac{9}{8} = 72$x
- **Blocking optimization only works if the blocks fit in the cache**
  - Suggests larger possible block size up to limit $3r^2 \leq C$
- **Matrix multiplication has inherent temporal locality:**
  - Input data: $3n^2$, computation $2n^3$
  - Every array element used $O(n)$ times!
  - But program has to be written properly

Cache-Friendly Code

- **Programmer can optimise for cache performance**
  - How data structures are organised
  - How data are accessed:
    - Nested loop structure
    - Blocking is a general technique
- **All systems favour "cache-friendly code"**
  - Getting absolute optimum performance is very platform specific
    - Cache sizes, cache block size, associativity, etc.
  - Can get most of the advantage with generic code:
    - Keep working set reasonably small (temporal locality)
    - Use small strides (spatial locality)
    - Focus on inner loop cycle

Learn About Your Machine

```
wmic memcache get MaxCacheSize
```

Modern processor specs: http://www.7-cpu.com/

The Memory Mountain