# i.MX8 SHE API

Revision\_1.0

Generated by Doxygen 1.8.11

ii CONTENTS

# Contents

	ЭПЕ	: API	'
2	Revi	ision History	1
3	Gen	eral concepts related to the API	2
	3.1	Session	2
4	Mod	lule Index	2
	4.1	Modules	2
5	Mod	lule Documentation	3
	5.1	Error codes	3
		5.1.1 Detailed Description	3
		5.1.2 Enumeration Type Documentation	3
	5.2	SHE keys	4
		5.2.1 Detailed Description	4
	5.3	SHE+ key extension	5
		5.3.1 Detailed Description	5
	5.4	Key store provisioning	6
		5.4.1 Detailed Description	6
		5.4.2 Function Documentation	6
	5.5	Session	8
		5.5.1 Detailed Description	8
		5.5.2 Function Documentation	8
	5.6	SHE commands	9
		5.6.1 Detailed Description	9
	5.7	CMD_GENERATE_MAC	10
		5.7.1 Detailed Description	10
		5.7.2 Function Documentation	10
	5.8	CMD_VERIFY_MAC	11
		5.8.1 Detailed Description	11

	5.8.2	Function Documentation		11
5.9	CMD_E	ENC_CBC		12
	5.9.1	Detailed Description		12
	5.9.2	Function Documentation		12
5.10	CMD_D	DEC_CBC		13
	5.10.1	Detailed Description		13
	5.10.2	Function Documentation		13
5.11	CMD_E	ENC_ECB		14
	5.11.1	Detailed Description		14
	5.11.2	Function Documentation		14
5.12	CMD_D	DEC_ECB		15
	5.12.1	Detailed Description		15
	5.12.2	Function Documentation		15
5.13	CMD_L	OAD_KEY		16
	5.13.1	Detailed Description		16
	5.13.2	Function Documentation		16
5.14	CMD_L	OAD_PLAIN_KEY		17
	5.14.1	Detailed Description		17
	5.14.2	Function Documentation		17
5.15	CMD_E	EXPORT_RAM_KEY	. •	18
	5.15.1	Detailed Description	. •	18
	5.15.2	Function Documentation		18
5.16	CMD_IN	NIT_RNG		19
	5.16.1	Detailed Description		19
	5.16.2	Function Documentation	. •	19
5.17	CMD_E	EXTEND_SEED	. 2	20
	5.17.1	Detailed Description	. 2	20
	5.17.2	Function Documentation	. 2	20
5.18	CMD_R	RND	. 2	21
	5.18.1	Detailed Description	. 2	21

2 Revision History

	5.18.2 Function Documentation	21
5.19	CMD_GET_STATUS	22
	5.19.1 Detailed Description	22
	5.19.2 Function Documentation	22
5.20	CMD_GET_ID	23
	5.20.1 Detailed Description	23
	5.20.2 Function Documentation	23
5.21	CMD_CANCEL	24
	5.21.1 Detailed Description	24
	5.21.2 Function Documentation	24
5.22	last rating code	25
	5.22.1 Detailed Description	25
	5.22.2 Function Documentation	25
5.23	Get info	26
	5.23.1 Detailed Description	26
	5.23.2 Function Documentation	26
5.24	OS porting guide	27
	5.24.1 Detailed Description	27
	5.24.2 Data Structure Documentation	28
	5.24.3 Function Documentation	28
Index		35
		-55

## 1 SHE API

This document is a software referece description of the API provided by the i.MX8 SHE solutions.

# 2 Revision History

Revision	date	description
0.5	Mai 03 2019	first draf
1.0	June 28 2019	complete functions definition

## 3 General concepts related to the API

## 3.1 Session

The API must be initialized by a potential requestor by opening a session.

The session establishes a route (MU, DomainID...) between the requester and the SHE module, and grants the usage of a specified key store. When a session is opened, the SHE module returns a handle identifying the session to the requester.

## 4 Module Index

#### 4.1 Modules

Here is a list of all modules:

Error codes	•
SHE keys	4
SHE+ key extension	5
Key store provisioning	6
Session	8
SHE commands	9
CMD_GENERATE_MAC	10
CMD_VERIFY_MAC	11
CMD_ENC_CBC	12
CMD_DEC_CBC	13
CMD_ENC_ECB	14
CMD_DEC_ECB	15
CMD_LOAD_KEY	16
CMD_LOAD_PLAIN_KEY	17
CMD_EXPORT_RAM_KEY	18
CMD_INIT_RNG	19
CMD_EXTEND_SEED	20
CMD_RND	21
CMD_GET_STATUS	22
CMD_GET_ID	23
CMD_CANCEL	24

5 Module Documentation 3

26 27
27

## 5.2 SHE keys

#### Macros

- #define **SHE\_KEY\_1** (0x04)
- #define **SHE\_KEY\_2** (0x05)
- #define **SHE\_KEY\_3** (0x06)
- #define **SHE\_KEY\_4** (0x07)
- #define **SHE\_KEY\_5** (0x08)
- #define SHE\_KEY\_6 (0x09)
- #define SHE\_KEY\_7 (0x0a)
- #define SHE\_KEY\_8 (0x0b)
- #define SHE\_KEY\_9 (0x0c)
- #define SHE\_KEY\_10 (0x0d)
- #define SHE\_RAM\_KEY (0x0e)

## 5.2.1 Detailed Description

Identifiers for SHE keys.

## 5.3 SHE+ key extension

```
Macros
```

```
#define SHE_KEY_DEFAULT (0x00)
no key extension: keys from 0 to 10 as defined in SHE specification.
#define SHE_KEY_N_EXT_1 (0x10)
keys 11 to 20.
#define SHE_KEY_N_EXT_2 (0x20)
keys 21 to 30.
#define SHE_KEY_N_EXT_3 (0x30)
keys 31 to 40.
#define SHE_KEY_N_EXT_4 (0x40)
keys 41 to 50.
```

## 5.3.1 Detailed Description

Identifiers for the SHE key extension.

## 5.4 Key store provisioning

#### Macros

• #define SHE STORAGE CREATE SUCCESS Ou

New storage created succesfully.

• #define SHE\_STORAGE\_CREATE\_WARNING 1u

New storage created but its usage is restricted to a limited security state of the chip.

• #define SHE\_STORAGE\_CREATE\_UNAUTHORIZED 2u

Creation of the storage is not authorized.

• #define SHE\_STORAGE\_CREATE\_FAIL 3u

Creation of the storage failed for any other reason.

• #define SHE\_STORAGE\_NUMBER\_UPDATES\_DEFAULT 300u

default number of maximum number of updated for SHE storage.

#### **Functions**

uint32\_t she\_storage\_create (uint32\_t key\_storage\_identifier, uint32\_t authentication\_nonce, uint16\_t max
 —updates\_number, uint8\_t \*signed\_message, uint32\_t msg\_len)

## 5.4.1 Detailed Description

#### 5.4.2 Function Documentation

5.4.2.1 uint32\_t she\_storage\_create ( uint32\_t key\_storage\_identifier, uint32\_t authentication\_nonce, uint16\_t max\_updates\_number, uint8\_t \* signed\_message, uint32\_t msg\_len )

Creates an empty SHE storage.

Must be called at least once on every device before using any other SHE API.

A signed message must be provided to replace an existing key store. This message is not necessary under some conditions related to chip's lifecycle.

## **Parameters**

key_storage_identifier	key store identifier
authentication_nonce	user defined nonce to be used as authentication proof for accesing the key store.
max_updates_number	maximum number of updates authorized on this new storage.  This parameter has the goal to limit the occupation of the monotonic counter used as anti-rollback protection.  If the maximum number of updates is reached, SHE still allows key store updates but without updating the monotonic counter giving the opportunity for rollback attacks.  Always forced to 300 in the current release.
signed_message	pointer to a signed message authorizing the operation (NULL if no signed message to be used)
msg_len	length in bytes of the signed message

Returns

## 5.5 Session

#### **Functions**

• struct she\_hdl\_s \* she\_open\_session (uint32\_t key\_storage\_identifier, uint32\_t authentication\_nonce, void(\*async\_cb)(void \*priv, she\_err\_t err), void \*priv)

• void she close session (struct she hdl s \*hdl)

#### 5.5.1 Detailed Description

#### 5.5.2 Function Documentation

5.5.2.1 struct she\_hdl\_s\* she\_open\_session ( uint32\_t key\_storage\_identifier, uint32\_t authentication\_nonce, void(\*)(void \*priv, she\_err\_t err) async\_cb, void \* priv )

Initiate a SHE session. The returned session handle pointer is typed with the struct "she\_hdl\_s". The user doesn't need to know or to access the fields of this struct.

It only needs to store this pointer and pass it to every calls to other APIs within the same SHE session.

Note that asynchronous API is currently not supported. async\_cb and priv pointers must be set to NULL.

#### **Parameters**

key_storage_identifier	key store identifier
authentication_nonce	user defined nonce used as authentication proof for accesing the key store
async_cb	user callback to be called on completion of a SHE operation
priv	user pointer to be passed to the callback

#### Returns

pointer to the session handle.

5.5.2.2 void she\_close\_session ( struct she\_hdl\_s \* hdl )

Terminate a previously opened SHE session

#### **Parameters**

hdl pointer to the session handler to be closed.

5.6 SHE commands 9

## 5.6 SHE commands

## Modules

- CMD\_GENERATE\_MAC
- CMD\_VERIFY\_MAC
- CMD\_ENC\_CBC
- CMD\_DEC\_CBC
- CMD\_ENC\_ECB
- CMD\_DEC\_ECB
- CMD\_LOAD\_KEY
- CMD\_LOAD\_PLAIN\_KEY
- CMD\_EXPORT\_RAM\_KEY
- CMD\_INIT\_RNG
- CMD\_EXTEND\_SEED
- CMD\_RND
- CMD\_GET\_STATUS
- CMD\_GET\_ID
- CMD\_CANCEL
- · last rating code

## 5.6.1 Detailed Description

## 5.7 CMD\_GENERATE\_MAC

#### Macros

#define SHE\_MAC\_SIZE 16u
 size of the MAC generated is 128bits.

## **Functions**

• she\_err\_t she\_cmd\_generate\_mac (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint16\_← t message\_length, uint8\_t \*message, uint8\_t \*mac)

## 5.7.1 Detailed Description

#### 5.7.2 Function Documentation

5.7.2.1 she\_err\_t she\_cmd\_generate\_mac ( struct she\_hdl\_s \* hdl, uint8\_t key\_ext, uint8\_t key\_id, uint16\_t message\_length, uint8\_t \* message, uint8\_t \* mac )

Generates a MAC of a given message with the help of a key identified by key\_id.

## **Parameters**

hdl	pointer to the SHE session handler
key_ext	identifier of the key extension to be used for the operation
key_id	identifier of the key to be used for the operation
message_length	lenght in bytes of the input message. The message is padded to be a multiple of 128 bits by SHE.
message	pointer to the message to be processed
mac	pointer to where the output MAC should be written (128bits should be allocated there)

## Returns

## 5.8 CMD\_VERIFY\_MAC

#### Macros

- #define SHE\_MAC\_VERIFICATION\_SUCCESS 0u
  - indication of mac verification success
- #define SHE\_MAC\_VERIFICATION\_FAILED 1u

indication of mac verification failure

#### **Functions**

she\_err\_t she\_cmd\_verify\_mac (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint16\_t message\_
 length, uint8\_t \*message, uint8\_t \*mac, uint8\_t mac\_length, uint8\_t \*verification\_status)

#### 5.8.1 Detailed Description

- 5.8.2 Function Documentation
- 5.8.2.1 she\_err\_t she\_cmd\_verify\_mac ( struct she\_hdl\_s \* hdl, uint8\_t key\_ext, uint8\_t key\_id, uint16\_t message\_length, uint8\_t \* message, uint8\_t \* mac, uint8\_t \* mac, uint8\_t \* verification\_status )

Verifies the MAC of a given message with the help of a key identified by key\_id.

#### **Parameters**

hdl	pointer to the SHE session handler
key_ext	identifier of the key extension to be used for the operation
key_id	identifier of the key to be used for the operation
message_length	lenght in bytes of the input message. The message is padded to be a multiple of 128 bits by SHE.
message	pointer to the message to be processed
mac	pointer to the MAC to be compared (implicitely 128 bits)
mac_length	number of bytes to compare (must be at least 4)
verification_status	pointer to where write the result of the MAC comparison

## Returns

## 5.9 CMD\_ENC\_CBC

#### Macros

#define SHE\_AES\_BLOCK\_SIZE\_128 16u
 size in bytes of a 128bits CBC block

## **Functions**

• she\_err\_t she\_cmd\_enc\_cbc (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint32\_t data\_length, uint8\_t \*iv, uint8\_t \*plaintext, uint8\_t \*ciphertext)

## 5.9.1 Detailed Description

#### 5.9.2 Function Documentation

5.9.2.1 she\_err\_t she\_cmd\_enc\_cbc ( struct she\_hdl\_s \* hdl, uint8\_t key\_ext, uint8\_t key\_id, uint32\_t data\_length, uint8\_t \* iv, uint8\_t \* plaintext, uint8\_t \* ciphertext )

CBC encryption of a given plaintext with the key identified by key\_id.

## **Parameters**

hdl	pointer to the SHE session handler
key_ext	identifier of the key extension to be used for the operation
key_id	identifier of the key to be used for the operation
data_length	lenght in bytes of the plaintext and the cyphertext. Must be a multiple of 128bits.
iv	pointer to the 128bits IV to use for the encryption.
plaintext	pointer to the message to be encrypted.
ciphertext	pointer to ciphertext output area.

#### Returns

5.10 CMD DEC CBC

## 5.10 CMD\_DEC\_CBC

#### **Functions**

• she\_err\_t she\_cmd\_dec\_cbc (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint32\_t data\_length, uint8\_t \*iv, uint8\_t \*ciphertext, uint8\_t \*plaintext)

## 5.10.1 Detailed Description

#### 5.10.2 Function Documentation

5.10.2.1 she\_err\_t she\_cmd\_dec\_cbc ( struct she\_hdl\_s \* hdl, uint8\_t key\_ext, uint8\_t key\_id, uint32\_t data\_length, uint8\_t \* iv, uint8\_t \* ciphertext, uint8\_t \* plaintext)

CBC decryption of a given ciphertext with the key identified by key\_id.

#### **Parameters**

hdl	pointer to the SHE session handler
key_ext	identifier of the key extension to be used for the operation
key_id	identifier of the key to be used for the operation
data_length	lenght in bytes of the plaintext and the cyphertext. Must be a multiple of 128bits.
iv	pointer to the 128bits IV to use for the decryption.
ciphertext	pointer to ciphertext to be decrypted.
plaintext	pointer to the plaintext output area.

## Returns

## 5.11 CMD\_ENC\_ECB

## **Functions**

• she\_err\_t she\_cmd\_enc\_ecb (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint8\_t \*plaintext, uint8\_t \*ciphertext)

## 5.11.1 Detailed Description

#### 5.11.2 Function Documentation

5.11.2.1 she\_err\_t she\_cmd\_enc\_ecb ( struct she\_hdl\_s \* hdl, uint8\_t key\_ext, uint8\_t key\_id, uint8\_t \* plaintext, uint8\_t \* ciphertext )

ECB encryption of a given plaintext with the key identified by key\_id.

#### **Parameters**

hdl	pointer to the SHE session handler	
key_ext	identifier of the key extension to be used for the operation	
key_id	identifier of the key to be used for the operation	
plaintext	pointer to the 128bits message to be encrypted.	
ciphertext	pointer to ciphertext output area (128bits).	

## Returns

5.12 CMD DEC ECB

## 5.12 CMD\_DEC\_ECB

#### **Functions**

• she\_err\_t she\_cmd\_dec\_ecb (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint8\_t \*ciphertext, uint8\_t \*plaintext)

## 5.12.1 Detailed Description

#### 5.12.2 Function Documentation

5.12.2.1 she\_err\_t she\_cmd\_dec\_ecb ( struct she\_hdl\_s \* hdl, uint8\_t key\_ext, uint8\_t key\_id, uint8\_t \* ciphertext, uint8\_t \* plaintext )

ECB decryption of a given ciphertext with the key identified by key\_id.

#### **Parameters**

hdl	pointer to the SHE session handler	
key_ext	identifier of the key extension to be used for the operation	
key_id	identifier of the key to be used for the operation	
ciphertext	ciphertext pointer to 128bits ciphertext to be decrypted.	
plaintext pointer to the plaintext output area (128bits).		

## Returns

## 5.13 CMD\_LOAD\_KEY

#### Macros

#define SHE\_KEY\_SIZE 16u
 SHE keys are 128 bits (16 bytes) long.

## **Functions**

• she\_err\_t she\_cmd\_load\_key (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint8\_t \*m1, uint8\_t \*m2, uint8\_t \*m3, uint8\_t \*m4, uint8\_t \*m5)

## 5.13.1 Detailed Description

#### 5.13.2 Function Documentation

5.13.2.1 she\_err\_t she\_cmd\_load\_key ( struct she\_hdl\_s \* hdl, uint8\_t key\_ext, uint8\_t key\_id, uint8\_t \* m1, uint8\_t \* m2, uint8\_t \* m3, uint8\_t \* m4, uint8\_t \* m5 )

Update an internal key of SHE with the protocol specified by SHE.

## **Parameters**

hdl	pointer to the SHE session handler	
key_ext	identifier of the key extension to be used for the operation	
key_id	identifier of the key to be used for the operation	
m1	pointer to M1 message - 128 bits	
m2	pointer to M2 message - 256 bits	
m3	pointer to M3 message - 128 bits	
m4	pointer to the output address for M4 message - 256 bits	
m5	pointer to the output address for M5 message - 128 bits	

#### Returns

## 5.14 CMD\_LOAD\_PLAIN\_KEY

## **Functions**

- she\_err\_t she\_cmd\_load\_plain\_key (struct she\_hdl\_s \*hdl, uint8\_t \*key)
- 5.14.1 Detailed Description
- 5.14.2 Function Documentation
- 5.14.2.1 she\_err\_t she\_cmd\_load\_plain\_key ( struct she\_hdl\_s \* hdl, uint8\_t \* key )

Load a key as plaintext to the RAM\_KEY slot without encryption and verification.

## **Parameters**

hdl	pointer to the SHE session handler
key	pointer to the plaintext key to be loaded - 128bits

#### Returns

## 5.15 CMD\_EXPORT\_RAM\_KEY

#### **Functions**

• she\_err\_t she\_cmd\_export\_ram\_key (struct she\_hdl\_s \*hdl, uint8\_t \*m1, uint8\_t \*m2, uint8\_t \*m3, uint8\_t \*m4, uint8\_t \*m5)

- 5.15.1 Detailed Description
- 5.15.2 Function Documentation
- 5.15.2.1 she\_err\_t she\_cmd\_export\_ram\_key ( struct she\_hdl\_s \* hdl, uint8\_t \* m1, uint8\_t \* m2, uint8\_t \* m3, uint8\_t \* m4, uint8\_t \* m5 )

exports the RAM\_KEY into a format protected by SECRET\_KEY.

#### **Parameters**

hdl	pointer to the SHE session handler
m1	pointer to the output address for M1 message - 128 bits
m2	pointer to the output address for M2 message - 256 bits
m3	pointer to the output address for M3 message - 128 bits
m4	pointer to the output address for M4 message - 256 bits
m5	pointer to the output address for M5 message - 128 bits

## Returns

5.16 CMD INIT RNG 19

## 5.16 CMD\_INIT\_RNG

#### **Functions**

• she\_err\_t she\_cmd\_init\_rng (struct she\_hdl\_s \*hdl)

5.16.1 Detailed Description

5.16.2 Function Documentation

5.16.2.1 she\_err\_t she\_cmd\_init\_rng ( struct she\_hdl\_s \* hdl )

initializes the seed and derives a key for the PRNG. The function must be called before CMD\_RND after every power cycle/reset.

#### **Parameters**

hdl pointer to the SHE session handler

#### Returns

## 5.17 CMD\_EXTEND\_SEED

#### Macros

• #define SHE\_ENTROPY\_SIZE 16u

#### **Functions**

• she\_err\_t she\_cmd\_extend\_seed (struct she\_hdl\_s \*hdl, uint8\_t \*entropy)

## 5.17.1 Detailed Description

5.17.2 Function Documentation

5.17.2.1 she\_err\_t she\_cmd\_extend\_seed ( struct she\_hdl\_s \* hdl, uint8\_t \* entropy )

extends the seed of the PRNG by compressing the former seed value and the supplied entropy into a new seed which will be used to generate the following random numbers. The random number generator has to be initialized by CMD\_INIT\_RNG before the seed can be extended.

#### **Parameters**

hdl	pointer to the SHE session handler	
entropy	pointer to the entropy vector (128bits) to use for the operation	

## Returns

5.18 CMD RND 21

## 5.18 CMD\_RND

Macros

• #define SHE\_RND\_SIZE 16u

#### **Functions**

• she\_err\_t she\_cmd\_rnd (struct she\_hdl\_s \*hdl, uint8\_t \*rnd)

5.18.1 Detailed Description

5.18.2 Function Documentation

5.18.2.1 she\_err\_t she\_cmd\_rnd ( struct she\_hdl\_s \* hdl, uint8\_t \* rnd )

returns a vector of 128 random bits. The random number generator has to be initialized by CMD\_INIT\_RNG before random numbers can be supplied.

#### **Parameters**

hdl	pointer to the SHE session handler
rnd	pointer to the output address for the generated 128bits random vector

## Returns

## 5.19 CMD\_GET\_STATUS

## **Functions**

• she\_err\_t she\_cmd\_get\_status (struct she\_hdl\_s \*hdl, uint8\_t \*sreg)

5.19.1 Detailed Description

5.19.2 Function Documentation

5.19.2.1 she\_err\_t she\_cmd\_get\_status ( struct she\_hdl\_s \* hdl, uint8\_t \* sreg )

returns the content of the status register

## Parameters

hdl	pointer to the SHE session handler
sreg	pointer to the output address for status register(8bits)

## Returns

5.20 CMD GET ID 23

## 5.20 CMD\_GET\_ID

#### Macros

- #define SHE\_CHALLENGE\_SIZE 16u /\* 128 bits \*/
- #define **SHE\_ID\_SIZE** 15u /\* 120 bits \*/

## **Functions**

she\_err\_t she\_cmd\_get\_id (struct she\_hdl\_s \*hdl, uint8\_t \*challenge, uint8\_t \*id, uint8\_t \*sreg, uint8\_←
t \*mac)

## 5.20.1 Detailed Description

## 5.20.2 Function Documentation

5.20.2.1 she\_err\_t she\_cmd\_get\_id ( struct she\_hdl\_s \* hdl, uint8\_t \* challenge, uint8\_t \* id, uint8\_t \* sreg, uint8\_t \* mac )

returns the identity (UID) and the value of the status register protected by a MAC over a challenge and the data.

#### **Parameters**

hdl	pointer to the SHE session handler	
challenge	pointer to the challenge vector (128bits)	
id	pointer to the output address for the identity (120bits)	
sreg	pointer to the output address for status register(8bits)	
mac	pointer to the output address for the computed MAC (128bits)	

#### Returns

## 5.21 CMD\_CANCEL

## **Functions**

• she\_err\_t she\_cmd\_cancel (struct she\_hdl\_s \*hdl)

5.21.1 Detailed Description

5.21.2 Function Documentation

5.21.2.1 she\_err\_t she\_cmd\_cancel ( struct she\_hdl\_s \* hdl )

interrupt any given function and discard all calculations and results.

## **Parameters**

hdl pointer to the SHE session handler

#### Returns

5.22 last rating code 25

## 5.22 last rating code

#### **Functions**

uint32\_t she\_get\_last\_rating\_code (struct she\_hdl\_s \*hdl)

5.22.1 Detailed Description

5.22.2 Function Documentation

5.22.2.1 uint32\_t she\_get\_last\_rating\_code ( struct she\_hdl\_s \* hdl )

Report rating code from last command

SHE API defines standard errors that should be returned by API calls. Error code reported by SECO are "translated" to these SHE error codes. This API allow user to get the error code reported by SECO for the last command before its translation to SHE error codes. This should be used for debug purpose only.

#### **Parameters**

hdl pointer to the SHE session handler

## Returns

rating code reported by last command

## 5.23 Get info

#### **Functions**

• she\_err\_t she\_get\_info (struct she\_hdl\_s \*hdl, uint32\_t \*user\_sab\_id, uint8\_t \*chip\_unique\_id, uint16\_ t \*chip\_monotonic\_counter, uint16\_t \*chip\_life\_cycle, uint32\_t \*she\_version)

## 5.23.1 Detailed Description

Get miscellaneous information. This function return, among others, all the information needed to build a valid signed message.

#### 5.23.2 Function Documentation

5.23.2.1 she\_err\_t she\_get\_info ( struct she\_hdl\_s \* hdl, uint32\_t \* user\_sab\_id, uint8\_t \* chip\_unique\_id, uint16\_t \* chip\_monotonic\_counter, uint16\_t \* chip\_life\_cycle, uint32\_t \* she\_version )

#### **Parameters**

hdl	pointer to the SHE session handler
user_sab_id	pointer to the output address for the user identity (32bits)
chip_unique_id	pointer to the output address for the chip unique identifier (64bits)
chip_monotonic_counter	pointer to the output address for the chip monotonic counter value (16bits)
chip_life_cycle	pointer to the output address for the chip current life cycle (16bits)
she_version	pointer to the output address for the SHE module version (32bits)

## Returns

## 5.24 OS porting guide

#### **Data Structures**

· struct seco\_mu\_params

#### Macros

- #define MU\_CHANNEL\_UNDEF (0x00u)
- #define MU\_CHANNEL\_SHE (0x01u)
- #define MU CHANNEL SHE NVM (0x02u)
- #define MU\_CHANNEL\_HSM (0x03u)
- #define MU\_CHANNEL\_HSM\_NVM (0x04u)
- #define DATA BUF IS INPUT 0x01u
- #define DATA BUF USE SEC MEM 0x02u
- #define DATA\_BUF\_SHORT\_ADDR 0x04u
- #define SEC MEM SHORT ADDR MASK 0xFFFFu

#### **Functions**

- struct seco\_os\_abs\_hdl \* seco\_os\_abs\_open\_mu\_channel (uint32\_t type, struct seco\_mu\_params \*mu
   —params)
- void seco\_os\_abs\_close\_session (struct seco\_os\_abs\_hdl \*phdl)
- int32\_t seco\_os\_abs\_send\_mu\_message (struct seco\_os\_abs\_hdl \*phdl, uint32\_t \*message, uint32\_t size)
- int32\_t seco\_os\_abs\_read\_mu\_message (struct seco\_os\_abs\_hdl \*phdl, uint32\_t \*message, uint32\_t size)
- int32\_t seco\_os\_abs\_configure\_shared\_buf (struct seco\_os\_abs\_hdl \*phdl, uint32\_t shared\_buf\_off, uint32\_t size)
- uint64 t seco os abs data buf (struct seco os abs hdl \*phdl, uint8 t \*src, uint32 t size, uint32 t flags)
- uint32\_t seco\_os\_abs\_crc (uint8\_t \*data, uint32\_t size)
- void seco os abs memset (uint8 t \*dst, uint8 t val, uint32 t len)
- void seco\_os\_abs\_memcpy (uint8\_t \*dst, uint8\_t \*src, uint32\_t len)
- uint8\_t \* seco\_os\_abs\_malloc (uint32\_t size)
- void seco\_os\_abs\_free (void \*ptr)
- int32\_t seco\_os\_abs\_storage\_write (struct seco\_os\_abs\_hdl \*phdl, uint8\_t \*src, uint32\_t size)
- int32 t seco os abs storage read (struct seco os abs hdl \*phdl, uint8 t \*dst, uint32 t size)
- void seco\_os\_abs\_start\_system\_rng (struct seco\_os\_abs\_hdl \*phdl)
- int32\_t seco\_os\_abs\_send\_signed\_message (struct seco\_os\_abs\_hdl \*phdl, uint8\_t \*signed\_message, uint32\_t msg\_len)

#### 5.24.1 Detailed Description

seco\_libs code itseld is independent from any OS or platform. This abstraction layer defines the functions that should be implemented on a specific OS or platform when porting seco\_libs on it.

#### 5.24.2 Data Structure Documentation

#### 5.24.2.1 struct seco\_mu\_params

Opens a MU channel Purpose of this function is to setup a communication channel using a messaging unit (MU) between the caller of this function and SECO. This session is uniquely identified by a platform handle. The pointer to this handle is returned here and has to be provided by the user on each call to platform dependent functions. The details of the seco\_os\_abs\_hdl structure are not described in this API so it can be custmized for each OS/platform porting.

One physical MU can be shared between several sessions but concurrent access should be protected. Seco can only process one command at a time. Once a command has been sent to SECO no other command should be sent on the physical MU (even by other sessions sharing same physical MU) until the response has been received. (but a response to a command from Seco should not be blocked - e.g. in storage case)

The mapping between physical MUs and sessions is considered as platform dependent. So no assumption are made about this by the caller.

#### **Parameters**

type	constant indicating for which purpose will be used this channel (see defines below)
mu_params	pointer where the MU params for this channel should be written. It is up to this abstraction layer to provide a mapping between channel types and associated MU params. Caller need to know these information to fill some SECO messages.

#### Returns

pointer to the MU channel handle.

#### **Data Fields**

uint8←	mu_id	index of the MU as per SECO point of view.
_t		
uint8←	interrupt_idx	Interrupt number of the MU used to indicate data availability.
_t		
uint8←	tz	indicate if current partition has TZ enabled.
_t		
uint8←	did	DID of the calling partition.
_t		
uint8 <i>←</i>	priority	SECO priority associated to this MU.
_t		
uint8←	operating_mode	SECO operating mode associated to this MU.
_t		

#### 5.24.3 Function Documentation

5.24.3.1 void seco\_os\_abs\_close\_session ( struct seco\_os\_abs\_hdl \* phdl )

Close a previously opened session.

#### **Parameters**

5.24.3.2 int32\_t seco\_os\_abs\_send\_mu\_message ( struct seco\_os\_abs\_hdl \* phdl, uint32\_t \* message, uint32\_t size )

Send a message to Seco over a messaging unit.

A message is made of 1 or more 32bits words. The 1st word is an header containing the length of the message and its type (command or response) The following protocol has to be respected when sending a message to SECO:

- · write the header in TR0 of the MU
- send and interrupt to SECO thanks to GI0 bit in CR register of the MU
- Write other words of the message. word at index n in the message has to be written in TR[n%4] register of the MU. Write to a TRx register has to be performed only when the corresponding TEx bit in SR register is equal to 1 (indicating that the TRx register is empty).

Note that a physical MU can be shared between several sessions. Concurent access to the physical MU should be prevented (SECO process commands one by one). So this API should block until the physical MU is available for this session.

#### **Parameters**

phdl	pointer to handle identifying the session to be used to carry the message.
message	pointer to the message itself. It has to be aligned on 32bits.
size	size in bytes of the message. It has to be multiple of 4 bytes.

### Returns

length in bytes written to the MU or negative value in case of error

5.24.3.3 int32\_t seco\_os\_abs\_read\_mu\_message ( struct seco\_os\_abs\_hdl \* phdl, uint32\_t \* message, uint32\_t size )

Read a message from Seco over a messaging unit.

This API is blocking until a message is sent by SECO

A message is made of 1 or more 32bits words. The 1st word is an header containing the length of the message and its type (command or response)

When receiving MU's GI0 interrupt from SECO this API should:

- · read the header in RR0 of the MU and extract its length
- · send and interrupt to SECO thanks to GI0 bit in CR register of the MU
- Write other words of the message. word at index n in the message has to be written in TR[n%4] register of the MU. Write to a TRx register has to be performed only when the corresponding TEx bit in SR register is equal to 1 (indicating that the TRx register is empty).

Typically for SHE this API will be called right after having sent a command to SECO in order to get the response. And for Storage an infinite loop will wait on this blocking API for a command from SECO.

#### **Parameters**

phdl	pointer to handle identifying the session to be used to carry the message.
message	pointer to the message itself. It has to be aligned on 32bits.
size	size in bytes of the message. It has to be multiple of 4 bytes.

#### Returns

length in bytes read from the MU or negative value in case of error

5.24.3.4 int32\_t seco\_os\_abs\_configure\_shared\_buf ( struct seco\_os\_abs\_hdl \* phdl, uint32\_t shared\_buf\_off, uint32\_t size )

Configure the use of shared buffer in secure memory

Seco allocates a shared buffer in secure memory to exchange data. Offset in secure memory and size are provided by Seco in a message decoded by caller. These information are provided to the platform dependent layer through this API to avoid parsing incoming messages here.

#### **Parameters**

phdl	pointer to the session handle associated to this shared buffer.
shared_buf_offset	offset of the shared buffer in secure memory.
size	size in bytes of the allocated shared buffer.

#### Returns

0 in case of success. Any other value means error.

5.24.3.5 uint64 t seco os abs data buf ( struct seco os abs hdl \* phdl, uint8 t \* src, uint32 t size, uint32 t flags )

Setup data buffer for command processing

The command messages sent to Seco most of the time do not carry the data to be processed. It uses pointers instead. This API is used to make sure the data are available to Seco when it receive a command and also that the result can be accessed by the caller after seco sent the response by either:

- copy to/from dedicated shared buffer in secure memory
- or perform appropriate cache management when using buffers in DDR It also provides the address to be inserted into the message to be sent to Seco: either the physical address or the offset in the shared buffer (see options below) yo be used by Seco.

Several options are available to describe the buffers. DATA\_BUF\_IS\_INPUT: the buffer described here is input to the next command. Otherwise this is an output. DATA\_BUF\_USE\_SEC\_MEM: the data should be copied to the shared buffer in secure memory or the output will be stored by Seco in it. It is expected that the buffers will be allocated in a contiguous manner in this shared memory since some optimizations depend on this (fast MAC). If not set any other memory can be used (e.g. DDR). In this case this API should take care of cache coherency and access rights before Seco tries access the physical memory. when using secure mem. DATA\_BUF\_SHORT\_A DDR: (only possible when using secure memory) returns the offset in secure memory (16bits) instead of full 64bits address (used to reduce the size of some Seco messages).

Once this API has been called the buffers should no more be accessed by the caller until the command has been sent to Seco and its response has been received.

## **Parameters**

phdl	pointer to the session handle for which this data buffer is used.
src	pointer to the data if input or to the area where the output should be written.
size	size in bytes of the input data or max size of the output.
flags	data buffer options as described above. Interpreted as a bit-field.

## Returns

the address to be inserted in the message to Seco to indicate him this buffer.

```
5.24.3.6 uint32_t seco_os_abs_crc ( uint8_t * data, uint32_t size )
```

Compute the CRC of a buffer.

Used for basic check of integrity on the storage to avoid sending a corrupted blob to Seco. No strong security requirement here since Seco will perform more robust integrity check on the blob.

CRC computation is abstracted here in order to let the possibility to use some platform optimized library instead of re-implementing.

#### **Parameters**

	data	pointer to the data on which the CRC must be computed. size in bytes of the data	
--	------	--	--

### Returns

32bits value of the CRC.

5.24.3.7 void seco\_os\_abs\_memset ( uint8\_t \* dst, uint8\_t val, uint32\_t len )

Force all bytes of a buffer to a given value.

### **Parameters**

dst	address of the buffer to be overwriten
val	value to be written in every bytes of the buffer
len	number of bytes to be written

5.24.3.8 void seco\_os\_abs\_memcpy ( uint8\_t \* dst, uint8\_t \* src, uint32\_t len )

Copy the content of a buffer to another location.

#### **Parameters**

dst	pointer to the destination buffer where data should be copied
src	pointer to the source buffer from where data should be copied
len	number of bytes to be copied

5.24.3.9 uint8\_t\* seco\_os\_abs\_malloc ( uint32\_t size )

Dynamically allocate memory.

#### **Parameters**

size	number of bytes to be allocated
------	---------------------------------

## Returns

pointer to the allocated buffer or NULL in case of error.

5.24.3.10 void seco\_os\_abs\_free ( void \* ptr )

Free a previously allocated buffer.

#### **Parameters**

5.24.3.11 int32\_t seco\_os\_abs\_storage\_write ( struct seco\_os\_abs\_hdl \* phdl, uint8\_t \* src, uint32\_t size )

Write data to the non volatile storage.

#### **Parameters**

phdl	pointer to the session handle for which this data buffer is used.
src	pointer to the data to be written to storage.
size	number of bytes to be written.

## Returns

number of bytes written.

5.24.3.12 int32\_t seco\_os\_abs\_storage\_read ( struct seco\_os\_abs\_hdl \* phdl, uint8\_t \* dst, uint32\_t size )

Read data from the non volatile storage.

#### **Parameters**

phdl	pointer to the session handle for which this data buffer is used.
dst	pointer to the data where data read from the storage should be copied.
size	number of bytes to be read.

## Returns

number of bytes read.

5.24.3.13 void seco\_os\_abs\_start\_system\_rng ( struct seco\_os\_abs\_hdl \* phdl )

Start the RNG from a system point of view.

Start the RNG HW through a SCU RPC: sc\_seco\_start\_rng()

#### **Parameters**

phdl	pointer to the session handle for which this data buffer is used.
------	---

5.24.3.14 int32\_t seco\_os\_abs\_send\_signed\_message ( struct seco\_os\_abs\_hdl \* phdl, uint8\_t \* signed\_message, uint32\_t msg\_len )

Send a signed message to SECO through dedicated SCU RPC

Purpose is to unlock the creation of a storage in some specific cases.

#### **Parameters**

signed_message	pointer to the signed message.
msg_len	length of the signed message

# Index

CMD_CANCEL, 24	ERC_SEQUENCE_ERROR
she cmd cancel, 24	Error codes, 3
CMD DEC CBC, 13	Error codes, 3
she_cmd_dec_cbc, 13	ERC_BUSY, 3
CMD_DEC_ECB, 15	ERC_GENERAL_ERROR, 3
she_cmd_dec_ecb, 15	ERC_KEY_EMPTY, 3
CMD ENC CBC, 12	ERC KEY INVALID, 3
she_cmd_enc_cbc, 12	ERC_KEY_NOT_AVAILABLE, 3
CMD_ENC_ECB, 14	ERC_KEY_UPDATE_ERROR, 3
she_cmd_enc_ecb, 14	ERC KEY WRITE PROTECTED, 3
CMD_EXPORT_RAM_KEY, 18	ERC MEMORY FAILURE, 3
she_cmd_export_ram_key, 18	ERC NO DEBUGGING, 3
CMD_EXTEND_SEED, 20	ERC_NO_ERROR, 3
she_cmd_extend_seed, 20	ERC_NO_SECURE_BOOT, 3
CMD_GENERATE_MAC, 10	ERC_RNG_SEED, 3
she_cmd_generate_mac, 10	ERC_SEQUENCE_ERROR, 3
CMD GET ID, 23	she_err_t, 3
she_cmd_get_id, 23	o.no_o.n, o
CMD_GET_STATUS, 22	Get info, 26
	she_get_info, 26
she_cmd_get_status, 22	
CMD_INIT_RNG, 19	Key store provisioning, 6
she_cmd_init_rng, 19	she storage create, 6
CMD_LOAD_KEY, 16	
she_cmd_load_key, 16	last rating code, 25
CMD_LOAD_PLAIN_KEY, 17	she_get_last_rating_code, 25
she_cmd_load_plain_key, 17	_0
CMD_RND, 21	OS porting guide, 27
she_cmd_rnd, 21	seco_os_abs_close_session, 28
CMD_VERIFY_MAC, 11	seco_os_abs_configure_shared_buf, 30
she_cmd_verify_mac, 11	seco_os_abs_crc, 31
	seco_os_abs_data_buf, 30
ERC_BUSY	seco_os_abs_free, 32
Error codes, 3	seco os abs malloc, 32
ERC_GENERAL_ERROR	seco_os_abs_memcpy, 31
Error codes, 3	seco_os_abs_memset, 31
ERC_KEY_EMPTY	seco_os_abs_read_mu_message, 29
Error codes, 3	seco_os_abs_send_mu_message, 29
ERC_KEY_INVALID	seco_os_abs_send_signed_message, 33
Error codes, 3	seco os abs start system rng, 32
ERC_KEY_NOT_AVAILABLE	seco_os_abs_storage_read, 32
Error codes, 3	seco_os_abs_storage_write, 32
ERC KEY UPDATE ERROR	5555_55_455_5t614g5_Wite, 52
Error codes, 3	SHE commands, 9
ERC_KEY_WRITE_PROTECTED	SHE keys, 4
Error codes, 3	SHE+ key extension, 5
ERC_MEMORY_FAILURE	seco_mu_params, 28
Error codes, 3	seco_os_abs_close_session
ERC_NO_DEBUGGING	OS porting guide, 28
Error codes, 3	seco_os_abs_configure_shared_buf
ERC_NO_ERROR	OS porting guide, 30
Error codes, 3	seco_os_abs_crc
ERC_NO_SECURE_BOOT	OS porting guide, 31
Error codes, 3	
ERC_RNG_SEED	seco_os_abs_data_buf OS porting guide, 30
Error codes, 3	seco_os_abs_free

36 INDEX

OS porting guide, 32 seco\_os\_abs\_malloc OS porting guide, 32 seco\_os\_abs\_memcpy OS porting guide, 31 seco\_os\_abs\_memset OS porting guide, 31 seco os abs read mu message OS porting guide, 29 seco\_os\_abs\_send\_mu\_message OS porting guide, 29 seco\_os\_abs\_send\_signed\_message OS porting guide, 33 seco\_os\_abs\_start\_system\_rng OS porting guide, 32 seco\_os\_abs\_storage\_read OS porting guide, 32 seco os abs storage write OS porting guide, 32 Session, 8 she\_close\_session, 8 she\_open\_session, 8 she\_close\_session Session, 8 she cmd cancel CMD CANCEL, 24 she cmd dec cbc CMD\_DEC\_CBC, 13 she\_cmd\_dec\_ecb CMD\_DEC\_ECB, 15 she cmd enc cbc CMD\_ENC\_CBC, 12 she\_cmd\_enc\_ecb CMD ENC ECB, 14 she\_cmd\_export\_ram\_key CMD\_EXPORT\_RAM\_KEY, 18 she cmd extend seed CMD\_EXTEND\_SEED, 20 she\_cmd\_generate\_mac CMD GENERATE MAC, 10 she\_cmd\_get\_id CMD\_GET\_ID, 23 she cmd get status CMD GET STATUS, 22 she cmd init rng CMD INIT RNG, 19 she\_cmd\_load\_key CMD\_LOAD\_KEY, 16 she\_cmd\_load\_plain\_key CMD\_LOAD\_PLAIN\_KEY, 17 she\_cmd\_rnd CMD RND, 21 she cmd verify mac CMD\_VERIFY\_MAC, 11 she\_err\_t Error codes, 3 she\_get\_info

Get info, 26

she\_get\_last\_rating\_code last rating code, 25 she\_open\_session Session, 8 she\_storage\_create Key store provisioning, 6