# i.MX8 SHE API Rev 1.2 NXP Copyright

Generated by Doxygen 1.8.15

1 SHE API	2
2 Revision History	2
3 General concepts related to the API	2
3.1 Session	2
4 Module Index	2
4.1 Modules	2
5 Module Documentation	3
5.1 Error codes	3
5.1.1 Detailed Description	3
5.1.2 Enumeration Type Documentation	3
5.2 SHE keys	5
5.2.1 Detailed Description	5
5.3 SHE+ key extension	6
5.3.1 Detailed Description	6
5.4 Key store provisioning	7
5.4.1 Detailed Description	7
5.4.2 Function Documentation	7
5.5 Session	9
5.5.1 Detailed Description	9
5.5.2 Function Documentation	9
5.6 SHE commands	11
5.6.1 Detailed Description	11
5.7 CMD_GENERATE_MAC	12
5.7.1 Detailed Description	12
5.7.2 Function Documentation	12
5.8 CMD_VERIFY_MAC	13
5.8.1 Detailed Description	13
5.8.2 Function Documentation	13
5.9 CMD_ENC_CBC	15
5.9.1 Detailed Description	15
5.9.2 Function Documentation	15
5.10 CMD_DEC_CBC	16
5.10.1 Detailed Description	16
5.10.2 Function Documentation	16
5.11 CMD_ENC_ECB	17
5.11.1 Detailed Description	17
5.11.2 Function Documentation	17
5.12 CMD_DEC_ECB	18
5.12.1 Detailed Description	18
5.12.2 Function Documentation	18

41

5.13 CMD_LOAD_KEY	19
5.13.1 Detailed Description	19
5.13.2 Function Documentation	19
5.14 CMD_LOAD_PLAIN_KEY	21
5.14.1 Detailed Description	21
5.14.2 Function Documentation	21
5.15 CMD_EXPORT_RAM_KEY	22
5.15.1 Detailed Description	22
5.15.2 Function Documentation	22
5.16 CMD_INIT_RNG	23
5.16.1 Detailed Description	23
5.16.2 Function Documentation	23
5.17 CMD_EXTEND_SEED	24
5.17.1 Detailed Description	24
5.17.2 Function Documentation	24
5.18 CMD_RND	25
5.18.1 Detailed Description	25
5.18.2 Function Documentation	25
5.19 CMD_GET_STATUS	26
5.19.1 Detailed Description	26
5.19.2 Function Documentation	26
5.20 CMD_GET_ID	27
5.20.1 Detailed Description	27
5.20.2 Function Documentation	27
5.21 CMD_CANCEL	28
5.21.1 Detailed Description	28
5.21.2 Function Documentation	28
5.22 last rating code	29
5.22.1 Detailed Description	29
5.22.2 Function Documentation	29
5.23 Get info	30
5.23.1 Detailed Description	30
5.23.2 Function Documentation	30
5.24 Abstraction layer	31
5.24.1 Detailed Description	32
5.24.2 Data Structure Documentation	32
5.24.3 Function Documentation	32

Index

## 1 SHE API

This document is a software referece description of the API provided by the i.MX8 SHE solutions.

## 2 Revision History

Revision	date	description
0.5	Mai 03 2019	first draf
1.0	June 28 2019	complete functions definition
1.1	December 20 2019	add she_cmd_load_key_ext API
1.2	September 10 2020	add she_storage_create_ext and she_cmd_verify_mac_bit_ext API

# 3 General concepts related to the API

### 3.1 Session

The API must be initialized by a potential requestor by opening a session.

The session establishes a route (MU, DomainID...) between the requester and the SHE module, and grants the usage of a specified key store. When a session is opened, the SHE module returns a handle identifying the session to the requester.

### 4 Module Index

## 4.1 Modules

Here is a list of all modules:

Error codes	3
SHE keys	5
SHE+ key extension	6
Key store provisioning	7
Session	9
SHE commands	11
CMD_GENERATE_MAC	12
CMD_VERIFY_MAC	13
CMD_ENC_CBC	15
CMD_DEC_CBC	16
CMD_ENC_ECB	17

5 Module Documentation 3

	CMD_DEC_ECB	18
	CMD_LOAD_KEY	19
	CMD_LOAD_PLAIN_KEY	21
	CMD_EXPORT_RAM_KEY	22
	CMD_INIT_RNG	23
	CMD_EXTEND_SEED	24
	CMD_RND	25
	CMD_GET_STATUS	26
	CMD_GET_ID	27
	CMD_CANCEL	28
	last rating code	29
Ge	t info	30
Ab	straction layer	31

## 5 Module Documentation

### 5.1 Error codes

### **Enumerations**

```
    enum she_err_t {
        ERC_NO_ERROR = 0x0,
        ERC_SEQUENCE_ERROR = 0x1,
        ERC_KEY_NOT_AVAILABLE = 0x2,
        ERC_KEY_INVALID = 0x3,
        ERC_KEY_EMPTY = 0x4,
        ERC_NO_SECURE_BOOT = 0x5,
        ERC_KEY_WRITE_PROTECTED = 0x6,
        ERC_KEY_UPDATE_ERROR = 0x7,
        ERC_ROM_SEED = 0x8,
        ERC_NO_DEBUGGING = 0x9,
        ERC_BUSY = 0xA,
        ERC_MEMORY_FAILURE = 0xB,
        ERC_GENERAL_ERROR = 0xC }
```

### 5.1.1 Detailed Description

Error codes returned by SHE functions.

### 5.1.2 Enumeration Type Documentation

### 5.1.2.1 she\_err\_t

enum she\_err\_t

## Enumerator

ERC_NO_ERROR	Success.
ERC_SEQUENCE_ERROR	Invalid sequence of commands.
ERC_KEY_NOT_AVAILABLE	Key is locked.
ERC_KEY_INVALID	Key not allowed for the given operation.
ERC_KEY_EMPTY	Key has not beed initialized yet.
ERC_NO_SECURE_BOOT	Conditions for a secure boot process are not met.
ERC_KEY_WRITE_PROTECTED	Memory slot for this key has been write-protected.
ERC_KEY_UPDATE_ERROR	Key update did not succeed due to errors in verification of the messages.
ERC_RNG_SEED	The seed has not been initialized.
ERC_NO_DEBUGGING	Internal debugging is not possible.
ERC_BUSY	A function of SHE is called while another function is still processing.
ERC_MEMORY_FAILURE	Memory error (e.g. flipped bits)
ERC_GENERAL_ERROR	Error not covered by other codes occured.

5.2 SHE keys 5

## 5.2 SHE keys

#### Macros

- #define **SHE\_KEY\_1** (0x04)
- #define **SHE\_KEY\_2** (0x05)
- #define **SHE\_KEY\_3** (0x06)
- #define **SHE\_KEY\_4** (0x07)
- #define **SHE\_KEY\_5** (0x08)
- #define **SHE\_KEY\_6** (0x09)
- #define **SHE\_KEY\_7** (0x0a)
- #define SHE\_KEY\_8 (0x0b)
- #define SHE\_KEY\_9 (0x0c)
- #define **SHE\_KEY\_10** (0x0d)
- #define **SHE\_RAM\_KEY** (0x0e)

### 5.2.1 Detailed Description

Identifiers for SHE keys.

## 5.3 SHE+ key extension

#### Macros

```
#define SHE_KEY_DEFAULT (0x00)

no key extension: keys from 0 to 10 as defined in SHE specification.
#define SHE_KEY_N_EXT_1 (0x10)

keys 11 to 20.
#define SHE_KEY_N_EXT_2 (0x20)

keys 21 to 30.
#define SHE_KEY_N_EXT_3 (0x30)

keys 31 to 40.
#define SHE_KEY_N_EXT_4 (0x40)

keys 41 to 50.
```

## 5.3.1 Detailed Description

Identifiers for the SHE key extension.

### 5.4 Key store provisioning

#### Macros

#define SHE STORAGE CREATE SUCCESS 0u

New storage created succesfully.

· #define SHE STORAGE CREATE WARNING 1u

New storage created but its usage is restricted to a limited security state of the chip.

#define SHE\_STORAGE\_CREATE\_UNAUTHORIZED 2u

Creation of the storage is not authorized.

• #define SHE\_STORAGE\_CREATE\_FAIL 3u

Creation of the storage failed for any other reason.

• #define SHE\_STORAGE\_NUMBER\_UPDATES\_DEFAULT 300u

default number of maximum number of updated for SHE storage.

#### **Functions**

- uint32\_t she\_storage\_create (uint32\_t key\_storage\_identifier, uint32\_t authentication\_nonce, uint16\_t max
   —updates\_number, uint8\_t \*signed\_message, uint32\_t msg\_len)
- uint32\_t she\_storage\_create\_ext (uint32\_t key\_storage\_identifier, uint32\_t authentication\_nonce, uint16\_
   t max\_updates\_number, uint8\_t min\_mac\_length, uint8\_t \*signed\_message, uint32\_t msg\_len)
- 5.4.1 Detailed Description
- 5.4.2 Function Documentation

#### 5.4.2.1 she\_storage\_create()

Creates an empty SHE storage.

Must be called at least once on every device before using any other SHE API.

A signed message must be provided to replace an existing key store. This message is not necessary under some conditions related to chip's lifecycle.

#### **Parameters**

key_storage_identifier	key store identifier
authentication_nonce	user defined nonce to be used as authentication proof for accesing the key store.
max_updates_number	Not supported: maximum number of updates authorized on this new storage.  This parameter has the goal to limit the occupation of the monotonic counter used as anti-rollback protection.  If the maximum number of updates is reached, SHE still allows key store updates but without updating the monotonic counter giving the opportunity for rollback attacks.  Always forced to the SHE available monotonic counter bits in the current release.
Generated by Doxygen Signed_message	pointer to a signed message authorizing the operation (NULL if no signed message to be used)
msg_len	length in bytes of the signed message

### Returns

error code

### 5.4.2.2 she\_storage\_create\_ext()

This is an extension of the she\_storage\_create API.

The functionality of the she\_storage\_create API is extended by adding the following argument:

#### **Parameters**

min_mac_length	MAC verification minimum length (in bits).
	By default, this SHE solution forbids to verify MAC whose length is lower than 32 bits. By
	setting this parameter the user can configure the MAC minimum length, this configuration is
	effective only when the she_cmd_verify_mac_bit_ext API is used (ignored otherwise).

5.5 Session 9

### 5.5 Session

#### **Functions**

- struct she\_hdl\_s \* she\_open\_session (uint32\_t key\_storage\_identifier, uint32\_t authentication\_nonce, void(\*async\_cb)(void \*priv, she\_err\_t err), void \*priv)
- void she close session (struct she hdl s \*hdl)

#### 5.5.1 Detailed Description

#### 5.5.2 Function Documentation

#### 5.5.2.1 she\_open\_session()

Initiate a SHE session. The returned session handle pointer is typed with the struct "she\_hdl\_s". The user doesn't need to know or to access the fields of this struct.

It only needs to store this pointer and pass it to every calls to other APIs within the same SHE session.

Note that asynchronous API is currently not supported. async\_cb and priv pointers must be set to NULL.

### Parameters

key_storage_identifier	key store identifier
authentication_nonce	user defined nonce used as authentication proof for accesing the key store
async_cb	user callback to be called on completion of a SHE operation
priv	user pointer to be passed to the callback

### Returns

pointer to the session handle.

#### 5.5.2.2 she\_close\_session()

Terminate a previously opened SHE session

## **Parameters**

hdl pointer to the session handler to be closed.

5.6 SHE commands

## 5.6 SHE commands

### Modules

- CMD\_GENERATE\_MAC
- CMD\_VERIFY\_MAC
- CMD\_ENC\_CBC
- CMD\_DEC\_CBC
- CMD\_ENC\_ECB
- CMD\_DEC\_ECB
- CMD\_LOAD\_KEY
- CMD\_LOAD\_PLAIN\_KEY
- CMD\_EXPORT\_RAM\_KEY
- CMD\_INIT\_RNG
- CMD\_EXTEND\_SEED
- CMD\_RND
- CMD\_GET\_STATUS
- CMD\_GET\_ID
- CMD\_CANCEL
- · last rating code

## 5.6.1 Detailed Description

# 5.7 CMD\_GENERATE\_MAC

#### Macros

#define SHE\_MAC\_SIZE 16u
 size of the MAC generated is 128bits.

### **Functions**

- she\_err\_t she\_cmd\_generate\_mac (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint16\_← t message\_length, uint8\_t \*message, uint8\_t \*mac)
- 5.7.1 Detailed Description
- 5.7.2 Function Documentation
- 5.7.2.1 she\_cmd\_generate\_mac()

Generates a MAC of a given message with the help of a key identified by key\_id.

### **Parameters**

hdl	pointer to the SHE session handler
key_ext	identifier of the key extension to be used for the operation
key_id	identifier of the key to be used for the operation
message_length	lenght in bytes of the input message. The message is padded to be a multiple of 128 bits by SHE.
message	pointer to the message to be processed
mac	pointer to where the output MAC should be written (128bits should be allocated there)

#### Returns

### 5.8 CMD\_VERIFY\_MAC

#### Macros

- #define SHE\_MAC\_VERIFICATION\_SUCCESS 0u indication of mac verification success
- #define SHE MAC VERIFICATION FAILED 1u

indication of mac verification failure

#### **Functions**

- she\_err\_t she\_cmd\_verify\_mac (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint16\_t message\_
   length, uint8\_t \*message, uint8\_t \*mac, uint8\_t mac\_length, uint8\_t \*verification\_status)
- she\_err\_t she\_cmd\_verify\_mac\_bit\_ext (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint16\_
   t message\_length, uint8\_t \*message, uint8\_t \*mac, uint8\_t mac\_bit\_length, uint8\_t \*verification\_status)
- 5.8.1 Detailed Description
- 5.8.2 Function Documentation

#### 5.8.2.1 she\_cmd\_verify\_mac()

Verifies the MAC of a given message with the help of a key identified by key\_id.

### **Parameters**

hdl	pointer to the SHE session handler
key_ext	identifier of the key extension to be used for the operation
key_id	identifier of the key to be used for the operation
message_length	lenght in bytes of the input message. The message is padded to be a multiple of 128 bits by SHE.
message	pointer to the message to be processed
mac	pointer to the MAC to be compared
mac_length	number of MAC bytes to be compared with the expected value. It cannot be lower than 4
	bytes.
verification_status	pointer to where write the result of the MAC comparison

### Returns

error code

### 5.8.2.2 she\_cmd\_verify\_mac\_bit\_ext()

This API is an extension of the she\_cmd\_verify\_mac API where the mac\_length argument is replaced by the following:

### **Parameters**

mac_bit_length	Number of MAC bits to be compared with the expected value.
	By default the provided value cannot be lower than 32 bit. This minimum length is optionally
	configurable at the key store provisioning by using the she_storage_create_ext
	min_mac_length argument.

5.9 CMD ENC CBC 15

## 5.9 CMD\_ENC\_CBC

#### Macros

#define SHE\_AES\_BLOCK\_SIZE\_128 16u
 size in bytes of a 128bits CBC block

#### **Functions**

• she\_err\_t she\_cmd\_enc\_cbc (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint32\_t data\_length, uint8\_t \*iv, uint8\_t \*plaintext, uint8\_t \*ciphertext)

#### 5.9.1 Detailed Description

#### 5.9.2 Function Documentation

#### 5.9.2.1 she\_cmd\_enc\_cbc()

CBC encryption of a given plaintext with the key identified by key\_id.

### **Parameters**

hdl	pointer to the SHE session handler
key_ext	identifier of the key extension to be used for the operation
key_id	identifier of the key to be used for the operation
data_length	lenght in bytes of the plaintext and the cyphertext. Must be a multiple of 128bits.
iv	pointer to the 128bits IV to use for the encryption.
plaintext	pointer to the message to be encrypted.
ciphertext	pointer to ciphertext output area.

#### Returns

## 5.10 CMD\_DEC\_CBC

#### **Functions**

• she\_err\_t she\_cmd\_dec\_cbc (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint32\_t data\_length, uint8\_t \*iv, uint8\_t \*ciphertext, uint8\_t \*plaintext)

### 5.10.1 Detailed Description

#### 5.10.2 Function Documentation

### 5.10.2.1 she\_cmd\_dec\_cbc()

CBC decryption of a given ciphertext with the key identified by key\_id.

#### **Parameters**

hdl	pointer to the SHE session handler
key_ext	identifier of the key extension to be used for the operation
key_id	identifier of the key to be used for the operation
data_length	lenght in bytes of the plaintext and the cyphertext. Must be a multiple of 128bits.
iv	pointer to the 128bits IV to use for the decryption.
ciphertext	pointer to ciphertext to be decrypted.
plaintext	pointer to the plaintext output area.

### Returns

5.11 CMD ENC ECB 17

## 5.11 CMD\_ENC\_ECB

#### **Functions**

• she\_err\_t she\_cmd\_enc\_ecb (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint8\_t \*plaintext, uint8\_t \*ciphertext)

### 5.11.1 Detailed Description

#### 5.11.2 Function Documentation

### 5.11.2.1 she\_cmd\_enc\_ecb()

ECB encryption of a given plaintext with the key identified by key\_id.

### **Parameters**

hdl	pointer to the SHE session handler
key_ext	identifier of the key extension to be used for the operation
key_id	identifier of the key to be used for the operation
plaintext	pointer to the 128bits message to be encrypted.
ciphertext	pointer to ciphertext output area (128bits).

### Returns

## 5.12 CMD\_DEC\_ECB

#### **Functions**

• she\_err\_t she\_cmd\_dec\_ecb (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint8\_t \*ciphertext, uint8\_t \*plaintext)

### 5.12.1 Detailed Description

#### 5.12.2 Function Documentation

### 5.12.2.1 she\_cmd\_dec\_ecb()

ECB decryption of a given ciphertext with the key identified by key\_id.

### **Parameters**

hdl	pointer to the SHE session handler
key_ext identifier of the key extension to be used for the op	
key_id	identifier of the key to be used for the operation
ciphertext	pointer to 128bits ciphertext to be decrypted.
plaintext	pointer to the plaintext output area (128bits).

### Returns

### 5.13 CMD\_LOAD\_KEY

#### Macros

#define SHE\_LOAD\_KEY\_EXT\_FLAGS\_STRICT\_OPERATION ((she\_cmd\_load\_key\_ext\_flags\_t)(1u << 7))</li>

The request is completed only when the key store is written in the NVM and the monotonic counter is incremented.

• #define SHE KEY SIZE 16u

SHE keys are 128 bits (16 bytes) long.

### **Typedefs**

typedef uint8\_t she\_cmd\_load\_key\_ext\_flags\_t

#### **Functions**

- she\_err\_t she\_cmd\_load\_key (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint8\_t \*m1, uint8\_t \*m2, uint8\_t \*m3, uint8\_t \*m4, uint8\_t \*m5)
- she\_err\_t she\_cmd\_load\_key\_ext (struct she\_hdl\_s \*hdl, uint8\_t key\_ext, uint8\_t key\_id, uint8\_t \*m1, uint8 ← t \*m2, uint8\_t \*m3, uint8\_t \*m4, uint8\_t \*m5, she\_cmd\_load\_key\_ext\_flags\_t flags)

#### 5.13.1 Detailed Description

#### 5.13.2 Function Documentation

### 5.13.2.1 she\_cmd\_load\_key()

Update an internal key of SHE with the protocol specified by SHE. The request is completed only when the new key has been written in the NVM. The monotonic counter is incremented for aach successful update.

#### **Parameters**

hdl	pointer to the SHE session handler
key_ext	identifier of the key extension to be used for the operation
key_id	identifier of the key to be used for the operation
m1	pointer to M1 message - 128 bits
m2	pointer to M2 message - 256 bits
m3	pointer to M3 message - 128 bits
m4	pointer to the output address for M4 message - 256 bits
<i>m5</i> Generated by	pointer to the output address for M5 message - 128 bits

#### Returns

error code

#### 5.13.2.2 she\_cmd\_load\_key\_ext()

```
she_err_t she_cmd_load_key_ext (
    struct she_hdl_s * hdl,
    uint8_t key_ext,
    uint8_t key_id,
    uint8_t * m1,
    uint8_t * m2,
    uint8_t * m3,
    uint8_t * m4,
    uint8_t * m5,
    she_cmd_load_key_ext_flags_t flags )
```

This is an extension of the she\_cmd\_load\_key API. The functionality of the she\_cmd\_load\_key API is extended by adding a flag argument.

• STRICT OPERATION flag: User can use this flag to perform multiple updates before writing the key store into the NVM and incrementing the monotonic counter. The updates to the key store must be considered as effective only after an operation specifying the flag "STRICT OPERATION" is aknowledged by SHE.

#### **Parameters**

hdl	pointer to the SHE session handler
key_ext	identifier of the key extension to be used for the operation
key_id	identifier of the key to be used for the operation
m1	pointer to M1 message - 128 bits
m2	pointer to M2 message - 256 bits
m3	pointer to M3 message - 128 bits
m4	pointer to the output address for M4 message - 256 bits
m5	pointer to the output address for M5 message - 128 bits
flags	bitmap specifying the operation properties.

#### Returns

## 5.14 CMD\_LOAD\_PLAIN\_KEY

### **Functions**

```
• she_err_t she_cmd_load_plain_key (struct she_hdl_s *hdl, uint8_t *key)
```

- 5.14.1 Detailed Description
- 5.14.2 Function Documentation
- 5.14.2.1 she\_cmd\_load\_plain\_key()

Load a key as plaintext to the RAM\_KEY slot without encryption and verification.

### **Parameters**

hdl	pointer to the SHE session handler
key	pointer to the plaintext key to be loaded - 128bits

#### Returns

## 5.15 CMD\_EXPORT\_RAM\_KEY

### **Functions**

```
• she_err_t she_cmd_export_ram_key (struct she_hdl_s *hdl, uint8_t *m1, uint8_t *m2, uint8_t *m3, uint8_t *m4, uint8_t *m5)
```

- 5.15.1 Detailed Description
- 5.15.2 Function Documentation
- 5.15.2.1 she\_cmd\_export\_ram\_key()

exports the RAM\_KEY into a format protected by SECRET\_KEY.

### **Parameters**

hdl	pointer to the SHE session handler
m1	pointer to the output address for M1 message - 128 bits
m2	pointer to the output address for M2 message - 256 bits
тЗ	pointer to the output address for M3 message - 128 bits
m4	pointer to the output address for M4 message - 256 bits
m5	pointer to the output address for M5 message - 128 bits

#### Returns

5.16 CMD INIT RNG 23

## 5.16 CMD\_INIT\_RNG

**Functions** 

```
• she_err_t she_cmd_init_rng (struct she_hdl_s *hdl)
```

- 5.16.1 Detailed Description
- 5.16.2 Function Documentation

```
5.16.2.1 she_cmd_init_rng()
```

initializes the seed and derives a key for the PRNG. The function must be called before CMD\_RND after every power cycle/reset.

### **Parameters**

hdl pointer to the SHE session handler

#### Returns

## 5.17 CMD\_EXTEND\_SEED

#### Macros

• #define SHE\_ENTROPY\_SIZE 16u

#### **Functions**

```
• she_err_t she_cmd_extend_seed (struct she_hdl_s *hdl, uint8_t *entropy)
```

- 5.17.1 Detailed Description
- 5.17.2 Function Documentation
- 5.17.2.1 she\_cmd\_extend\_seed()

extends the seed of the PRNG by compressing the former seed value and the supplied entropy into a new seed which will be used to generate the following random numbers. The random number generator has to be initialized by CMD\_INIT\_RNG before the seed can be extended.

#### **Parameters**

hdl	pointer to the SHE session handler
entropy	pointer to the entropy vector (128bits) to use for the operation

#### Returns

5.18 CMD RND 25

### 5.18 CMD\_RND

Macros

• #define SHE\_RND\_SIZE 16u

#### **Functions**

```
• she_err_t she_cmd_rnd (struct she_hdl_s *hdl, uint8_t *rnd)
```

- 5.18.1 Detailed Description
- 5.18.2 Function Documentation
- 5.18.2.1 she\_cmd\_rnd()

returns a vector of 128 random bits. The random number generator has to be initialized by CMD\_INIT\_RNG before random numbers can be supplied.

### **Parameters**

hdl	pointer to the SHE session handler
rnd	pointer to the output address for the generated 128bits random vector

Returns

## 5.19 CMD\_GET\_STATUS

### **Functions**

```
• she_err_t she_cmd_get_status (struct she_hdl_s *hdl, uint8_t *sreg)
```

- 5.19.1 Detailed Description
- 5.19.2 Function Documentation

```
5.19.2.1 she_cmd_get_status()
```

returns the content of the status register

### **Parameters**

hdl	pointer to the SHE session handler
sreg	pointer to the output address for status register(8bits)

### Returns

5.20 CMD GET ID 27

### 5.20 CMD\_GET\_ID

#### Macros

- #define SHE\_CHALLENGE\_SIZE 16u /\* 128 bits \*/
- #define **SHE\_ID\_SIZE** 15u /\* 120 bits \*/

### **Functions**

she\_err\_t she\_cmd\_get\_id (struct she\_hdl\_s \*hdl, uint8\_t \*challenge, uint8\_t \*id, uint8\_t \*sreg, uint8\_←
t \*mac)

### 5.20.1 Detailed Description

5.20.2 Function Documentation

## 5.20.2.1 she\_cmd\_get\_id()

returns the identity (UID) and the value of the status register protected by a MAC over a challenge and the data.

#### **Parameters**

hdl	pointer to the SHE session handler
challenge	pointer to the challenge vector (128bits)
id	pointer to the output address for the identity (120bits)
sreg	pointer to the output address for status register(8bits)
mac	pointer to the output address for the computed MAC (128bits)

### Returns

## 5.21 CMD\_CANCEL

### **Functions**

```
• she_err_t she_cmd_cancel (struct she_hdl_s *hdl)
```

- 5.21.1 Detailed Description
- 5.21.2 Function Documentation

### 5.21.2.1 she\_cmd\_cancel()

interrupt any given function and discard all calculations and results.

#### **Parameters**

hdl pointer to the SHE session handler

### Returns

5.22 last rating code 29

### 5.22 last rating code

#### **Functions**

```
• uint32_t she_get_last_rating_code (struct she_hdl_s *hdl)
```

- 5.22.1 Detailed Description
- 5.22.2 Function Documentation

### 5.22.2.1 she\_get\_last\_rating\_code()

Report rating code from last command

SHE API defines standard errors that should be returned by API calls. Error code reported by SECO are "translated" to these SHE error codes. This API allow user to get the error code reported by SECO for the last command before its translation to SHE error codes. This should be used for debug purpose only.

### **Parameters**

hdl pointer to the SHE session handler

#### Returns

rating code reported by last command

### 5.23 Get info

#### **Functions**

she\_err\_t she\_get\_info (struct she\_hdl\_s \*hdl, uint32\_t \*user\_sab\_id, uint8\_t \*chip\_unique\_id, uint16\_
 t \*chip\_monotonic\_counter, uint16\_t \*chip\_life\_cycle, uint32\_t \*she\_version)

### 5.23.1 Detailed Description

Get miscellaneous information. This function return, among others, all the information needed to build a valid signed message.

#### 5.23.2 Function Documentation

### 5.23.2.1 she\_get\_info()

#### **Parameters**

hdl	pointer to the SHE session handler
user_sab_id	pointer to the output address for the user identity (32bits)
chip_unique_id	pointer to the output address for the chip unique identifier (64bits)
chip_monotonic_counter	pointer to the output address for the chip monotonic counter value (16bits)
chip_life_cycle	pointer to the output address for the chip current life cycle (16bits)
she_version	pointer to the output address for the SHE module version (32bits)

### Returns

### 5.24 Abstraction layer

#### **Data Structures**

· struct seco\_mu\_params

#### **Macros**

- #define MU CHANNEL UNDEF (0x00u)
- #define MU CHANNEL SECO SHE (0x01u)
- #define MU\_CHANNEL\_SECO\_SHE\_NVM (0x02u)
- #define MU CHANNEL SECO HSM (0x03u)
- #define MU CHANNEL SECO HSM 2ND (0x04u)
- #define MU\_CHANNEL\_SECO\_HSM\_NVM (0x05u)
- #define MU CHANNEL V2X SV0 (0x10u)
- #define MU\_CHANNEL\_V2X\_SV1 (0x11u)
- #define MU\_CHANNEL\_V2X\_SHE (0x12u)
- #define MU\_CHANNEL\_V2X\_SG0 (0x13u)
- #define MU CHANNEL V2X SG1 (0x14u)
- #define MU CHANNEL V2X SHE NVM (0x15u)
- #define MU\_CHANNEL\_V2X\_HSM\_NVM (0x16u)
- #define DATA\_BUF\_IS\_INPUT 0x01u
- #define DATA BUF USE SEC MEM 0x02u
- #define DATA\_BUF\_SHORT\_ADDR 0x04u
- #define SEC\_MEM\_SHORT\_ADDR\_MASK 0xFFFFu

#### **Functions**

- struct seco\_os\_abs\_hdl \* seco\_os\_abs\_open\_mu\_channel (uint32\_t type, struct seco\_mu\_params \*mu
   —params)
- uint32\_t seco\_os\_abs\_has\_v2x\_hw (void)
- void seco\_os\_abs\_close\_session (struct seco\_os\_abs\_hdl \*phdl)
- int32\_t seco\_os\_abs\_send\_mu\_message (struct seco\_os\_abs\_hdl \*phdl, uint32\_t \*message, uint32\_t size)
- int32\_t seco\_os\_abs\_read\_mu\_message (struct seco\_os\_abs\_hdl \*phdl, uint32\_t \*message, uint32\_t size)
- int32\_t seco\_os\_abs\_configure\_shared\_buf (struct seco\_os\_abs\_hdl \*phdl, uint32\_t shared\_buf\_off, uint32\_t size)
- uint64\_t seco\_os\_abs\_data\_buf (struct seco\_os\_abs\_hdl \*phdl, uint8\_t \*src, uint32\_t size, uint32\_t flags)
- uint32\_t seco\_os\_abs\_crc (uint8\_t \*data, uint32\_t size)
- void seco\_os\_abs\_memset (uint8\_t \*dst, uint8\_t val, uint32\_t len)
- void seco\_os\_abs\_memcpy (uint8\_t \*dst, uint8\_t \*src, uint32\_t len)
- uint8 t \* seco os abs malloc (uint32 t size)
- void seco os abs free (void \*ptr)
- int32\_t seco\_os\_abs\_storage\_write (struct seco\_os\_abs\_hdl \*phdl, uint8\_t \*src, uint32\_t size)
- int32\_t seco\_os\_abs\_storage\_read (struct seco\_os\_abs\_hdl \*phdl, uint8\_t \*dst, uint32\_t size)
- int32\_t seco\_os\_abs\_storage\_write\_chunk (struct seco\_os\_abs\_hdl \*phdl, uint8\_t \*src, uint32\_t size, uint64 t blob id)
- int32\_t seco\_os\_abs\_storage\_read\_chunk (struct seco\_os\_abs\_hdl \*phdl, uint8\_t \*dst, uint32\_t size, uint64 t blob id)
- void seco\_os\_abs\_start\_system\_rng (struct seco\_os\_abs\_hdl \*phdl)
- int32\_t seco\_os\_abs\_send\_signed\_message (struct seco\_os\_abs\_hdl \*phdl, uint8\_t \*signed\_message, uint32\_t msg\_len)

#### 5.24.1 Detailed Description

seco\_libs code itself is independent from any OS or platform. This abstraction layer defines the functions that should be implemented on a specific OS or platform when porting seco\_libs on it.

#### 5.24.2 Data Structure Documentation

#### 5.24.2.1 struct seco\_mu\_params

Opens a MU channel Purpose of this function is to setup a communication channel using a messaging unit (MU) between the caller of this function and SECO. This session is uniquely identified by a platform handle. The pointer to this handle is returned here and has to be provided by the user on each call to platform dependent functions. The details of the seco\_os\_abs\_hdl structure are not described in this API so it can be custmized for each OS/platform porting.

One physical MU can be shared between several sessions but concurrent access should be protected. Seco can only process one command at a time. Once a command has been sent to SECO no other command should be sent on the physical MU (even by other sessions sharing same physical MU) until the response has been received. (but a response to a command from Seco should not be blocked - e.g. in storage case)

The mapping between physical MUs and sessions is considered as platform dependent. So no assumption are made about this by the caller.

#### **Parameters**

type	constant indicating for which purpose will be used this channel (see defines below)
mu_params	pointer where the MU params for this channel should be written. It is up to this abstraction layer to provide a mapping between channel types and associated MU params. Caller need to know these information to fill some SECO messages.

#### Returns

pointer to the MU channel handle.

### **Data Fields**

uint8_t	mu_id	index of the MU as per SECO point of view.
uint8_t	interrupt_idx	Interrupt number of the MU used to indicate data availability.
uint8_t	tz	indicate if current partition has TZ enabled.
uint8_t	did	DID of the calling partition.

## 5.24.3 Function Documentation

## 5.24.3.1 seco\_os\_abs\_has\_v2x\_hw()

Check if the V2X accelerator is present on this HW

#### Returns

null if V2X HW is not available. Not null if present.

#### 5.24.3.2 seco\_os\_abs\_close\_session()

Close a previously opened session.

#### **Parameters**

```
phdl pointer to the session handle to be closed.
```

#### 5.24.3.3 seco\_os\_abs\_send\_mu\_message()

Send a message to Seco over a messaging unit.

A message is made of 1 or more 32bits words. The 1st word is an header containing the length of the message and its type (command or response) The following protocol has to be respected when sending a message to SECO:

- · write the header in TR0 of the MU
- · send and interrupt to SECO thanks to GI0 bit in CR register of the MU
- Write other words of the message. word at index n in the message has to be written in TR[n%4] register of the MU. Write to a TRx register has to be performed only when the corresponding TEx bit in SR register is equal to 1 (indicating that the TRx register is empty).

Note that a physical MU can be shared between several sessions. Concurrent access to the physical MU should be prevented (SECO process commands one by one). So this API should block until the physical MU is available for this session.

#### **Parameters**

phdl	pointer to handle identifying the session to be used to carry the message.
message	pointer to the message itself. It has to be aligned on 32bits.
size	size in bytes of the message. It has to be multiple of 4 bytes.

#### Returns

length in bytes written to the MU or negative value in case of error

#### 5.24.3.4 seco\_os\_abs\_read\_mu\_message()

Read a message from Seco over a messaging unit.

This API is blocking until a message is sent by SECO

A message is made of 1 or more 32bits words. The 1st word is an header containing the length of the message and its type (command or response)

When receiving MU's GI0 interrupt from SECO this API should:

- · read the header in RR0 of the MU and extract its length
- · send and interrupt to SECO thanks to GI0 bit in CR register of the MU
- Write other words of the message. word at index n in the message has to be written in TR[n%4] register of the MU. Write to a TRx register has to be performed only when the corresponding TEx bit in SR register is equal to 1 (indicating that the TRx register is empty).

Typically for SHE this API will be called right after having sent a command to SECO in order to get the response. And for Storage an infinite loop will wait on this blocking API for a command from SECO.

#### **Parameters**

phdl	pointer to handle identifying the session to be used to carry the message.
message	pointer to the message itself. It has to be aligned on 32bits.
size	size in bytes of the message. It has to be multiple of 4 bytes.

### Returns

length in bytes read from the MU or negative value in case of error

#### 5.24.3.5 seco\_os\_abs\_configure\_shared\_buf()

Configure the use of shared buffer in secure memory

Seco allocates a shared buffer in secure memory to exchange data. Offset in secure memory and size are provided by Seco in a message decoded by caller. These information are provided to the platform dependent layer through this API to avoid parsing incoming messages here.

#### **Parameters**

phdl	pointer to the session handle associated to this shared buffer.
shared_buf_offset	offset of the shared buffer in secure memory.
size	size in bytes of the allocated shared buffer.

#### Returns

0 in case of success. Any other value means error.

#### 5.24.3.6 seco\_os\_abs\_data\_buf()

Setup data buffer for command processing

The command messages sent to Seco most of the time do not carry the data to be processed. It uses pointers instead. This API is used to make sure the data are available to Seco when it receive a command and also that the result can be accessed by the caller after seco sent the response by either:

- · copy to/from dedicated shared buffer in secure memory
- or perform appropriate cache management when using buffers in DDR It also provides the address to be inserted into the message to be sent to Seco: either the physical address or the offset in the shared buffer (see options below) yo be used by Seco.

Several options are available to describe the buffers. DATA\_BUF\_IS\_INPUT: the buffer described here is input to the next command. Otherwise this is an output. DATA\_BUF\_USE\_SEC\_MEM: the data should be copied to the shared buffer in secure memory or the output will be stored by Seco in it. It is expected that the buffers will be allocated in a contiguous manner in this shared memory since some optimizations depend on this (fast MAC). If not set any other memory can be used (e.g. DDR). In this case this API should take care of cache coherency and access rights before Seco tries access the physical memory. when using secure mem. DATA\_BUF\_SHORT\_A DDR: (only possible when using secure memory) returns the offset in secure memory (16bits) instead of full 64bits address (used to reduce the size of some Seco messages).

Once this API has been called the buffers should no more be accessed by the caller until the command has been sent to Seco and its response has been received.

#### **Parameters**

phdl	pointer to the session handle for which this data buffer is used.
src	pointer to the data if input or to the area where the output should be written.
size	size in bytes of the input data or max size of the output.
flags	data buffer options as described above. Interpreted as a bit-field.

#### Returns

the address to be inserted in the message to Seco to indicate him this buffer.

#### 5.24.3.7 seco\_os\_abs\_crc()

### Compute the CRC of a buffer.

Used for basic check of integrity on the storage to avoid sending a corrupted blob to Seco. No strong security requirement here since Seco will perform more robust integrity check on the blob.

CRC computation is abstracted here in order to let the possibility to use some platform optimized library instead of re-implementing.

#### **Parameters**

```
data pointer to the data on which the CRC must be computed. \size size in bytes of the data
```

#### Returns

32bits value of the CRC.

### 5.24.3.8 seco\_os\_abs\_memset()

Force all bytes of a buffer to a given value.

### **Parameters**

dst	address of the buffer to be overwriten
val	value to be written in every bytes of the buffer
len	number of bytes to be written

## 5.24.3.9 seco\_os\_abs\_memcpy()

```
uint8_t * src,
uint32_t len )
```

Copy the content of a buffer to another location.

#### **Parameters**

dst	pointer to the destination buffer where data should be copied
src	pointer to the source buffer from where data should be copied
len	number of bytes to be copied

### 5.24.3.10 seco\_os\_abs\_malloc()

Dynamically allocate memory.

#### **Parameters**

	size	number of bytes to be allocated
--	------	---------------------------------

## Returns

pointer to the allocated buffer or NULL in case of error.

### 5.24.3.11 seco\_os\_abs\_free()

Free a previously allocated buffer.

## **Parameters**

```
ptr pointer to the buffer to free
```

### 5.24.3.12 seco\_os\_abs\_storage\_write()

Write data to the non volatile storage.

#### **Parameters**

phdl	pointer to the session handle for which this data buffer is used.
src	pointer to the data to be written to storage.
size	number of bytes to be written.

#### Returns

number of bytes written.

### 5.24.3.13 seco\_os\_abs\_storage\_read()

Read data from the non volatile storage.

#### **Parameters**

phdl	pointer to the session handle for which this data buffer is used.
dst	pointer to the data where data read from the storage should be copied.
size	number of bytes to be read.

#### Returns

number of bytes read.

#### 5.24.3.14 seco\_os\_abs\_storage\_write\_chunk()

Write a subset of data to the non volatile storage.

In case of large storage SECO will split it in "chunks" that will be encrypted in blobs. A unique identifier within the system allow the storage manager to store and read it without ambiguity.

### **Parameters**

phdl	pointer to the session handle for which this data buffer is used.
src	pointer to the data to be written to storage.
size	number of bytes to be written. \patam blob_id unique identifier of the blob corresponding to the storage
	chunk to be written

#### Returns

number of bytes written.

#### 5.24.3.15 seco\_os\_abs\_storage\_read\_chunk()

Read a subset of data from the non volatile storage.

In case of large storage SECO will split it in "chunks" that will be encrypted in blobs. A unique identifier within the system allow the storage manager to store and read it without ambiguity.

#### **Parameters**

phdl	pointer to the session handle for which this data buffer is used.
dst	pointer to the data where data read from the storage should be copied.
size	number of bytes to be read. \patam blob_id unique identifier of the blob corresponding to the storage
	chunk to be read

### Returns

number of bytes read.

### 5.24.3.16 seco\_os\_abs\_start\_system\_rng()

Start the RNG from a system point of view.

Start the RNG HW through a SCU RPC: sc\_seco\_start\_rng()

#### **Parameters**

phdl pointer to the session handle for which this data buffer is used.

## 5.24.3.17 seco\_os\_abs\_send\_signed\_message()

```
uint8_t * signed_message,
uint32_t msg_len )
```

Send a signed message to SECO through dedicated SCU RPC

Purpose is to unlock the creation of a storage in some specific cases.

### **Parameters**

signed_message	pointer to the signed message.
msg_len	length of the signed message

# Index

Abstraction layer, 31	ERC_KEY_EMPTY	
seco_os_abs_close_session, 33	Error codes, 4	
seco_os_abs_configure_shared_buf, 34	ERC_KEY_INVALID	
seco_os_abs_crc, 36	Error codes, 4	
seco_os_abs_data_buf, 35	ERC_KEY_NOT_AVAILABLE	
seco_os_abs_free, 37	Error codes, 4	
seco_os_abs_has_v2x_hw, 32	ERC_KEY_UPDATE_ERROR	
seco_os_abs_malloc, 37	Error codes, 4	
seco_os_abs_memcpy, 36	ERC_KEY_WRITE_PROTECTED	
seco_os_abs_memset, 36	Error codes, 4	
seco_os_abs_read_mu_message, 33	ERC_MEMORY_FAILURE	
seco_os_abs_send_mu_message, 33	Error codes, 4	
seco_os_abs_send_signed_message, 39	ERC_NO_DEBUGGING	
seco_os_abs_start_system_rng, 39	Error codes, 4	
seco_os_abs_storage_read, 38	ERC_NO_ERROR	
seco_os_abs_storage_read_chunk, 39	Error codes, 4	
seco_os_abs_storage_write, 37	ERC_NO_SECURE_BOOT	
seco_os_abs_storage_write_chunk, 38	Error codes, 4	
	ERC_RNG_SEED	
CMD_CANCEL, 28	Error codes, 4	
she_cmd_cancel, 28	ERC_SEQUENCE_ERROR	
CMD_DEC_CBC, 16	Error codes, 4	
she_cmd_dec_cbc, 16	Error codes, 3	
CMD_DEC_ECB, 18	ERC_BUSY, 4	
she_cmd_dec_ecb, 18	ERC_GENERAL_ERROR, 4	
CMD_ENC_CBC, 15	ERC_KEY_EMPTY, 4	
she_cmd_enc_cbc, 15	ERC_KEY_INVALID, 4	
CMD_ENC_ECB, 17	ERC_KEY_NOT_AVAILABLE, 4	
she_cmd_enc_ecb, 17	ERC_KEY_UPDATE_ERROR, 4	
CMD_EXPORT_RAM_KEY, 22	ERC_KEY_WRITE_PROTECTED, 4	
she_cmd_export_ram_key, 22	ERC_MEMORY_FAILURE, 4	
CMD_EXTEND_SEED, 24	ERC_NO_DEBUGGING, 4	
she_cmd_extend_seed, 24	ERC_NO_ERROR, 4	
CMD_GENERATE_MAC, 12	ERC_NO_SECURE_BOOT, 4	
she_cmd_generate_mac, 12	ERC_RNG_SEED, 4	
CMD_GET_ID, 27	ERC_SEQUENCE_ERROR, 4	
she_cmd_get_id, 27	she_err_t, 3	
CMD_GET_STATUS, 26		
she_cmd_get_status, 26	Get info, 30	
CMD_INIT_RNG, 23	she_get_info, 30	
she_cmd_init_rng, 23		
CMD_LOAD_KEY, 19	Key store provisioning, 7	
she_cmd_load_key, 19	she_storage_create, 7	
she_cmd_load_key_ext, 20	she_storage_create_ext, 8	
CMD_LOAD_PLAIN_KEY, 21		
she_cmd_load_plain_key, 21	last rating code, 29	
CMD_RND, 25	she_get_last_rating_code, 29	
she_cmd_rnd, 25		
CMD_VERIFY_MAC, 13	seco_mu_params, 32	
she_cmd_verify_mac, 13	seco_os_abs_close_session	
she_cmd_verify_mac_bit_ext, 14	Abstraction layer, 33	
EDG BLICV	seco_os_abs_configure_shared_buf	
ERC_BUSY	Abstraction layer, 34	
Error codes, 4	seco_os_abs_crc	
ERC_GENERAL_ERROR	Abstraction layer, 36	
Error codes, 4	seco_os_abs_data_buf	

42 INDEX

Abatraction layer 25	CMD LOAD KEV 10
Abstraction layer, 35	CMD_LOAD_KEY, 19
seco_os_abs_free	she_cmd_load_key_ext
Abstraction layer, 37	CMD_LOAD_KEY, 20
seco_os_abs_has_v2x_hw	she_cmd_load_plain_key
Abstraction layer, 32	CMD_LOAD_PLAIN_KEY, 21
seco_os_abs_malloc	she_cmd_rnd
Abstraction layer, 37	CMD_RND, 25
seco_os_abs_memcpy	she_cmd_verify_mac
Abstraction layer, 36	CMD_VERIFY_MAC, 13
seco_os_abs_memset	she_cmd_verify_mac_bit_ext
Abstraction layer, 36	CMD_VERIFY_MAC, 14
seco_os_abs_read_mu_message	she_err_t
Abstraction layer, 33	Error codes, 3
seco_os_abs_send_mu_message	she_get_info
Abstraction layer, 33	Get info, 30
seco_os_abs_send_signed_message	she_get_last_rating_code
Abstraction layer, 39	last rating code, 29
seco_os_abs_start_system_rng	she_open_session
Abstraction layer, 39	Session, 9
seco_os_abs_storage_read	she_storage_create
Abstraction layer, 38	Key store provisioning, 7
seco_os_abs_storage_read_chunk	she_storage_create_ext
Abstraction layer, 39	Key store provisioning, 8
• •	, ,
seco_os_abs_storage_write	
Abstraction layer, 37	
seco_os_abs_storage_write_chunk	
Abstraction layer, 38	
Session, 9	
she_close_session, 9	
she_open_session, 9	
SHE commands, 11	
SHE keys, 5	
SHE+ key extension, 6	
she_close_session	
Session, 9	
she_cmd_cancel	
CMD CANCEL, 28	
she_cmd_dec_cbc	
CMD_DEC_CBC, 16	
she_cmd_dec_ecb	
CMD_DEC_ECB, 18	
she cmd enc cbc	
CMD_ENC_CBC, 15	
she_cmd_enc_ecb	
CMD_ENC_ECB, 17	
she_cmd_export_ram_key	
CMD_EXPORT_RAM_KEY, 22	
she_cmd_extend_seed	
CMD_EXTEND_SEED, 24	
she_cmd_generate_mac	
CMD_GENERATE_MAC, 12	
she_cmd_get_id	
CMD_GET_ID, 27	
she_cmd_get_status	
CMD_GET_STATUS, 26	
she_cmd_init_rng	
CMD_INIT_RNG, 23	
she_cmd_load_key	