

NetX™

Hypertext Transfer Protocol (HTTP)

User Guide

Renesas Synergy™ Platform

All information contained in these materials, including products and product specifications, represents information on the product at the time of publication and is subject to change by Renesas Electronics Corp. without notice. Please review the latest information published by Renesas Electronics Corp. through various means, including the Renesas Electronics Corp. website (<http://www.renesas.com>).

Notice

1. Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation or any other use of the circuits, software, and information in the design of your product or system. Renesas Electronics disclaims any and all liability for any losses and damages incurred by you or third parties arising from the use of these circuits, software, or information.
2. Renesas Electronics hereby expressly disclaims any warranties against and liability for infringement or any other claims involving patents, copyrights, or other intellectual property rights of third parties, by or arising from the use of Renesas Electronics products or technical information described in this document, including but not limited to, the product data, drawings, charts, programs, algorithms, and application examples.
3. No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of Renesas Electronics or others.
4. You shall not alter, modify, copy, or reverse engineer any Renesas Electronics product, whether in whole or in part. Renesas Electronics disclaims any and all liability for any losses or damages incurred by you or third parties arising from such alteration, modification, copying or reverse engineering.
5. Renesas Electronics products are classified according to the following two quality grades: "Standard" and "High Quality". The intended applications for each Renesas Electronics product depends on the product's quality grade, as indicated below.

"Standard": Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; industrial robots; etc.

"High Quality": Transportation equipment (automobiles, trains, ships, etc.); traffic control (traffic lights); large-scale communication equipment; key financial terminal systems; safety control equipment; etc.

Unless expressly designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not intended or authorized for use in products or systems that may pose a direct threat to human life or bodily injury (artificial life support devices or systems; surgical implantations; etc.), or may cause serious property damage (space system; undersea repeaters; nuclear power control systems; aircraft control systems; key plant systems; military equipment; etc.). Renesas Electronics disclaims any and all liability for any damages or losses incurred by you or any third parties arising from the use of any Renesas Electronics product that is inconsistent with any Renesas Electronics data sheet, user's manual or other Renesas Electronics document.
6. When using Renesas Electronics products, refer to the latest product information (data sheets, user's manuals, application notes, "General Notes for Handling and Using Semiconductor Devices" in the reliability handbook, etc.), and ensure that usage conditions are within the ranges specified by Renesas Electronics with respect to maximum ratings, operating power supply voltage range, heat dissipation characteristics, installation, etc. Renesas Electronics disclaims any and all liability for any malfunctions, failure or accident arising out of the use of Renesas Electronics products outside of such specified ranges.
7. Although Renesas Electronics endeavors to improve the quality and reliability of Renesas Electronics products, semiconductor products have specific characteristics, such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Unless designated as a high reliability product or a product for harsh environments in a Renesas Electronics data sheet or other Renesas Electronics document, Renesas Electronics products are not subject to radiation resistance design. You are responsible for implementing safety measures to guard against the possibility of bodily injury, injury or damage caused by fire, and/or danger to the public in the event of a failure or malfunction of Renesas Electronics products, such as safety design for hardware and software, including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult and impractical, you are responsible for evaluating the safety of the final products or systems manufactured by you.
8. Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. You are responsible for carefully and sufficiently investigating applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive, and using Renesas Electronics products in compliance with all these applicable laws and regulations. Renesas Electronics disclaims any and all liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
9. Renesas Electronics products and technologies shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations. You shall comply with any applicable export control laws and regulations promulgated and administered by the governments of any countries asserting jurisdiction over the parties or transactions.
10. It is the responsibility of the buyer or distributor of Renesas Electronics products, or any other party who distributes, disposes of, or otherwise sells or transfers the product to a third party, to notify such third party in advance of the contents and conditions set forth in this document.
11. This document shall not be reprinted, reproduced or duplicated in any form, in whole or in part, without prior written consent of Renesas Electronics.
12. Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products.

(Note 1) "Renesas Electronics" as used in this document means Renesas Electronics Corporation and also includes its directly or indirectly controlled subsidiaries.

(Note 2) "Renesas Electronics product(s)" means any product developed or manufactured by or for Renesas Electronics.

Renesas Synergy Specific Information

If you are using NetX HTTP for the Renesas Synergy platform, please use the following information.

Multi-Part, Multi-Thread Support

Page 12: Multi-part support and multi-thread support have not been tested for SSP v1.5.0.

Installation

Page 13: If you are using Renesas Synergy SSP and the e² studio ISDE, HTTP will already be installed. You can ignore the HTTP Installation.



Hypertext Transfer Protocol (HTTP)

User Guide

Express Logic, Inc.

858.613.6640
Toll Free 888.THREADX
FAX 858.521.4259

www.expresslogic.com

©2002-2018 by Express Logic, Inc.

All rights reserved. This document and the associated NetX software are the sole property of Express Logic, Inc. Each contains proprietary information of Express Logic, Inc. Reproduction or duplication by any means of any portion of this document without the prior written consent of Express Logic, Inc. is expressly forbidden. Express Logic, Inc. reserves the right to make changes to the specifications described herein at any time and without notice in order to improve design or reliability of NetX. The information in this document has been carefully checked for accuracy; however, Express Logic, Inc. makes no warranty pertaining to the correctness of this document.

Trademarks

NetX, Piconet, and UDP Fast Path are trademarks of Express Logic, Inc. ThreadX is a registered trademark of Express Logic, Inc.

All other product and company names are trademarks or registered trademarks of their respective holders.

Warranty Limitations

Express Logic, Inc. makes no warranty of any kind that the NetX products will meet the USER's requirements, or will operate in the manner specified by the USER, or that the operation of the NetX products will operate uninterrupted or error free, or that any defects that may exist in the NetX products will be corrected after the warranty period. Express Logic, Inc. makes no warranties of any kind, either expressed or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose, with respect to the NetX products. No oral or written information or advice given by Express Logic, Inc., its dealers, distributors, agents, or employees shall create any other warranty or in any way increase the scope of this warranty, and licensee may not rely on any such information or advice.

Part Number: 000-1054
Revision 5.11

Contents

Chapter 1 Introduction to HTTP	5
HTTP Requirements.....	5
HTTP Constraints.....	5
HTTP URL (Resource Names).....	6
HTTP Client Requests.....	6
HTTP Server Responses	7
HTTP Communication	7
HTTP Authentication	8
HTTP Authentication Callback.....	9
HTTP Invalid Username/Password Callback.....	10
HTTP Insert GMT Date Header Callback	11
HTTP Cache Info Get Callback	11
HTTP Multipart Support.....	12
HTTP Multi-Thread Support	12
HTTP RFCs.....	12
Chapter 2 Installation and Use of HTTP	13
Product Distribution	13
HTTP Installation.....	13
Using HTTP	13
Small Example System	14
Configuration Options.....	18
Chapter 3 Description of HTTP Services	22
nx_http_client_create	25
nx_http_client_delete	27
nx_http_client_get_start	28
nx_http_client_get_packet.....	30
nx_http_client_put_start	32
nx_http_client_put_packet.....	34
nx_http_client_set_connect_port.....	36
nx_http_server_cache_info_callback_set.....	37
nx_http_server_callback_data_send	39
nx_http_server_callback_generate_response_header.....	41
nx_http_server_callback_packet_send	43
nx_http_server_callback_response_send	45
nx_http_server_content_get	47
nx_http_server_content_get_extended	49
nx_http_server_content_length_get	51
nx_http_server_content_length_get_extended	52
nx_http_server_create.....	54
nx_http_server_delete	56
nx_http_server_get_entity_content	57

nx_http_server_get_entity_header	59
nx_http_server_gmt_callback_set	61
nx_http_server_invalid_userpassword_notify_set	62
nx_http_server_mime_maps_additional_set	64
nx_http_server_packet_content_find	66
nx_http_server_packet_get	68
nx_http_server_param_get	69
nx_http_server_query_get	71
nx_http_server_start	73
nx_http_server_stop	74
nx_http_server_type_get	75

Chapter 1

Introduction to HTTP

The Hypertext Transfer Protocol (HTTP) is a protocol designed for transferring content on the Web. HTTP is a simple protocol that utilizes reliable Transmission Control Protocol (TCP) services to perform its content transfer function. Because of this, HTTP is a highly reliable content transfer protocol. HTTP is one of the most used application protocols. All operations on the Web utilize the HTTP protocol.

HTTP Requirements

In order to function properly, the NetX HTTP package requires that a NetX (version 5.2 or later) is installed. In addition, an IP instance must already be created and TCP must be enabled on that same IP instance. The demo file in section “Small Example System” in **Chapter 2** will demonstrate how this is done.

The HTTP Client portion of the NetX HTTP package has no further requirements.

The HTTP Server portion of the NetX HTTP package has several additional requirements. First, it requires complete access to TCP *well-known port 80* for handling all Client HTTP requests. The HTTP Server is also designed for use with the FileX embedded file system. If FileX is not available, the user may port the portions of FileX used to their own environment. This is discussed in later sections of this guide.

HTTP Constraints

The NetX HTTP protocol implements the HTTP 1.0 standard. However, there are following constraints:

1. Persistent connections are not supported
2. Request pipelining is not supported
3. The HTTP Server supports both basic and MD5 digest authentication, but not MD5-sess. At present, the HTTP Client supports only basic authentication.

4. No content compression is supported.
5. TRACE, OPTIONS, and CONNECT requests are not supported.
6. The packet pool associated with the HTTP Server or Client must be large enough to hold the complete HTTP header.
7. HTTP Client services are for content transfer only—there are no display utilities provided in this package.

HTTP URL (Resource Names)

The HTTP protocol is designed to transfer content on Web. The requested content is specified by the Universal Resource Locator (URL). This is the primary component of every HTTP request. URLs always start with a “/” character and typically correspond to files on the HTTP Server. Common HTTP file extensions are shown below:

Extension	Meaning
.htm (or .html)	Hypertext Markup Language (HTML)
.txt	Plain ASCII text
.gif	Binary GIF image
.xbm	Binary Xbitmap image

HTTP Client Requests

The HTTP has a simple mechanism for requesting Web content. There is basically a set of standard HTTP commands that are issued by the Client after a connection has been successfully established on the TCP *well-known port 80*. The following shows some of the basic HTTP commands:

HTTP Command	Meaning
GET resource HTTP/1.0	<i>Get the specified resource</i>
POST resource HTTP/1.0	<i>Get the specified resource and pass attached input to the HTTP Server</i>
HEAD resource HTTP/1.0	<i>Treated like a GET but not content is returned by the HTTP Server</i>
PUT resource HTTP/1.0	<i>Place resource on HTTP Server</i>
DELETE resource HTTP/1.0	<i>Delete resource on the Server</i>

These ASCII commands are generated internally by Web browsers and the NetX HTTP Client services to perform HTTP operations with an HTTP Server.

Note that the HTTP Client application default to the connect port of 80. However, it can change the connect port to the HTTP Server at runtime using the *nx_http_client_set_connect_port* service. See Chapter 4 for more details of this service. This is to accommodate web servers that occasionally use alternate ports for Client connections.

HTTP Server Responses

The HTTP Server utilizes the same *well-known TCP port 80* to send Client command responses. Once the HTTP Server processes the Client command, it returns an ASCII response string that includes a 3-digit numeric status code. The numeric response is used by the HTTP Client software to determine whether the operation succeeded or failed. Following is a list of various HTTP Server responses to Client commands:

Numeric Field	Meaning
200	<i>Request was successful</i>
400	<i>Request was not formed properly</i>
401	<i>Unauthorized request, client needs to send authentication</i>
404	<i>Specified resource in request was not found</i>
500	<i>Internal HTTP Server error</i>
501	<i>Request not implemented by HTTP Server</i>
502	<i>Service is not available</i>

For example, a successful Client request to PUT the file “test.htm” is responded with the message “HTTP/1.0 200 OK.”

HTTP Communication

As mentioned previously, the HTTP Server utilizes the *well-known TCP port 80* to field Client requests. HTTP Clients may use any available TCP port. The general sequence of HTTP events is as follows:

HTTP GET Request:

1. Client issues TCP connect to Server port 80.
2. Client sends “**GET resource HTTP/1.0**” request (along with other header information).
3. Server builds an “**HTTP/1.0 200 OK**” message with additional information followed immediately by the resource content (if any).
4. Server performs a disconnection.
5. Client performs a disconnection.

HTTP PUT Request:

1. Client issues TCP connect to Server port 80.
2. Client sends “**PUT resource HTTP/1.0**” request, along with other header information, and followed by the resource content.
3. Server builds an “**HTTP/1.0 200 OK**” message with additional information followed immediately by the resource content.
4. Server performs a disconnection.
5. Client performs a disconnection.

Note: as mentioned previously, the HTTP Client can change the default connect port from 80 to another port using the `nx_http_client_set_connect_port` for web servers that use alternate ports to connect to clients.

HTTP Authentication

HTTP authentication is optional and isn't required for all Web requests. There are two flavors of authentication, namely *basic* and *digest*. Basic authentication is equivalent to the *name* and *password* authentication found in many protocols. In HTTP basic authentication, the name and passwords are concatenated and encoded in the base64 format. The main disadvantage of basic authentication is the name and password are transmitted openly in the request. This makes it somewhat easy for the name and password to be stolen. Digest authentication addresses this problem by never transmitting the name and password in the request. Instead, an algorithm is used to derive a 128-bit key or digest from the name, password, and other information. The NetX HTTP Server supports the standard MD5 digest algorithm.

When is authentication required? Basically, the HTTP Server decides if a requested resource requires authentication. If authentication is required and the Client request did not include the proper authentication, a “HTTP/1.0 401 Unauthorized” response with the type of authentication required is sent to the Client. The Client is then expected to form a new request with the proper authentication.

HTTP Authentication Callback

As mentioned before, HTTP authentication is optional and isn’t required on all Web transfers. In addition, authentication is typically resource dependent. Access of some resources on the Server require authentication, while others do not. The NetX HTTP Server package allows the application to specify (via the `nx_http_server_create` call) an authentication callback routine that is called at the beginning of handling each HTTP Client request.

The callback routine provides the NetX HTTP Server with the username, password, and realm strings associated with the resource and return the type of authentication necessary. If no authentication is necessary for the resource, the authentication callback should return the value of **NX_HTTP_DONT_AUTHENTICATE**. Otherwise, if basic authentication is required for the specified resource, the routine should return **NX_HTTP_BASIC_AUTHENTICATE**. And finally, if MD5 digest authentication is required, the callback routine should return **NX_HTTP_DIGEST_AUTHENTICATE**. If no authentication is required for any resource provided by the HTTP Server, the callback is not needed and a NULL pointer can be provided to the HTTP Server create call.

The format of the application authenticate callback routine is very simple and is defined below:

```
UINT nx_http_server_authentication_check(NX_HTTP_SERVER *server_ptr,
                                         UINT request_type, CHAR *resource,
                                         CHAR **name, CHAR **password,
                                         CHAR **realm);
```

The input parameters are defined as follows:

Parameter	Meaning
<i>request_type</i>	Specifies the HTTP Client request, valid requests are defined as: NX_HTTP_SERVER_GET_REQUEST NX_HTTP_SERVER_POST_REQUEST NX_HTTP_SERVER_HEAD_REQUEST

NX_HTTP_SERVER_PUT_REQUEST NX_HTTP_SERVER_DELETE_REQUEST

<i>resource</i>	Specific resource requested.
<i>name</i>	Destination for the pointer to the required username.
<i>password</i>	Destination for the pointer to the required password.
<i>realm</i>	Destination for the pointer to the realm for this authentication.

The return value of the authentication routine specifies if authentication is required. *name*, *password*, and *realm* pointers are not used if **NX_HTTP_DONT_AUTHENTICATE** is returned by the authentication callback routine. Otherwise the HTTP server developer must ensure that **NX_HTTP_MAX_USERNAME** and **NX_HTTP_MAX_PASSWORD** defined in *nx_http_server.h* are large enough for the username and password specified in the authentication callback. These are both defaulted to size 20 chars.

HTTP Invalid Username/Password Callback

The optional invalid username/password callback in NetX HTTP Server is invoked if HTTP server receives an invalid username and password combination in a Client request. If the HTTP server application registers a callback with HTTP server it will be invoked if either basic or digest authentication fails in *nx_http_server_get_process*, in *nx_http_server_put_process*, or in *nx_http_server_delete_process*.

To register a callback with the HTTP server, the following service is defined in NetX HTTP Server.

```
UINT nx_http_server_invalid_userpassword_notify_set(
    NX_HTTP_SERVER *http_server_ptr,
    UINT *invalid_username_password_callback)
    (CHAR *resource,
     ULONG *client_nx_address,
     UINT request_type)
```

The request types are defined as follows:

There is an optional callback in NetX HTTP Server to insert a date header in its response messages. This callback is invoked when the HTTP Server is responding to a put or get request

```
UINT _nx_http_server_gmt_callback_set(
    NX_HTTP_SERVER *server_ptr,
    VOID (*gmt_get)(NX_HTTP_SERVER DATE *date)
```

```
typedef struct NX_HTTP_SERVER_DATE_STRUCT
{
    USHORT          nx_http_server_year;           /* Year */
    UCHAR           nx_http_server_month;          /* Month */
    UCHAR           nx_http_server_day;            /* Day */
    UCHAR           nx_http_server_hour;           /* Hour */
    UCHAR           nx_http_server_minute;         /* Minute */
    UCHAR           nx_http_server_second;         /* Second */
    UCHAR           nx_http_server_weekday;        /* Weekday */
} NX_HTTP_SERVER_DATE;
```

The HTTP Server has a callback to request the max age and date from the HTTP application for a specific resource. This information is used to determine if the HTTP server sends the entire page in response to a Client Get request. If the “if modified since” in the Client request is not found or does not match the “last modified” date returned by the get cache callback, the entire page is sent.

```
UINT _nx_http_server_cache_info_callback_set(
    NX_HTTP_SERVER *server_ptr,
    UINT (*cache_info_get)
```

```
(CHAR *, UINT *, NX_HTTP_SERVER_DATE *) )
```

HTTP Multipart Support

Multipurpose Internet Mail Extensions (MIME) was originally intended for the SMTP protocol, but its use has spread to HTTP. MIME allows messages to contain mixed message types (e.g. image/jpg and text/plain) within the same message. NetX HTTP Server has added services to determine content type in HTTP messages containing MIME from the Client. To enable HTTP multipart support and use these services, the configuration option **NX_HTTP_MULTIPART_ENABLE** must be defined.

```
UINT nx_http_server_get_entity_header(NX_HTTP_SERVER *server_ptr,
                                      NX_PACKET **packet_pptr,
                                      UCHAR *entity_header_buffer,
                                      ULONG buffer_size);

UINT nx_http_server_get_entity_content(NX_HTTP_SERVER *server_ptr,
                                       NX_PACKET **packet_pptr,
                                       ULONG *available_offset,
                                       ULONG *available_length)
```

For more details on the use of these services, see their description in Chapter 3 “Description of HTTP Services”.

HTTP Multi-Thread Support

The NetX HTTP Client services can be called from multiple threads simultaneously. However, read or write requests for a particular HTTP Client instance should be done in sequence from the same thread.

HTTP RFCs

NetX HTTP is compliant with RFC1945 “Hypertext Transfer Protocol/1.0”, RFC 2581 “TCP Congestion Control”, RFC 1122 “Requirements for Internet Hosts”, and related RFCs.

Chapter 2

Installation and Use of HTTP

This chapter contains a description of various issues related to installation, setup, and usage of the NetX HTTP component.

Product Distribution

HTTP for NetX is shipped on a single CD-ROM compatible disk. The package includes three source files, two include files, and a file that contains this document, as follows:

<code>nx_http_client.h</code>	Header file for HTTP Client for NetX
<code>nx_http_server.h</code>	Header file for HTTP Server for NetX
<code>nx_http_client.c</code>	C Source file for HTTP Client for NetX
<code>nx_http_server.c</code>	C Source file for HTTP Server for NetX
<code>nx_md5.c</code>	MD5 digest algorithms
<code>filex_stub.h</code>	Stub file if FileX is not present
<code>nx_http.pdf</code>	Description of HTTP for NetX
<code>demo_netx_http.c</code>	NetX HTTP demonstration

HTTP Installation

In order to use HTTP for NetX, the entire distribution mentioned previously should be copied to the same directory where NetX is installed. For example, if NetX is installed in the directory “*\threadx\arm7\green*” then the *nx_http_client.h* and *nx_http_client.c* for NetX HTTP Client applications, and *nx_http_server.h* and *nx_http_server.c* for NetX HTTP Server applications. *nx_md5.c* should be copied into this directory. For the demo ‘ram driver’ application NetX HTTP Client and Server files should be copied into the same directory.

Using HTTP

Using HTTP for NetX is easy. Basically, the application code must include *nx_http_client.h* and/or *nx_http_server.h* after it includes *tx_api.h*, *fx_api.h*, and *nx_api.h*, in order to use ThreadX, FileX, and NetX, respectively. Once the HTTP header files are included, the application code is then able to make the HTTP function calls specified later in this guide. The

application must also include *nx_http_client.c*, *nx_http_server.c*, and *md5.c* in the build process. These files must be compiled in the same manner as other application files and its object form must be linked along with the files of the application. This is all that is required to use NetX HTTP.

Note that if `NX_HTTP_DIGEST_ENABLE` is not specified in the build process, the *md5.c* file does not need to be added to the application. Similarly, if no HTTP Client capabilities are required, the *nx_http_client.c* file may be omitted.

Note also that since HTTP utilizes NetX TCP services, TCP must be enabled with the *nx_tcp_enable* call prior to using HTTP.

Small Example System

An example of how easy it is to use NetX HTTP is described in Figure 1.1 that appears below. In this example, the HTTP include file *nx_http_client.h* and *nx_http_server.h* are brought in at line 8. Next, the HTTP Server is created in “*tx_application_define*” at line 131. Note that the HTTP Server control block “*Server*” was defined as a global variable at line 25 previously. After successful creation, an HTTP Server is started at line 136. At line 149 the HTTP Client is created. And finally, the Client writes the file at line 157 and reads the file back at line 195.

```

001 /* This is a small demo of HTTP on the high-performance NetX TCP/IP stack.
002    This demo relies on ThreadX, NetX, and FileX to show a simple HTML
003    transfer from the client and then back from the server. */
004
005 #include "tx_api.h"
006 #include "fx_api.h"
007 #include "nx_api.h"
008 #include "nx_http_client.h"
009 #include "nx_http_server.h"
010 #define DEMO_STACK_SIZE 4096
011
012
013 /* Define the ThreadX and NetX object control blocks... */
014
015 TX_THREAD thread_0;
016 TX_THREAD thread_1;
017 NX_PACKET_POOL pool_0;
018 NX_PACKET_POOL pool_1;
019 NX_IP ip_0;
020 NX_IP ip_1;
021 FX_MEDIA ram_disk;
022
023 /* Define HTTP objects. */
024
025 NX_HTTP_SERVER my_server;
026 NX_HTTP_CLIENT my_client;
027
028 /* Define the counters used in the demo application... */
029
030 ULONG error_counter;
031

```

```

032
033 /* Define the RAM disk memory. */
034
035 UCHAR          ram_disk_memory[32000];
036
037
038 /* Define function prototypes. */
039
040 void    thread_0_entry(ULONG thread_input);
041 VOID    _fx_ram_driver(FX_MEDIA *media_ptr) ;
042 void    _nx_ram_network_driver(struct NX_IP_DRIVER_STRUCT *driver_req);
043 UINT    authentication_check(NX_HTTP_SERVER *server_ptr, UINT request_type,
044                             CHAR *resource, CHAR **name, CHAR **password, CHAR **realm);
045
046 /* Define the application's authentication check. This is called by
047    the HTTP server whenever a new request is received. */
048 UINT    authentication_check(NX_HTTP_SERVER *server_ptr, UINT request_type,
049                             CHAR *resource, CHAR **name, CHAR **password, CHAR **realm)
050 {
051
052     /* Just use a simple name, password, and realm for all
053        requests and resources. */
054     *name = "name";
055     *password = "password";
056     *realm = "NetX HTTP demo";
057
058     /* Request basic authentication. */
059     return(NX_HTTP_BASIC_AUTHENTICATE);
060 }
061
062
063 /* Define main entry point. */
064
065 int main()
066 {
067
068     /* Enter the ThreadX kernel. */
069     tx_kernel_enter();
070 }
071
072
073 /* Define what the initial system looks like. */
074 void    tx_application_define(void *first_unused_memory)
075 {
076
077     CHAR    *pointer;
078
079
080     /* Setup the working pointer. */
081     pointer = (CHAR *) first_unused_memory;
082
083     /* Create the main thread. */
084     tx_thread_create(&thread_0, "thread 0", thread_0_entry, 0,
085                     pointer, DEMO_STACK_SIZE,
086                     2, 2, TX_NO_TIME_SLICE, TX_AUTO_START);
087     pointer = pointer + DEMO_STACK_SIZE;
088
089     /* Initialize the NetX system. */
090     nx_system_initialize();
091
092     /* Create packet pool. */
093     nx_packet_pool_create(&pool_0, "NetX Packet Pool 0",
094                          600, pointer, 8192);
095     pointer = pointer + 8192;
096
097     /* Create an IP instance. */
098     nx_ip_create(&ip_0, "NetX IP Instance 0", IP_ADDRESS(1, 2, 3, 4),
099                 0xFFFFF00UL, &pool_0, _nx_ram_network_driver,
100                 pointer, 4096, 1);
101     pointer = pointer + 4096;
102
103     /* Create another packet pool. */
104     nx_packet_pool_create(&pool_1, "NetX Packet Pool 1", 600, pointer, 8192);
105     pointer = pointer + 8192;
106
107     /* Create another IP instance. */
108     nx_ip_create(&ip_1, "NetX IP Instance 1", IP_ADDRESS(1, 2, 3, 5),
109                 0xFFFFF00UL, &pool_1, _nx_ram_network_driver,
110                 pointer, 4096, 1);
111     pointer = pointer + 4096;
112

```

```

113 /* Enable ARP and supply ARP cache memory for IP Instance 0. */
114 nx_arp_enable(&ip_0, (void *) pointer, 1024);
115 pointer = pointer + 1024;
116
117 /* Enable ARP and supply ARP cache memory for IP Instance 1. */
118 nx_arp_enable(&ip_1, (void *) pointer, 1024);
119 pointer = pointer + 1024;
120
121 /* Enable TCP processing for both IP instances. */
122 nx_tcp_enable(&ip_0);
123 nx_tcp_enable(&ip_1);
124
125 /* Open the RAM disk. */
126 fx_media_open(&ram_disk, "RAM DISK",
127 _fx_ram_driver, ram_disk_memory, pointer, 4096);
128 pointer += 4096;
129
130 /* Create the NetX HTTP Server. */
131 nx_http_server_create(&my_server, "My HTTP Server", &ip_1, &ram_disk,
132 pointer, 4096, &pool_1, authentication_check, NX_NULL);
133 pointer = pointer + 4096;
134
135 /* Start the HTTP Server. */
136 nx_http_server_start(&my_server);
137 }
138
139
140 /* Define the test thread. */
141 void thread_0_entry(ULONG thread_input)
142 {
143
144 NX_PACKET *my_packet;
145 UINT status;
146
147
148 /* Create an HTTP client instance. */
149 status = nx_http_client_create(&my_client, "My Client", &ip_0,
150 &pool_0, 600);
151
152 /* Check status. */
153 if (status)
154 error_counter++;
155
156 /* Prepare to send the simple 103-byte HTML file to the Server. */
157 status = nx_http_client_put_start(&my_client, IP_ADDRESS(1,2,3,5),
158 "/test.htm", "name", "password", 103, 50);
159
160 /* Check status. */
161 if (status)
162 error_counter++;
163
164 /* Allocate a packet. */
165 status = nx_packet_allocate(&pool_0, &my_packet, NX_TCP_PACKET,
166 NX_WAIT_FOREVER);
167
168 /* Check status. */
169 if (status != NX_SUCCESS)
170 return;
171
172 /* Build a simple 103-byte HTML page. */
173 nx_packet_data_append(my_packet, "<HTML>\r\n", 8,
174 &pool_0, NX_WAIT_FOREVER);
175 nx_packet_data_append(my_packet,
176 "<HEAD><TITLE>NetX HTTP Test</TITLE></HEAD>\r\n", 44,
177 &pool_0, NX_WAIT_FOREVER);
178 nx_packet_data_append(my_packet, "<BODY>\r\n", 8,
179 &pool_0, NX_WAIT_FOREVER);
180 nx_packet_data_append(my_packet, "<H1>NetX Test Page</H1>\r\n", 25,
181 &pool_0, NX_WAIT_FOREVER);
182 nx_packet_data_append(my_packet, "</BODY>\r\n", 9,
183 &pool_0, NX_WAIT_FOREVER);
184 nx_packet_data_append(my_packet, "</HTML>\r\n", 9,
185 &pool_0, NX_WAIT_FOREVER);
186
187 /* Complete the PUT by writing the total length. */
188 status = nx_http_client_put_packet(&my_client, my_packet, 50);
189
190 /* Check status. */
191 if (status)
192 error_counter++;
193

```

```

194      /* NOW GET the file back! */
195      status = nx_http_client_get_start(&my_client, IP_ADDRESS(1,2,3,5),
196                                     "/test.htm", NX_NULL, 0, "name", "password", 50);
197
198      /* Check status. */
199      if (status)
200          error_counter++;
201
202      /* Get a packet. */
203      status = nx_http_client_get_packet(&my_client, &my_packet, 20);
204
205      /* Check for an error. */
206      if ((status) || (my_packet -> nx_packet_length != 103))
207          error_counter++;
208
209      /* Check to see if we have a packet. */
210      if (status == NX_SUCCESS)
211      {
212
213          /* Yes, release it! */
214          nx_packet_release(my_packet);
215      }
216
217      /* Flush the media. */
218      fx_media_flush(&ram_disk);
219 }

```

Figure 1.1 Example of HTTP use with NetX

Configuration Options

There are several configuration options for building HTTP for NetX. Following is a list of all options, where each is described in detail. The default values are listed, but can be redefined prior to inclusion of *nx_http_client.h* and *nx_http_server.h*:

Define	Meaning
NX_DISABLE_ERROR_CHECKING	Defined, this option removes the basic HTTP error checking. It is typically used after the application has been debugged.
NX_HTTP_SERVER_PRIORITY	The priority of the HTTP Server thread. By default, this value is defined as 16 to specify priority 16.
NX_HTTP_NO_FILEX	Defined, this option provides a stub for FileX dependencies. The HTTP Client will function without any change if this option is defined. The HTTP Server will need to either be modified or the user will have to create a handful of FileX services in order to function properly.
NX_HTTP_TYPE_OF_SERVICE	Type of service required for the HTTP TCP requests. By default, this value is defined as NX_IP_NORMAL to indicate normal IP packet service.
NX_HTTP_SERVER_THREAD_TIME_SLICE	The number of timer ticks the Server thread is allowed to run before yielding to threads of the same priority. The default value is 2.
NX_HTTP_FRAGMENT_OPTION	Fragment enable for HTTP TCP requests. By default, this value is NX_DONT_FRAGMENT to disable HTTP TCP fragmenting.

NX_HTTP_SERVER_WINDOW_SIZE	Server socket window size. By default, this value is 2048 bytes.
NX_HTTP_TIME_TO_LIVE	Specifies the number of routers this packet can pass before it is discarded. The default value is set to 0x80.
NX_HTTP_SERVER_TIMEOUT	Specifies the number of ThreadX ticks that internal services will suspend for. The default value is set to 10 seconds (10 * NX_IP_PERIODIC_RATE).
NX_HTTP_SERVER_TIMEOUT_ACCEPT	Specifies the number of ThreadX ticks that internal services will suspend for in internal <i>nx_tcp_server_socket_accept</i> calls. The default value is set to (10 * NX_IP_PERIODIC_RATE).
NX_HTTP_SERVER_TIMEOUT_DISCONNECT	Specifies the number of ThreadX ticks that internal services will suspend for in internal <i>nx_tcp_socket_disconnect</i> calls. The default value is set to 10 seconds (10 * NX_IP_PERIODIC_RATE).
NX_HTTP_SERVER_TIMEOUT_RECEIVE	Specifies the number of ThreadX ticks that internal services will suspend for in internal <i>nx_tcp_socket_receive</i> calls. The default value is set to 10 seconds (10 * NX_IP_PERIODIC_RATE).
NX_HTTP_SERVER_TIMEOUT_SEND	Specifies the number of ThreadX ticks that internal services will

suspend for in internal *nx_tcp_socket_send* calls. The default value is set to 10 seconds (10 * NX_IP_PERIODIC_RATE).

NX_HTTP_MAX_HEADER_FIELD

Specifies the maximum size of the HTTP header field. The default value is 256.

NX_HTTP_MULTIPART_ENABLE

If defined, enables HTTP Server to support multipart HTTP requests.

NX_HTTP_SERVER_MAX_PENDING

Specifies the number of connections that can be queued for the HTTP Server. The default value is set to 5.

NX_HTTP_MAX_RESOURCE

Specifies the number of bytes allowed in a client supplied *resource name*. The default value is set to 40.

NX_HTTP_MAX_NAME

Specifies the number of bytes allowed in a client supplied *username*. The default value is set to 20.

NX_HTTP_MAX_PASSWORD

Specifies the number of bytes allowed in a client supplied *password*. The default value is set to 20.

NX_HTTP_SERVER_MIN_PACKET_SIZE

Specifies the minimum size of the packets in the pool specified at Server creation. The minimum size is needed to ensure the complete HTTP header can be contained in one packet. The default value is set to 600.

NX_HTTP_CLIENT_MIN_PACKET_SIZE

Specifies the minimum size of the packets in the pool specified at

Client creation. The minimum size is needed to ensure the complete HTTP header can be contained in one packet. The default value is set to 300.

NX_HTTP_SERVER_RETRY_SECONDS

Set the Server socket retransmission timeout in seconds. The default value is set to 2.

NX_HTTP_SERVER_RETRY_MAX

This sets the maximum number of retransmissions on Server socket. The default value is set to 10.

NX_HTTP_SERVER_RETRY_SHIFT

This value is used to set the next retransmission timeout. The current timeout is multiplied by the number of retransmissions thus far, shifted by the value of the socket timeout shift. The default value is set to 1 for doubling the timeout.

NX_HTTP_SERVER_RETRY_TRANSMIT_QUEUE_DEPTH

This specifies the maximum number of packets that can be enqueued on the Server socket retransmission queue. If the number of packets enqueued reaches this number, no more packets can be sent until one or more enqueued packets are released. The default value is set to 20.

Chapter 3

Description of HTTP Services

This chapter contains a description of all NetX HTTP services (listed below) in alphabetical order.

In the “Return Values” section in the following API descriptions, values in **BOLD** are not affected by the **NX_DISABLE_ERROR_CHECKING** define that is used to disable API error checking, while non-bold values are completely disabled.

HTTP Client services:

`nx_http_client_create`
Create an HTTP Client Instance

`nx_http_client_delete`
Delete an HTTP Client instance

`nx_http_client_get_start`
Start an HTTP GET request

`nx_http_client_get_packet`
Get next resource data packet

`nx_http_client_put_start`
Start an HTTP PUT request

`nx_http_client_put_packet`
Send next resource data packet

`nx_http_client_set_connect_port`
Change the port to connect to the HTTP Server

HTTP Server services:

`nx_http_server_cache_info_callback_set`
Set callback to retrieve age and last modified date of specified URL

`nx_http_server_callback_data_send`
Send HTTP data from callback function

`nx_http_server_callback_generate_response_header`
Create response header in callback functions

`nx_http_server_callback_packet_send`
Send an HTTP packet from an HTTP callback

`nx_http_server_callback_response_send`
Send response from callback function

`nx_http_server_content_get`
Get content from the request

`nx_http_server_content_get_extended`
Get content from the request; supports empty (zero Content Length) requests

`nx_http_server_content_length_get`
Get length of content in the request

`nx_http_server_content_length_get_extended`
Get length of content in the request; supports empty (zero Content Length) requests

`nx_http_server_create`
Create an HTTP Server instance

`nx_http_server_delete`
Delete an HTTP Server instance

`nx_http_server_get_entity_content`
Return size and location of entity content in URL

`nx_http_server_get_entity_header`
Extract URL entity header into specified buffer

`nx_http_server_gmt_callback_set`
Set callback to retrieve GMT date and time

`nx_http_server_invalid_userpassword_notify_set`
Set callback for when invalid username and password is received in a Client request

`nx_http_server_mime_maps_additional_set`
Define additional mime maps for HTML

`nx_http_server_packet_content_find`

*Extract content length in HTTP header
and set pointer to start of content data*

`nx_http_server_packet_get`
Receive client packet directly

`nx_http_server_param_get`
Get parameter from the request

`nx_http_server_query_get`
Get query from the request

`nx_http_server_start`
Start the HTTP Server

`nx_http_server_stop`
Stop the HTTP Server

`nx_http_server_type_get`
Extract HTTP type e.g. text/plain from header

nx_http_client_create

Create an HTTP Client Instance

Prototype

```
UINT nx_http_client_create(NX_HTTP_CLIENT *client_ptr,
                          CHAR *client_name, NX_IP *ip_ptr, NX_PACKET_POOL *pool_ptr,
                          ULONG window_size);
```

Description

This service creates an HTTP Client instance on the specified IP instance.

Input Parameters

client_ptr	Pointer to HTTP Client control block.
client_name	Name of HTTP Client instance.
ip_ptr	Pointer to IP instance.
pool_ptr	Pointer to default packet pool. Note that the packets in this pool must have a payload large enough to handle the complete response header. This is defined by NX_HTTP_CLIENT_MIN_PACKET_SIZE in <i>nx_http_client.h</i> .
window_size	Size of the Client's TCP socket receive window.

Return Values

NX_SUCCESS	(0x00)	Successful HTTP Client create
NX_PTR_ERROR	(0x16)	Invalid HTTP, ip_ptr, or packet pool pointer
NX_HTTP_POOL_ERROR(0xE9)		Invalid payload size in packet pool

Allowed From

Initialization, Threads

Example

```
/* Create the HTTP Client instance "my_client" on "ip_0". */  
status = nx_http_client_create(&my_client, "my client", &ip_0, &pool_0, 100);  
  
/* If status is NX_SUCCESS an HTTP Client instance was successfully  
   created. */
```

nx_http_client_delete

Delete an HTTP Client Instance

Prototype

```
UINT nx_http_client_delete(NX_HTTP_CLIENT *client_ptr);
```

Description

This service deletes a previously created HTTP Client instance.

Input Parameters

client_ptr Pointer to HTTP Client control block.

Return Values

NX_SUCCESS	(0x00)	Successful HTTP Client delete
NX_PTR_ERROR	(0x16)	Invalid HTTP pointer
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```
/* Delete the HTTP Client instance "my_client." */
status = nx_http_client_delete(&my_client);

/* If status is NX_SUCCESS an HTTP Client instance was successfully
   deleted. */
```

nx_http_client_get_start

Start an HTTP GET request

Prototype

```
UINT nx_http_client_get_start(NX_HTTP_CLIENT *client_ptr,
                             ULONG ip_address, CHAR *resource, CHAR *input_ptr,
                             UINT input_size, CHAR *username, CHAR *password,
                             ULONG wait_option);
```

Description

This service attempts to GET the resource specified by “resource” pointer on the previously created HTTP Client instance. If this routine returns NX_SUCCESS, the application can then make multiple calls to *nx_http_client_get_packet* to retrieve packets of data corresponding to the requested resource content.

Note that the resource string can refer to a local file e.g. “/index.htm” or it can refer to another URL e.g. <http://abc.website.com/index.htm> if the HTTP Server indicates it supports referring GET requests.

Input Parameters

client_ptr	Pointer to HTTP Client control block.
ip_address	IP address of the HTTP Server.
resource	Pointer to URL string for requested resource.
input_ptr	Pointer to additional data for the GET request. This is optional. If valid, the specified input is placed in the content area of the message and a POST is used instead of a GET operation.
input_size	Number of bytes in optional additional input pointed to by input_ptr.
username	Pointer to optional user name for authentication.
password	Pointer to optional password for authentication.
wait_option	Defines how long the service will wait for the HTTP Client get start request. The wait options are defined as follows:

time out value (0x00000001 through 0xFFFFFFFF)
TX_WAIT_FOREVER (0xFFFFFFFF)

Selecting TX_WAIT_FOREVER causes the calling thread to suspend indefinitely until the HTTP Server responds to the request.

Selecting a numeric value (0x1-0xFFFFFFFF) specifies the maximum number of timer-ticks to stay suspended while waiting for the HTTP Server response.

Return Values

NX_SUCCESS	(0x00)	Successfully sent HTTP Client GET start message
NX_HTTP_ERROR	(0xE0)	Internal HTTP Client error
NX_HTTP_NOT_READY	(0xEA)	HTTP Client not ready
NX_HTTP_FAILED	(0xE2)	HTTP Client error communicating with the HTTP Server.
NX_HTTP_AUTHENTICATION_ERROR	(0xEB)	Invalid name and/or password.
NX_PTR_ERROR	(0x07)	Invalid pointer input
NX_CALLER_ERROR	(0x11)	Invalid caller of this service.

Allowed From

Threads

Example

```
/* Start the GET operation on the HTTP Client "my_client." */
status = nx_http_client_get_start(&my_client, IP_ADDRESS(1,2,3,5), "/TEST.HTM",
                                NX_NULL, 0, "myname", "mypassword", 1000);

/* If status is NX_SUCCESS, the GET request for TEST.HTM is started and is so
   far successful. The client must now call nx_http_client_get_packet multiple
   times to retrieve the content associated with TEST.HTM. */

#define POST_MESSAGE "Add this data to the message content"

/* Start the POST operation on the HTTP Client "my_client." */
status = nx_http_client_get_start(&my_client, IP_ADDRESS(1,2,3,5), "/TEST.HTM",
                                POST_MESSAGE, strlen(POST_MESSAGE) + 1,
                                "myname", "mypassword", 1000);

/* If status is NX_SUCCESS, the POST_MESSAGE is added to the message in the POST request
   for TEST.HTM and successfully sent. */
```


nx_http_client_get_packet

Get next resource data packet

Prototype

```
UINT nx_http_client_get_packet(NX_HTTP_CLIENT *client_ptr,
                              NX_PACKET **packet_ptr, ULONG
                              wait_option);
```

Description

This service retrieves the next packet of content of the resource requested by the previous *nx_http_client_get_start* call. Successive calls to this routine should be made until the return status of NX_HTTP_GET_DONE is received.

Input Parameters

client_ptr	Pointer to HTTP Client control block.
packet_ptr	Destination for packet pointer containing partial resource content.
wait_option	Defines how long the service will wait for the HTTP Client get packet. The wait options are defined as follows: timeout value (0x00000001 through 0xFFFFFFFF) TX_WAIT_FOREVER (0xFFFFFFFF) Selecting TX_WAIT_FOREVER causes the calling thread to suspend indefinitely until the HTTP Server responds to the request. Selecting a numeric value (0x1-0xFFFFFFFF) specifies the maximum number of timer-ticks to stay suspended while waiting for the HTTP Server response.

Return Values

NX_SUCCESS	(0x00)	Successful HTTP Client get packet.
-------------------	--------	------------------------------------

NX_HTTP_GET_DONE	(0xEC)	HTTP Client get packet is done
NX_HTTP_NOT_READY	(0xEA)	HTTP Client not in get mode.
NX_HTTP_BAD_PACKET_LENGTH	(0xED)	Invalid packet length
NX_PTR_ERROR	(0x07)	Invalid pointer input
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```

/* Get the next packet of resource content on the HTTP Client "my_client."
   Note that the nx_http_client_get_start routine must have been called
   previously. */
status = nx_http_client_get_packet(&my_client, &next_packet, 1000);

/* If status is NX_SUCCESS, the next packet of content is pointed to
   by "next_packet". */

```

nx_http_client_put_start

Start an HTTP PUT request

Prototype

```
UINT nx_http_client_put_start(NX_HTTP_CLIENT *client_ptr,
                             ULONG ip_address, CHAR *resource,
                             CHAR *username, CHAR *password,
                             ULONG total_bytes, ULONG wait_option);
```

Description

This service attempts to send a PUT request with the specified resource to the HTTP Server at the supplied IP address. If this routine is successful, the application code should make successive calls to the *nx_http_client_put_packet* routine to actually send the resource contents to the HTTP Server.

Note that the resource string can refer to a local file e.g. “/index.htm” or it can refer to another URL e.g. <http://abc.website.com/index.htm> if the HTTP Server indicates it supports referring PUT requests.

Input Parameters

client_ptr	Pointer to HTTP Client control block.				
ip_address	IP address of the HTTP Server.				
resource	Pointer to URL string for resource to send to Server.				
username	Pointer to optional user name for authentication.				
password	Pointer to optional password for authentication.				
total_bytes	Total bytes of resource being sent. Note that the combined length of all packets sent via subsequent calls to <i>nx_http_client_put_packet</i> must equal this value.				
wait_option	Defines how long the service will wait for the HTTP Client PUT start. The wait options are defined as follows: <table data-bbox="613 1774 1247 1890"> <tr> <td>timeout value</td><td>(0x00000001 through 0xFFFFFFFF)</td></tr> <tr> <td>TX_WAIT_FOREVER</td><td>(0xFFFFFFFF)</td></tr> </table>	timeout value	(0x00000001 through 0xFFFFFFFF)	TX_WAIT_FOREVER	(0xFFFFFFFF)
timeout value	(0x00000001 through 0xFFFFFFFF)				
TX_WAIT_FOREVER	(0xFFFFFFFF)				

Selecting TX_WAIT_FOREVER causes the calling thread to suspend indefinitely until the HTTP Server responds to the request.

Selecting a numeric value (0x1-0xFFFFFFFF) specifies the maximum number of timer-ticks to stay suspended while waiting for the HTTP Server response.

Return Values

NX_SUCCESS	(0x00)	Successfully sent PUT request
NX_HTTP_USERNAME_TOO_LONG	(0xF1)	Username too large for buffer
NX_HTTP_NOT_READY	(0xEA)	HTTP Client not ready
NX_PTR_ERROR	(0x07)	Invalid pointer input
NX_SIZE_ERROR	(0x09)	Invalid total size of resource
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```
/* Start an HTTP PUT to place the 20-byte resource "/TEST.HTM" on the HTTP Server
   at IP address 1.2.3.5. */
status = nx_http_client_put_start(&my_client, IP_ADDRESS(1, 2, 3, 5),
                                  "/TEST.HTM", "myname", "mypassword", 20, NX_WAIT_FOREVER);

/* If status is NX_SUCCESS, the PUT operation for TEST.HTM has successfully been
   started. */
```

nx_http_client_put_packet

Send next resource data packet

Prototype

```
UINT nx_http_client_put_packet(NX_HTTP_CLIENT *client_ptr,
                               NX_PACKET *packet_ptr,
                               ULONG wait_option);
```

Description

This service attempts to send the next packet of resource content to the HTTP Server. Note that this routine should be called repetitively until the combined length of the packets sent equals the “total_bytes” specified in the previous *nx_http_client_put_start* call.

Input Parameters

client_ptr	Pointer to HTTP Client control block.
packet_ptr	Pointer to next content of the resource to being sent to the HTTP Server.
wait_option	Defines how long the service will wait internally to process the HTTP Client PUT packet. The wait options are defined as follows: <div style="margin-left: 20px;"> <p>timeout value (0x00000001 through 0xFFFFFFFF)</p> <p>TX_WAIT_FOREVER (0xFFFFFFFF)</p> <p>Selecting TX_WAIT_FOREVER causes the calling thread to suspend indefinitely until the HTTP Server responds to the request.</p> <p>Selecting a numeric value (0x1-0xFFFFFFFF) specifies the maximum number of timer-ticks to stay suspended while waiting for the HTTP Server response.</p> </div>

Return Values

NX_SUCCESS	(0x00)	Successfully sent HTTP Client packet.
-------------------	--------	---------------------------------------

NX_HTTP_NOT_READY	(0xEA)	HTTP Client not ready
NX_HTTP_REQUEST_UNSUCCESSFUL_CODE		
	(0xEE)	Received Server error code
NX_HTTP_BAD_PACKET_LENGTH		
	(0xED)	Invalid packet length
NX_HTTP_AUTHENTICATION_ERROR	(0xEB)	Invalid name and/or Password
NX_HTTP_INCOMPLETE_PUT_ERROR		
	(0xEF)	Server responds before PUT Is complete
NX_PTR_ERROR	(0x07)	Invalid pointer input
NX_INVALID_PACKET	(0x12)	Packet too small for TCP header
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```

/* Send a 20-byte packet representing the content of the resource
   "/TEST.HTM" to the HTTP Server. */
status = nx_http_client_put_packet(NX_HTTP_CLIENT *client_ptr, NX_PACKET
*packet_ptr, ULONG wait_option);

/* If status is NX_SUCCESS, the 20-byte resource contents of TEST.HTM has
   successfully been sent. */

```

nx_http_client_set_connect_port

Set the connection port to the Server

Prototype

```
UINT nx_http_client_set_connect_port(NX_HTTP_CLIENT *client_ptr,
                                     UINT port);
```

Description

This service changes the connect port when connecting to the HTTP Server to the specified port at runtime. Otherwise the connect port defaults to 80. This must be called before *nx_http_client_get_start()* and *nx_http_client_put_start()* e.g. when the HTTP Client connects with the Server.

Input Parameters

client_ptr	Pointer to HTTP Client control block.
port	Port for connecting to the Server.

Return Values

NX_SUCCESS	(0x00)	Successfully changed the connect port
NX_INVALID_PORT	(0x46)	Port exceeds the maximum (0xFFFF) or is zero.
NX_PTR_ERROR	(0x07)	Invalid pointer input

Allowed From

Threads, Initialization

Example

```
NX_HTTP_CLIENT *client_ptr;

/* Change the connect port to 114. */
status = nx_http_client_set_connect_port(client_ptr, 114);

/* If status is NX_SUCCESS, the connect port is successfully changed. */
```

nx_http_server_cache_info_callback_set

Set the callback to retrieve URL max age and date

Prototype

```
UINT nx_http_server_cache_info_callback_set(NX_HTTP_SERVER *server_ptr,
      UINT (*cache_info_get)(CHAR *resource,
                             UINT *max_age,
                             NX_HTTP_SERVER_DATE
                             *date));
```

Description

This service sets the callback service invoked to obtain the maximum age and last modified date of the specified resource.

Input Parameters

server_ptr	Pointer to HTTP Server control block.
cache_info_get	Pointer to the callback
max_age	Pointer to maximum age of a resource
data	Pointer to last modified date returned.

Return Values

NX_SUCCESS	(0x00)	Successfully set the callback
NX_PTR_ERROR	(0x07)	Invalid pointer input

Allowed From

Initialization

Example

```
NX_HTTP_SERVER my_server;

UINT cache_info_get(CHAR *resource, UINT *max_age,
                    NX_HTTP_SERVER_DATE *last_modified);

/* After my_server is created with nx_http_server_create and before the HTTP
   server is set by nx_http_server_start(), set the cache info callback: */
status = nx_http_server_cache_info_callback_set(&my_server, cache_info_get);

/* If status is NX_SUCCESS, the callback was successfully sent. */
```

nx_http_server_callback_data_send

Send data from callback function

Prototype

```
UINT nx_http_server_callback_data_send(NX_HTTP_SERVER *server_ptr,
                                       VOID *data_ptr,
                                       ULONG data_length);
```

Description

This service sends the data in the supplied packet from the application's callback routine. This is typically used to send dynamic data associated with GET/POST requests. Note that if this function is used, the callback routine is responsible for sending the entire response in the proper format. In addition, the callback routine must return the status of NX_HTTP_CALLBACK_COMPLETED.

Input Parameters

server_ptr	Pointer to HTTP Server control block.
data_ptr	Pointer to the data to send.
data_length	Number of bytes to send.

Return Values

NX_SUCCESS	(0x00)	Successfully sent Server data
NX_PTR_ERROR	(0x07)	Invalid pointer input

Allowed From

Threads

Example

```
UINT my_request_notify(NX_HTTP_SERVER *server_ptr, UINT request_type,
                      CHAR *resource, NX_PACKET *packet_ptr)
{
    /* Look for the test resource! */
    if ((request_type == NX_HTTP_SERVER_GET_REQUEST) &&
        (strcmp(resource, "/test.htm") == 0))
    {
        /* Found it, override the GET processing by sending the resource
           contents directly. */
    }
}
```

```

nx_http_server_callback_data_send(server_ptr,
    "HTTP/1.0 200 \r\nContent-Length:
    103\r\nContent-Type: text/html\r\n\r\n",
    63);

nx_http_server_callback_data_send(server_ptr, "<HTML>\r\n<HEAD><TITLE>NetX
    HTTP Test </TITLE></HEAD>\r\n
    <BODY>\r\n<H1>NetX Test Page
    </H1>\r\n</BODY>\r\n</HTML>\r\n", 103);

    /* Return completion status. */
    return(NX_HTTP_CALLBACK_COMPLETED);
}

return(NX_SUCCESS);
}

```

nx_http_server_callback_generate_response_header

Create a response header in a callback function

Prototype

```
UINT nx_http_server_callback_generate_response_header(
    NX_HTTP_SERVER *server_ptr,
    NX_PACKET **packet_pptr,
    CHAR *status_code, UINT content_length,
    CHAR *content_type, CHAR* additional_header);
```

Description

This service calls the internal function *_nx_http_server_generate_response_header* when the HTTP server responds to Client get, put and delete requests. It is intended for use in HTTP server callback functions when the HTTP server application is designing its response to the Client.

Input Parameters

server_ptr	Pointer to HTTP Server control block.
packet_pptr	Pointer a packet pointer allocated for message
status_code	Indicate status of resource. Examples: NX_HTTP_STATUS_OK NX_HTTP_STATUS_MODIFIED NX_HTTP_STATUS_INTERNAL_ERROR
content_length	Size of content in bytes
content_type	Type of HTTP e.g. "text/plain"
additional_header	Pointer to additional header text

Return Values

NX_SUCCESS	(0x00)	Successfully created HTML header
NX_PTR_ERROR	(0x07)	Invalid pointer input

Allowed From

Threads

Example

```

CHAR demotestbuffer[] = "<html>\r\n\r\n<head>\r\n\r\n<title>Main  \
    window</title>\r\n</head>\r\n\r\n<body>Test message\r\n  \
    </body>\r\n</html>\r\n";

/* my_request_notify is the application request notify callback registered with
the HTTP server in nx_http_server_create, creates a response to the received
Client request. */

UINT my_request_notify(NX_HTTP_SERVER *server_ptr, UINT request_type,
    CHAR *resource, NX_PACKET *recv_packet_ptr)
{
    NX_PACKET *sresp_packet_ptr;
    ULONG string_length;
    CHAR temp_string[30];
    ULONG length = 0;

    length = strlen(&demotestbuffer[0]);

    /* Derive the client request type from the client request. */
    string_length = (ULONG) nx_http_server_type_get(server_ptr, server_ptr ->
        nx_http_server_request_resource, temp_string);

    /* Null terminate the string. */
    temp_string[temp] = 0;

    /* Now build a response header with server status is OK and no additional header
    info. */
    status = nx_http_server_callback_generate_response_header(http_server_ptr,
        &resp_packet_ptr, NX_HTTP_STATUS_OK,
        length, temp_string, NX_NULL);

    /* If status is NX_SUCCESS, the header was successfully appended. */

    /* Now add data to the packet. */
    status = nx_packet_data_append(resp_packet_ptr, &demotestbuffer[0],
        strlen(&demotestbuffer[0]), server_ptr ->
        nx_http_server_packet_pool_ptr, NX_WAIT_FOREVER);
    if (status != NX_SUCCESS)
    {
        nx_packet_release(resp_packet_ptr);
        return status;
    }

    /* Now send the packet! */
    status = nx_tcp_socket_send(&(server_ptr -> nx_http_server_socket),
        resp_packet_ptr, NX_HTTP_SERVER_TIMEOUT_SEND);

    if (status != NX_SUCCESS)
    {
        nx_packet_release(resp_packet_ptr);
        return status;
    }

    /* Let HTTP server know the response has been sent. */
    return NX_HTTP_CALLBACK_COMPLETED;
}

```

nx_http_server_callback_packet_send

Send an HTTP packet from callback function

Prototype

```
UINT nx_http_server_callback_packet_send(NX_HTTP_SERVER *server_ptr,
                                         NX_PACKET *packet_ptr);
```

Description

This service sends a complete HTTP server response from an HTTP callback. HTTP server will send the packet with the NX_HTTP_SERVER_TIMEOUT_SEND. The HTTP header and data must be appended to the packet. If the return status indicates an error, the HTTP application must release the packet.

The callback should return NX_HTTP_CALLBACK_COMPLETED.

See *nx_http_server_callback_generate_response_header* for a more detailed example.

Input Parameters

server_ptr	Pointer to HTTP Server control block
packet_ptr	Pointer to the packet to send

Return Values

NX_SUCCESS	(0x00)	Successfully sent HTTP Server packet
NX_PTR_ERROR	(0x07)	Invalid pointer input

Allowed From

Threads

Example

```
/* The packet is appended with HTTP header and data and is ready to send to the
   client directly. */
status = nx_http_server_callback_response_send(server_ptr, packet_ptr);
if (status != NX_SUCCESS)
{
```

```
        nx_packet_release(packet_ptr);  
    }  
    return(NX_HTTP_CALLBACK_COMPLETED);
```

nx_http_server_callback_response_send

Send response from callback function

Prototype

```
UINT nx_http_server_callback_response_send(NX_HTTP_SERVER *server_ptr,
                                           CHAR *header,
                                           CHAR *information,
                                           CHAR additional_info);
```

Description

This service sends the supplied response information from the application's callback routine. This is typically used to send custom responses associated with GET/POST requests. Note that if this function is used, the callback routine must return the status of NX_HTTP_CALLBACK_COMPLETED.

Input Parameters

server_ptr	Pointer to HTTP Server control block.
header	Pointer to the response header string.
information	Pointer to the information string.
additional_info	Pointer to the additional information string.

Return Values

NX_SUCCESS	(0x00)	Successfully sent HTTP Server response
-------------------	--------	--

Allowed From

Threads

Example

```

UINT my_request_notify(NX_HTTP_SERVER *server_ptr, UINT request_type,
                      CHAR *resource, NX_PACKET *packet_ptr)
{
    /* Look for the test resource! */
    if ((request_type == NX_HTTP_SERVER_GET_REQUEST) &&
        (strcmp(resource, "/test.htm") == 0))
    {
        /* In this example, we will complete the GET processing with
           a resource not found response. */
        nx_http_server_callback_response_send(server_ptr,
                                              "HTTP/1.0 404 ",
                                              "NetX HTTP Server unable to find
                                              file: ", resource);

        /* Return completion status. */
        return(NX_HTTP_CALLBACK_COMPLETED);
    }

    return(NX_SUCCESS);
}

```

nx_http_server_content_get

Get content from the request

Prototype

```
UINT nx_http_server_content_get(NX_HTTP_SERVER *server_ptr,
                                NX_PACKET *packet_ptr,
                                ULONG byte_offset,
                                CHAR *destination_ptr,
                                UINT destination_size,
                                UINT *actual_size);
```

Description

This service attempts to retrieve the specified amount of content from the POST or PUT HTTP Client request. It should be called from the application's request notify callback specified during HTTP Server creation (*nx_http_server_create*).

Input Parameters

server_ptr	Pointer to HTTP Server control block.
packet_ptr	Pointer to the HTTP Client request packet. Note that this packet must not be released by the request notify callback.
byte_offset	Number of bytes to offset into the content area.
destination_ptr	Pointer to the destination area for the content.
destination_size	Maximum number of bytes available in the destination area.
actual_size	Pointer to the destination variable that will be set to the actual size of the content copied.

Return Values

NX_SUCCESS	(0x00)	Successful HTTP Server content get
NX_HTTP_ERROR	(0xE0)	HTTP Server internal error
NX_HTTP_DATA_END	(0xE7)	End of request content
NX_HTTP_TIMEOUT	(0xE1)	HTTP Server timeout in getting next packet of content

NX_PTR_ERROR	(0x07)	Invalid pointer input
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```
/* Assuming we are in the application's request notify callback
   routine, retrieve up to 100 bytes of content starting at offset
   0. */
status = nx_http_server_content_get(&my_server, packet_ptr,
                                     0, my_buffer, 100, &actual_size);

/* If status is NX_SUCCESS, "my_buffer" contains "actual_size" bytes of
   request content. */
```

nx_http_server_content_get_extended

Get content from the request/supports zero length Content Length

Prototype

```
UINT nx_http_server_content_get_extended(NX_HTTP_SERVER *server_ptr,
                                         NX_PACKET *packet_ptr,
                                         ULONG byte_offset,
                                         CHAR *destination_ptr,
                                         UINT destination_size,
                                         UINT *actual_size);
```

Description

This service is almost identical to *nx_http_server_content_get*; it attempts to retrieve the specified amount of content from the POST or PUT HTTP Client request. However it handles requests with Content Length of zero value ('empty request') as a valid request. It should be called from the application's request notify callback specified during HTTP Server creation (*nx_http_server_create*).

Input Parameters

server_ptr	Pointer to HTTP Server control block.
packet_ptr	Pointer to the HTTP Client request packet. Note that this packet must not be released by the request notify callback.
byte_offset	Number of bytes to offset into the content area.
destination_ptr	Pointer to the destination area for the content.
destination_size	Maximum number of bytes available in the destination area.
actual_size	Pointer to the destination variable that will be set to the actual size of the content copied.

Return Values

NX_SUCCESS	(0x00)	Successful HTTP content get
NX_HTTP_ERROR	(0xE0)	HTTP Server internal error
NX_HTTP_DATA_END	(0xE7)	End of request content
NX_HTTP_TIMEOUT	(0xE1)	HTTP Server timeout in getting next packet

NX_PTR_ERROR	(0x07)	Invalid pointer input
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```
/* Assuming we are in the application's request notify callback
   routine, retrieve up to 100 bytes of content starting at offset
   0. */
status = nx_http_server_content_get_extended(&my_server, packet_ptr,
                                             0, my_buffer, 100, &actual_size);

/* If status is NX_SUCCESS, "my_buffer" contains "actual_size" bytes of
   request content. */
```

nx_http_server_content_length_get

Get length of content in the request

Prototype

```
UINT nx_http_server_content_length_get(NX_PACKET *packet_ptr);
```

Description

This service attempts to retrieve the HTTP content length in the supplied packet. If there is no HTTP content, this routine returns a value of zero. It should be called from the application's request notify callback specified during HTTP Server creation (*nx_http_server_create*).

Input Parameters

packet_ptr	Pointer to the HTTP Client request packet. Note that this packet must not be released by the request notify callback.
-------------------	---

Return Values

content length	On error, a value of zero is returned
-----------------------	---------------------------------------

Allowed From

Threads

Example

```
/* Assuming we are in the application's request notify callback
   routine, get the content length of the HTTP Client request. */
length = nx_http_server_content_length_get(packet_ptr);

/* The "length" variable now contains the length of the HTTP Client
   request content area. */
```

nx_http_server_content_length_get_extended

Get length of content in the request/supports Content Length of zero value

Prototype

```
UINT nx_http_server_content_length_get_extended(NX_PACKET *packet_ptr,
                                                UINT *content_length);
```

Description

This service is similar to *nx_http_server_content_length_get*; attempts to retrieve the HTTP content length in the supplied packet. However, the return value indicates successful completion status, and the actual length value is returned in the input pointer *content_length*. If there is no HTTP content/Content Length = 0, this routine still returns a successful completion status and the *content_length* input pointer points to a valid length (zero). It should be called from the application's request notify callback specified during HTTP Server creation (*nx_http_server_create*).

Input Parameters

packet_ptr	Pointer to the HTTP Client request packet. Note that this packet must not be released by the request notify callback.
content_length	Pointer to value retrieved from Content Length field

Return Values

NX_SUCCESS	(0x00)	Successful HTTP Server content get
NX_HTTP_INCOMPLETE_PUT_ERROR	(0xEF)	Improper HTTP header format
NX_PTR_ERROR	(0x07)	Invalid pointer input

Allowed From

Threads

Example

```
/* Assuming we are in the application's request notify callback
   routine, get the content length of the HTTP Client request. */
ULONG content_length;

status = nx_http_server_content_length_get_extended(packet_ptr, &content_length);
```

```
/* If the "status" variable indicates successful completion, the "length" variable  
contains the length of the HTTP Client request content area. */
```


nx_http_server_create

Create an HTTP Server instance

Prototype

```
UINT nx_http_server_create(NX_HTTP_SERVER *http_server_ptr,
    CHAR *http_server_name, NX_IP *ip_ptr, FX_MEDIA *media_ptr,
    VOID *stack_ptr, ULONG stack_size, NX_PACKET_POOL *pool_ptr,
    UINT (*authentication_check)(NX_HTTP_SERVER *server_ptr,
        UINT request_type, CHAR *resource, CHAR **name,
        CHAR **password, CHAR **realm),
    UINT (*request_notify)(NX_HTTP_SERVER *server_ptr,
        UINT request_type, CHAR *resource, NX_PACKET *packet_ptr));
```

Description

This service creates an HTTP Server instance, which runs in the context of its own ThreadX thread. The optional *authentication_check* and *request_notify* application callback routines give the application software control over the basic operations of the HTTP Server.

Input Parameters

http_server_ptr	Pointer to HTTP Server control block.
http_server_name	Pointer to HTTP Server's name.
ip_ptr	Pointer to previously created IP instance.
media_ptr	Pointer to previously created FileX media instance.
stack_ptr	Pointer to HTTP Server thread stack area.
stack_size	Pointer to HTTP Server thread stack size.
authentication_check	Function pointer to application's authentication checking routine. If specified, this routine is called for each HTTP Client request. If this parameter is NULL, no authentication will be performed.
request_notify	Function pointer to application's request notify routine. If specified, this routine is called prior to the HTTP server processing of the request. This allows the resource name to be redirected or fields within a resource to be updated prior to completing the HTTP Client request.

Return Values

NX_SUCCESS	(0x00)	Successful HTTP Server create.
NX_PTR_ERROR	(0x07)	Invalid HTTP Server, IP, media, stack, or packet pool pointer.
NX_HTTP_POOL_ERROR	(0xE9)	Packet payload of pool is not large enough to contain complete HTTP request.

Allowed From

Initialization, Threads

Example

```
/* Create an HTTP Server instance called "my_server." */
status = nx_http_server_create(&my_server, "my server", &ip_0, &ram_disk,
                               stack_ptr, stack_size, &pool_0,
                               my_authentication_check, my_request_notify);

/* If status equals NX_SUCCESS, the HTTP Server creation was successful. */
```

`nx_http_server_delete`

Delete an HTTP Server instance

Prototype

```
UINT nx_http_server_delete(NX_HTTP_SERVER *http_server_ptr);
```

Description

This service deletes a previously created HTTP Server instance.

Input Parameters

http_server_ptr Pointer to HTTP Server control block.

Return Values

NX_SUCCESS	(0x00)	Successful HTTP Server delete
NX_PTR_ERROR	(0x07)	Invalid HTTP Server pointer
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```
/* Delete the HTTP Server instance called "my_server." */
status = nx_http_server_delete(&my_server);

/* If status equals NX_SUCCESS, the HTTP Server delete was successful. */
```

nx_http_server_get_entity_content

Retrieve the location and length of entity data

Prototype

```
UINT nx_http_server_get_entity_content(NX_HTTP_SERVER *server_ptr,
                                       NX_PACKET **packet_pptr,
                                       ULONG *available_offset,
                                       ULONG *available_length);
```

Description

This service determines the location of the start of data within the current multipart entity in the received Client messages, and the length of data not including the boundary string. Internally HTTP server updates its own offsets so that this function can be called again on the same Client datagram for messages with multiple entities. The packet pointer is updated to the next packet where the Client message is a multi-packet datagram.

Note that NX_HTTP_MULTIPART_ENABLE must be enabled to use this service.

See *nx_http_server_get_entity_header* for more details.

Input Parameters

server_ptr	Pointer to HTTP Server
packet_pptr	Pointer to location of packet pointer
available_offset	Pointer to offset of entity data from the packet prepend pointer
available_length	Pointer to length of entity data

Return Values

NX_SUCCESS	(0x00)	Successfully retrieved size and location of entity content
NX_HTTP_BOUNDARY_ALREADY_FOUND	(0xF4)	Content for the HTTP server internal multipart markers is already found

NX_HTTP_ERROR	(0xE0)	HTTP Server internal error
NX_PTR_ERROR	(0x07)	Invalid pointer input

Allowed From

Threads

Example

```

NX_HTTP_SERVER my_server;

UINT          offset, length;
NX_PACKET    *packet_ptr;

/* Inside the request notify callback, the HTTP server application first obtains
   the entity header to determine details about the multipart data. If
   successful, it then calls this service to get the location of entity data: */
status = nx_http_server_get_entity_content(&my_server, &packet_ptr, *offset,
                                           &length);

/* If status equals NX_SUCCESS, offset and location determine the location of the
   entity data. */

```

nx_http_server_get_entity_header

Retrieve the contents of entity header

Prototype

```
UINT nx_http_server_get_entity_header(NX_HTTP_SERVER *server_ptr,
                                     NX_PACKET **packet_pptr,
                                     UCHAR *entity_header_buffer,
                                     ULONG buffer_size);
```

Description

This service retrieves the entity header into the specified buffer. Internally HTTP Server updates its own pointers to locate the next multipart entity in a Client datagram with multiple entity headers. The packet pointer is updated to the next packet where the Client message is a multi-packet datagram.

Note that NX_HTTP_MULTIPART_ENABLE must be enabled to use this service.

Input Parameters

server_ptr	Pointer to HTTP Server
packet_pptr	Pointer to location of packet pointer
entity_header_buffer	Pointer to location to store entity header
buffer_size	Size of input buffer

Return Values

NX_SUCCESS	(0x00)	Successfully retrieved entity header
NX_HTTP_NOT_FOUND	(0xE6)	Entity header field not found
NX_HTTP_TIMEOUT	(0xE1)	Time expired to receive next packet for multipacket client message
NX_PTR_ERROR	(0x07)	Invalid pointer input
NX_CALLER_ERROR	(0x11)	Invalid caller of this service
NX_HTTP_ERROR	(0xE0)	Internal HTTP error

Allowed From

Threads

Example

```

/* my_request_notify is the application request notify callback registered with
the HTTP server in nx_http_server_create, creates a response to the received
client request. */

UINT my_request_notify(NX_HTTP_SERVER *server_ptr, UINT request_type,
                      CHAR *resource, NX_PACKET *packet_ptr)
{
    NX_PACKET    *sresp_packet_ptr;
    UINT         offset, length;
    NX_PACKET    *response_pkt;
    UCHAR        buffer[1440];

    /* Process multipart data. */
    if(request_type == NX_HTTP_SERVER_POST_REQUEST)
    {
        /* Get the content header. */
        while(nx_http_server_get_entity_header(server_ptr, &packet_ptr, buffer,
                                              sizeof(buffer)) == NX_SUCCESS)
        {
            /* Header obtained successfully. Get the content data location. */
            while(nx_http_server_get_entity_content(server_ptr, &packet_ptr, &offset,
                                                  &length) == NX_SUCCESS)
            {
                /* Write content data to buffer. */
                nx_packet_data_extract_offset(packet_ptr, offset, buffer, length,
                                             &length);
                buffer[length] = 0;
            }
        }

        /* Generate HTTP header. */
        status = nx_http_server_callback_generate_response_header(server_ptr,
                                                                &response_pkt, NX_HTTP_STATUS_OK, 800, "text/html",
                                                                "Server: NetX HTTP 5.3\r\n");

        if(status == NX_SUCCESS)
        {
            if(nx_http_server_callback_packet_send(server_ptr, response_pkt) !=
              NX_SUCCESS)
            {
                nx_packet_release(response_pkt);
            }
        }
    }
    Else
    {
        /* Indicate we have not processed the response to client yet.*/
        Return NX_SUCCESS;
    }

    /* Release the received client packet. */
    nx_packet_release(packet_ptr);

    /* Indicate the response to client is transmitted. */
    return(NX_HTTP_CALLBACK_COMPLETED);
}

```

nx_http_server_gmt_callback_set

Set the callback to obtain GMT date and time

Prototype

```
UINT nx_http_server_gmt_callback_set(NX_HTTP_SERVER *server_ptr,
                                     VOID (*gmt_get)(NX_HTTP_SERVER_DATE *date));
```

Description

This service sets the callback to obtain GMT date and time with a previously created HTTP server. This service is invoked with the HTTP server is creating a header in HTTP server responses to the Client.

Input Parameters

server_ptr	Pointer to HTTP Server
gmt_get	Pointer to GMT callback
date	Pointer to the date retrieved

Return Values

NX_SUCCESS	(0x00)	Successfully set the callback
NX_PTR_ERROR	(0x07)	Invalid packet or parameter pointer.

Allowed From

Threads

Example

```
NX_HTTP_SERVER my_server;

VOID get_gmt(NX_HTTP_SERVER_DATE *now);

/* After the HTTP server is created by calling nx_http_server_create, and before
starting HTTP services when nx_http_server_start is called, set the GMT
retrieve callback: */

status = nx_http_server_gmt_callback_set(&my_server, get_gmt);

/* If status equals NX_SUCCESS, the get_gmt will be called to set the HTTP server
response header date. */
```


nx_http_server_invalid_userpassword_notify_set

Set the callback to to handle invalid user/password

Prototype

```
UINT nx_http_server_invalid_userpassword_notify_set(
    NX_HTTP_SERVER *http_server_ptr,
    UINT (*invalid_username_password_callback)
    (CHAR *resource,
     ULONG client_address,
     UINT request_type));
```

Description

This service sets the callback invoked when an invalid username and password is received in a Client get, put or delete request, either by digest or basic authentication. The HTTP server must be previously created.

Input Parameters

server_ptr	Pointer to HTTP Server
invalid_username_password_callback	Pointer to invalid user/pass callback
resource	Pointer to the resource specified by the client
client_address	Client address
request_type	Indicates client request type. May be: NX_HTTP_SERVER_GET_REQUEST NX_HTTP_SERVER_POST_REQUEST NX_HTTP_SERVER_HEAD_REQUEST NX_HTTP_SERVER_PUT_REQUEST NX_HTTP_SERVER_DELETE_REQUEST

Return Values

NX_SUCCESS	(0x00)	Successfully set the callback
NX_PTR_ERROR	(0x07)	Invalid pointer input

Allowed From

Threads

Example

```
NX_HTTP_SERVER my_server;
VOID invalid_username_password_callback (NX_CHAR *resource,
                                         ULONG  client_address,
                                         UINT   request_type);

/* After the HTTP server is created by calling nx_http_server_create, and before
   starting HTTP services when nx_http_server_start is called, set the invalid
   username password callback: */

status = nx_http_server_gmt_callback_set(&my_server,
                                         invalid_username_password_callback);

/* If status equals NX_SUCCESS, the invalid_username_password_callback function
   will be called when the HTTP server receives an invalid username/password. */
```

nx_http_server_mime_maps_additional_set

Set additional MIME maps for HTML

Prototype

```
UINT nx_http_server_mime_maps_additional_set(
    NX_HTTP_SERVER *server_ptr,
    NX_HTTP_SERVER_MIME_MAP *mime_maps,
    UINT mime_maps_num);
```

Description

This service allows the HTTP application developer to add additional MIME types from the default MIME types supplied by NetX HTTP Server (see *nx_http_server_get_type* for list of defined types).

When a client request is received, e.g. a GET request, HTTP server parses the requested file type from the HTTP header using preferentially the additional MIME map set and if no match is found, it looks for a match in the default MIME map of the HTTP server. If no match is found, the MIME type defaults to “text/plain”.

If the request notify function is registered with the HTTP server, the request notify callback can call *nx_http_server_type_get* to parse the file type.

Input Parameters

server_ptr	Pointer to HTTP Server instance
mime_maps	Pointer to a MIME map array
mime_map_num	Number of MIME maps in array

Return Values

NX_SUCCESS	(0x00)	Successful HTTP Server MIME map set
NX_PTR_ERROR	(0x07)	Invalid pointer input

Allowed From

Initialization, Threads

Example

```
/* my_server is an NX_HTTP_SERVER previously created. */
NX_HTTP_SERVER_MIME_MAP my_mime_maps [2];
static NX_HTTP_SERVER_MIME_MAP my_mime_maps[] =
{
    {"abc",      "yourtype/abc"},
    {"xyz",      "mytype/xyz"},
};
status = nx_http_server_mime_maps_additional_set(&my_server,
                                                  &my_mime_maps[0], 2);

/* If status equals NX_SUCCESS, two additional MIME types are added to the HTTP
   server MIME map set. */
```

nx_http_server_packet_content_find

Extract content length and set pointer to start of data

Prototype

```
UINT nx_http_server_packet_content_find(NX_HTTP_SERVER *server_ptr,
                                         NX_PACKET **packet_ptr,
                                         UINT *content_length);
```

Description

This service extracts the content length from the HTTP header. It also updates the supplied packet as follows: the packet prepend pointer (start of location of packet buffer to write to) is set to the HTTP content (data) just passed the HTTP header.

If the beginning of content is not found in the current packet, the function waits for the next packet to be received using the `NX_HTTP_SERVER_TIMEOUT_RECEIVE` wait option.

Note this should not be called before calling *nx_http_server_get_entity_header* because it modifies the prepend pointer past the entity header.

Input Parameters

server_ptr	Pointer to HTTP server instance
packet_ptr	Pointer to packet pointer for returning the packet with updated prepend pointer
content_length	Pointer to extracted content_length

Return Values

NX_SUCCESS	(0x00)	HTTP content length found and packet successfully updated
NX_HTTP_TIMEOUT	(0xE1)	Time expired waiting on next packet
NX_PTR_ERROR	(0x07)	Invalid pointer input

Allowed From

Threads

Example

```
/* The HTTP server pointed to by server_ptr is previously created and started.
The server has received a Client request packet, recv_packet_ptr, and the packet
content find service is called from the request notify callback function
registered with the HTTP server. */

UINT content_length;

status = nx_http_server_packet_content_find(server_ptr, recv_packet_ptr,
                                             &content_length);

/* If status equals NX_SUCCESS, the content length specifies the content length
and the packet pointer prepend pointer is set to the HTTP content (data). */
```

nx_http_server_packet_get

Receive the next HTTP packet

Prototype

```
UINT nx_http_server_packet_get(NX_HTTP_SERVER *server_ptr,
                               NX_PACKET **packet_ptr);
```

Description

This service returns the next packet received on the HTTP server socket. The wait option to receive a packet is NX_HTTP_SERVER_TIMEOUT_RECEIVE.

Input Parameters

server_ptr	Pointer to HTTP server instance
packet_ptr	Pointer to received packet

Return Values

NX_SUCCESS	(0x00)	Successfully received next HTTP packet
NX_HTTP_TIMEOUT	(0xE1)	Time expired waiting on next packet
NX_PTR_ERROR	(0x07)	Invalid pointer input

Allowed From

Threads

Example

```
/* The HTTP server pointed to by server_ptr is previously created and started. */
UINT content_length;
NX_PACKET *recv_packet_ptr;

status = nx_http_server_packet_get(server_ptr, &recv_packet_ptr);
/* If status equals NX_SUCCESS, a Client packet is obtained. */
```

nx_http_server_param_get

Get parameter from the request

Prototype

```
UINT nx_http_server_param_get(NX_PACKET *packet_ptr,
                              UINT param_number, CHAR *param_ptr,
                              UINT max_param_size);
```

Description

This service attempts to retrieve the specified HTTP URL parameter in the supplied request packet. If the requested HTTP parameter is not present, this routine returns a status of NX_HTTP_NOT_FOUND. This routine should be called from the application's request notify callback specified during HTTP Server creation (*nx_http_server_create*).

Input Parameters

packet_ptr	Pointer to HTTP Client request packet. Note that the application should not release this packet.
param_number	Logical number of the parameter starting at zero, from left to right in the parameter list.
param_ptr	Destination area to copy the parameter.
max_param_size	Maximum size of the parameter destination area.

Return Values

NX_SUCCESS	(0x00)	Successful HTTP Server parameter get
NX_HTTP_NOT_FOUND	(0xE6)	Specified parameter not found
NX_HTTP_IMPROPERLY_TERMINATED_PARAM	(0xF3)	Request parameter not properly terminated
NX_PTR_ERROR	(0x07)	Invalid pointer input
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```
/* Assuming we are in the application's request notify callback
   routine, get the first parameter of the HTTP Client request. */
status = nx_http_server_param_get(request_packet_ptr, 0, param_destination,
                                   30);

/* If status equals NX_SUCCESS, the NULL-terminated first parameter can be found
   in "param_destination." */
```

nx_http_server_query_get

Get query from the request

Prototype

```
UINT nx_http_server_query_get(NX_PACKET *packet_ptr, UINT query_number,
                             CHAR *query_ptr, UINT max_query_size);
```

Description

This service attempts to retrieve the specified HTTP URL query in the supplied request packet. If the requested HTTP query is not present, this routine returns a status of NX_HTTP_NOT_FOUND. This routine should be called from the application's request notify callback specified during HTTP Server creation (*nx_http_server_create*).

Input Parameters

packet_ptr	Pointer to HTTP Client request packet. Note that the application should not release this packet.
query_number	Logical number of the parameter starting at zero, from left to right in the query list.
query_ptr	Destination area to copy the query.
max_query_size	Maximum size of the query destination area.

Return Values

NX_SUCCESS	(0x00)	Successful HTTP Server query get
NX_HTTP_FAILED	(0xE2)	Query size too small.
NX_HTTP_NOT_FOUND	(0xE6)	Specified query not found
NX_HTTP_NO_QUERY_PARSED	(0xF2)	No query in Client request
NX_PTR_ERROR	(0x07)	Invalid pointer input
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```
/* Assuming we are in the application's request notify callback
   routine, get the first query of the HTTP Client request. */
status = nx_http_server_query_get(request_packet_ptr, 0, query_destination,
                                   30);

/* If status equals NX_SUCCESS, the NULL-terminated first query can be found
   in "query_destination." */
```

nx_http_server_start

Start the HTTP Server

Prototype

```
UINT nx_http_server_start(NX_HTTP_SERVER *http_server_ptr);
```

Description

This service starts the previously create HTTP Server instance.

Input Parameters

http_server_ptr	Pointer to HTTP Server instance.
------------------------	----------------------------------

Return Values

NX_SUCCESS	(0x00)	Successful HTTP Server start
NX_PTR_ERROR	(0x07)	Invalid pointer input

Allowed From

Initialization, Threads

Example

```
/* Start the HTTP Server instance "my_server." */
status = nx_http_server_start(&my_server);

/* If status equals NX_SUCCESS, the HTTP Server has been started. */
```

nx_http_server_stop

Stop the HTTP Server

Prototype

```
UINT nx_http_server_stop(NX_HTTP_SERVER *http_server_ptr);
```

Description

This service stops the previously create HTTP Server instance. This routine should be called prior to deleting an HTTP Server instance.

Input Parameters

http_server_ptr	Pointer to HTTP Server instance.
------------------------	----------------------------------

Return Values

NX_SUCCESS	(0x00)	Successful HTTP Server stop
NX_PTR_ERROR	(0x07)	Invalid pointer input
NX_CALLER_ERROR	(0x11)	Invalid caller of this service

Allowed From

Threads

Example

```
/* Stop the HTTP Server instance "my_server." */
status = nx_http_server_stop(&my_server);

/* If status equals NX_SUCCESS, the HTTP Server has been stopped. */
```

nx_http_server_type_get

Extract file type from Client HTTP request

Prototype

```
UINT nx_http_server_type_get(NX_HTTP_SERVER *http_server_ptr,
                             CHAR *name, CHAR *http_type_string);
```

Description

This service extracts the HTTP request type in the buffer *http_type_string* and its length in the return valud from the input buffer *name*, usually the URL. If no MIME map is found, it defaults to the “text/plain” type. Otherwise it compares the extracted type against the HTTP Server default MIME maps for a match. The default MIME maps in NetX HTTP Server are:

html	text/html
htm	text/html
txt	text/plain
gif	image/gif
jpg	image/jpeg
ico	image/x-icon

If supplied, it will also search a user defined set of additional MIME maps. See *nx_http_server_mime_maps_additional_set* for more details on user defined maps.

Input Parameters

http_server_ptr	Pointer to HTTP Server instance
name	Pointer to buffer to search
http_type_string	(Pointer to extracted HTML type)

Return Values

Length of string in bytes	Non zero value is success Zero indicates error
----------------------------------	---

Allowed From

Application

Example

```
/* my_server is a previously created HTTP server, which starts accepting client requests when nx_http_server_start is called*/
```

```
CHAR temp_string[20];  
UINT string_length;
```

```
/* Extract the HTTP type. */  
string_length = nx_http_server_type_get(&my_server_ptr,  
my_server.nx_http_server_request_resource, temp_string);
```

```
/* If string_length is non zero, the HTTP string is extracted. */
```

For a more detailed example, see the description for *[nx_http_server_callback_generate_response_header](#)*.

NetX Hypertext Transfer Protocol (HTTP) User Guide

Publication Date: Rev.5.13 Nov 5, 2018

Published by: Renesas Electronics Corporation



SALES OFFICES

Renesas Electronics Corporation

<http://www.renesas.com>

Refer to "<http://www.renesas.com/>" for the latest and detailed information.

Renesas Electronics Corporation

TOYOSU FORESIA, 3-2-24 Toyosu, Koto-ku, Tokyo 135-0061, Japan

Renesas Electronics America Inc.

1001 Murphy Ranch Road, Milpitas, CA 95035, U.S.A.

Tel: +1-408-432-8888, Fax: +1-408-434-5351

Renesas Electronics Canada Limited

9251 Yonge Street, Suite 8309 Richmond Hill, Ontario Canada L4C 9T3

Tel: +1-905-237-2004

Renesas Electronics Europe Limited

Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5FH, U.K

Tel: +44-1628-651-700

Renesas Electronics Europe GmbH

Arcadiastrasse 10, 40472 Düsseldorf, Germany

Tel: +49-211-6503-0, Fax: +49-211-6503-1327

Renesas Electronics (China) Co., Ltd.

Room 1709 Quantum Plaza, No.27 ZhichunLu, Haidian District, Beijing, 100191 P. R. China

Tel: +86-10-8235-1155, Fax: +86-10-8235-7679

Renesas Electronics (Shanghai) Co., Ltd.

Unit 301, Tower A, Central Towers, 555 Langao Road, Putuo District, Shanghai, 200333 P. R. China

Tel: +86-21-2226-0888, Fax: +86-21-2226-0999

Renesas Electronics Hong Kong Limited

Unit 1601-1611, 16/F., Tower 2, Grand Century Place, 193 Prince Edward Road West, Mongkok, Kowloon, Hong Kong

Tel: +852-2265-6688, Fax: +852 2886-9022

Renesas Electronics Taiwan Co., Ltd.

13F, No. 363, Fu Shing North Road, Taipei 10543, Taiwan

Tel: +886-2-8175-9600, Fax: +886 2-8175-9670

Renesas Electronics Singapore Pte. Ltd.

80 Bendemeer Road, Unit #06-02 Hyflux Innovation Centre, Singapore 339949

Tel: +65-6213-0200, Fax: +65-6213-0300

Renesas Electronics Malaysia Sdn.Bhd.

Unit 1207, Block B, Menara Amcorp, Amcorp Trade Centre, No. 18, Jln Persiaran Barat, 46050 Petaling Jaya, Selangor Darul Ehsan, Malaysia

Tel: +60-3-7955-9390, Fax: +60-3-7955-9510

Renesas Electronics India Pvt. Ltd.

No.777C, 100 Feet Road, HAL 2nd Stage, Indiranagar, Bangalore 560 038, India

Tel: +91-80-67208700, Fax: +91-80-67208777

Renesas Electronics Korea Co., Ltd.

17F, KAMCO Yangjae Tower, 262, Gangnam-daero, Gangnam-gu, Seoul, 06265 Korea

Tel: +82-2-558-3737, Fax: +82-2-558-5338

NetX Hypertext Transfer Protocol (HTTP) User Guide