



RESISTOR SIZES and Packages

PDF Version

Chapter 2 - Resistor Standards and Codes



Resistors are available in a large number of different package styles and sizes. The most commonly used today are the rectangular surface mount (SMD) resistors, but also the good old axial resistor is still used extensively in through-hole designs. This page provides information on the dimensions of SMD, axial, and MELF packages. It also provides some recommended land patterns for SMD components for solder attach to PCBs.

Pages in Chapter 2

Overview

Resistor Color Code

Resistor Values

Resistor SMD Code

Resistor Sizes and Packages

Resistor Symbols

SMD Resistor Sizes

The shape and size of surface mount resistors are standardized, with most manufacturers using the JEDEC standards. The size of SMD resistors is indicated by a numerical code, such as 0603. This code contains the length and width of the package. So, the imperial code 0603 indicates a length of 0.060" and a width of 0.030".

The SMD package code can be given in either imperial or metric units. In general, the imperial code is used more often to indicate the package size. Confusingly, even when the imperial naming convention is used, the metric dimensions are often used during the design of the printed circuit boards (PCBs). In general, you can assume the code is in imperial units, but the dimensions used are in mm. The SMD resistor size used depends primarily on the required power rating, the minimum feature size of the PCB manufacturing, and the limitations of the pick-and-place equipment. The following table lists the dimensions and specifications of commonly used surface mount packages.

resistor size


Code	Length (l)	Width (w)	Height (h)	Power
------	------------	-----------	------------	-------

Imperial	Metric	inch	mm	inch	mm	inch	mm	Watt
0201	0603	0.024	0.6	0.012	0.3	0.01	0.25	1/20 (0.05)
0402	1005	0.04	1.0	0.02	0.5	0.014	0.35	1/16 (0.062)
0603	1608	0.06	1.55	0.03	0.85	0.018	0.45	1/10 (0.10)
0805	2012	0.08	2.0	0.05	1.2	0.018	0.45	1/8 (0.125)
1206	3216	0.12	3.2	0.06	1.6	0.022	0.55	1/4 (0.25)
1210	3225	0.12	3.2	0.10	2.5	0.022	0.55	1/2 (0.50)
1812	3246	0.12	3.2	0.18	4.6	0.022	0.55	1
2010	5025	0.20	5.0	0.10	2.5	0.024	0.6	3/4 (0.75)
2512	6332	0.25	6.3	0.12	3.2	0.024	0.6	1

Solder Pad Land Pattern

When designing with surface mount components, the right solder pad size and land pattern should be used. The following table shows recommended dimensions of the land pattern for common surface mount packages. The table lists the dimensions for reflow soldering. For wave soldering, smaller pads are used.

land pattern



Code		Pad length (a)		Pad width (b)		Gap (c)	
Imperial	Metric	inch	mm	inch	mm	inch	mm
0201	0603	0.012	0.3	0.012	0.3	0.012	0.3
0402	1005	0.024	0.6	0.020	0.5	0.020	0.5
0603	1608	0.035	0.9	0.024	0.6	0.035	0.9
0805	2012	0.051	1.3	0.028	0.7	0.047	1.2
1206	3216	0.063	1.6	0.035	0.9	0.079	2.0
1812	3246	0.19	4.8	0.035	0.9	0.079	2.0
2010	5025	0.11	2.8	0.059	0.9	0.15	3.8
2512	6332	0.14	3.5	0.063	1.6	0.15	3.8

Axial Resistor Sizes

The size of axial resistors is not as standardized as the SMD resistors, and different manufacturers often use slightly different dimensions. Furthermore, the size of an axial resistor depends on the power rating and the type of resistor such as carbon composition, wirewound, carbon film, or metal film. The following drawing and table give an indication of the dimensions of common carbon film and metal film axial resistors. Whenever the exact size needs to be known, always check the manufacturer datasheet of

the component.

Axial resistor size



Power rating	Body length (l)	Body diameter (d)	Lead length (a)	Lead diameter (da)
Watt	mm	mm	mm	mm
1/8 (0.125)	3.0 ± 0.3	1.8 ± 0.3	28 ± 3	0.45 ± 0.05
1/4 (0.25)	6.5 ± 0.5	2.5 ± 0.3	28 ± 3	0.6 ± 0.05
1/2 (0.5)	8.5 ± 0.5	3.2 ± 0.3	28 ± 3	0.6 ± 0.05
1	11 ± 1	5 ± 0.5	28 ± 3	0.8 ± 0.05

MELF Resistor Package Sizes

Metal electrode leadless face (MELF) is another type of surface mount resistor package.. The main advantage of using MELF instead of standard SMD packages is the lower thermal coefficient and better stability. The **temperature coefficient of resistance** (TCR) of thin film MELF resistors is often between 25-50 ppm/K while standard thick film

SMD resistors often have a TCR of > 200 ppm/K. The lower TCR of MELF resistors is due to their cylindrical construction. This cylindrical construction also gives the package distinct disadvantages, mainly when the components have to be placed using pick and place machines. Because of their round shape a special suction cup and more vacuum is required.

There are three common MELF package sizes: MicroMELF, MiniMELF and MELF. The following table lists the characteristics of these types.

MELF resistor



Name	Abbr. Code	Length	Diameter	Power
		mm	mm	Watt
MicroMELF	MMU 0102	2.2	1.1	0.2 - 0.3
MiniMELF	MMA 0204	3.6	1.4	0.25 - 0.4
MELF	MMB 0207	5.8	2.2	0.4 - 1.0

Resources

Online

- [JEDEC : JEP95 - standardized component outlines](#)



CONTENT FROM PARTNERS



MRC Rolls Suppress Harmful Interference Currents

Content from RFMW

COMMENTS ☐

0 Comments



Log in to comment



PRODUCTS

Batteries

Charging

Components & Materials

Design & Manufacturing

Electric Vehicles

Energy Storage

Generation

Microgrid

Power Supplies

Reliability & Security

Semiconductors & ICs

Smart Grid

Test & Measurement

Transmission & Distribution

APPLICATIONS

Distributed Energy

Electrification

Government

Industrial

Industry News

Infrastructure

Medical

Military & Aerospace

Non-renewable Energy

Recycling

Reg & Standards

Renewable Energy

Transportation

Utilities

CONTENT

News

New Industry Products

Technical Articles

Market Insights

Industry Articles

Industry White Papers

Textbook

Resistor Guide

Capacitor Guide

Tools

CONNECT WITH US

Contact Us

Advertise Us

Write For Us

SIGN UP

Register

MORE FROM OUR NETWORK



