

Deep Exponential Families: Biologically-Plausible Hierarchical Bayesian Inference?

David Halpern

Department of Psychology
New York University

OIST Computational Neuroscience Course 2015




NYU

GRADUATE SCHOOL
OF ARTS & SCIENCE

Background

- ▶ Humans and animals have been shown to perform near optimal hierarchical Bayesian inference in a wide variety of perceptual and cognitive tasks
 - ▶ But analytic computation of full posterior is often intractable and must be approximated
- ▶ What plausible neural algorithms could support this?



NYU

GRADUATE SCHOOL
OF ARTS & SCIENCE

Previous Work

- ▶ One proposal: variational inference (Beck et al. 2012)
 - ▶ Assume a parametric form of distributions for approximation and then use coordinate ascent (EM) to minimize KL divergence to true posterior
 - ▶ The coordinate ascent method produces dynamic equations which could be implemented by neurons after a lot of training
- ▶ Requires analytic derivation of coordinate ascent equations
 - ▶ No understanding of learning process
- ▶ Often involves complex nonlinear operations




NYU

GRADUATE SCHOOL
OF ARTS & SCIENCE

Approach

- ▶ Interpret a Deep Neural Net as a generative model (Ranganath et al. 2015)
- ▶ Each layer of neurons corresponds to a layer in the hierarchical distribution
- ▶ Model learns the weights (i.e. how layers are connected) through training
 - ▶ (In theory)



NYU

GRADUATE SCHOOL
OF ARTS & SCIENCE

Why is this plausible?

- ▶ Requires that neurons sample from exponential family distributions
 - ▶ We already model neural noise as exponential family distributions!
- ▶ Other computations are just linear sums
- ▶ No need to specify tuning curves of input layer or how to integrate information from input layer
- ▶ Only uses information from neighboring layers
- ▶ Algorithm finds closest approximation with arbitrary exponential-family distributions
- ▶ Caveats
 - ▶ A lot of reliance on feedback connections
 - ▶ Need to be able to semiaccurately modulate mean/variance of synaptic weights/spikes
 - ▶ Need to be able to extract mean rate (i.e. integrate) over a number of spikes




NYU

GRADUATE SCHOOL
OF ARTS & SCIENCE

Results

- ▶ ...None
- ▶ Seems to be very difficult to learn distributions
 - ▶ Perhaps due to variational assumption about weights
- ▶ Tried simplifying models and smarter learning rates (RMSProp)



NYU

GRADUATE SCHOOL
OF ARTS & SCIENCE

Conclusions/Future Work

- ▶ Potentially interesting, more biologically plausible Bayesian inference AND learning
- ▶ Related to recent work on STDP as gradient descent in variational inference by Bengio et al. (2015)
- ▶ Future work
 - ▶ Compare to C code posted by authors this weekend
 - ▶ Try Bayesian filtering approach to gradient descent updates as in Hounsby and Blei (2014)



NYU

GRADUATE SCHOOL
OF ARTS & SCIENCE