

# A comparison of neural networks for approximate Bayesian inference


David Halpern, Emin Orhan and Wei Ji Ma



Lots of behavioral evidence that the brain represents and computes with uncertainty  
But how do neurons do this?


## Task

Categorize an orientation drawn from one of two overlapping distributions  
Optimality requires subjects to keep track of uncertainty **from trial to trial**  
People do that to some extent (Qamar et al. 2013)



## Neural encoding model

Neurons have Gaussian tuning curves around a preferred orientation  $f_1(s), \dots, f_N(s)$  and Poisson variability



## Optimal inference in model

$$P(C, s|\mathbf{r}) = \left( \prod_i \frac{f_i(s)^{r_i}}{r_i!} \right) \sqrt{\frac{\tau_C}{2\pi}} e^{-\frac{\tau_C s^2}{2}}$$

C is the category, s is the stimulus  
r is the neural response and  $\tau_C$  is the precision of the category distribution

## Variational Inference

Assume that the posterior is factorizable, i.e.

$$P(C, s|\mathbf{r}) \approx Q(C|\mathbf{r})Q(s|\mathbf{r})$$

We then get variational distributions


$$Q(C|\mathbf{r}) \sim \text{Bernoulli}(p) \quad Q(s|\mathbf{r}) \sim \mathcal{N}(\eta, \tau)$$

Interpret as three-neuron dynamical system (as in Beck et al. 2012)

$$\frac{dp}{dt} = 1 - p \left( 1 + \sqrt{\frac{\tau_0}{\tau_1}} e^{-\frac{((\frac{\eta}{\tau})^2 + \frac{1}{\tau})\Delta\tau}{2}} \right) \eta = \sum_i \frac{r_i}{\sigma_{tc}^2} s_i^{\text{pref}}$$


$$\frac{d\tau}{dt} = -\tau + \sum_i \frac{r_i}{\sigma_{tc}^2} + (\tau_0 - p\Delta\tau)$$

Comparing approximations to analytic posterior




## Neural Network

- One hidden layer
- Fully connected with Rectified Linear Unit activations
- 3 x (number of updates to convergence) hidden units in order to match the variational network
- Trained with 3000 randomly generated samples using stochastic gradient descent with mean squared error loss
- 100 epochs



## Conclusions



At higher gains, variational inference can be more efficient than a multilayer neural net

Future work:

Compare to a generic recurrent neural network

Use KL divergence as loss

Train on class labels