

MINI SDS

Formula Colorpak Pro Series Aerosol Fastdry Enamel Satin Black

INGREDIENTS	CAS NO	%	8HR OEL
toluene	108-88-3	15-30	75 mg/m3
ethylbenzene	100-41-4	<4	87 mg/m3
xylene	1330-20-7	5-12	350 mg/m3
acetone	67-64-1	12-20	594 mg/m3

GHS



DG



UN No: **1950**
Hazchem Code: **Not Applicable**
DG Class: **2.1**
Subsidiary Hazard: **Not Applicable**
Packing Group: **Not Applicable**
Poisons Schedule: **Not Applicable**

PROPERTIES



Liquid. Gas. Does not mix with water. Floats on water. Extremely flammable.

EMERGENCY



HEALTH HAZARD INFORMATION



Signal word: **Danger**

Hazard statement(s):	H222+H229	Extremely flammable aerosol. Pressurized container: may burst if heated.
	H302	Harmful if swallowed.
	H315	Causes skin irritation.
	H319	Causes serious eye irritation.
	H336	May cause drowsiness or dizziness.
	H351	Suspected of causing cancer.
	H361d	Suspected of damaging the unborn child.
	H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.	
AUH044	Risk of explosion if heated under confinement.	

FIRST AID

Swallowed:	Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water (minimum 15 mins). Medical attention.
Skin:	Wash with soap & water. Apply cleansing cream.
Fire Fighting:	Keep containers cool. Foam.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+

X

+

X

+

+

+

X — Must not be stored together

O — May be stored together with specific preventions

+

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.VITON/CHLOROBUTYL 2.VITON
Respirator:	Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Keep out of reach of children. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Keep away from heat. Keep away from sources of ignition. No smoking.
Fire/Explosion Hazard:	HIGHLY FLAMMABLE. Toxic smoke/fumes in a fire. Risk of explosion if heated under confinement. In case of fire and/or explosion, DO NOT BREATHE FUMES.