

Class design

From last time: finish Names example
(from last Thur lect slides)

- practice with
 - coding array algorithms
 - implementing classes
 - and using good development techniques
- incremental development
- for lookup, **remove**, insert:
 - design test cases first
 - implement code
 - code refactoring
 - test code

Today's Class Design topics

- Preconditions
- Class invariants
 - representation invariants
 - testing repr. invariants

Announcements

- This week's lab: milestone for PA2 (today's lecture helpful for lab)
- Don't wait until after MT to start PA2
- Midterm 1 is on Tue 2/23 9:30am – 10:50am
 - 6:30 – 7:50am for students in Asia
 - email coming soon confirming your designated exam time
 - sample problems have been published
 - Closed book, closed note, no outside s/w, websites, or electronic devices
 - blank scratch paper ok for scratch work (not submitted)
 - online exam
 - rehearsal exam coming soon

Method preconditions

- a restriction on how a method can be called
 - Ex (from book): in **BankAccount** class

void deposit(double amount)

Precondition:

- document any preconditions in the method comment
- why not
"amount must be type double" ?

Method contract

- client must satisfy precondition
- a contract between client code and method:
 - if you call the function this way,
we guarantee it will do what we say it does
 - otherwise, behavior is undefined
- avoid performing duplicate checks between client and method code

POLL: preconditions

- **BankAccount** example

void deposit(double amount)


Precondition: **amount > 0**

Asynchronous participation: [Link to Preconditions poll](#)

What should method do?

- a call that violates the precondition is incorrect (remember: undefined results)
- Java **assert** statement is useful:
`assert amount > 0;`

Restrictions on implicit parameter

 `x.foo () ;`

Another reason for a precondition:

- restriction on *when* certain methods can be called
 - object can be in different states
- Illegal to call `next ()` when `Scanner` has no more input (eof in lab4)
- **PRE: hasNext () is true**
- Try to minimize them

Your Precondition comments

- Two ways to document at the top of a method:
- Javadoc style (next to param in question):

```
@param amount  
    the amount of money to deposit,  
    must be > 0
```

- Or state all preconditions on separate line:

```
PRE: amount > 0
```


Class Invariants

- a statement about an object that's always true between method calls:
 - true after constructor
 - true after every mutator
 - (therefore, also true before every method call)
- interface invariant: true from client view
- representation invariant: true about object representation

Interface Invariants

- sometimes related to preconditions
- Example in book: **BankAccount**
Invariant: `getBalance() >= 0`
- would document in overall class comment
- For **CoinTossSimulator** class:
Invariant: `getNumTrials() =
 getTwoHeads() + getTwoTails() +
 getHeadTails()`
- For **Names** class
Invariant: `names are in alphabetical order
 and are unique`

Representation invariants

- a statement about the *internal object representation* that's always true between method calls:
 - true after constructor
 - true after every mutator
 - (therefore, also true before every method call)
- describes valid internal state of the object
 - any restrictions on what can be in instance variables
 - any relationships between values in different instance variables

Ex: Repr. invar. for **Names** class


- ... that uses *ArrayList* representation

```
class Names {  
    . . .  
    private ArrayList<String> namesArr;  
    /* Representation invariant:  
       -- names are unique  
       -- names are in alphabetical order in namesArr  
       -- number of names stored is namesArr.size()  
    */  
}
```

Ex 2: Repr. invariant for **Names** class

- ... that uses *partially filled array* representation

```
class Names {  
    . . .  
    private String[] namesArr;  
    private int numNames;  
}
```



Ex 2 of repr. invariants (cont.)

| Names | | | | | | |
|----------|-----|-----|-----|---|---|-------|
| | 0 | 1 | 2 | 3 | 4 | . . . |
| namesArr | Ann | Bob | Jun | | | . . . |
| numNames | 3 | | | | | |

repr. invariant:

- `numNames` is the number of names
- $0 \leq \text{numNames} \leq \text{namesArr.length}$
- if `numNames > 0`, the names are in `namesArr`
 locs: `[0, numNames)`
- names are in alphabetical order
- names are unique

Different invar. with same data types

```
class Names {  
    . . .  
    private String[] namesArr;  
    private int lastLoc;  
}
```

| Names | | | | | | |
|----------|-----|-----|-----|---|---|-------|
| | 0 | 1 | 2 | 3 | 4 | . . . |
| namesArr | Ann | Bob | Jun | | | . . . |
| lastLoc | 2 | | | | | |

Different invariant (cont.)

| Names | | | | | | |
|----------|-----|-----|-----|---|---|-------|
| | 0 | 1 | 2 | 3 | 4 | . . . |
| namesArr | Ann | Bob | Jun | | | . . . |
| lastLoc | 2 | | | | | |

- representation invariant:

Testing representation invariants

- Can use **assert** for sanity checks.
- One kind of sanity check:
 check representation invariant
- Write a *private* method:
 boolean isValidObject()
- at end of every method:
 assert isValidObject();
- You will be doing this in pa2.