

jQuery HTML / CSS Methods

The following table lists all the methods used to manipulate the HTML and CSS.

The methods below work for both HTML and XML documents. Exception: the `html()` method.

Method	Description
<u>addClass()</u>	Adds one or more class names to selected elements
<u>after()</u>	Inserts content after selected elements
<u>append()</u>	Inserts content at the end of selected elements
<u>appendTo()</u>	Inserts HTML elements at the end of selected elements
<u>attr()</u>	Sets or returns attributes/values of selected elements
<u>before()</u>	Inserts content before selected elements
<u>clone()</u>	Makes a copy of selected elements
<u>css()</u>	Sets or returns one or more style properties for selected elements
<u>detach()</u>	Removes selected elements (keeps data and events)
<u>empty()</u>	Removes all child nodes and content from selected elements
<u>hasClass()</u>	Checks if any of the selected elements have a specified class name
<u>height()</u>	Sets or returns the height of selected elements
<u>html()</u>	Sets or returns the content of selected elements
<u>innerHeight()</u>	Returns the height of an element (includes padding, but not border)
<u>innerWidth()</u>	Returns the width of an element (includes padding, but not border)
<u>insertAfter()</u>	Inserts HTML elements after selected elements
<u>insertBefore()</u>	Inserts HTML elements before selected elements

<u>offset()</u>	Sets or returns the offset coordinates for selected elements (relative to the document)
<u>offsetParent()</u>	Returns the first positioned parent element
<u>outerHeight()</u>	Returns the height of an element (includes padding and border)
<u>outerWidth()</u>	Returns the width of an element (includes padding and border)
<u>position()</u>	Returns the position (relative to the parent element) of an element
<u>prepend()</u>	Inserts content at the beginning of selected elements
<u>prependTo()</u>	Inserts HTML elements at the beginning of selected elements
<u>prop()</u>	Sets or returns properties/values of selected elements
<u>remove()</u>	Removes the selected elements (including data and events)
<u>removeAttr()</u>	Removes one or more attributes from selected elements
<u>removeClass()</u>	Removes one or more classes from selected elements
<u>removeProp()</u>	Removes a property set by the prop() method
<u>replaceAll()</u>	Replaces selected elements with new HTML elements
<u>replaceWith()</u>	Replaces selected elements with new content
<u>scrollLeft()</u>	Sets or returns the horizontal scrollbar position of selected elements
<u>scrollTop()</u>	Sets or returns the vertical scrollbar position of selected elements
<u>text()</u>	Sets or returns the text content of selected elements
<u>toggleClass()</u>	Toggles between adding/removing one or more classes from selected elements
<u>unwrap()</u>	Removes the parent element of the selected elements
<u>val()</u>	Sets or returns the value attribute of the selected elements (for form elements)
<u>width()</u>	Sets or returns the width of selected elements
<u>wrap()</u>	Wraps HTML element(s) around each selected element

<u>wrapAll()</u>	Wraps HTML element(s) around all selected elements
<u>wrapInner()</u>	Wraps HTML element(s) around the content of each selected element