

Histograms of oriented gradients

2014/08/22

ked

Authors

- Navneet Dalal and Bill Triggs



Authors

- Navneet Dalal



- A founder of Flutter
- (A gesture recognition startup company created in 2010)

Authors

■ Navneet



□ A founder

□ (A gesture

FLUTTER

**WE ARE EXCITED TO
ANNOUNCE THAT--**

WE HAVE BEEN ACQUIRED BY

The Google logo, featuring its characteristic four colors: blue, red, yellow, and green.

When we started three years ago, our dream to build a ubiquitous and power-efficient gesture recognition technology was considered by many as just "a dream", not a real possibility. Since then, we have strived to build the best machine vision algorithms and a delightful user experience.

Even after we launched our first app, we didn't stop our research; your enthusiasm and support pushed us to continue to do better. We're inspired everyday when we hear, for example, that Flutter makes you feel like a superhero — because any sufficiently advanced technology should be indistinguishable from magic, right?

Today, we are thrilled to announce that we will be continuing our research at Google. We share Google's passion for 10x thinking, and we're excited to add their rocket fuel to our journey.

We'd like to extend a special thank you to all of our users; your feedback and evangelism inspire us every day. Flutter users will be able to continue to use the app, and stay tuned for future updates.


Best,

A handwritten signature in black ink, appearing to read 'N. Dalal'.

010)

Overview – HOG

Typical person detection scheme using SVM



*Navneet Dalal and Bill Triggs. Histograms of Oriented Gradients for Human Detection. In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, San Diego, USA, June 2005. Vol. II, pp. 886-893.

Gradient

Computing Gradients

- Centered:
$$f'(x) = \lim_{h \rightarrow 0} \frac{f(x+h) - f(x-h)}{2h}$$

- Filter masks in x and y directions

- Centered:


-1	0	1
----	---	---

-1
0
1

- Gradient

- Magnitude:

$$s = \sqrt{s_x^2 + s_y^2}$$



- Orientation:

$$\theta = \arctan\left(\frac{s_y}{s_x}\right)$$

Input image



Normalise gamma & colour

Compute gradients


Accumulate weighted votes for gradient orientation over spatial cells

Normalise contrast within overlapping blocks of cells

Collect HOGs for all blocks over detection window

Cell & block

- Cell
 - 8 x 8 pixels
- Block
 - 2 x 2 cells
 - 50% overlap for neighbors




Example

■ For a 64 x 128 image

Blocks, Cells

- 16x16 blocks of 50% overlap.
 - $7 \times 5 = 105$ blocks in total
- Each block should consist of 2x2 cells with size 8x8.





Quantization

Tri-linear Interpolation

- Each block consists of 2x2 cells with size 8x8
- Quantize the gradient orientation into 9 bins (0-180)

- The vote is the gradient magnitude
- Interpolate votes linearly between neighboring bin centers.
 - Example: if $\theta=85$ degrees.
 - Distance to the bin centre Bin 70 and Bin 90 are 15 and 5 degrees, respectively.
 - Hence, ratios are $5/20=1/4$, $15/20=3/4$.
- The vote can also be weighted with Gaussian to downweight the pixels near the edges of the block.



Parameters – bins

Accumulate weight votes over spatial cells



Input image



Normalise gamma & colour


Compute gradients

Accumulate weighted votes for gradient orientation over spatial cells

Normalise contrast within overlapping blocks of cells

Collect HOGs for all blocks over detection window

- How many bins should be in histogram?
- Should we use oriented or non-oriented gradients?
- How to select weights?
- Should we use overlapped blocks or not? If yes, then how big should be the overlap?
- What block size should we use?



Parameters – cell & block

Accumulate weight votes over spatial cells



Input image



Normalise gamma & colour


Compute gradients

Accumulate weighted votes
for gradient orientation over
spatial cells

Normalise contrast within
overlapping blocks of cells


Collect HOGs for all blocks
over detection window

- How many bins should be in histogram?
- Should we use oriented or non-oriented gradients?
- How to select weights?
- Should we use overlapped blocks or not? If yes, then how big should be the overlap?
- What block size should we use?



Histogram normalization

Contrast normalization





Normalise gamma & colour

Compute gradients

Accumulate weighted votes for gradient orientation over spatial cells

Normalise contrast within overlapping blocks of cells

Collect HOGs for all blocks over detection window




$$L1-norm = \frac{v}{\|v\|_1 + \varepsilon}$$

$$L1-sqrt = \frac{v}{\sqrt{\|v\|_1 + \varepsilon}}$$


$$L2-norm = \frac{v}{\sqrt{\|v\|_2^2 + \varepsilon}}$$

$L2-Hys$ - $L2-norm$ followed by clipping (limiting the maximum values of v to 0.2) and renormalising


Feature description



(a) R-HOG/SIFT




(b) C-HOG



(c) Single centre C-HOG

Input image



Normalise gamma & colour

Compute gradients

Accumulate weighted votes
for gradient orientation over
spatial cells

Normalise contrast within
overlapping blocks of cells

Collect HOGs for all blocks
over detection window

Compare to SIFT


-- by authors

R-HOG compared to SIFT Descriptor

- R-HOG blocks appear quite similar to the SIFT descriptors.
- But, R-HOG blocks are computed in dense grids at some **single scale without orientation alignment**.
- SIFT descriptors are computed at sparse, scale-invariant key image points and are rotated to align orientation.

SVM weight

Pictorial Example



- (a) average gradient image over training examples
- (b) each “pixel” shows max positive SVM weight in the block centered on that pixel
- (c) same as (b) for negative SVM weights
- (d) test image
- (e) its R-HOG descriptor
- (f) R-HOG descriptor weighted by positive SVM weights
- (g) R-HOG descriptor weighted by negative SVM weights

Thx.
