

"(FOR FLOOR STANDING TYPE)

All dimensions in mm

MS Modular Type IP42.

Finished with RAL 7032 Electrostatic Powder Coat after pre treatment of Steel Sheet.

Single Door Front Access Only.

Component Plate White Colour.

Door turns to open lock Facility.

System Cabinet/Enclosure Design for 415V, 3Phase, 4Wire, 50Hz

Bottom/Gland plate removable.

Earth Bread for Door to Body Earth Connectivity.

Floor Standing Type with lifting Lugs.

Cable Entry from Bottom/Top.

Ventilation Louvers (Optional)

Tolerance 5mm \pm

Panel Manufacturing Standard IEC 61439-1

(FOR WALL MOUNTED TYPE)

All dimensions in mm

MS Sheet Welded Folded Type IP 54.

Finished with RAL 7032 Electrostatic Powder Coat after pre treatment of Steel Sheet.

Single Door Front Access Only.

Component Plate White Colour.

Door turns to open lock Facility.

System Cabinet/Enclosure Design for 415V, 3Phase, 4Wire, 50Hz

Bottom/Gland plate removable.

Earth Bread for Door to Body Earth Connectivity.

Wall Mounted Type.

Cable Entry from Bottom.

Ventilation Louvers (Optional)

Tolerance 5mm \pm

Panel Manufacturing Standard IEC 61439-1"