

I Series

LED Explosion Proof Light





















Certifications:

- Marking ATEX
 - II2 G Ex db IIB T4 Gb
 - II2 D Ex tb IIIC T63.5°C Db IP66
- Marking IECEx
 - Ex db IIB T4 Gb
 - Ex tb IIIC T63.5°C Db IP66
- Marine Marking
 - UL 1598
 - UL1598A
 - ABS

- Marking UL844 (North American)
 - Class I, Division 1, Groups C, D
 - Class I, Division 2, Groups A, B, C, D
 - Olass II, Division 1, Groups E, F, G
 - Class II, Division 2, Groups F, G
 - Class III
- IP66

Standard Materials:


- Housing: Copper-free aluminum
- Lens: Tempered Glass
- Hardware: Stainless steel
- Mounting Bracket: Stainless steel

LED Explosion Proof Light - I Series

Key Features:

- Dimming function available; battery backup optional.
- High-quality SMT LED and Meanwell driver.
- Heavy-duty and high impact resistance.
- Replaceable LED board and drivers.
- Integrated junction box for driver.
- Marine rating powder coated finish treatment.
- High efficacy up to 140 lumens per watt.
- 5-year warranty.
- Low temperature applications to -40°C (-40°F) and high temperature up to 60°C (140°F).

Catalog Number Logic:



- PRODUCT CATEGORY
 - Explosion proof light
- WATTAGE
 - PRODUCT SERIES 20W-120W
- DIMMING OPTION
 - D= Dimmable N= Non-dimmable

- (5) CCT

 - From 2200K to 7000K
 - 22=2200K, 30=3000K, ..., 70=7000K
- **BEAM ANGLE**
 - D40= 40°
 - **•** D90= 90° • D60= 60° **D**120= 120°


- **GLASS TYPE**
 - A=blank: Flat glass
 - A=C: Spherical glass


Technical Data:

Model	Wattage	Operating Voltage	Lumens (lm)	Efficacy (lm/W)	CRI	ССТ	Emergency Time
EX-20W I2YZDA	20W	AC100-277V/200-480V or DC12-36V	2,800	140 >7		0 2200K-7000K	3 hours
EX-40W I2YZDA	40W		5,600				
EX-50W I2YZDA	50W		7,000				
EX-60W I2YZDA	60W		8,400				
EX-40W I4YZDA	40W		5,600		>70		
EX-60W I4YZDA	60W		8,400				
EX-80W I4YZDA	80W		11,200				
EX-100W I4YZDA	100W		14,000				
EX-120W I4YZDA	120W		16,800				



LED Explosion Proof Light - I Series





Packing Information:


Model	Quantity/Carton	Packing Size	Net Weight	Gross Weight
12	1 PCS	30.31x13.39x10.43inch	12 kg/ 26.45 lbs	14 kg/ 30.86 lbs
14	1 PCS	53.54x13.39x10.43inch	18.5 kg/ 40.79 lbs	21.5 kg/ 47.40 lbs




LED Explosion Proof Light - I Series

Mounting Methods:


Ceiling Mounting:




Ohain Mounting:



Wall Mounting:



Pole Pendant Mounting:



Pole Bracket Mounting:



Accessories:



Model: Ex-Junction Box
Name: Junction Box
Material: Aircraft Aluminum A383



Model: EX-Straight Pipe

Name: Straight Pipe Material: Iron



Model: Ex-Conduit 01

Name: Metal Conduit

Material: Stainless Steel and Aluminum



Model: EX-Bended Pipe Name: Bended Pipe Material: Iron



Model: Ex-Chain

Name: Pendant Chain Material: Stainless Steel S3040



Model: Ex-Bracket

Name: U-bracket Material: Stainless Steel

Application:

- Oil and gas industry
 - · All petroleum production and refining
 - Petroleum loading and transportation
 - · Petroleum storage and retail
 - LNG industry
 - All mining operations and service
- Ocean, marine and aerospace field
 - · Ocean platform operation facilities
 - Aerospace clean room and production
 - · Ocean vessel operations
- Food and alcohol industry
 - Flour and fine particle production and storage
 - · Food and distilling production
 - Alcohol industry

- Chemical industry
 - · All types of paint facilities
 - · Chemical production and storage
- Metal treatment
 - · Steel and aluminum factories
 - Pumping stations in any environment
 - · Metal smelting, foundry and fabrication
- Other high humidity, high dust, high temperature, vapor locations.