



CSS Layout - The position Property

[< Previous](#)[Next >](#)

The **position** property specifies the type of positioning method used for an element (static, relative, fixed, absolute or sticky).

The position Property

The **position** property specifies the type of positioning method used for an element.

There are five different position values:

- **static**
- **relative**
- **fixed**
- **absolute**
- **sticky**

Elements are then positioned using the top, bottom, left, and right properties. However, these properties will not work unless the **position** property is set first. They also work differently depending on the position value.

position: static;

HTML elements are positioned static by default

This <div> element has **position: fixed;**

Static positioned elements are not affected by the top, bottom, left, and right properties.

An element with `position: static;` is not positioned in any special way; it is always positioned according to the normal flow of the page:

This <div> element has position: static;

Here is the CSS that is used:

Example

```
div.static {  
  position: static;  
  border: 3px solid #73AD21;  
}
```

Try it Yourself »

position: relative;

An element with `position: relative;` is positioned relative to its normal position.

Setting the top, right, bottom, and left properties of a relatively-positioned element will cause it to be adjusted away from its normal position. Other content will not be adjusted to fit into any gap left by the element.

This <div> element has position: relative;

Here is the CSS that is used:

Example

```
div.relative {  
  position: relative;  
  left: 30px;  
  border: 3px solid #73AD21;  
}
```

This <div> element has position: fixed;

[Try it Yourself »](#)

position: fixed;

An element with `position: fixed;` is positioned relative to the viewport, which means it always stays in the same place even if the page is scrolled. The top, right, bottom, and left properties are used to position the element.

A fixed element does not leave a gap in the page where it would normally have been located.

Notice the fixed element in the lower-right corner of the page. Here is the CSS that is used:

Example

```
div.fixed {  
  position: fixed;  
  bottom: 0;  
  right: 0;  
  width: 300px;  
  border: 3px solid #73AD21;  
}
```

[Try it Yourself »](#)

position: absolute;


This <div> element has `position: fixed;`

An element with `position: absolute;` is positioned relative to the nearest positioned ancestor (instead of positioned relative to the viewport, like fixed).

However; if an absolute positioned element has no positioned ancestors, it uses the document body, and moves along with page scrolling.

Note: A "positioned" element is one whose position is anything except `static`.

Here is a simple example:



Here is the CSS that is used:

Example

```
div.relative {  
  position: relative;  
  width: 400px;  
  height: 200px;  
  border: 3px solid #73AD21;  
}  
  
div.absolute {  
  position: absolute;  
  top: 80px;  
  right: 0;  
  width: 200px;  
  height: 100px;  
  border: 3px solid #73AD21;  
}
```

Try it Yourself »

This <div> element has `position: fixed;`

position: sticky;

An element with `position: sticky;` is positioned based on the user's scroll position.

A sticky element toggles between `relative` and `fixed`, depending on the scroll position. It is positioned relative until a given offset position is met in the viewport - then it "sticks" in place (like `position: fixed`).

Try to scroll inside this frame to understand how sticky positioning works.

Note: IE/Edge 15 and earlier versions do not support sticky position.

I am sticky!

Note: Internet Explorer, Edge 15 and earlier versions do not support sticky positioning. Safari requires a `-webkit-` prefix (see example below). You must also specify at least one of `top`, `right`, `bottom` or `left` for sticky positioning to work.

In this example, the sticky element sticks to the top of the page (`top: 0`), when you reach its scroll position.

Example

```
div.sticky {  
  position: -webkit-sticky; /* Safari */  
  position: sticky;  
  top: 0;  
  background-color: green;  
  border: 2px solid #4CAF50;  
}
```

Try it Yourself »

This `<div>` element has `position: fixed;`

Overlapping Elements

When elements are positioned, they can overlap other elements.

The **z-index** property specifies the stack order of an element (which element should be placed in front of, or behind, the others).

An element can have a positive or negative stack order:



This is a heading

Because the image has a z-index of -1, it will be placed behind the text.

Example

```
img {  
  position: absolute;  
  left: 0px;  
  top: 0px;  
  z-index: -1;  
}
```

Try it Yourself »

An element with greater stack order is always in front of an element with a lower stack order.


Note: If two positioned elements overlap without a **z-index** specified, the element positioned last in the HTML code will be shown on top.

This <div> element has **position: fixed;**

Positioning Text In an Image

How to position text over an image:

Example



Try it Yourself:

[Top Left »](#)[Top Right »](#)[Bottom Left »](#)[Bottom Right »](#)[Centered »](#)

More Examples

[Set the shape of an element](#)

This example demonstrates how to set the shape of an element. The element is clipped into this shape, and displayed.

Test Yourself with Exercises!

[Exercise 1 »](#)[Exercise 2 »](#)[Exercise 3 »](#)[Exercise 4 »](#)[Exercise 5 »](#)

This <div> element has **position: fixed;**

All CSS Positioning Properties

| Property | Description |
|-----------------|--|
| <u>bottom</u> | Sets the bottom margin edge for a positioned box |
| <u>clip</u> | Clips an absolutely positioned element |
| <u>left</u> | Sets the left margin edge for a positioned box |
| <u>position</u> | Specifies the type of positioning for an element |
| <u>right</u> | Sets the right margin edge for a positioned box |
| <u>top</u> | Sets the top margin edge for a positioned box |
| <u>z-index</u> | Sets the stack order of an element |

[< Previous](#)[Next >](#)

This <div> element has `position: fixed;`



COLOR PICKER



SHOP

HOW TO

Tabs
Dropdov

This <div> element has `position: fixed;`

Accordions

Side Navigation

Top Navigation

Modal Boxes

Progress Bars

Parallax

Login Form

HTML Includes

Google Maps

Range Sliders

Tooltips

Slideshow

Filter List

Sort List

SHARE



CERTIFICATES

HTML

CSS

JavaScript

SQL

Python

PHP

jQuery

Bootstrap

XML

[Read More »](#)

This <div> element has `position: fixed;`

[Java Reference](#)[Angular Reference](#)

Top Examples

[HTML Examples](#)[CSS Examples](#)[JavaScript Examples](#)[How To Examples](#)[SQL Examples](#)[Python Examples](#)[W3.CSS Examples](#)[Bootstrap Examples](#)[PHP Examples](#)[jQuery Examples](#)[Java Examples](#)[XML Examples](#)

Web Certificates

[HTML Certificate](#)[CSS Certificate](#)[JavaScript Certificate](#)[SQL Certificate](#)[Python Certificate](#)[jQuery Certificate](#)[PHP Certificate](#)[Bootstrap Certificate](#)[XML Certificate](#)[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.



This <div> element has **position: fixed;**

This <div> element has `position: fixed;`

[REPORT ERROR](#)

[FORUM](#)

[ABOUT](#)

[SHOP](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[jQuery Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Col](#)
[jQuery Refe](#)

This <div> element has **position: fixed;**