



CSS Web Safe Font Combinations

[< Previous](#)[Next >](#)

Commonly Used Font Combinations

The font-family property should hold several font names as a "fallback" system, to ensure maximum compatibility between browsers/operating systems. If the browser does not support the first font, it tries the next font.

Start with the font you want, and end with a generic family, to let the browser pick a similar font in the generic family, if no other fonts are available:

Example

```
p {  
  font-family: "Times New Roman", Times, serif;  
}
```

[Try it Yourself »](#)

Below are some commonly used font combinations, organized by generic family.

Serif Fonts



HTML

CSS

MORE ▼

EXERCISES ▼



Georgia, serif

This is a heading

This is a paragraph

"Palatino Linotype", "Book Antiqua", Palatino, serif

This is a heading

This is a paragraph

"Times New Roman", Times, serif

This is a heading

This is a paragraph



Sans-Serif Fonts

font-family	Example text
Arial, Helvetica, sans-serif	<h1>This is a heading</h1> <p>This is a paragraph</p>
"Arial Black", Gadget, sans-serif	<h1>This is a heading</h1> <p>This is a paragraph</p>
"Comic Sans MS", cursive, sans-serif	



HTML

CSS

MORE ▼

EXERCISES ▼



	This is a paragraph
Impact, Charcoal, sans-serif	This is a heading
	This is a paragraph
"Lucida Sans Unicode", "Lucida Grande", sans-serif	This is a heading
	This is a paragraph
Tahoma, Geneva, sans-serif	This is a heading
	This is a paragraph
"Trebuchet MS", Helvetica, sans-serif	This is a heading
	This is a paragraph
Verdana, Geneva, sans-serif	This is a heading
	This is a paragraph

Monospace Fonts

font-family	Example text
"Courier New", Courier, monospace	This is a heading This is a paragraph
"Lucida Console", Monaco, monospace	This is a



HTML

CSS

MORE ▼

EXERCISES ▼



This is a paragraph


Tip: Also check out all available [Google Fonts](#) and how to use them.

[< Previous](#)[Next >](#)

[HTML](#)[CSS](#)[MORE ▼](#)[EXERCISES ▼](#)[SHOP](#)[HOW TO](#)[Tabs](#)[Dropdowns](#)[Accordions](#)[Side Navigation](#)[Top Navigation](#)[Modal Boxes](#)[Progress Bars](#)[Parallax](#)[Login Form](#)[HTML Includes](#)[Google Maps](#)[Range Sliders](#)[Tooltips](#)[Slideshow](#)[Filter List](#)[Sort List](#)[SHARE](#)[CERTIFICATES](#)[HTML](#)[CSS](#)[JavaScript](#)[SQL](#)



[Read More »](#)

[HTML](#)[CSS](#)[MORE ▼](#)[EXERCISES ▼](#)[REPORT ERROR](#)[FORUM](#)[ABOUT](#)[SHOP](#)

Top Tutorials

[HTML Tutorial](#)[CSS Tutorial](#)[JavaScript Tutorial](#)[How To Tutorial](#)[SQL Tutorial](#)[Python Tutorial](#)[W3.CSS Tutorial](#)[Bootstrap Tutorial](#)[PHP Tutorial](#)[jQuery Tutorial](#)

[HTML](#)[CSS](#)[MORE ▾](#)[EXERCISES ▾](#)

Top References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [SQL Reference](#)
- [Python Reference](#)
- [W3.CSS Reference](#)
- [Bootstrap Reference](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [jQuery Reference](#)
- [Java Reference](#)
- [Angular Reference](#)

Top Examples

- [HTML Examples](#)
- [CSS Examples](#)
- [JavaScript Examples](#)
- [How To Examples](#)
- [SQL Examples](#)
- [Python Examples](#)
- [W3.CSS Examples](#)
- [Bootstrap Examples](#)
- [PHP Examples](#)
- [jQuery Examples](#)
- [Java Examples](#)
- [XML Examples](#)

Web Certificates

- [HTML Certificate](#)
- [CSS Certificate](#)
- [JavaScript Certificate](#)
- [SQL Certificate](#)
- [Python Certificate](#)
- [jQuery Certificate](#)
- [PHP Certificate](#)
- [Bootstrap Certificate](#)
- [XML Certificate](#)

[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.
Powered by W3.CSS.

