ш3schools.com





HTML

CSS

MORE ▼

EXERCISES ▼ **①**



Q

CSS Lists

Previous

Next >

Unordered Lists:

- Coffee
- Tea
- · Coca Cola
- Coffee
- Tea
- Coca Cola

Ordered Lists:

- 1. Coffee
- 2. Tea
- 3. Coca Cola
- I. Coffee
- II. Tea
- III. Coca Cola

HTML Lists and CSS List Properties

In HTML, there are two main types of lists:

- unordered lists () the list items are marked with bullets
- ordered lists () the list items are marked with numbers or letters

The CSS list properties allow you to:

- Set different list item markers for ordered lists
- Set different list item markers for unordered lists
- Set an image as the list item marker
- · Add background colors to lists and list items

Different List Item Markers

The list-style-type property specifies the type of list item marker.

The following example shows some of the available list item markers:

Example

```
ul.a {
   list-style-type: circle;
}

ul.b {
   list-style-type: square;
}

ol.c {
   list-style-type: upper-roman;
}

ol.d {
   list-style-type: lower-alpha;
}
```

Try it Yourself »

Note: Some of the values are for unordered lists, and some for ordered lists.

An Image as The List Item Marker

The list-style-image property specifies an image as the list item marker:

Example

```
ul {
   list-style-image: url('sqpurple.gif');
}
```

Try it Yourself »


Position The List Item Markers

The list-style-position property specifies the position of the list-item markers (bullet points).

"list-style-position: outside;" means that the bullet points will be outside the list item. The start of each line of a list item will be aligned vertically. This is default:

- Coffee A
 brewed drink
 prepared from
 roasted coffee
 beans...
- Tea
- Coca-cola

"list-style-position: inside;" means that the bullet points will be inside the list item. As it is part of the list item, it will be part of the text and push the text at the start:



Example

```
ul.a {
    list-style-position: outside;
}

ul.b {
    list-style-position: inside;
}
```

Try it Yourself »

Remove Default Settings

The list-style-type:none property can also be used to remove the markers/bullets. Note that the list also has default margin and padding. To remove this, add margin:0 and padding:0 to or :

Example

```
ul {
   list-style-type: none;
   margin: 0;
   padding: 0;
}
```

Try it Yourself »

List - Shorthand property

The list-style property is a shorthand property. It is used to set all the list properties
in one declaration:

Example

```
ul {
   list-style: square inside url("sqpurple.gif");
}

Try it Yourself »
```

When using the shorthand property, the order of the property values are:

- list-style-type (if a list-style-image is specified, the value of this property will be displayed if the image for some reason cannot be displayed)
- list-style-position (specifies whether the list-item markers should appear inside or outside the content flow)
- list-style-image (specifies an image as the list item marker)

If one of the property values above are missing, the default value for the missing property will be inserted, if any.

Styling List With Colors

We can also style lists with colors, to make them look a little more interesting.

Anything added to the or tag, affects the entire list, while properties added to the tag will affect the individual list items:

Example

```
ol {
  background: #ff9999;
  padding: 20px;
}
ul {
  background: #3399ff;
  padding: 20px;
}
ol li {
  background: #ffe5e5;
  padding: 5px;
  margin-left: 35px;
}
ul li {
  background: #cce5ff;
  margin: 5px;
}
```

Result:

- 1. Coffee
- 2. Tea
- 3. Coca Cola
- Coffee
- Tea
- Coca Cola

Try it Yourself »

More Examples

Customized list with a red left border

This example demonstrates how to create a list with a red left border.

Full-width bordered list

This example demonstrates how to create a bordered list without bullets.

All the different list-item markers for lists

This example demonstrates all the different list-item markers in CSS.

Test Yourself with Exercises!

Exercise 1 » Exercise 2 » Exercise 3 » Exercise 4 »

All CSS List Properties

Property	Description
<u>list-style</u>	Sets all the properties for a list in one declaration
<u>list-style-</u> <u>image</u>	Specifies an image as the list-item marker
<u>list-style-</u> position	Specifies the position of the list-item markers (bullet points)
<u>list-style-type</u>	Specifies the type of list-item marker

Previous

Next >



COLOR PICKER



SHOP

HOW TO

Tabs Dropdowns

Accordions
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List

SHARE







CERTIFICATES

HTML CSS JavaScript SQL Python PHP jQuery Bootstrap XML

Read More »

Java Reference Angular Reference

Top Examples

HTML Examples
CSS Examples
JavaScript Examples
How To Examples
SQL Examples
Python Examples
W3.CSS Examples
Bootstrap Examples
PHP Examples
jQuery Examples
Java Examples
XML Examples

Web Certificates

HTML Certificate
CSS Certificate
JavaScript Certificate
SQL Certificate
Python Certificate
jQuery Certificate
PHP Certificate
Bootstrap Certificate
XML Certificate

Get Certified »

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.



REPORT ERROR

FORUM

ABOUT

SHOP

Top Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
jQuery Tutorial
Java Tutorial
C++ Tutorial

Top References

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors
jQuery Reference