

CSS Selectors

[< Previous](#)[Next >](#)

CSS Selectors

CSS selectors are used to "find" (or select) the HTML elements you want to style.

We can divide CSS selectors into five categories:

- Simple selectors (select elements based on name, id, class)
- Combinator selectors (select elements based on a specific relationship between them)
- Pseudo-class selectors (select elements based on a certain state)
- Pseudo-elements selectors (select and style a part of an element)
- Attribute selectors (select elements based on an attribute or attribute value)

This page will explain the most basic CSS selectors.

The CSS element Selector

The element selector selects HTML elements based on the element name.

Example

Here, all <p> elements on the page will be center-aligned, with a red text color:

```
p {  
  text-align: center;  
  color: red;  
}
```

Try it Yourself »

The CSS id Selector

The id selector uses the id attribute of an HTML element to select a specific element.

The id of an element is unique within a page, so the id selector is used to select one unique element!

To select an element with a specific id, write a hash (#) character, followed by the id of the element.

Example

The CSS rule below will be applied to the HTML element with id="para1":

```
#para1 {  
  text-align: center;  
  color: red;  
}
```

Try it Yourself »

Note: An id name cannot start with a number!

The CSS class Selector

The class selector selects HTML elements with a specific class attribute.

To select elements with a specific class, write a period (.) character, followed by the class name.

Example

In this example all HTML elements with class="center" will be red and center-aligned:

```
.center {  
  text-align: center;  
  color: red;  
}
```

[Try it Yourself »](#)

You can also specify that only specific HTML elements should be affected by a class.

Example

In this example only <p> elements with class="center" will be center-aligned:

```
p.center {  
  text-align: center;  
  color: red;  
}
```

[Try it Yourself »](#)

HTML elements can also refer to more than one class.

Example

In this example the <p> element will be styled according to class="center" and to class="large":

```
<p class="center large">This paragraph refers to two classes.</p>
```

Try it Yourself »

Note: A class name cannot start with a number!

The CSS Universal Selector

The universal selector (*) selects all HTML elements on the page.

Example

The CSS rule below will affect every HTML element on the page:

```
* {  
  text-align: center;  
  color: blue;  
}
```

Try it Yourself »

The CSS Grouping Selector

The grouping selector selects all the HTML elements with the same style definitions.

Look at the following CSS code (the h1, h2, and p elements have the same style definitions):

```
h1 {  
  text-align: center;  
  color: red;  
}  
  
h2 {  
  text-align: center;  
  color: red;  
}  
  
p {  
  text-align: center;  
  color: red;  
}
```

It will be better to group the selectors, to minimize the code.

To group selectors, separate each selector with a comma.

Example

In this example we have grouped the selectors from the code above:

```
h1, h2, p {  
  text-align: center;  
  color: red;  
}
```

Try it Yourself »

Test Yourself with Exercises!

[Exercise 1 »](#)[Exercise 2 »](#)[Exercise 3 »](#)[Exercise 4 »](#)

All CSS Simple Selectors

Selector	Example	Example description
<u>.class</u>	.intro	Selects all elements with class="intro"
<u>#id</u>	#firstname	Selects the element with id="firstname"
<u>*</u>	*	Selects all elements
<u>element</u>	p	Selects all <p> elements
<u>element,element,..</u>	div, p	Selects all <div> elements and all <p> elements

[< Previous](#)[Next >](#)



COLOR PICKER



SHOP

HOW TO

Tabs
Dropdowns

Accordions
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List


SHARE



CERTIFICATES

HTML
CSS
JavaScript
SQL
Python
PHP
jQuery
Bootstrap
XML

[Read More »](#)



[REPORT ERROR](#)

[FORUM](#)

[ABOUT](#)

[SHOP](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[jQuery Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[jQuery Reference](#)
[Java Reference](#)
[Angular Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[jQuery Examples](#)

[Java Examples](#)[XML Examples](#)

Web Certificates

[HTML Certificate](#)[CSS Certificate](#)[JavaScript Certificate](#)[SQL Certificate](#)[Python Certificate](#)[jQuery Certificate](#)[PHP Certificate](#)[Bootstrap Certificate](#)[XML Certificate](#)[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

