

CSS Layout - Overflow

[< Previous](#)[Next >](#)

The CSS **overflow** property controls what happens to content that is too big to fit into an area.

molestie consequat, vel illum dolore eu feugiat nulla facilisis at vero eros et accumsan et iusto odio dignissim qui blandit praesent luptatum zzril delenit augue duiis dolore te feugait nulla facilisi. Nam liber tempor cum soluta nobis eleifend option congue nihil imperdiet doming id quod mazim placerat facer possim assum.

[Try it Yourself »](#)

CSS Overflow

The **overflow** property specifies whether to clip the content or to add scrollbars when the content of an element is too big to fit in the specified area.

The **overflow** property has the following values:

- **visible** - Default. The overflow is not clipped. The content renders outside the element's box
- **hidden** - The overflow is clipped, and the rest of the content will be invisible
- **scroll** - The overflow is clipped, and a scrollbar is added to see the rest of the content
- **auto** - Similar to **scroll**, but it adds scrollbars only when necessary

Note: The `overflow` property only works for block elements with a specified height.

Note: In OS X Lion (on Mac), scrollbars are hidden by default and only shown when being used (even though "overflow:scroll" is set).

overflow: visible

By default, the overflow is `visible`, meaning that it is not clipped and it renders outside the element's box:

You can use the overflow property when you want to have better control of the layout. The overflow property specifies what happens if content overflows an element's box.

Example

```
div {  
  width: 200px;  
  height: 50px;  
  background-color: #eee;  
  overflow: visible;  
}
```

Try it Yourself »

overflow: hidden

With the **hidden** value, the overflow is clipped, and the rest of the content is hidden:

You can use the overflow property when you want to have better control of the layout. The overflow

Example

```
div {  
  overflow: hidden;  
}
```

[Try it Yourself »](#)

overflow: scroll

Setting the value to **scroll**, the overflow is clipped and a scrollbar is added to scroll inside the box. Note that this will add a scrollbar both horizontally and vertically (even if you do not need it):

You can use the overflow property when you want to have better control of

Example

```
div {  
  overflow: scroll;  
}
```

[Try it Yourself »](#)

overflow: auto

The `auto` value is similar to `scroll`, but it adds scrollbars only when necessary:

You can use the overflow property when you want to have better control of



Example

```
div {  
  overflow: auto;  
}
```

[Try it Yourself »](#)

overflow-x and overflow-y

The `overflow-x` and `overflow-y` properties specifies whether to change the overflow of content just horizontally or vertically (or both):

`overflow-x` specifies what to do with the left/right edges of the content.

`overflow-y` specifies what to do with the top/bottom edges of the content.

You can use the overflow property when you want to have better control of



Example

```
div {  
  overflow-x: hidden; /* Hide horizontal scrollbar */  
  overflow-y: scroll; /* Add vertical scrollbar */  
}
```

[Try it Yourself »](#)

Test Yourself with Exercises!

[Exercise 1 »](#)

[Exercise 2 »](#)

[Exercise 3 »](#)

All CSS Overflow Properties

Property	Description
<u>overflow</u>	Specifies what happens if content overflows an element's box
<u>overflow-x</u>	Specifies what to do with the left/right edges of the content if it overflows the element's content area
<u>overflow-y</u>	Specifies what to do with the top/bottom edges of the content if it overflows the element's content area

[< Previous](#)

[Next >](#)



COLOR PICKER



SHOP

HOW TO

- Tabs
- Dropdowns

Accordions
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List

SHARE



CERTIFICATES

HTML
CSS
JavaScript
SQL
Python
PHP
jQuery
Bootstrap
XML

[Read More »](#)

[Java Reference](#)
[Angular Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[jQuery Examples](#)
[Java Examples](#)
[XML Examples](#)

Web Certificates

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[jQuery Certificate](#)
[PHP Certificate](#)
[Bootstrap Certificate](#)
[XML Certificate](#)

[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#). Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.



[REPORT ERROR](#)

[FORUM](#)

[ABOUT](#)

[SHOP](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[jQuery Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[jQuery Reference](#)