



CSS Pseudo-classes

[< Previous](#)[Next >](#)

What are Pseudo-classes?

A pseudo-class is used to define a special state of an element.

For example, it can be used to:

- Style an element when a user mouses over it
- Style visited and unvisited links differently
- Style an element when it gets focus

Mouse Over Me

Click Me To Get Focus

Syntax

The syntax of pseudo-classes:

```
selector:pseudo-class {  
  property: value;
```

 }

Anchor Pseudo-classes

Links can be displayed in different ways:

Example

```
/* unvisited link */
a:link {
    color: #FF0000;
}

/* visited link */
a:visited {
    color: #00FF00;
}

/* mouse over link */
a:hover {
    color: #FF00FF;
}

/* selected link */
a:active {
    color: #0000FF;
}
```

Try it Yourself »

Note: `a:hover` MUST come after `a:link` and `a:visited` in the CSS definition in order to be effective! `a:active` MUST come after `a:hover` in the CSS definition in order to be effective! Pseudo-class names are not case-sensitive.

Pseudo-classes and CSS Classes

Pseudo-classes can be combined with CSS classes:

When you hover over the link in the example, it will change color:

Example

```
a.highlight:hover {  
  color: #ff0000;  
}
```

[Try it Yourself »](#)

Hover on <div>

An example of using the `:hover` pseudo-class on a `<div>` element:

Example

```
div:hover {  
  background-color: blue;  
}
```

[Try it Yourself »](#)

Simple Tooltip Hover

Hover over a <div> element to show a <p> element (like a tooltip):

Hover over me to show the <p> element.

Example

```
p {  
  display: none;  
  background-color: yellow;  
  padding: 20px;  
}  
  
div:hover p {  
  display: block;  
}
```

Try it Yourself »

CSS - The :first-child Pseudo-class

The **:first-child** pseudo-class matches a specified element that is the first child of another element.

Match the first <p> element

In the following example, the selector matches any <p> element that is the first child of any element:

Example

```
p:first-child {  
  color: blue;  
}
```

[Try it Yourself »](#)

Match the first <i> element in all <p> elements

In the following example, the selector matches the first <i> element in all <p> elements:

Example

```
p i:first-child {  
  color: blue;  
}
```

[Try it Yourself »](#)

Match all <i> elements in all first child <p> elements

In the following example, the selector matches all <i> elements in <p> elements that are the first child of another element:

Example

```
p:first-child i {  
  color: blue;  
}
```

[Try it Yourself »](#)

CSS - The :lang Pseudo-class

The `:lang` pseudo-class allows you to define special rules for different languages.

In the example below, `:lang` defines the quotation marks for `<q>` elements with `lang="no"`:

Example

```
<html>
<head>
<style>
q:lang(no) {
  quotes: "~" "~";
}
</style>
</head>
<body>

<p>Some text <q lang="no">A quote in a paragraph</q> Some text.</p>

</body>
</html>
```

Try it Yourself »

More Examples

Add different styles to hyperlinks

This example demonstrates how to add other styles to hyperlinks.

Use of :focus

This example demonstrates how to use the `:focus` pseudo-class.

Test Yourself with Exercises!

[Exercise 1 »](#)[Exercise 2 »](#)[Exercise 3 »](#)[Exercise 4 »](#)

All CSS Pseudo Classes

Selector	Example	Example description
<u>:active</u>	a:active	Selects the active link
<u>:checked</u>	input:checked	Selects every checked <input> element
<u>:disabled</u>	input:disabled	Selects every disabled <input> element
<u>:empty</u>	p:empty	Selects every <p> element that has no children
<u>:enabled</u>	input:enabled	Selects every enabled <input> element
<u>:first-child</u>	p:first-child	Selects every <p> elements that is the first child of its parent
<u>:first-of-type</u>	p:first-of-type	Selects every <p> element that is the first <p> element of its parent
<u>:focus</u>	input:focus	Selects the <input> element that has focus
<u>:hover</u>	a:hover	Selects links on mouse over
<u>:in-range</u>	input:in-range	Selects <input> elements with a value within a specified range
<u>:invalid</u>	input:invalid	Selects all <input> elements with an invalid value
<u>:lang(<i>language</i>)</u>	p:lang(it)	Selects every <p> element with a lang attribute value starting with "it"
<u>:last-child</u>	p:last-child	Selects every <p> elements that is the last child of its parent
<u>:last-of-type</u>	p:last-of-type	Selects every <p> element that is the last <p> element of its parent
<u>:link</u>	a:link	Selects all unvisited links

<u>:not(selector)</u>	:not(p)	Selects every element that is not a <p> element
<u>:nth-child(n)</u>	p:nth-child(2)	Selects every <p> element that is the second child of its parent
<u>:nth-last-child(n)</u>	p:nth-last-child(2)	Selects every <p> element that is the second child of its parent, counting from the last child
<u>:nth-last-of-type(n)</u>	p:nth-last-of-type(2)	Selects every <p> element that is the second <p> element of its parent, counting from the last child
<u>:nth-of-type(n)</u>	p:nth-of-type(2)	Selects every <p> element that is the second <p> element of its parent
<u>:only-of-type</u>	p:only-of-type	Selects every <p> element that is the only <p> element of its parent
<u>:only-child</u>	p:only-child	Selects every <p> element that is the only child of its parent
<u>:optional</u>	input:optional	Selects <input> elements with no "required" attribute
<u>:out-of-range</u>	input:out-of-range	Selects <input> elements with a value outside a specified range
<u>:read-only</u>	input:read-only	Selects <input> elements with a "readonly" attribute specified
<u>:read-write</u>	input:read-write	Selects <input> elements with no "readonly" attribute
<u>:required</u>	input:required	Selects <input> elements with a "required" attribute specified
<u>:root</u>	root	Selects the document's root element
<u>:target</u>	#news:target	Selects the current active #news element (clicked on a URL containing that anchor name)
<u>:valid</u>	input:valid	Selects all <input> elements with a valid value
<u>:visited</u>	a:visited	Selects all visited links

All CSS Pseudo Elements

Selector	Example	Example description
<u>::after</u>	p::after	Insert content after every <p> element
<u>::before</u>	p::before	Insert content before every <p> element
<u>::first-letter</u>	p::first-letter	Selects the first letter of every <p> element
<u>::first-line</u>	p::first-line	Selects the first line of every <p> element
<u>::selection</u>	p::selection	Selects the portion of an element that is selected by a user

[< Previous](#)[Next >](#)

COLOR PICKER



SHOP

HOW TO

Tabs
Dropdowns

Accordions
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List


SHARE



CERTIFICATES

HTML
CSS
JavaScript
SQL
Python
PHP
jQuery
Bootstrap
XML

[Read More »](#)





[REPORT ERROR](#)

[FORUM](#)

[ABOUT](#)

[SHOP](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[jQuery Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[jQuery Reference](#)

[Java Reference](#)
[Angular Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[jQuery Examples](#)
[Java Examples](#)
[XML Examples](#)

Web Certificates

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[jQuery Certificate](#)
[PHP Certificate](#)
[Bootstrap Certificate](#)
[XML Certificate](#)

[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#). Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

