4	3		2		1	
	COUTING		LEGEND OF SYMBOLS			
	LIGHTING		SECURITY CARD READER		FIRE ALARM	
	RECESSED LUMINAIRE SURFACE MOUNTED LUMINAIRE		CARD READER KEYPAD	- 2	SMOKE ALARM SMOKE DETECTOR	
	SURFACE MOUNTED LUMINAIRE WALL MOUNTED LUMINAIRE		KEYPAD	Ŏ		
	RECESSED WALL WASH LIMMAIRE		ELECTRIC STRIKE		SMOKE DETECTOR UNDER FLOOR	
	RECESSED WALL WASH LUMINAIRE RECESSED LUMINAIRE ON EMERGENCY POWER		MAGLOCK	_ -	RATE OF RISE HEAT DETECTOR	
	SURFACE MOUNTED LUMINAIRE ON EMERGENCY POWER		DOOR CONTACT		FIXED TEMPERATURE HEAT DETECTOR (58 DEGREE C)	D
	WALL MOUNTED LUMINAIRE ON EMERGENCY POWER		DURESS ALARM		FIXED TEMPERATURE HEAT DETECTOR (88 DEGREE C) RATE OF RISE HEAT DETECTOR IN CEILING PLENUM	_
	RECESSED LUMINAIRE		MAGLOCK RELEASE PUSHBUTTON	l ă	RATE OF RISE HEAT DETECTOR IN CEILING PLENUM	
	SURFACE MOUNTED LUMINAIRE	RX	REQUEST TO EXIT (REX) MOTION SENSOR		COMBINATION SMOKEHEAT DETECTOR	
	STRIP LUMINAIRE	BP	BLUE PULLSTATION	⊕ \$/	DUCT SMOKE DETECTOR - SA' DENOTES SUPPLY AIR, TA' DENOTES RETURN AIR	
	WALL MOUNTED LUMINAIRE	MS	MOTION SENSOR -WALL MOUNTED		RETURN AIK	
	SUSPENDED LINEAR		MOTION SENSOR -CEILING MOUNTED GLASS BREAK		S. DUCT SMOKE DETECTOR CW SHUTDOWN RELAY FIRE ALARM BREAKGLASS ABORT STATION	
	RECESSED LUMINAIRE ON EMERGENCY POWER	9	GLASS BREAK	ă	ADODT CTATION	
	STRIP LUMINAIRE ON EMERGENCY POWER		INTERCOM	ES	SPRINKI FR FI OW SWITCH	
	SURFACE MOUNTED LUMINAIRE ON EMERGENCY POWER		CCTV CAMERA		SPRINKLER FLOW SWITCH SPRINKLER TAMPER SWITCH PRESSURE SWITCH	
	WALL MOUNTED LUMINAIRE ON EMERGENCY POWER TRACK LIGHTING CW LIGHTING HEADS AS SHOWN		SECURITY HORN	PS	PRESSURE SWITCH	
	TRACK LIGHTING CW LIGHTING HEADS AS SHOWN			8	SOLENOID VALVEIACTUATOR	
	SURFACE MOUNTED H.LD. LUMINAIRE		POWER		END OF LINE RESISTOR	
	RECESSED H.LD. LUMINAIRE WALL H.ID. LUMINAIRE	— <u> </u>	SINGLEISPECIAL PURPOSE RECEPTACLE DUPLEX RECEPTACLE	E	FIRE ALARM BELL -WALL MOUNTED	
	WALL H.I.D. LUMINAIRE POLE MOUNTED LUMINAIRE		DUPLEX RECEPTACLE ISOLATED GROUND RECEPTACLE		FIRE ALARM HORN -WALL MOUNTED	
			GROUND FAULT RECEPTABLE		FIRE ALARM MINI HORN WITH SILENCE BUTTON -WALL MTD	
	LIGHTING BOLLARD LIGHTING LUMINAIRE TYPE TAG	— I — X	SPLIT CIRCUIT RECEPTACLE SPLIT CIRCUIT RECEPTACLE	94	FIRE ALARM MINI HORN WITHOUT SILENCE BUTTON -WALL MTD	
	EXIT LIGHT -CEILING (CW ARROWS AS INDICATED)	<u> </u>	WEATHERPROOF RECEPTACLE	S 15	GO STATE STROBE -WALL MTD STATE STROBE CONTROL IN CANDELAS FIRE ALARM STROBE CONTROL IN CANDELAS STATE OF THE ALARM COMMINATION BELL AND STROBE -WALL MTD STATE OF THE ALARM STROBE CONTROL IN CANDELAS STROBECTURE CONTROL IN CANDELAS STROBEC	
	EXIT LIGHT -WALL (CW ARROWS AS INDICATED)		WEATHERPROOF RECEPTACLE SWITCH RECEPTACLE	15	FIRE ALARM COMBINATION BELL AND STROBE -WALL MTD XXXXI DENOTES STROBE OUTPUT IN CANDELAS	
	EMERGENCY LIGHTING BATTERY PACK		FOURPLEX RECEPTACLE	S 15	icd XXM DENOTES STRORE OUTPUT IN CANDEL AS	
	EMERGENCY LIGHTING BATTERY PACK C/W LIGHTING HEADS		ISOLATED GROUND FOURPLEX RECEPTAGLE	II (GD)	FIRE ALARM HORN -CEILING MOUNTED	
	SINGLE REMOTE LIGHTING HEAD -CEILING MOUNTED	- 6	T-SLOT DUPLEX RECEPTACLE (5-20R)	(6) 15	FIRE ALARM COMBINATION HORN AND STROBE -CEILING MOUNTED	
	DOUBLE REMOTE LIGHTING HEAD -CEILING MOUNTED		FOUNTAIN RECEPTALE SCLATED GROUND FOURT EX RECEPTALE 1-5,0.01 DUPLEX RECEPTALE (5-26R) 1-5,0.01 DUPLEX RECEPTALE (5-26R)	(A) 15	dd FIRE ALARM COMBINATION HORN AND STRIDBE -CELLING MOUNTED XXM DENOTES STROBE OUTPUT IN CANDELAS dd FIRE ALARM STROBE -CELLING MOUNTED XXM DENOTES STROBE OUTPUT IN CANDELAS	С
	SINGLE REMOTE LIGHTING HEAD -WALL MOUNTED	-	T-SLOT COMPUTER RECEPTACLE (5-20R) COMPTER DUPLEX RECEPTACLE	@ z		
	DOUBLE REMOTE LIGHTING HEAD -WALL MOUNTED		COMPTER DUPLEX RECEPTACLE		FIRE ALARM COMPINIATION OF METROTRORS, CELLING MOUNTED	
	SWITCH -SINGLE GANG	— •	COMPUTER FOURPLEX RECEPTACLE	@1 15 21	XXxd DENOTES STROBE OUTPUT IN CANDELAS XXXW DENOTES SPEAKER TAP SETTING IN WATTS	
	SWITCH-TWO GANG		FLOOR MOUNTED RECEPTACLE	© 2	M XXX DENOTES SPEARS TAP SETTING IN WAITS FRE ALAB SPEARS ANAL MONTES WAY DENOTES SPEARS ANAL SETTING IN WAITS AND DENOTES SPEARS ANAL SETTING IN WAITS	
	SWITCH-THREE GANG SWITCH-FOUR GANG		PLOOR MOUNTED RECEPTACLE PLOOR MOUNTED FOURPLEX RECEPTACLE PLOOR MOUNTED FOURPLEX RECEPTACLE	高 15	FIRE ALARM COMBINATION SPEAKER/STROBE -WALL MOUNTED XXxxd DENOTES STROBE OUTPUT IN CANDELAS	
	SWITCH-FOOR GANG SWITCH-TWO POLE	— 	DI OOD MOINTEN ION ATEN ORDININ EN IDDI EV DECEDTACI E		XXW DENOTES SPEAKER TAP SETTING IN WATTS	
			FLOOR MOUNTED ISOLATED GROUND FOURPLEX RECEPTACLE FLOOR MOUNTED COMPUTER DUPLEX RECEPTACLE		DOUBLINGS SPENIES TAP SETTING IN WATTS PRE PRICIE SOLATION MODULE (DC) SUITE ISOLATOR (NAC) CONTROL MODULE	
	SWITCH-THREE WAY SWITCH-LOW VOLTAGE	- I - 5	CEILING MOUNTED SINGLE/SPECIAL PURPOSE RECEPTACLE	SI	SHITE ISOLATOR (NAC)	
	switch-keyswitch		CEILING MOUNTED DUPLEX RECEPTACLE	- I	CONTROL MODILIE	
	D SWITCH-DIMMER SWITCH	9	CEILING MOUNTED DUPLEX RECEPTACLE CEILING MOUNTED JUNCTIONISLAB BOX	MM	MONITORING MODULE	
	SWITCH -MOTION SENSOR SWITCH		WALL MOUNTED JUNCTION BOX	0	MONITORING MODULE DOOR HOLD OPEN	
	SWITCH CW PILOT LIGHT - SINGLE GANG		FLOOR MOUNTED JUNCTION/SLAB BOX ELECTRICAL PANELBOARD -SURFACE MOUNTED	ANN	FIRE ALARM ANNUNCIATOR	20:
	P PHOTO ELECTRIC CELL		ELECTRICAL PANELBOARD -SURFACE MOUNTED		FIRE ALARM CONTROL PANEL	
	MOTION SENSOR -CEILING MOUNTED		ELECTRICAL PANELBOARD -RECESSED MOUNTED	FSA	FIRE ALARM TRANSPONDER	
	MOTION SENSOR -WALL MOUNTED		CONTROL TRANSFORMER CONTROL TRANSFORMER	FDNE	FIRE ALARM DO NOT ENTER SIGN	
	OS OCCUPANCY SENSOR - CEILING MOUNTED SYSTEMS		TIMECLOCK		ZONE BOXES	
	SYSTEMS Voice outlet	-	MECHANICAL		POWER ZONE BOX DATA ZONE BOX VOICE ZONE BOX	
	DATA CUTLET	— <u> </u> ~	MOTOR	- U4	DATA ZONE BOX	
	COMBINATION VOICE/DATA OUTLET	— ¥	SWITCH -MANUAL STARTER		COMMUNICATIONS ZONE BOX	
	TELEVISION OUTLET	᠆᠆ᡰ᠊ᢆᢐ	MOTOR C/W MANUAL STARTER		VOICE ZONE BUX COMMUNICATIONS ZONE BOX PA ZONE BOX SECURITY ZONE BOX	
	FLOOR MOUNTED VOICE OUTLET		MOTOR CW DISCONNECT SWITCH	52	SECURITY ZONE BOX	В
	FLOOR MOUNTED DATA OUTLET			F2	FIRE ZONE BOX	5
	FLOOR MOUNTED COMBINATION VOICE/DATA OUTLET	⊐⊫≞	UNFUSED DISCONNECT SWITCH	AV	AUDIO/VIDEO ZONE BOX	THE
	FLOOR MOUNTED TELEVISION OUTLET	⊢ =	FUSED DISCONNECT SWITCH COMBINATION MAG STARTER/DISCONNECT SWITCH	SP	SPEAKER ZONE BOX	REF
	CEILING MOUNTED VOICE OUTLET		MAGNETIC STARTER	-	GENERAL	COT DIM AND PRO
	CEILING MOUNTED DATA OUTLET		FAMICIFED CONTROLLED		CONDUIT CONCEALED IN WALL OR CEILING	DIM
	CEILING MOUNTED COMBINATION VOICE/DATA OUTLET		THERMOSTAT		CONDUIT CONCEALED IN WALLICEILING -EMERGENCY OR UPS POWER	PRI CON
	CEILING MOUNTED TELEVISION OUTLET	š	SENSOR		CONDUIT CONCEALED IN SLAB	DO
	MCROPHONE OUTLET PA SPEAKER -CELLING MOUNTED	MECH	MOTOR IDENTIFICATION TAG		CONDUIT BURIED BELOW GRADE	THE
	PA SPEAKER - CEILING MOUNTED		AIR QUALITY SENSOR		CONDUIT-UP CONDUIT-DOWN	THE FOR APF
	PA SPEAKER -WALL MOUNTED				DENOTES WEATHERPROOF DEVICE	
	LOCAL SPEAKER -CEILING MOUNTED VOLUME CONTROLLER				DENOTES WEATHERPROOF DEVICE DENOTES EXISTING DEVICE TO REMAIN	
	CHIME / BUZZER				DENOTES EXISTING DEVICE TO REMOVE BACK TO SOURCE	
	PUSHBUTTON	_			DENOTES EXISTING DEVICE TO REMOVE BACK TO SOURCE DENOTES REMOVE AND REPLACE WITH NEW	
	CH CH CLOCK CELLING MOLINTED W FACE INDICATORS	_			DENOTES EXISTING DEVICE TO BE RELOCATED	
	G G COCK END MOUNTED WALL WELVE INDICATORS			RL	DENOTES RELOCATED DEVICE	
	C COOK PACE MOUNTAINS	_			DENOTES NEW DEVICE	
	CLOCK FACE MOUNT WALL PAC PCLE WATER DETECTOR			С	DENOTES EXISTING DEVICE TO RECIRCUIT	
	WATER DETECTOR			В	DENOTES EXISTING DEVICE TO BLANK OFF	
	WIRELESS ACCESS POINT -CEILING MOUNTED			Q01	DEVICE CONNECTION TAG (REFER TO DEVICE CONNECTION	-
	■ WIRELESS ACCESS POINT -WALL MOUNTED				DENOTES DEVICE MOUNTED IN MILLWORK	MAA
	Z CALL -IN HOPN				DENOTES DEVICE MOUNTED IN SURFACE RACEWAY	PRO
				##	DENOTES DEVICE MOUNTED ON SURFACE	A DRA
						
						CHE
						SH