

COT 6417 - Algorithms on Strings and Sequences

Fall 2020

Homework 3

Name: Nabila Shahnaz Khan

PID: 5067496

#Question 1:

Solution:

Here, $F[n, m]$ denote the total number of alignments between two strings X and Y , of lengths n and m respectively. Let, $F[i, j]$ denote the total number of alignments between the substring $X[1, i]$ and $Y[1, j]$, where $1 \leq i \leq n$ and $1 \leq j \leq m$.

While aligning two strings X and Y using dynamic programming matrix, at position $[i, j]$, the alignment cost will depend on the positions $[i-1, j-1]$, $[i-1, j]$, $[i, j-1]$. The number of possible path to access entry $[i, j]$ is equal to the sum of the number of paths to access entries $[i-1, j-1]$, $[i-1, j]$, $[i, j-1]$.

So, total possible alignments for entry $[i, j]$ = total possible alignments for entry $[i-1, j-1]$ + total possible alignments for entry $[i-1, j]$ + total possible alignments for entry $[i, j-1]$.

▪ Recurrence Relation:

Base Case: $F[i, 0] = 1$, for $0 \leq i \leq n$ and $F[0, j] = 1$, for $1 \leq j \leq m$

Then, for $1 \leq i \leq n$ and $1 \leq j \leq m$

$$F[i, j] = F[i-1, j-1] + F[i-1, j] + F[i, j-1]$$

▪ Calculating $F[3, 4]$ using the Recurrence Relation:

		\xrightarrow{m}				
$\downarrow n$		-	Y_1	Y_2	Y_3	Y_4
	-	1	1	1	1	1
	X_1	1	3	5	7	9
	X_2	1	5	13	25	41
	X_3	1	7	25	63	129

Using recurrence relation,

$$\begin{aligned} F[3, 4] &= F[2, 3] + F[2, 4] + F[3, 3] \\ &= (F[1, 2] + F[1, 3] + F[2, 2]) \\ &\quad + (F[1, 3] + F[1, 4] + F[2, 3]) \\ &\quad + (F[2, 2] + F[2, 3] + F[3, 2]) \\ &= (5 + 7 + 13) + (7 + 9 + 25) + (13 + 25 + 25) \\ &= 129 \end{aligned}$$

#Question2:

Solution:

Here, suppose X and Y are two strings with length n and m respectively. In a unit cost model, the cost of a match is 0, and the cost of a substitution and a gap are both 1. Using the unit cost model, the recurrence relation for calculating the optimal edit distance between two strings is given below:

▪ Recurrence Relation:

Let $M[i, j]$ denote the minimum cost of aligning $X[1, i]$ and $Y[1, j]$ using the unit cost model where $1 \leq i \leq n$ and $1 \leq j \leq m$.

$$M[i, j] = \text{minimum} \begin{cases} M[i-1, j-1] + \text{cost}(x_i, y_j) \\ M[i-1, j] + 1 \\ M[i, j-1] + 1 \end{cases}$$

$$\text{cost}(x_i, y_j) = \begin{cases} 0, & x_i = y_j \\ 1, & \text{otherwise} \end{cases}$$

Base case:

$M[i, 0] = i * 1$, for $0 \leq i \leq n$ and $M[0, j] = j * 1$, for $1 \leq j \leq m$

Here, $M[n, m]$ is the optimal edit distance for X and Y.

▪ Calculation of Edit Distance:

Input: X = acagatta, Y = tagctta

Dynamic Programming Matrix:

	-	t	a	g	c	t	t	a
-	0	1	2	3	4	5	6	7
a	1	1	1	2	3	4	5	6
c	2	2	2	2	2	3	4	5
a	3	3	2	3	3	3	4	4
g	4	4	3	2	3	4	4	5
a	5	5	4	3	3	4	5	4
t	6	5	5	4	4	3	4	5
t	7	6	6	5	5	4	3	4
a	8	7	6	6	6	5	4	3

Backtracking Matrix:

Let, U = Up, L = Left, D = Diagonal

	-	t	a	g	c	t	t	a
-	0	L	L	L	L	L	L	L
a	U	D	D	L	L	L	L	D
c	U	D	D	D	D	L	L	L
a	U	U	D	D	D	D	D	D
g	U	D	U	D	L	D	D	D
a	U	D	D	U	D	D	D	D
t	U	D	U	U	D	D	D	L
t	U	D	D	U	D	D	D	L
a	U	U	D	U	D	U	U	D

Alignment:

g = gap, s = substitute, m = match

a	c	a	g	a	t	t	a
-	t	a	g	c	t	t	a
g	s	m	m	s	m	m	m

#Question 3:

Solution:

Here, S is a string of length n generated from a constant size alphabet. Query Q(i, j) should return the length of the longest common prefix of S[i, n] and S[j, n].

▪ Construction of Suffix Tree:

In order to preprocess string S, first we have to build a suffix tree T for string S. This will require O(n) runtime. In the suffix tree, the paths from leaf nodes i to root (path P_i) and from leaf j to root (path P_j) will represent the suffixes S[i, n] and S[j, n] respectively. The longest common prefix (LCP) of substrings S[i, n] and S[j, n] is same as the Longest Common Ancestor (LCA) of paths P_i and P_j in tree T.

▪ **Calculating LCA:**

LCA of nodes i and j , known as $lca(i, j)$, can be calculated in constant time using the concept of Euler Tour of tree T and RMQ (Range Minimum Queries). For that, we will need to use three additional arrays known as E , L and R .

Array E holds listing of the nodes visited in a DFS traversal of T and array L contains the tree-depth of each nodes stored in E . Size of both E and L is $2n - 1$. Array R is of size n and contains the index of the first appearance of a node in array E . Together, these three arrays require $O(n \log n)$ bits. For nodes i and j , their lowest common ancestor is the node at the smallest tree depth that is visited between an occurrence of i and an occurrence of j in the Euler Tour. So,

$$lca(i, j) = E[RMQ_L(R[i], R[j])]$$

▪ **RMQ on Array L :**

RMQ_L can be done in $O(1)$ time with the help of preprocessing of the array L . For preprocessing, we have to divide the array L into $\frac{2n}{\log n}$ blocks where size of each block is $\frac{1}{2} \log n$. Then we have to form two arrays, B and C , both of size $\frac{2n}{\log n}$. B contains the minimum element from each of the blocks in A and C contains the locations of the minimum in each block of A . Suppose, $\frac{2n}{\log n} = b$. While calculating $RMQ_L(i, j)$, there will be two possible cases:

Case 1: i and j are not in the same block

Case 2: i and j are in the same block

- Handling Case 1: We have to find location of the minimum element in the range from i to the end of the block and in the range from the beginning of the block containing j to index j . We will also need to consider the location of the minimum elements in the range of blocks completely contained between i and j .

Then from all these minimum values of the blocks, we finally have to select the position of the smallest minimum block value. In order to do that, array B is preprocessed. We constructed $\lfloor \log b \rfloor + 1$ arrays $B_0, B_1, \dots, B_{\lfloor \log b \rfloor}$ such that $B_j[i]$ contains $RMQA(i, i + 2^j)$, provided $i + 2^j \leq n$. Required time and

space for preprocessing will be $O(b \log b) = O\left(\frac{n}{\log n} \log \frac{n}{\log n}\right) = O(n)$. So, number of bits required for preprocessing will be $O(n \log n)$.

- Handling Case 2: To handle this case, we have to pre-compute and store corresponding RMQ for each pair (i, j) of indices that fall in a block. As consecutive entries in L differ by +1 or -1, preprocessing of the distinct blocks will take $\frac{1}{2}\sqrt{n} \times O(\log^2 n) = O(n)$ time.

So, overall, query $Q(i, j)$ will return LCP of $S[i, n]$ and $S[j, n]$ in $O(1)$ time using preprocessing. The preprocessing will require linear time in total and uses no more than $O(n \log n)$ bits.

#Question 4:

Solution:

Jaccard similarity of two sets measures how similar the two sets are. The Jaccard similarity of two sets x and y is, $S(x, y) = \frac{|x \cap y|}{|x \cup y|}$.

Jaccard distance is defined as 1 minus the Jaccard Similarity. So, Jaccard distance, $D(x, y) = 1 - S(x, y)$.

Now, the **Locality-Sensitive Functions** take two items and makes a decision about whether these items should be a candidate pair. Let $d_1 < d_2$ be two distances according to some distance measure d . A family F of functions is said to be **(d_1, d_2, p_1, p_2)-sensitive** if for every f in F :

1. If $d(x, y) \leq d_1$, then the probability that $f(x) = f(y)$ is at least p_1 .
2. If $d(x, y) \geq d_2$, then the probability that $f(x) = f(y)$ is at most p_2 .

Family of minhash function is an example of sensitive function. This means, for any distance d_1 and d_2 , minhash function family is (d_1, d_2, p_1, p_2) -sensitive if $D(x, y) \leq d_1$ for the probability that $f(x) = f(y)$ is at least p_1 and $D(x, y) \geq d_2$ for the probability that $f(x) = f(y)$ is at most p_2 , where $0 \leq d_1 < d_2 \leq 1$.

Now, Jaccard similarity of sets x and y , $S(x, y) = 1 - D(x, y) \geq 1 - d_1$ [as $D(x, y) \leq d_1$]. Similarly we can show, $S(x, y) = 1 - D(x, y) \leq 1 - d_2$. But we know that the Jaccard similarity of x and y , $S(x, y)$, is equal to the probability that a minhash function will hash x and y to the same value. As $1 - d_1 \leq S(x, y) \leq 1 - d_2$, we can say $p_1 = 1 - d_1$ and $p_2 = 1 - d_2$.

So, the family of minhash functions is a $(d_1, d_2, 1-d_1, 1-d_2)$ -sensitive family for any d_1 and d_2 , where $0 \leq d_1 < d_2 \leq 1$.