

FastAPI Python Concepts Study Notes

Table of Contents

1. Introduction to FastAPI

- What is FastAPI?
- Key Features

2. Installation

3. Basic Concepts

- Request and Response
- Path Parameters
- Query Parameters
- Request Body

4. Data Validation

- Pydantic Models
- Validation in FastAPI

5. Dependency Injection

- What is Dependency Injection?
- Creating Dependencies

6. Middleware

- Definition of Middleware
- How to Create Middleware

7. Routes and Routers

- Creating Routes
- Using Routers for Modular Design

8. Asynchronous Programming

- Understanding Asynchronous in Python
- Async Functions in FastAPI

9. Error Handling

- Exception Handling
- Custom Error Responses

10. Summary

1. Introduction to FastAPI

What is FastAPI?

- FastAPI is a modern web framework for building APIs with Python 3.6+ based on standard Python type hints.
- It is designed to create high-performance APIs.

Key Features

- **Fast**: High performance, comparable to NodeJS and Go.
- **Easy**: Designed for simplicity and ease of use.
- **Pythonic**: Leverages Python type hints for easy validation.
- **Automatic documentation**: Interactive API documentation (Swagger UI).
- **Asynchronous Support**: Built-in support for async and await.

2. Installation

To install FastAPI with the supporting ASGI server, use pip:

```
pip install fastapi[all]
```

- `fastapi`: The core library.
- `uvicorn`: ASGI server used to run FastAPI apps.

3. Basic Concepts

Request and Response

- ****Request****: The data sent by the client (e.g., a web browser).
- ****Response****: The data returned by the server.

Path Parameters

- Dynamic parameters in the route path.
- Example of defining a path parameter in FastAPI:

```
@app.get("/items/{item_id}")  
  
async def read_item(item_id: int):  
  
    return {"item_id": item_id}
```

Query Parameters

- Key-value pairs sent in the URL to further specify the request.

```
@app.get("/items/")  
  
async def read_items(skip: int = 0, limit: int = 10):  
  
    return {"skip": skip, "limit": limit}
```

Request Body

- Used to send complex data structures (e.g., JSON) in POST requests.

```
from pydantic import BaseModel
```

```
class Item(BaseModel):
```

```
    name: str
```

```
    description: str = None
```

```
    price: float
```

```
    tax: float = None
```

```
@app.post("/items/")
```

```
async def create_item(item: Item):
```

```
return item
```

```
---
```

4. Data Validation

Pydantic Models

- FastAPI uses Pydantic for data validation and settings management.
- Helps ensure that data is of the expected format.

Validation in FastAPI

- FastAPI validates the data automatically based on specified models.

Example:

```
from pydantic import BaseModel
```

```
class User(BaseModel):
```

```
    name: str
```

```
    age: int
```

```
    email: str
```

```
@app.post("/users/")
```

```
async def create_user(user: User):
```

```
    return user
```

```
---
```

5. Dependency Injection

What is Dependency Injection?

- A way to manage dependencies and reduce tight coupling in your code.

Creating Dependencies

- Use `Depends` to declare dependencies in FastAPI.

Example:

```
from fastapi import Depends

def get_query_param(q: str = None):
    return q

@app.get("/items/")
async def read_items(q: str = Depends(get_query_param)):
    return {"query": q}

---
```

6. Middleware

Definition of Middleware

- Middleware is a function that runs before or after every request.

How to Create Middleware

- Use `starlette.middleware`.

Example:

```
from starlette.middleware.cors import CORSMiddleware

app.add_middleware(
    CORSMiddleware,
    allow_origins=["*"],
    allow_credentials=True,
    allow_methods=["*"],
    allow_headers=["*"],
)
```

7. Routes and Routers

Creating Routes

- Define endpoints using decorators.

Example:

```
@app.get("/health/")
async def health_check():
    return {"status": "healthy"}
```

Using Routers for Modular Design

- Use `APIRouter` for organizing routes.

Example:

```
from fastapi import APIRouter

router = APIRouter()

@router.get("/items/{item_id}")
async def get_item(item_id: int):
    return {"item_id": item_id}

app.include_router(router)
```

8. Asynchronous Programming

Understanding Asynchronous in Python

- Allows writing concurrent code using the `async` and `await` syntax.

Async Functions in FastAPI

- Define async functions to handle requests for better performance.

Example:

```
@app.get("/async-items/")
async def async_get_items():
    await asyncio.sleep(1) # Simulates asynchronous processing
    return ["item1", "item2"]

---
```

9. Error Handling

Exception Handling

- FastAPI allows you to manage exceptions and provide custom responses.

Example:

```
from fastapi import HTTPException

@app.get("/items/{item_id}")
async def get_item(item_id: int):
    if item_id > 10: # Example condition
        raise HTTPException(status_code=404, detail="Item not found")
    return {"item_id": item_id}
```

Custom Error Responses

- You can customize error responses globally.

Example:

```
from fastapi.responses import JSONResponse

@app.exception_handler(HTTPException)
```

```
async def http_exception_handler(request, exc):  
  
    return JSONResponse(  
  
        status_code=exc.status_code,  
  
        content={"message": exc.detail},  
  
    )
```

10. Summary

- FastAPI is an efficient framework for building RESTful APIs.
- It integrates data validation using Pydantic and handles asynchronous requests gracefully.
- Dependency injection promotes clean code architecture.
- Middleware can be used for cross-cutting concerns, and error handling can be customized.
- FastAPI auto-generates interactive API documentation, facilitating ease of use.

FastAPI is a powerful tool that allows developers to create high-performance APIs with minimal effort while maintaining code clarity and simplicity.

Use these notes to understand the concepts and functionalities of FastAPI, and revise them for better retention of knowledge!