Rajalakshmi Engineering College

Name: Nachiyappan Muthuraman

Email: 240801211@rajalakshmi.edu.in

Roll no: 240801211 Phone: 6381571350

Branch: REC

Department: I ECE AF

Batch: 2028

Degree: B.E - ECE



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 3

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

1. Problem Statement

Write a program to implement a queue using an array and pointers. The program should provide the following functionalities:

Insert an element into the queue. Delete an element from the queue. Display the elements in the queue.

The queue has a maximum capacity of 5 elements. If the queue is full and an insertion is attempted, a "Queue is full" message should be displayed. If the queue is empty and a deletion is attempted, a "Queue is empty" message should be displayed.

Input Format

Each line contains an integer representing the chosen option from 1 to 3.

Option 1: Insert an element into the queue followed by an integer representing the element to be inserted, separated by a space.

Option 2: Delete an element from the queue.

Option 3: Display the elements in the queue.

Output Format

For option 1 (insertion):-

- 2. "Queue is full." if the queue is already full and cannot accept more elements. 1. The program outputs: "<data> is inserted in the queue." if the data is

For option 2 (deletion):-

- 1. The program outputs: "Deleted number is: <data>" if an element is successfully deleted and returns the value of the deleted element.
- 2. "Queue is empty." if the queue is empty no elements can be deleted.

For option 3 (display):-

- 1. The program outputs: "Elements in the queue are: <element1> <element2> ... <elementN>" where <element1>, <element2>, ..., <elementN> represent the elements present in the queue.
- 2. "Queue is empty." if the queue is empty no elements can be displayed.

For invalid options, the program outputs: "Invalid option."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 10

```
Output: 10 is inserted in the queue.
     Elements in the queue are: 10
     Invalid option.
     Answer
     #include <stdio.h>
     #include <stdlib.h>
     #define max 5
     int queue[max];
     int front = -1, rear = -1;
// You are using GCC int insertq(int *data)
       //Type your code here
       if(rear == max-1 ||rear - front == max-1){
          return 0;
       }
       else{
          if(front == -1){
            front++;
          queue[++rear] = *data;
         return 1;
     int delq()
       //Type your code here
       if(rear == -1 || rear < front){
          printf("Queue is empty.\n");
          return 0;
       }
       else{
front ++;
return 1
          printf("Deleted number is: %d\n", queue[front]);
```

```
void display()
  //Type your code here
  if(rear == -1 || rear < front){
     printf("Queue is empty.\n");
  }
  else{
     printf("Elements in the queue are: ");
     for(int i = front; i<= rear; i++){
       printf("%d ", queue[i]);
     printf("\n");
int main()
  int data, reply, option;
  while (1)
  {
     if (scanf("%d", &option) != 1)
       break;
     switch (option)
       case 1:
         if (scanf("%d", &data) != 1)
            break;
         reply = insertq(&data);
          if (reply == 0)
            printf("Queue is full.\n");
          else
            printf("%d is inserted in the queue.\n", data);
          break;
       case 2:
                      Called without arguments
          delq(); //
          break:
       case 3:
          display();
          break;
       default:
```

printf(break) } return 0; } Status: Correct	("Invalid option \n"); ;	240801211	24080121 ¹ Marks: 10/10
240801211	240801211	240801211	240801211
240801211	240801211	240801211	240801211