The Mildly Rtarded HIVE — NeVeR Go FuLl ReTaRd

Hive workshop sourcebook

U-1.4-slim · 17 September 2026 · Tokens only · No profile folder · No host tree chrome · No liturgy

This book rebuilds the shop that puts one named job on disk and brings back a receipt. It does not rebuild a church, a court, or a second operating system.

A local globe board was one worked example. Do not treat that example as the workshop.

Path tokens

Token	Means
%USERPROFILE%	Current user profile on the host. Never print the expanded folder.
%HIVE_ROOT%	Parent of lane work trees on the host. Lead already has it. Never print it.
%HUD_URL%	Loopback preview for a tool that has one. Printed on that job only.
<lane>	The named sitting. One per write.

1. What the workshop is

A split bench.

Research stays in chat. **Lead** is the clerk on the host PC. **Build** is the bench.

They pass one job through two files. The notes file and the work tree stay pickup-ready so the next sitting can continue without git.

Output of the shop is whatever the operator named. The shop does not care which domain it is in. It cares that one job lands on disk and comes back with a receipt.

Seat	Does	Does not
Research	Talk to the operator. Write one job. Check the reply.	Edit the host PC. Dump notes onto Build.
Lead	Write the out-box. Watch the in-box. Pass the brief.	Invent the product. Mix two lanes.
Build	Do the job. Write the tree. Reply with a receipt.	Pull extra scope. Put secrets in a share zip.

Lead is a clerk, not an architect. Build is a bench, not a product manager. Research is a mouth and a checklist, not a second disk.

2. House rules

1. This lane does not need git. Pickup is the folder, NOTES.md, and the two handoff files.
2. The bot writes on the host PC. A cloud workspace is not that PC.
3. One named lane per sitting. Do not mix trees.
4. One job per write. Last line is stop.
5. Missing data stays blank. Do not invent rows to look finished.
6. Keys stay on the box and out of zips.
7. Skills and briefs use tokens. Never print an expanded profile folder or host tree chrome.
8. Call Lead only when asked — talk to Lead, file bus, wake the box, send Build a job.
9. Software does not mark a claim proven. A person opens the file.
10. Do not delete existing skill folders. Asleep is fine. Recreating absorbed names is not the job.
11. Wake extra desks only when the job names their problem.

12. The worked example is not shop law.

3. Disk map

Thing	Token path
Out-box	%USERPROFILE%\.grok\handoff\LEAD-TO-BUILD.md
In-box	%USERPROFILE%\.grok\handoff\BUILD-TO-LEAD.md
Lane tree	%HIVE_ROOT%\work\<lane>
Lane notes	%HIVE_ROOT%\work\<lane>\NOTES.md
Skills	skills\<name>\SKILL.md under the host skill root
File-bus note	skills\hive-slim\references\file-bus.md
Local preview	%HUD_URL% when the tool has one

If a heavy skill folder from an older book is already on disk, leave it there. Do not load it unless the job needs it.

4. How a tool gets made

1. Operator names the next cut in one sentence and names the lane.

2. Research finds Lead by name search. Do not create another Lead.

3. Send Lead one async note — append this job, then watch the in-box.

4. Lead writes the dated block and reports heading + file time.

5. Build answers accepted <id> or blocked <id> first.

6. Build lists what changed, token path, what failed, stop.

7. Research tells the operator. Operator opens the artifact.

8. If Lead stops mid-write, check the heading before sending a second job.

9. If the operator is only talking, leave Lead alone.

10. Update NOTES.md with the job id, path, and blanks. Then stop.

5. Job ticket

Out-box

```
## YYYY-MM-DD HH:MM ET short-name
id: JOB-YYYYMMDD-HHMM
who: Lead
lane: <lane>
job: One sentence.
tree: %HIVE_ROOT%\work\<lane>
stop
```

Add preview: %HUD_URL% only when that job has a local preview.

No second paragraph. No research dump. No keys. No “also maybe”.

In-box

```
id: JOB-YYYYMMDD-HHMM
accepted: yes | blocked
who: Build
lane: <lane>
what: What changed on disk.
path: token path of the artifact
failed: list or none
stop
```

failed may be a short list. It may not be a fake complete catalog.

6. Receipt check

Check	Pass
Id	In-box id matches the out-box id
Path	Named file exists on the lane tree
Open	Operator can open it without extra tribal steps
Failed	Failures listed. Nothing invented to fill a hole
Secrets	No keys in the tree that will be zipped
Chrome	No expanded profile folder in the brief
Stop	Build stopped. No bonus work

If any row fails, the job is not done. Write the next sentence. Do not “finish” it in chat.

7. Before you share a pack

Check	Fail = do not zip
Two kinds	Rules pack separate from a worked example
Secrets	Empty except a short README
Samples	No live harvest dumps
Paths	Tokens only. No profile folder, phone, or mail
Local servers	Loopback only
Completeness	Incomplete packs say incomplete

8. Skill diet

The shop needs almost nothing loaded.

Skill	State	Use for
hive-slim	active	This book. Seats, tickets, receipt, first hour.
build-ops	on-call	One target tree. Map a tool before install.
evidence-gate	on-call	A claim will leave the box or be relied on.
skill-creator	bundled	Add or edit skills. Do not delete the set.

Leave older skill folders intact if they already exist. Do not recreate them. Do not route ordinary file-bus work through them.

Wake a specialist only when the sentence names its problem:

Job actually is	Then wake
Contested public claim	evidence-gate
Install / adopt a tool	build-ops tool-map
Interactive public map	gis-layer / visual-systems
Share zip / closeout pack	oversight-delivery
Host-PC write	hive-slim file-bus only

If the sentence is “write README.txt that says the lane name,” no specialist wakes.

9. First hour on a new box

1. Put skills/hive-slim/SKILL.md and references/file-bus.md in the host skill root.

2. Create the two handoff files under %USERPROFILE%\.grok\handoff\ if they do not exist.

3. Create %HIVE_ROOT%\work\<lane> for the sitting.

4. Write an empty NOTES.md in that lane.

5. Send one tiny job — write README.txt that says the lane name. Confirm the receipt.

6. Operator opens the file.

7. Only then start product work.

If step 5 fails, fix the bus. Do not start the product.

10. Lane notes

One file — %HIVE_ROOT%\work\<lane>\NOTES.md

```
NOTES  lane: <lane>

Now

Done
```

```
JOB-YYYYMMDD-HHMM → token path

Failed / blank

Next
```

That is the working document. No growth log. No locked eight-section liturgy. No mission score table.

Log last out-box heading and in-box time if handoff is flaky. Do not log legal names, phone, mail, or expanded folders.

11. File-bus protocol

On command only. The operator must ask to talk to Lead, send a Build job, wake the box, or run host-PC work.

Who	Does	Does not
Research	Brief the operator. Write one job. Audit the receipt.	Edit the host. Paste raw tree chrome as the whole answer.
Lead	Append the job. Watch the in-box. Relay the brief.	Invent product. Mix lanes.
Build	Do one job from the out-box. Write the tree. Brief the in-box.	Pull extra scope.

Find Lead by name search. Use the returned id. Do not mint a replacement. If several match, pick the one named Lead.

Send an async prompt to Lead. Then wait until a Build brief or a blocker. An “Appending…” line is not done. Mid-write — check heading and file time. Do not paste a second full job unless the heading is missing.

12. Lead prompt (copy)

```
You are Lead. Clerk only.

Resolve %USERPROFILE%\.grok\handoff\ on this box.
Append the block below to LEAD-TO-BUILD.md.
Then watch BUILD-TO-LEAD.md.

Do not invent product. Do not mix lanes. Do not expand tokens in your reply.
Reply with heading, file time, and then the in-box when Build writes it.

## YYYY-MM-DD HH:MM ET short-name
id: JOB-YYYYMMDD-HHMM
who: Lead
lane: <lane>
job: <one sentence>
tree: %HIVE_ROOT%\work\<lane>
stop
```

13. Build law (copy)

```
You are Build. One job. One tree.

Read the latest out-box block.
Answer accepted <id> or blocked <id> first.
Do only the sentence.
Write the tree.
List failed blanks. Do not invent.
No secrets in anything that might be zipped.
No extra files from an example pack unless the sentence named them.
Write the in-box. Stop.
```

14. Worked example — shape only

One product the old shop already cut. Use it to see pack shape. Do not copy its domain into the next tool unless that is the job.

```
lane: named by the operator for that sitting
tree: %HIVE_ROOT%\work\<lane>
start: Start-Hud.ps1
preview: %HUD_URL%
idea: local 3D board, layer list, hover cards, public sample rows
files: README-SHARE.md DEMO.md PLAN.md OPSEC.md Start-Hud.ps1
       board/hud-server.py board/globe.html
       sample catalogs + third-party library vendored locally
law on this example: blanks stay blank; keys stay local; loopback only
```

If those files are missing on this machine, they are missing. Do not invent them to look finished.

15. What this book refuses to be

This shop does not require a three-agent cosmology for a README, claim scores for a file the operator can open, slogans on skill files, codenames for a local tool sitting, a specialist desk awake by default, git as the source of truth, a second Lead, or bonus work “while we are in there.”

Those may exist in older folders. They are not this workshop.

Appendix A — shop files

Copy these verbatim. They are the shop.

FILE skills/hive-slim/SKILL.md

```
---
name: hive-slim
description: Split bench for host-PC work. Research writes one job. Lead clerks two handoff files. Build does the sentence and sto
metadata:
  status: active
  version: "1.4-slim"
---

# Hive Slim

Use when the operator wants work on the host PC through the file-bus.

Do not edit the host from Research.
Do not wake Lead unless asked.
Do not load extra skills unless the job names their problem.

Paths stay tokens.
One lane. One job. Last line stop.
Receipt — id, path, open, failed, secrets, chrome, stop.

Full protocol — references/file-bus.md
```

FILE skills/hive-slim/references/file-bus.md

```
# File-bus

On command only.

Out-box: `%USERPROFILE%\.grok\handoff\LEAD-TO-BUILD.md`
In-box: `%USERPROFILE%\.grok\handoff\BUILD-TO-LEAD.md`
Tree: `%HIVE_ROOT%\work\<lane>`
Notes: `%HIVE_ROOT%\work\<lane>\NOTES.md`

Find Lead by name search. Do not create Lead.

Send one async job block. Watch the in-box.
Appending is not done.
Mid-write: check heading and time. Do not double-send.

Out-box shape:

```
## YYYY-MM-DD HH:MM ET short-name
id: JOB-YYYYMMDD-HHMM
who: Lead
lane: <lane>
job: <one sentence>
tree: %HIVE_ROOT%\work\<lane>
stop
```

In-box shape:

```
id: JOB-YYYYMMDD-HHMM
accepted: yes | blocked
who: Build
lane: <lane>
what: <what changed>
path: <token path>
failed: <list or none>
stop
```

Off switch: if the operator is only talking, do not ping Lead.
```

FILE NOTES.md template

```
NOTES  lane: <lane>
```

```
Now

Done

Failed / blank
none

Next
none
```

Appendix B — example pack only

Short files from one finished cut belong in a companion zip if you still have it. They are product, not shop law.

If the files are missing on this machine, list them as missing. Do not reconstruct them here.

Shop test — a stranger can send the README job, open the file, and start product work without reading any older book.

If they cannot, the slim version failed. Add back one rule, not a desk.